

DEHUMIDISTAT HD16

Features and Specifications:

- Mounts in duct or on wall surface
- Positive ON and OFF settings
- Attractive White Color
- SPST, Snap-Acting, Dust-Proof Switch
- 24 VAC
- Electrical Ratings (120 VAC, Full Load): 50 VA at 24 VAC
- Duct or Wall Mounting
- 4% to 6% RH Differential
- Temperature Ranges: -20 F to +120 F / -29 C to +49 C
- Operating Humidity Range: 20 to 80% RH.
- Dimensions: 3¾" H x 3¼" W x 2" D / 95.3 mm H x 82.6 mm W x 50.8 mm D



Your Total Space Solution

- Huge 130 Pint Removal Capacity per Day Means Optimum Humidity Control
- Unit-Mounted Control Included or Optional Wall-Mounted Dehumidistat
- Quiet Operation Lined with 1" High-Density Insulation Minimizes Noise Transfer to Living Spaces
- Condensate Float Switch Included
- Primary and Second Drain Connections
- Stainless Steel Drain Pan
- Compact, Heavy-Gauge Cabinet
- 8" Beaded Duct Connections Ready to Connect to Duct Work
- Works with Central Cooling System or as a Stand-Alone Unit
- Easy-to-Clean Filter with Easy Access



DH-130A