

Instructions for GPS GameSpy Connect

THANK YOU for your purchase of the GPS GameSpy Connect Module. Please read this booklet before using the unit. If you should have any questions about this product or any other Moultrie product, please contact us using the information on the back of this sheet. Please register your product at www.moultriefeeders.com TO ACTIVATE YOUR WARRANTY.

GPS GameSpy Connect leverages the cell phone network to wirelessly upload photos from your camera to your Moultrie Inbox, allows you to change your camera settings from the Moultrie Camera Settings web page, and provides the GPS (Global Positioning System) coordinates of the GPS GameSpy Connect module's location. The GPS coordinates are attached to each photo taken.

IMPORTANT - PLEASE READ:

- → GPS GameSpy Connect is ONLY for use with Moultrie game cameras that are GPS GameSpy Connect enabled (ex. I45, I65, M45 and M65). See www.moultriegamemanagement.com Camera Compatibility tab for details.
- → GPS GAMESPY CONNECT WILL ONLY WORK WHERE THERE IS AT&T CELL PHONE NETWORK COVERAGE (see Network Coverage Test below).
- → GPS GameSpy Connect requires a Moultrie monthly membership plan.
- → GPS coordinates will only be transmitted to the Moultrie Server if the top of the GPS GameSpy Connect is exposed to the sky.

NETWORK COVERAGE TEST:

(1) Sign-up and register to activate device (Page 4)

(2) Install batteries in GPS GameSpy Connect (page 2)

(3) Place the TEST/AUTO switch to TEST (page 3). The GPS GameSpy Connect module does not need to be connected to the camera for this test.

(4) **TEST:** The GSM STATUS INDICATOR (page 3) will blink repeatedly within 30 seconds if the GPS GameSpy Connect has connected to the local cellular tower. If it does not blink repeatedly within 30 seconds, you do not have the necessary network coverage at this location.

(5) Place the TEST/AUTO switch back to AUTO when done.





Refer to Page 3 for a description of the items shown above

I OVERVIEW (cont.)

→ RJ45 COMMUNICATION CABLE

Connect the RJ45 Communication Cable to the female port on the Moultrie Camera. Assure there are no sharp bends in cable and that the connector "clicks" into place when installed in the camera.

→ BATTERIES

GPS Game Spy Connect module requires six AA batteries. To install or replace batteries, remove four thumb screws from front panel and note the polarity shown on previous page. New Alkaline batteries will last approximatley 30 days if IMMEDIATE UPLOAD is OFF and the Photo Upload Frequency is set to "Once per Day" in the Camera Settings page on the Moultrie Server. Energizer Lithium batteries will last significantly longer.

→ TEST/AUTO SWITCH

When set to AUTO, power will be controlled by the Moultrie camera. **Use of the TEST setting for anything other than initial registration is not recommended and will cause excessive battery power drain.** The TEST setting should only be used during initial registration if a camera is NOT connected.

→ GSM STATUS INDICATOR

When module is turned on by the camera (Page 4), the GSM STATUS INDICATOR will blink repeatedly within 30 seconds if the GPS GameSpy Connect has connected to the local cellular tower. If the GSM STATUS INDICATOR remains on solid after approximately 30 seconds, it is likely that you do not have the necessary network coverage at this location or have not yet registered - refer to the Troubleshooting Section of this document for details.

→ POWER CONNECTION MOULTRIE ACCESSORY

Accepts Moultrie options for extending or replacing batteries. Refer to www.moultriefeeders.com for more information.

→ MOUNTING BRACKETS

Slide provided Mounting Strap or Mounting Bar through Mounting Brackets. Strap can go around tree or pole. Bar may be used for securing with screws. Mount with antenna pointing up.

→ GSM CELLULAR ANTENNA

Must be pointing up and should not be covered by metallic surfaces.

→ GPS INTERNAL ANTENNA

Works best if it has direct exposure to the sky; however, it is capable of working under tree cover.

ACCOUNT REGISTRATION

Monthly Membership Plans range in price based on the number of photos you intend to send each month. To register open your computer's browser, go to www.moultriegamemanagement.com , select "New Account" and follow the on-screen instructions.



2 During registration you will be asked for the SIM and IMSI numbers which are located under the battery door as shown.

1



3 The SIM cellular network activation could take up to an hour, but typically takes about 15 minutes.

> Each time the camera is turned on, the system attempts to communicate to the website. To verify everything is working correctly, go to the CAMERAS tab and select ACCOUNT STATUS as shown.

If the Account Status shows a "Last Activity", this indicates that the registration was successful and the system is working correctly.

If an hour has expired since registration and the "Camera is being Activated" screen still appears, refer to the Troubleshooting section of this document.





P	NDING ACTIV	ATION	_	_			
	LAI MARIER: 1905	10421257665538	Mill 5104102	17660938		-	-
	ABBAR SATERY'S	ern.	- 1974	maniria		- 11	miAca
			Camera Please ch	is being eck back	activated. in a while!		279





Follow these steps to setup your GPS GameSpy Connect Module:

1 Install 6 AA batteries (Page 3 - Batteries)

- 2 Verify Network Coverage (Page 1 Network Coverage Test)
- **3** Verify ON/AUTO switch is on AUTO (Page 3 ON/AUTO Switch)
- 4 Connect RJ45 Communication Cable to Camera (Page 3- RJ45 Com Cable)
- **5** Turn camera's switch to ON (refer to Camera's User Manual)
- **6** Turn "Cellular Modem" ON in Camera's Setup Menu (Page 7 File Upload)
- 7 Mount GPS GameSpy Connect to tree or post using Mounting Brackets

OPERATION: The Camera will automatically turn on the GPS GameSpy Connect module when one of the following events occur:

- → Camera is first turned on.
- → It is the "Photo Upload Time" as configured in the Camera Settings page on the web site (default setting).
- → A picture was just taken and "IMMEDIATE UPLOAD PHOTOS" is turned ON in the camera's setup menu and Photo Upload Frequency is set to "Immediately" in the Camera Settings page on the web site.

When the camera turns on the module it will go into "CELLULAR UPLOAD" mode which is indicated on the camera's display. During Cellular Upload, the Camera is using the GPS GameSpy Connect Module to receive settings from the website, send camera settings, and transfer photos to the Moultrie InBox.

The antenna gain, including cable loss, must not exceed 3 dBi at 1900 MHz / 1.4 dBi at 850 MHz for mobile operating configurations and 7 dBi at 1900 MHz / 1.4 dBi at 850 MHz for fixed mounted operations, as defined in 2.1091 and 1.1307 of the rules for satisfying RF exposure compliance.

The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be collocated or operating in conjunction with any other antenna or transmitter.

The final product operating with this transmitter must include operating instructions and applicable warnings, as described in this filing, for end users and installers to satisfy RF exposure compliance requirements. OEM integrators must be informed of the specific requirements.

This device contains functions that are not operational in U.S. Territories. This filing is only applicable for US operations.

IV SYSTEM CONFIGURATION

All settings can be modified on the web site and most settings can be modified on the camera. SETTINGS ARE EXCHANGED BETWEEN THE WEB SITE AND CAMERA ONLY WHEN THE NEXT CELLULAR UPLOAD OCCURS. Refer to the OPERATION section in the SETUP AND OPERATION (Page 5) for a description of when cellular upload occurs.

If the settings are modified on the camera, the website will be updated. If settings are modified on the web site, the camera will be updated. The website's settings will overwrite the camera's settings if a modification is made at both the web site and the camera.

Settings on	Settings on	Description
Website	Camera	
Select	Not available	If you have multiple cameras, this list appears and allows you to select
Camera	at Camera	the camera of interest
Camera	Camera	10 Characters - The Camera Name can be printed on the photos and
Name	Name	provides a point of reference when multiple cameras are used.
Time Zone	Not available	The Camera's time and date is set by the Moultrie website. Select the
	at Camera	time zone in which the camera is located
Capture	Capture	Camera's operational mode - Still or Video. If set to video, a .jpg photo
Mode	Mode	is also generated. Note that videos are not sent to the website.
Photo Upload	Not available	The time of day to do the initial upload.
Time	at Camera	
Photo Upload	Immediate	On the website, you can choose to have the camera upload every 2,6,12,
Frequency	Upload	or once per day (from the Photo Upload Time) OR upload photos
	Photos	immediately after they are taken. UPLOADING ONCE PER DAY
		WILL OPTIMIZE BATTERY LIFE
Photo Upload	Max	Use this option to limit number of images sent per day - 5, 10, 20, 30, 50
Daily Max	Images/Day	or Unlimited
Photo	Photo	Low, Medium, High, or Enhanced. The higher the photo capture
Capture	Quality	resolution, the larger the photo.
Resolution		
Photo Upload	Photo	Photos can be stored in camera memory at one resolution (Photo Quality)
Resolution	Upload	and sent to the Moultrie Server (Photo Upload) in a lower resolution. The
	Resolution	lower the Photo Upload Resolution the more photos that can be sent
		within your plan limit.
Multi-Shot	Multi-Shot	1, 2, or 3 shots. Each time the camera is activated via the motion
Count	Count	detector, the camera can take this number of photos in a row.
Photo Delay	Photo Delay	1, 5, 10, 30 or 60 minutes – the number of minutes the camera waits
-	-	before taking another photo.
Trigger	Feature Not	Motion detection (passive infrared) or time lapse
Mode	Available on	
	Some	
	Models	
Video	Video	Video resolution can be set to LOW or HIGH. The higher the quality of
Resolution	Resolution	the video, the more memory it consumes. However, higher quality videos
		have higher resolution

IV SYSTEM CONFIGURATION (cont.)

Settings on	Settings on	Description
Website	Camera	
Video Length	Video	5, 15 or 30 seconds - When the GameSpy Camera is configured for
	Length	VIDEO, the camera will record video for a designated amount of time
		each time an animal is detected. The default video length is 10 seconds at
		night.
Time Lapse	Feature Not	The interval for the Time Lapse feature.
Frequency	Available on	
	Some	
	Models	
Timer Lapse	Feature Not	The start time for the Time Lapse feature.
Start Time	Available on	*
	Some	
	Models	
Flash	Flash	Turns the Flash on off
File Upload	Cellular	Enables the ability to unload photos to the Moultrie Inhoy THIS MUST
The opload	Modem	BE ON FOR THE GPS GAMESPY CONNECT TO OPERATE.
Delete Photo	Delete	A photo will only be sent to the Moultrie Server one time; however, it
After Upload	Photos After	will be retained in the camera's memory (internal memory or optional
_	Upload	SD card). To save space in the internal memory or on the SD card, you
	•	can configure the system to delete each photo after it has been sent to the
		Moultrie InBox. Note: SD Card Lock must be off for this feature to
		work.
Info Strip	Info Strip	Turn on or off the information strip on the bottom of each photo.
Printed on		
Photo		
Temperature	Temperature	The temperature can be printed on the photo in degrees Fahrenheit or
	*	Celsius.
Delete All	Delete	Remove all the images from the internal memory or the SD card if
Photos	Photos	installed.

TROUBLESHOOTING

v)

Symptom	Possible Cause	Solution Reference
It says "Camera is being	 No GSM Network Coverage 	 Page 1: Network Coverage Test
Activated" in the	 Low or no batteries 	Page 2: Batteries
Account Status screen and	 Low or no batteries in camera 	 Refer to Camera's User Manual
it has been more than 1	 Camera is turned OFF 	 Refer to Camera's User Manual
hour	 RJ45 Com Cable is unplugged or broken 	 Page 2: RJ45 Communication Cable
	 "Cellular Modem" is OFF at camera 	Page 7 : File Upload/Cellular Modem
GSM Status Indicator	 No GSM Network Coverage 	 Page 1: Network Coverage Test
remains on solid and does	 Low or no batteries 	Page 2: Batteries
not flash after		
approximately 30 seconds		
GSM Status Indicator	 Low or no batteries 	Page 2: Batteries
does not illuminate when	 RJ45 Com Cable is unplugged or broken 	 Page 2: RJ45 Communication Cable
camera is first turned on	 ON/AUTO switch is in the ON position 	 Page 2 : ON/AUTO Switch
GSM Status Indicator	 ON/AUTO switch is in the ON position 	 Page 2 : ON/AUTO Switch
always remains flashing		
or solid even when		
camera is turned OFF		
GSM Status Indicator is	• No "event" has occurred to turn it on	• Page 4: Setup – see Operation
OFF	 Low/no Batteries 	Page 2: Batteries
	 RJ45 Com Cable is unplugged or broken 	Page 2: RJ45 Communication Cable

V TROUBLESHOOTING (cont.)

Symptom	Possible Cause	Solution Reference
When turning on camera,	RJ45 Com Cable is unplugged or broken	Page 2: RJ45 Communication Cable
"CELLULAR UPLOAD"	Low or no batteries	Page 2: Batteries
mode is not displayed on	 Low or no Batteries in Camera 	Refer to Camera's User Manual
the camera's screen within	 "Cellular Modem" is not turned ON 	Page 7 : File Upload/Cellular Modem
60 seconds	 "File Upload" is OFF at web site 	• Page 7 : File Upload/Cellular Modem
Settings changed on the	Cellular upload has not yet happened	• Page 6
camera are not sent to the	1 5 11	e
website or vice-versa		
Battery life on GPS Game	 ON/AUTO switch is in ON position 	Page 2: ON/AUTO Switch
Spy Connect is short	 Transmitting more than once per day 	 Page 6: Photo Upload Frequency
	 Non-alkaline battery used 	
No GPS coordinates /	 GPS Antenna is not exposed to sky 	Page 3: GPS Internal Antenna
location information		_
shown on web site		
While in CELLULAR	 RJ45 Com Cable is unplugged or broken 	Page 2: RJ45 Communication Cable
UPLOAD mode, camera	 Low or no batteries 	Page 2: Batteries
display indicates "Wait		
Modem" and gets no		
further in the		
communication process		
While in CELLULAR	 System has not been registered 	Page 4 : Account registration
UPLOAD mode, camera	 No GSM Network Coverage 	 Page 1: Network Coverage Test
display indicates "Wait	 Low or no batteries 	Page 2: Batteries
Server and gets no		
acompunication process		
While in CELLULAP	• System has not been registered	• Page 4 : A accurt registration
UPLOAD mode_display	• System has not been registered	• Fage 4 . Account registration
indicates "Cam Not On		
File"		
Pictures never get sent to	 "Cellular Modem" is OFF at camera 	• Page 7 : File Upload/Cellular Modem
Moultrie Inbox even after	• "File Upload" is OFF at web site	• Page 7 : File Upload/Cellular Modem
"CELLULAR UPLOAD"	• You have exceeded your max daily limit	Page 6: Photo Upload Daily Max
mode is displayed on the	• You have exceeded the monthly plan limit	Check Data Transfer in Account
camera's display	51	Status on website
Pictures use to get sent,	 "Cellular Modem" is OFF at camera 	Page 7 : File Upload/Cellular Modem
but are no longer sent to	 "File Upload" is OFF at web site 	• Page 7 : File Upload/Cellular Modem
the Moultrie Inbox	• Your max daily limit is set too low	• Page 6: Photo Upload Daily Max
	• You have exceeded the monthly plan limit	Check Data Transfer in Account
	· · · · · · · · · · · · · · · · · · ·	Status on website
Getting too many pictures	• You have not set a limit on number of	 Page 6: Photo Upload Daily Max
per day	photos sent per day	
Using-up too much of	• Files being transmitted are too large	Page 6 : Photo Upload Resolution
your data plan too quickly	Sending too many photos	Page 6: Photo Upload Daily Max
	• Membership plan is too small	Call Moultrie to increase plan



Our Service Department will gladly answer any questions you have. Call 205-664-6700 or 800-653-3334, Monday - Friday, 8:00 AM to 5:00 PM CST. www.moultriefeeders.com