

Electrical Sampling Modules

80E10 • 80E09 • 80E08 • 80E07 • 80E06 • 80E06X2 • 80E04 • 80E03 • 80E01
Data Sheet



Features & Benefits

All Modules

- Up to 70 GHz Bandwidth and 5 ps Measured Rise Time (10 - 90%)
- Lowest Noise for Analysis – 450 μV_{RMS} at 60 GHz, 300 μV_{RMS} at 30 GHz
- Remote Samplers*¹ Enable Location of Sampler Near DUT and Ensure Best Signal Fidelity
- Independent Sampler Deskew Ensures Easy Fixture and Probe De-embedding
- Dual Channel (Except 80E01 and 80E06)
- Precision Microwave Connectors (3.5 mm, 2.92 mm, 2.4 mm, and 1.85 mm)
- Probe Support (Except 80E06)

TDR Modules

- 15 ps Reflected True Differential Fully Integrated TDR Rise Time (12 ps Incident) and Feature Resolution Below 1 mm
- Efficient, Accurate, Easy to Use, and Cost-effective S-parameters up to 50 GHz

Applications

- Impedance Characterization and S-parameter Measurements for Serial Data Applications
- Advanced Jitter, Noise, and BER Analysis
- Channel and Eye-diagram Simulation and Measurement-based Spice Modeling

80E10, 80E08, and 80E04

- High-performance TDR/T Measurements
- Impedance Profile, Inductance, Capacitance, and S-parameters
- Transmission Line Quality, Impedance, and Crosstalk
- True Differential, Common Mode, and Single-ended Measurements
- Efficient Fault Isolation

80E09, 80E07, 80E06, 80E01

- High-frequency, Low-noise Signal Acquisition
- Fast Rise Time Measurements
- Jitter Analysis and Waveform Analysis

80E03

- Device Characterization, Transmission Quality, Waveform Parameters
- Low Signal Measurements

*¹ Integrated on 80E07 - 80E10 and optional on 80E01 - 80E04 and 80E06.

TDR Modules: 80E10, 80E08, and 80E04

The 80E10, 80E08, and 80E04 are dual-channel Time Domain Reflectometry (TDR) sampling modules, providing up to 12 ps incident and 15 ps reflected rise time in the 80E10 (18 ps incident in 80E08 and 23 ps incident in 80E04). Each channel of these modules is capable of generating a fast step for use in TDR mode and the acquisition portion of the sampling module monitors the incident step and any reflected energy. The polarity of each channel's step can be selected independently. This allows for differential or common mode TDR or S-parameters testing of two coupled lines, in addition to the independent testing of isolated lines. The independent step generation for each channel allows true differential measurements, which ensures measurement accuracy for differential devices.

The 80E10 and 80E08 are small form factor, fully integrated independent 2-meter remote sampler systems, enabling location of the sampler near the DUT and ensuring the best signal fidelity. An optional 2-meter extender is available for 80E04. The modules characterize crosstalk by using TDR steps to drive one line (or line pair for differential crosstalk) while monitoring a second line (or line pair) with the other channel (or another module for differential crosstalk). The "filter" function on the 8200 and 8000 Series mainframes can be used with TDR or crosstalk measurements to characterize expected system performance with slower edge rates.

All modules have independent incident step and receiver deskew to remove the effect of measurement fixtures and probes, that enable faster and easier de-embedding of test fixtures. The 80E10 sampling modules provide an acquisition rise time of 7 ps, with up to 50 GHz user-selectable equivalent bandwidth (with 50, 40, and 30 GHz settings). The 80E08 sampling bandwidth is 30 GHz (user selectable with 30 and 20 GHz settings) and 80E04 sampling bandwidth is 20 GHz. The 20 GHz P8018 single-ended and 18 GHz P80318 differential variable pitch TDR probes provide excellent performance and compliance, ensuring easy and accurate backplane and package measurements.

When the user employs these modules with Tektronix IConnect® TDR and VNA software, he or she can acquire up to 1,000,000 data points and obtain up to 50 GHz differential, mixed mode, and single-ended S-parameters. IConnect also enables impedance, S-parameters, and Eye-diagram compliance testing as required by various serial data standards, as well as full channel analysis, Touchstone (SnP) file output and SPICE modeling for gigabit interconnects.

Sampling Modules: 80E09, 80E07, 80E06, 80E03, and 80E01

The 80E09 and 80E07 are dual-channel modules with remote samplers, capable of 450 μV_{RMS} noise at 60 GHz sampling bandwidth, and 300 μV at 30 GHz sampling bandwidth. Each small form factor remote sampler is attached to a 2-meter cable in order to minimize the effects of cables, probes, and fixtures, allow close location of the sampler to the DUT, and ensure best signal fidelity. User-selectable bandwidth settings (60/40/30 on 80E09 and 30/20 on 80E07) offer optimal noise/bandwidth trade-off.

80E06 and 80E01 are single-channel, 70+ and 50 GHz bandwidth sampling modules. 80E06 provides the widest measurement bandwidth and fastest rise-time measurements with world-class signal fidelity. Both 80E06 and 80E01 provide superior maximum operating range of ± 1.6 V. Both of these modules can be used with the optional 2-meter extender cable, which ensures superior signal fidelity and measurement flexibility.

The 80E03 is a dual-channel, 20 GHz sampling module. This sampling module provides an acquisition rise time of 17.5 ps or less. An optional 2-meter extender cable is available.

When used with Tektronix 80SJNB Jitter, Noise, and BER software, these modules enable separation of both Jitter and noise into their components, understand precise causes of Eye closure, and obtain highly accurate extrapolation of BER and 3-D Eye contour. When used with 82A04 phase reference module, time-base accuracy can be improved down to 200 fs_{RMS} Jitter, which together with the 300 μV noise floor and 14 bits of resolution ensures the highest signal fidelity for the measured signals.

Characteristics

Characteristic	Application Type	Channels	Input Impedance	Channel Input Connector	Bandwidth* ²
80E10	True differential TDR, S-parameters, and fault isolation	2	50 $\pm$ 1.0 Ω	1.85 mm female, precision adapter to 2.92 mm included with 50 Ω SMA termination	50/40/30 GHz* ^{3, 4}
80E09	High-frequency, low noise signal acquisition and jitter characterization	2	50 $\pm$ 1.0 Ω	1.85 mm female, precision adapter to 2.92 mm included with 50 Ω SMA termination	60/40/30 GHz* ^{3, 4}
80E08	True differential TDR and S-parameters	2	50 $\pm$ 1.0 Ω	2.92 mm female	30/20 GHz* ^{3, 4}
80E07	Optimal noise/performance trade-off for jitter characterization	2	50 $\pm$ 1.0 Ω	2.92 mm female	30/20 GHz* ^{3, 4}
80E06	High-speed electrical device characterization	1	50 $\pm$ 0.5 Ω	1.85 mm female, precision adapter to 2.92 mm included with 50 Ω SMA termination	70+ GHz
80E04	TDR impedance and crosstalk characterization	2	50 $\pm$ 0.5 Ω	3.5 mm female	20 GHz* ³
80E03	Device characterization	2	50 $\pm$ 0.5 Ω	3.5 mm female	20 GHz* ³
80E01	High-frequency, high maximum operating range signal acquisition	1	50 $\pm$ 0.5 Ω	2.4 mm female, precision adapter to 2.92 mm included with 50 Ω SMA termination	50 GHz

*² Values shown are warranted unless printed in an italic typeface which represents an unwarranted characteristic value that the instrument will typically perform to.

*³ Calculated from 0.35 bandwidth rise time product.

*⁴ User selectable.

Module	Rise Time (10% to 90%)	Dynamic Range	Offset Range	Maximum Operating Voltage	Maximum Nondestruct Voltage, DC + AC _{p-p}	Vertical Number of Digitized Bits
80E10	7 ps* ³	1.0 V _{p-p}	$\pm$ 1.1 V	$\pm$ 1.1 V	2.0 V	14 bits full scale
80E09	5.8 ps* ³	1.0 V _{p-p}	$\pm$ 1.1 V	$\pm$ 1.1 V	2.0 V	14 bits full scale
80E08	11.7* ³	1.0 V _{p-p}	$\pm$ 1.1 V	$\pm$ 1.1 V	2.0 V	14 bits full scale
80E07	11.7* ³	1.0 V _{p-p}	$\pm$ 1.1 V	$\pm$ 1.1 V	2.0 V	14 bits full scale
80E06	5.0 ps* ³	1.0 V _{p-p}	$\pm$ 1.6 V	$\pm$ 1.6 V	2.0 V	14 bits full scale
80E04	$\leq$ 17.5 ps	1.0 V _{p-p}	$\pm$ 1.6 V	$\pm$ 1.6 V	3.0 V	14 bits full scale
80E03	$\leq$ 17.5 ps	1.0 V _{p-p}	$\pm$ 1.6 V	$\pm$ 1.6 V	3.0 V	14 bits full scale
80E01	7 ps * ³	1.0 V _{p-p}	$\pm$ 1.6 V	$\pm$ 1.6 V	2.0 V	14 bits full scale

*³ Calculated from 0.35 bandwidth rise time product.

Module	Vertical Sensitivity Range	DC Vertical Voltage Accuracy, Single Point, within $\pm 2^\circ\text{C}$ of Compensated Temperature	Typical Step Response Aberrations*2	RMS Noise*2
80E10	10 mV to 1.0 V full scale	$\pm[2 \text{ mV} + 0.007 \text{ (Offset)} + 0.02 \text{ (Vertical Value - Offset)}]$	$\pm 1\%$ or less over the zone 10 ns to 20 ps before step transition; +6%, -10% or less for the first 400 ps following step transition; +0%, -4% or less over the zone 400 ps to 3 ns following step transition; +1%, -2% or less over the zone 3 ns to 100 ns following step transition; $\pm 1\%$ after 100 ns following step transition	50 GHz: $600 \mu\text{V}$, $\leq 700 \mu\text{V}$ 40 GHz: $370 \mu\text{V}$, $\leq 480 \mu\text{V}$ 30 GHz: $300 \mu\text{V}$, $\leq 410 \mu\text{V}$
80E09	10 mV to 1.0 V full scale	$\pm[2 \text{ mV} + 0.007 \text{ (Offset)} + 0.02 \text{ (Vertical Value - Offset)}]$	$\pm 1\%$ or less over the zone 10 ns to 20 ps before step transition; +6%, -10% or less for the first 400 ps following step transition; +0%, -4% or less over the zone 400 ps to 3 ns following step transition; +1%, -2% or less over the zone 3 ns to 100 ns following step transition; $\pm 1\%$ after 100 ns following step transition	60 GHz: $450 \mu\text{V}$, $\leq 600 \mu\text{V}$ 40 GHz: $330 \mu\text{V}$, $\leq 480 \mu\text{V}$ 30 GHz: $300 \mu\text{V}$, $\leq 410 \mu\text{V}$
80E08	10 mV to 1.0 V full scale	$\pm[2 \text{ mV} + 0.007 \text{ (Offset)} + 0.02 \text{ (Vertical Value - Offset)}]$	$\pm 1\%$ or less over the zone 10 ns to 20 ps before step transition; +6%, -10% or less for the first 400 ps following step transition; +0%, -4% or less over the zone 400 ps to 3 ns following step transition; +1%, -2% or less over the zone 3 ns to 100 ns following step transition; $\pm 1\%$ after 100 ns following step transition	30 GHz: $300 \mu\text{V}$, $\leq 410 \mu\text{V}$ 20 GHz: $280 \mu\text{V}$, $\leq 380 \mu\text{V}$
80E07	10 mV to 1.0 V full scale	$\pm[2 \text{ mV} + 0.007 \text{ (Offset)} + 0.02 \text{ (Vertical Value - Offset)}]$	$\pm 1\%$ or less over the zone 10 ns to 20 ps before step transition; +6%, -10% or less for the first 400 ps following step transition; +0%, -4% or less over the zone 400 ps to 3 ns following step transition; +1%, -2% or less over the zone 3 ns to 100 ns following step transition; $\pm 1\%$ after 100 ns following step transition	30 GHz: $300 \mu\text{V}$, $\leq 410 \mu\text{V}$ 20 GHz: $280 \mu\text{V}$, $\leq 380 \mu\text{V}$
80E06	10 mV to 1.0 V full scale	$\pm[2 \text{ mV} + 0.007 \text{ (Offset)} + 0.02 \text{ (Vertical Value - Offset)}]$	$\pm 5\%$ or less for first 300 ps following step transition	1.8 mV, $\leq 2.4 \text{ mV}$ (maximum)
80E04	10 mV to 1.0 V full scale	$\pm[2 \text{ mV} + 0.007 \text{ (Offset)} + 0.02 \text{ (Vertical Value - Offset)}]$	$\pm 3\%$ or less over the zone 10 ns to 20 ps before step transition; +10%, -5% or less for the first 300 ps following step transition; $\pm 3\%$ or less over the zone 300 ps to 5 ns following step transition; $\pm 1\%$ or less over the zone 5 ns to 100 ns following step transition; 0.5% after 100 ns following step transition	$600 \mu\text{V}$, $\leq 1.2 \text{ mV}$ (maximum)
80E03	10 mV to 1.0 V full scale	$\pm[2 \text{ mV} + 0.007 \text{ (Offset)} + 0.02 \text{ (Vertical Value - Offset)}]$	$\pm 3\%$ or less over the zone 10 ns to 20 ps before step transition; +10%, -5% or less for the first 300 ps following step transition; $\pm 3\%$ or less over the zone 300 ps to 5 ns following step transition; $\pm 1\%$ or less over the zone 5 ns to 100 ns following step transition; $\pm 0.5\%$ after 100 ns following step transition	$600 \mu\text{V}$, $\leq 1.2 \text{ mV}$ (maximum)
80E01	10 mV to 1.0 V full scale	$\pm[2 \text{ mV} + 0.007 \text{ (Offset)} + 0.02 \text{ (Vertical Value - Offset)}]$	$\pm 3\%$ or less over the zone 10 ns to 20 ps before step transition; +12%, -5% or less for the first 300 ps following step transition; +5.5%, -3% or less over the zone 300 ps to 3 ns following step transition; $\pm 1\%$ or less over the zone 3 ns to 100 ns following step transition; $\pm 0.5\%$ after 100 ns following step transition	1.8 mV, $\leq 2.3 \text{ mV}$ (maximum)

*2 Values shown are warranted unless printed in an italic typeface which represents a unwarranted characteristic value that the instrument will typically perform to.

TDR System (80E10, 80E08, 80E04 only)

Characteristic	80E10	80E08	80E04
Channels	2	2	2
Input Impedance	50 Ω nominal	50 Ω nominal	50 Ω nominal
Channel Input Connector	1.85 mm	2.92 mm	3.5 mm
Bandwidth	50 GHz	30 GHz	20 GHz
TDR Step Amplitude	250 mV (polarity of either step may be inverted)	250 mV (polarity of either step may be inverted)	250 mV (polarity of either step may be inverted)
TDR System Reflected Rise Time	15 ps	20 ps	28 ps
TDR System Incident Rise Time	12 ps	18 ps	23 ps
TDR Step Deskew Range	± 250 ps	± 250 ps	± 50 ps
TDR Sampler Deskew Range	± 250 ps	± 250 ps	+100 ns -500 ps (slot skew only)
TDR Step Maximum Repetition Rate	200 kHz	200 kHz	200 kHz

Physical Characteristics

Module	Dimension (mm / in.)			Weight (kg / lb.)
	Width	Height	Depth	Net
80E10*5	55 / 2.2	25 / 1.0	75 / 3.0	0.175 / 0.37
80E09*5	55 / 2.2	25 / 1.0	75 / 3.0	0.175 / 0.37
80E08*5	55 / 2.2	25 / 1.0	75 / 3.0	0.175 / 0.37
80E07*5	55 / 2.2	25 / 1.0	75 / 3.0	0.175 / 0.37
80E06	79 / 3.1	25 / 1.0	135 / 5.3	0.4 / 0.87
80E04	79 / 3.1	25 / 1.0	135 / 5.3	0.4 / 0.87
80E03	79 / 3.1	25 / 1.0	135 / 5.3	0.4 / 0.87
80E01	79 / 3.1	25 / 1.0	135 / 5.3	0.4 / 0.87

*5 Remote sampler module characteristics.

Ordering Information**80E10**

Dual-channel, 50 GHz True Differential TDR Sampling Module with Remote Samplers.

Includes: User manual, certificate of traceable calibration standard, two precision adapters to 2.92 mm included with 50 Ω SMA terminations.**80E09**

Dual-channel, 60 GHz Sampling Module.

Includes: User manual, certificate of traceable calibration standard, two precision adapters to 2.92 mm included with 50 Ω SMA terminations.**80E08**

Dual-channel, 30 GHz True Differential TDR Sampling Module with Remote Samplers.

Includes: User manual, certificate of traceable calibration standard, two 50 Ω SMA terminations.**80E07**

Dual-channel, 30 GHz Sampling Module.

Includes: User manual, certificate of traceable calibration standard, two 50 Ω SMA terminations.**80E06**

70+ GHz Electrical Sampling Module.

Includes: User manual, calibration data report, precision adapter to 2.92 mm with 50 Ω SMA termination.**80E06X2** – Bundled ordering configuration provides two 80E06 modules.**80E04**

Dual-channel, 20 GHz True Differential TDR Sampling Module.

Includes: User manual, calibration data report, two 50 Ω SMA terminations.**80E03**

Dual-channel, 20 GHz Sampling Module.

Includes: User manual, calibration data report, two 50 Ω SMA terminations.**80E01**

Single-channel, 50 GHz Sampling Module.

Includes: User manual, calibration data report, precision adapter to 2.92 mm included with 50 Ω SMA termination.

Service Options

- Opt. C3** – Calibration Service 3 Years.
- Opt. C5** – Calibration Service 5 Years.
- Opt. D1** – Calibration Data Report (not available with 80E07 - 80E10).
- Opt. D3** – Calibration Data Report 3 Years (with Opt. C3).
- Opt. D5** – Calibration Data Report 5 Years (with Opt. C5).
- Opt. R3** – Repair Service 3 Years (including warranty).
- Opt. R5** – Repair Service 5 Years (including warranty).

Other Accessories

Sampling Module Extender Cable (2-meter length) – Order 80N01 (not for use with 80E07 - 80E10).

2x Attenuator (SMA Male-to-Female) – Order 015-1001-xx.

5x Attenuator (SMA Male-to-Female) – Order 015-1002-xx.

Adapter (2.4 mm male to 2.92 mm female – can also be used as 1.85 mm male to 2.92 mm female) – Order 011-0157-xx.

P8018 – 20 GHz Single-ended TDR Probe. 80A02 module (below) recommended for static protection of the sampling or TDR module.

P80318 – 18 GHz Differential TDR Probe. 80A02 module (below) recommended for static protection of each channel of the sampling or TDR module.

80A02 – EOS/ESD Protection Module (1 channel). P8018 or P80318 TDR probe (above) recommended.

Interconnect Cables (3rd party)

Tektronix recommends using quality high-performance interconnect cables with these high-bandwidth products in order to minimize measurement degradation and variations. The W.L. Gore & Associates' cable assemblies, accessible at <http://www.gore.com/tektronix>, are compatible with the 2.92 mm, 2.4 mm, and 1.85 mm connector interface of the 80Exx modules. Assemblies can be ordered by contacting Gore (at the URL above).

Calibration Kits and Accessories (3rd party)

To facilitate S-parameter measurements with these electrical modules and IConnect® software, we recommend precision calibration kits, adapter kits, connector savers, airlines, torque wrenches, and connector gauges from Maury Microwave. These components, accessible at www.maurymw.com/tektronix.htm, are compatible with the 2.92 mm, 2.4 mm, and 1.85 mm connector interface of the 80Exx modules. Cal kits and other components can be ordered by contacting Maury Microwave (at the URL above).



Product(s) are manufactured in ISO registered facilities.

Contact Tektronix:

- ASEAN / Australasia (65) 6356 3900
- Austria +41 52 675 3777
- Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
- Belgium 07 81 60166
- Brazil +55 (11) 3759-7627
- Canada 1 (800) 661-5625
- Central East Europe, Ukraine, and the Baltics +41 52 675 3777
- Central Europe & Greece +41 52 675 3777
- Denmark +45 80 88 1401
- Finland +41 52 675 3777
- France +33 (0) 1 69 86 81 81
- Germany +49 (221) 94 77 400
- Hong Kong (852) 2585-6688
- India (91) 80-42922600
- Italy +39 (02) 25086 1
- Japan 81 (3) 6714-3010
- Luxembourg +44 (0) 1344 392400
- Mexico, Central/South America & Caribbean 52 (55) 54247900
- Middle East, Asia, and North Africa +41 52 675 3777
- The Netherlands 090 02 021797
- Norway 800 16098
- People's Republic of China 86 (10) 6235 1230
- Poland +41 52 675 3777
- Portugal 80 08 12370
- Republic of Korea 82 (2) 6917-5000
- Russia & CIS +7 (495) 7484900
- South Africa +27 11 206 8360
- Spain (+34) 901 988 054
- Sweden 020 08 80371
- Switzerland +41 52 675 3777
- Taiwan 886 (2) 2722-9622
- United Kingdom & Ireland +44 (0) 1344 392400
- USA 1 (800) 426-2200

For other areas contact Tektronix, Inc at: 1 (503) 627-7111

Updated 5 August 2009

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tektronix.com



Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

12 Aug 2009 85W-13497-8

