



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1014ZX COMBINATION SANDER WITH CABINET STAND

Product Dimensions:

Weight..... 148 lbs.
Length/Width/Height..... 18 x 15 x 58 in.
Foot Print (Length/Width)..... 15 x 16-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Cardboard
Content..... Machine
Weight..... 104 lbs.
Length/Width/Height..... 19 x 28 x 15 in.

Carton #2

Type..... Cardboard
Content..... Stand
Weight..... 52 lbs.
Length/Width/Height..... 20 x 17 x 28 in.

Electrical:

Switch..... Safety Key Type
Switch Voltage..... 110V
Cord Length..... 8-1/2 ft.
Cord Gauge..... 16 gauge
Minimum Circuit Size..... 20 amp
Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 3/4 HP
Voltage..... 110/220V
Prewired..... 110V
Phase..... Single
Amps..... 12/6A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Belt Drive
Bearings..... Sealed, Permanently Lubricated

Main Specifications:

Table Info

Table Tilt.....	0 - 45 deg.
Floor To Table Height.....	37-1/2 in.
Miter Gauge Slot Width.....	3/4 in.
Miter Gauge Slot Height.....	17/32 in.
Disc Table Length.....	12-1/4 in.
Disc Table Width.....	6 in.
Disc Table Thickness.....	1 in.

Belt Info

Sanding Belt Width.....	6 in.
Sanding Belt Length.....	48 in.
Sanding Belt Speed.....	2300 FPM
Belt Arm Tilt.....	0 - 90 deg.
Height Belt Arm Horizontal.....	42 in.
Height Belt Arm Vertical.....	58 in.
Belt Release.....	Quick Release
Drive Roller Type.....	Aluminum
Drive Roller Length.....	6 in.
Drive Wheel Diameter.....	3-1/2 in.
Idler Roller Type.....	Aluminum
Idler Roller Length.....	6 in.
Idler Roller Diameter.....	3-1/2 in.

Spindle Info

Arbor Size.....	5/8 in.
Total Arbor Length.....	11-1/2 in.

Disc Info

Sanding Disc Diameter.....	9 in.
Sanding Disc Speed.....	3450 RPM

Platen Info

Platen Type.....	Graphite Coated
Platen Length.....	16 in.
Platen Width.....	6-1/4 in.
Platen Travel.....	0 - 90 deg.

Construction

Base Construction.....	Cast Iron
Stand Construction.....	Sheet Metal
Table Construction.....	Cast Iron
Frame Construction.....	Cast Iron
Disc Construction.....	Cast Iron
Miter Gauge Construction.....	Die Cast Aluminum
Paint.....	Powder Coated

Other

No. Of Dust Ports.....	2
Dust Port Size.....	2, 2-1/2 in.
Mobile Base.....	G8683

Other Specifications:

Country Of Origin Taiwan
Warranty 1 Year
Serial Number Location On the Stand
Assembly Time 30 minutes

Features:

- Solid Cabinet Stand
- Built-in Storage Shelf
- Quick Belt Release Mechanism
- Cast Iron Table, Disc and Body