



Mobile, Eco⁺ Green Projection



Up to 6500h increased lamp life + 70% energy saving



Native XGA resolution



3000L - Project in ambient light



Detailed images, crisper whites & ultra rich blacks with 13,000:1 contrast



HDMI – Hassle free one cable connection













Mobile, Eco+ Green Projection

The EX556 is the perfect projector for all your display needs. A bright 3000L with a 13,000:1 contrast, ensures your presentations and graphics are crystal clear leaving your audience speechless every time the projector is turned on. Ideal for use with interactive whiteboards in schools or delivering an important presentation at work. Simply connect to your projector via HDMI for a one cable hassle free connection.

Installed or on the move, the versatile EX556 incorporates a built in speaker, 120Hz 3D Ready technology, optional wireless capabilities and and Eco+ technology that brings together superb picture quality and performance with optimized lamp life through energy saving features that are easy to use.



GREEN SOLUTIONS

ECO+ TECHNOLOGY FROM OPTOMA INCREASES OUR COMMITMENT TO REDUCING THE IMPACT WE ALL MAKE ON THE ENVIRONMENT

ECO+ MODE

Saving energy, saves money! Eco+ technology reduces the power consumption to as little as 30%. This intelligent feature also has a positive effect on the lamp life, increasing it up to 70% while lowering the total cost of ownership and reducing maintenance*.



Dynamically adjusts the brightness and power consumption



Bright scene ~100% Power consumption



Dark scene ~ 30% Power consumption

AUTO POWER OFF

There may be instances when the projector is left running when not in use. To help save energy if the projector is left running and no source is detected, the "Auto Power Off" feature automatically turns off the projector after a set period of time.

ECO AV MUTE

Stay in control of your presentation with the Eco AV mute feature. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also instantly reduces the power consumption to 30%, further prolonging the life of your lamp.



Eco AV mute off 100% Power consumption



Eco AV mute on 30% Power consumption

ENVIRONMENTALLY FRIENDLY

To achieve the maximum 6500hrs² lamp life, the projector should be operating in Eco⁺ mode and the auto power off feature should be enabled to automatically switch off the projector if it is accidentally left on. Enabling the <0.5W standby mode ensures the minimum energy consumption when the projector is not switched on.



We know that improving our products is the best way to reduce our impact on the environment. That's why at Optoma, we design our products to have a long usable life, use fewer materials, ship with the minimum packaging and be free of all possible toxic substances. Naturally, energy efficiency and being recyclable are built in at the design stage. With each new product, we strive towards minimising our environmental impact. For full details of Optoma Project Green please visit our website

BRIGHT, CLEAR, FOCUSED IMAGES

Bright 3000 ANSI Lumens, Perfect for projecting in lights on environments. And with DarkChip3™ technology from Texas Instruments combined with Eco⁺ technology produces a stunning 13,000:1 contrast ratio for pin sharp graphics and crystal clear text. Crisper whites, ultra-rich blacks make images come alive and text easier to read - ideal for business and education presentations.





2000:1 Contrast Ratio

13,000:1 Contrast Ratio

3D TECHNOLOGY

Using the inherent speed of DLP technology, The Optoma EX556 can output video and images at an astonishing rate of 120Hz, allowing you to show full screen, full colour, stereoscopic 3D.



Typical applications include use with 3D educational or 3D design and modelling systems. See website for updates.

WIRELESS PRESENTING (OPTIONAL EXTRA)

Making presentations couldn't be easier using the optional wireless features of the EX556. Using the wireless VGA dongle (Additional power required and sold separately) you can connect and display presentations and video material wirelessly from a laptop, PC or mobile device.

CONTROL

The extensive RS232 command set makes it simple and easy to control the EX556 with any control system.

AMX Compatibility - Dynamic Discovery Protocol is incorporated into the EX556. This feature allows for easy installation with AMX control systems.

AUDIO CAPABILITY

Built-in speakers offers excellent audio support. The EX556 is easy to set up without the need for costly external speakers.



RAPID OFF

It takes less than 10 seconds for the projector to power up and shutdown, saving both time and energy.

QUICK RESUME

Allows you to saving time by not waiting for the projector to cool down before it can power up again. If the projector is accidentally turned off, this feature allows the projector to be instantly powered on again, if selected within a period of 100 seconds.



AMAZING COLOURS

The EX556 incorporates BrilliantColor™ technology to produce stunningly bright images with perfectly balanced life-like colours.

COLOUR GUARANTEE

We are so confident that the EX556 image colour quality will remain as good as the day you bought it that Optoma will guarantee it for five years.



FEATURES

- ✓ Top cover lamp replacement
- ✓ Keypad lock
- ✓ Quick keystore correction
- ✓ Password protection for added security
- ✓ USB mouse
- ✓ Carry case



EX556 SPECIFICATIONS

| Native Papalution | XGA 1024 x 768 | | | | | |
|---------------------------------------|--|--|--|--|--|--|
| Native Resolution | | | | | | |
| Max Supported Resolution | UXGA (1600 x 1200) | | | | | |
| Brightness - BRIGHT mode ¹ | 3000 ANSI Lumens | | | | | |
| Contrast Ratio | 13,000:1 | | | | | |
| Noise Level | 28dB (ECO+ mode) | | | | | |
| Lamp Life ² | 6500/5000/4500 (Eco+/Eco/Bright mode) | | | | | |
| Weight / Dimensions (W x D x H) | 2.2 kg / 288 x 220 x 84mm | | | | | |
| Projection Lens | F/2.41 - 2.55; f=21.8 - 23.98mm, 1.1x Manual Zoom | | | | | |
| Throw Ratio | 1.95 - 2.15:1 (Projection Distance:Image Width) | | | | | |
| Projection Distance | 1.2 - 12m | | | | | |
| Image Size | 0.7 - 7.70m (27.49" - 303.12") Diagonal 4:3 | | | | | |
| Display Technology | Single 0.55" XGA DC3 DMD chip DLP® Technology | | | | | |
| | by Texas Instruments | | | | | |
| Remote Control | Full function remote with mouse controls and direct source | | | | | |
| | selecting | | | | | |
| Inputs | HDMI | | | | | |
| | 2 x 15 Pin D-Sub VGA Component via adaptor | | | | | |
| | S-Video 4 Pin Mini Din | | | | | |
| | Composite RCA | | | | | |
| | 3.5mm Audio Mini Jack | | | | | |
| | USB (remote mouse) | | | | | |
| Control | RS232 - 9 Pin D-sub | | | | | |
| OUTPUT | 15 Pin D-Sub VGA | | | | | |
| 3337 | 3.5mm Audio Mini Jack | | | | | |
| Audio | 2W Speaker | | | | | |
| Aspect Ratio | 4:3 Native, 16:9 Compatible | | | | | |
| Keystone Correction | ± 40° Vertical | | | | | |
| On Screen Display | 18 Languages: English, German, French, Italian, Spanish, | | | | | |
| OII Screeti Dispiay | Portuguese, Polish, Dutch, Russian, Finnish, Swedish, | | | | | |
| | Greek, Norwegian/Danish, Hungarian, Czech, Turkish, | | | | | |
| | | | | | | |
| Violes Commerciality | Arabic & Farsi | | | | | |
| Video Compatibility | PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p | | | | | |
| Uniformity | 85% | | | | | |
| Displayable Colours | 1.07 Billion | | | | | |
| Horizontal Scan Rate | 15.4 - 91.1kHz | | | | | |
| Power Supply | 100 - 240V, 50 - 60Hz | | | | | |
| Power Consumption | 275W BRIGHT mode < 0.5W Standby mode | | | | | |
| | 220W ECO mode < 0.5W Standby mode | | | | | |
| | 200W ECO+ mode < 0.5W Standby mode | | | | | |
| Operating Conditions | Operating: 5 - 40°C, 85% Humidity (Max), | | | | | |
| | 3000m Altitude (Max) | | | | | |
| Security | Security Bar, Kensington Lock Port, Password Protection | | | | | |
| Standard Accessories | Soft Carry Bag, AC Power Cord, VGA Cable, Full Function | | | | | |
| | Remote, Batteries x 2, Quick Start Guide, CD User Manual, | | | | | |
| | Warranty Card | | | | | |
| RoHS | Compliant | | | | | |
| Lamp Warranty | 6 months or 1000 hours - whichever comes sooner | | | | | |
| Warranty | Warranty may vary by country. Please see | | | | | |
| - · | www.optomaeurope.com or ask your local | | | | | |
| | supplier for details | | | | | |
| Colour Guarantee ³ | 5 Years | | | | | |
| 3D Support | 120Hz frame sequential 3D for resolutions up to 720p. | | | | | |
| os cappoir | 60Hz field sequential 3D for resolutions up to 480i | | | | | |
| 3D Viewing | Requires Optoma DLP® Link TM active shutter glasses – | | | | | |
| OD VIOWING | sold separately | | | | | |
| 3D Compatibility | The 3D features of Optoma projectors can only be used with | | | | | |
| SD Compatibility | | | | | | |
| | compatible 3D content. Typical applications include use with | | | | | |
| | 3D educational or 3D design and modelling systems. Support | | | | | |
| | for 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D TM | | | | | |
| | and 3D games from the Sony® PS3 or Microsoft® Xbox 360 | | | | | |
| | will require the Optoma 3D-XL that is available separately. | | | | | |

EASY TO USE REMOTE CONTROL

EX556 Remote Control

- 1 Power
- 2 Mouse select
- 3 Source
- 4 Re-sync
- 5 Left mouse click
- 6 Right mouse click
- 7 Mouse control
- 8 Display mode
- 9 Page up/down control
- 10 Vertical keystone correction
- 11 Volume control
- 12 Brightness
- 13 Menu
- 14 Direct input source select
- 15 Eco AV mute
- **16** Eco+
- 17 3D control

EX556 Connections

- 18 USB (Remote mouse)
- **19** HDMI
- 20 Video
- 21 S-Video
- 22 VGA Out
- 23 VGA 1
- 24 RS232
- 25 Audio In
- **26** VGA 2
- 27 KensingtonTM Lock
- 28 Audio Out



Exceptional Connectivity / Multiple Terminals



| rojection Distance (m) | Max. Horizontal Image Size (m) | Min. Horizontal Image Size (m) | Max. Vertical Image Size (m) | Min. Vertical Image Size (m) | Max Diagonal Image Size (m) | Max Diagonal Image Size (inch) | Max. Image Offset (m |
|------------------------|-----------------------------------|-----------------------------------|------------------------------|------------------------------|--------------------------------|-----------------------------------|----------------------|
| 1.20 | 0.62 | 0.56 | 0.46 | 0.42 | 0.77 | 30.31 | 0.07 |
| 2.00 | 1.03 | 0.93 | 0.77 | 0.70 | 1.28 | 50.52 | 0.12 |
| 2.50 | 1.28 | 1.16 | 0.96 | 0.87 | 1.60 | 63.15 | 0.14 |
| 3.00 | 1.54 | 1.40 | 1.16 | 1.05 | 1.92 | 75.78 | 0.17 |
| 4.00 | 2.05 | 1.86 | 1.54 | 1.40 | 2.57 | 101.04 | 0.23 |
| 5.00 | 2.56 | 2.33 | 1.93 | 1.75 | 3.21 | 126.30 | 0.29 |
| 6.00 | 3.08 | 2.79 | 2.31 | 2.10 | 3.85 | 151.56 | 0.35 |
| 7.00 | 3.59 | 3.26 | 2.70 | 2.45 | 4.49 | 176.82 | 0.40 |
| 8.00 | 4.10 | 3.72 | 3.08 | 2.80 | 5.13 | 202.08 | 0.46 |
| 9.00 | 4.62 | 4.19 | 3.47 | 3.15 | 5.77 | 227.34 | 0.52 |
| 10.00 | 5.13 | 4.65 | 3.86 | 3.50 | 6.42 | 252.60 | 0.58 |
| 11.00 | 5.64 | 5.12 | 4.24 | 3.85 | 7.06 | 277.86 | 0.64 |
| 12.00 | 6.15 | 5.58 | 4.63 | 4.20 | 7.70 | 303.12 | 0.69 |

For guide purposes only

EX556 is capable of 16:9 aspect ratio projection. When projecting a 16:9 image the image sizes, screen height and offset information will differ from the above.

Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ

www.optoma.eu

