EB-W28



DATASHEET



















The EB-W28 is a portable 3LCD business projector with an innovative QR code function; download the Epson iProjection app² and scan the projected QR code to connect and share content. Designed to make collaboration easy and instant, it also features high brightness and business-centric features.

Easy sharing

It's never been easier to take what you're seeing on a smart device and share it with a larger audience. The iProjection QR function means that any smartphone or tablet with the free iProjection app can scan the QR code projected by the EB-W28 to instantly connect and share content¹.

Unbeatable image quality

With WXGA resolution, 10,000:1 contrast ratio and 3,000 Lumens brightness, 3LCD technology ensures crisp images and equally high White and Colour Light Output for bright and vivid colours, and three times brighter colours than leading competitors³.

Portable design

The EB-W28 can easily be carried between meeting rooms, or installed in boardrooms.

Flexible placement

A 1.2x optical zoom and horizontal and vertical keystone adjustment makes it easy to adjust your image for your environment.

Business-centric features

Easy comparisons in meetings are possible using the split-screen functionality. Multi-PC Projection software allows moderator control and up to 50 users to share content, and Epson Network Projection provides sharing of customised settings across a fleet of projectors.

KEY FEATURES

- Easily connect smart devices
 Just scan a projected QR code to connect
- High resolution WXGA resolution for detailed images
- Great image quality
 Epson's 3LCD technology ensures a crisp image
- High brightness
 3,000 lumens and high White and Colour Light Output
- Built for business
 Split-screen and Multi PC Projection software





PRODUCT SPECIFICATIONS

IMAGE

Colour Reproduction Upto 1.07 billion colours

Colour Light Output 3.000 lumen-2.100 lumen (economy)

White Light Output 3.000 lumen - 2.100 lumen (economy) In accordance with ISO 21118:2012

Resolution WXGA, 1280 x 800, 16:10

Contrast Ratio 10.000 : 1

Lamp 200 W, 5.000 h durability, 6.000 h durability (economy mode)

Keystone Correction Auto vertical: ± 30 °, Manual horizontal ± 30 °

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 0,59 inch with MLA (D8)

OPTICAL

Projection Ratio 1,30 - 1,56:1

Zoom Manual, Factor: 1,2

Projection Size 33 inches - 320 inches

Projection Distance Wide/Tele 1,68 m - 2,02 m (60 inch screen)

Projection Lens F Number 1,58 - 1,72 Focal Distance 16.9 mm - 20.28 mm

Focus Manual Offset 10:1

CONNECTIVITY

USB Display Function 3 in 1: Image / Mouse / Sound

Interfaces USB 2.0 Type A, USB 2.0 Type B, Wireless LAN IEEE 802.11b/g/n (optional), VGA in, HDMI in,

Composite in, Component in, S-Video in, RGB in, MHL, Cinch audio in

Epson iProjection App Ad-Hoc / Infrastructure

ADVANCED FEATURES

Security Kensington lock, Security cable hole, Wireless LAN security, Password protection

Features AV Mute Slide. Built-in speaker. Direct Power on/off. Document Camera Compatible.

Horizontal and vertical keystone correction, MHL audio/video interface, Network projection,

OSD copy function, Quick Corner, Split-Screen-Function, Wireless LAN capable, iProjecton

set-up by QR code

Video Colour Modes Blackboard, Dynamic, Presentation, Sports, sRGB, Theatre, Whiteboard

GENERAL

Energy Use 270 W, 201 W (economy), 0,28 W (standby)
Product dimensions 297 x 234 x 77 mm (Width x Depth x Height)

Product weight 2,4 kg

OTHER

Warranty 24 months Carry in, Lamp: 12 months or 1.000 h

LOGISTICS INFORMATION

| V11H654040 |
|----------------------------|
| 8715946541884 |
| 360 x 300 x 160 mm |
| 4,03 Kg |
| Multiple country of origin |
| 6 Units (13 x 78) |
| |

EB-W28

WHAT'S IN THE BOX

- Carrying bag
- Computer cable
- Main unit
- Power cable
- Remote control incl. batteries
- USB cable
- User's Manual Set
- Warranty Documents

OPTIONAL ACCESSORIES

- Lamp ELPLP78 EB-SXW03/SXW18/X24 V13H010L78
- Air Filter ELPAF32 EB-SXW11/12/14 V13H134A32
- Adapter ELPAP07 Wireless LAN b/g/n V12H418P13
- Screen ELPSC26 80" Multi-Aspect V12H002S26
- Screen ELPSC24 80" Pantograph 16:10 V12H002S24
- Screen ELPSC32 50" Desktop type V12H002S32
- Ceiling Mount ELPMB23 White V12H003B23
- Ceiling pipe ELPFP13 668-918mm
 V12H003P13
- Ceiling pipe ELPFP14 918-1168mm V12H003P14



Solytron Bulgaria Ltd. Solytron Bulgaria 64, Hristofor Kolumb Blvd Sofia Airport Center Office Building A2, fl. I, Office 124, 1592 Sofia

fl. I, Office 124, 1592 Sofia Bulgaria www.solytron.bg Tel.: 00359 29602343 PolyComp 2, Bunaia Str. 1506 Sofia Bulgaria www.polycomp.bg Tel.: 00359 2 814 41 41 QR code function requires iProjection app, available on Android and iOS devices 2. iProjection App available on Android and iOS devices 3. Compared to leading 1-chip DLP business and education projectors based on NPD data, July 2011 through June 2012. Colour Brightness (Colour Light Output) measured in accordance with IDMS 15.4. Colour Brightness will vary depending on usage conditions. For more information please visit www.epson.eu/CLO

