The projector for businesses and individuals that demand only the best at a fraction of the cost

Multimedia Projector EMP-X3

Most affordable
XGA projector
without compromising
performance and
functionality offers
the best value ever.



Easy-to-Use Help Function



Single-Foot Release Lever



Large, Well-Marked buttons



High Brightness

2000 ANSI Im of Brightness in 2.6kg (5.7 lbs)

"Instant Off" Quick Shutdown

EMP-X3 deliver up to 2000 ANSI Im of brightness in a compact and light weight body.



Soft, Bright, Beautiful... 3LCD Technology

natural images and smoother, sharper video playback. No colour break-up makes images

DLPTM (Digital Light ProcessingTM) is a trademark of


Compact and Bright

- Epson's Innovative New E-TORL Lamp









completed.

Simply press

the power



(E-TORL: Epson-Twin Optimize Reflection Lamp)

3LCD technology

gentler on the eyes.

achieves brighter, more

Epson's recently developed small, high performance "E-TORL" lamps efficiently gather and project light to effectively eliminate light-leakage and minimize light diffraction. This system combines an ellipsoidal reflector with an aspherical lens and a hemisphere mirror to produce a lamp so small and highly efficient.

Quick Start-Up

With EMP-X3's surprisingly short 4-second start-up time, there is no need to wait around to view high-quality images.

Direct Power-On

The direct power-on function allows the EMP-X3 to be activated automatically when the room power is switched on. This eliminate the need to press the projector's power button.

7 Selectable Projection Modes

With 7 presentation modes to choose from, these preset settings allow you to select the mode that best suits your viewing environment.

Mode Selection: Presentation, Theatre, Game, Photo, Sports, sRGB, Blackboard

Source Search

Merely push the "Source Search" button and the EMP-X3 instantly recognizes signals and projects media from any source.

Easy-to-Use Help Function



Epson's new built-in program, guides you step-by-step through any problem you may have and helps you get back to your presentation quickly.

Single-Foot Release Lever



The well-balanced single-foot has an easily accessible release lever which allows the user to adjust the projection level with just one hand.

Large, Well-Marked buttons



Epson is focused on making its projectors easy to use for beginners and experts alike. At a glance, the operation of EMP-X3 is clear and easy to understand.

Security Functions

Power-On Protect / User's Logo Protect / Timer Protect / Key Lock

With 3 passwords protect functions and key lock functionality, the EMP-X3 have your security concerns covered. So, regardless of theft or mischief, your projector is protected with these innovative security functions.

EMP-X3



Weight = Approx. 2.6 kg

INDIA

Epson India Pvt Ltd Tel: (91) 080-3051-5000 Fax: (91) 080-3051-5005

INDONESIA

PT Epson Indonesia Tel: (62) 021-572-3161 Fax: (62) 021-572-4357 www.epson.co.id

MALAYSIA

Epson Trading (M) Sdn Bhd Tel: (60) 03-5628-8288 Fax: (60) 03-5628-8388 www.epson.com.my

PHILIPPINES

Epson Philippines Corporation Tel: (63) 02-813-6567 Fax: (63) 02-811-1163 www.epson.com.ph

SINGAPORE

Epson Singapore Pte Ltd Tel: (65) 6586-5500 Fax: (65) 6271-7066 www.epson.com.sg

THAILAND / INDOCHINA Epson (Thailand) Co., Ltd Tel: (66) 02-670-0680 Fax: (66) 02-670-0688 www.epson.co.th

Specifications

Part Number			V11H177052
Projection System			RGB Liquid-Crystal Shutter Projection System
Specification of Main Parts	LCD	Size	0.6 inch with MLA (x 3)
		Driving Method	Polysilicon TFT Active Matrix
		Pixel Number	786432 Dots (1024 x 768) x 3
		Native Resolution	XGA
	Projection Lens		Manual Focus & 1.2 x Optical Zoom
			F=1.6 / f=18.4-22.1 mm
	Lamp	Туре	170 W UHE
		Life	2000 hours (High Brightness mode) / 3000 hours (Low Brightness mode)
Screen Size (Projected Distar	nce)		30 to 300 inch [0.9 to 10.8 m]
Brightness	High / Low Brightness	Mode	2000 ANSI Im / 1500 ANSI Im
Contrast			400:1
Colour Reproduction			Full-Colour (16.77 Million Colours)
Sound Output			1 W Monaural
Effective Scanning	Pixel Clock		13.5 MHz to 162 MHz
Frequency Range	Horizontal		15 KHz to 92 KHz
(Analog)	Vertical		50 Hz to 85 Hz
Keystone Correction			Vertical: -30 to +30 Degrees
Analog RGB I/O	Display Performance	Native	1024 x 768 Dots
		Resize	1600 x 1200 / 1280 x 1024 / 800 x 600 / 640 x 480
	Input Terminal	Video	D-sub 15-Pin x 1
		Audio	RCA x 2
	Output Terminal	Video	D-sub 15-pin x 1
Video I/O	Input Signal	Video Standard	NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM
	Input Terminal	Video	Composite Video: RCA (Yellow) x 1
			S-Video: Mini DIN x 1
			Component Video: D-sub 15-Pin x 1
			Video-RGB: D-sub 15-Pin x 1
		Audio	RCA x 2
Control I/O	USB I/O Terminal		Type B x 1
Operating Temperature			5°C to 35°C <41°F to 95°F>
Start-Up Period			About 4 Sec.
Cool-Down Period			Instant Off
Power Supply Voltage			100 - 240 VAC ± 10%, 50 / 60 Hz
Power Consumption	Lamp On		240W
	Stand-by		5W
Dimension (D x W x H)			246 x 327 x 86 mm (Excludes Feet)
Weight			Approx. 5.7 lbs. / 2.6 kg
Fan Noise			30 dB (Low Brightness Mode)
Supplied Access	sories		

Power Cable	1.8 m
Computer Cable	1.8 m
Remote Control With AAA Type Alkaline Batteries x 2pcs	
Soft Carrying Case	
Password Protect Sticker	
User's Manual	

Optional Accessories

ELPLP34 (Part No. V13H010L34)	Replacement Lamp
ELPAF08 (Part No. V13H134A08)	Air Filter Set, 2 Sheets

Connector Panel

Projection Distance

Diagonal Screen Size (inches)	Wide (cm)	Tele (cm)	
30	87	105	
40	117	141	
60	177	213	
80	237	285	
100	297	358	
200	598	719	
200	000	1000	



All products and brand names herein are for identification purposes only and may be the trademarks or registered trademarks of their respective owners. Epson disclaims any and all rights in those marks. All images are simulated in this brochure. Specifications are subject to change without prior notice.

www.epson.com.sg



Printed in September 05







Multimedia Projector

EMP-X3

EXCEPTIONAL AFFORDABILITY BRILLIANT PERFORMANCE

