

BOTANY CLASSIC START UP INSTRUCTIONS

1. Remove the cabinet panels from underneath the spas touch pad.
2. Remove both filters from the spa (see page 11 in your user manual).
Place a hose in the filter box to fill the spa with water (see page 9 in your user manual).
(Remove the fittings from your hose to prevent them falling into the spas plumbing).

As the spa is filling with water check all barrel unions inside the cabinet for any leaks as it is possible for these fitting to have worked their way loose in transport. The barrel unions are the fitting which connect the pumps to the plumbing.

Also set your main diverter on the spa to the centre so that both sides of the spas plumbing will fill up with water. The main diverter is the largest handle on the top side of your spa.

Fill the spa until the water level covers the top of the highest jet.

Note: Do not leave your spa exposed to the sun with-out water in it and the hardcover on, this will cause the spa to delaminate and is not covered under warranty (this can happen within a 30 minute period if it is a hot enough day). It is extremely important that you fill your spa with water and fit the hardcover as soon as the spa is put outside even if your electrician is not coming straight away.

3. Have a qualified electrician connect the spa to power. The power supply your electrician needs to connect is 15Amp Single Phase with the appropriate sized RCD in your houses metre box. The wiring diagram can be found on page 8 of your user manual. The panels to remove from the spa to find the electrical connection point will be the panels directly underneath the digital touch pad on the spa.

Your electrician can drill a hole anywhere through the fibreglass base to pull the electrical cable through. Just make sure that the area behind where they drill is clear of any spa parts inside the cabinet.

Once the spa has power connected to it and it is filled with water turn the power on. Never turn the spa on if you do not have it filled with water. Put the spa into Active mode see page 12 of your user manual. Once you are in active mode press Jets 1 see page 13 of your user manual, you should now have water movement within the spa. Wait 5 minutes then press Jets 1 to turn the pump off.

4. Go to page 14 in your user manual and follow the instructions to set the time of day and the cleaning cycle. Now set your desired temperature following the turning on heating instructions on page 15 of your user manual.
5. Go to your chemical instructions and balance the spas water.