



# S90 Mobile Payment Terminal

**PAX's S90** mobile POS terminal has been designed to offer superior wireless performance, embedded in a ruggedized yet stylish form factor. With a large memory and high capacity Li-ion rechargeable battery, the S90 is one of the most popular mobile terminals with merchants today.

The S90 comes with PCI PTS 3.x certification, optional built-in contactless, and delivers secure transactions using an ARM11 processor to support DUKPT, Master/Session, DES and 3DES.

# S90 Mobile Payment Terminal

## FEATURES & BENEFITS



- PCI PTS 3.x approved
- High speed ARM 11 processor
- Large memory capacity
- Optional built-in contactless
- Optional 1D barcode scanner
- USB connectivity
- Large capacity battery
- GPRS, CDMA, 3G

## SPECIFICATIONS

### Processor

32-bit ARM11

### Memory

192MB (128MB Flash, 64MB DDR)

### Display

128 x 64 pixel LCD,  
White backlit

### Keypad

10 numeric / letter keys, 8 function keys  
4 ATM keys, 1 Power ON / OFF key

### Printer

Thermal printer, speed: 18 lines per second  
Paper roll width / diameter: 58mm / 38mm

### Magnetic Card Reader

Track 1 / 2 / 3, bi-directional

### Smart Card Reader

EMV L1 & L2 certified

### Contactless card Reader (optional)

13.56MHz, ISO / IEC 14443 Type A / B,  
Mifare®, Felica, NFC  
4 RF Indicators

### Card Slots

2 SAMs  
1 SIM

### Barcode Reader (optional)

1D barcode scanner

### Communication

GPRS / CDMA / 3G (WCDMA)  
Modem (optional):  
Sync. (HDLC up to 9600bps)  
Async. (V.92, up to 56Kbps)

### Peripheral Ports

1 x RS232, 1x Mini USB (OTG)  
1 x Line (optional), 1 x power charge

### Security

PCI PTS 3.x approved  
DUKPT, Master / Session, DES, 3DES  
ANSI / ISO9564 format 0, 1, 3  
PIN ciphered key algorithm  
ANSI X9.9 / X9.19 MAC algorithm

### Environmental

0°C to 50°C (32°F to 122°F) operating temperature  
-20°C to 70°C (-4°F to 158°F) storage temperature  
10% to 93% relative humidity, non-condensing

### Voltage

Input: 100~240VAC, 50Hz / 60Hz, 1.0A  
Output: 9.5VDC, 4A

### Battery

Li-ion battery 1800mAh, 7.4V

### Physical

Length: 199mm  
Width: 87mm  
Height: 61.5mm

### Weight

504g with battery

### Accessories (optional)

Holder  
Charging Dock  
Car Charger

### Certifications

PCI PTS 3.x  
EMV L1 & L2  
EMV Contactless L1

[www.pax.us](http://www.pax.us)

THIS DOCUMENT IS PROVIDED TO YOU FOR INFORMATIONAL PURPOSES ONLY. ALL FEATURES AND SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.  
PAX are either trademarks or registered trademarks of PAX Technology Limited in China and/or other countries.  
All other trademarks or brand names are the properties of their respective holders. Copyright 2014, PAX Technology Limited, All Rights Reserved.

