	U DISE CODE		210111045	03												
14	Servo Stabilizer Protect		5KVA (1 Phase Servo Motor Operated Line Voltage Corrector), Input Range: : 50V-270V (Singie Phase), Mounting: On Wheels. Output range: 220V/230V/240V single phase (adjustable), earthing terminals, overload cutoff, output protection through MCB, Frequence range: 50+/- 3% hertz. Operating temperature: 0 to 50 degrees celsius.													
	Serial no.		2901140129													
	Silent Generator Set Champ		ISO 9001 Certified, Minimum 3 KVA Petrol/Diesel based silent generator set with Safe Cabling and Installation													
15	Serial no.	1	51311026253													
16	Initial meter reading of the Silent Generator Set			Please Tick												
17	Earthing (as per IS specifications)		Copper plate earthing stations making earthing with copper earth plate	Please Tick												
18	Lighting (ISI mark)	4	40W Tube Light with Electronic Choke (ISI mark)	Please Tick												
19	Ceiling / Wall mounted fans (ISI mark)	2	18″ blade with regulator, 3 Blade Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj/ Havells													
20	Exhaust fans (ISI mark)	2	300mm sweep, 45 Watts, Speed 1330 RPM Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj / Havells	Please Tick												
21		15	5 A- 240 V switches													
	Switches and sockets (ISI Mark)	15	2 in 1 5A and 15A Sockets													
	livial ky	2	15 A - 240 V socket with shutter													
		e Tan	ndicative Brands: - Anchor / Havells / crabtree /Wipro /Phillips / Legrand Switches and sockets is to be provided for all electronics/IT equipments including printer and Projection System to be placed at lab technician table.													
22	Computer Table Tajpuria	13	Dimensions Width 1200mm x Depth 609mm x Height 750mm 18mm pre laminated particle board conforming IS: 12823. Pretreated & powder coated steel frame. Good quality PVC edge bending to be provided on pre laminated board. No Sharp corners, smooth edges are essential. Legs frame made of 1.5 inch square pipe, 16 gauges. Table rests on good quality glide screws. Full length footrest is to be provided. One 65mm diameter hole for drawing cables is to be provided , this hole has to be covered with steel cover Good quality telescopic lider along with full width keyboard with 30cm projected depth panel, keyboard free space is 10 cm. Table must have a modesty panel of 200mm height to be provided.End caps o be provided. BIFMA Certified													
23	Chair Uma Plastic/Moderna	41	Armless Moulded Chairs, Cream colour, IStandard Compliant	Please Tick												
24	Electrical meter Initial reading		\bigcirc													
25	Painting	• -	he surface of Wall and Ceiling to be painted, shall be prepared to the satisfaction of OKCL / MSM and shall be applied with 2 coats of primer and then with 2 coats of distemper paint of standard make as approved by OKCL / OMSM.													
26	Lab Cleanliness Kit	1 set	Dusting cloth, hand held vacuum cleaner, Dust cloth covers for all the IT equipments and one Foot mat	Please Tick												
27	Curtains	Full lab	To maintain proper darkness in the Lab / Classroom during Projection	Please Tick												
28	Wall Clock	1	ISI Mark, Wall Clock	Please Tick												
29	Notice Board	1	Sieet x 3feet, P/F 15 thk Pinup board with fabric wrapped all around	Please Tick												
30	White Board	1	4 ftx3 ft minimum 18mm thickness white board	Please												

*** Please note that all the three signatures are mandetory on all the sheets.

****All fields are to up mandatorily. TECH er's NESWAS d. 4

Headmaster G. M. High School Dahita

Signature of School Head Master/Mistress with Seal

Tayesh Mahoto Signature of OKCL Representative with Seal

	U DISE CODE			2		0)	1	1	0	4	5	0	3
8	Integrated Computer Projector K-YAN	Projector & optical Science Sc								, Minimu to 16 GB ard V,	,	Please 1	lick	
	Serial no.	1	13		60		20	0	1	2	2	8	3	2
9	Interactive White Board Smart	1	 Active Size: Minimum 77" diagonal Active Area: Minimum active area 156 cm W × 117cm H Resolution: Digitizing resolution is approximately 32767 × 32767 Aspect Ratio: 4:3.Board Surface: Durable Hard-coated steel surface, optimized for projection, maintenance free, compatible with dry-erase markers and easily cleaned with whiteboard clean isopropyl alcohol (IPA),Operating System: Windows XP SP3, Windows Vista* SP2 or Windows 7 operating system and Linux,Writing Tools: Both finger and pen touch without any special tools, supports multi touch and use of non mechanical and battery free objects. Power Options: Power consumption is less than 0.5 W (100 mA at 5 V). Must obtain power from the computer through USB cable for Windows* and Linux* computers. Technology: Touch technology. No interference from Electromagnetic sources/sunlight and other external influences Data Ports: 12 Mbit /s USB connection (full-speed USB 1.1 or USB 2.0). Storage: Saving of files in PC,Software: Must include a complete version of the white boarding software application on a C DVD. Software must also be available online for download. Users must be able to access the soft without having to register for an online community. Software must be available for update via a product updating service that can automatically scan for new updates and latr users to their availability. Must support Windows* / Linux* operating systems.Should have interactive feature palm touch, image gallery, image enlarge; snap shots, recording lectures, reveal option, focus to specific part of content, zoom etc. Must supply additional software to collaborate external conte and facilitate teachers to create new content and manage and deliver other content .Must suppl application for remote collaboration to work on the same content simultaneously and write dire into each other's documents. Minimum 100 to maximum 500 user can concurrently use the facility.Accessories: Stylus/ Pens, USB Cable, Software CD, user manual etc. to be a pa											2 Tick
	Serial no.		50	4	8	0		C	2	<u> </u>	0	6	2	5
10	Multi Function Printer	1	Mode: Up to 18 ppm, Print technology: Laser, Print quality black (best): Up to 600 x 600 dpi (1200 dpi effective), Display: at least 2-line LCD, Processor speed: Minimum 400 MHz, Connectivity, standard: Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port, RI-11 Telephone port, Duplex printing: Automatic Scanner type: Flatbed, ADF, Scan file format: JPEG, TIF (compressed and uncompressed), PDF, GIF, BMP, Scan resolution, optical: Up to 1200 dpi, Certified by IDC.											Tick
	Serial no.		CN	P	8	F	8	B	9	7	-9			
11	On Line UPS Delta	1	ISO 9001 Certified Pure sine wave, E Battery type : Sea UPS and Cabling, ' temperature: 0 to sine wave output	fficiency led. Mai With DG 50 degr	90 % or l ntenance Set com	etter on Free, M Datibilitie Is,noise l	rated fu icro Cont es, freque	II load, In troller Basency rang	put Pow sed Doul e 50+/- (ver Facto ble Conv 6% hertz,	r > 0.90, ersion O , operati	nline ng	Please	Tick
	Serial no.		0 0	2	1	3	C	0	3	de	.0	0	W	5
	Networking	15	16 Port Unmanaga Mutli fucntion pri				CAT-6 cal	bling (in c	asing ca	ping) for	all the n	odes,	Please	Tick
12	Serial no.		QS	5	H	2	D	B	0	0	2	3	Ò	2
13	Fire Extinguisher	1	Portable	e Carbon	Dioxide I	Handheld	l fire ext	inguisher	s as per l	IS specifi	cation		Please	Tick
	Expiry Date		03	6	2	R	\bigcirc	2	Ч		5		L	

	U DISE CODE				2	1	O	1	F	t	0	4	5	0	3
3	Shared Computing Device N-computing	Device CAT6 cables (each of 5 meters length)), Power consumption of each access device should no											vith 5 uld not CAT 6	Plea	ise Tick
	Monitor		connectiv degrees (r higher LE vity with m horizontal CO /Energ	vertica	ck finish al), wall	, brightn mountin	ess 250 c	d/m2, vie	wing an	gle 170 g	degrees/	160		se Tick
	Serial no.	t 1	.($\eta_{k} \geq 1$		P	ls. fill the	serial no	o.s of all t	he 12 M	onitors				
	1		M	M	L	γ	6	S	S	0	1	4	3	4	5
	$\mathcal{A} = \mathcal{A} - \mathcal{A}$		O'	4	B	A	E	8	5	1	0		2	- 8	
	2		M	M	L	X		S	5	0	1	4	3	4	6
			0	1	9	\mathbf{O}	E	4	2	O	24				
	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	10 C	M	MI	_	X	K	S	S	0	1	4	3	4	6
			0	11	E	2	2	2	2	0	4			,	
	23 1 V		M	M	1	X	K	Ś	S	0	1	4	2	4	R
	4	1	0	1	B	9	6	4	2	0	4				0
	5	1	M	M	L	X	K	5	S	0	1	4	S	4	6
	×		0	1	6	4	3	2	2	0	4				
4	6	12	M			X	6 r	Sc	S	0	1	4	3	4	5
				1.		H	F	8	5	-	. 0	1.	2	1.	1
	7		0	1 0	9	$\frac{\times}{1}$	K	2	2	0	-	4	3	4	6
			M	M	L	X	K	S	S	0	7	4	3	4	6
			O	1	6	5	B	4	2	0	U	5	_	F	-
			M	MI		X	K	S	5	0	1	21	3	4	6
	9		0.	1	A	E	F	4	2	0	4	-1			0
			M	mI		V	6	5	C	0	1	1.	2	1.	(-
	10		0	4	D	D	B	8	5	1	0	4	0	7	2
	11		M	MI		X	R	S	S	0	1	4	3	4	6
			0	F	1	3	6	4	2	0	4	1		1	0
	12		M	M	L	Y	6	S	S	0	1	4	3	4	5
	~		CY	D	5	D	8	5	1	0					
5	Web Cam Brand Zebronic (Pls. tick) Wipro	1	Min 5MF	P camera, S	Suppor	t for HD	Video ca re	lling (128 duction	0 X 720 p	oixels), B	uilt-in m	ic with n	noise	Please	Tick
6	Headphones	40					Headph	one with	Mic					Please	Tick
7	Headphone Sharer	10				5-Way	3.5-mm	Headpho	one Splitt	er				Please	Tick





Implementation of e Vidyalaya Project in 4000 Govt. & Govt. aided Schools of Odisha

This is to certify that the following items/Human Resources have been duly delivered and installed/deployed in our school and all equipment/items are in proper condition for implementation of ICT lab with following details.

IMPLEMENTATION PARTNER								Please tick whichever is applicable												
IL&FS Education & Technology Services Ltd.																				
Telecommunication Cosultants India Ltd																				
U DISE CODE								1	0	7	1	1'	0	4	5	0	2			
		Date	1				Ŏ	TY	0	2	2	0	1	4	-					
School Name	GG	M		H	1	6	M		S	C	H	0	0	Ĺ						
Village	D	A	H		T	A	- <u>1</u>		21	1										
Block	R	A	J	B	0	R	A	S	A	M	B	A	R			à				
District	R	A	R	G	A	R	H		11			71	1							
Address	AI	T-PO		D	A	H	t	7	Ä		V	A	~	R	B	S				
×	DI	\$T -	B	A	R	G	A	R	H		Pin:	7	6	8	0	3	6			
Name of Head Master/ Mistress(HM)	L	A	X	M	1		K	A	N	T	A		D	A	S	H				
HM Contact No.	9	9	3	8	1	2	0	9	8	2										
Name of School Coordinator	S	υ	B	H	E	N	D	U	1	D	A	S	H							
School Coordinator's Contact no.	9	8	5	3	6	6	2	9	1	3										
Implementation partner's School Code	0	P	Z	4	~	B	A	R	6	-	1	6	0	4						
Room Dimension (in feet)	Length:			25				Breadth	. 1		1	5				Please Tick				
Sr. no.	M	Item Iake & Mo	del	Qty.				Specification & Serial No.												
1	Desktop X86 Architectur Acer Make expandable to 16							re 3.2 Ghz or higher Processor with 4 dedicated cores, RAM 4GB or higher .6GB, 500 GB HDD, 19-inch or Higher LED Monitor, Built-in audio, 300 Watt er, DVD Writer,10/100/1000BaseT Ethernet, 104 Key Keyboard and Optical Mouse With at least 2 Free Full Height PCI slots,												
		Serial no.			U	X	\checkmark	8	5	S	1	0	1	9	Ð	5	2			
	1				7	9	9	17	5											
the second se	Des	stand ktop(Stand Acer Make	d by)		expan	dable to :	16GB, 50 er, DVD \	re 3.2 Ghz or higher Processor with 4 dedicated cores, RAM 4GB or higher 6GB, 500 GB HDD, 19-inch or Higher LED Monitor, Built-in audio, 300 Watt r, DVD Writer,10/100/1000BaseT Ethernet, 104 Key Keyboard and Optical Mouse With at least 2 Free Full Height PCI slots												
2		Corial		1	C	Х	\sim	8	5	S	ł	0	1	8	D	5	2			
		Serial no.			7	9	1	4	4			4								