

Tekelec EAGLE[®] 5

Signaling Application System

Release 34.0

Master Index

909-0028-01 Revision B

December 2005



TEKELEC

**Copyright 2005 Tekelec.
All Rights Reserved
Printed in U.S.A.**

Notice

Information in this documentation is subject to change without notice. Unauthorized use or copying of this documentation can result in civil or criminal penalties.

Any export of Tekelec products is subject to the export controls of the United States and the other countries where Tekelec has operations.

No part of this documentation may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying or recording, for any purpose without the express written permission of an authorized representative of Tekelec.

Other product names used herein are for identification purposes only, and may be trademarks of their respective companies.

Trademarks

The Tekelec logo, EAGLE, G-Flex, G-Port, IP⁷, IP⁷Edge, IP⁷ Secure Gateway, and TALI are registered trademarks of Tekelec, Inc. TekServer is a trademark of Tekelec, Inc. All other trademarks are the property of their respective owners.

Patents

This product is covered by one or more of the following U.S. and foreign patents:

U.S. Patent Numbers:

5,008,929, 5,953,404, 6,167,129, 6,324,183, 6,327,350, 6,456,845, 6,606,379, 6,639,981, 6,647,113, 6,662,017, 6,735,441, 6,745,041, 6,765,990, 6,795,546, 6,819,932, 6,836,477, 6,839,423, 6,885,872, 6,901,262, 6,914,973, 6,940,866, 6,944,184, 6,954,526, 6,954,794, 6,959,076, 6,965,592, 6,967,956, 6,968,048, 6,970,542

Ordering Information

Additional copies of this document can be ordered from:

Tekelec Network Signaling Group
Attention: Central Logistics
5200 Paramount Parkway
Morrisville, North Carolina, 27560

Or e-mail your request to *CentralLogistics@tekelec.com*.

Master Index

Eagle 34.0

This section provides an alphabetized index of the Eagle 34.0 documentation set. Each index entry includes the center four digits of the manual part number and the page number where it occurs in that manual. Use Adobe Acrobat Reader 6.0.1 or later.

Symbols

#, 0178:B-22
%full threshold reached - upload required, 0338:3-251
(N)CDSR already exists for specified CGSR, 0177:2-810
(N)CGSR already exists for specified OPNAME, 0177:2-808
(N)SERV must be GPORT/PPSMS/MNPSMS/EIR when (N)SNAI=CCRNDN, 0177:2-711
(N)SERV value is invalid for the specified (N)SNAI, 0177:2-695
(N)SNP must be E164 when (N)SERV=GPORT/PPSMS/MNPSMS, 0177:2-709
(N)SNP must be E164 when NSERV=INPMR, 0177:2-695
(N)SNP/(N)SNAI must not be specified when (N)SERV=INPQ/EIR, 0177:2-697
.doc file extension, 0197:2-37, 0197:2-74, 0197:2-98, 0197:2-102
.txt file extension, 0197:2-37, 0197:2-74, 0197:2-98, 0197:2-102
<command> command not recognized (C<col>), 0177:2-504
<command> command not supported by this implementation (C<col>), 0177:2-504
<device> is <condition>, 0177:2-415
<parm_desc> is out of range - <parm>, 0177:2-8
<parm_desc> is out of range, <min>...<max> - <parm>, 0177:2-8
<parm_desc> is out of range, <min>...<max>, '<char>' - <parm>, 0177:2-8
<parm_desc> is out of range, <min>...<max>, '<char>', '<char>' - <parm>, 0177:2-9
<parm_desc> num digits incorrect, min <min> max <max> - <parm>, 0177:2-19
<parm_desc> too long, min <min>, max <max>, - <parm>, 0177:2-17
<parm_desc> too short, min <min>, max <max>, - <parm>, 0177:2-16
<parm_desc> value is undefined - <parm>, 0177:2-18
<parm_desc> is out of range, <min>...<max> - <parm>, 0177:2-24
<reserved word> cannot be used in this command <reserved name> = reserved word, 0177:2-439
"Cables", 0243:1-6
"Connectors", 0243:1-6
"Integrated Sentinel", 0243:1-6
"LEDs", 0243:1-6
"Power Cords to Peripherals", 0243:1-6

Numerics

0454 - Service Error Threshold Alarm Cleared, 0338:3-568
100% of DSM memory, 0193:5-7
100BASE-T, 0193:2-14
100BASE-T Ethernet bus, 0193:2-4, 0195:2-10
100BASE-T Ethernet network
 ELAP Sync, 0178:2-8
 main DSM, 0178:2-7, 0183:2-9

Master Index

10BASE-T, 0193:2-14
10BASE-T Ethernet bus, 0193:2-4, 0195:2-10
10BASE-T Ethernet network
 backup DSM, 0178:2-7, 0183:2-9
1114 Clock selection mismatch, 0338:3-519
1114 E1/T1 clock requires TDM-GTI, 0338:3-516
1114, 1116 Clock selection mismatch, 0338:3-523
1114, 1116 E1/T1 clock requires TDM-GTI, 0338:3-518
1114-P 1114-S 1116-P clocks failed, 0338:3-250
1114-P 1114-S 1116-S clocks failed, 0338:3-249
1114-P 1114-S clocks failed, 0338:3-248
1114-P 1116-P 1116-S clocks failed, 0338:3-247
1114-P 1116-P clocks failed, 0338:3-246
1114-P 1116-S clock failed, 0338:3-245
1114-P clock failed, 0338:3-244
1114-PHS clock failed, 0338:3-275
1114-PHS, 1114-SHS clocks failed, 0338:3-283
1114-PHS, 1114-SHS, 1116-PHS clocks failed, 0338:3-287
1114-PHS, 1114-SHS, 1116-SHS clocks failed, 0338:3-285
1114-PHS, 1116-PHS clocks failed, 0338:3-279
1114-PHS, 1116-PHS, 1116-SHS clocks failed, 0338:3-281
1114-PHS, 1116-SHS clocks failed, 0338:3-277
1114-S 1116-P 1116-S clocks failed, 0338:3-243
1114-S 1116-P clocks failed, 0338:3-242
1114-S 1116-S clocks failed, 0338:3-241
1114-S clock failed, 0338:3-240
1114-SHS clock failed, 0338:3-267
1114-SHS, 1116-PHS clocks failed, 0338:3-271
1114-SHS, 1116-PHS, 1116-SHS clocks failed, 0338:3-273
1114-SHS, 1116-SHS clocks failed, 0338:3-269
1116 Clock selection mismatch, 0338:3-521
1116 E1/T1 clock requires TDM-GTI, 0338:3-517
1116-P 1116-S clocks failed, 0338:3-239
1116-P clock failed, 0338:3-238
1116-PHS clock failed, 0338:3-263
1116-PHS, 1116-SHS clocks failed, 0338:3-265
1116-S clock failed, 0338:3-237
1116-SHS clock failed, 0338:3-261
1330, 0338:3-972
145C tag, 0224:4-16
14-bit ITU national spare point code, 0098:2-8, 0098:2-11, 0098:2-23, 0098:3-8, 0098:3-10, 0098:3-15,
 0098:3-20, 0098:3-21, 0098:4-9, 0098:4-11, 0098:4-18, 0098:4-25, 0098:4-27, 0098:6-10, 0098:6-12,
 0098:6-19, 0098:6-26, 0098:6-27, 0098:6-28, 0098:6-29, 0098:7-10, 0098:7-11, 0098:7-12, 0098:7-17,
 0098:7-24, 0098:7-25, 0098:8-9, 0098:8-13, 0098:8-14, 0098:8-22, 0098:8-23, 0098:8-27, 0098:8-30,
 0098:8-31, 0098:9-13, 0098:9-14, 0098:9-23, 0098:9-30, 0098:9-31, 0098:9-32, 0098:11-9, 0098:11-13,
 0098:11-14, 0098:11-15, 0098:11-23, 0098:11-27, 0098:11-30, 0098:11-31, 0098:11-32, 0098:12-13,
 0098:12-14, 0098:12-23, 0098:12-29, 0098:12-30, 0098:12-31
15 Minute Measurements Controlled Feature - EAGLE 5 SAS
 Activating, 0142:A-26
1500 Signaling Links, 0100:3-98, 0120:3-10
15-minute measurement collection in progress, 0177:2-599
15-minute measurement feature must be on, 0177:2-602

18911

Heading 2

LSMS/ELAP PING Enhancement, 0178:2-16

18GB to 36GB Hard Drive Upgrade (Release 29.1)(IP7 Release 7.1), 0347:2-2

1900 number portability - PCS, 0288:3-22

20% LIM cards, 0188:5-7

21 digits of CDPA, 0193:2-10

24923

Heading 2

EPAP UAMs, 0183:4-18

2500 Routing Keys (IP7 Release 7.1), 0347:2-4

30 - Read-only file system, 0197:2-121

30-minute measurement collection in progress, 0177:2-109

32 - Broken pipe, 0197:2-121

35 - Unsupported value, 0197:2-121

386/486 register cannot be specified, 0177:2-313

40 - A destination address is required, 0197:2-119

40,000 GTT Capacity, 0347:2-8

40,000 GTT Capacity (Release 28.0), 0347:2-8

40,000 GTT Capacity (Release 28.0) (IP7 Release 6.0), 0347:2-8

4000 Routesets (23.0), 0347:2-5

alarms, 0347:2-7

destination commands, 0347:2-6

rtrv-feat, 0347:2-6

41 - Protocol wrong type for socket, 0197:2-119

42 - The protocol is not available, 0197:2-119

43 - The protocol is not supported, 0197:2-119

44 - The socket type is not supported, 0197:2-119

45 - The operation is not supported on the socket, 0197:2-119

46 - The protocol family is not supported, 0197:2-119

47 - The address family is not supported, 0197:2-119

48 - The address is already in use, 0197:2-119

48 Million Numbers (27.0), 0347:2-8

alarms, 0347:2-15

changed commands, 0347:2-15

hardware requirements, 0347:2-12

new commands, 0347:2-14

system requirements, 0347:2-12

upgrade considerations, 0347:2-13

48 Million Numbers feature

see LNP 48 Million Numbers feature

48 Million Numbers feature, LNP, 0178:2-2

49 - The requested address cannot be assigned, 0197:2-119

4-port DS0 monitor applique, 0212:B-6

4-port DSCS monitor applique, 0212:B-8

4-port E1 monitor applique, 0212:B-4

4-port T1 monitor applique, 0212:B-2

4-port V.35 monitor applique, 0212:B-7

5 Minute Linkset Data (25.0), 0347:2-15

changed commands, 0347:2-16

50 - Socket operation on non-socket, 0197:2-119

500 SS7 Links (21.0), 0347:2-20

Master Index

changed commands, 0347:2-20
5000 Routes, 0120:2-23
5000 Routes (26.1), 0347:2-21
 changed commands, 0347:2-21
51 - The network is unreachable, 0197:2-119
52 - The network dropped the connection on reset, 0197:2-119
53 - Software caused the connection to abort, 0197:2-119
54 - The connection was reset by the peer, 0197:2-120
55 - No buffer space available, 0197:2-120
56 - The socket is already connected, 0197:2-120
56 Million G-Flex Entries (Release 29.1) (IP7 Release 7.1), 0347:2-3
569 - The file name is already specified, 0197:2-106
57 - The socket is not connected, 0197:2-120
58 - Can't send after socket shutdown, 0197:2-120
5-8 Bit Sequencing Assurance (24.0), 0347:2-17
 changed commands, 0347:2-18
 signaling link selection conversion, 0347:2-18
59 - Too many references: can't splice, 0197:2-120
595 - File open failed, 0197:2-106
597 - SFTP client packet send failure, 0197:2-106
598 - The SFTP connection is closed, 0197:2-106
599 - SFTP packet read failure, 0197:2-106
5-minute measurement collection in progress, 0177:2-110
60 - The connection timed out, 0197:2-120
600 - SFTP protocol error, 0197:2-107
6000 Routesets, 0120:2-23
6000 Routesets (Release 29.0), 0347:2-22
600-0154-01, 2970:3-19, 2970:3-20
600-0193-01, 2970:3-14
600-0934-01, 0224:5-69, 2970:3-13
601 - Undefined, 0197:2-107
601-0010-01, 2970:3-22
606-0062-01, 0224:5-69, 2970:3-13, 2970:3-14
608 - SFTP received a invalid ID in the response received during a read operation on remote
 directory, 0197:2-107
609 - SFTP: Handle mismatch error, 0197:2-107
61 - The connection was refused, 0197:2-120
610 - Unexpected SSH2_FXP_ATTRS, 0197:2-107
611 - Unexpected SSH_FXP_NAME, 0197:2-107
612 - SSH_FXP_REALPATH request failure, 0197:2-108
613 - SSH_FXP_READLINK request failure, 0197:2-108
614 - unexpected SSH_FXP_NAME, 0197:2-108
615 - The SFTP client received more data than expected, 0197:2-108
616 - The SFTP client failed to read the data from the file descriptor, 0197:2-108
617 - Excessive identity files, 0197:2-109
62 - The network is down, 0197:2-121
624 - The debug levels allowed for SSH protocol in openSSH is 0-9, 0197:2-109
625 - Failure to read the client configuration file, 0197:2-109
626 - Invalid compression level is specified in the client configuration file, 0197:2-109
627 - SSH failure to setup the IO with the server, 0197:2-109
628 - SSH failure to open the channel for the SSH connection with the server, 0197:2-109
629 - SSH failure to setup the channel for the SSH connection with the server, 0197:2-109

- 630 - SSH failure to verify the SSH client host key, 0197:2-109
- 631 - SSH user authentication failure, 0197:2-110
- 632 - The authentication method is NULL in the client software, 0197:2-110
- 633 - Permission is denied by the server due to authentication failure, 0197:2-110
- 633 - User login failure, 0197:2-106
- 640 - A bad message was received during the SSH authentication, 0197:2-110
- 641 - Missing authentication context, encountered during the SSH user authorization, 0197:2-111
- 642 - Failure during the public key read / verification operation, 0197:2-111
- 643 - Undefined SFTP / SSH error, 0197:2-111
- 644 - Unexpected SSH_FXP_STATUS error, 0197:2-111
- 645 - A bad option was specified in the SSH client on the EAGLE 5 SAS, 0197:2-111
- 646 - An unsupported escape character was used in the SSH client on the EAGLE 5 SAS, 0197:2-111
- 647 - An unsupported cipher type was used in the SSH client on the EAGLE 5 SAS, 0197:2-111
- 648 - An unsupported MAC type was used in the SSH client on the EAGLE 5 SAS, 0197:2-112
- 649 - A bad port was used in the SSH client on the EAGLE 5 SAS, 0197:2-112
- 65 - There is no route to the host, 0197:2-121
- 65,535 Entries per Translation Type (22.0), 0347:2-24
- 652-0841-01, 2970:3-19, 2970:3-20
- 652-0954-01, 0224:5-69, 2970:3-13
- 656 - Bad forwarding was used in the SSH client on the EAGLE 5 SAS, 0197:2-112
- 657 - Bad forwarding ports were specified in the SSH client on the EAGLE 5 SAS, 0197:2-112
- 658 - A bad dynamic port was specified in the SSH client on the EAGLE 5 SAS, 0197:2-112
- 658-0941-01, 0224:5-121
- 658-0941-02, 0224:5-121
- 659 - The host was not specified in the SSH client on the EAGLE 5 SAS, 0197:2-113
- 660 - An invalid option or argument was specified in the SSH client on the EAGLE 5 SAS, 0197:2-114
- 661 - The hostname was not specified in the SSH client on the EAGLE 5 SAS, 0197:2-114
- 663 - The SSH client was unable to load the cipher type on the EAGLE 5 SAS, 0197:2-114
- 664 - Asynchronous IO is not supported on IPSM, SSH client error, 0197:2-114
- 665 - Compression is already enabled in the SSH client on the EAGLE 5 SAS, 0197:2-114
- 666 - Unknown cipher number on the SSH client on the EAGLE 5 SAS, 0197:2-114
- 667 - The SSH client key length is invalid, 0197:2-114
- 668 - No key is available on the SSH client on the EAGLE 5 SAS, 0197:2-114
- 669 - The secure connection was closed by the remote server, 0197:2-115
- 67 - The host is down, 0197:2-121
- 670 - Connection failure due to network outage or the connection was lost due to a faulty SSHD / SFTP server or network, 0197:2-115
- 671 - An unexpected packet type was received from the SFTP / SSHD server, 0197:2-115
- 672 - A bad packet length was received from the SSHD / SFTP server, 0197:2-115
- 673 - A cryptographic attack was detected by the SSH client, 0197:2-115
- 674 - The SSH / SFTP client on the EAGLE 5 SAS failed to read from the remote side, 0197:2-116
- 675 - Corrupted check bytes were detected on the SSH / SFTP client on the EAGLE 5 SAS, 0197:2-116
- 676 - Corrupted MAC on input was detected by the SSH / SFTP client on the EAGLE 5 SAS, 0197:2-116
- 677 - Corrupted pad on input was detected by the SSH / SFTP client on the EAGLE 5 SAS, 0197:2-116
- 678 - SSH / SFTP tried to close a connection that is already closed, 0197:2-116
- 679 - The SSH / SFTP client on the EAGLE 5 SAS failed to write to the remote side, 0197:2-117
- 680 - SSH / SFTP tried to set the packet size twice, 0197:2-117
- 681 - A bad packet size was detected by the SSH / SFTP client on the EAGLE 5 SAS, 0197:2-117
- 682 - The connection timed out when SSH tried to connect to SSHD, 0197:2-118
- 683 - The SSH connection was refused by the remote server, 0197:2-118
- 684 - The SSHD server is unreachable, 0197:2-118
- 685 - The network has reset, 0197:2-118

Master Index

686 - The SSH / SFTP connection has been aborted, 0197:2-118
687 - The SFTP / SSH connection has been reset by the peer, 0197:2-118
688 - Failed to allocate network buffers, 0197:2-118
689 - The SSH / SFTP socket is already connected, 0197:2-118
690 - The SSH / SFTP socket is not connected, 0197:2-118
691 - The network channel is down, 0197:2-118
692 - The SSHD / SFTP server connection host is down, 0197:2-118
693 - SFTP client channel read failure, 0197:2-118
694 - SFTP client channel write failure, 0197:2-118
695 - SFTP client channel open failure, 0197:2-118
7000 Routesets, 0120:2-23
80% card stability threshold, 0188:2-25
80% full applique memory, 0188:5-13
80% of IS-NR LIMs, 0188:2-24, 0188:5-7, 0193:5-4
80% Threshold of Support, 0188:5-6, 0190:5-6, 0193:5-9, 0195:4-6
8000 Routesets, 0120:2-23
804-0176-01, 2970:3-8, 2970:3-45
830-0232-01, 0224:5-86
830-0398-xx, 0224:5-79, 0224:5-89, 0224:5-90, 0224:5-100, 2970:3-7, 2970:3-8, 2970:3-11, 2970:3-12
830-0404-xx, 0224:5-79, 0224:5-89, 0224:5-100, 2970:3-6
830-0528-xx, 2970:3-8, 2970:3-34, 2970:3-45, 2970:3-46, 2970:3-48, 2970:3-68
830-0531-04, 0224:5-107
830-0535-xx, 0224:5-107
830-0605-02, 0224:5-122, 0224:5-129
830-0609-01, 0224:5-64, 0224:5-73
830-0609-xx, 2970:3-8, 2970:3-12, 2970:3-29, 2970:3-35, 2970:3-39, 2970:3-40, 2970:3-50, 2970:3-51
830-0622-xx, 0224:5-119
830-0638-xx, 0224:5-86
830-0657-xx, 0224:6-21, 2970:3-8, 2970:3-29, 2970:3-33, 2970:3-41, 2970:3-44, 2970:3-50, 2970:3-54
830-0699-01, 0224:6-16
830-0699-xx, 2970:3-8, 2970:3-29, 2970:3-32, 2970:3-35, 2970:3-36, 2970:3-38, 2970:3-51, 2970:3-67
830-0708-xx, 2970:3-8, 2970:3-29, 2970:3-34, 2970:3-49, 2970:3-68
830-0709-xx, 2970:3-8, 2970:3-9, 2970:3-29, 2970:3-34, 2970:3-46, 2970:3-48, 2970:3-51, 2970:3-68
830-0710-xx, 2970:3-8, 2970:3-55
830-0772-xx, 0224:5-125
830-0788-xx, 0224:5-25
830-0873-07, 0224:5-104
830-0873-xx, 0224:5-83
830-0894-xx, 0224:5-125
830-0895-01, 0224:5-125, 0224:5-126
840-0016-02, 2970:3-19
840-0064-01, 0212:3-6
840-0089-01, 0212:3-6
850-0330-02 / 03 / 04, 0224:5-13
850-0330-06, 0224:5-11, 0224:5-13, 0224:5-64, 0224:5-73, 0224:5-86, 0224:5-104, 0224:5-105
850-0488-xx, 2970:3-36
870-0774-10, 0224:5-6, 0224:5-91
870-0774-15, 0224:2-5
870-1824-01, 0224:5-63, 0338:A-78
870-1965-01, 0224:5-6, 0224:5-91
870-1984-02, 0224:5-25
870-1984-03, 0224:5-25

870-1984-04, 0224:5-25
 870-1984-xx, 0224:5-25
 870-2062-02, 0224:5-133
 870-2197-01, 0224:5-25
 870-2198-XX, 0224:5-125
 870-2238-01, 0212:3-6
 870-2278-01, 0212:3-6
 870-2360-01, 0224:5-6, 0224:5-91
 870-2372-01, 0224:5-25
 870-2508-01, 0224:5-25
 870-2785-01, 2969:7-4
 890-0001-01, 0212:3-118, 0224:5-54
 890-1037-01, 0224:5-122, 0224:5-123, 0224:5-128
 890-1038-01, 0224:5-68
 890-1038-02, 0224:5-68
 890-1050-01, 2970:3-19
 890-1050-03, 2970:3-19
 8-Bit SLS Support (21.0), 0347:2-25
 8-Port Connector Box
 description, 0212:4-31, 0212:4-38, 0212:4-43

A

A bad dynamic port was specified in the SSH client on the EAGLE 5 SAS - Error code 658, 0197:2-112
 A bad message was received during the SSH authentication - Error code 640, 0197:2-110
 A bad option was specified in the SSH client on the EAGLE 5 SAS - Error code 645, 0197:2-111
 A bad packet length was received from the SSHD/SFTP server - Error code 672, 0197:2-115
 A bad packet size was detected by the SSH/SFTP client on the EAGLE 5 SAS - Error code 681, 0197:2-117
 A bad port was used in the SSH client on the EAGLE 5 SAS - Error code 649, 0197:2-112
 A complete point code must be entered, 0177:2-233
 A cryptographic attack was detected by the SSH client - Error code 673, 0197:2-115
 A destination address is required - Error code 40, 0197:2-119
 A mated linkset cannot have more than one link assigned, 0177:2-782
 A maximum of 8 PCs are allowed in a group, 0177:2-351
 A problem occurred while trying to access the GWS database, 0177:2-401
 A SEHSL feature key must be enabled to provision SEHSL, 0177:2-804
 A side, 0224:4-24
 A specific NIC must be specified in the range (0-3), 0177:2-245
 A specific SI must be specified in the range (0-15), 0177:2-405
 A specific SSN must be specified in the range (1-255,*), 0177:2-244
 A specified SI value must be 3 for SUA, 0177:2-797
 A timeout occurred while processing SCSI Debug Command, 0177:2-497
 A TTN-reserved service type name only if it matches SERV, 0177:2-486
 AAL, 0338:1-18
 AAL5, 0338:1-18
 AAL5CP, 0338:1-18
 AATM, 0338:1-18
 Able/Unable states, ELAP, 0178:2-10
 Abort Transaction, 0348:3-14
 command, 0348:3-14
 PDBI sample session, 0348:4-8

Master Index

- request message, 0348:3-15
- response message, 0348:3-15
- response return codes, 0348:3-15
- abort_txn command, 0348:3-14
- aborting
 - audit, 2339:5-24
 - bulk load, 2339:6-12
 - user-initiated resynchronization, 2339:4-11
- About FTRA window, 0197:2-13, 0197:2-104
- AC power
 - Power distribution unit, 2969:3-13
- access
 - configuration menu, 0178:5-13, 0183:5-14
- ACCESS can only be specified with TYPE=P486-DATA, 0177:2-304
- access code, 0193:2-2, 0193:2-7
- ACCESS parameter value is invalid for this card, 0177:2-760
- accessing
 - ELAP GUI interface, 2712:A-1
 - ELAP text interface, 2712:A-6
 - EPAP GUI interface, 0096:A-1
 - EPAP text interface, 0096:A-4
- Account Inactivity, 0178:3-108, 0183:3-138
- ACG, 0338:1-18
- ACG Node Overload Level Change, 0338:3-812
- ACK, 0348:1-10
- ACM, 0212:3-21, 0212:3-37, 0212:3-95, 0224:2-2, 0224:5-21, 0224:A-4, 0243:1-37, 0338:1-18
- ACM card replacement, 0338:A-39
- ACN, 0193:1-11
- Acronyms, 0188:1-10, 0190:1-10, 0195:1-10, 0348:1-10
- acronyms, 0100:1-14, 0120:1-14, 0142:1-14
 - document, 2970:1-18
- acronyms, list, 0193:1-11
- ACT, 0338:1-18
- act-alm-trns, 0145:5-2
- act-cdl, 0145:5-2
- act-dlk, 0145:5-4, 0145:6-2
- act-echo, 0145:5-5
- act-file-trns, 0145:5-6, 0190:5-17, 0193:5-24
- act-flash, 0145:5-9
- act-ftp-trns, 0145:5-12
- act-gpl, 0145:5-13, 0188:3-12, 0190:3-16, 0193:3-10, 0195:3-16
- ACTION and SRCLPSET must be specified together, 0177:2-514
- action commands, 0145:4-9
- ACTION must be specified as FORWARD, DUPLICATE, or DUPDISC, 0177:2-454
- ACTION or FORBID parameter shouldn't be specified, 0177:2-719
- Action requires either SAPC or MATELSN, not both, 0177:2-784
- Actions Taken When Hardware Determined to be Invalid, 0188:2-24, 0190:2-51
- Actions Taken When Hardware Invalid, 0193:5-6
- Actions Taken When System is in Unstable Loading Mode, 0188:5-7, 0190:5-7, 0193:5-9
- Actions Taken When the System is in an Unstable Loading Mode, 0195:4-7
- Activat, 0338:1-18
- Activate, 0145:5-5

Activate Echo to a Terminal

Miscellaneous Command Adjustments (26.0), 0347:4-119

Activate File Transfer, 0190:5-17, 0193:5-24

activate INP subsystem, 0193:4-43

activate optional features, 0188:3-3

activate signaling link, 0188:4-19, 0188:4-20, 0188:4-35, 0190:4-19, 0190:4-35, 0193:4-19, 0193:4-20, 0193:4-35

activate signaling link, act-slk

IPGWI, 0100:3-67, 0100:3-119, 0100:3-136, 0100:3-158, 0100:3-178, 0100:3-179, 0100:3-200, 0100:3-201, 0100:3-306, 0100:3-309, 0100:3-329, 0100:3-333

IPLIM, 0100:3-67, 0100:3-119, 0100:3-136

SS7IPGW, 0100:3-67, 0100:3-119, 0100:3-136, 0100:3-158, 0100:3-178, 0100:3-179, 0100:3-200, 0100:3-201, 0100:3-306, 0100:3-309, 0100:3-329, 0100:3-333, 0188:4-19, 0188:4-20, 0188:4-35, 0190:4-19, 0190:4-35, 0193:4-19, 0193:4-20, 0193:4-35

Activating

15 Minute Measurements Controlled Feature, 0142:A-26

Command Class Management Controlled Feature, 0142:A-3

Eagle OAM IP Security Enhancements Controlled Feature, 0142:A-12

IP User Interface Controlled Feature, 0142:A-3

LNP Feature on the EAGLE 5 SAS, 0288:2-123

LNP Feature Overview, 0288:2-4

LNP Short Message Service Feature, 0288:3-79

Network Security Enhancements Controlled Feature, 0142:A-3

activating

ITU National and International Spare Point Code Support feature, 0120:2-42, 0120:2-51

Activating Controlled Features procedure, 0197:2-3

Activating the ANSI-ITU-China SCCP Conversion Feature, 0099:A-36, 0099:A-43, 0099:A-44, 0099:A-45, 0099:A-46

Activating the Eagle OA&M IP Security Enhancements Controlled Feature procedure, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105

Activating the Enhanced GSM MAP Screening Feature, 0097:5-24, 0097:5-32, 0097:5-33, 0097:5-34, 0097:5-35, 0097:5-36

Activating the GSM MAP Screening Feature, 0097:5-24, 0097:5-32, 0097:5-33, 0097:5-34, 0097:5-35, 0097:5-36

Activating the IGTTLS Feature, 0099:A-3

Activating the LNP Short Message Service Feature, 0288:3-79

ACTIVE, 0178:3-7, 0183:3-7, 0183:3-9

active, 0190:5-2, 0195:4-2

active and standby EPAP servers, 0188:2-13

Active device state does not permit database change, 0177:2-613

active EPAP, 0188:5-2, 0190:2-35, 0190:2-42, 0190:3-15, 0190:5-2, 0193:2-4, 0193:3-9, 0195:3-14, 0195:4-2

active EPAP RTDB database, 0190:2-33

active EPAP RTDB database process, 0188:2-21

Active MASP

LNP forced simplex mode, 0338:3-103

Active MASP has become isolated, 0338:3-94

ACTIVE not available for type-enttype combination, 0177:2-115

Active OAM database is incoherent, 0177:2-419

Active OAM must be equipped with E586 hardware, 0177:2-554

Active TDM in unknown upgrade mode, 0177:2-524

Active/Standby

ELAP relation to LSMS connection, 0178:2-10

Master Index

- ELAP roles, 0178:2-5
- ELAP switchover, 0178:2-5
- active/standby EPAP servers, 0188:2-7
- Active/Stby GPL versions are not compatible, 0177:2-631
- act-lpo, 0145:5-23
- ACTNAME already exists in GWS Action Set Table, 0177:2-593
- ACTNAME and ACTID cannot both be specified, 0177:2-595
- ACTNAME specified must exist in the GWS Stop Action Set table, 0177:2-590
- act-oap-config, 0145:5-25
- act-oap-config parameters
 - performance impact, 2970:4-13
- act-slk, 0145:5-28, 0188:4-5, 0188:4-20, 0190:4-5, 0190:4-19, 0193:4-6, 0193:4-20
- act-upgrade, 0145:8-2
- act-user, 0145:5-30
- Add an IMSI, 0183:3-61, 0183:3-77, 0183:3-81
- Add Authorized PDBA Client IP, 0178:3-103, 0183:3-87, 0183:3-133
- Add button, 0197:2-1, 0197:2-18, 0197:2-20, 0197:2-24, 0197:2-62
 - Retrieve Tables, 0197:2-58
- add capability PC, 0188:4-8, 0190:4-10, 0193:4-10
- Add DN, 0183:3-65
- Add DN Block, 0183:3-69
- Add External NTP Server, 0178:5-25, 0183:5-28
- Add Group screen, 0178:3-97
- add mated application, 0188:4-18, 0190:4-18, 0193:4-18
- Add Network Entity, 0183:3-73
- add route for new DPC, 0188:4-17, 0190:4-17, 0193:4-17
- add signaling link, 0188:4-16, 0190:4-16, 0193:4-16
- Add UI Group, 0183:3-127
- Add User, 0183:3-114
- Add User screen, 0178:3-84
- ADD/DROP mode provisioned FORCE=YES required, 0177:2-547
- Adding
 - Command to the Selected Commands Box, 0197:2-62
 - Multiple Commands to the Selected Commands Box, 0197:2-63
 - Range of Commands to the Selected Commands Box, 0197:2-63
 - STP Configuration Record, 0197:2-20, 0197:2-50
- adding
 - card, 0120:3-5, 0120:C-31, 0142:4-98
 - cluster point code, 0120:2-142
 - destination point code, 0120:2-191
 - linkset, 0120:3-6, 0120:3-17
 - point code, 0120:3-5
 - remote loopback points, 0120:3-241, 0120:3-247
 - route, 0120:3-153, 0120:3-164, 0120:3-172, 0120:3-181
 - shelf, 0120:3-4, 0142:4-90
 - signaling link, 0120:3-5, 0120:3-6, 0120:3-130, 0120:C-34
 - user, 0142:4-21
- Adding a Blocked DPC Screen, 0098:8-8, 0119:5-44
- Adding a Blocked OPC Screen, 0098:11-8, 0119:5-94
- Adding a Cluster Point Code, 0119:2-2, 0119:2-12
- Adding a Concerned Signaling Point Code, 0099:2-68
- Adding a Destination Point Code, 0119:2-18

Adding a DSM, 0288:2-17
 Adding a Gateway Linkset, 0119:5-124
 Adding a Global Title Translation, 0099:3-17
 Adding a GLS Card, 0098:2-46
 Adding a GSM MAP Screening Entry, 0097:5-92, 0097:5-110, 0097:5-111, 0097:5-112, 0097:5-113, 0097:5-114
 Adding a GSM MAP Screening Operation Code, 0097:5-64, 0097:5-74, 0097:5-75, 0097:5-76, 0097:5-77
 Adding a GSM Subsystem Number Screening Entry, 0097:5-59, 0097:5-61
 Adding a GTT Selector, 0099:4-12
 Adding a GTT Set, 0099:4-3
 Adding a Mapped SS7 Message Translation Type, 0099:2-60
 Adding a Mated Application, 0119:4-2, 0119:6-2
 adding a point code to the self-identification of the EAGLE 5 SAS, 0120:2-81
 Adding a Route, 0119:3-36
 Adding a Screen Set, 0098:13-3
 Adding a TCP/IP Data Link, 0097:3-32
 Adding a TCP/IP Node, 0097:3-43
 Adding a Translation Type, 0099:3-3
 Adding ACG Manual Initiated Controls, 0288:4-20
 Adding an ACG Node Overload Control Level, 0288:4-13
 Adding an Allowed Affected Point Code Screen, 0098:3-4, 0119:5-3
 Adding an Allowed Called Party Address Screen, 0098:4-5, 0119:5-8
 Adding an Allowed Calling Party Address Screen, 0098:6-6, 0119:5-23
 Adding an Allowed DPC Screen, 0098:9-8, 0119:5-60
 Adding an Allowed ISUP Message Type Screen, 0098:15-9
 Adding an Allowed OPC Screen, 0098:12-8, 0119:5-109
 Adding an Allowed SIO Screen, 0098:10-9, 0119:5-76
 Adding an Allowed Translation Type Screen, 0098:5-4, 0119:5-17
 Adding an Application Socket, 0100:3-170
 Adding an IP Host, 0100:3-144
 Adding an SCCP Card, 0099:2-48, 0195:5-4, 0195:5-5
 Adding an SS7 Linkset, 0119:3-2
 Adding an SS7 Signaling Link, 0119:3-24
 Adding an STP Configuration Record
 FTRA 1.0, 0197:2-20, 0197:2-21, 0197:2-22, 0197:2-23, 0197:2-24
 FTRA 2.0, 0197:2-20, 0197:2-21, 0197:2-22, 0197:2-23, 0197:2-24
 Adding an X.25 Gateway Destination, 0097:2-25
 Adding an X.25 Linkset, 0097:2-40
 Adding an X.25 Route, 0097:2-97
 Adding an X.25 Signaling Link, 0097:2-76
 Adding Global Title Address Information, 0099:4-26, 0119:6-9
 Adding Security Parameters, 0178:5-7
 Adding Security Params to Java Policy File, 0183:5-6
 Additional Integrated Sentinel Support (Release 28.2), 0347:2-26
 ADDR parameter is invalid for this card, 0177:2-759
 address
 default router, 0178:5-18, 0183:5-20
 netmask, 0178:5-18, 0183:5-20
 Address (MPCx) of mate subsystem must be a full PC, 0177:2-372
 Address (PCx) of primary subsystem must be a full PC, 0177:2-372
 address mapping
 X.25/SS7 Gateway Feature (Eagle 20.0), 0347:5-181

Master Index

- addresses for network, 0188:2-15
- addresses, IP
 - see IP addresses
- ADDTBLCNV and DELTBLCNV cannot be specified together, 0177:2-836
- ADJ DPC, 0338:1-18
- ADJ required if MPC / MSSN is given or MULT=DOM or SHR, 0177:2-166
- Adjacent Destination Point Code, 0338:1-18
- Adjacent even numbered port has signaling link assigned, 0177:2-546
- Adjacent Point Code, 0338:1-18
- ADL, 0188:1-10, 0188:5-6, 0190:1-10, 0190:5-6, 0193:1-11, 0195:1-10, 0195:4-5
- ADMHIPRI - LNP Administration Priority, 0288:3-52
- administer G-Port feature, 0190:3-1
- administering EIR features, 0195:3-1
- administering INP features, 0193:3-1
- administering point codes
 - ANSI/ITU MTP Gateway (20.0), 0347:2-38
- Administrable SLTMs (20.0), 0347:2-28
- administration
 - Enhanced Bulk Download (25.0), 0347:2-147
 - EOAP, 0025:8-12
 - High Speed Master Timing (26.0), 0347:3-63
 - Nested Cluster Routing (EAGLE 26.0), 0347:4-161
 - Temporary Alarm Inhibiting and Offline Functions (EAGLE 25.0), 0347:5-124
- administration of User IDs and passwords, 0145:4-17
- Administrative Architecture, 0188:2-10, 0190:2-36
- administrative updates, 0188:2-25
- admonishments, 0193:1-9
- admonishments, documentation, 0178:1-9, 0183:1-9, 0348:1-8
- ADU, 0193:1-11
- Advanced Intelligent Network, 0338:1-18
- Advantages, 0347:3-13
- advantages
 - G-Flex C7 Relay (26.3), 0347:3-13
- affected commands
 - Flexible Point Code Formatting (26.0), 0347:3-6
 - SEAS Enhancements (EAGLE 26.0), 0347:5-63
- Aging, 0178:3-110, 0183:3-140
- AI, 0338:1-18
- AIN, 0288:3-22
- AINF Applique (21.0), 0347:2-29
- AINTVL, 0288:4-3, 0288:4-5, 0288:4-20, 0288:4-22, 0288:4-23, 0288:4-25, 0288:4-26, 0288:4-27, 0288:4-28, 0288:4-29
- AIPADDR parameter
 - chg-oap-config, 2970:4-11
- air filter
 - part number, 0095:B-3, 2969:B-3
 - replace, 0095:7-18, 2969:7-18
- air filter, changing, 0338:2-31, 0338:2-33
- Air filters, 2969:7-4
- air management card, 0224:5-63, 0338:A-78
- air supply grille, removing, 0338:2-34
- airflow indicator arrows, 0338:2-34

- Alarm, 0338:1-18
- alarm board (FAP), 0338:2-6
- alarm cable installation, 0224:5-86
- alarm card, breaker panel
 - FRU, 0096:5-2
 - replacement procedure, 0096:5-2
- alarm card, MPS Server
 - description, 0025:6-12, 0212:4-28
- Alarm cleared by deleting card, 0338:3-513
- Alarm cleared by deleting route, 0338:3-515
- Alarm cleared by deleting SLK, 0338:3-514
- Alarm cleared for GPL, 0338:3-91
- Alarm cleared running non-activated GPL, 0338:3-93
- Alarm Clearing Procedures, 0338:3-45
- alarm condition, 0193:5-3
- alarm conditions, 0188:5-2, 0190:5-2, 0195:4-2
- alarm conditions, FAP, 0338:2-7
- alarm connectors, 0212:3-26
- alarm data strings
 - contents, 0178:4-3, 0183:4-16
 - list using rept-stat-mps command, 0178:4-11
- Alarm Enhancements (26.0), 0347:2-29
- Alarm in Fuse panel, 0338:3-159
- Alarm LED, 0183:3-7
- alarm LED, 0096:3-11, 2712:3-8
- Alarm LEDs, 0178:3-8
- alarm LEDs, 0096:3-11, 2712:3-8
- Alarm LEDs on the Fuse and Alarm Panel (FAP), 0338:3-6
- alarm levels, 0145:4-3
- alarm related banner messages, 0183:3-146
- alarm system functionality
 - Temporary Alarm Inhibiting and Offline Functions (EAGLE 25.0), 0347:5-120
- Alarm thresholds - LNP telephone number - changing, 0288:3-86
- Alarm Thresholds - SCCP - Changing, 0099:2-200
- alarm totals, 0190:3-15, 0193:3-8, 0195:3-13
- Alarm View Window, 0178:3-8
- Alarm View window, 0183:3-8
- Alarms, 0188:5-11, 0190:5-11, 0195:4-12
 - Card, 0338:F-3
 - Clock (Holdover Clock), 0338:F-6
 - Clock System, 0338:F-6
 - Customer Defined Trouble (CDT), 0338:F-6
 - DCM, 0338:F-7
 - DLK, 0338:F-8
 - DPC System, 0338:F-9
 - DSM, 0338:F-10
 - E1 Port, 0338:F-10
 - EIR, 0338:F-11
 - EMAP, 0338:F-11
 - EMAP (NDC), 0338:F-11
 - EROUTE, 0338:F-12
 - Fuse, 0338:F-12

Master Index

- GLS, 0338:F-13
- GPL, 0338:F-13
- HS Clock System, 0338:F-14
- IMT Bus, 0338:F-15
- IMT System, 0338:F-15
- INP System, 0338:F-15
- IP TPS System, 0338:F-16
- IP7, 0338:F-16
- Linkset, 0338:F-16
- LNP System, 0338:F-17
- LSMS Connection, 0338:F-17
- LSMS System, 0338:F-18
- MCPM, 0338:F-18
- MEAS System, 0338:F-18
- MPS (ELAP/EPAP), 0338:F-19
- MPS Alarm Support, 0338:F-19
- NDC System, 0338:F-20
- routers, 0243:A-17
- SCCP System, 0338:F-20
- SEAS OAP, 0338:F-20
- SEAS System, 0338:F-21
- SEAS X25, 0338:F-21
- Security Log, 0338:F-22
- Security System, 0338:F-22
- SLK, 0338:F-22
- STPLAN, 0338:F-25
- System, 0338:F-25
- System GPL, 0338:F-26
- T1, 0338:F-26
- TAS, 0243:A-20
- Terminal, 0338:F-26
- X-LIST, 0338:F-27
- alarms, 0193:5-14
 - 4000 Routesets (23.0), 0347:2-7
 - 48 Million Numbers (27.0), 0347:2-15
 - alarm priorities, 0178:4-3, 0183:4-2
 - categories, 0178:4-14, 0183:4-16
 - clearing alarm, 0178:4-15, 0183:4-18
 - DSM/ ELAP in rept-stat-trbl report, 0178:4-12
 - DSM-ELAP Link status, 0178:4-16
 - DSM-EPAP Link status, 0183:4-18
 - Eagle Application Support for E1 (26.3), 0347:2-108
 - ELAP application, 0178:4-14
 - ELAP-DSM UAMs, 0178:4-16
 - Enhanced Bulk Download (25.0), 0347:2-145
 - Enhanced GPL Management (25.0), 0347:2-154
 - EOAP, 2970:4-20
 - EPAP application, 0183:4-16
 - EPAP UAMs, 0183:4-18
 - see also UAMs, EPAP
 - Garrett Magnum Hubs, 0243:A-16
 - G-Flex, G-Port, INP, and DSM/ EPAP in rept-stat-trbl report, 0183:4-13

Group Ticket Voucher (23.0), 0347:3-36
 GSM MAP Screening (26.1), 0347:3-44
 IP Connection Available/ Unavailable, 0178:4-16, 0183:4-18
 MPS Available alarm, 0178:4-15, 0183:4-17
 MPS platform, 0178:4-14, 0183:4-16
 MPS platform and ELAP application, 0178:4-15
 MPS Server LEDs, 0212:4-32
 MTP Restart (EAGLE 21.0), 0347:4-135
 multiple alarm conditions, 0178:4-4, 0183:4-3
 rept-stat-mps command to list data strings, 0178:4-11
 RTDB Audit, 0178:4-16, 0183:4-19
 Telect Breaker Panel, 0243:A-14
 totals in Hourly Maintenance Report, 0183:4-15
 totals in rept-stat-alm report, 0178:4-4, 0178:4-13, 0183:4-3, 0183:4-13
 Variable Length GTT (Eagle 26.1), 0347:5-172
 Weighted SCP Load Balancing (Eagle 27.2), 0347:5-176
 Alarms appearing on the system terminal screen, 0338:3-8
 Alarms on Application Cards, 0338:3-8
 Alarms Reference and User's Manual, 0212:1-18, 0243:1-18
 alarms, critical, 0338:2-7
 alarms, FAP, 0338:2-8
 alarms, fuse, 0338:2-8
 alarms, major, 0338:2-7
 alarms, minor, 0338:2-7
 ALIAS, 0288:3-22, 0288:3-23, 0288:3-24, 0288:3-25, 0288:3-29, 0288:3-30, 0288:3-31, 0288:3-32, 0288:3-33,
 0288:3-36, 0288:3-37, 0288:3-59, 0288:3-62
 Alias already in use, 0177:2-188
 Alias defined as a destination point code, 0177:2-127
 Alias defined as translation type, 0177:2-189
 Alias DPCs cannot be a member of a Network or Cluster, 0177:2-378
 Alias is not assigned to SERV, 0177:2-479
 Alias not assigned to translation name, 0177:2-189
 Alias not assigned to translation type, 0177:2-190
 Alias not defined, 0177:2-128
 Alias PC table is full, 0177:2-812
 Alias PCs are not valid for cluster destinations, 0177:2-367
 Alias PCs exceed Max allowed for Feature Quantity, 0177:2-803
 Alias type matches DPC type, 0177:2-129
 Aligning Signaling Links in a fully Restarting Node
 MTP Restart (EAGLE 21.0), 0347:4-134
 ALL cannot be specified with a subsystem, 0177:2-187
 All cards on shelf must be unequipped, 0177:2-77
 All clocks have failed, 0338:3-202
 All entered point code elements must be C if any are C, 0177:2-198
 All high speed clocks have failed, 0338:3-289
 All IMT System level alarms cleared, 0338:3-187
 All links in linkset must have same IPLIML2 setting, 0177:2-492
 All links of LSN must use same error correction method, 0177:2-38
 All new PC parms must be null if NI, ZONE, MSA or NPC = C, 0177:2-220
 All OAP terminals are removed, 0338:3-464
 ALL only qualifier allowed with given card type, 0177:2-79
 All SEAS UAL sessions unavailable, 0338:3-438

Master Index

All signaling links serviced by the E1 must be deactivated, 0177:2-726
All signaling links serviced by the T1 must be deactivated, 0177:2-319
All signaling links serviced by this E1 / T1 must be deleted, 0177:2-730
All STC Networks Available, 0338:3-577
All SUBNETID table entries must be of length SUBNETIDLEN, 0177:2-825
All VENDID table entries must be of length VENDIDLEN, 0177:2-817
ALL=YES cannot be specified with a point code, 0177:2-183
ALL=YES must be specified to delete all SSNs for a PC, 0177:2-174
ALL=YES must be specified to delete the entire group, 0177:2-173
alloc-mem, 0145:5-31
Allow a Mated Application to Work as Primary-Secondary and Secondary-Primary (22.0), 0347:2-29
allow DSM card, 0188:4-39, 0190:4-39, 0193:4-44
allow inhibited card, 0188:4-19, 0188:4-25, 0188:4-34, 0190:4-19, 0190:4-25, 0190:4-34, 0193:4-19,
0193:4-25, 0193:4-34
Allow rejected
terminal is not equipped, 0177:2-182
Allowed Affected Destination Field, 0098:2-2
Allowed Affected Destination Field Screen (22.0), 0347:2-32
command, 0347:2-33
Allowed Affected Point Code, 0098:2-2
Allowed Called Party Address, 0098:2-2
Allowed Calling Party Address, 0098:2-2
Allowed CDPA Screen on SCCP Management Format ID (22.0), 0347:2-35
Allowed Destination Point Code, 0098:2-2
Allowed ISUP Message Type, 0098:2-2
Allowed ISUP Message Type Screen Configuration, 0098:15-1
Allowed Originating Point Code, 0098:2-2
Allowed Signaling Information Octet, 0098:2-2
Allowed Translation Type, 0098:2-2
allowing
DSM, 2339:8-3
mated application subsystem, 2339:8-4
ALM, 0338:1-18
ALPHA+NUM+PUNC must not be greater than 12, 0177:2-330
Already in nodal isolation, 0177:2-424
Already logged on, 0177:2-11
Alternate bus must be IS-NR, 0177:2-441
Alternate Command Keywords (20.0), 0347:2-35
alternate point code, 0120:2-2
alw, 0100:3-191
alw-card, 0188:3-12, 0188:4-5, 0188:4-6, 0188:4-7, 0188:4-19, 0188:4-25, 0188:4-34, 0188:5-7, 0188:5-13,
0190:3-15, 0190:4-5, 0190:4-6, 0190:4-7, 0190:4-19, 0190:4-25, 0190:4-34, 0190:5-7, 0190:5-13, 0193:3-9,
0193:4-5, 0193:4-6, 0193:4-7, 0193:4-19, 0193:4-25, 0193:4-34, 0193:5-6, 0193:5-10, 0195:3-14, 0195:4-7
alw-card command, 0197:2-45
alw-imt, 0145:5-36
alw-map-ss, 0145:5-37, 0193:4-43, 0195:3-15
alw-map-ss command, 2339:8-4
alw-slk, 0145:5-38
alw-trm, 0145:5-39
AMA, 0338:1-18
AMATYPE, 0288:3-55, 0288:3-57
AMAFEATID, 0288:3-55, 0288:3-57

AMASLPID, 0288:3-55, 0288:3-57
 AMD K-6 processor, 0188:2-10, 0190:2-36
 AMD-K6 main board, 0190:2-50
 Amem single bit error report, 0338:3-714
 American National Standards Institut, 0338:1-18
 American National Standards Institute, 0188:1-1
 American Wire Gage, 0224:4-10
 amount of applique memory present, 0188:5-3
 An ACTNAME must be specified, 0177:2-594
 An invalid option or argument was specified in the SSH client on the EAGLE 5 SAS - Error code 660, 0197:2-114
 An MIC of TYPE=ALL already exists, 0177:2-449
 An MIC with the same service and digits already exists, 0177:2-449
 An unexpected packet type was received from the SFTP/SSHD server - Error code 671, 0197:2-115
 An unsupported cipher type was used in the SSH client on the EAGLE 5 SAS - Error code 647, 0197:2-111
 An unsupported escape character was used in the SSH client on the EAGLE 5 SAS - Error code 646, 0197:2-111
 An unsupported MAC type was used in the SSH client on the EAGLE 5 SAS - Error code 648, 0197:2-112
 ANAME parameter
 chg-oap-config, 2970:4-11
 anchor and frame, 0224:3-15
 anchor assembly
 for raised floor with support channel, 0095:4-14, 2969:4-14
 for raised floor with support channel and spring nut, 0095:4-17, 2969:4-17
 raised floor over concrete, 0095:4-10, 2969:4-10
 slab floor, 0095:4-7, 2969:4-7
 anchor bolt, 0224:3-22
 anchor frame
 for raised floor with support channel, 0095:4-13, 2969:4-13
 for raised floor with support channel and spring nut, 0095:4-16, 2969:4-16
 to concrete under raised floor, 0095:4-10, 2969:4-10
 to slab floor, 0095:4-6, 2969:4-6
 anchor holes, in raised floor, 0095:4-5, 2969:4-5
 AND parameter must be 6 or 10, 0177:2-452
 ANMASK parameter
 chg-oap-config, 2970:4-11
 ANSI, 0188:1-1, 0338:1-18, 0348:1-10
 ANSI G-Flex Support at 1700 TPS per DCM (Release 30.3), 0347:2-36
 ANSI PC is identical to ANSI CPC, 0177:2-67
 ANSI PC parameters are invalid for ITU cards, 0177:2-519
 ANSI site id not defined, 0177:2-314
 ANSI/ITU MTP Gateway (20.0), 0347:2-36
 administering point codes, 0347:2-38
 changed commands, 0347:2-41
 level 3 MSU discrimination, 0347:2-36
 local link congestion, 0347:2-38
 MSU routing, 0347:2-37
 remote link congestion, 0347:2-39
 ANSI/ITU point code type mismatch, 0177:2-670
 ANSI/ITU SCCP and TCAP Conversion (22.2), 0347:2-40

Master Index

ANSI/ITU SCCP and TCAP Conversion (24.0), 0347:2-41
changed command, 0347:2-42

ANSI-ITU-China SCCP Conversion, 0099:1-2, 0099:2-3, 0099:2-6, 0099:2-7, 0099:2-16, 0099:2-17, 0099:2-30, 0099:2-33, 0099:2-40, 0099:2-43, 0099:2-44, 0099:2-47, 0099:2-48, 0099:2-69, 0099:2-71, 0099:2-82, 0099:2-86, 0099:2-92, 0099:2-118, 0099:2-124, 0099:2-162, 0099:2-163, 0099:2-171, 0099:2-172, 0099:2-179, 0099:2-181, 0099:2-193, 0099:2-194, 0099:3-2, 0099:3-21, 0099:3-23, 0099:3-28, 0099:3-32, 0099:3-53, 0099:3-54, 0099:3-55, 0099:3-58, 0099:3-62, 0099:4-2, 0099:4-27, 0099:4-30, 0099:4-34, 0099:4-35, 0099:4-38, 0099:4-39, 0099:4-54, 0099:4-57, 0099:4-60, 0099:4-63, 0099:A-36, 0099:A-37, 0099:A-38, 0099:A-39, 0099:A-41, 0099:A-42
options
changing, 0099:2-193, 0099:2-195

ANSI-ITU-China SCCP Conversion Feature
Activating, 0099:A-36, 0099:A-43, 0099:A-44, 0099:A-45, 0099:A-46

AP, 0338:1-18

APC, 0338:1-18

APC cannot be of a different domain than previous, 0177:2-253

APC cannot be ref. by an X.25 route with LC2NM=YES, 0177:2-279

APC not defined as destination point code, 0177:2-129

APC/SAPC type and group code must match DPC, 0177:2-582

APC/SAPC with specified group code already exists for linkset, 0177:2-749

APCNTYPE parameter is only valid for ITUN/ITUN24 link sets, 0177:2-803

APDU, 0193:1-11

API, 0348:1-10

Appendix A, LEDs, 0224:1-11, 0243:1-12

Appendix B, Connectors, 0224:1-11, 0243:1-12

Appendix C, Cables, 0224:1-11, 0243:1-12

Appendix D, Power Cords to Peripherals, 0224:1-11, 0243:1-12

APPL, 0195:5-16, 0195:5-23, 0195:5-24, 0195:5-29, 0195:5-30, 0195:5-31, 0195:5-33, 0195:5-35, 0195:5-37, 0195:5-38, 0195:5-40, 0195:5-51, 0288:3-38, 0288:3-39, 0288:3-42, 0288:3-43, 0288:3-44, 0288:3-45, 0288:3-46, 0288:3-49, 0288:3-50, 0288:3-51, 0338:1-18, 0347:4-88

appl, 0097:2-11, 0100:3-4

APPL is invalid for report or entity, 0177:2-307

APPL is invalid for specified PERIOD, 0177:2-308

APPL not valid for command, 0177:2-609

APPL or LOC parameter must be specified, 0177:2-308

APPL parameter must be specified with CONVERTNET action, 0177:2-611

APPL parameter valid only with CONVERTNET action, 0177:2-615

APPL=ALL can only be selected when SERIAL=YES is specified, 0177:2-631

appl=vsccp, 0188:4-15, 0188:4-22, 0188:4-30, 0190:4-16, 0190:4-22, 0190:4-30, 0193:4-16, 0193:4-22, 0193:4-30

APPL=VSCCP parameter, 0188:3-12

Application, 0338:1-18

application alarms, ELAP, 0178:4-14

application alarms, EPAP, 0183:4-16

Application already assigned, 0177:2-477

Application Communication Module, 0025:3-9, 0212:2-12, 0224:5-21

Application Communication Module (ACM), 0212:3-19

application communication module (ACM), 0212:3-93

Application Communications Modul, 0338:1-18

Application Communications Module (ACM) measurements, 0338:4-48

Application Communications Modules (ACMs), 0212:3-20

application data loader, 0188:5-6, 0190:5-6, 0195:4-5

- Application Interface (AINF), 0212:3-68
- Application Processor, 0338:1-18
- Application Processor (AP), 0212:3-62
- Application self recovery, 0338:1-15
- Application Server, 0338:1-18
- Application Server Process, 0338:1-18
- Application Service Module, 0025:3-10, 0212:2-14
- Application Service Module (ASM), 0212:3-87
- application service module (ASM), 0212:3-18
- Application Service Module (ASM) measurements, 0338:4-47
- Application Services Module, 0338:1-18
- Application Sockets on Port B Not Allowed, 0177:2-733
- Application Subsystem, 0025:3-7, 0212:2-8
- Application Trouble Handler, 0338:1-18
- Application type not in LNP database, 0177:2-478
- application, detecting problems, 0096:3-11, 2712:3-8
- Application, FTRA
 - exiting, 0197:2-4, 0197:2-14
 - starting, 0197:2-4
 - using, 0197:2-4
- Applications, 0025:3-20, 0100:2-3, 0100:2-4
- applications
 - Types of Routing Strategies Available, 0347:4-174
- Application-Specific Integrated Circuits, 0212:4-26
- applique, 0190:2-50
- applique board, 0188:2-10, 0190:2-36
- applique hardware configuration, 0188:5-5
- applique memory, 0188:5-13
- applique memory present, 0188:5-3
- appliques
 - 4-port DS0 monitor, 0212:B-6
 - 4-port DSCS monitor, 0212:B-8
 - 4-port E1 monitor, 0212:B-4
 - 4-port T1 monitor, 0212:B-2
 - 4-port V.35 monitor, 0212:B-7
- architecture view, 0183:3-3
- architecture, MPS Server I/O, 0212:4-28
- architecture, PDBI/ PDBA/ EPAP system, 0348:2-6
- Area Code, 0288:4-2
- area code
 - LNP—Automatic Call Gapping (Release 22.0), 0347:4-57
- Argument definition error, bad argument type, 0177:2-19
- Argument frame overflow, 0177:2-3
- ARM register must be specified, 0177:2-756
- AROUTER parameter
 - chg-oap-config, 2970:4-11
- arp, 0145:9-2
- arrow key operations, terminal, 0145:4-12
- AS, 0338:1-18
- AS Available, 0338:3-352
- AS Restricted, 0338:3-353
- AS table is full, 0177:2-745

Master Index

AS Unavailable, 0338:3-351
AS Unrestricted, 0338:3-354
AS/socket cannot be deleted while assigned to a routing key, 0177:2-735
ASCII, 0348:1-10
ASi, 0338:1-18
ASi (Application Specific Interface), 0338:1-18
ASi 4000 SCP, 0212:2-24, 0212:4-3
ASi 4000 Service Control Point, 0212:1-8
ASL8 is only valid for ANSI link sets, 0177:2-364
aslog, 0145:9-5
ASM, 0224:2-2, 0224:A-5, 0338:1-18, 0348:1-10
ASM / TSM family, 0190:2-36
ASM with GLS, 0338:1-18
ASM with SCCP, 0338:1-18
ASM, TDM, and MCPM upgrade procedures, 0224:5-28
ASM/TSM-GLS card replacement, 0224:5-32
ASM/TSM-SCCP card replacement, 0224:5-28
ASM-GLS, 0338:1-18
ASM-SCCP, 0338:1-18
ASM-SCCP card replacement, 0338:A-36
ASP, 0338:1-18
asplog, 0145:9-6
assign individual subscribers to HLRs, 0188:2-2
assign routes and linksets, 0188:4-8, 0190:4-10, 0193:4-10
assign service selectors, 0193:4-42
Assigned SLKs must be deleted before apcntype can be changed, 0177:2-832
Associated State for Maintenance, 0338:1-18
Association connection parameters must be unique, 0177:2-739
Association in maximum allowed application servers, 0177:2-829
Association is still assigned to AS, 0177:2-746
Association name already exists, 0177:2-740
Association name not found, 0177:2-742
assocrtt, 0145:9-11
Assumptions/Limitations, 0188:2-21
assumptions/limitations
 Enhanced GTT (26.0), 0347:2-157
asynchronous maintenance modem
 Embedded OAP (24.0), 0347:2-138
AST, 0338:1-18
AST possible values, 0145:A-3
Asynchronous DSM Report, 0348:4-14
Asynchronous IO is not supported on IPSM, SSH client error - Error code 664, 0197:2-114
asynchronous replication, 0348:2-7, 0348:3-48
Asynchronous Transfer Mode, 0338:1-18
At least one MCP card must be IS-NR, 0177:2-603
At least one MCPM card must be configured in system, 0177:2-305
At least one Non-Key parm that is to be changed is required, 0177:2-762
At least one of TIMER, PARM, SRCSET must be entered, 0177:2-625
At least one optional parameter is required, 0177:2-44
At least one other optional parameter is required, 0177:2-787
At least one parameter must be changed, 0177:2-33
At least one parameter must be changed(NSNP, NSNAI, NSERV), 0177:2-555

At least TTA, TTI must be specified for a direction of BOTH, 0177:2-722
 At least two ports must have security admin authority, 0177:2-337
 At most two linksets can be assigned same cost, 0177:2-140
 ATH, 0338:1-18
 ATM, 0224:5-81, 0224:5-82, 0224:A-6, 0243:A-3, 0338:1-18, 0338:A-22
 ATM Adaptation Layer, 0338:1-18
 ATM Adaptation Layer Type 5, 0338:1-18
 ATM Applique, 0338:1-18
 ATM high speed signaling link parameter set
 changing, 0120:C-50
 ATM LIM, 0224:5-81
 ATMANSI, 0097:6-7, 0097:6-21
 ATMITU, 0097:6-7, 0097:6-21
 atomic command, 0348:2-12
 attach fan assembly to frame rail, 0338:5-96, 0338:A-87, 2970:6-45
 Attributes required, 0177:2-654
 AuC, 0188:1-10, 0188:2-1, 0190:1-10, 0193:1-11, 0195:1-10
 AUD, 0288:3-52, 0288:3-55, 0288:3-57
 aud-data, 0145:5-40
 Audible Alarms, 0338:3-4
 audit
 aborting, 2339:5-24
 log file, 2339:5-37
 managing, 2339:5-13
 overview, 2339:5-2
 restrictions, 2339:5-9
 stages, 2339:5-11, 2339:5-12
 audit and reconcile
 from the LSMS GUI, 2339:5-13
 options, 2339:5-9
 stages, 2339:5-11, 2339:5-12
 Audit of LNP backup database completed, 0338:3-755
 Audit of LNP database completed, 0338:3-814
 Audit Requirements, 0188:2-25, 0190:2-52
 Audit, RTDB
 alarms, 0178:4-16, 0183:4-19
 auditing OAP database
 Support LSMS Disaster Recovery (EAGLE 23.1), 0347:5-113
 Auditing the Eagle via High-Speed Audit
 Support for LSMS Audit Enhancements (EAGLE 26.1), 0347:5-100
 auditing the OAP database
 Eagle Initiated OAP User Interface (24.0), 0347:2-119
 Aurora serial card driver, 0338:5-23, 2970:7-22
 Authentication Center, 0188:2-1
 Authority Violation, 0177:2-2
 Authorized IP List menu, 0183:3-87
 Authorized IP menu, 0178:3-103, 0178:3-104, 0178:3-105, 0178:3-106, 0183:3-133, 0183:3-134,
 0183:3-135, 0183:3-136
 Authorized IPs, 0178:3-103, 0183:3-133
 auto-configuration, 0178:5-26, 0183:5-34
 AUTOEXEC.BAT, 0197:2-7
 Automatic Call Gapping, 0025:4-5, 0288:4-1, 0288:4-2, 0338:1-18, 0347:4-57

Master Index

Automatic Destination Field Screening, 0098:13-2
Automatic Message Accounting, 0338:1-18
automatic resynchronization, 2339:2-5, 2339:2-8, 2339:4-2
availability, 0096:2-22, 2712:2-19
Availability reports, 0338:4-42
Awaiting LSMS bulk download, 0338:3-979
AWG, 0224:4-10
AXi 1000, 0212:4-19
AXi 2000, 0212:4-19
AXi Application Frame 1, 0212:4-14
AXi Network Frame, 0212:4-14
AXi Systems, 0212:1-10

B

B side, 0224:4-24
Back-end check, 0183:3-11
back-end check, 0178:3-11
background audit, 0188:2-25
backing up changes, chg-db, 2970:4-26, 2970:4-37
backplane board (FAP), 0338:2-6
backplane monitor, 0338:5-21, 2970:7-20
backplane, control shelf, 0224:B-19
backplane, extension shelf, 0224:B-25, 0243:B-9
backpower protection, 0338:2-9
backup
 Database Management Command Functions (20.0), 0347:2-84
backup and restore operations, 0193:2-6
backup DSM network, 0178:2-7, 0183:2-9, 0190:2-38
Backup File System, 0183:3-47
Backup IP Address - FTRA 2.0, 0197:2-22
Backup IP Address - FTRA 2.0 or greater, 0197:2-18
Backup IP Address Field - FTRA 2.0 or greater, 0197:2-18, 0197:2-22
Backup LNP database corrupted, 0338:3-534
Backup LNP database has been corrected, 0338:3-544
Backup LNP database is inconsistent, 0338:3-540
Backup menu, 0183:3-95
backup of file system, 0183:3-47
backup procedures, 0142:2-32
 backup database on fixed disk, 0142:2-32
 backup database to removable cartridge, 0142:2-35
Backup Provisioning Network Interface (Release 29.0), 0347:2-43
Backup RTDB, 0178:3-38
Backup the PDB, 0183:3-95
Backup the RTDB, 0183:3-29
Bad Arguments
 response message, 0348:3-6
 return code, 0348:3-6
Bad forwarding ports were specified in the SSH client on the EAGLE 5 SAS - Error code 657, 0197:2-112
Bad forwarding was used in the SSH client on the EAGLE 5 SAS - Error code 656, 0197:2-112
banner format, output, 0145:4-15

banner header section, 0178:3-2, 0183:3-2
 Banner Information Messages, 0178:3-115
 banner section, 0178:3-6, 0183:3-6
 banner, displaying error text, 0096:3-13, 2712:3-10
 Batch Mode, 0178:3-60
 BC should be less than 2000, 0177:2-313
 bdn, 0348:3-20, 0348:3-25, 0348:3-29, 0348:3-31
 Begin Transaction, 0348:3-11
 command, 0348:3-11
 request message, 0348:3-11
 response message, 0348:3-13
 response return codes, 0348:3-13
 begin_txn command, 0348:3-11
 BEI must be YES if APC domain is X.25, 0177:2-252
 bid, 0348:3-46
 Billing Functions, 0025:4-8
 bimsi, 0348:3-34
 BIPADDR parameter
 chg-oap-config, 2970:4-11
 bit rotation
 ITU SLS enhancement, 0120:3-30
 BITS, 0224:5-85, 0224:5-88, 0224:5-104, 0224:5-115
 BITS cable installation, 0224:5-88, 0224:5-104
 BITS clock connectors, 0224:B-9
 BITS connectors, 0212:3-27
 black and white flag, 0224:4-24
 Black List Processing, 0195:2-7
 blk-slk, 0145:5-45
 BLM Applied to LSMS BLM-Based Operations - Removing, 0288:2-26
 BLM must be provisioned and IS-NR for an upload, 0177:2-641
 BLM / DCM card must be provisioned and IS-NR for bulk download, 0177:2-640
 BLM / DCM LNP database must be coherent to do a bulk download, 0177:2-640
 block instance table, 0348:2-5
 Blocked Destination Point Code, 0098:2-2
 Blocked Originating Point Code, 0098:2-2
 blown fuse, 0338:2-8
 blue flag, 0224:4-24
 BNAME parameter
 chg-oap-config, 2970:4-11
 BNMASK parameter
 chg-oap-config, 2970:4-11
 boot disk, 0338:5-12, 2970:7-10
 BOOT=NO not supported for specified gpl, 0177:2-832
 Both DR and DA parameters cannot be entered, 0177:2-79
 Both LIMIT and INTRVL must be specified for UIM threshold., 0177:2-611
 Both LOC and LINK must be specified, 0177:2-118
 Both NP and NAI must be specified if either is present, 0177:2-749
 Both NPV and NAIV must be either * or numbers, 0177:2-738
 Both OAM cards must be of the same type to update database, 0177:2-456
 Both OAM cards must be of type GPSM-II to enable TSCSYNC, 0177:2-332
 Both WRNLN and WRNTX must be specified, 0177:2-335
 Box

Master Index

- Command List, 0197:2-56, 0197:2-58, 0197:2-60, 0197:2-64, 0197:2-65
- Secure Connection - FTTRA 2.0 or greater, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-45, 0197:2-50, 0197:2-51
- Selected Commands, 0197:2-56, 0197:2-58, 0197:2-62, 0197:2-64, 0197:2-65, 0197:2-66
 - Adding a Command, 0197:2-62
 - Adding a Range of Commands, 0197:2-63
 - Adding Multiple Commands, 0197:2-63
 - Command Removed, 0197:2-65
 - Command Selected to be Removed, 0197:2-64
- Stop on error
 - Update Tables, 0197:2-83
- Stop on error, Update Tables window, 0197:2-80, 0197:2-83, 0197:2-92, 0197:2-93, 0197:2-94
- Use STP and FTP UserNames, Passwords for all STPs, 0197:2-19, 0197:2-20, 0197:2-38, 0197:2-39, 0197:2-40
- box, 8-Port Connector
 - see 8-Port Connector Box
- BPDCM GPL, 0097:6-24
- BPS must be 1544000 for LIMATM cards, 0177:2-510
- BPS must be 4800,9600,19200,56000,64000,1544000 or 2048000, 0177:2-50
- BPS must be 56000 for all ports on Multi Port LIM, 0177:2-422
- BPS must be 56000 or 64000, 0177:2-36, 0177:2-37
- brace bolts, 0224:3-6
- brackets, 0224:5-69
- Breaker, 0243:A-14
- breaker panel
 - alarm card FRU, 0096:5-2
 - alarm card replacement procedure, 0096:5-2
 - FRU, 0096:5-2, 2712:5-2
 - replacement procedure, 0096:5-5, 2712:5-5
- Breaker panels, 0212:4-52
- Bridge Amplifier, 0212:B-9
- broadcast data, 0190:2-38
- broadcast signaling point code group, 0193:4-37
- broadcast transfer messages
 - network routing, 0120:2-177
- Broken pipe - Error code 32, 0197:2-121
- BROUTER parameter
 - chg-oap-config, 2970:4-11
- Browse button
 - FTP Server Configuration Menu, 0197:2-52, 0197:2-53
 - Update Tables, 0197:2-80, 0197:2-81
- browser connectivity, 0178:5-29, 0183:5-36, 0288:2-58
- browser window, 0178:3-5, 0183:3-5
- browsers, 0178:5-3
- Building Integrated Timing System, 0224:5-85, 0224:5-88
- Building Integrated Timing System (BITS), 0212:3-27, 0212:3-64, 0212:3-68, 0224:1-5
- building requirements, 0212:6-3
- Bulk download from LSMS to the BLM card must have completed, 0177:2-641
- Bulk Load
 - Disabling, 0288:2-139
 - Error Messages, 0288:2-103
 - Log File, 0288:2-101

Procedure, 0288:2-92
 bulk load
 aborting, 2339:6-12
 from LSMS, 2339:2-6
 log file, 2339:6-11, 2339:6-20
 managing, 2339:6-5
 options, 2339:2-11
 overview, 2339:2-10
 bus, 0224:4-9
 busy icon, 0178:3-6, 0183:3-6
 Button
 Add, 0197:2-1, 0197:2-18, 0197:2-20, 0197:2-24, 0197:2-58, 0197:2-62
 Browse
 FTP Server Configuration Menu, 0197:2-52, 0197:2-53
 Update Tables window, 0197:2-80, 0197:2-81
 Cancel, 0197:2-36
 Print window
 Retrieve Tables Log, 0197:2-73
 System Log, 0197:2-101
 Update Tables Log, 0197:2-97
 Save window
 Retrieve Tables Log, 0197:2-74
 System Log, 0197:2-103
 Update Tables Log, 0197:2-98
 Select Starting Directory window, 0197:2-54
 Select window, 0197:2-81, 0197:2-82
 Close, 0197:2-18, 0197:2-27, 0197:2-29, 0197:2-52
 Retrieve Tables, 0197:2-58
 Update Tables, 0197:2-80
 Commit, Update Validation Complete window, 0197:2-85, 0197:2-86
 Delete, 0197:2-18, 0197:2-27, 0197:2-29, 0197:2-42
 Edit, Update Validation Complete window, 0197:2-85, 0197:2-86, 0197:2-87, 0197:2-88
 Load, 0197:2-58, 0197:2-66, 0197:2-75
 Modify, 0197:2-18, 0197:2-38, 0197:2-39
 Refresh, 0197:2-18, 0197:2-25, 0197:2-27, 0197:2-29, 0197:2-31, 0197:2-41
 Remove, 0197:2-58, 0197:2-64
 Reset, 0197:2-58, 0197:2-65
 Retrieve, 0197:2-56, 0197:2-58, 0197:2-66, 0197:2-67
 Retrieve from Local Database, 0197:2-56, 0197:2-58, 0197:2-66
 Retrieve from STP, 0197:2-56, 0197:2-58, 0197:2-67
 Save
 Retrieve Tables Log, 0197:2-74
 System Log, 0197:2-103
 Update Tables Log, 0197:2-98
 Select, 0197:2-18, 0197:2-27, 0197:2-29
 Select Starting Directory window, 0197:2-54
 Select window, 0197:2-81, 0197:2-82
 Set, 0197:2-55
 FTP Server Configuration Menu, 0197:2-52
 Stop, Update Validation Complete window, 0197:2-85
 Store, 0197:2-58, 0197:2-65, 0197:2-75
 Test, 0197:2-18, 0197:2-27, 0197:2-29, 0197:2-33

Master Index

Validate, 0197:2-80, 0197:2-84
Update Tables window, 0197:2-79
BYTE, WORD or DWORD must be entered, 0177:2-80

C

C value not allowed, 0177:2-221
C7 network, 0188:1-1
CA or CB register value is invalid for this card, 0177:2-757
cable
 CD-ROM, 0338:5-11, 2970:7-7
 hard drive card, 0338:5-11, 2970:7-7
Cable Arm, 0224:4-22
Cable Connector, 0224:5-12
cable ends, 0224:4-12
Cable Holes, 0224:3-15
cable holes, in raised floor, 0095:4-5, 2969:4-5
cable list, 2970:3-8
cable management arms, 0095:3-10, 2969:3-9
Cable Rack Mounting Kit, 0224:3-16, 0224:3-18
Cable Running List, 0224:5-107
Cables, 0224:4-21
cables
 labeling, 0224:2-8, 0224:C-4, 0243:C-4
Cables, Adapter for -03 and -04 backplanes, 0224:C-49, 0243:C-50
cabling
 additional NE server, 0095:5-16, 2969:5-14
 frame, 0095:4-20, 2969:4-20
calculates checksums, 0188:2-25, 0190:2-52
Call Flows, 0188:2-3, 0190:2-6, 0195:2-3
Call Originated from GSM MSC for Migrated Subscriber, 0190:2-22
Call Originated from GSM MSC for Non-Migrated (IS41 only) Subscriber, 0190:2-24
Call Originated from IS-41 MSC for Migrated Subscriber, 0190:2-21
Call Originated from IS-41 MSC for Non-Migrated Subscriber, 0190:2-23
Call to an Exported Number by Direct Routing, 0190:2-8
Called Party Number, 0193:2-6, 0193:2-11
calling name conversion facility, 0288:3-69
Calling Name Conversion Facility (CNCF) (23.1), 0347:2-43, 0347:2-57
 conversion of GN to PIP, 0347:2-51
 conversion of PIP to GN, 0347:2-50
 Gateway Screening Change commands, 0347:2-58
 Gateway Screening Enter commands, 0347:2-57
 Gateway Screening Retrieve commands, 0347:2-58
 Gateway Screening stop action commands, 0347:2-57
 limitations, 0347:2-45
 message conversion, 0347:2-52
 PIP and GN parameters, 0347:2-48
 rtrv-feat, 0347:2-44
 Unsolicited Information Messages, 0347:2-59
call-related message, 0190:2-45
call-related messages, 0190:2-5
call-related SRI messages, 0190:2-45

Can't switch existing Pfx / Sfx, use RDMOD to reset, 0177:2-764
 Can't switch existing Pfx / Sfx, use RMGTT to reset, 0177:2-775
 Can't send after socket shutdown - Error code 58, 0197:2-120
 cancel-cmd, 0145:5-48
 cancel-echo, 0145:5-51
 cancel
 rtrv-dstn, 0100:3-39, 0120:3-35, 0120:3-155, 0120:3-165, 0120:3-173, 0120:3-182, 0120:3-271
 rtrv-ls, 0100:3-39, 0120:3-35, 0120:3-155, 0120:3-165, 0120:3-173, 0120:3-182, 0120:3-271
 rtrv-rte, 0120:3-155, 0120:3-165, 0120:3-173, 0120:3-182
 Cancel button, 0197:2-36
 Print window
 Retrieve Tables Log, 0197:2-73
 System Log, 0197:2-101
 Update Tables Log window, 0197:2-97
 Save window
 Retrieve Tables Log, 0197:2-74
 System Log, 0197:2-103
 Update Tables Log, 0197:2-98
 Select Starting Directory window, 0197:2-54
 Select window, 0197:2-81, 0197:2-82
 Cancelling rtrv and rept-stat Commands
 Miscellaneous Command Adjustments (26.0), 0347:4-120
 cancel-lnp-dpcer, 0145:5-51
 cancel-lnp-tnrpt, 0145:5-52
 cancel-lpo, 0145:5-53
 cancel-slk, 0145:5-54
 cancel-user, 0145:5-56
 Cannot add NP and NAI to an entry where GTIXLAT is 22, 0177:2-762
 Cannot allow terminal configured as type=none, 0177:2-56
 Cannot assign ITU and ANSI LHOST to the same AS, 0177:2-308
 Cannot assign LHOST to the B interface, 0177:2-663
 Cannot assign LHOST / ALHOST to the B interface, 0177:2-740
 Cannot change existing STP True PC if in MAP table, 0177:2-492
 Cannot change if existing connection type is PVC, 0177:2-296
 Cannot change routing key and attribute values, 0177:2-724
 Cannot change terminal authority while user is logged on, 0177:2-336
 Cannot change the RC parameter with the ENT command, 0177:2-456
 Cannot change TYPE as system requires 2 SA enabled terminals, 0177:2-337
 Cannot change TYPE as system requires two SA enabled terminals, 0177:2-342
 Cannot decrease PVC below a logical channel in use, 0177:2-299
 Cannot decrease SVC below number of SVCs already in use, 0177:2-299
 Cannot delete last route to DPC ref. by an X.25 route, 0177:2-278
 Cannot delete last route to DPC ref. by redirect func, 0177:2-278
 Cannot delete last route to DPC ref. In MAP table, 0177:2-277, 0177:2-799
 Cannot delete STP self ID if a DPC of same type is defined, 0177:2-71
 Cannot delete the last route to a DPC referenced in the MRN table, 0177:2-436
 Cannot echo to OAP terminal, 0177:2-664
 Cannot enter a wildcard with XLAT=2, Use XLAT=4 for wildcard, 0177:2-813
 Cannot enter MTPRSE with SLSOCBIT, SLSRSB parameters, 0177:2-665
 Cannot enter MULTCC if STP Options DefCC is NONE, 0177:2-598
 Cannot enter the same PC more than once, 0177:2-423
 Cannot execute command until table initialization complete, 0177:2-780

Master Index

Cannot inhibit IMT bus - alternate bus is in abnormal stat, 0177:2-320
Cannot leave a solitary PC in group, 0177:2-423
Cannot mix Unchannnelized and Channelized modes on E1 card, 0177:2-801
Cannot provision EMDC card with 15 min coll feature on, 0177:2-602
Cannot read DB Stat Table (<database>, <disk>, <MASP status>), 0177:2-417
Cannot set DefCC to none if a GSM Options MULTCC is defined, 0177:2-585
Cannot specify ALL=YES when command given, 0177:2-6
Cannot specify LC without LOC, 0177:2-297
Cannot specify LSN parameter with ALL=YES, 0177:2-131
Cannot turn on feature with EMDC provisioned, 0177:2-600
Cannot use NEXT if preceding RTRV-LOG command used TYPE=ALL, 0177:2-776
capability point code, 0188:4-8, 0188:4-10, 0188:4-11, 0190:4-10, 0190:4-11, 0190:4-12, 0193:4-10, 0193:4-11, 0193:4-12, 0193:4-36
Capability point code already defined as a route DPC, 0177:2-69
Capability point code is already being used, 0177:2-68
Capability point code matches STP's own point code, 0177:2-69
capability point codes
 EIR, 0195:5-2
Capacity, 0224:4-25
Capacity of TDM(s) / TSM(s) insufficient to support request, 0177:2-592
capacity status reporting, DSM memory, 0178:4-7
Capture Log Files, 0178:3-63
Card
 GPSM-II, 0197:2-3
 IPSM, 0197:2-3
 MCAP, 0197:2-3
 TDM, 0197:2-3
card
 adding, 0120:3-5
 FRU, breaker panel alarm, 0096:5-2
 MPS Server alarm, 0025:6-12, 0212:4-28
 Quad FastEthernet Network Interface, 0212:4-31
 replacement procedure, breaker panel alarm, 0096:5-2
 SAI/P, 0212:4-31, 0212:4-43
Card backup database has been corrected, 0338:3-121
Card backup database is corrupted, 0338:3-123
Card backup database is inconsistent, 0338:3-122
Card database has been corrected, 0338:3-113
Card database is corrupted, 0338:3-118
Card database is inconsistent, 0338:3-114
Card DB is stable, 0338:3-599
Card DB load timeout, check GLS card, 0338:3-598
Card does not exist or is not a LIM (LOC), 0177:2-117
Card does not exist or is not an LPE, 0177:2-106
Card does not support command driven loopback, 0177:2-791
Card does not support more than 2 Links, 0177:2-422
Card GPL of link does not match domain of linkset APC, 0177:2-250
Card GPL state conflict, 0177:2-792
Card GPL type IPGWI requires a link set with IPGWAPC=YES, 0177:2-668
Card GPL type SS7IPGW requires IPGWAPC=YES, 0177:2-649
Card has been reloaded, 0338:3-173
Card has IP LNK with IP address assigned, 0177:2-270

Card has reset, 0338:3-82
 Card having link in linkset must first be inhibited, 0177:2-783
 Card having link in mate linkset must first be inhibited, 0177:2-783
 Card is isolated from the system, 0338:3-100
 Card is not a SS7GX25 card, 0177:2-300
 Card is not an ACMENET card, 0177:2-258
 Card is not in service, 0177:2-159
 Card is not running approved GPL, 0338:3-83
 Card is present, 0338:3-102
 Card is running non-activated GPL, 0338:3-92
 card loading interrupted or aborted, 0190:5-7, 0193:5-9, 0195:4-6
 Card location already equipped, 0177:2-26
 Card location is unequipped, 0177:2-27
 Card location must be 1113 or 1115, or APPL=E(OAM), 0177:2-94
 Card location must be 1114 or 1116, 0177:2-95
 Card location must be 1114, 1116, or 1117, 0177:2-96
 Card location not assigned a TCP/IP link, 0177:2-259
 Card location specified must be an OAM card, 0177:2-495
 Card location specified must be an SCCP card, 0177:2-436
 Card location specified must be the standby, 0177:2-56
 Card must be inhibited before executing this command, 0177:2-258
 Card not using config. SCTP csum method, 0338:3-374
 Card Related MPS Alarms, 0193:5-18, 0195:4-15
 Card Replacement Procedures, 0338:A-1
 Card responding normally, 0338:3-502
 Card slot location out of range, 0177:2-52
 Card slot reserved by system, 0177:2-53
 card state, 0190:2-51
 Card successfully loaded with data, 0338:3-203
 Card temperature exceeds nominal lvl
 T1, 0338:3-154
 Card temperature is critical lvl
 T2, 0338:3-150
 Card temperature within nominal levels, 0338:3-158
 card type
 signaling link, 0120:3-5
 Card type must be VXWSLAN for a 100Mbit link, 0177:2-833
 Card type of LIMCH does not support E1PORT = 2, 0177:2-726
 Card type of LIMCH does not support T1PORT = 2, 0177:2-322
 Card(s) cannot warm restart - FORCE parameter required, 0145:6-403, 0177:2-658
 Card(s) not in-service normal - FORCE parameter required, 0177:2-614
 Card's A/B interface IP Networks must be unique, 0177:2-558
 CAS=ON is invalid for HC-MIM, 0177:2-544
 categories, alarm, 0178:4-14, 0183:4-16
 caution
 changing point code, 0188:4-4, 0188:4-11, 0190:4-4, 0190:4-12, 0193:4-4, 0193:4-12
 init-sys command, 0188:4-4, 0188:4-12, 0190:4-5, 0190:4-13, 0193:4-5, 0193:4-13
 Caution icon, 0188:1-8, 0190:1-8, 0193:1-9
 Cautionary Information, 0224:3-2
 CC, 0188:1-10, 0190:1-10, 0193:1-11, 0195:1-10
 CCBS, 0193:1-11
 Cccmmd table must be accessible, 0177:2-255

Master Index

Cccnames table must be accessible, 0177:2-256
CCGT, 0348:1-10
ccgt, 0348:3-38, 0348:3-42
CCGT and NGTI are mutually exclusive, 0177:2-775
CCGT must be NO when PC is the STP's PC or CPC, 0177:2-571
CCGT must be NO when RI is set to GT, 0177:2-573
CCNC, 0188:3-4
CCNC already exists, 0177:2-553
CCNC and MCCMNC parameters must be entered together, 0177:2-552
CCNC cannot be NONE, 0177:2-551
CCNC/MCCMNC numbering plan conversion, 0188:3-4
ccnc=, 0188:4-37
CCNR, 0193:1-11
CCP - Charge Number and Charge Party Station, 0288:3-53
CCRNDN, 0190:1-10, 0195:1-10
CCS7ITU, 0097:6-7, 0097:6-20
CD/DVD, 2969:7-4
CDPA, 0193:1-11
CdPA, 0188:1-10, 0190:1-10, 0195:1-10
CdPA SSN, 0347:5-20
CDPN, 0193:2-6, 0193:2-18
CDPN digits, 0193:2-19
CDPN NAI, 0193:2-19
cdpnai, 0193:2-19
CDPNNAI and SNAI must be specified together, 0177:2-97
CDPNNAI doesn't exist in INPOPTS Table, 0177:2-90
cdpnpx, 0193:2-11, 0193:2-22
CDPNPFX doesn't exist in INPOPTS Table, 0177:2-89
CDPNPFX must be specified, 0177:2-41
CDPNPFX must not be NONE, 0177:2-87
CD-ROM, 0212:3-149, 0212:3-151, 0338:5-9, 0348:1-10, 2970:7-6
specification, 0212:4-27
CD-ROM drive, 0197:2-2, 0197:2-5, 0197:2-8
CD-ROM jumper settings, 0338:5-10, 2970:7-7
CDSR does not exist in the database, 0177:2-808
CDSR must be specified when NCDSR is specified, 0177:2-809
CDU, 0193:1-11
cdu, 0145:8-8
CDU for DSM (26.05), 0347:2-62
CDU Port, 0347:2-62
enhanced commands, 0347:2-63
new commands, 0347:2-63
Ping Test, 0347:2-62
Quick Test, 0347:2-62
CDU Port
CDU for DSM (26.05), 0347:2-62
central office ground, 0095:6-8, 0224:4-19, 2969:6-9
CFG parameter
chg-oap-config, 2970:4-11
CGPA, 0193:1-11
CgPA, 0188:1-10, 0190:1-10, 0195:1-10
CGPA entry can't be provisioned, 0177:2-805

CGPA entry is referred by CDPA entries, 0177:2-680
 CGSR doesn't exist for specified OPNAME, 0177:2-682
 CGSR must be specified when CDSR is specified, 0177:2-718
 CGSR or CDSR shouldn't be specified when SADDR is specified, 0177:2-718
 chalk line, 0095:4-4, 2969:4-4
 CHANBRDG is invalid for even numbered card location, 0177:2-548
 CHANBRDG is only valid for HC-MIM, 0177:2-544
 CHANBRDG parameter is invalid for even numbered port, 0177:2-545
 Change Allowed menu, 0178:3-32
 Change Enabled, 0178:3-29
 Change Enabled menu, 0178:3-25, 0178:3-26, 0183:3-22
 change features, chg-feat
 DCM, 0338:3-380, 0338:5-99, 0338:A-90, 2970:3-71, 2970:6-48
 change G-Flex-specific system options, 0188:3-4
 change GSM system options, 0188:4-8, 0188:4-37, 0190:4-8, 0190:4-36
 change link parameters, 0188:4-24, 0188:4-33, 0190:4-24, 0190:4-33, 0193:4-24, 0193:4-33
 Change Params, 0183:3-103
 Change Password, 0178:5-21, 0183:5-24
 Change Password menu, 0178:3-110, 0178:5-21, 0183:3-140, 0183:5-24
 Change PDBA Number Prefix, 0183:3-106
 change service providers, 0190:2-2
 Change Simplex Mode, 0178:3-21
 Change Status, 0178:3-18, 0183:3-18
 change TCP/IP information for DSM, 0188:4-23, 0188:4-32, 0190:4-23, 0190:4-32, 0193:4-23, 0193:4-32
 change true PC, 0188:4-8, 0190:4-10, 0193:4-10
 changed commands
 48 Million Numbers (27.0), 0347:2-15
 5 Minute Linkset Data (25.0), 0347:2-16
 500 SS7 Links (21.0), 0347:2-20
 5000 Routes (26.1), 0347:2-21
 5-8 Bit Sequencing Assurance (24.0), 0347:2-18
 ANSI/ITU MTP Gateway (20.0), 0347:2-41
 ANSI/ITU SCCP and TCAP Conversion (24.0), 0347:2-42
 Enhanced Bulk Download (25.0), 0347:2-151
 Enhanced GPL Management (25.0), 0347:2-152
 Enhanced GTT (26.0), 0347:2-156
 Flash Memory Management (23.0), 0347:3-4
 Flexible Point Code Formatting (26.0), 0347:3-6
 G-Port MNP (26.2), 0347:3-21
 GSM MAP Screening (26.1), 0347:3-43
 GTT by TT Measurements and GR-376 Enhancements (26.0), 0347:3-50
 IP7 Transport Feature (26.1), 0347:3-118
 ITU MTP Restart (26.0), 0347:3-158
 ITU SLS Enhancements (26.0), 0347:3-161
 ITU-TFR Procedure (26.1), 0347:3-163
 Large System (27.2), 0347:4-2
 LNP AIN Query Enhancement (26.0), 0347:4-50
 LRN Table Increase (26.1), 0347:4-95
 Miscellaneous Command Adjustments (26.0), 0347:4-119
 Multiple LFS Tests (EAGLE 26.0), 0347:4-142
 Multi-Port LIM (EAGLE 27.1), 0347:4-152
 National Spare Network Indicator Support (EAGLE 22.2), 0347:4-155

Master Index

- National Spare Network Indicator Support (EAGLE 24.0), 0347:4-157
- Nested Cluster Routing (EAGLE 26.0), 0347:4-172
- Number Pooling (EAGLE 24.0), 0347:4-198
- Number Pooling / Efficient Data Representation (EDR) (EAGLE 26.1), 0347:4-203
- PCS 1900 LNP Query (EAGLE 26.0), 0347:5-6
- Selective Alarm Inhibiting (EAGLE 22.0), 0347:5-76
- Simplifying BIP (Board ID PROM) for Eagle STP Boards (EAGLE 23.1), 0347:5-80
- STPLAN with Default Router (EAGLE 23.0), 0347:5-94
- Temporary Alarm Inhibiting and Offline Functions (EAGLE 25.0), 0347:5-128
- TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-147
- Types of Routing Strategies Available, 0347:4-181
- Variable Length GTT (Eagle 26.1), 0347:5-171
- changed commands
 - Group Ticket Voucher for SCCP Cards (27.0), 0347:3-40
- changed event log command
 - Thresholding of UIM Messages (EAGLE 25.0), 0347:5-132
- changed files
 - LNP Measurements Enhancements (25.0), 0347:4-54
- Changeover and Changeback Procedure for Processor Outage and LIN (21.0), 0347:2-66
- changing
 - ATM high speed signaling link parameter set, 0120:C-50
 - cluster point code
 - attributes, 0120:2-161
 - destination point code, 0120:2-226
 - level 2 timers, 0120:3-219
 - level 3 timers, 0120:3-222
 - linkset, 0120:3-74
 - password, 0142:4-48
 - remote loopback points, 0120:3-250
 - route, 0120:3-206
 - security defaults, 0142:4-7
 - security log characteristics, 0142:4-17
 - self identification of the EAGLE 5 SAS, 0120:2-90
 - signaling link test message, 0120:3-228
 - terminal characteristics, 0142:4-51
 - terminal command class assignment, 0142:4-72
 - user information, 0142:4-35
- Changing a Blocked DPC Screen, 0098:8-26, 0119:5-55
- Changing a Blocked OPC Screen, 0098:11-26, 0119:5-103
- Changing a DCM Parameter Set, 0100:3-216
- Changing a Destination Point Code, 0119:2-24
- Changing a Gateway Linkset, 0119:5-137
- Changing a Global Title Translation, 0099:3-49, 0119:4-16
- Changing a GSM MAP Screening Entry, 0097:5-125, 0097:5-135, 0097:5-136, 0097:5-137, 0097:5-138, 0097:5-139
- Changing a GSM MAP Screening Operation Code, 0097:5-82, 0097:5-88, 0097:5-89, 0097:5-90, 0097:5-91
- Changing a GTT Selector, 0099:4-21
- Changing a Linkset, 0097:2-61, 0119:3-13
- Changing a Mapped SS7 Message Translation Type, 0099:2-66
- Changing a Mated Application, 0099:2-117, 0119:4-7, 0119:6-7
- Changing a Route, 0119:3-38

Changing a Screen Set, 0098:13-15
 Changing an ACG Node Overload Control Level, 0288:4-18
 Changing an Allowed Affected Point Code Screen, 0098:3-17, 0119:5-7
 Changing an Allowed Called Party Address Screen, 0098:4-22, 0119:5-15
 Changing an Allowed Calling Party Address Screen, 0098:6-23, 0119:5-33
 Changing an Allowed DPC Screen, 0098:9-26, 0119:5-71
 Changing an Allowed ISUP Message Type Screen, 0098:15-20
 Changing an Allowed OPC Screen, 0098:12-25, 0119:5-118
 Changing an Allowed SIO Screen, 0098:10-23, 0119:5-87
 Changing an Allowed Translation Type Screen, 0098:5-14, 0119:5-21
 Changing an Application Socket, 0100:3-191
 Changing an IP Card, 0100:3-35, 0100:3-152
 Changing an IP Link, 0100:3-127
 Changing an IP7 Secure Gateway Option, 0100:3-35
 Changing an MRN Group, 0099:2-153
 Changing an X.25 Gateway Destination, 0097:2-34
 Changing an X.25 Route, 0097:2-115
 Changing Global Title Address Information, 0099:4-54, 0119:6-15
 changing options
 ANSI-ITU-China SCCP Conversion, 0099:2-193, 0099:2-195
 SCCP Class 1 Sequencing, 0099:2-20, 0099:2-196, 0099:2-197, 0099:2-198, 0099:2-199
 changing passwords, 0095:6-16, 2969:6-16
 changing point code
 caution, 0188:4-4, 0188:4-11, 0190:4-4, 0190:4-12, 0193:4-4, 0193:4-12
 Changing the DPC Quantity, 0120:2-23
 Changing the HC MIM Temperature Alarm Thresholds, 0120:3-279
 Changing the LNP telephone number alarm thresholds, 0288:3-86
 Changing the SCCP Alarm Thresholds, 0099:2-200
 Changing the Self Identification of the EAGLE 5 SAS, 0119:2-16
 Changing the System-Wide GSM MAP Screening Options, 0097:5-56, 0097:5-58
 Changing the X.25 Signaling Link Parameters, 0097:2-130
 Channel bridged slave port is invalid for link provisioning, 0177:2-798
 Channel Card, 0224:5-119
 Chapter 1, Introduction, 0224:1-11, 0243:1-12
 Chapter 2, General Installation Information, 0224:1-11
 Chapter 3, Frames and Shelves, 0224:1-11
 Chapter 4, Fuses and Breakers, 0224:1-11
 Chapter 4, Sentinel describes the Expanded Services Platform, 0243:1-12
 Chapter 5, Eagle STP/IP7 Secure Gateway Assemblies, 0224:1-11
 Chapter 7, OAP/EOAP, 0224:1-11
 Chapter 8, Integrated Sentinel, 0243:1-12
 Charge Number and Charge Party Station - CCP, 0288:3-53
 Chassis Dimensions and weight, 2969:3-9
 Check_IMEI Message Handling, 0195:2-15
 checklist, post-installation, 0095:6-13, 2969:6-13
 checksum value stored, 0188:2-25
 checksums, 0190:2-52
 checksums and alarms
 EOAP, 2970:4-14
 chg-acg-mic, 0145:5-56
 chg-acg-noc, 0145:5-58
 chg-appl-rtkey, 0145:5-60

Master Index

chg-as, 0145:5-73
chg-asp, 0145:5-74
chg-assoc, 0145:5-69
chg-atm-lps, 0145:5-80
chg-attr-seculog, 0145:5-83
chg-bip-flt, 0145:8-14
chg-bip-rec, 0145:8-15
chg-cmdclass, 0145:5-86
chg-ctrl-feat, 0145:5-87
chg-db, 0119:2-2, 0119:2-7, 0119:2-12, 0119:2-16, 0119:2-18, 0119:2-21, 0119:2-24, 0119:3-2, 0119:3-11, 0119:3-13, 0119:3-24, 0119:3-33, 0119:3-36, 0119:3-38, 0119:4-2, 0119:4-5, 0119:4-7, 0119:4-9, 0119:4-15, 0119:4-16, 0119:5-3, 0119:5-5, 0119:5-7, 0119:5-8, 0119:5-11, 0119:5-15, 0119:5-17, 0119:5-20, 0119:5-21, 0119:5-23, 0119:5-27, 0119:5-33, 0119:5-37, 0119:5-39, 0119:5-43, 0119:5-44, 0119:5-49, 0119:5-55, 0119:5-60, 0119:5-66, 0119:5-71, 0119:5-76, 0119:5-84, 0119:5-87, 0119:5-94, 0119:5-100, 0119:5-103, 0119:5-109, 0119:5-116, 0119:5-118, 0119:5-124, 0119:5-136, 0119:5-137, 0119:5-148, 0119:5-149, 0119:5-150, 0119:5-152, 0119:5-155, 0119:6-2, 0119:6-5, 0119:6-7, 0119:6-9, 0119:6-14, 0119:6-15, 0145:5-89
chg-db:action=backup:dest=fixed, 0142:2-33, 0338:3-76
chg-db:action=backup:dest=remove, 0142:2-36, 0142:2-70
chg-db:action=repair, 0142:2-51
chg-db:action=restore:src=fixed, 0142:2-40
chg-db:action=restore:src=remove, 0142:2-44, 0142:2-74
chg-dcmps, 0145:5-100
chg-dstn, 0145:5-102
chg-e1, 0145:5-112
chg-feat, 0119:2-2, 0119:2-7, 0119:2-12, 0119:3-4, 0119:3-16, 0119:5-3, 0119:5-8, 0119:5-17, 0119:5-23, 0119:5-37, 0119:5-44, 0119:5-60, 0119:5-76, 0119:5-94, 0119:5-109, 0119:5-124, 0119:5-150, 0145:5-115, 0188:3-3, 0188:4-8, 0188:4-35, 0190:4-8, 0190:4-35, 0193:3-3, 0193:4-8, 0193:4-35
Change Feature Status Command, 0188:3-3, 0190:3-3, 0193:3-3, 0195:3-2
gflex=on, 0188:4-8, 0188:4-35, 0190:4-8, 0190:4-35, 0193:4-8, 0193:4-35
chg-ftp-serv, 0142:4-150, 0142:4-151, 0145:5-125
chg-ftp-serv EAGLE 5 SAS command, 0197:2-52
chg-gpl, 0145:5-127, 0188:3-12, 0190:3-16, 0193:3-10, 0195:3-16
chg-gsmmap-scrn, 0145:5-131
chg-gsmopts, 0145:5-136, 0188:4-8, 0188:4-37, 0190:4-8, 0190:4-36
Change EIR System Options Command, 0195:3-5
Change G-Flex System Options Command, 0188:3-4
Change G-Port System Options Command, 0190:3-5
chg-gsms-opcode, 0145:5-144
chg-gta, 0145:5-148
chg-gtcnv, 0145:5-154
chg-gtt, 0145:5-158
chg-gttset, 0145:5-165
chg-gtw-stp, 0145:5-167
chg-gws-actset, 0145:5-168
chg-gws-redirect, 0145:5-172
chg-inpopts, 0145:5-174, 0193:2-11, 0193:2-18, 0193:2-19, 0193:3-11, 0193:4-8, 0193:4-40
chg-ip-card, 0142:4-138, 0145:5-178, 0188:3-14, 0188:4-6, 0188:4-7, 0188:4-23, 0188:4-32, 0190:3-17, 0190:4-6, 0190:4-7, 0190:4-23, 0190:4-32, 0193:3-12, 0193:4-6, 0193:4-7, 0193:4-23, 0193:4-32
chg-ip-lnk, 0142:4-138, 0142:4-158, 0145:5-180, 0188:3-14, 0188:4-6, 0188:4-7, 0188:4-24, 0188:4-33, 0190:3-18, 0190:4-6, 0190:4-7, 0190:4-24, 0190:4-33, 0193:3-12, 0193:4-6, 0193:4-7, 0193:4-24, 0193:4-33
chg-isupvar-attrb, 0145:5-183

chg-l2t, 0145:5-188
 chg-l3t, 0145:5-191
 chg-lbp, 0145:5-196
 chg-lnp-lrn, 0145:5-198
 chg-lnp-npanxx, 0145:5-201
 chg-lnpopts, 0145:5-211
 chg-lnp-refnum, 0145:8-16
 chg-lnp-serv, 0145:5-204
 chg-lnp-sub, 0145:5-206
 chg-lnp-ttmap, 0145:5-209
 chg-ls, 0145:5-214
 chg-m2pa-tset, 0145:5-227
 chg-map, 0145:5-229, 0193:3-9
 chg-meas, 0145:5-236
 chg-measopts, 0145:5-238, 0195:3-17
 chg-mrn, 0145:5-245
 chg-netopts, 0145:5-252
 chg-oap-config, 0145:5-253
 chg-pid, 0145:5-258
 CHG-PID not allowed while in upgrade mode, 0177:2-414
 chg-prefix, 0145:5-259
 chg-pstn-pres, 0145:5-262
 chg-rte, 0145:5-263
 chg-sccpopts command, 0099:2-196, 0099:2-197
 chg-scr-blkdpc, 0145:5-273
 chg-scr-blkopc, 0145:5-281
 chg-scr-cdpa, 0145:5-288
 chg-scr-cgpa, 0145:5-294
 chg-scr-destfld, 0145:5-301
 chg-scr-isup, 0145:5-312
 chg-scr-opc, 0145:5-315
 chg-scr-sio, 0145:5-321
 chg-secu-dflt, 0145:5-330
 chg-secu-trm, 0145:5-335
 chg-sg-opts, 0145:5-339
 chg-sid, 0145:5-345, 0188:4-4, 0188:4-11, 0190:4-4, 0190:4-12, 0193:3-3, 0193:4-4, 0193:4-8, 0193:4-12,
 0193:4-36, 0195:3-15
 chg-slt, 0145:5-354
 chg-srvsel, 0193:3-3
 Change EIR Service Selector Command, 0195:3-6
 Change G-Flex Service Selector Command, 0188:3-6
 Change G-Port Service Selector Command, 0190:3-7
 chg-ss7opts, 0145:5-360
 chg-ss7opts command, 0120:3-94, 0120:3-269, 0120:3-273, 0120:3-276, 0120:3-277
 chg-ss-appl, 0195:3-16
 chg-stpopts, 0119:2-2, 0145:5-361, 0188:4-8, 0188:4-36, 0190:3-4, 0190:4-8, 0190:4-36, 0193:3-3, 0193:4-8,
 0193:4-39, 0193:5-23
 chg-stpopts command, 0099:2-20, 0099:2-196, 0099:2-197
 chg-t1, 0145:5-375
 chg-tbl, 0145:8-18
 chg-th-alm, 0145:5-377
 chg-th-sccp, 0145:5-379

Master Index

chg-trm, 0145:5-380
chg-trm command, 0197:2-48
chg-trm:trm=:all=no EAGLE 5 SAS command, 0197:2-67
chg-ttmap, 0145:5-390
chg-uaps, 0145:5-391
chg-user, 0145:5-394
chg-x25-dstn, 0145:5-399
chg-x25-rte, 0145:5-400
chg-x25-slk, 0145:5-402
China-ANSI-ITU SCCP Conversion, 0099:1-2, 0099:2-3, 0099:2-6, 0099:2-7, 0099:2-16, 0099:2-17, 0099:2-30, 0099:2-33, 0099:2-40, 0099:2-43, 0099:2-44, 0099:2-47, 0099:2-48, 0099:2-69, 0099:2-71, 0099:2-82, 0099:2-86, 0099:2-92, 0099:2-118, 0099:2-124, 0099:2-162, 0099:2-163, 0099:2-171, 0099:2-172, 0099:2-179, 0099:2-181, 0099:2-193, 0099:2-194, 0099:3-2, 0099:3-21, 0099:3-23, 0099:3-28, 0099:3-32, 0099:3-53, 0099:3-54, 0099:3-55, 0099:3-58, 0099:3-62, 0099:4-2, 0099:4-27, 0099:4-30, 0099:4-34, 0099:4-35, 0099:4-38, 0099:4-39, 0099:4-54, 0099:4-57, 0099:4-60, 0099:4-63, 0099:A-36, 0099:A-37, 0099:A-38, 0099:A-39, 0099:A-41, 0099:A-42
chk-unref-ent, 0145:5-404
chmod command, 0197:2-52, 0197:2-53
CI, 0224:2-2, 0224:A-7, 0243:1-37
CIC bit
 ITU SLS enhancement, 0120:3-31
CIC outside of valid range for SI, 0177:2-671
CIC Range overlaps an existing routing key, 0177:2-634
cice, 0100:3-224, 0100:3-236, 0100:3-253, 0100:3-260, 0100:3-261, 0100:3-268, 0100:3-269, 0100:3-278
cics, 0100:3-224, 0100:3-235, 0100:3-252, 0100:3-253, 0100:3-260, 0100:3-268, 0100:3-278
CICS must be less than or equal to CICE, 0177:2-634
circular route detection
 configuring, 0120:3-231
circular routing
 network routing, 0120:2-178
CLASS, 0288:3-22
Class name is not an existing command class name, 0177:2-125
Class name is not an existing configurable command class, 0177:2-105
classlseq parameter, 0099:2-20, 0099:2-196
 SCCP Class 1 Sequencing, 0099:2-20, 0099:2-196, 0099:2-197
classes, command, 0145:4-17
Cleaning Printer, 0338:2-35
Cleaning the OAP Fan Filter, 0338:2-31, 0338:2-33
Clear To Send (CTS), 0212:3-67
Clearing a Temporary FAK alarm, 0099:A-12, 0100:6-7, 0142:A-36
clearing alarm, 0178:4-15, 0183:4-18
Clearing an FAK alarm, 0288:3-83
Clearing the display
 Connectivity Test Log, 0197:2-34, 0197:2-35
 Retrieve Tables Log, 0197:2-70, 0197:2-71
 System Log, 0197:2-99, 0197:2-100
 Update Tables Log, 0197:2-94, 0197:2-95
client connections, 0183:2-25, 0348:2-10, 0348:3-8
C-link linkset, 0100:3-7, 0120:3-6
CLLI, 0347:1-13
CLLI cannot be specified without Point Code, 0177:2-34
CLLI is already being used by a route, 0177:2-68

- CLLI is not identical to that of matching Destination, 0177:2-133
- CLLI not defined in route table, 0177:2-130
- CLLI used by STP, 0177:2-57
- CLLI-based Names Enabled, 0338:4-8
- CLOCK, 0224:5-110
- Clock
 - HCMIM, 0212:3-115
- clock, 0224:5-85, 0224:5-106, 0224:5-115
- Clock A, 0212:3-32
- Clock A for card failed, B normal, 0338:3-104
- Clock A for card normal, 0338:3-110
- Clock alarm(s) cleared, 0338:3-193
- Clock B for card failed, A normal, 0338:3-106
- Clock B for card normal, 0338:3-111
- Clock Cable, 0224:5-104
- clock cable, 0224:5-104
- Clock Cable Diagram, 0224:5-102
- clock cable installation, 0224:5-12
- clock cables, 0224:5-101, 0224:5-112
- clock connection cable
 - install, 0224:C-36, 2970:3-41
 - route, 2970:3-42
- clock connectors, 0224:B-5, 0224:B-7, 0224:B-10, 0224:B-12
- clock in/out cable
 - install, 2970:3-40
- Clock selection corrected, 0338:3-525
- Clock Supply Cables, 0224:5-88
- Clock / Alarm, 0224:5-7
- Clocks A and B for card failed, 0338:3-108
- Clocks A and B for card normal, 0338:3-112
- Clocks A and B TSCs are resynchronized, 0338:3-170
- close, 0348:3-8
- Close button
 - FTP Connection Configuration Menu, 0197:2-52
 - Retrieve Tables window, 0197:2-58
 - STP Connection Configuration Menu, 0197:2-18, 0197:2-27, 0197:2-29
 - Update Tables, 0197:2-80
- Closing
 - Connectivity Test Log window, 0197:2-34, 0197:2-38
 - Retrieve Tables Log window, 0197:2-70, 0197:2-74
 - System Log window, 0197:2-99, 0197:2-103
 - Update Tables Log window, 0197:2-94, 0197:2-98
- clr-disk-stats, 0145:8-20
- clr-imt-stats, 0145:5-407
- cluster destination point code, 0120:2-3
- Cluster DPCs are only valid if the CRMD feature is ON, 0177:2-368
- Cluster DPCs can't inherit A or E linkset types, 0177:2-796
- cluster management
 - ITU network, 0120:2-125
- cluster management when Cluster Routing feature is turned off
 - Cluster Routing and Management Diversity (21.0), 0347:2-71
- cluster point code

Master Index

- adding, 0120:2-142
- changing attributes, 0120:2-161
- cluster routing
 - Cluster Routing and Management Diversity (21.0), 0347:2-70
 - Cluster Routing and Management Diversity feature, 0120:2-119, 0120:2-124
- Cluster Routing and Management Diversity (21.0), 0347:2-67
 - cluster management when Cluster Routing feature is turned off, 0347:2-71
 - cluster routing, 0347:2-70
 - compatibility with ITU network and X.25 gateway, 0347:2-71
 - compatibility with non-cluster routing STPs, 0347:2-70
 - exception lists, 0347:2-67
- Cluster Routing and Management Diversity feature, 0120:2-119
 - cluster routing, 0120:2-124
 - compatibility with non-cluster routing systems, 0120:2-125
 - diversity rules, 0120:2-126
 - example, 0120:2-128
 - when feature is turned off, 0120:2-126
- CMD parameter is not a valid Eagle command, 0177:2-26
- CNAM, 0288:3-22
- CNCF, 0288:3-69
- Cnvrsn Discard
 - CGPA PC alias undefined, 0338:3-824
 - Invalid SCCP element len, 0338:3-829
 - SCCP MSU too large, 0338:3-822
- Cnvrsn Discard - Invalid TCAP element, 0338:3-827
- Cnvrsn Discard - Invalid TCAP element len, 0338:3-828
- Code and Application Data Loading, 0188:5-5, 0190:5-5, 0193:5-7, 0195:4-4
- Coherent, 0188:2-27
- collect=on cannot be specified with 15 min coll operational, 0177:2-601
- Combination of SS7 PC / SSNs exists in X.25 route table, 0177:2-293
- Combination of X.25 addresses exists in X.25 route table, 0177:2-292
- Combination of X.25 addresses not in X.25 route table, 0177:2-287
- Combined total baud rate for all ports cannot exceed 168K, 0177:2-155
- Comm. attributes cannot be entered for OAP terminal, 0177:2-347
- Command
 - EAGLE 5 SAS
 - alw-card, 0197:2-45
 - chg-ftp-serv, 0197:2-52
 - chg-trm, 0197:2-48
 - chg-trm:trm=:all=no, 0197:2-67
 - ent-ftp-serv, 0197:2-52
 - init-card, 0197:2-45, 0197:2-48, 0197:2-49
 - pass:loc=xxxx
 - cmd="netstat -p tcp", 0197:2-124
 - cmd="ping yy.yy.yy.yy", 0197:2-123
 - rst-card, 0197:2-45
 - rtrv, 0197:2-58, 0197:2-75, 0197:2-77
 - rtrv-card, 0197:2-3
 - rtrv-ctrl-feat, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
 - rtrv-feat, 0197:2-56
 - rtrv-ftp-serv, 0197:2-119
 - rtrv-gta, 0197:2-56, 0197:2-61, 0197:2-67

- rtrv-gtt, 0197:2-56, 0197:2-61, 0197:2-67
- rtrv-gttset, 0197:2-56, 0197:2-61, 0197:2-67
- rtrv-gttset, 0197:2-56, 0197:2-61, 0197:2-67
- rtrv-ip-lnk, 0197:2-48, 0197:2-49
- rtrv-secu-dflt, 0197:2-23
- rtrv-trm, 0197:2-47, 0197:2-48, 0197:2-67
- rtrv-tt, 0197:2-56, 0197:2-61, 0197:2-67
- FTRA
 - ftra -c, 0197:2-75, 0197:2-77
- Selecting, 0197:2-60
- command
 - abort_txn, 0348:3-14
 - alw-card, 0193:5-6
 - alw-map-ss, 0193:4-43
 - begin_txn, 0348:3-11
 - chg-feat, 0193:3-3
 - chg-inpopts, 0193:2-11, 0193:2-18, 0193:4-8, 0193:4-40
 - chg-map, 0193:3-9
 - chg-sid, 0188:4-4, 0188:4-11, 0190:4-4, 0190:4-12, 0193:3-3, 0193:4-4, 0193:4-8, 0193:4-12, 0193:4-36
 - chg-stpopts, 0193:5-23
 - connect, 0348:3-8
 - disconnect, 0348:3-10
 - dlt_entity, 0348:3-44
 - dlt_sub, 0348:3-28
 - dlt-csp, 0193:3-11
 - dlt-homern, 0193:3-3
 - dlt-map, 0193:3-9
 - dump_conn, 0348:3-52
 - end_txn, 0348:3-13
 - ent_entityn, 0348:3-36
 - ent_subn, 0348:3-15
 - ent-cspc, 0193:4-8, 0193:4-37
 - ent-homern, 0190:4-37, 0193:3-3, 0193:4-41
 - ent-map, 0193:3-9, 0193:4-8, 0193:4-38
 - ent-srvsel, 0193:3-3, 0193:4-42
 - ent-ss-appl, 0193:4-8, 0193:4-39
 - init-sys, 0188:4-4, 0188:4-12, 0190:4-5, 0190:4-13, 0193:4-5, 0193:4-13
 - rept-stat-epap, 0193:5-2, 0193:5-7
 - rept-stat-sccp, 0193:4-43, 0193:5-2, 0193:5-6
 - rept-stat-sys, 0193:5-6, 0193:5-7, 0195:3-10
 - rtrv_entity, 0348:3-46
 - rtrv_subn, 0348:3-30
 - rtrv-cspc, 0193:4-8, 0193:4-37
 - rtrv-feat, 0193:3-3
 - rtrv-homern, 0190:4-8, 0190:4-37, 0193:4-8, 0193:4-41
 - rtrv-inpopts, 0193:3-11, 0193:4-8, 0193:4-41
 - rtrv-map, 0193:3-9, 0193:4-38
 - rtrv-oap-config, 2970:4-18, 2970:4-30
 - rtrv-sid, 0193:3-3, 0193:4-36
 - rtrv-srvsel, 0193:3-3
 - rtrv-ss-appl, 0193:4-8, 0193:4-39
 - status, 0348:3-51

Master Index

- switchover, 0348:3-48
- upd_entity, 0348:3-40
- upd_subn, 0348:3-22
- Command aborted
 - due to system error, 0177:2-257
- Command Aborted messages, 0145:4-15
- Command Accepted messages, 0145:4-14
- Command action is out of phase with expected procedure, 0177:2-63
- Command already in progress, 0177:2-169
- Command Atomicity, 0348:2-12
- Command cannot be executed on a Telnet terminal, 0177:2-805
- Command cannot be executed on an MGMT terminal, 0177:2-454
- Command cannot be executed on an OAP terminal, 0177:2-333
- Command Class Management (Release 29.0), 0347:2-72
- Command Class Management Controlled Feature
 - Activating, 0142:A-3
 - Deactivating, 0142:A-38
- Command Class Management feature must be enabled, 0177:2-98
- command classes, configuration of, 0145:4-17
- Command Complete
 - Connectivity Test window, 0197:2-34
 - Retrieve Tables window, 0197:2-56, 0197:2-67, 0197:2-68
 - Update Tables window, 0197:2-85, 0197:2-86, 0197:2-89
- Command Completed messages, 0145:4-14
- Command Driven Loopback (CDL), 0338:3-70
- Command driven loopback in progress, 0177:2-791
- Command driven loopback not in progress, 0177:2-792
- command examples, 0190:3-1
- Command Executed messages, 0145:4-14
- Command Failed messages, 0145:4-14
- Command File
 - Editing, 0197:2-2, 0197:2-87
 - Editor window, 0197:2-85, 0197:2-87, 0197:2-88, 0197:2-89
 - File Menu, 0197:2-89
 - File Menu, 0197:2-89
 - Invalid Command, 0197:2-88
 - Field, Update Tables window, 0197:2-81, 0197:2-82, 0197:2-84
 - Selected, Update Tables window, 0197:2-81
 - Stop on error box checked, 0197:2-83
 - Sending to the Selected STP, 0197:2-86
- Command files, sending to the EAGLE 5 SAS, 0197:2-4
- Command In progress, Cannot Close Window message, 0197:2-88
- Command is not supported for IPLIM and SS7IPGW links, 0177:2-623
- Command is not supported for SS7IPGW links, 0177:2-623
- Command Line Interface, 0197:2-1, 0197:2-58, 0197:2-65, 0197:2-66, 0197:2-75
 - Automatic Start, 0197:2-77
 - Manual Start, 0197:2-75
 - UNIX, 0197:2-76
 - Windows, 0197:2-76
- command line interface (lsmsclaa), LSMS, 2339:5-32
- command line, connecting to, 2712:A-3

Command List

- Box, 0197:2-56, 0197:2-58, 0197:2-60, 0197:2-64, 0197:2-65
- Field
 - Retrieve Tables window, 0197:2-58
 - Update Tables window, 0197:2-80
- Side, 0197:2-64
- Command not allowed while in upgrade mode, 0177:2-490
- Command Not Found, 0177:2-633
- Command not supported for non-IPGWx linksets, 0177:2-601
- Command not supported with current IPLIML2 setting, 0177:2-529
- Command not valid for IPGWI, 0177:2-670
- Command not valid for IPLIM, 0177:2-653
- Command not valid for IPLIMI, 0177:2-661
- Command not valid for SS7IPGW, 0177:2-653
- Command Output Changes (22.0), 0347:2-74
- command prompt
 - DOS, 0197:2-75
 - shell, 0197:2-75
- Command Rejected Messages
 - description, 0177:2-2, 0177:3-2
- Command Rejected messages, summary, 0145:4-14
- Command Removed from the Selected Commands Box, 0197:2-65
- Command Response messages, 0145:4-15
- Command Response Timeout, freeing up scroll area, 0177:2-440
- Command Selected to be Removed in the Selected Commands Box, 0197:2-64
- command syntax, specifications, classes, 0190:3-1
- Command will cause system clock outage – Use FORCE=YES, 0177:2-556
- Commands, 0188:2-19, 0188:3-8, 0190:3-10, 0193:3-1, 0195:3-9
 - act-gpl, 0195:3-16
 - alw-card, 0195:3-14
 - alw-map-ss, 0195:3-15
 - chg-ctrl-feat, 0195:3-8
 - chg-feat, 0195:3-2
 - chg-gpl, 0195:3-16
 - chg-gsmopts, 0195:3-5
 - chg-map, 0195:3-15
 - chg-measopts, 0195:3-13, 0195:3-17
 - chg-sid, 0195:3-15
 - chg-ss-appl, 0195:3-16
 - copy-gpl, 0195:3-16
 - dlt-card, 0195:3-14
 - dlt-map, 0195:3-15
 - dlt-sid, 0195:3-15
 - dlt-ss-appl, 0195:3-16
- EAGLE 5 SAS, 0197:2-1, 0197:2-79, 0197:2-80
- EGTT
 - rtrv-gta, 0197:2-56, 0197:2-61, 0197:2-67
 - rtrv-gttset, 0197:2-56, 0197:2-61, 0197:2-67
 - rtrv-gttset, 0197:2-56, 0197:2-61, 0197:2-67
- GTT
 - rtrv-gtt, 0197:2-56, 0197:2-61, 0197:2-67
 - rtrv-tt, 0197:2-56, 0197:2-61, 0197:2-67

Master Index

- enable-ctrl-feat, 0195:3-8
- ent-card, 0195:3-14, 0195:3-16
- ent-map, 0195:3-15
- ent-ss-appl, 0195:3-16
- inh-alm, 0195:3-17
- inh-card, 0195:3-14
- inh-map-ss, 0195:3-15
- Menu, 0197:2-13
- Menu window, 0197:2-58, 0197:2-65, 0197:2-80
- rept-ftp-meas, 0195:3-17
- rept-stat-alm, 0195:3-13
- rept-stat-db, 0195:3-14
- rept-stat-gpl, 0195:3-16
- rept-stat-mps, 0195:3-12
- rept-stat-sccp, 0195:3-11
- rept-stat-sys, 0195:3-10
- rept-stat-trbl, 0195:3-13
- rtrv-card, 0195:3-14
- rtrv-ctrl-feat, 0195:3-9
- rtrv-feat, 0195:3-2
- rtrv-gpl, 0195:3-16
- rtrv-measopts, 0195:3-17
- rtrv-ss-appl, 0195:3-16
- Selecting a Range, 0197:2-61
- Selecting Multiple, 0197:2-62
- unhb-alm, 0195:3-17
- commands
 - about, 0145:4-9
 - Allowed Affected Destination Field Screen (22.0), 0347:2-33
 - alw-map-ss, 2339:8-4
 - command classes, 0145:4-17
 - duplicate parameters in, 0145:4-10
 - ELAP log viewer navigation, 0178:3-70
 - EPAP log viewer navigation, 0183:3-33
 - GR-376 Interface (26.0), 0347:3-29
 - inh-map-ss, 2339:8-4
 - keywords, 0145:4-9
 - Link Fault Sectionalization (21.0), 0347:4-16
 - LNP Measurements Enhancements (25.0), 0347:4-54
 - output banner format, 0145:4-15
 - parameters, 0145:4-9
 - pass: cmd="netstat", 0183:4-14
 - pass: cmd="Ping", 0183:4-14
 - reports and output message types generated by, 0145:4-14
 - rept-stat-alm, 0178:4-4, 0178:4-13, 0183:4-3, 0183:4-13
 - rept-stat-db, 0178:4-9, 0183:4-11
 - rept-stat-epap, 0183:4-11
 - rept-stat-mps
 - description, 0178:4-10
 - report multiple alarm conditions, 0178:4-4, 0183:4-3
 - rept-stat-sccp, 0183:4-9, 2339:8-5
 - rept-stat-trbl, 0178:4-4, 0178:4-12, 0183:4-3, 0183:4-13

- rmv-card, 2339:8-3
- rst-card, 2339:8-3
- Triggerless LNP (EAGLE 24.0), 0347:5-136
- commands, action, 0145:4-9
- commands, entering, 0145:4-9
- commands, functions performed by, 0145:4-9
- Commit button, Update Validation Complete window, 0197:2-85, 0197:2-86
- Common Language Location Identifier, 0212:1-23, 0224:1-22, 0243:1-23, 2970:1-10
- Common Language Location Identifier (CLLI), 0347:1-13
- Communication errors, 0178:B-20
- Communication Module (ACM), 0212:3-9
- Communication Settings are not allowed on TELNET terminals, 0177:2-127
- Communication Subsystem, 0025:3-5, 0212:2-6
- Communications Processor (CP), 0212:3-63
- communications processor (CP), 0212:3-97
- compatibility with ITU network and X.25 gateway
 - Cluster Routing and Management Diversity (21.0), 0347:2-71
- compatibility with non-cluster routing STPs
 - Cluster Routing and Management Diversity (21.0), 0347:2-70
- complete database reload, 0188:2-27, 0190:2-39
- complex network, 0120:3-8
- Complexity, 0178:3-110, 0183:3-140
- complexity checking, 0178:3-108, 0183:3-138
- compliance, regulatory, 0095:2-4, 2969:2-4
- component interaction scenario
 - Support for LSMS Audit Enhancements (EAGLE 26.1), 0347:5-102
- Component Measurements, 0338:4-21
- Components of OEM-Based Products, 0212:2-30
- components, MPS
 - list of hardware, 0025:6-2
 - specifications, 0025:6-11
 - storage, 0212:4-27
- composite clock, 0224:5-82
- Compression is already enabled in the SSH client on the EAGLE 5 SAS - Error code 665, 0197:2-114
- Concerned node table for this group is full, 0177:2-170
- Concerned Signaling Point Codes, 0099:2-40, 0099:2-44, 0099:3-2, 0099:4-2
- concrete floor preparation, 0224:3-20
- concurrent client connections, 0183:2-25, 0348:2-10, 0348:3-8
- Concurrent Logins, 0178:3-109, 0183:3-139
- Concurrent User Logins, 0178:3-109, 0183:3-139
- conditioning number, 0193:2-11
- Conditions That Create an Unstable Loading Mode, 0190:5-7, 0193:5-9, 0195:4-6
- Conditions That Create Unstable Loading Mode, 0188:5-7
- conditions, multiple alarm, 0178:4-4, 0183:4-3
- Config. SCTP csum method alarm cleared, 0338:3-375
- Configuration
 - EIR, 0195:5-2
 - ELAP, 0288:2-40
 - ELAP 5.0, 0288:2-45
 - ELAP Software Overview, 0288:2-33
 - Equipment Identity Register, 0195:5-2
 - Menu - ELAP, 0288:2-44, 0288:2-45

Master Index

- Menu - ELAP 2.x, 0288:2-44
- Procedure - ELAP, 0288:2-56
- Procedure - ELAP 5.0, 0288:2-45
- configuration
 - of command classes, 0145:4-17
 - of terminals and printers, 0145:4-3
- Configuration and Initialization, 0178:5-8, 0183:5-7
- Configuration data checksum alarm cleared, 0338:3-478
- Configuration data checksum mismatch, 0338:3-475
- Configuration Menu, 0178:5-13, 0183:5-14, 0183:5-17
- Configuration menu, 0183:3-2
- configuration menu
 - Change Password, 0178:5-21, 0183:5-24
 - Configure DSM Networks, 0178:5-19, 0183:5-21
 - Configure ELAP Sync Network, 0178:5-18
 - Configure EPAP Sync Network, 0183:5-20
 - Configure Provisioning Network, 0178:5-18, 0183:5-20
 - description, 0178:5-13, 0183:5-14
 - elapconfig login name, 0178:5-13
 - epapconfig, 0183:5-14
 - Exchange Secure Shell Keys, 0178:5-21, 0183:5-24
 - Select Time Zone, 0178:5-20, 0183:5-23, 0183:A-1
- Configuration Menu Conventions, 0178:5-11, 0183:5-13
- configuration parameters, 0193:2-2
- Configuration Procedure, 0178:5-26, 0183:5-34
- configuration procedure, 0178:5-29, 0183:5-36, 0288:2-58
- Configuration record, STP, 0197:2-16, 0197:2-17, 0197:2-18, 0197:2-20, 0197:2-25, 0197:2-27, 0197:2-29, 0197:2-30, 0197:2-31, 0197:2-32, 0197:2-33, 0197:2-38, 0197:2-39, 0197:2-40, 0197:2-41, 0197:2-42, 0197:2-44, 0197:2-45, 0197:2-50
- FTRA 1.0, 0197:2-31
- FTRA 2.0, 0197:2-31, 0197:2-32
- Configuration record, STP - FTRA 1.0
 - Adding, 0197:2-20, 0197:2-21, 0197:2-22, 0197:2-23, 0197:2-24
- Configuration record, STP - FTRA 2.0
 - Adding, 0197:2-20, 0197:2-21, 0197:2-22, 0197:2-23, 0197:2-24
- Configuration Window
 - PuTTY, 0142:B-2, 0142:B-3, 0142:B-5, 0142:B-6, 0142:B-7
- configure
 - customer (provisioning) network IP addresses, 0178:5-18, 0183:5-20
 - customer (provisioning) network netmask, 0178:5-18, 0183:5-20
 - customer network default router address, 0178:5-18, 0183:5-20
 - DSM network IP addresses, 0178:5-19, 0183:5-21
 - ELAP Sync network IP addresses, 0178:5-18
 - EPAP Sync network IP addresses, 0183:5-20
 - remote dial-in serial port, 0178:2-9
- Configure DSM Network menu, 0178:5-17, 0178:5-19, 0183:5-21, 0288:2-48
- Configure DSM Networks, 0178:5-19, 0183:5-21
- configure Eagle point code, 0188:4-4, 0188:4-11, 0190:4-4, 0190:4-12, 0193:4-4, 0193:4-12
- Configure ELAP Sync Network, 0178:5-18
- Configure EPAP Sync Network, 0183:5-20
- Configure NTP Server, 0178:5-24, 0183:5-28
- Configure Provisioning Network, 0178:5-18, 0183:5-20

Configure Provisioning Network menu, 0178:5-17, 0183:5-19
 Configure Record Delay, 0183:3-30
 Configure Sync Network menu, 0178:5-18, 0183:5-20
 configuring
 circular route detection, 0120:3-231
 destination tables, 0120:2-1
 measurements terminal, 0142:4-121
 restore device state option, 0142:4-176
 secondary point codes, 0120:2-63
 TFA/ TFR pacing rate, 0120:3-235
 UIM threshold, 0142:4-116
 Configuring a Linkset for the GSM MAP Screening Feature, 0097:5-43, 0097:5-53, 0097:5-54, 0097:5-55
 Configuring a Mate IPGWx Linkset, 0100:3-55
 Configuring an IPGWx Linkset, 0100:3-35
 Configuring for the CNCF Feature, 0098:14-4
 Configuring for the DTA Feature, 0097:4-15
 configuring INP capability point code, 0193:4-36
 Configuring IP Retransmission Parameters, 0100:3-210
 Configuring the DSM Ethernet Link to the MPS, 0288:2-28
 Configuring the EAGLE 5 SAS, 0197:2-3
 Configuring the ELAP 5.0 Procedure, 0288:2-56
 Configuring the ELAP Procedure, 0288:2-58
 Configuring the Frequency of RST Messages on Low Priority Routes (22.0), 0347:2-75
 Configuring the MTP MAP Screening Feature, 0097:5-37, 0097:5-41, 0097:5-42
 Configuring the Options for Handling TFCs on ITU-I and ITU-N Networks, 0120:3-276, 0120:3-278
 Configuring the Restricted Linkset Option, 0120:3-269, 0120:3-274, 0120:3-275
 Configuring the Triggerless LNP Feature, 0288:3-64
 Configuring Unauthorized Use Warning Message (22.0), 0347:2-77
 Conflicting parameters specified, 0177:2-736
 conflicts with existing entry, 0177:2-438
 Congestion
 Copy Function De-activated, 0338:3-585
 congestion, 0190:5-2, 0195:4-2
 Congestion Abatement Reporting (21.0), 0347:2-79
 congestion indicator, 0188:5-2, 0190:5-2, 0193:5-3, 0195:4-2
 Connect, 0348:3-8
 command, 0348:3-8
 request message, 0348:3-8
 response message, 0348:3-10
 response return codes, 0348:3-10
 connect command, 0348:3-8
 Connect Response, 0193:2-20
 Connect to MMI Port, 0178:3-67, 0183:3-38
 connecting to server command line, 2712:A-3
 Connection
 definition, 0097:2-5, 0347:5-182
 connection
 between PDBA and PDBI client, 0348:3-8
 DSM to ELAP, 0178:2-7
 ELAP Sync network, 0178:2-4, 0178:2-8
 ELAP to DSM, 0178:2-4
 existing ELAP to LSMS, 0178:2-11

Master Index

- idle time, 0348:3-9
- initial ELAP to LSMS, 0178:2-10
- limit of PDBI clients, 0183:2-25, 0348:2-10
- LSMS to ELAP, 0178:2-5, 0178:2-10
- PDBA, dump information for debug, 0348:3-52
- primary LSMS to ELAP, 0178:2-10
- provisioning (customer) network, 0178:2-9
- remote Dialup PPP, 0178:2-9
- security, PDBI, 0348:2-11
- socket-based, 0183:2-25, 0348:2-10
- status, ELAP-to-DSM, 0178:4-16
- Connection adapter type does not match AS adapter type, 0177:2-737
- Connection determination, 0097:2-5
- connection determination
 - X.25/SS7 Gateway Feature (Eagle 20.0), 0347:5-182
- Connection failure due to network outage or the connection was lost due to a faulty SSHD / SFTP server or network - Error code 670, 0197:2-115
- Connection not compatible with SLK IPLIML2 setting, 0177:2-526
- connection status, EPAP-to-DSM, 0183:4-18
- connections
 - concurrent clients, 0183:2-25, 0348:2-10, 0348:3-8
- Connectivity, 0100:2-21, 0100:2-22
- connectivity, 0178:5-29, 0183:5-36, 0188:2-27, 0288:2-58
- Connectivity Test - I procedure, 0197:2-122
- Connectivity Test - II procedure, 0197:2-123
- Connectivity Test Log, 0197:2-33, 0197:2-34, 0197:2-35, 0197:2-36, 0197:2-37
 - Clearing the Display, 0197:2-34, 0197:2-35
 - closing, 0197:2-34, 0197:2-38
 - File Menu, 0197:2-34
 - Print window, 0197:2-36
 - Printing, 0197:2-34, 0197:2-36
 - Save window, 0197:2-37
 - saved file confirmation window, 0197:2-37, 0197:2-38
 - saving to a file, 0197:2-34, 0197:2-37
 - window, 0197:2-33, 0197:2-34, 0197:2-35, 0197:2-36, 0197:2-37, 0197:2-38, 0197:2-46, 0197:2-49, 0197:2-50
 - errors, 0197:2-34
 - no errors, 0197:2-33
- Connectivity Test Log window
 - File Menu, 0197:2-34, 0197:2-35
- Connector Box, 8-Port
 - see 8-Port Connector Box
- conn-imt, 0145:5-409
- connmgr, 0145:9-13
- Conns cannot exist in rkeys with and without rcontext, 0177:2-813
- considerations before installing, 0190:2-47
- Consistent Command Response Conversion (22.2), 0347:2-80
- Consistent Command Response Conversion (24.0), 0347:2-81
- Contents of DSM Status Messages, 0193:5-4
- continual memory validation, DSM daughterboard, 0178:4-6
- Continue message, 0193:2-22
- Continue Response, 0193:2-20

- continuous reload, DSM, 0178:2-18, 0183:2-30
- contract agreements, 0193:1-8
- Control Frame, 0224:4-36
- Control frame, 0224:3-27
- Control Frame (CF), 0212:3-4
- control frame (CF), 0212:3-18
- control number of trapped MSUs, 0188:3-2
- control shelf backplane, 0212:3-21
- Controlled Feature
 - ANSI-ITU-China SCCP Conversion - Activating, 0099:A-36, 0099:A-43, 0099:A-44, 0099:A-45, 0099:A-46
 - IGTTLS - Activating, 0099:A-3
 - IGTTLS - Turning off, 0099:A-14
 - Large System # Links - Enabling, 0097:2-134, 0100:3-98, 0120:3-10
 - XGTT Table Expansion - Enabling, 0099:A-17
 - XMAP Table Expansion - Enabling, 0099:A-27
- Controlled Feature Activation
 - 15 Minute Measurements, 0142:A-26
 - Command Class Management, 0142:A-3
 - Eagle OAM IP Security Enhancements, 0142:A-12
 - IP User Interface, 0142:A-3
 - Network Security Enhancements, 0142:A-3
- Controlled Feature Deactivation
 - Command Class Management, 0142:A-38
 - Eagle OAM IP Security Enhancements, 0142:A-38
 - IP User Interface, 0142:A-38
 - Network Security Enhancements, 0142:A-38
- Controlled Feature is not enabled, 0177:2-529
- controlled features
 - turn on and off, 0145:5-87
- Conv to intl num - Dflt CC not found, 0338:3-890
- Conv to intl num - Dflt MCC not found, 0338:3-892
- Conv to intl num - Dflt MNC not found, 0338:3-893
- Conv to intl num - Dflt NDC not found, 0338:3-891
- conventions
 - document, 2970:1-17
- Conversion Discard
 - Invalid SCCP msg type, 0338:3-823
- Conversion of E.214 MGT to E.212 IMSI, 0188:2-32
- conversion of GN to PIP
 - Calling Name Conversion Facility (CNCF) (23.1), 0347:2-51
- Conversion of MGT to IMSI not possible, 0338:3-895
- Conversion of National/Local Numbers to International Numbers, 0188:2-31
- conversion of PIP to GN
 - Calling Name Conversion Facility (CNCF) (23.1), 0347:2-50
- conversion parameter combinations, 0188:3-4
- converted number sizes, 0188:2-32
- Converting ITU National Point Code Formats, 0145:A-10
- Cooling fan failure, 0338:3-379
- Cooling fan normal, 0338:3-384
- Cooling Fans, 0096:3-16, 2712:3-13
- copies TDM resident database tables, 0188:3-8

Master Index

copper-plated hardware, 0224:4-17

Copy

- RTDB from Remote Mated NE Procedure, 0288:2-115
- RTDB from the Mate ELAP Procedure, 0288:2-108

copy disk procedure, 0142:2-54

Copy Function Activated, 0338:3-586

copy GPL

- Database Management Command Functions (20.0), 0347:2-85

copy measurements

- Database Management Command Functions (20.0), 0347:2-85

COPY must be in ACT1, 0177:2-594

copy RTDB

- from ELAP mate, 2339:3-3
- from standby ELAP on mated network element, 2339:3-4

Copy to or from Transfer Area, 0190:5-17, 0193:5-24

copy-disk, 0145:5-410

copy-fta, 0145:5-413, 0190:5-17, 0193:5-24

copy-gpl, 0145:5-415, 0188:3-12, 0190:3-16, 0193:3-10, 0195:3-16

Copying

- One RTDB from Another RTDB, 0288:2-104
- RTDB from ELAP on Remote Mated NE, 0288:2-105
- RTDB from Mated ELAP, 0288:2-104

copying database from active to standby fixed disk, 0142:2-54

copy-meas, 0145:5-417

copyright information, 0197:2-104

copy-seculog, 0145:5-418

copy-tbl, 0145:8-20

corrected errors, 0096:3-14, 2712:3-11

Corrective Maintenance, 0338:1-3

corrupt alarm, 0188:2-25

corrupted, 0190:3-15, 0193:3-9, 0195:3-14

Corrupted check bytes were detected on the SSH / SFTP client on the EAGLE 5 SAS - Error code 675, 0197:2-116

corrupted database, 0188:5-3, 0188:5-13

corrupted database found, 0190:5-13

Corrupted MAC on input was detected by the SSH / SFTP client on the EAGLE 5 SAS - Error code 676, 0197:2-116

Corrupted pad on input was detected by the SSH / SFTP client on the EAGLE 5 SAS - Error code 677, 0197:2-116

Corrupted RTDB Database Alarm, 0178:2-20, 0183:2-33

Corruption Cross Correction, 0178:2-21, 0183:2-34

Cost Factor on Routing (20.0), 0347:2-82

Could not access active fixed disk, 0177:2-354

Could not access removable disk, 0177:2-352, 0177:2-354

Could not access standby fixed disk, 0177:2-353

Could not block link for testing, 0177:2-324

CPC, 0120:2-92, 0188:4-8, 0190:4-10, 0193:1-11, 0193:4-10, 0195:1-10

CPCA, 0120:2-92

CPCI, 0120:2-92

CPCN, 0120:2-92

CPCTYPE, 0120:2-92

CPCTYPE cannot be specified with NCPC, 0177:2-481

CPCTYPE cannot be specified without CPC, 0177:2-481
 CPCTYPE parameter chg-sid, 0193:4-36
 CPCx has not been provisioned, 0177:2-376
 CPCx must be ANSI if CPCTYPE equals LNP, 0177:2-482
 CPCx must not be ANSI if CPCTYPE is INP or EIR, 0177:2-693
 CPS, 0348:1-10
 CPU, 0348:1-10
 MPS Server specifications, 0212:4-27
 Craftsperson, 0347:3-128
 Create a block entry of IMEIs, 0348:3-55
 Create a new IMSI and associate it with an existing IMEI, 0348:3-56
 Create a single entry IMEI, 0348:3-53
 Create IMEI Data, 0348:3-53
 Create Network Entity, 0348:3-36
 command, 0348:3-36
 PDBI sample session, 0348:4-2
 request message, 0348:3-36
 response message, 0348:3-39
 response return codes, 0348:3-39
 Create Subscription, 0348:3-15
 command, 0348:3-15
 PDBI sample session, 0348:4-3
 request message
 one IMSI and one to eight DNs, 0348:3-16
 one or more DNs on same NE with no IMSI, 0348:3-17
 porting a block of DNs, 0348:3-20
 single IMSI with no DN, 0348:3-15
 response message, 0348:3-22, 0348:3-57, 0348:3-60, 0348:3-64
 response return codes, 0348:3-22, 0348:3-57, 0348:3-60, 0348:3-64
 Creating an EMS Configuration Component, 0288:2-76
 Creating New Java Policy File, 0178:5-8, 0183:5-6
 creation of UIMs
 Thresholding of UIM Messages (EAGLE 25.0), 0347:5-129
 crimp, 0224:4-21
 crimp the lugs, 0224:4-12
 Crimping tool, 0224:4-14
 crimping tool, 0095:6-2, 2969:6-3
 CRITALMINH not set trying to inhibit critical alarms, 0177:2-522
 Critical Alarm, 0212:3-5, 0338:3-3
 Critical alarms, 0183:3-7
 critical alarms, 0145:4-3, 0338:2-7
 Critical Application Alarm, 0183:4-17
 Critical Application Failure(s), 0338:3-484
 Critical customer trouble detected, 0338:3-141
 Critical holdover clock trouble detected, 0338:3-146
 Critical Platform Alarm, 0183:4-16
 Critical Platform Errors, 0096:4-2, 2712:4-2
 Critical Platform Failure(s), 0338:3-483
 critical problem, 0224:1-21, 0243:1-22, 0347:1-12
 CRMD feature must be ON, 0177:2-245
 cron, 0197:2-75, 0197:2-77, 0197:2-78
 CRON FTRA Wrapper Script, 0197:2-78

Master Index

crontab, 0197:2-78
Cross-Connect Panel, 0224:5-20
CRP, 0195:1-10
CSPC broadcast group already exists, 0177:2-167
CSPC broadcast group table is full, 0177:2-167
CSPC group cannot contain both PCN and PCN24 point codes, 0177:2-835
CSPC group does not exist, 0177:2-168
CSPC group network type does not match PC network type, 0177:2-183
CSV file format, 0197:2-1, 0197:2-56, 0197:2-58, 0197:2-66, 0197:2-75, 0197:2-77
CTX parameter is invalid for this card, 0177:2-755
Current, 0188:2-27
Current actv OAM db is not supported for this upgrade, 0177:2-66
Current database not coherent, 0177:2-355
current G-Flex statistics, 0188:2-25
Current ITU-N site id must be disabled for this assignment, 0177:2-341
current revision, 0190:1-8, 0195:1-7
Current set of next elog entries have been overwritten, 0177:2-780
Current stdby OAM db is not supported for this upgrade, 0177:2-66
Current STP
 Selected, 0197:2-43
 FTRA 1.0, 0197:2-43
 FTRA 2.0, 0197:2-44
 Selected: field, 0197:2-41
 Selecting, 0197:2-4, 0197:2-42
customer (provisioning) network
 configure IP addresses, 0178:5-18, 0183:5-20
 description, 0178:2-9
Customer Assistance, 0095:1-7, 0145:1-8, 0188:1-9, 0190:1-8, 0193:1-9, 0195:1-8, 0212:1-20, 0224:1-20, 0243:1-21, 2969:1-7
Customer Care Center, 0097:1-10, 0098:1-10, 0099:1-8, 0100:1-9, 0119:1-11, 0120:1-8, 0142:1-8, 0177:1-8, 0197:2-3, 0197:2-5, 0197:2-48, 0197:2-105, 0197:2-106, 0197:2-107, 0197:2-108, 0197:2-109, 0197:2-110, 0197:2-111, 0197:2-112, 0197:2-113, 0197:2-114, 0197:2-115, 0197:2-116, 0197:2-117, 0197:2-118, 0197:2-119, 0197:2-120, 0197:2-121, 0224:1-21, 0288:1-9, 2970:1-8, 2970:1-10
Customer Contact Center, 0183:1-9, 0188:1-9, 0190:1-9, 0338:1-10
Customer Definable Alarms (20.0), 0347:2-82
customer documentation, 0190:1-7, 0195:1-7
customer network, 0188:2-9, 0190:2-35
 description, 0183:2-10
Customer Provisioning Network, 0188:2-13, 0190:2-41, 0193:2-12, 0193:2-13
Customer Service Report, 0212:1-23, 2970:1-10
Customer Service Report (CSR), 0224:1-22, 0243:1-23, 0347:1-13
Customer Service Request, 0212:1-21, 0224:1-21, 0243:1-22, 0347:1-12, 2970:1-8
Customer Support Center, 0178:1-9, 0183:1-9, 0188:1-9, 0190:1-8, 0193:1-9, 0195:1-8, 0338:1-10, 0348:1-9
Customer Support Centers, 0183:1-9, 0188:1-9, 0338:1-10
Customer trouble cleared, 0338:3-145
Customer trouble detected, 0338:3-144
customer's external provisioning system, 0190:2-35
CWMIN must be less than or equal 16384 for IPGW associations, 0177:2-490
Cyclic Redundancy Check (CRC), 0212:3-97

D

D1G applique, 0190:2-50
 DA, 0348:1-10
 da, 0348:3-38, 0348:3-42
 DA parameter is invalid for this card, 0177:2-759
 dact-alm-trns, 0145:6-2
 dact-cdl, 0145:6-2
 dact-cmd, 0145:6-3
 dact-echo, 0145:6-5
 dact-rstst, 0145:6-8
 dact-slk, 0145:6-9
 dact-user, 0145:6-10
 Daily Availability Measurements, 0338:4-37
 Daily availability reports, 0338:4-37
 Daily LNP System Wide Measurements, 0338:4-64
 Daily Maintenance Measurements, 0338:4-50
 Daily measurement collection in progress, 0177:2-109
 Daily Procedures, 0338:2-15
 Danger icon, 0188:1-8, 0190:1-8, 0193:1-9
 Data, 0348:3-2
 data, 0348:3-31, 0348:3-32, 0348:3-33, 0348:3-34, 0348:3-46
 Data audit already in progress, 0177:2-95
 data broadcast, 0190:2-38
 DATA can only be specified with P486, 0177:2-303
 Data Collection Applications Manual, 0212:1-18, 0243:1-18
 Data Collection Details, 0338:4-10
 Data Collection Subsystem, Collection and Delivery document, 0243:1-19
 Data Communication Equipment (DCE), 0212:3-67
 Data Communications Module, 0212:3-19
 data element, format in response messages, 0348:3-3
 data from customer network, 0190:2-35
 Data missing for <parm> parameter (C<col>), 0177:2-499
 Data Model on Platform, 0348:2-4
 Data Organization, 0348:2-5
 DATA parameter is invalid for this card, 0177:2-756
 data strings, alarm
 see alarm data strings, 0178:4-3, 0183:4-16
 Data Terminal Equipment (DTE), 0212:3-27, 0212:3-67
 Data Terminal Ready (DTR), 0212:3-67
 database, 0193:2-20
 copying from active to standby fixed disk, 0142:2-54
 EIR, 0195:2-10
 GTT, 0193:5-26
 INP, 0193:2-2, 0193:2-4, 0193:5-26
 loading complete, 0193:5-7, 0195:4-4
 look up, 0193:2-11, 0193:2-20
 look-up, 0193:2-18
 look-up failure, 0193:2-18
 MAP, 0193:4-39
 memory requirements, 0193:5-7
 national, 0193:2-16
 provisioned, 0193:2-4, 0195:2-10

Master Index

- provisioning, 0348:2-7
- query, 0193:2-2, 0193:2-7
- records, 0193:2-5, 0195:2-10
- repairing, 0142:2-48
- restoring from backup partition of fixed disk, 0142:2-39
- RTDB, 0193:2-7, 0195:2-12
- search, 0193:2-11
- size requirements, 0193:5-7
- standby, 0348:2-7
- status information, 0195:3-14
- subscriber lookup, 0193:2-20
- verifying, 0142:2-10
- Database action ended - FAIL, 0338:3-754
- Database action ended - OK, 0338:3-753
- Database Administration, 0288:1-2
- database administration, 0190:2-47, 0193:2-17
- Database Administration Manual - System Management, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
- Database Archival, 0338:2-15, 0338:2-20, 0338:2-24, 0338:2-38
- Database Audit, 0025:4-7
- database back-up, 0178:5-26, 0183:5-34
- database backup, 0183:3-47
- Database BACKUP started, 0338:3-751
- database capacity, 0195:2-5
- Database Communications Module, 0025:3-9, 0212:2-12
- Database Communications Module (DCM), 0212:3-9
- Database consistency violation - maintenance required, 0177:2-33
- database corrupt alarm, 0188:2-25, 0190:2-52
- database corrupted, 0188:5-3
- database download, 0188:2-11
- Database Download Starting Record Number, 0193:5-4
- database exception status, 0190:3-15, 0193:3-9, 0195:3-14
- Database in the BLM card must be coherent for an upload, 0177:2-642
- Database Integrity Enhancements (20.0), 0347:2-83
- Database is incoherent, 0177:2-425
- Database Level Number, 0193:5-4
- Database Lookup, 0188:2-33, 0190:2-54, 0190:2-63
- Database maint. in progress - retry later, 0177:2-76
- Database maintenance is required, 0177:2-31
- database maintenance required
 - notification, 2339:3-3
- Database Management Command Functions (20.0), 0347:2-83
 - backup, 0347:2-84
 - copy GPL, 0347:2-85
 - copy measurements, 0347:2-85
 - disk directory, 0347:2-85
 - restore, 0347:2-84
- database management procedures, 0142:2-1
- database memory requirements, 0190:5-5, 0195:4-4
- Database Overview, 0188:2-20
- database partitions
 - overview, 0100:1-11, 0120:1-11, 0142:1-11

database reload, 0188:2-27, 0190:2-39
 Database repair is required, 0177:2-31
 Database RESTORE started, 0338:3-752
 Database Service Module, 0188:2-7
 Database Service Module (Eagle STP), 0025:3-10, 0212:2-14
 Database Services Module, 0348:2-2
 Database tables, retrieving from the EAGLE 5 SAS, 0197:2-4
 database time stamp (DBTS), 2339:4-3
 Database Transport Access (DTA)
 LNP—Impact of LNP on Other Features (22.0), 0347:4-68
 Database Transport Access (DTA) (20.0), 0347:2-85
 Database Unsolicited Output Message Group, 0338:D-27
 database, DSM
 see DSM
 database, PDB
 see PDB
 database, RTDB
 see RTDB
 Database, STP Connection Configuration, 0197:2-16, 0197:2-18, 0197:2-19, 0197:2-20, 0197:2-24,
 0197:2-42
 daughterboard, DSM
 continual memory validation, 0178:4-6
 local memory verification, 0183:4-5
 real-time memory verification, 0183:4-5
 Day is invalid for type-enttype combination, 0177:2-516
 Day must be specified when PERIOD=SPECIFIC, 0177:2-518
 Day out of range, 0177:2-98
 Day-To-Hour Availability Measurements, 0338:4-40
 Day-to-hour availabilty reports, 0338:4-40
 Day-to-Hour Maintenance Measurements, 0338:4-78
 Day-to-hour measurement collection in progress, 0177:2-109
 Day-to-hour measurement data not yet collected, 0177:2-108
 Day-to-hour reports, 0338:4-78
 DB, 0348:1-10
 DB is incoherent (<database>, <disk>, <MASP status>), 0177:2-417
 DB restore has cleared and Disabled PDS, 0338:3-908
 DB status is UPG 1 (<database>, <disk>, <MASP status>), 0177:2-417
 db=mps, 0178:4-10
 DCB, 0190:1-10, 0193:1-11, 0195:1-10, 0348:1-10
 DCBs, 0190:2-40
 DCM, 0188:1-10, 0190:1-10, 0195:1-10, 0212:3-18, 0212:3-19, 0212:3-20, 0212:3-21, 0212:3-28, 0212:3-37,
 0212:6-10, 0224:2-2, 0243:1-37, 0348:1-10
 change features, chg-feat, 0338:3-380, 0338:5-99, 0338:A-90, 2970:3-71, 2970:6-48
 dcm, 0100:3-4
 DCM Applied to LSMS BLM-Based Operations - Removing, 0288:2-23
 DCM card
 Enhanced Bulk Download (25.0), 0347:2-148
 DCM card replacement, 0338:A-42
 DCM LED, 0224:A-8
 DCM parameter set, 0100:3-3
 dcmps, 0100:3-191
 DCMX, 0224:5-25

Master Index

Deactivating

- Command Class Management Controlled Feature, 0142:A-38
- Eagle OAM IP Security Enhancements Controlled Feature, 0142:A-38
- IP User Interface Controlled Feature, 0142:A-38
- Network Security Enhancements Controlled Feature, 0142:A-38

Deactivating the LNP SMS Feature, 0288:3-84

debug command ent-trace, 0188:2-25, 0190:2-51

Debug Commands, 0145:8-1

debug DNS to IP addressing tables, 0188:3-15

debug log, PDBA file format, 0348:2-15

Debug Menu, 0178:3-61, 0183:3-31

DEBUG must be on, 0177:2-496

debug, dump PDBA information for, 0348:3-52

debugging domain name server (DNS) to IP addressing tables, 0190:3-19, 0193:3-14

Decode Eagle MPS Alarm, 0178:3-23, 0183:3-20

Decode MPS Alarm Strings Reference Procedure, 0096:3-20, 0096:3-23, 0096:3-25, 2712:3-18, 2712:3-21

decoded INAP CDPN digits, 0193:2-19

dedicated network, 0188:2-13

Def Router IP Addr must be local to this cards A, B network, 0177:2-579

default

- DMS network IP addresses, 0178:2-7, 0183:2-9

- ELAP Sync network IP addresses, 0178:2-8

- EPAP Sync network IP addresses, 0183:2-9

- router IP address, 0178:5-18, 0183:5-20

- values for ELAP user interface prompts, 0178:5-11

- values for EPAP user interface prompts, 0183:5-13

Default GTT, 0178:3-43

default limit to connections, 0183:2-25, 0348:2-10, 0348:3-8

default network values, 0178:5-26, 0183:5-34, 0288:2-56

default router, 0142:4-138

Default Routing Keys, 0100:2-27

default values, 0178:5-26, 0183:5-34

defcc, 0193:5-23

defmapvr parameter, 0190:2-55

defmcc=, 0188:4-37

defmnc=, 0188:4-37

defndc, 0193:5-23

Degraded Mode - 1 card failed, 0338:3-594

Degraded Mode - multiple cards failed, 0338:3-595

Degraded Mode, Invalid OAM HW config, 0338:3-549

Delete a block of IMEIs, 0348:3-62

Delete a single entry IMEI, 0348:3-61

Delete button, 0197:2-18, 0197:2-27, 0197:2-29, 0197:2-42

Delete DN, 0183:3-66

Delete DN Block, 0183:3-70

delete EIR service selector command, 0195:3-7

Delete Entry from File Transfer Area, 0190:5-17, 0193:5-24

delete G-Flex service selector command, 0190:3-8

delete G-Flex service selectors, 0188:3-7

Delete Group Profile, 0178:3-100

Delete GT option, 0188:2-34

Delete IMSI, 0183:3-62, 0183:3-79, 0183:3-83

- Delete IMSI(s) from the associated IMEI, 0348:3-62
- Delete LNP 10-Digit Telephone Number Subscription, 0178:B-13, 0178:B-14
- Delete LNP Location Routing Number, 0178:B-15
- Delete LNP Subscription, 0178:3-51
- Delete Network Entity, 0183:3-74, 0348:3-44
 - command, 0348:3-44
 - request message, 0348:3-44
 - response message, 0348:3-45
 - response return codes, 0348:3-45
- Delete NPA-NXX Records, 0178:3-54
- Delete Override GTT Records, 0178:3-57
- Delete Split NPANXX, 0178:B-15
- Delete STP Data window, 0197:2-42
- Delete Subscription, 0348:3-28
 - command, 0348:3-28
 - request message
 - delete DN block, 0348:3-29
 - delete IMSI, 0348:3-28
 - delete single DN, 0348:3-28
 - response message, 0348:3-29
 - response return codes, 0348:3-29
- Delete the IMSI from all IMEIs, 0348:3-63
- Delete UI Group Profile, 0183:3-130
- Delete UI User, 0183:3-120
- Delete User screen, 0178:3-91
- Deleting an EMS Configuration Component, 0288:2-86
- Deleting an STP Configuration Record, 0197:2-41
- Deleting the CdPA GT Digits, 0188:2-34
- delivery agent, 0188:5-12
- dependencies
 - TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-150
- Derivations for N1 and N2
 - Preventive Cyclic Retransmission (PCR) (EAGLE 20.0), 0347:5-32
- Description
 - Retrieve Tables window, 0197:2-58
 - Update Tables window, 0197:2-80
- description
 - G-Flex C7 Relay (26.3), 0347:3-13
 - INP Number Normalization (26.3), 0347:3-86
- Description of PDBI, 0348:2-1
- Design Overview and System Layout, 0193:2-4, 0195:2-9
- design, ELAP overall, 0178:2-4
- design, EPAP overall, 0183:2-4
- Dest IP Address already exists for this card, 0177:2-576
- Dest IP Address cannot be local to this cards A, B network, 0177:2-576
- Dest IP Address does not exist for this card, 0177:2-576
- Dest IP Address is invalid, 0177:2-575
- destination, 0120:2-2
- Destination address must be a full point code, 0177:2-370
- Destination card invalid, 0177:2-96
- destination commands
 - 4000 Routesets (23.0), 0347:2-6

Master Index

Destination disk capacity equals 0, 0177:2-355
Destination disk is unformatted, 0177:2-351
Destination element
 definition, 0097:2-5, 0347:5-182
Destination location must specify the standby fixed disk, 0177:2-353
Destination location must specify the standby removable disk, 0177:2-353
Destination parameter not supported, 0177:2-65
destination point code, 0120:2-3, 0188:2-19, 0190:2-47, 0193:2-17
 adding, 0120:2-191
 changing, 0120:2-226
 removing, 0120:2-214
destination point codes, 0188:4-4, 0188:4-8, 0190:4-4, 0190:4-10, 0193:4-4, 0193:4-10
Destination Routing Address, 0193:2-22
destination tables
 configuring, 0120:2-1
Destination's alias PCs must be full PCs, 0177:2-372
detecting and reporting problems, 0096:3-11, 2712:3-8
Determination of MAP Phase, 0190:2-55
Determine LIM, MIM, and MPL Changeout Time, 0338:A-16
DEV state does not allow alarms to be inhibited, 0177:2-412
DEV type is not supported by specified location, 0177:2-829
dev=dlk parameter, 0195:3-17
Device alarm inhibit table not accessible, 0177:2-523
device control blocks, 0190:2-40
DFLTACT can not be ATIERR unless OPCODE=71, 0177:2-681
DFLTACT must be specified as FORWARD, DUPLICATE, or DUPDISC, 0177:2-339
DGTS, 0288:4-5, 0288:4-20, 0288:4-22, 0288:4-23, 0288:4-25, 0288:4-26, 0288:4-27, 0288:4-28, 0288:4-29
DGTS parameter must be 3 or 6-10 digits, 0177:2-448
DHCP, 0097:6-6
dial-up modem, 0190:5-17, 0193:5-24
Dial-Up PPP Network, 0188:2-16, 0190:2-44, 0193:2-15
Dialup PPP network
 description, 0178:2-9, 0183:2-10
 IP addresses, 0178:2-9
 modem, 0178:2-9
 remote dial-in port, 0178:2-9
Different Database Level Alarm Repetition When UAM 34 Has Been Raised
 Miscellaneous Command Adjustments (26.1), 0347:4-121
Digits Valid, 0288:3-32
Dimensions and Weight, 0212:4-23
diode board (FAP), 0338:2-6
diode boards, removing, 0338:2-9
diode jumper, 0338:2-8
diode testing, 0338:2-8
DIP switch settings, 0212:B-9, 0224:5-110
direct interface to networks, 0188:2-2
Direct Memory Access (DMA), 0212:3-68, 0212:3-97
direct routing, 0190:2-6
disabled states
 National Spare Network Indicator Support (EAGLE 22.2), 0347:4-155
 National Spare Network Indicator Support (EAGLE 24.0), 0347:4-157
Disabling Bulk Load, 0288:2-139

Disabling the Gateway Screening Redirect Function, 0097:4-51
 Disallow Simultaneous Logins Sessions with the Same User ID (21.0), 0347:2-93
 disaster recovery, 0096:2-16, 2712:2-14
 DISCARDTFCI Option, 0120:3-276, 0120:3-277
 DISCARDTFCN Option, 0120:3-276, 0120:3-277
 disc-imt, 0145:6-11
 Disconnect, 0348:3-10
 command, 0348:3-10
 request message, 0348:3-10
 response message, 0348:3-11
 response return codes, 0348:3-11
 disconnect command, 0348:3-10
 disconnect power
 fan assembly, 0338:5-93, 0338:A-83, 2970:6-42
 Disk Access, 0096:3-15, 2712:3-12
 Disk access error - fixed disk, 0177:2-102
 Disk Coherency Tests (20.0), 0347:2-93
 Disk Copy Fixed to Fixed (20.0), 0347:2-94
 disk directory
 Database Management Command Functions (20.0), 0347:2-85
 disk drive, replacement procedure, 0096:5-11, 2712:5-9
 disk drives, removable cartridge, 0145:4-2
 disk measurement status unreadable, 0338:3-711
 Disk space, 0197:2-2
 disk systems, 0025:4-10
 disks, MPS Server SCSI, 0212:4-27
 disp-bip, 0145:8-22
 disp-bp, 0145:8-23, 0188:3-13
 disp-disk-dir, 0145:8-26
 disp-disk-stats, 0145:8-29
 disp-fta-dir, 0145:6-12, 0190:5-17, 0193:5-24
 Display, 0100:3-156
 Clearing
 Connectivity Test Log, 0197:2-34, 0197:2-35
 Retrieve Tables Log, 0197:2-70, 0197:2-71
 System Log, 0197:2-99, 0197:2-100
 Update Tables Log, 0197:2-94, 0197:2-95
 display card status, rept-stat-card
 IPGWI, 0100:3-117, 0100:3-132, 0100:3-156
 IPLIM, 0100:3-132, 0100:3-156
 SS7IPGW, 0100:3-117, 0100:3-132, 0100:3-156
 Display Configuration menu, 0178:5-16, 0183:5-18
 display current IP host information, 0188:4-22, 0188:4-31, 0190:4-22, 0190:4-31, 0193:4-22, 0193:4-31
 display current link parameters, 0188:4-24, 0188:4-33, 0190:4-24, 0190:4-33, 0193:4-24, 0193:4-33
 Display External NTP Server, 0178:5-24, 0183:5-28, 0183:5-30
 display feature status, 0188:3-4
 Display File Transfer Area, 0190:5-17, 0193:5-24
 display G-Flex service selectors, 0188:3-7
 Display Inhibited Alarms (Release 29.0), 0347:2-94
 Display Release Levels, 0178:3-22, 0183:3-20
 display signaling link status, rept-stat-slk
 IPGWI, 0100:3-116, 0100:3-119, 0100:3-131, 0100:3-136, 0100:3-154, 0100:3-158, 0100:3-178,

Master Index

0100:3-200, 0100:3-306, 0100:3-329, 0100:3-431, 0100:3-441
IPLIM, 0100:3-119, 0100:3-131, 0100:3-136, 0100:3-154, 0100:3-431, 0100:3-441
SS7IPGW, 0100:3-116, 0100:3-119, 0100:3-131, 0100:3-136, 0100:3-154, 0100:3-158, 0100:3-178,
0100:3-179, 0100:3-200, 0100:3-201, 0100:3-307, 0100:3-309, 0100:3-329, 0100:3-333, 0100:3-431,
0100:3-441, 0188:4-20, 0190:4-20, 0193:4-20
display STP and G-Flex DB status and level per DSM, 0188:3-8
displaying
 OAP configuration, 2970:4-18, 2970:4-30
 terminal configuration, rtrv-trm, 2970:4-16, 2970:4-28
Displaying an Existing STP Configuration Record, 0197:2-25
disp-lba, 0145:8-30
disp-mem, 0145:8-32, 0188:3-13
Distributing
 LNP Database after LSMS-Based Operation or RTDB Copy, 0288:2-134
 RTDB LNP Database to DSMs Procedure, 0288:2-135
 RTDB, Returning to Normal Service, 0288:2-135
dlt_entity command, 0348:3-44
dlt_sub command, 0348:3-28
dlt-acg-mic, 0145:6-13
dlt-acg-noc, 0145:6-14
dlt-appl-rtkey, 0145:6-14, 0145:6-15
dlt-appl-sock, 0145:6-20
dlt-asp, 0145:6-21
dlt-assoc, 0145:6-22
dlt-bp, 0145:8-34, 0188:3-13
dlt-card, 0145:6-23, 0188:3-12, 0188:4-7, 0188:4-28, 0190:3-16, 0190:4-7, 0190:4-28, 0193:3-9, 0193:4-7,
0193:4-28
dlt-csp, 0193:3-11
dlt-cspc, 0145:6-24, 0193:3-11
dlt-dstn, 0145:6-27
dlt-e1, 0145:6-31
dlt-fta, 0145:6-32, 0190:5-17, 0193:5-24
dlt-ftp-serv, 0142:4-148, 0145:6-34
dlt-gsmmap-scrn, 0145:6-35
dlt-gsms-opcode, 0145:6-36
dlt-gsmssn-scrn, 0145:6-37
dlt-gta, 0145:6-38
dlt-gtcnv, 0145:6-39
dlt-gtt, 0145:6-42
dlt-gttset, 0145:6-44
dlt-gttset, 0145:6-45
dlt-gws-redirect, 0145:6-46
dlt-homern, 0145:6-48, 0193:3-3
dlt-home-smsc, 0145:6-47
dlt-ip-host, 0145:6-48, 0188:3-14, 0190:3-18, 0193:3-12
dlt-ip-node, 0145:6-49
dlt-ip-rte, 0145:6-51
dlt-lbp, 0145:6-53
dlt-lnp-lrn, 0145:6-54
dlt-lnp-npanxx, 0145:6-55
dlt-lnp-serv, 0145:6-57
dlt-lnp-sp, 0145:6-58

- dlt-lnp-sub, 0145:6-59
- dlt-ls, 0145:6-61
- dlt-map, 0145:6-62, 0193:3-9
- dlt-mrn, 0145:6-64
- DLTPFX, 0193:1-11
- dltpfx, 0193:2-11
- DLTPFX must not be specified, when NCDPNPFX is NONE, 0177:2-88
- dlt-prefix, 0145:6-71
- dlt-pstn-pres, 0145:6-73
- dlt-rmt-appl, 0145:6-74
- dlt-rte, 0145:6-76
- dlt-scr-aftpc, 0145:6-80
- dlt-scr-blkdpc, 0145:6-84
- dlt-scr-blkopc, 0145:6-88
- dlt-scr-cdpa, 0145:6-92
- dlt-scr-cgpa, 0145:6-95
- dlt-scr-destfld, 0145:6-99
- dlt-scr-dpc, 0145:6-103
- dlt-scr-isup, 0145:6-106
- dlt-scr-opc, 0145:6-107
- dlt-scrset, 0145:6-114
- dlt-scr-sio, 0145:6-111
- dlt-scr-tt, 0145:6-113
- dlt-sid, 0195:3-15
- dlt-slk, 0119:3-33, 0145:6-116
- dlt-spc, 0145:6-118
- dlt-split-npa, 0145:6-120
- dlt-srvsel, 0145:6-121, 0193:3-3
 - Delete G-Flex Service Selector Command, 0188:3-7
- dlt-ss-appl, 0145:6-122, 0195:3-16
- dlt-subnetid, 0145:6-123
- dlt-t1, 0145:6-124
- dlt-tt, 0145:6-125
- dlt-uim-acthresh, 0145:6-128
- dlt-user, 0145:6-129
- dlt-vendid, 0145:6-129
- dlt-x25-dstn, 0145:6-130
- dlt-x25-rte, 0145:6-131
- DN, 0193:1-11, 0348:1-10
- dn, 0348:3-17, 0348:3-18, 0348:3-24, 0348:3-25, 0348:3-28, 0348:3-31
- DN Block menu, 0183:3-68
- DN Blocks, 0348:2-5, 0348:2-21
- DN menu, 0183:3-64
- DN range, 0348:2-5
- DNS, 0190:3-19, 0193:3-14
- document
 - acronyms, 2970:1-18
 - conventions, 2970:1-17
 - references, 2970:1-17
- Document Conventions, 0288:1-3, 0288:2-4
- document part number, 0190:1-8, 0193:1-8, 0195:1-7
- documentation

Master Index

admonishments, 0095:1-7, 0145:1-9, 0178:1-9, 0183:1-9, 0348:1-8, 2969:1-6
delivery, 0095:1-6, 2969:1-6
packaging, 0095:1-6, 0178:1-8, 0183:1-8, 0348:1-8, 2969:1-6
part numbers, 0178:1-8, 0183:1-8, 0348:1-7
updates, 0095:1-6, 0178:1-8, 0183:1-8, 0348:1-7, 2969:1-6
Documentation Admonishments, 0188:1-8, 0190:1-8, 0195:1-8
Documentation Packaging, Delivery, and Updates, 0177:1-8, 0188:1-7, 0190:1-7, 0193:1-8, 0195:1-7, 0212:1-20
documentation set, 0100:1-8, 0193:1-2, 0348:1-2
documents
 Alarms Reference and User's Manual, 0212:1-18, 0243:1-18
 Data Collection Applications Manual, 0212:1-18, 0243:1-18
 Feature Notice, 0212:1-17, 0243:1-18
 hardware and installation, 0212:1-18, 0243:1-19
 list of Sentinel, 0212:1-17, 0243:1-18
 Release Notice, 0212:1-18, 0243:1-18
 System Administrator's Guide, 0212:1-18, 0243:1-18
 technical reference documents, 0212:1-19, 0243:1-19
 User's Manual, 0212:1-18, 0243:1-18
dollies, 0224:3-9
Dolly Heavy-Duty Frame, 0224:3-7
Domain indicated by GTIx must match that of existing TT, 0177:2-471
Domain must be SS7 if SPC is specified, 0177:2-647
DOS, 0197:2-7
DOS command prompt, 0197:2-75
Double, 0212:3-19
down, 0190:5-2, 0195:4-2
download, 0193:2-9, 0195:2-13
download files from STP, 0190:5-17, 0193:5-24
downloads in progress, 0188:5-3
DPADDR cannot be entered with DR/DA, 0177:2-302
DPC, 0188:4-4, 0188:4-8, 0190:4-4, 0190:4-10, 0193:1-11, 0193:4-4, 0193:4-10, 0338:F-8
dpc, 0097:2-25, 0100:3-252
DPC - SS status changed, 0338:3-424
DPC assigned to SS7 address does not exist in SS7 domain, 0177:2-291
DPC assigned to SS7 address has no SS7 routes, 0177:2-292
DPC assigned to X.25 address has no SS7 routes, 0177:2-291
DPC assigned to X.25 address does not exist in X.25 domain, 0177:2-290
DPC cannot be defined as a remote application IPC, 0177:2-454
DPC defined as linkset APC, 0177:2-133
DPC is allowed, 0338:3-392
DPC is already being used, 0177:2-132
DPC is prohibited, 0338:3-394
DPC is referenced by SCCP in the MRN table, 0177:2-432
DPC is referenced by SCCP's MAP table, 0177:2-369
DPC is restricted, 0338:3-393
DPC must be a cluster DPC or cluster member, 0177:2-50
DPC must be removed from X.25 route tbl, 0177:2-255
DPC must be specified as wildcard when used with STAT, 0177:2-386
DPC must have at least one route defined, 0177:2-277
DPC must not specify a cluster route for IPGWAPC link set, 0177:2-650
DPC parameter must be specified, 0177:2-521

DPC parameter needed with MODE=FULL, 0177:2-158
 DPC Quantity
 Changing, 0120:2-23
 DPC subsystem has been deleted, 0338:3-413
 DPC Subsystem is Abnormal, 0338:3-421
 DPC subsystem is allowed, 0338:3-410
 DPC subsystem is blocked, 0338:3-411
 DPC Subsystem is Normal, 0338:3-420
 DPC subsystem is prohibited, 0338:3-412
 DPC Subsystem is prohibited and blocked, 0338:3-419
 dpci, dpcn parameters, 0188:4-9, 0190:4-10, 0193:4-10
 DR parameter is invalid for this card, 0177:2-758
 DRA, 0193:1-11
 DRAM, 0212:3-91
 DRANAI and DRANAIV must not be specified together, 0177:2-694
 DRANP and DRANPV must not be specified together, 0177:2-694
 DRARM parameter is invalid for this card, 0177:2-758
 DRARM parameter is invalid for this processor, 0177:2-758
 drill bit, masonry, 0095:4-3, 2969:4-3
 drive, tape
 see tape drive
 drklog, 0145:9-20
 drkq, 0100:3-122
 Drop down list
 STP Name, 0197:2-18, 0197:2-25
 FTRA 1.0, 0197:2-25, 0197:2-27
 FTRA 2.0, 0197:2-25, 0197:2-26, 0197:2-27, 0197:2-28
 DRTN, 0288:4-3, 0288:4-5, 0288:4-13, 0288:4-14, 0288:4-15, 0288:4-16, 0288:4-18, 0288:4-19, 0288:4-20,
 0288:4-22, 0288:4-23, 0288:4-25, 0288:4-26, 0288:4-27, 0288:4-28, 0288:4-29
 DS0 4-link monitor configuration window, 0212:B-6
 DS0 and NEI link elements do not support non-latching tests, 0177:2-389
 DS0 monitor applique, 0212:B-6
 DS0A, 0212:3-68
 DSA Key Fingerprint, 0197:2-48, 0197:2-49
 DSCS bridge amplifier
 description, 0212:B-9
 DIP switch settings, 0212:B-9
 front view, 0212:B-9
 installing, 0212:B-10
 limitations, 0212:B-11
 part number, 0212:B-11
 rear view, 0212:B-10
 DSM, 0188:1-10, 0188:2-7, 0190:1-10, 0193:1-11, 0195:1-10, 0212:3-21, 0212:3-37, 0224:2-2, 0224:5-25,
 0243:1-37, 0348:1-10
 Adding, 0288:2-17
 allowing card, 2339:8-3
 connection to ELAP, 0178:2-7
 continuous reload, 0178:2-18, 0183:2-30
 database level, 0178:4-5, 0183:4-4
 database levels and reloading, 0183:2-30
 daughterboard continual memory validation, 0178:4-6
 daughterboard local memory verification, 0183:4-5

Master Index

- daughterboard real-time memory verification, 0183:4-5
- DSM-ELAP Link status alarms, 0178:4-16
- DSM-EPAP Link status alarms, 0183:4-18
- Ethernet Link to the MPS - Configuring, 0288:2-28
- incoherent or out-of-sync database, 0183:2-8
- incremental loading model, 0178:2-17, 0183:2-29
- inhibiting, rmv-card, 2339:8-3
- memory capacity status reporting, 0178:4-7, 0183:4-9
- motherboard verification, 0183:4-4
- network troubleshooting reports, 0183:4-14
- primary, 0178:2-21, 0178:4-2, 0183:2-34, 0183:4-2
- provisioning description, 0178:2-17
- provisioning model, 0183:2-29
- provisioning task description, 0183:2-27
- provisioning task overview, 0183:2-8
- reload, 0178:2-17, 0183:2-29
- status of connection to ELAP, 0178:4-16
- status of connection to EPAP, 0183:4-18
- Status Requests, 0178:4-4, 0183:4-3
- system hardware verification, 0178:4-5, 0183:4-4
- system status reporting, 0183:4-8
- UAMs, 0178:4-16, 0183:4-18
- unstable loading mode, 0178:4-7, 0183:4-6
- verifying status, 2339:8-5
- warm restart, 0178:2-18
- DSM (Database Service Module) Cards, 0188:2-10, 0190:2-36
- DSM (Database Services Module), 0193:2-8, 0195:2-12
- DSM accepts DB updates, 0188:5-3
- DSM Application Data Loading, 0193:5-8
- DSM Applique Memory Verification, 0188:2-23, 0190:2-50, 0193:5-5
- DSM card failure, 0188:5-12
- DSM card polls, 0188:2-9, 0190:2-35
- DSM cards, 0193:2-3, 0193:2-8, 0195:2-8, 0195:2-12
- DSM Code Loading, 0188:5-5, 0190:5-5, 0193:5-7, 0195:4-5
- DSM Database Alarms, 0188:5-14, 0190:5-13
- DSM Database Audit Alarm, 0188:5-13, 0190:5-13, 0195:4-15
- DSM Database Levels and Reloading, 0188:2-27, 0190:2-39
- DSM Failure, 0188:5-12, 0190:5-12
- DSM Hardware-Related Alarms, 0188:5-12, 0190:5-12
- DSM Info menu, 0183:3-92
- DSM insufficient memory, 0188:5-11
- DSM LED, 0224:A-8
- DSM List, 0348:4-16
- DSM Main Board Verification, 0188:2-23, 0190:2-50, 0193:5-5
- DSM Memory Capacity Status Reporting, 0188:5-4, 0190:5-4, 0193:5-7, 0195:4-4
- DSM Memory Size, 0188:5-3, 0190:5-3, 0193:5-4, 0195:4-3
- DSM multicast hardware, 0188:2-27, 0190:2-39
- DSM Networks, 0188:2-14, 0190:2-43, 0193:2-14
- DSM networks
 - configure IP addresses, 0178:5-19, 0183:5-21
 - description, 0178:2-4, 0178:2-7, 0183:2-4, 0183:2-9
 - IP addresses, 0178:2-7, 0183:2-9

DSM Provisioning and Reload, 0188:2-26, 0190:2-38
 DSM provisioning module, 0193:2-4, 0195:2-10
 DSM Reload Requirements, 0188:2-27, 0190:2-39
 DSM Reloading Model, 0188:2-26, 0190:2-38
 DSM status, 0188:5-3, 0190:5-2, 0195:4-2
 DSM Status Message Fields, 0188:5-3, 0190:5-3, 0195:4-3
 DSM Status Messages – When Sent, 0188:5-3, 0190:5-3, 0193:5-3, 0195:4-3
 DSM Status Reporting to EPAP, 0190:5-3, 0195:4-3
 DSM Status Reporting to the EPAP, 0195:4-3
 DSM Status Request message, 0188:5-3
 DSM Status Requests, 0190:5-2, 0193:5-3, 0195:4-2
 DSM/EPAP IP link alarms, 0190:3-14, 0193:3-7
 DSM's are required when LNP and VGTT are ON, 0177:2-715
 DSM-based boards, 0188:5-1, 0190:5-1, 0195:4-1
 DSM-EPAP Link, 0188:5-12, 0190:5-12, 0193:5-16, 0195:4-13
 DSM-EPAP link status, 0188:5-12
 DSM-VxWorks-SCCP application, 0188:2-10, 0190:2-36
 DSTN address must be a full, network or cluster PC, 0177:2-383
 DSTN5000 feature must be enabled, 0177:2-516
 DSX, 0224:5-12, 0224:5-18
 DUAL OAP configuration is needed for LNP feature, 0177:2-482
 dual provisioning, 0190:2-35
 dual-slot DCM card, 0347:5-82
 dual-slot STC, 0097:6-4, 0097:6-7, 0097:6-8, 0097:6-19, 0097:6-21, 0097:6-23
 Dump Connections, 0348:3-52
 command, 0348:3-52
 request message, 0348:3-53
 response message, 0348:3-53
 response return codes, 0348:3-53
 dump_conn command, 0348:3-52
 Duplicate ACTs in different slots are not allowed, 0177:2-593
 Duplicate packets, 0197:2-125
 duplicate parameters in command, 0145:4-10
 Duplicate Point Code Support, 0183:2-13
 DUR=PERM can only be specified with a 486 processor, 0177:2-303
 DURAL must be specified within 0.995959 or 999999, 0177:2-333
 Duration Index, 0288:4-2, 0288:4-3, 0288:4-4, 0288:4-5, 0288:4-13, 0288:4-18, 0288:4-20, 0288:4-21, 0288:4-27, 0288:4-28
 DV, 0288:3-22, 0288:3-23, 0288:3-24, 0288:3-25, 0288:3-29, 0288:3-30, 0288:3-31, 0288:3-32, 0288:3-33, 0288:3-36, 0288:3-37, 0288:3-62
 DV must be SCCP when SERV is a user defined type, 0177:2-485
 DV must be TCAP when SERV is WNP, AIN, PCS, IN or LNPQS, 0177:2-486
 DVD-ROM
 specification, 0212:4-27
 Dynamic database is inconsistent, 0338:3-608, 0338:3-609
 Dynamic Host Configuration Protocol, 0097:6-6
 dynamic random access memory (DRAM), 0212:3-91
 Dynamic rtkeys + SRKQ exceed max allowed rtkey limit, 0177:2-655
 DYNRTK feature must be enabled to perform this operation, 0177:2-657

E

- E.164, 0188:2-1, 0188:2-5, 0188:2-22, 0188:2-30, 0188:2-32, 0193:2-10
- E.164 entity address, 0188:2-3
- E.164 MSISDN number (DN), 0190:3-2, 0193:3-16
- E.164 MSISDN number (MSISDN), 0188:3-2
- E.164 number, 0188:3-2
- E.164 numbers, 0190:2-47
- E.212, 0188:2-1, 0188:2-30, 0188:2-32
- E.212 IMSI, 0188:3-2
- E.212 IMSI number (IMSI), 0188:3-2
- E.212 International IMSI, 0188:2-32
- E.212 number, 0188:2-4
- E.212 numbers, 0188:2-21
- E.214, 0188:2-22, 0188:2-32
- E.214 (E.212) Routing Example - Location Updating, 0188:2-4
- E.214 MGT, 0188:2-32
- E.214 numbers, 0188:2-21
- E1, 0212:3-19, 0212:3-21, 0212:3-104, 0212:3-109, 0224:5-118, 0224:5-120, 0224:5-121, 0224:5-123, 0224:5-125, 0224:5-129, 0224:A-6, 0224:A-11, 0224:A-12, 0243:A-3, 0243:A-5, 0338:A-22, 0338:A-23
- E1 4-link Monitor Configuration window, 0212:B-5
- E1 Administration and Alarms (26.3), 0347:2-104
 - E1 Operation within an EAGLE, 0347:2-104
 - Eagle Application Support for E1, 0347:2-105
- E1 ATM High Speed Link (Release 28.1), 0347:2-110
- E1 ATM High Speed Link (Release 28.1) (IP7 Release 6.0), 0347:2-110
- E1 backplane, 0120:A-8, 0212:3-106, 0212:3-110, 0224:5-123, 0224:5-128, 0224:5-130
- E1 Backplanes, 0224:5-121
- E1 Card, 0224:5-119
- E1 card
 - clocking options, 0120:A-9, 0120:B-8
 - configured as channel card, 0120:A-5, 0120:B-4
 - configured as E1 card, 0120:A-5, 0120:B-4
 - determining configuration, 0120:A-8, 0120:B-7
- E1 card location is unequipped, 0177:2-736
- E1 interface, 0224:5-122
- E1 Interface Kit, 0224:5-122
- E1 is assigned to card, 0177:2-725
- E1 monitor applique, 0212:B-4
- E1 Operation within an EAGLE
 - E1 Administration and Alarms (26.3), 0347:2-104
- E1 Patch Cables, 0224:5-129
- E1 patch cables, 0224:5-122
- E1 Port test command in progress, 0177:2-558
- E1 Port test command not in progress, 0177:2-558
- E1 specified by E1LOC / E1PORT is using CAS, TS=16 not allowed, 0177:2-728
- E1/T1 Configuration Form, 0224:5-132
- E1/T1 MIM, 0097:6-7, 0224:5-81, 0224:5-82, 0224:5-125
- E1/T1 Multi-Channel Interface, 0347:2-114
- E1/T1 Multi-Channel Interface Module (Release 28.0), 0347:2-114
- E1/T1 Multi-Channel Interface Module (Release 28.0) (IP7 Release 6.0), 0347:2-114
- E1/T1 Port greater than 2 unavailable, 0177:2-548
- E1-ATM, 0097:6-7

E1PORT specified by E1LOC is not equipped, 0177:2-727
 E1-T1 MIM, 0224:1-10
 E5IS must be on, 0177:2-705
 EADDR cannot be specified without SADDR, 0177:2-679
 EADDR must be greater than SADDR, 0177:2-678
 EADDR shouldn't be specified when SADDR = *, 0177:2-807
 EAGLE 5 SAS, 0195:1-1, 0212:1-6, 0224:1-5
 Telnet terminals, 0197:2-18, 0197:2-48, 0197:2-67
 UIM - Unsolicited Information Message, 0197:2-48, 0197:2-49, 0197:2-67
 EAGLE 5 SAS Card
 GPSM-II, 0197:2-3
 IPSM, 0197:2-3
 MCAP, 0197:2-3
 TDM, 0197:2-3
 EAGLE 5 SAS chg-ftp-serv command, 0197:2-52
 EAGLE 5 SAS chg-trm:trm=:all=no command, 0197:2-67
 EAGLE 5 SAS clock and date
 setting, 0142:4-3
 EAGLE 5 SAS command
 alw-card, 0197:2-45
 chg-ftp-serv, 0197:2-52
 chg-trm, 0197:2-48
 chg-trm:trm=:all=no, 0197:2-67
 ent-ftp-serv, 0197:2-52
 init-card, 0197:2-45, 0197:2-48, 0197:2-49
 pass:loc=xxxx
 cmd="netstat -p tcp", 0197:2-124
 cmd="ping yy.yy.yy.yy", 0197:2-123
 rst-card, 0197:2-45
 rtrv, 0197:2-58, 0197:2-75, 0197:2-77
 rtrv-card, 0197:2-3
 rtrv-ctrl-feat, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
 rtrv-feat, 0197:2-56
 rtrv-ftp-serv, 0197:2-119
 rtrv-gta, 0197:2-56, 0197:2-61, 0197:2-67
 rtrv-gtt, 0197:2-56, 0197:2-61, 0197:2-67
 rtrv-gttset, 0197:2-56, 0197:2-61, 0197:2-67
 rtrv-gttset, 0197:2-56, 0197:2-61, 0197:2-67
 rtrv-ip-lnk, 0197:2-48, 0197:2-49
 rtrv-secu-dflt, 0197:2-23
 rtrv-trm, 0197:2-47, 0197:2-48, 0197:2-67
 rtrv-tt, 0197:2-56, 0197:2-61, 0197:2-67
 EAGLE 5 SAS command files
 sending, 0197:2-4
 EAGLE 5 SAS commands, 0193:3-1, 0197:2-1, 0197:2-79, 0197:2-80
 EAGLE 5 SAS configuration, 0197:2-3
 EAGLE 5 SAS database tables
 retrieving, 0197:2-4
 EAGLE 5 SAS documentation set, 0193:1-2
 EAGLE 5 SAS DSM databases, 0193:2-3
 EAGLE 5 SAS EGTT commands
 rtrv-gta, 0197:2-56, 0197:2-61, 0197:2-67

Master Index

- rtrv-gttssel, 0197:2-56, 0197:2-61, 0197:2-67
- rtrv-gttset, 0197:2-56, 0197:2-61, 0197:2-67
- EAGLE 5 SAS ent-ftp-serv command, 0197:2-52
- EAGLE 5 SAS Feature
 - EGTT, 0197:2-56
 - FTP Retrieve and Replace, 0197:2-3
 - GTT, 0197:2-56
 - IP User Interface, 0197:2-3
- EAGLE 5 SAS feature
 - Eagle OA&M IP Security Enhancements, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
- EAGLE 5 SAS GTT commands
 - rtrv-gtt, 0197:2-56, 0197:2-61, 0197:2-67
 - rtrv-tt, 0197:2-56, 0197:2-61, 0197:2-67
- EAGLE 5 SAS maintenance terminal, 0193:2-17
- EAGLE 5 SAS Manual, Database Administration Manual - System Management, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
- EAGLE 5 SAS mated application table, 0193:2-17
- EAGLE 5 SAS pass:loc=xxxx
 - cmd="netstat -p tcp" command, 0197:2-124
 - cmd="ping yy.yy.yy.yy" command, 0197:2-123
- EAGLE 5 SAS procedure
 - Activating Controlled Features, 0197:2-3
 - Activating the Eagle OA&M IP Security Enhancements Controlled Feature, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
- EAGLE 5 SAS Provisioning, 0097:6-6
- EAGLE 5 SAS Public Host Key Fingerprint, 0197:2-45, 0197:2-46, 0197:2-48, 0197:2-50
- EAGLE 5 SAS Public Key Fingerprint, 0197:2-19, 0197:2-48, 0197:2-49
- EAGLE 5 SAS release 30.2 or greater, 0197:2-3, 0197:2-19, 0197:2-24
- EAGLE 5 SAS rtrv-card command, 0197:2-3
- EAGLE 5 SAS rtrv-ctrl-feat command, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
- EAGLE 5 SAS rtrv-feat command, 0197:2-56
- EAGLE 5 SAS rtrv-ftp-serv command, 0197:2-119
- EAGLE 5 SAS rtrv-gta command, 0197:2-56, 0197:2-61, 0197:2-67
- EAGLE 5 SAS rtrv-gtt command, 0197:2-56, 0197:2-61, 0197:2-67
- EAGLE 5 SAS rtrv-gttssel command, 0197:2-56, 0197:2-61, 0197:2-67
- EAGLE 5 SAS rtrv-gttset command, 0197:2-56, 0197:2-61, 0197:2-67
- EAGLE 5 SAS rtrv-secu-dflt command, 0197:2-23
- EAGLE 5 SAS rtrv-trm command, 0197:2-67
- EAGLE 5 SAS rtrv-tt command, 0197:2-56, 0197:2-61, 0197:2-67
- Eagle Agents
 - Manually Verifying and Restarting, 0288:2-140
- Eagle Application Support for E1
 - E1 Administration and Alarms (26.3), 0347:2-105
- Eagle Application Support for E1 (26.3)
 - alarms, 0347:2-108
 - enhanced commands, 0347:2-106
 - hardware requirements, 0347:2-106
 - limitations, 0347:2-109
 - new commands, 0347:2-106
 - upgrade considerations, 0347:2-109
- Eagle can only accept messages of 450 or fewer bytes (C<col>), 0177:2-509
- Eagle chg-db

- Change Database Commands, 0188:3-8, 0190:3-10
- Eagle chg-feat Commands, 0188:3-3, 0190:3-3, 0195:3-2
- Eagle commands, 0195:3-1
- Eagle Commands for EIR Feature, 0195:3-2
- Eagle Commands for INP, 0193:3-1
- Eagle documentation set, 0348:1-2
- Eagle DSM Audit of MPS Databases, 0178:2-19, 0183:2-32
- Eagle DSM databases, 0195:2-8
- Eagle Duplicate Point Code feature, 0183:2-13
- Eagle EIR Commands, 0195:3-1
- Eagle EIR Service Selector Commands, 0195:3-6, 0195:3-8
- Eagle EIR System Options Commands, 0195:3-3
- Eagle G-Flex Commands, 0188:3-1
- Eagle G-Flex Service Selector Commands, 0188:3-5
- Eagle G-Flex Subsystem Number Commands, 0188:3-8
- Eagle G-Flex System Options Commands, 0188:3-4
- Eagle G-Port Commands, 0190:3-1
- Eagle G-Port Service Selector Commands, 0190:3-6, 0190:3-9
- Eagle G-Port System Options Commands, 0190:3-5
- Eagle Initiated OAP User Interface (24.0), 0347:2-118
 - LNP Service commands, 0347:2-119
 - OAP commands, 0347:2-118
- Eagle Initiated OAP User Interface (24.0)
 - auditing the OAP database, 0347:2-119
- Eagle LNP Application Processor
 - see ELAP
- Eagle LNP Functional Capabilities, 0025:4-4
- Eagle maintenance terminal, 0190:2-47
- Eagle mated application table, 0188:2-18
- Eagle Measurement Reports (20.0), 0347:2-119
- Eagle OA&M IP Security Enhancements feature, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
- Eagle OAM IP Security Enhancements Controlled Feature
 - Activating, 0142:A-12
 - Deactivating, 0142:A-38
- EAGLE Provisioning Application Processor, 0193:2-3, 0193:2-5
- Eagle Provisioning Application Processor, 0195:2-8, 0195:2-11
- Eagle Provisioning Application Processors, 0188:2-7, 0190:2-35
- Eagle Release 31.5 UAM/ UIM Changes, 0338:3-37
- Eagle Release 33.0 UAM/ UIM Changes, 0338:3-37
- Eagle rept-stat-db
 - Report Database Status, 0188:3-8, 0190:3-10
- Eagle STP, 0025:1-4, 0190:1-1, 0212:1-6, 0224:1-9, 0224:1-10
- Eagle STP and IP7 Secure Gateway Systems, 0025:3-2, 0212:2-3
- Eagle Support for Integrated Sentinel, 0097:1-3, 0097:6-2, 0097:6-4, 0097:6-10, 0097:6-11, 0097:6-13, 0097:6-14, 0097:6-19, 0097:6-22, 0097:6-27, 0347:2-120
- Eagle Support for Integrated Sentinel (Release 28.0), 0347:2-120
- Eagle Terminal Database Commands, 0188:3-3, 0190:3-3
- Eagle terminal interfaces, 0188:3-2
- EAGLE-Based Products, 0212:1-6
- Ear protectors, 0224:3-20
- ear protectors, 0095:4-3, 2969:4-3
- earthquake resistance, 0095:2-6, 0212:6-4, 2969:2-6

Master Index

EBI, 0212:3-53
Echo capability not applicable on originating terminal, 0177:2-518
Echo is not set for this port, 0177:2-98
Echo not allowed for telnet terminals, 0177:2-160
EDCM, 0212:3-19, 0212:3-81, 0224:2-2, 0243:1-37
Edit button, Update Validation Complete window, 0197:2-85, 0197:2-86, 0197:2-87, 0197:2-88
Edit menu
 FTP-Based Table Retrieve Application, 0197:2-16, 0197:2-80
Editing a Command File, 0197:2-87
edn, 0348:3-20, 0348:3-26, 0348:3-29, 0348:3-31
EDSM Status Requests, 0188:5-2
Effect of Corrupted record received from MPS, 0178:2-21, 0183:2-33
EGMS feature requires DSM card with VSCCP APPL or better, 0177:2-679
EGTA cannot be specified without GTA, 0177:2-167
EGTA must be greater than or equal to GTA, 0177:2-173
EGTT cannot be ON if any SCCP card has a 486 processor, 0177:2-572
EGTT commands
 EAGLE 5 SAS
 rtrv-gta, 0197:2-56, 0197:2-61, 0197:2-67
 rtrv-gttset, 0197:2-56, 0197:2-61, 0197:2-67
 rtrv-gttset, 0197:2-56, 0197:2-61, 0197:2-67
EGTT Feature, 0197:2-56
EGTT must be ON before this command can be entered, 0177:2-565
EGTT Set commands
 Enhanced GTT (26.0), 0347:2-156
eid, 0348:3-46
Eight-Port Connector Box, 0212:4-55
EILA, 0097:6-7, 0212:3-18, 0212:3-19, 0212:3-21, 0212:3-37
EILA (P/N 870-2049-01, 0224:2-2, 0224:A-6, 0243:1-37, 0243:A-3, 0338:A-22
eimsi, 0348:3-34
EIR, 0195:2-2, 0195:5-2, 0195:5-5, 0195:5-13, 0195:5-14, 0195:5-15, 0195:5-16, 0195:5-18, 0195:5-19,
 0195:5-23, 0195:5-24, 0195:5-25, 0195:5-27, 0195:5-29, 0195:5-30, 0195:5-33, 0195:5-34, 0195:5-35,
 0195:5-36, 0195:5-37, 0195:5-39, 0195:5-40, 0195:5-41, 0195:5-42, 0195:5-43, 0195:5-45, 0195:5-48,
 0195:5-51, 0195:5-53, 0195:5-54, 0195:5-56, 0195:5-58, 0195:5-59, 0195:5-60
 Call Flow, 0195:2-4
 Call Flows, 0195:2-3
 capability, 0195:2-13
 Capability Point Codes, 0195:2-14
 capability point codes, 0195:5-2
 Configuration, 0195:5-2
 Considerations, 0195:2-3
 Data Collection, 0195:2-15
 Encoding Errors, 0195:2-15
 Equipment Identity Register, 0195:2-2
 List Log File, 0195:2-16
 List Log Format, 0195:2-17
 log file, 0195:2-16
 Log File Serviceability, 0195:2-16
 network, 0195:2-3
 Protocol, 0195:2-13
 subsystem, 0195:2-14
EIR Activation Unsuccessful due to Insufficient Database, 0195:4-11

EIR Alarms, 0195:4-12
 Card Related MPS Alarms, 0195:4-15
 DSM-EPAP Link, 0195:4-13
 MPS (EPAP) Alarms, 0195:4-13
 Subsystem Alarms, 0195:4-17
 EIR and INP are mutually exclusive, 0177:2-763, 0177:2-765
 EIR and LNP are mutually exclusive, 0177:2-766
 EIR Configuration, 0195:5-1
 EIR Data Initialization, 0195:4-5
 EIR Enabled, but Database Exceeds DSM Memory, 0195:4-10
 EIR Enabled, but DSM Memory Insufficient for Database, 0195:4-10
 EIR Enabled, but DSM Memory Less Than 1 GB, 0195:4-9
 EIR Enabled, but DSM Not Connected to EPAP, 0195:4-10
 EIR Enabled, Normal Operating Sequence, 0195:4-9
 EIR feature cannot be enabled if ASM / TSM is present, 0177:2-766
 EIR feature must be enabled, 0177:2-769
 EIR feature must be ON, 0177:2-603
 EIR Measurements, 0195:4-22
 EIR MSU Handler
 Data Collection, 0195:2-15
 Encoding Errors, 0195:2-15
 EIR Not Enabled at First, but then Activated on DSM, 0195:4-11
 EIR Not Enabled, DSM Running in TSM Emulation, 0195:4-9
 EIR Protocol
 Check_IMEI Message Handling, 0195:2-15
 Messages for Local Subsystems, 0195:2-14
 MTP and SCCP Management to Support EIR, 0195:2-14
 EIR Status Reporting, 0195:4-4
 EIR Subsystem Alarms, 0195:4-17
 EIR Subsystem is available, 0338:3-572
 EIR Subsystem is disabled, 0338:3-570
 EIR Subsystem is not available, 0338:3-569
 EIR subsystem is offline in database, 0177:2-769
 EIR Subsystem is removed, 0338:3-573
 EIR Subsystem normal, card(s) abnormal, 0338:3-571
 EIR system options (gsmopts), 0195:3-3
 EIR System Status Reports, 0195:4-3
 EIR UAMs, 0195:4-12
 Card Related MPS Alarms, 0195:4-15
 DSM-EPAP Link, 0195:4-13
 MPS (EPAP) Alarms, 0195:4-13
 Subsystem Alarms, 0195:4-17
 EIR UIMs, 0195:4-18
 Either ALIASN or ALIASN24, not both, for destination, 0177:2-549
 Either BUS or Location (not both) must be specified, 0177:2-720
 Either INP or GPORT feature must be ON, 0177:2-714
 Either LOC or APPL (not both) must be specified, 0177:2-106
 Either LSN or LOC and LINK must be specified, 0177:2-115
 Either PLNP or WNP Features must be ON, 0177:2-684
 Either TLNP or ISUP NP with EPAP must be enabled, 0177:2-828
 Either TYPE or TTN must be specified, 0177:2-196
 Eject CD menu, 0178:3-76, 0178:5-22, 0183:3-46, 0183:5-25

Master Index

ELAP

- Able/Unable states for provisioning, 0178:2-10
- Active/Standby
 - relation to LSMS connection, 0178:2-10
 - roles, 0178:2-5
 - switchover, 0178:2-5
- alarms
 - see also alarms
 - application, 0178:4-14
 - DSM-ELAP Link status, 0178:4-16
 - in rept-stat-mps report, 0178:4-11
 - RTDB Audit, 0178:4-16
 - UAMs, 0178:4-14
- change login name passwords, 0178:5-21
- Configuration and Initialization, 0288:2-40
- Configuration feature, 0288:2-4, 0288:2-124, 0288:2-128, 0288:2-129
- Configuration Menu, 0288:2-44, 0288:2-45
- Configuration Procedure, 0288:2-56, 0288:2-58
- connection to DSMs, 0178:2-4, 0178:2-7
- definition, 0178:2-2
- DSM UAMs, 0178:4-16
- existing connection to LSMS, 0178:2-11
- general description, 0178:2-3
- GUI interface, accessing, 2712:A-1
- initial connection to LSMS, 0178:2-10
- initialization, 0178:5-8
- log viewer navigation commands, 0178:3-70
- LSMS connection, 0178:2-5
- Maintenance Blocks, 0178:4-2
- MPS Server memory to support, 0212:4-27
- overall design, 0178:2-4
- Software Configuration Overview, 0288:2-33
- status of connection to DSM, 0178:4-16
- supports LNP 48 Million Numbers feature, 0025:6-2
- Sync network
 - configure IP addresses, 0178:5-18
 - description, 0178:2-4, 0178:2-8
 - IP addresses, 0178:2-8
- text interface, accessing, 2712:A-6
- time zone, 0178:5-20
- user interface
 - error message format, 0178:5-12
 - list of error messages, 0178:3-112
- user interface menus
 - configuration, 0178:5-13
 - default values for prompts, 0178:5-11
 - Escape key to exit operations, 0178:5-11
 - responding to prompts, 0178:5-11
- User Interfaces - Overview, 0288:2-33
- user login names
 - access configuration menu, 0178:5-13
 - elapconfig

- for ELAP initialization, 0178:5-8
- Workstation - Setting Up, 0288:2-33
- ELAP 2.x
 - Configuration Menu, 0288:2-44
- ELAP 5.0
 - Configuration and Initialization, 0288:2-45
 - Configuration Procedure, 0288:2-45, 0288:2-56
- ELAP architecture does not support LNP quantity requested, 0177:2-817
- ELAP Areas, 0178:3-6
- ELAP Configuration feature, 0288:2-124
- ELAP Error Messages, 0178:3-112
- ELAP menu, 0178:3-12
- ELAP must be available to verify LNP quantity support, 0177:2-818
- ELAP User Interfaces, 0178:3-2
- elapconfig, 0178:5-13
- elapconfig login name
 - access configuration menu, 0178:5-13
 - for ELAP initialization, 0178:5-8
- electric shock, 0095:6-2, 0224:4-14, 2969:6-2
- ELEI is only valid for cluster destinations, 0177:2-367
- ELEI is only valid if the CRMD feature is ON, 0177:2-368
- Element Management System Alarm Monitor (EMSALM), 0145:4-8
- elements overwritten, 0338:3-757
- elevation requirements, 0095:2-6, 2969:2-6
- Embedded OAP (24.0), 0347:2-128, 0347:2-134
 - asynchronous maintenance modem, 0347:2-138
 - EOAP Connector, 0347:2-133
 - EOAP Processor Card, 0347:2-131
 - EOAP-to-Eagle Interface, 0347:2-140
 - EOAP-to-LSMS Interface, 0347:2-141
 - EOAP-to-SEAS Interface, 0347:2-141
 - fans, 0347:2-139
 - Hard Drive and CD-ROM Drive, 0347:2-133
 - hardware requirements, 0347:2-130
 - Power Supply card, 0347:2-132
 - Serial card, 0347:2-132
 - Third-Party software, 0347:2-139
 - User Console, 0347:2-138
- Embedded Operations Applications Processor, 0025:3-18, 0212:2-18
- embossing dies, 0224:4-16
- Emergency Response, 0195:1-9
- Emergency response, 0097:1-10, 0098:1-10, 0099:1-9, 0100:1-9, 0119:1-12, 0120:1-9, 0142:1-9, 0288:1-10
- emergency response, 0212:1-23, 0224:1-22, 0243:1-23, 0347:1-13, 2970:1-10
- emergency response (Tekelec Technical Services), 2339:1-14
- EMS, 0193:1-11
 - Configuration Component, 0288:2-76
 - Configuration Component - Creating, 0288:2-76
 - Configuration Component - Deleting, 0288:2-86
 - Configuration Component - Modifying, 0288:2-82
 - Configuration Component - Viewing, 0288:2-84
 - Routing, 0288:2-88
 - Modify, 0288:2-88

Master Index

- View, 0288:2-91
- EMS Agent available, 0338:3-471
- EMS Agent unavailable, 0338:3-469
- EMSALM terminal type, 0142:4-56
- EMSALM terminals, 0145:4-8
- enable G-Flex feature, 0188:4-35, 0190:4-35
- enable INP feature, 0193:4-35
- enable-ctrl-feat, 0145:6-131
- enabled states
 - National Spare Network Indicator Support (EAGLE 22.2), 0347:4-155
 - National Spare Network Indicator Support (EAGLE 24.0), 0347:4-156
- Enabling a Permanent or Temporary Key, 0100:6-3
- Enabling the EIR Feature, 0195:5-13
- Enabling the Large System # Links Controlled Feature, 0097:2-134, 0100:3-98, 0120:3-10
- Enabling the XGTT Table Expansion Feature, 0099:A-17
- Enabling the XMAP Table Expansion Feature, 0099:A-27
- ENCODE = AMI not currently supported, 0177:2-749
- encryption keys for secure shell, 0178:5-21, 0183:5-24
- End Cabinet Alarm Indicators, 0338:3-8
- End node internal point codes, 0100:3-4
- end panels, 0212:3-6
- End Transaction, 0348:3-13
 - command, 0348:3-13
 - request message, 0348:3-13
 - response message, 0348:3-14
 - response return codes, 0348:3-14
- end_txn command, 0348:3-13
- endchar, 0348:3-9
- Ending bucket cannot be less than starting bucket, 0177:2-443
- Enforce password complexity checking, 0178:3-108, 0183:3-138
- Enhanced Bulk Download (25.0), 0347:2-144
 - administration, 0347:2-147
 - alarms, 0347:2-145
 - changed commands, 0347:2-151
 - DCM card, 0347:2-148
 - hardware requirements, 0347:2-144
 - limitations, 0347:2-151
 - minimum LSMS/Eagle Ethernet facility, 0347:2-149
 - new commands, 0347:2-150
 - new GPLs, 0347:2-147
 - OAM reboot during bulk download, 0347:2-150
 - serviceability, 0347:2-147
 - upgrade considerations, 0347:2-150
- Enhanced Bulk Download already in progress, 0177:2-642
- Enhanced Bulk Download not in progress, 0177:2-642
- Enhanced Commands
 - Security Log Increase (EAGLE 26.05), 0347:5-73
- enhanced commands
 - CDU for DSM (26.05), 0347:2-63
 - Eagle Application Support for E1 (26.3), 0347:2-106
 - INAP-based Number Portability (INP) (26.05), 0347:3-83
 - INP Number Normalization (26.3), 0347:3-86

ITU Duplicate Point Code Routing (26.05), 0347:3-157
 ITU Gateway Measurements Enhancements (26.05), 0347:3-165
 Multiple Point Code Support (EAGLE 26.05), 0347:4-149
 Stand-alone Eagle G-Flex Relay Function, 0347:3-16
 Two-Point IPLIMx (Eagle 27.1), 0347:5-159
 Weighted SCP Load Balancing (Eagle 27.2), 0347:5-176
 Enhanced Database Status Reports (20.0), 0347:2-151
 Enhanced GPL Management (25.0), 0347:2-152
 alarms, 0347:2-154
 changed commands, 0347:2-152
 Upgrade Considerations, 0347:2-152
 Enhanced GSM MAP Screening
 Activating, 0097:5-24, 0097:5-32, 0097:5-33, 0097:5-34, 0097:5-35, 0097:5-36
 Enhanced GSM Map Screening feature must be enabled, 0177:2-809
 Enhanced GSM Map Screening feature must be ON, 0177:2-806
 Enhanced GSM Map Screening must be ON, 0177:2-761
 Enhanced GTT (26.0), 0347:2-154
 Assumptions/Limitations, 0347:2-157
 Changed Commands, 0347:2-156
 EGTT Set Commands, 0347:2-156
 GTA Commands, 0347:2-156
 new commands, 0347:2-155
 protocol details, 0347:2-155
 upgrade considerations, 0347:2-155
 Enhanced Link Diagnostics (22.0), 0347:2-157
 Enhanced Load Distribution (21.0), 0347:2-158
 Enhancement to Backup TFR/TCR Procedures (21.0), 0347:2-163
 Enhancement to GTT Failure Messages (25.0), 0347:2-164
 Enhancements to GWS Reject Messages (25.0), 0347:2-166
 SEAS Compliance, 0347:2-166
 Ent-/Chg-GTT Failure Message Shows Overlap
 Miscellaneous Command Adjustments (26.1), 0347:4-121
 ent_entity command, 0348:3-36
 ent_sub command, 0348:3-15
 ent-acg-mic, 0145:6-137
 ent-acg-noc, 0145:6-139
 ent-appl-rtkey, 0145:6-140
 ent-appl-sock, 0145:6-146
 ent-as, 0145:6-149
 ent-asp, 0145:6-150
 ent-assoc, 0145:6-151
 ent-bp, 0145:8-35, 0188:3-13, 0190:3-17, 0193:3-11
 ent-card, 0145:6-155, 0188:3-12, 0188:4-5, 0188:4-6, 0188:4-7, 0188:4-15, 0188:4-22, 0188:4-30, 0188:5-8,
 0190:3-16, 0190:4-5, 0190:4-6, 0190:4-7, 0190:4-16, 0190:4-21, 0190:4-30, 0190:5-8, 0193:3-9, 0193:4-5,
 0193:4-6, 0193:4-7, 0193:4-16, 0193:4-22, 0193:4-30, 0193:5-11, 0195:3-16, 0195:4-8
 ent-cspc, 0145:6-163, 0193:3-11, 0193:4-8, 0193:4-37
 ent-dlk, 0145:6-166
 ent-dstn, 0145:6-167, 0188:4-5, 0188:4-13, 0190:4-5, 0190:4-14, 0193:4-5, 0193:4-14
 ent-e1, 0145:6-179
 enter destination PC, 0188:4-13, 0190:4-14, 0193:4-14
 enter DPC, 0188:4-13, 0190:4-14, 0193:4-14
 enter G-Flex service selectors, 0188:4-8, 0188:4-37, 0190:4-8, 0190:4-38

Master Index

enter INP service selectors, 0193:4-9
enter linkset, 0188:4-14, 0190:4-15, 0193:4-15
Enter param VENIDLEN, or params VENDID, VENDNUM and VENDTYPE, 0177:2-827
Enter params SUBNETIDLEN or paramrs SUBNETID and SUBNETNUM, 0177:2-827
entering
 init-sys command, 0188:4-4, 0188:4-12, 0190:4-5, 0190:4-13, 0193:4-5, 0193:4-13
Entering a Global Title Translation to a Non-Mated Application without Adding the Application as
 Mated Application (22.0), 0347:2-168
Entering an STP Name, 0197:2-29
entering commands, 0145:4-9
Entering forced simplex mode, 0338:3-97
Enterprise 450
 servers, 0025:4-10
ent-ftp-serv, 0142:4-145, 0145:6-183
ent-ftp-serv EAGLE 5 SAS command, 0197:2-52
ent-gsmmap-scrn, 0145:6-185
ent-gsms-opcode, 0145:6-191
ent-gsmssn-scrn, 0145:6-195
ent-gta, 0145:6-196
ent-gtcnv, 0145:6-202
ent-gtt, 0145:6-206
ent-gttset, 0145:6-213
ent-gttset, 0145:6-215
ent-gws-redirect, 0145:6-216
ent-homern, 0145:6-220, 0190:4-37, 0193:3-3, 0193:4-41
ent-home-smsc, 0145:6-219
ent-ip-host, 0145:6-221, 0188:3-14, 0188:4-6, 0188:4-7, 0188:4-22, 0188:4-31, 0190:3-18, 0190:4-6,
 0190:4-7, 0190:4-22, 0190:4-31, 0193:3-12, 0193:4-6, 0193:4-7, 0193:4-22, 0193:4-31
ent-ip-node, 0145:6-222
ent-ip-rte, 0145:6-224
entity data, 0190:2-47
Entity must be specified when Entity type is specified, 0177:2-795
Entity Number, 0188:3-2
entity number, 0188:2-29
entity PC, 0188:2-18
entity point codes, 0188:2-18
Entity Point Codes and Routes, 0188:2-19, 0190:2-47, 0193:2-17
ent-lbp, 0145:6-226
ent-lnp-lrn, 0145:6-228
ent-lnp-npanxx, 0145:6-231
ent-lnp-serv, 0145:6-234
ent-lnp-sp, 0145:6-236
ent-lnp-sub, 0145:6-236
ent-ls, 0145:6-240, 0188:4-5, 0188:4-14, 0190:4-5, 0190:4-15, 0193:4-5, 0193:4-15
ent-map, 0145:6-250, 0188:4-5, 0188:4-18, 0190:4-5, 0190:4-18, 0193:3-9, 0193:4-5, 0193:4-8, 0193:4-18,
 0193:4-38
ent-mrn, 0145:6-256
ent-na, 0145:6-263
ent-pstn-pres, 0145:6-264
Entries in static route key table cannot exceed SRKQ, 0177:2-655
entries in the Internet Protocol host table, 0190:3-18, 0193:3-12
ent-rmt-appl, 0145:6-266

ent-rte, 0145:6-268, 0188:4-5, 0188:4-17, 0190:4-5, 0190:4-17, 0193:4-5, 0193:4-17
 Entry already exists for this application at this IP Address, 0177:2-334
 Entry already exists for this application at this priority, 0177:2-335
 Entry already exists with specified GTII-TT-NP(V)-NAI(V)-SSN, 0177:2-698
 Entry already exists with specified GTIN24-TT-NP(V)-NAI(V)-SSN, 0177:2-735
 Entry already exists with specified GTIN-TT-NP(V)-NAI(V)-SSN, 0177:2-698
 Entry already exists with specified GTI-TT-NP(V)-NAI(V)-SSN, 0177:2-694
 Entry being deleted is referenced by a GSM Map Screen entry, 0177:2-677
 Entry does not exist with specified GTII-TT-NP(V)-NAI(V)-SSN, 0177:2-699
 Entry does not exist with specified GTIN24-TT-NP(V)-NAI(V)-SSN, 0177:2-834
 Entry does not exist with specified GTIN-TT-NP(V)-NAI(V)-SSN, 0177:2-700
 Entry does not exist with specified GTI-TT-NP(V)-NAI(V)-SSN, 0177:2-695
 Entry is already defined as the STP Options DefCC, 0177:2-584
 ent-scr-aftpc, 0145:6-272
 ent-scr-blkdpc, 0145:6-276
 ent-scr-blkopc, 0145:6-282
 ent-scr-cdpa, 0145:6-287
 ent-scr-cgpa, 0145:6-291
 ent-scr-destfld, 0145:6-296
 ent-scr-dpc, 0145:6-300
 ent-scr-isup, 0145:6-304
 ent-scr-opc, 0145:6-306
 ent-scrset, 0145:6-317
 ent-scr-sio, 0145:6-311
 ent-scr-tt, 0145:6-315
 ent-serial-num, 0145:6-319
 ent-shlf, 0145:6-320
 ent-sid, 0145:6-321
 ent-slk, 0145:6-323, 0188:4-5, 0188:4-16, 0190:4-5, 0190:4-16, 0193:4-5, 0193:4-16
 ent-spc, 0145:6-337
 ent-split-npa, 0145:6-340
 ent-srvsel, 0145:6-341, 0188:4-8, 0188:4-37, 0190:4-8, 0190:4-38, 0193:3-3, 0193:4-9, 0193:4-42
 Enter EIR Service Selectors Command, 0195:3-6
 Enter G-Flex Service Selectors Command, 0188:3-6
 Enter G-Port Service Selectors Command, 0190:3-7
 ent-ss-appl, 0145:6-345, 0193:4-8, 0193:4-39, 0195:3-16
 ent-subnetid, 0145:6-346
 ent-t1, 0145:6-348
 ent-trace, 0145:8-41, 0188:2-25, 0188:3-1, 0190:2-51, 0190:3-1, 0193:3-15
 ent-tt, 0145:6-350
 ent-ttmap, 0145:6-352
 enttype=lsonismt, 0338:4-117
 ent-user, 0145:6-353
 ent-vendid, 0145:6-357, 0145:7-672
 ent-x25-dstn, 0145:6-359
 ent-x25-rte, 0145:6-360
 ENUM must be greater or equal to mate parameter SNUM, 0177:2-777
 ENUM range does not match SNUM
 1-999 or 1000-1499, 0177:2-778
 ENUM requires an SNUM as its mate parameter, 0177:2-777
 Environment variable
 FTRA_HOME, 0197:2-1, 0197:2-7, 0197:2-9

Master Index

- JRE_HOME, 0197:2-1, 0197:2-7, 0197:2-9
- system, 0197:2-7, 0197:2-9
- user, 0197:2-7, 0197:2-9
- environmental requirements, 0095:2-5, 0212:6-4, 2969:2-5
- EOAM, 0195:5-16
- EOAP, 0025:1-6, 0193:1-11, 0212:1-7, 0224:2-3, 0224:A-15, 2970:3-57
 - administration, 0025:8-12
 - alarms, 2970:4-20
 - checksums and alarms, 2970:4-14
 - overview, 2970:1-2
 - serial and Ethernet cabling diagram, 0338:5-129, 2970:6-83
 - shelf, 2970:3-20
 - update configuration, 2970:4-23, 2970:4-34
 - updating, 2970:4-13
- EOAP A
 - shutting down, 0338:5-65, 0338:5-85, 0338:5-87, 0338:5-122, 2970:6-12, 2970:6-32, 2970:6-35, 2970:6-40, 2970:6-59, 2970:6-75, 2970:6-84
- EOAP connectors
 - Embedded OAP (24.0), 0347:2-133
- EOAP Hardware Troubleshooting, 0338:5-5
- EOAP power cables, 2970:3-36
- EOAP Processor Card
 - Embedded OAP (24.0), 0347:2-131
- EOAP provisioning
 - installing UAL software, 2970:4-4
- EOAP shelf
 - flange, 0338:5-72, 2970:6-20
 - how to remove, 0338:5-71, 2970:6-18
 - mounting brackets, 0338:5-72, 2970:6-20
 - tools and equipment, 2970:3-12, 2970:3-19, 2970:3-57, 2970:3-61, 2970:3-62
- EOAP/OAP Support of HSOP Protocol, 0347:2-169
- EOAP/OAP Support of HSOP Protocol (Release 28.0), 0347:2-169
- EOAP-to-Eagle Interface
 - Embedded OAP (24.0), 0347:2-140
- EOAP-to-LSMS Interface
 - Embedded OAP (24.0), 0347:2-141
- EOAP-to-SEAS Interface
 - Embedded OAP (24.0), 0347:2-141
- EPAP, 0188:1-10, 0188:2-7, 0190:1-10, 0190:2-35, 0193:1-11, 0193:2-3, 0193:2-5, 0195:1-10, 0195:2-8, 0195:2-11, 0347:2-2, 0348:1-10
 - active EPAP, 0195:2-10
 - Active/Standby
 - roles, 0183:2-4
 - switchover, 0183:2-6
 - alarms
 - see also UAMs, EPAP
 - application, 0183:4-16
 - descriptions, 0183:4-18
 - DSM-EPAP Link status, 0183:4-18
 - RTDB Audit, 0183:4-19
 - change login name passwords, 0183:5-24
 - description, 0348:2-1

- EPAP A, 0195:2-9
- EPAP B, 0195:2-9
- general description, 0183:2-2
- GUI interface, accessing, 0096:A-1
- initialization, 0183:5-7
- log viewer navigation commands, 0183:3-33
- maintains database updates, 0188:2-10
- Maintenance Blocks, 0183:4-2
- mated EPAP system, 0195:2-9
- MPS Server memory to support, 0212:4-27
- Normal Output, 0096:3-17, 2712:3-14
- overall design, 0183:2-4
- platforms, 0195:2-9
- standby EPAP, 0195:2-10
- Status and Error Reporting via Maintenance Blocks, 0195:2-13
- status of connection to DSM, 0183:4-18
- status reporting and alarms, 0348:2-9
- support of GSM features, 0025:6-1
- Sync network
 - configure IP addresses, 0183:5-20
 - description, 0183:2-4, 0183:2-9
 - IP addresses, 0183:2-9
- system, 0195:2-9
- task descriptions, 0183:2-27
- task overview, 0183:2-8
- text interface, accessing, 0096:A-4
- time zone, 0183:5-23, 0183:A-1
- UAMs, 0183:4-18
- updates PDB, 0188:2-10
- user interface
 - error message format, 0183:5-14
 - list of error messages, 0183:3-142
- user interface menus
 - configuration, 0183:5-14
 - default values for prompts, 0183:5-13
 - Escape key to exit operations, 0183:5-13
 - responding to prompts, 0183:5-13
- user login names, 0183:5-7
- epapconfig
 - access configuration menu, 0183:5-14
- EPAP - DSM Connection Status, 0188:5-12, 0190:5-12
- EPAP - DSM Loading Interface, 0193:5-8
- EPAP 'A', 0190:5-2, 0195:4-2
- EPAP 'B', 0190:5-2, 0195:4-2
- EPAP (Eagle Provisioning Application Processor), 0188:2-8, 0190:2-35, 0193:2-7, 0195:2-12
- EPAP 2.0 Alarm Migration from ELAP, 0347:2-171
- EPAP 2.0 Alarm Migration from ELAP (Eagle 28.0), 0347:2-171
- EPAP A, 0188:2-7, 0188:2-15, 0190:2-38, 0193:2-4
 - status, 0188:5-2
- EPAP A, Link A, 0188:2-26
- EPAP A, Link B, 0188:2-26
- EPAP Application Data Loading, 0188:5-5, 0190:5-5, 0195:4-5

Master Index

EPAP architecture, 0188:2-21, 0190:2-35
EPAP Areas, 0183:3-6
EPAP Audit, 0178:2-19, 0183:2-31
EPAP automatically updates PDB, 0190:2-35
EPAP B, 0188:2-7, 0188:2-15, 0190:2-38, 0193:2-4
 status, 0188:5-2
EPAP B, Link A, 0188:2-26
EPAP B, Link B, 0188:2-26
EPAP Configuration Menu, 0183:5-14
EPAP Configure NTP Server Menu Exit, 0183:5-29
EPAP Continuous Reload, 0188:2-26, 0190:2-38
EPAP database, 0193:2-19
EPAP DCBs, 0188:2-12
EPAP GUI Main Screen, 0183:3-5
EPAP Hardware Interconnection, 0183:2-31
EPAP IP addresses in DSM network, 0190:2-44
EPAP IP Addresses in the DSM Network, 0188:2-15, 0190:2-44, 0193:2-15
EPAP Maintenance Blocks, 0188:5-2, 0190:5-2, 0193:5-2, 0195:4-2
EPAP menu, 0183:3-12
EPAP network addresses, 0188:2-15, 0190:2-44, 0193:2-15
EPAP platforms, 0193:2-4
EPAP RTDB incoherent, 0188:5-14
EPAP Server, 0183:3-7
EPAP Status and Alarm Reporting, 0193:5-2
EPAP Status and Alarms, 0188:5-1, 0190:5-1, 0195:4-2
EPAP Status and Error Reporting via Maintenance Blocks, 0188:2-12, 0190:2-40, 0193:2-9, 0195:2-13
EPAP Sync Network, 0188:2-13, 0190:2-42, 0193:2-13, 0193:2-14
EPAP system, 0193:2-4
EPAP tracks downloads in progress, 0188:5-3
EPAP UAMs, 0188:5-12, 0190:5-12
EPAP UI, 0183:3-3
EPAP UIMs, 0190:5-17
EPAP/ELAP 2.0 Security and UI Enhancements, 0347:2-172
EPAP/ELAP 2.0 Security and UI Enhancements (Release 28.0), 0347:2-172
EPAP/PDBA Overview, 0193:2-5, 0195:2-11
EPAP/PDBA user interface terminal, 0188:2-16
epapconfig, 0178:5-26, 0178:5-29, 0183:5-7, 0183:5-14, 0183:5-34, 0183:5-36, 0288:2-59
 access configuration menu, 0183:5-14
EPAP-DSM Loading Interface, 0188:5-6, 0190:5-6, 0195:4-5
EPRI cannot be less than PRI, 0177:2-199
ept-stat-epap, 0190:2-40
equipment damage, 0188:1-8, 0190:1-8, 0193:1-9, 0195:1-8
Equipment Identity Register, 0195:1-1, 0195:2-2, 0195:5-2, 0195:5-5, 0195:5-13, 0195:5-14, 0195:5-15,
 0195:5-16, 0195:5-18, 0195:5-19, 0195:5-23, 0195:5-24, 0195:5-25, 0195:5-27, 0195:5-29, 0195:5-30,
 0195:5-33, 0195:5-34, 0195:5-35, 0195:5-36, 0195:5-37, 0195:5-39, 0195:5-40, 0195:5-41, 0195:5-42,
 0195:5-43, 0195:5-45, 0195:5-48, 0195:5-51, 0195:5-53, 0195:5-54, 0195:5-56, 0195:5-58, 0195:5-59,
 0195:5-60
 capability point codes, 0195:5-2
 Configuration, 0195:5-2
equipment required
 initial installation, 2970:3-20
equipment, MPS hardware, 0025:6-2

ERI

- MTP and SCCP Management to Support EIR, 0195:2-14
- EROUTE capacity normal, card(s) abnormal, 0338:3-582
- EROUTE is Removed, 0338:3-578
- EROUTE not configured, 0177:2-461
- EROUTE System Capacity Exceeded, 0338:3-581
- EROUTE System is Available, 0338:3-579
- EROUTE System threshold Exceeded, 0338:3-580
- Error code
 - 30 - Read-only file system, 0197:2-121
 - 32 - Broken pipe, 0197:2-121
 - 35 - Unsupported value, 0197:2-121
 - 40 - A destination address is required, 0197:2-119
 - 41 - Protocol wrong type for socket, 0197:2-119
 - 42 - The protocol is not available, 0197:2-119
 - 43 - The protocol is not supported, 0197:2-119
 - 44 - The socket type is not supported, 0197:2-119
 - 45 - The operation is not supported on the socket, 0197:2-119
 - 46 - The protocol family is not supported, 0197:2-119
 - 47 - The address family is not supported, 0197:2-119
 - 48 - The address is already in use, 0197:2-119
 - 49 - The requested address cannot be assigned, 0197:2-119
 - 50 - Socket operation on non-socket, 0197:2-119
 - 51 - The network is unreachable, 0197:2-119
 - 52 - The network dropped the connection on reset, 0197:2-119
 - 53 - Software caused the connection to abort, 0197:2-119
 - 54 - The connection was reset by the peer, 0197:2-120
 - 55 - No buffer space available, 0197:2-120
 - 56 - The socket is already connected, 0197:2-120
 - 57 - The socket is not connected, 0197:2-120
 - 58 - Can't send after socket shutdown, 0197:2-120
 - 59 - Too many references: can't splice, 0197:2-120
 - 595 - File open failed, 0197:2-106
 - 596 - The file name is already specified, 0197:2-106
 - 597 - SFTP client packet send failure, 0197:2-106
 - 598 - The SFTP connection is closed, 0197:2-106
 - 599 - SFTP packet read failure, 0197:2-106
 - 60 - The connection timed out, 0197:2-120
 - 600 - SFTP protocol error, 0197:2-107
 - 601 - Undefined, 0197:2-107
 - 608 - SFTP received a invalid ID in the response received during a read operation on remote directory, 0197:2-107
 - 609 - SFTP: Handle mismatch error, 0197:2-107
 - 61 - The connection was refused, 0197:2-120
 - 610 - Unexpected SSH2_FXP_ATTRS, 0197:2-107
 - 611 - Unexpected SSH_FXP_NAME, 0197:2-107
 - 612 - SSH_FXP_REALPATH request failure, 0197:2-108
 - 613 - SSH_FXP_READLINK request failure, 0197:2-108
 - 614 - unexpected SSH_FXP_NAME, 0197:2-108
 - 615 - The SFTP client received more data than expected, 0197:2-108
 - 616 - The SFTP client failed to read the data from the file descriptor, 0197:2-108
 - 617 - Excessive identity files, 0197:2-109

Master Index

- 62 - The network is down, 0197:2-121
- 624 - The debug levels allowed for SSH protocol in openSSH is 0-9, 0197:2-109
- 625 - Failure to read the client configuration file, 0197:2-109
- 626 - Invalid compression level is specified in the client configuration file, 0197:2-109
- 627 - SSH failure to setup the IO with the server, 0197:2-109
- 628 - SSH failure to open the channel for the SSH connection with the server, 0197:2-109
- 629 - SSH failure to setup the channel for the SSH connection with the server, 0197:2-109
- 630 - SSH failure to verify the SSH client host key, 0197:2-109
- 631 - SSH user authentication failure, 0197:2-110
- 632 - The authentication method is NULL in the client software, 0197:2-110
- 633 - Permission is denied by the server due to authentication failure, 0197:2-110
- 633 - User login failure, 0197:2-106
- 640 - A bad message was received during the SSH authentication, 0197:2-110
- 641 - Missing authentication context, encountered during the SSH user authorization, 0197:2-111
- 642 - Failure during the public key read/verification operation, 0197:2-111
- 643 - Undefined SFTP/SSH error, 0197:2-111
- 644 - Unexpected SSH_FXP_STATUS error, 0197:2-111
- 645 - A bad option was specified in the SSH client on the EAGLE 5 SAS, 0197:2-111
- 646 - An unsupported escape character was used in the SSH client on the EAGLE 5 SAS, 0197:2-111
- 647 - An unsupported cipher type was used in the SSH client on the EAGLE 5 SAS, 0197:2-111
- 648 - An unsupported MAC type was used in the SSH client on the EAGLE 5 SAS, 0197:2-112
- 649 - A bad port was used in the SSH client on the EAGLE 5 SAS, 0197:2-112
- 65 - There is no route to the host, 0197:2-121
- 656 - Bad forwarding was used in the SSH client on the EAGLE 5 SAS, 0197:2-112
- 657 - Bad forwarding ports were specified in the SSH client on the EAGLE 5 SAS, 0197:2-112
- 658 - A bad dynamic port was specified in the SSH client on the EAGLE 5 SAS, 0197:2-112
- 659 - The host was not specified in the SSH client on the EAGLE 5 SAS, 0197:2-113
- 660 - An invalid option or argument was specified in the SSH client on the EAGLE 5 SAS, 0197:2-114
- 661 - The hostname was not specified in the SSH client on the EAGLE 5 SAS, 0197:2-114
- 663 - The SSH client was unable to load the cipher type on the EAGLE 5 SAS, 0197:2-114
- 664 - Asynchronous IO is not supported on IPSM, SSH client error, 0197:2-114
- 665 - Compression is already enabled in the SSH client on the EAGLE 5 SAS, 0197:2-114
- 666 - Unknown cipher number on the SSH client on the EAGLE 5 SAS, 0197:2-114
- 667 - The SSH client key length is invalid, 0197:2-114
- 668 - No key is available on the SSH client on the EAGLE 5 SAS, 0197:2-114
- 669 - The secure connection was closed by the remote server, 0197:2-115
- 67 - The host is down, 0197:2-121
- 670 - Connection failure due to network outage or the connection was lost due to a faulty SSHD/SFTP server or network, 0197:2-115
- 671 - An unexpected packet type was received from the SFTP/SSHD server, 0197:2-115
- 672 - A bad packet length was received from the SSHD/SFTP server, 0197:2-115
- 673 - A cryptographic attack was detected by the SSH client, 0197:2-115
- 674 - The SSH/SFTP client on the EAGLE 5 SAS failed to read from the remote side, 0197:2-116
- 675 - Corrupted check bytes were detected on the SSH/SFTP client on the EAGLE 5 SAS, 0197:2-116
- 676 - Corrupted MAC on input was detected by the SSH/SFTP client on the EAGLE 5 SAS, 0197:2-116
- 677 - Corrupted pad on input was detected by the SSH/SFTP client on the EAGLE 5 SAS, 0197:2-116
- 678 - SSH/SFTP tried to close a connection that is already closed, 0197:2-116

679 - The SSH /SFTP client on the EAGLE 5 SAS failed to write to the remote side, 0197:2-117
 680 - SSH /SFTP tried to set the packet size twice, 0197:2-117
 681 - A bad packet size was detected by the SSH /SFTP client on the EAGLE 5 SAS, 0197:2-117
 682 - The connection timed out when SSH tried to connect to SSHD, 0197:2-118
 683 - The SSH connection was refused by the remote server, 0197:2-118
 684 - The SSHD server is unreachable, 0197:2-118
 685 - The network has reset, 0197:2-118
 686 - The SSH /SFTP connection has been aborted, 0197:2-118
 687 - The SFTP/SSH connection has been reset by the peer, 0197:2-118
 688 - Failed to allocate network buffers, 0197:2-118
 689 - The SSH /SFTP socket is already connected, 0197:2-118
 690 - The SSH /SFTP socket is not connected, 0197:2-118
 691 - The network channel is down, 0197:2-118
 692 - The SSHD /SFTP server connection host is down, 0197:2-118
 693 - SFTP client channel read failure, 0197:2-118
 694 - SFTP client channel write failure, 0197:2-118
 695 - SFTP client channel open failure, 0197:2-118
 Error Codes
 FTP, 0197:2-105
 Generic Network, 0197:2-119
 SFTP, 0197:2-105
 SSH, 0197:2-105
 error codes, 0178:3-112, 0183:3-142
 error conditions corrected, 0096:3-14, 2712:3-11
 Error in FEATCTRL.TBL date, maintenance required, 0177:2-722
 Error message
 STP Name does not exist, 0197:2-32
 Error Message Format, 0178:5-12, 0183:5-14
 Error message format, 0178:B-19
 Error Message Reporting Enhancement (21.0), 0347:2-178
 Error Messages, 0178:3-112, 0183:3-142
 error messages
 Logout on Communications Failures (22.0), 0347:4-94
 error messages, ELAP
 format, 0178:5-12
 list of user interface, 0178:3-112
 error messages, EPAP
 format, 0183:5-14
 list of user interface, 0183:3-142
 Errors
 SFTP, 0197:2-106
 SFTP Client, 0197:2-106
 SSH Client, 0197:2-109
 SSH /SFTP Connection/Setup, 0197:2-118
 Errors - contacting the Customer Care Center, 0097:1-10, 0098:1-10, 0099:1-8, 0100:1-9, 0119:1-11,
 0120:1-8, 0142:1-8, 0197:2-3, 0197:2-5, 0197:2-48, 0197:2-105, 0197:2-106, 0197:2-107, 0197:2-108,
 0197:2-109, 0197:2-110, 0197:2-111, 0197:2-112, 0197:2-113, 0197:2-114, 0197:2-115, 0197:2-116,
 0197:2-117, 0197:2-118, 0197:2-119, 0197:2-120, 0197:2-121, 0288:1-9
 errors, displayed in GUI banner, 0096:3-13, 2712:3-10
 ES, 0188:1-10, 0190:1-10, 0193:1-11, 0195:1-10
 Escape key to exit ELAP user interface operations, 0178:5-11
 Escape key to exit EPAP user interface operations, 0183:5-13

Master Index

ESP, 0097:1-3, 0097:6-2, 0097:6-3, 0097:6-4, 0097:6-7, 0097:6-19, 0212:4-39
ESP Servers, 0212:5-15
ESP Subsystem Hardware Components, 0212:5-15
Ethernet, 0097:6-7, 0142:4-128, 0338:5-22, 2970:7-21
 Quad FastEthernet Network Interface card, 0212:4-31
ethernet applique, 0212:3-95
Ethernet B Interface for IPGWx and IPLIMx, 0347:2-179
Ethernet bandwidth, 0188:2-13
Ethernet connection, 0197:2-2
Ethernet hub description, 0243:2-13
Ethernet Link to the MPS - Configuring, 0288:2-28
Ethernet links, 0188:2-10, 0193:2-4, 0195:2-10
Ethernet network
 100BASE-T, 0178:2-7, 0178:2-8, 0183:2-9
 10BASE-T, 0178:2-7, 0183:2-9
 DSM networks, 0178:2-4, 0178:2-7, 0183:2-4, 0183:2-9
 ELAP Sync, 0178:2-4, 0178:2-8
 EPAP Sync, 0183:2-4
Ethernet ports, 0188:2-10
Ethernet switch
 replace, 0095:7-4, 2969:7-7
ETSI, 0190:1-10, 0193:1-11, 0195:1-10, 0348:1-10
ETSI GSM 03.03 standard, 0190:2-6
ETSI GSM 03.66 standard, 0190:2-2
ETSI NP standards, 0348:2-4
ETSI standards, 0190:2-5
ETT already mapped for LSN and IO specified, 0177:2-363
ETT cannot be mapped to MTT with same value, 0177:2-363
ETT not defined for LSN and IO specified, 0177:2-362
European Telecommunications Standards Institution, 0193:2-1
eval, 0178:B-22
Event interval argument - not valid (C<col>), 0177:2-503
event reporting
 MTP Restart (EAGLE 21.0), 0347:4-134
Example EPAP/PDBA Network, 0348:2-2
Example Individual IMEI Table, 0195:2-5
Example of Basic Error Correction vs. PCR
 Preventive Cyclic Retransmission (PCR) (EAGLE 20.0), 0347:5-29
exception list, 0120:2-120
exception lists
 Cluster Routing and Management Diversity (21.0), 0347:2-67
exception status, 0190:3-15, 0193:3-9, 0195:3-14
Excessive identity files - Error code 617, 0197:2-109
Exchange Secure Shell Keys, 0178:5-21, 0183:5-24
Exchange Secure Shell Keys menu, 0178:5-21, 0183:5-24
execute selected command remotely by the targeted card, 0188:3-14
existing commands
 MTP Restart (EAGLE 21.0), 0347:4-135
existing ELAP connection to LSMS, 0178:2-11
Exit Confirmation window, 0197:2-14
Exit menu, 0178:5-25, 0183:5-27, 0183:5-33, 0197:2-13
exit user interface operations with Escape key, 0178:5-11, 0183:5-13

Exit window, 0197:2-14, 0197:2-15
 Exiting Degraded Mode, 0338:3-550
 Exiting the FTRA application, 0197:2-4, 0197:2-14
 expansion cabinets, 0025:4-10
 expansion shields, 0224:3-16
 expired password procedure, 0145:4-21
 export a file to PDB, 0183:3-101
 Export PDB to File, 0183:3-100
 export the PDB, 0183:3-100
 EXT ALM, 0212:3-26, 0224:C-20, 0243:C-19
 EXT not valid with ACTION=RESET, 0177:2-311
 Extended Bus Interface (20.0), 0347:2-182
 extended services platform, 0097:6-2, 0097:6-19
 Extended Services Platform Host Servers, 0212:4-39
 extender board (FAP), 0338:2-7
 Extension Frame, 0224:4-36
 Extension frame, 0224:3-27
 Extension Frame (EF), 0212:3-4, 0212:3-9
 extension frame (EF), 0212:3-9
 Extension frame 01, 0224:3-27
 Extension frame 02, 0224:3-27
 Extension frame 03, 0224:3-27
 Extension frame 04, 0224:3-27
 extension shelf, 0212:3-28
 extension shelf backplane, 0212:3-31
 Extension Shelf Backplane (23.0), 0347:2-182
 extension shelf power connectors, 0224:B-61, 0243:B-24
 External Alarm (EXT ALM), 0212:3-26
 external alarm cable installation, 0224:5-87
 external alarm connector, 0212:3-26, 0224:B-35
 external interface descriptions
 external interface descriptions, 0347:2-134
 external tooth washer, 0224:5-69, 2970:3-13
 External/Customer Alarm Interface, 0212:3-52

F

Failed accessing maintenance data, 0177:2-385
 Failed accessing the memory equipage table, 0177:2-591
 Failed reading ACG MIC table, 0177:2-445
 Failed reading ACG NOC table, 0177:2-444
 Failed reading Application Socket table, 0177:2-800
 Failed reading FEATPFX, 0177:2-828
 Failed reading GSM Options Table, 0177:2-559
 Failed reading GSM SSN Table, 0177:2-559
 Failed reading GTT DBMM table, 0177:2-471
 Failed reading GTT Selector Table, 0177:2-560
 Failed reading GTT Set Table, 0177:2-560
 Failed Reading GTT TRANS table, 0177:2-471
 Failed reading HOME SMSC ADDRESS table, 0177:2-540
 Failed reading HOMERN Table, 0177:2-690
 Failed reading INPOPTS Table, 0177:2-690

Master Index

Failed reading level 2 timer set table, 0177:2-63
Failed reading level 3 timer set table, 0177:2-64, 0177:2-65
Failed reading Link Fault Sectionalization table, 0177:2-386
Failed reading linkset table, 0177:2-38
Failed reading LNP Options table, 0177:2-480
Failed Reading LNP SS Appl table, 0177:2-472
Failed Reading LNP TT SERV table, 0177:2-472
Failed reading MAS configuration table, 0177:2-49
Failed reading OAP configuration table, 0177:2-586
Failed reading redirect table, 0177:2-276
Failed reading Secondary Point Code (SPC) table, 0177:2-643
Failed reading SERV Selector Table, 0177:2-560
Failed reading shelf table, 0177:2-28
Failed reading site identification table, 0177:2-377
Failed reading SLTM table, 0177:2-72
Failed Reading SS Appl table, 0177:2-586
Failed reading STP options table, 0177:2-366
Failed reading SUBNETID table, 0177:2-823
Failed reading terminal table, 0177:2-45
Failed reading the ATM link parameter set table, 0177:2-513
Failed reading the E1/T1 table, 0177:2-731
Failed reading the extended link table, 0177:2-256
Failed reading the GWS Stop Action Set table, 0177:2-590
Failed reading the IMT table, 0177:2-27
Failed reading the link table, 0177:2-28
Failed reading the MRN table, 0177:2-431
Failed reading the password table, 0177:2-329, 0177:2-331
Failed reading the route table, 0177:2-280
Failed reading the security log attributes table, 0177:2-434
Failed reading the UIM Threshold Table, 0177:2-630
Failed reading the user identification table, 0177:2-74
Failed reading the X.25 destination table, 0177:2-280
Failed reading the X.25 route table, 0177:2-280
Failed reading trouble text table, 0177:2-497
Failed reading tt map table, 0177:2-360
Failed reading VENDID table, 0177:2-815
Failed reading/writing Extended Linkset Table, 0177:2-407
Failed reading/writing Extended STP Options Table, 0177:2-408
Failed to allocate network buffers - Error code 688, 0197:2-118
Failed User, 0183:3-112
Failed User Logins, 0178:3-108, 0183:3-138
Failure during the public key read/verification operation - Error code 642, 0197:2-111
Failure Inhibiting EIR SS, 0338:3-654, 0338:3-655
Failure Inhibiting LNP SS, 0338:3-811
Failure Inhibiting Local SS, 0338:3-821
failure of database look-up, 0193:2-18
Failure on both IMT A and IMT B, 0338:3-191
Failure reading the GSM Map SCRN Table, 0177:2-677
Failure reading the GSM OPCODE Table, 0177:2-676
Failure reading the GSM SSN Screening Table, 0177:2-675
Failure to read the client configuration file - Error code 625, 0197:2-109
Failures detected on one IMT bus, 0338:3-188

- FAK alarm - Clearing, 0288:3-83
- FAK Alarm - Temporary
 - Clearing, 0099:A-12, 0142:A-36
- fall-through case, 0347:5-20
- False Link Congestion Management (21.0), 0347:3-1
- Fan assemblies, 2969:7-4
- Fan Assembly, 0224:5-54
- fan assembly
 - installed below DCM card, 0338:A-86
 - part number label, 0095:B-3, 0095:B-6, 2969:B-3, 2969:B-6
 - replace, 0095:7-20, 2969:7-20, 2969:7-22
- Fan Assembly (EAGLE/GR-376 EOAP) Replacement, 0338:A-82
- fan door, replacing, 0338:2-34
- Fan feature must be enabled, 0177:2-666
- fan filter, replacing, 0096:3-9, 2712:3-6
- fan power cables
 - install, 2970:3-39
- fan support, 2970:3-11
- fan switch
 - set to OFF, 0338:5-100, 0338:A-90, 2970:3-66, 2970:3-72, 2970:6-49
 - set to ON, 0338:5-98, 0338:A-89, 2970:6-47
- Fan Tray, 0212:3-118
- fans
 - Embedded OAP (24.0), 0347:2-139
- FAP, 0224:4-9, 0224:5-164, 0338:2-2
- FAP alarm conditions, 0338:2-7
- FAP alarms, 0338:2-8
- FAP component functions, 0338:2-5
- FAP component replacement, 0338:2-6
- FAP components, 0338:2-4
- FAP components, hot swapping, 0338:2-6
- FAP functions, 0338:2-3
- FAP Load Balance Verification (PN 870-0243-XX only), 0338:2-25
- FAP_JB (Jumper Board), 0224:4-7
- Fast Ethernet switch, 0025:4-10
- fault tolerance, 0096:2-22, 2712:2-19
- feat commands, 0188:3-3
- FEATPFX table full, 0177:2-822
- Feature
 - Eagle OA&M IP Security Enhancements, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
 - EGTT, 0197:2-56
 - FTP Retrieve and Replace, 0197:2-3
 - GTT, 0197:2-56
 - IP User Interface, 0197:2-3
- feature
 - X.25 Gateway, 0097:1-2
- Feature Activation Overview, 0188:4-3, 0190:4-4
- Feature bit configuration requires DSM card with VSCCP appl, 0177:2-575
- feature commands
 - LNP—Changes to Existing Commands (22.0), 0347:4-61
- feature concept
 - High Speed Master Timing (26.0), 0347:3-60

Master Index

Feature corresponding to APPL not ON, 0177:2-246
Feature Description, 0190:2-1, 0190:2-2, 0193:2-1, 0195:2-1
feature functions
 PCS 1900 LNP Query (EAGLE 26.0), 0347:5-3
Feature Guide
 documents
 Feature Guide, 0212:1-17, 0243:1-18
Feature Name is not valid, 0177:2-822
Feature Notice, 0212:1-17, 0243:1-18
Feature Prefix already exists, 0177:2-821
Feature Prefix not found, 0177:2-823
Feature Prefix Number invalid, 0177:2-822
Feature Prefix still in use, 0177:2-823
Feature Prefix too long, 0177:2-820
Feature Prefix too short, 0177:2-820
feature, LNP 48 Million Numbers, 0178:2-2
features
 fan, 0338:5-99, 0338:A-90, 2970:3-71, 2970:6-48
 G-Flex, 0025:6-1
 G-Port, 0025:6-1
 GSM, 0025:6-1
 INP, 0025:6-1
 ITU National and International Spare Point Code Support, 0120:2-42, 0120:2-51
 LNP 48 Million Numbers, 0025:6-2
 MPS system additional, 0025:6-11, 0212:4-28
 MPS system supported, 0025:6-1
 multiple point code support, 0120:2-55
Field
 Command File, Update Tables window, 0197:2-81, 0197:2-82, 0197:2-84
 Command List
 Retrieve Tables, 0197:2-58
 Update Tables, 0197:2-80
 Current STP Selected:, 0197:2-41
 File Name:, 0197:2-54
 Select Starting Directory window, 0197:2-54
 Select window, 0197:2-82
 Files of type:
 Select Starting Directory window, 0197:2-54
 Select window, 0197:2-82
 FTP Password, 0197:2-18, 0197:2-24
 FTP UserName, 0197:2-18, 0197:2-23
 IP Address, 0197:2-52
 Backup - FTRA 2.0 or greater, 0197:2-18, 0197:2-22
 Primary - FTRA 2.0 or greater, 0197:2-17, 0197:2-22
 IP Address - FTRA 1.0, 0197:2-17, 0197:2-22
 Look in:
 Select Starting Directory window, 0197:2-54
 Select window, 0197:2-82
 Path, 0197:2-52
 Selected Commands, Retrieve Tables, 0197:2-58
 STP Name, 0197:2-4, 0197:2-17, 0197:2-18, 0197:2-20, 0197:2-25, 0197:2-29
 STP name typed

- FTRA 1.0, 0197:2-29
- FTRA 2.0, 0197:2-29, 0197:2-30
- STP Password, 0197:2-18, 0197:2-23
- STP UserName, 0197:2-18, 0197:2-22
- Subpath, 0197:2-52
- Field Replaceable Units
 - guidelines, 0096:5-1, 2712:5-1
 - locating replacement procedures, 0096:5-2, 2712:5-2
 - part numbers, 0096:5-2, 2712:5-2
- Field Replaceable Units (FRUs), 0096:5-2, 2712:5-2
- Field Replaceable Units (FRUs), MPS, 0096:5-3, 0096:5-4, 2712:5-3, 2712:5-4
- File already exists, 0177:2-124
- file extension
 - .doc, 0197:2-37, 0197:2-74, 0197:2-98, 0197:2-102
 - .txt, 0197:2-37, 0197:2-74, 0197:2-98, 0197:2-102
- File format
 - CSV, 0197:2-1, 0197:2-56, 0197:2-58, 0197:2-66, 0197:2-75, 0197:2-77
- File menu
 - Command File Editor window, 0197:2-89
 - Connectivity Test Log, 0197:2-34, 0197:2-35
 - FTP-Based Table Retrieve Application window, 0197:2-14
 - Retrieve Tables Log, 0197:2-70, 0197:2-71
 - System Log, 0197:2-99, 0197:2-100
 - Update Tables Log, 0197:2-94, 0197:2-95
- File Name: Field
 - Select Starting Directory window, 0197:2-54
 - Select window, 0197:2-82
- File Naming Conventions
 - CLLI-based Names Disabled, 0338:4-7
 - CLLI-based Names Enabled, 0338:4-8
- File open failed - Error code 595, 0197:2-106
- File System, 0096:3-16, 2712:3-13
- File System Backup, 0183:5-26
- file system backup, 0183:3-47
- File Transfer Area, 0190:5-17, 0193:5-24
- File Transfer for LNP Measurements, 0338:2-18
- File transfer in progress, 0177:2-89
- File Transfer Options, 0183:2-25
- File Transfer Utility (20.0), 0347:3-3
- filelength not valid with ACTION=RENAME, 0177:2-311
- FILELENGTH not valid with ACTION=RESET, 0177:2-310
- FileManager, 0197:2-8
- files
 - UNIX time zone, 0178:1-2, 0178:5-20, 0178:A-1, 0183:5-23, 0183:A-1
- Files of type: Field
 - Select Starting Directory window, 0197:2-54
 - Select window, 0197:2-82
- files, import/ export and PDBA debug log formats, 0348:2-15
- Fingerprint
 - Key
 - DSA, 0197:2-48, 0197:2-49
 - Public Host Key

Master Index

EAGLE 5 SAS, 0197:2-45, 0197:2-46, 0197:2-48, 0197:2-50
Public Key
EAGLE 5 SAS, 0197:2-19, 0197:2-48, 0197:2-49
finish cables
backplane, 2970:3-50
fire protection requirements, 0095:2-5, 2969:2-5
First octet of IPADDR cannot be 127, 0177:2-259
Fixed connection, 0097:2-7
fixed connection, 0347:5-183
fixed disk
formatting, 0142:2-91
Fixed disk contains Eagle data (use FORCE=YES), 0177:2-57
fixed disk drive
overview, 0100:1-12, 0120:1-12, 0142:1-12
Fixed disk is inaccessible (internal problem), 0177:2-416
Fixed disk is not initialized, 0177:2-416
Fixed disk is not inserted, 0177:2-416
flag - strict host key, 0197:2-46
flange
EOAP shelf, 0338:5-72, 2970:6-20
Flash Memory Management (23.0), 0347:3-3
Changed Commands, 0347:3-4
IMT Command Changes, 0347:3-5
New Commands, 0347:3-4
flash-card, 0145:6-363
Flexible Point Code Formatting (26.0), 0347:3-6
Affected Commands, 0347:3-6
Changed Commands, 0347:3-6
floor
loading, 0095:2-7, 2969:2-7
mark layout, 0095:4-4, 2969:4-4
plan, 0095:4-4, 2969:4-4
preparation
additional for raised floors, 0095:4-5, 2969:4-5
for heavy duty frame, 0095:4-3, 2969:4-3
raised
additional preparations, 0095:4-5, 2969:4-5
anchoring frame to concrete under raised floor, 0095:4-10, 2969:4-10
anchoring frame using support channel and spring nut, 0095:4-16, 2969:4-16
anchoring with support channel, 0095:4-13, 2969:4-13
slab
anchor assembly, 0095:4-7, 2969:4-7
slab, anchoring frame, 0095:4-6, 2969:4-6
Floor Layout, 0224:3-12
floor loading, 0212:6-5
floor plan, 0224:3-12
Floor Preparation, 0224:3-14
floor preparation, 0224:3-11, 0224:3-20
For Mate Point Code (MPC), MSSN, MateRC, RC must be provided, 0177:2-428
For SUBNETNUM specified the prefix is not provisioned, 0177:2-826
For VENDNUM specified the prefix is not provisioned, 0177:2-819
FORBID can not be STATE or LOCATION for the given OPNAME, 0177:2-680

force, 0348:3-16, 0348:3-17, 0348:3-19, 0348:3-21, 0348:3-50
 Force Change on Initial Login, 0178:3-110, 0183:3-140
 force option, 0188:5-8, 0190:5-8, 0193:5-11, 0195:4-8
 FORCE parameter
 chg-oap-config, 2970:4-12
 FORCE parameter required, 0177:2-149
 FORCE parameter valid only with DATA parameter, 0177:2-658
 Force Standby menu, 0178:3-17, 0183:3-17
 FORCE valid only with APPL, DATA or INITCLK parameters, 0177:2-658
 FORCE=YES is required to isolate card from IMT, 0177:2-419
 FORCE=YES is required when card is allowed, 0177:2-323
 FORCE=YES must be given to inhibit last OAP terminal, 0177:2-317
 FORCE=YES must be specified, 0177:2-632
 Force=YES must be specified, 0177:2-639
 FORCE=YES must be specified for NUM greater than 1000, 0177:2-174
 FORCE=YES must be specified if NUM is greater than 50, 0177:2-479
 FORCE=YES must be specified to change existing stop action, 0177:2-595
 FORCE=YES must be specified to delete entire node, 0177:2-267
 FORCE=YES must be specified to initialize the last OAP, 0177:2-349
 force=yes parameter, 0188:3-12
 forced retransmission
 Preventive Cyclic Retransmission (PCR) (EAGLE 20.0), 0347:5-30
 FORCED STANDBY, 0178:3-7, 0183:3-7
 foreach, 0178:B-22
 format
 common response message, 0348:3-3
 ELAP error messages, 0178:5-12
 EPAP error messages, 0183:5-14
 optional parameters, 0348:3-3
 PDBA debug log, 0348:2-15
 PDBA import and export files, 0348:2-15
 response message data element, 0348:3-3
 format, output banner, 0145:4-15
 format-disk, 0145:6-366
 formatting
 fixed disk, 0142:2-91
 removable cartridge, 0142:2-79
 fourth octet, 0188:2-15, 0190:2-44
 frame
 anchoring
 to concrete under raised floor, 0095:4-10, 2969:4-10
 to raised floor using support channel, 0095:4-13, 2969:4-13
 to raised floor with support channel and spring nut, 0095:4-16, 2969:4-16
 to slab floor, 0095:4-6, 2969:4-6
 floor preparation, 0095:4-3, 2969:4-3
 layout, 0095:4-4, 2969:4-4
 template, 0095:4-4, 2969:4-4
 unpacking, 0095:4-2, 2969:4-2
 Frame Anchoring, 0224:3-16
 frame for EOAP shelf, 2970:3-20
 Frame ID out of range, 0177:2-51
 frame rail, 0338:5-71, 2970:6-18

Master Index

- Frame Side Panels, 0224:3-33
- frame, MPS
 - layout, 0212:4-13
- frames, 0183:3-5
- FRCSMPLX - Simplex Mode, 0288:3-52
- frequency limiting, 0193:2-19
- front view
 - hub, 0212:4-47
 - MPS frame layout, 0212:4-13
 - MPS Server, 0212:4-25
 - MPS Server detail, 0212:4-22, 0212:4-30
 - Netra t 1400, 0212:4-25
- FRU
 - replacement
 - tools required, 0095:7-3, 2969:7-6
- FRUs, 0096:5-2, 2712:5-2
 - guidelines, 0096:5-1, 2712:5-1
 - locating replacement procedures, 0096:5-2, 2712:5-2
 - part numbers, 0096:5-2, 2712:5-2
- FRUs, MPS, 0096:5-3, 0096:5-4, 2712:5-3, 2712:5-4
- FSM, 0348:1-10
- FTA, 0190:5-17, 0193:1-12, 0193:5-24
- FTA, wxtracting LNP measurements from, 0145:5-8
- FTP, 0195:1-10
- FTP Error Codes, 0197:2-105
- FTP Password Field, 0197:2-18, 0197:2-24
- FTP Retrieve and Replace (Release 29.0) (IP7 Release 7.0), 0347:3-9
- FTP Retrieve and Replace Feature, 0025:3-9, 0197:2-3
- FTP SERV table must contain one entry with application USER, 0177:2-538
- FTP server, 0142:4-136, 0142:4-140, 0142:4-144, 0142:4-145, 0142:4-148, 0142:4-150, 0142:4-151, 0197:2-51, 0197:2-122
 - secure, 0197:2-51
- FTP Server Configuration, 0197:2-1, 0197:2-4, 0197:2-51
 - Menu, 0197:2-13, 0197:2-51
 - Browse button, 0197:2-52, 0197:2-53
 - Close button, 0197:2-52
 - IP Address, 0197:2-51, 0197:2-122
 - IP Address Field, 0197:2-52
 - Path Field, 0197:2-52
 - Set button, 0197:2-52, 0197:2-55
 - Subpath Field, 0197:2-52
 - Menu window, 0197:2-23, 0197:2-51, 0197:2-52, 0197:2-105, 0197:2-108, 0197:2-122, 0197:2-123
- FTP Server Data Set window, 0197:2-55
- FTP Server password must be 1 - 15 characters in length, 0177:2-459
- FTP Server table entry not found for this APP/IPADDR, 0177:2-336
- FTP Server table must be accessible, 0177:2-335
- FTP Server Verification procedure, 0197:2-122
- FTP transfer already in progress, 0177:2-538
- FTP UserName Field, 0197:2-18, 0197:2-23
- FTP-Based Table Retrieve Application
 - Edit Menu, 0197:2-16, 0197:2-51, 0197:2-80
 - File Menu, 0197:2-14

- Help Menu, 0197:2-104
- View Menu, 0197:2-72, 0197:2-95, 0197:2-100
- window, 0197:2-13, 0197:2-14, 0197:2-20, 0197:2-33, 0197:2-38, 0197:2-41, 0197:2-60, 0197:2-71, 0197:2-72, 0197:2-73, 0197:2-80, 0197:2-95, 0197:2-96, 0197:2-97, 0197:2-100, 0197:2-101, 0197:2-102, 0197:2-104
 - File menu, 0197:2-14
- ftpctest, 0145:9-29
- FTR, 0188:1-10, 0190:1-10, 0195:1-10
- FTRA, 0025:3-9
 - Command
 - fttra -c, 0197:2-75, 0197:2-77
 - Initialization, 0197:2-13
 - STP IP connection
 - secure, 0197:2-19, 0197:2-24
 - version level, 0197:2-104
- FTRA 1.0
 - Current STP Selected, 0197:2-43
 - STP Configuration Record, 0197:2-31
 - Adding, 0197:2-20, 0197:2-21, 0197:2-22, 0197:2-23, 0197:2-24
 - STP Connection Configuration Menu
 - IP Address, 0197:2-18, 0197:2-22
 - IP Address Field, 0197:2-17
 - STP Name drop down list, 0197:2-25, 0197:2-27
 - STP name typed, 0197:2-29
- FTRA 2.0
 - Current STP Selected, 0197:2-44
 - FTP Server, 0197:2-51
 - Secure FTP Server, 0197:2-51
 - STP Configuration Record, 0197:2-31, 0197:2-32
 - Adding, 0197:2-20, 0197:2-21, 0197:2-22, 0197:2-23, 0197:2-24
 - STP Connection Configuration
 - Menu window, 0197:2-51
 - STP Connection Configuration Menu
 - Backup IP Address, 0197:2-18
 - Backup IP Address Field, 0197:2-22
 - IP Address
 - Backup, 0197:2-18, 0197:2-22
 - Primary, 0197:2-17, 0197:2-22
 - Primary IP Address, 0197:2-18
 - Primary IP Address Field, 0197:2-22
 - Secure Connection Box, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-45, 0197:2-50, 0197:2-51
 - STP Name drop down list, 0197:2-25, 0197:2-26, 0197:2-27, 0197:2-28
 - STP name typed, 0197:2-29, 0197:2-30
- FTRA application
 - exiting, 0197:2-4, 0197:2-14
 - starting, 0197:2-4
 - using, 0197:2-4
- fttra -c command, 0197:2-75, 0197:2-77
- fttra file, 0197:2-46
- FTRA icon, 0197:2-13
- FTRA Requirements
 - Hardware, 0197:2-2

Master Index

- Unix Workstation, 0197:2-2
- Windows Workstation, 0197:2-2
- Software, 0197:2-2
 - Unix Workstation, 0197:2-2
 - Windows Workstation, 0197:2-2
- FTRA software
 - installing, 0197:2-4
 - Unix, 0197:2-9
 - Windows, 0197:2-5
- FTRA window
 - GTT Warning window, 0197:2-56
 - Retrieve Tables, 0197:2-4, 0197:2-56, 0197:2-57, 0197:2-60, 0197:2-75
 - description, 0197:2-58
 - GTT Warning window, 0197:2-56
 - Update Tables, 0197:2-4, 0197:2-79, 0197:2-80, 0197:2-81, 0197:2-82, 0197:2-83, 0197:2-88, 0197:2-89, 0197:2-92, 0197:2-93, 0197:2-94
 - description, 0197:2-80
 - Select, description, 0197:2-82
 - Update Validation Complete, 0197:2-84, 0197:2-85, 0197:2-86
 - Update Validation Complete with errors, 0197:2-86
- ftira.bat, 0197:2-7, 0197:2-46
- FTRA_HOME environment variable, 0197:2-1, 0197:2-7, 0197:2-9
- Full Download Request message, 0188:5-6
- Full LNP database reload initiated, 0338:3-885
- full point code, 0120:2-3
- Full Point Code must be specified, 0177:2-459
- Full Routing Keys, 0100:2-26
- Fully specified connection required to change OPEN, 0177:2-628
- Functional Description, 0178:2-19, 0183:2-31
- functional description, 0188:1-2
- Functional Diagram – G-Flex in SCCP, 0188:2-29
- fuse, 0224:4-22, 0224:5-142
- fuse alarm, 0338:2-8
- Fuse Alarm Interface, 0212:3-52
- fuse alarm verification, 0224:5-163
- Fuse Amp, 0224:4-10
- Fuse and Alarm Panel, 0212:3-121, 0212:3-131, 0224:4-6
- fuse and alarm panel, 0338:2-2
- Fuse and Alarm Panel (FAP), 0212:3-7, 0212:3-14, 0212:3-22, 0212:3-31
- fuse and alarm panel (FAP), 0212:3-119
- Fuse and alarm panel front items, 0338:3-7
- fuse and alarm panel P/N 804-0007-06, 0212:3-127, 0212:3-130, 0212:3-136, 0224:5-144
- Fuse and Alarm Panel Rear View, 0212:3-128
- Fuse Flag Color, 0224:4-10
- fuse holder board (FAP), 0338:2-7
- Fuse Holders, 0224:4-8
- Fuse Location, 0224:4-25
- fuse panel, 0338:5-6, 2970:7-3
- Fuse Panel alarm has cleared, 0338:3-161
- fuse panel shelf power connectors, 0224:B-68, 0243:B-28
- Fuse Positions, 0224:4-24
- fuse positions

DCM fan assembly, 0338:3-379
 EOAP, 0338:5-6, 2970:7-3
 Fuse Spares Inventory, 0338:2-36
 fuse, blown, 0338:2-8
 FWORD can only be used with PADDR, 0177:2-301
 FWORD is not supported at this time, 0177:2-301

G

Gateway configuration procedure, 0097:2-9
 Gateway Measurements, 0338:4-107
 Gateway routing, 0097:2-5
 gateway routing, 0347:5-181
 Gateway Screening
 LNP—Impact of LNP on Other Features (22.0), 0347:4-67
 Gateway Screening (GWS), 0212:3-87
 Gateway Screening (GWS) Configuration, 0098:2-1, 0098:3-1, 0098:4-1, 0098:5-1, 0098:6-1, 0098:7-1, 0098:8-1, 0098:9-1, 0098:10-1, 0098:11-1, 0098:12-1, 0098:13-1, 0098:14-1, 0098:15-1
 Gateway Screening Change commands
 Calling Name Conversion Facility (CNCF) (23.1), 0347:2-58
 Gateway Screening Enter commands
 Calling Name Conversion Facility (CNCF) (23.1), 0347:2-57
 Gateway Screening Retrieve commands
 Calling Name Conversion Facility (CNCF) (23.1), 0347:2-58
 Gateway screening rules table is full, 0177:2-239
 Gateway Screening States, 0098:2-5
 Gateway Screening stop action commands
 Calling Name Conversion Facility (CNCF) (23.1), 0347:2-57
 Gateway STP - GTWYSTP, 0288:3-52
 Gateway STP impact
 National Spare Network Indicator Support (EAGLE 22.2), 0347:4-155
 gateway STP impact
 National Spare Network Indicator Support (EAGLE 24.0), 0347:4-157
 Gateway Threshold Exceeded Notification (22.0), 0347:3-25
 gc, 0348:3-37, 0348:3-41
 GDB, 0188:1-11, 0190:1-10, 0193:1-12, 0195:1-10, 0348:1-10
 GDB requirements, 0190:2-49
 general information, 0188:1-2
 general instructions for MPS alarm recovery procedures, 0096:3-19, 2712:3-18
 General Procedure for G-Flex Activation, 0188:4-3, 0190:4-2, 0190:4-4
 General Procedure for INP Activation, 0193:4-2, 0193:4-4
 general purpose relay connector 01, 0224:B-38, 0243:B-10
 general purpose relay connector 02, 0224:B-39, 0243:B-11
 General Purpose Relay Connectors, 0212:3-28
 General Purpose Serial Interface Connector, 0212:3-28
 General Purpose Service Module II card, 0190:2-52
 General Purpose Service Module-II (GPSM-II) for MCAP Slot (Release 28.0), 0347:3-31
 General Requirements, 0188:2-22, 0190:2-49
 general requirements
 Nested Cluster Routing (EAGLE 26.0), 0347:4-162
 Generic Network Error Codes, 0197:2-119
 getcomm, 0100:3-122

Master Index

GFDB, 0188:1-11, 0190:1-10, 0193:1-12, 0195:1-10
G-Flex, 0188:1-11, 0190:1-10, 0193:1-12, 0347:2-2, 0348:1-10
G-Flex Activation Unsuccessful due to Insufficient Database, 0188:5-11
GFLEX and LNP are mutually exclusive, 0177:2-701
G-Flex C7 Relay
 description, 0188:2-1
G-Flex C7 Relay (26.3), 0347:3-13
 Description, 0347:3-13
G-Flex C7 Relay feature, 0188:1-1
G-Flex C7 Relay Overview, 0188:2-1
G-Flex Data Initialization, 0188:5-6
G-Flex Enabled, but Database Exceeds DSM Memory, 0188:5-10
G-Flex Enabled, but DSM Memory Insufficient for Database, 0188:5-10
G-Flex Enabled, but DSM Memory Less Than 1 GB, 0188:5-9
G-Flex Enabled, but DSM Not Connected to EPAP, 0188:5-9
G-Flex Enabled, Normal Operating Sequence, 0188:5-9
G-Flex feature, 0025:6-1
 status reporting, 0183:4-9
G-Flex Feature Activation, 0188:4-1
GFLEX feature must be on, 0177:2-550
G-Flex Loading Mode Support, 0188:2-25
G-Flex Measurements, 0188:5-16
G-Flex MSU measurements, 0188:5-17
G-Flex MSUs, 0188:2-25
G-Flex Not Enabled at First, but then Activated on DSM, 0188:5-11
G-Flex Not Enabled, DSM Running in TSM Emulation, 0188:5-9
GFLEX or EIR feature must be on, 0177:2-772
GFLEX or GPORT feature must be ON, 0177:2-788
GFLEX or GPORT feature must be on, 0177:2-711
G-Flex pegs, 0188:5-17
G-Flex platforms, 0188:2-10
G-Flex provisioning requests, 0188:2-10
G-Flex Relay Data Combinations, 0188:2-30
G-Flex Relay Function, 0188:2-28
G-Flex relay function, 0188:2-17
G-Flex selector-specified service numbering plan, 0188:2-32
G-Flex statistics, 0188:2-25
G-Flex Status Reporting, 0188:5-4
G-Flex Subsystem Alarms, 0188:5-14
G-Flex System Status Reports, 0188:5-4
G-Flex UIMs, 0188:5-15
G-Flex VSCCP application, 0188:2-23
GFLEX, INP, or GPORT feature must be ON, 0177:2-693
GFLEX / GPORT / EIR feature must be on, 0177:2-772
GFLEX / GPORT / INP must be ON or EIR must be enabled, 0177:2-770
GFLEX / INP / GPORT / EIR / LNP ELAP Config feature must be ON, 0177:2-744
GFRF, 0188:2-28
GFRF Forwarding Message
 SCCP Portion, 0188:2-34
GFRF forwarding message
 SCCP portion, 0188:2-34
GFRF Forwarding Message - MTP Portion, 0188:2-33

Global System for Mobile communications, 0188:1-1, 0190:2-2
 Global Timing Interface, 0224:2-5
 Global Title digits (GT), 0188:3-2, 0190:3-2, 0193:3-16
 global title domain, 0190:3-8, 0195:3-7
 Global Title Indicator, 0188:2-22
 global title information, 0190:2-7
 Global Title Translation, 0097:5-24, 0188:2-3, 0190:1-1, 0193:2-10, 0195:1-2, 0288:3-38, 0288:3-59, 0288:3-60, 0347:4-76
 Global Title Translation (GTT) (20.0), 0347:3-28
 Global Title Translation Modification, 0099:1-2, 0099:1-3, 0099:2-6, 0099:2-7, 0099:2-15, 0099:2-43, 0099:2-46, 0099:2-47, 0099:2-48, 0099:3-22, 0099:3-23, 0099:3-26, 0099:3-27, 0099:3-32, 0099:3-34, 0099:3-53, 0099:3-54, 0099:3-57, 0099:3-58, 0099:3-61, 0099:3-64, 0099:4-30, 0099:4-33, 0099:4-34, 0099:4-38, 0099:4-57, 0099:4-59, 0099:4-60, 0099:4-63, 0099:A-39
 Global Title Translations, 0099:3-2
 Globalcast Communications, 0190:2-37
 GLS have been removed from the system, 0338:3-369
 GLS is at minimum service limit, 0338:3-365
 GLS is available, 0338:3-364
 GLS is not available, 0338:3-367
 GMSC, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-10, 0348:1-10
 GMSCA, 0190:2-9
 GMT, 0224:5-117
 GMT fuse holders, 0338:3-6
 GMT fuses, 0338:3-6
 GP01, 0212:3-28
 GP02, 0212:3-28
 GPDB, 0190:2-10, 0193:1-12, 0348:1-10
 GPL, 0178:1-11, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-10, 0348:1-10
 GPL has been corrected, 0338:3-124
 GPL is corrupted, 0338:3-125
 GPL management procedures, 0142:3-1
 G-Port, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-10, 0347:5-20, 0348:1-10
 G-Port Activation Unsuccessful due to Insufficient Database, 0190:5-11
 G-Port Circular Route Prevention, 0190:2-2
 G-Port Considerations, 0190:2-47
 G-Port Data Initialization, 0190:5-6, 0193:5-8
 G-Port database audit, 0190:2-35
 G-Port Enabled, but Database Exceeds DSM Memory, 0190:5-10
 G-Port Enabled, but DSM Memory Insufficient for Database, 0190:5-10
 G-Port Enabled, but DSM Memory Less Than 1 GB, 0190:5-9
 G-Port Enabled, but DSM Not Connected to EPAP, 0190:5-9
 G-Port Enabled, Normal Operating Sequence, 0190:5-9
 G-Port feature, 0025:6-1
 status reporting, 0183:4-9
 G-Port Feature Activation, 0190:4-1
 GPORT feature must be on, 0177:2-709
 GPORT feature must be on when (N)SERV=GPORT, 0177:2-708
 GPORT feature requires DSM Cards, 0177:2-708
 G-Port Loading Mode Support, 0190:2-52
 G-Port Measurements, 0190:5-17
 G-Port measurements, 0190:3-13
 G-Port Message Handling, 0190:2-56

Master Index

- G-Port Message Relay messages, 0190:2-47
- G-Port MNP (26.2), 0347:3-20
 - changed commands, 0347:3-21
 - New Commands, 0347:3-20
 - Upgrade Considerations, 0347:3-25
- G-Port MNP feature, 0190:1-1, 0190:2-2
- G-Port MNP Overview, 0190:2-2
- G-Port Mobile Number Portability database, 0347:5-19, 0347:5-20
- G-Port Node in GSM Network, 0190:2-46
- G-Port Not Enabled at First, but then Activated on DSM, 0190:5-11
- G-Port Not Enabled, DSM Running in TSM Emulation, 0190:5-8
- G-Port numbering capability, 0190:3-3
- G-Port Protocol, 0190:2-52
- G-Port selector table, 0190:2-49
- G-Port Status Reporting, 0190:5-4
- G-Port Subsystem Alarms, 0190:5-14
- G-Port system options (gsmopts), 0190:3-5
- G-Port System Status Reports, 0190:5-4
- G-Port traffic alarms, 0190:5-14
- G-Port UIMs, 0190:5-15
- GPSI, 0212:3-28
- GPSM-II, 0190:2-52, 0197:2-3
- GPSM-II card IMASP), 0145:4-2
- GPSM-II LEDs, 0338:A-9
- GPSM-II required to support more than 700 links, 0177:2-462
- GR-376 EOAP, 0025:3-18, 0212:2-19
- GR-376 Interface (26.0), 0347:3-28
 - commands, 0347:3-29
 - Limitations, 0347:3-30
- Graphical User Interface, 0178:3-2, 0183:3-1
- graphical user interface, 0183:3-2
- gray flag, 0224:4-24
- Gray List Processing, 0195:2-7
- green cable, 0224:4-20
- grille, removing, 0338:2-34
- ground
 - main, 0095:6-5, 2969:6-5
 - plane, 0095:6-3, 2969:6-3
 - window, 0095:6-4, 2969:6-4
- ground bar, 0224:4-16
- Ground Cable, 0224:4-16
- ground cable, 0224:4-16
- ground cable installation, 0224:4-20
- ground plane, 0224:4-14
- Ground Window, 0224:4-15
- Grounding, 0095:2-8, 2969:2-8
- grounding, 0212:6-5, 0224:4-14
- group administration, 0096:2-21, 2712:2-19
- group code, 0183:2-13, 0188:4-9, 0190:4-10, 0193:4-10
- Group code must be in SID or SPC table, 0177:2-753
- Group code not allowed when ITUDUPPC feat is OFF, 0177:2-753
- Group code not allowed with specified network type, 0177:2-752

Group Code of destination and Secondary PC must match, 0177:2-673
 Group Code of DPCN and OPCN must match, 0177:2-713
 Group code required for ITUN when ITUDUPPC feat is ON, 0177:2-752
 Group Ticket Voucher (23.0), 0347:3-33
 Alarms, 0347:3-36
 Measurements, 0347:3-38
 Group Ticket Voucher for SCCP Cards (27.0), 0347:3-39
 Changed Commands, 0347:3-40
 New UAMs/ UIMs, 0347:3-40
 Upgrade Considerations, 0347:3-41
 groupcode of DPC(s) and APC/ SAPC must match when MULTGC=NO, 0177:2-731
 Groups menu, 0178:3-96, 0183:3-126
 Grp Code of dstn & True PC must match if no Secondary PC, 0177:2-673
 GSM, 0188:1-1, 0188:1-11, 0190:1-11, 0190:2-2, 0193:1-12, 0195:1-10, 0348:1-10
 GSM 03.66, 0190:2-48
 GSM 09.02, 0190:2-48
 GSM Alarms
 Subsystem Alarms, 0193:5-20, 0193:5-21
 GSM and INP System Hardware Verification, 0193:5-5
 GSM features, 0025:6-1
 GSM MAP Screening
 Activating, 0097:5-24, 0097:5-32, 0097:5-33, 0097:5-34, 0097:5-35, 0097:5-36
 Adding an Entry, 0097:5-92, 0097:5-110, 0097:5-111, 0097:5-112, 0097:5-113, 0097:5-114
 Adding Operation Code, 0097:5-64, 0097:5-74, 0097:5-75, 0097:5-76, 0097:5-77
 Changing an, 0097:5-125, 0097:5-135, 0097:5-136, 0097:5-137, 0097:5-138, 0097:5-139
 Changing Operation Code, 0097:5-82, 0097:5-88, 0097:5-89, 0097:5-90, 0097:5-91
 Changing System-Wide Options, 0097:5-56, 0097:5-58
 Configuring a Linkset, 0097:5-43, 0097:5-53, 0097:5-54, 0097:5-55
 Enhanced
 Activating, 0097:5-24, 0097:5-32, 0097:5-33, 0097:5-34, 0097:5-35, 0097:5-36
 Removing an Entry, 0097:5-115, 0097:5-123, 0097:5-124
 Removing Operation Code, 0097:5-78, 0097:5-81
 GSM MAP Screening (26.1), 0347:3-41
 alarms, 0347:3-44
 Changed Commands, 0347:3-43
 Hardware Requirements, 0347:3-42
 Limitations, 0347:3-45
 New Commands, 0347:3-42
 Upgrade Considerations, 0347:3-42
 GSM MAP Screening Duplicate / Forward (Release 29.0), 0347:3-45
 GSM MAP Screening feature must be enabled, 0177:2-679
 GSM Map Screening feature must be ON, 0177:2-674
 GSM Map Screening rcvd unknown origin, 0338:3-896
 GSM Map SCRn entry already exists or overlaps another entry, 0177:2-678
 GSM network operators, 0190:1-1
 GSM networks, 0190:1-1, 0347:5-19
 GSM Status Reporting, 0193:5-7
 GSM Subsystem Alarms, 0193:5-20
 GSM Subsystem Number Screening Entry
 Adding, 0097:5-59, 0097:5-61
 Removing, 0097:5-62, 0097:5-63
 GSM System and INP System Status Reporting, 0193:5-6

Master Index

GSMOPTS

EIR Global Response is ON, 0338:3-960, 0338:3-961
gsmopts commands, 0188:3-4, 0190:3-5, 0195:3-3
GSMOPTS table, 0190:3-4, 0190:3-5, 0193:3-3, 0195:3-5
GT Conversion table is full, 0177:2-762
GTA, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-10, 0348:1-11
GTA commands
 Enhanced GTT (26.0), 0347:2-156
GTA does not exist in any range, 0177:2-165
GTA does not match translation type's number of digits, 0177:2-165
GTA Length does not match GTT Set number of digits, 0177:2-570
GTA length is not defined for GTTSET, 0177:2-716
GTA length is not defined for TT, 0177:2-716
GTA range does not exist, 0177:2-164
GTA range is already assigned, 0177:2-166
GTA range overlaps a current range, 0099:3-22, 0099:3-43, 0099:3-53, 0099:4-28, 0099:4-49, 0099:4-55, 0177:2-163
GTAI, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-10
GTI, 0188:1-11, 0188:2-22, 0190:1-11, 0193:1-12, 0195:1-10
GTI (A)=4, and GTI (X)=1 and 3 are not supported, 0177:2-563
GTI input clock anomalies detected, 0338:3-830
GTI network domain does not match GTT set, 0177:2-567
GTI/GTIA is invalid for specified (N)SERV, 0177:2-696
GTI/GTIA/GTII/GTIN not within specified range of 1 to 4, 0177:2-732
GTIA/GTI must not be specified when (N)SERV= GPORT, 0177:2-710
GTII must not be specified when (N)SERV = INPQ, 0177:2-696
GTT, 0178:1-11, 0188:1-11, 0188:2-3, 0190:1-1, 0190:1-11, 0193:1-12, 0195:1-2, 0195:1-10, 0347:5-21, 0348:1-11
GTT by TT Measurements and GR-376 Enhancements (26.0), 0347:3-48
 Changed Commands, 0347:3-50
 Upgrade Considerations, 0347:3-50
GTT commands
 EAGLE 5 SAS
 rtrv-gtt, 0197:2-56, 0197:2-61, 0197:2-67
 rtrv-tt, 0197:2-56, 0197:2-61, 0197:2-67
GTT DBMM table is full, 0177:2-598
GTT Error Reporting Enhancements (21.0), 0347:3-50
GTT Feature, 0197:2-56
GTT feature must be ON, 0177:2-247
GTT must be on before EGTT can be on, 0177:2-561
GTT must be ON before GPORT can be ON, 0177:2-707
GTT must be ON before INP can be ON, 0177:2-689
GTT must be ON before MGTT can be ON, 0177:2-282
GTT must be ON before VGTT can be ON, 0177:2-667
GTT must be ON before XGTT can be enabled, 0177:2-465
GTT Selector already exists in GTII-TT-NP(V)-NAI(V), 0177:2-685
GTT Selector already exists in GTIN24-TT-NP(V)-NAI(V), 0177:2-549
GTT Selector already exists in GTIN-TT-NP(V)-NAI(V), 0177:2-685
GTT Selector does not exist in GTII-TT-NP(V)-NAI(V), 0177:2-686
GTT Selector does not exist in GTIN24-TT-NP(V)-NAI(V), 0177:2-549
GTT Selector does not exist in GTIN-TT-NP(V)-NAI(V), 0177:2-686
GTT Selector specified by GTI-TT-NP(V)-NAI(V) already exists, 0177:2-565

GTT Selector specified by GTI-TT-NP(V)-NAI(V) does not exist, 0177:2-566
 GTT selectors, 0190:2-49
 GTT Set specified by GTTSN already exists, 0177:2-566
 GTT Set specified by GTTSN does not exist, 0177:2-566
 GTT Set specified by GTTSN has GTAs assigned to it, 0177:2-569
 GTT Set specified by GTTSN has GTT Selectors assigned to it, 0177:2-568
 GTT Set table is full, 0177:2-567
 GTT Table Increase (Release 29.0), 0347:3-51
 GTT table is full, 0177:2-190
 GTT UIM 21 Digit Length Enhancement (Release 29.0), 0347:3-52
 GTT Warning window, 0197:2-56
 GTT/SCCP measurements, 0188:5-17
 GTTSN must not be specified as NONE, 0177:2-568
 Gtway IP Address is invalid, 0177:2-636
 Gtway IP Address must be local to this cards A, B network, 0177:2-637
 GTWYSTP - Gateway STP, 0288:3-52
 GUI, 0178:1-11, 0178:3-2, 0183:5-2
 GUI Main Screen, 0178:3-5, 0183:3-5
 GUI menus, 0183:3-2, 0183:5-2
 GWS and LNP must be ON before TLNP can be ON, 0177:2-596
 GWS Error Reporting Enhancement (21.0), 0347:3-53
 GWS feature must be ON, 0177:2-249
 GWS MSU discard threshold exceeded, 0338:3-801
 GWS MSU discarded by redirect function, 0338:3-716
 GWS MSU too large to be redirected, 0338:3-718
 GWS must be ON before CNCF can be ON, 0177:2-588
 GWS must be ON if LAN is ON, 0177:2-244
 GWS rcvd a priority that is not allowed, 0338:3-626
 GWS rcvd AFTPC that could not be CNCFd, 0338:3-856
 GWS rcvd AFTPC that could not be RDCTd, 0338:3-767
 GWS rcvd CDPA that could not be CNCFd, 0338:3-852
 GWS rcvd CDPA that could not be RDCTd, 0338:3-763
 GWS rcvd CGPA that could not be CNCFd, 0338:3-854
 GWS rcvd CGPA that could not be RDCTd, 0338:3-765
 GWS rcvd Cld Party that is not allowed, 0338:3-631
 GWS rcvd Clg Party that is not allowed, 0338:3-629
 GWS rcvd DPC that is blocked, 0338:3-622
 GWS rcvd DPC that is not allowed, 0338:3-618
 GWS rcvd H0/H1 that is not allowed, 0338:3-737
 GWS rcvd invalid GTI in TT screening, 0338:3-809
 GWS rcvd ISUP that is not allowed, 0338:3-806
 GWS rcvd nonSCCP msg in CGPA/CDPA screen, 0338:3-808
 GWS rcvd nonSNM msg in DESTFLD screening, 0338:3-807
 GWS rcvd OPC that is blocked, 0338:3-620
 GWS rcvd OPC that is not allowed, 0338:3-616
 GWS rcvd RSP, AFTPC not in routing tbl, 0338:3-698
 GWS rcvd RSR, AFTPC not in routing tbl, 0338:3-699
 GWS rcvd SCMG with not allowed AFTPC, 0338:3-635
 GWS rcvd SIO that is not allowed, 0338:3-624
 GWS rcvd TFA, AFTPC not in routing tbl, 0338:3-696
 GWS rcvd TFC, AFTPC not in routing tbl, 0338:3-628, 0338:3-748, 0338:3-749, 0338:3-750
 GWS rcvd TFP, AFTPC not in routing tbl, 0338:3-694

Master Index

GWS rcvd TFR, AFTPC not in routing tbl, 0338:3-695
GWS rcvd Translation Type not allowed, 0338:3-633
GWS rcvd TT that could not be CNCFd, 0338:3-858
GWS rcvd TT that could not be RDCTd, 0338:3-769
GWS rcvd UPU, AFTPC not in routing tbl, 0338:3-697
GWS/GTT shared table is full, 0177:2-234
GWSA, GWSM, GWSD are invalid without SCRSET specified, 0177:2-133
GX25 cannot make connection, 0338:3-788
GX25 DPC not defined, 0338:3-785
GX25 incorrect X25 address, 0338:3-780
GX25 logical channel cleared, 0338:3-790
GX25 outbound data exceeds packet size, 0338:3-776
GX25 route already connected, 0338:3-779
GX25 route not available, 0338:3-778
GX25 route not found, 0338:3-777
GX25 unexpected restart received, 0338:3-791
GX25 unrecognized X25 called address, 0338:3-787
GX25 unrecognized X25 calling address, 0338:3-786
GX25 unsupported MSU type received, 0338:3-783
GX25 unsupported packet type received, 0338:3-781

H

H0 and H1 cannot be specified for SI greater than 2, 0177:2-201
H0 and H1 must be specified for given SI, 0177:2-200
H0/H1 matches existing H0/H1 in given SR, 0177:2-200
H1 must be wild card if H0 is wild card, 0177:2-202
Halt MPS menu, 0178:5-23, 0183:5-26
Halt MPS screen, 0178:3-78, 0183:3-49
Hard Disk Drive, 0212:3-54
hard disk drive
 label, 0095:B-9, 0095:B-11, 0095:B-12, 0095:B-14, 0095:B-15, 0095:B-18, 2969:B-9, 2969:B-11, 2969:B-12, 2969:B-14, 2969:B-17
 part number, 0095:B-9, 0095:B-11, 0095:B-12, 0095:B-14, 0095:B-15, 0095:B-18, 2969:B-9, 2969:B-11, 2969:B-12, 2969:B-14, 2969:B-17
 replace, 0095:7-23, 2969:7-24
hard drive, 2969:7-4
hard drive and CD-ROM drive
 Embedded OAP (24.0), 0347:2-133
hard drive card
 replace, 0338:5-103, 2970:6-52
 troubleshoot, 0338:5-8, 2970:7-5
hard drive jumper settings, 0338:5-10, 2970:7-7
hard drives, 2969:7-4
hardware
 platform, 0025:4-10
 platform, MPS, 0178:2-3, 0183:2-2
 verification of DSM system, 0183:4-4
 verification, DSM system, 0178:4-5
Hardware and Installation Manuals, 0212:1-18, 0243:1-19
hardware configuration, 0188:5-5, 0190:2-51
 Link Fault Sectionalization (21.0), 0347:4-15

- hardware configuration required, 0190:5-12
- hardware descriptions, 0212:3-1, 0212:4-1, 0224:3-1, 0224:4-1, 0224:5-1
- Hardware Notes, 0212:6-13
- Hardware Operational Test Manual, 0224:2-11, 0243:1-40
- Hardware Repair and Return, 0212:1-24, 2970:1-11
- hardware required
 - Large System (27.2), 0347:4-1
- Hardware Requirements, 0188:5-1, 0190:5-1, 0195:4-1, 0197:2-2
 - Unix Workstation, 0197:2-2
 - Windows Workstation, 0197:2-2
- hardware requirements
 - 48 Million Numbers (27.0), 0347:2-12
 - Eagle Application Support for E1 (26.3), 0347:2-106
 - Embedded OAP (24.0), 0347:2-130
 - Enhanced Bulk Download (25.0), 0347:2-144
 - GSM MAP Screening (26.1), 0347:3-42
 - High-Speed Multiplexer (HMUX) (27.2), 0347:3-68
 - INAP-based Number Portability (INP) (26.05), 0347:3-82
 - INP Number Normalization (26.3), 0347:3-86
 - Multi-Port LIM (EAGLE 27.1), 0347:4-154
 - STPLAN Port to DCM (EAGLE 26.0), 0347:5-91
 - TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-149
 - Variable Length GTT (Eagle 26.1), 0347:5-172
 - Weighted SCP Load Balancing (Eagle 27.2), 0347:5-176
- hardware return, 0212:1-24, 0224:1-23, 0243:1-24, 0338:1-11, 2970:1-11
- Hardware Verification Codes, 0338:E-1
- hardware, MPS
 - list of equipment, 0025:6-2
 - overview, 0212:4-12
- hardware, MPS frame
 - layout, 0212:4-13
- hardware, MPS system configuration, 0025:6-4, 0096:2-5, 2712:2-5
- HC MIM Temperature Alarm Thresholds - Changing, 0120:3-279
- HCAP, 0193:1-12
- HCMIM, 0212:3-111, 0212:3-112
 - dependencies, 0212:3-112
 - description, 0212:3-111
 - requirements, 0212:3-112
 - timing, 0212:3-115
- HC-MIM does not support interface to a channel card, 0177:2-544
- header format, 0178:5-11
- Heading 1, 0224:5-1
- Health Check Procedure - MPS, 0288:2-74
- Health Check, System
 - status and alarm reporting, 0178:4-2, 0183:4-1
- heat-shrink, 0224:4-16
- Heat-shrink gun, 0224:4-16
- Heat-shrink gun (hot air blower), 0224:4-14
- Heavy Duty Frame, 0224:3-27, 0224:3-28
- heavy duty frame
 - anchoring to concrete under raised floor, 0095:4-10, 2969:4-10
 - anchoring to raised floor with support channel and spring nut, 0095:4-16, 2969:4-16

Master Index

- anchoring to slab floor, 0095:4-6, 2969:4-6
- floor preparation, 0095:4-3, 2969:4-3
- installing, recommended tools, 0095:4-3, 2969:4-3
- Heavy-Duty Frame Panels, 0224:3-25
- Help menu
 - FTP-Based Table Retrieve Application, 0197:2-104
- hexadecimal, 0197:2-48
- hexadecimal digits, 0190:2-48, 0193:2-10
- HH must be specified when PERIOD=SPECIFIC, 0177:2-114
- High Density Interconnect (HDI), 0212:3-21, 0212:3-31
- high provisioning traffic situations, 0190:5-2, 0195:4-2
- High Speed Clock A for card normal, 0338:3-224
- High speed clock alarm(s) cleared, 0338:3-290
- High Speed Clock B for card normal, 0338:3-225
- High Speed Clocks A and B for card failed, 0338:3-222
- High Speed Clocks A and B for card normal, 0338:3-236
- High speed IMT packet router, 0212:3-38
- High Speed Master Timing (26.0), 0347:3-57
 - administration, 0347:3-63
 - feature concept, 0347:3-60
 - maintenance, 0347:3-64
 - master clock, 0347:3-60
 - MCAP card, 0347:3-63
 - system clocks, 0347:3-60
 - TDM card, 0347:3-61
- High Speed Operations Protocol, 0025:4-4
- High-Capacity Multichannel Interface Module, 0025:3-11, 0212:3-111
- high-speed Ethernet links, 0193:2-4, 0195:2-10
- High-Speed IMT Packet Router, 0025:3-6
- High-Speed Master Timing, 0025:3-13, 0212:2-18, 0224:5-81
- High-Speed Multiplexer, 0025:3-7, 0212:2-8
- High-speed Multiplexer, 0224:1-5, 0224:5-6, 0224:5-91, 0224:5-140
- High-Speed Multiplexer (HMUX) (27.2), 0347:3-66
 - Hardware Requirements, 0347:3-68
 - New / Changed Commands, 0347:3-67
 - Upgrade Considerations, 0347:3-69
- high-traffic situations, 0188:2-11, 0190:2-36
- HIPR, 0025:3-6, 0212:3-38
- HIPR must be equipped on the shelf where HC-MIM card reside, 0177:2-546
- HIPR, High-Speed Inter-processor Message Transport Packet Router, 0338:A-16
- HLR, 0188:1-1, 0188:1-11, 0188:2-1, 0190:1-11, 0193:1-12, 0195:1-10, 0347:5-20, 0348:1-11
- HLR translation, 0190:2-46
- HLRB, 0190:2-7, 0190:2-10
- HMUX, 0097:6-7, 0097:6-19, 0212:3-37, 0212:3-43, 0224:2-3, 0224:5-83, 0243:1-37
- HMUX not responding Error, 0338:3-504
- HMUXTVG must be ON before E5IS can be ON, 0177:2-704
- HMUXTVG option, 0097:6-7
- Holdover BITS Clock Support (21.0), 0347:3-69
- holdover clock, 0212:3-139, 0224:5-112
- holdover clock BITS clock source cables, 0224:5-115
- holdover clock card placement, 0224:5-108
- Holdover Clock FAP, 0224:5-112

holdover clock fuses, 0224:5-117
 holdover clock installation, 0224:5-108
 holdover clock output connections, 0224:5-112
 holdover clock output panel frame ground, 0224:5-109
 holdover clock power connections, 0224:5-109
 holdover clock switch settings, 0224:5-110
 Holdover clock trouble cleared, 0338:3-149
 holes are drilled, 0224:3-21
 Home Location Register, 0188:1-1, 0188:2-1
 Home Location Register (HLR), 0347:5-19
 Home RNs, 0193:2-18
 HOME SMSC specific addresses, 0347:5-23
 Home SMSC Table is full, 0177:2-541
 HOME SMSCADDR table, 0347:5-23
 HOMERN, 0193:2-18, 0193:2-21
 HOMERN Table is full, 0177:2-690
 Host assignment to IPLIM / IPLIMI card not supported, 0177:2-745
 Host Key - Secure EAGLE 5 SAS
 Provisioning, 0197:2-45
 host key checking - strict, 0197:2-46
 Host Key Fingerprint
 Public
 EAGLE 5 SAS, 0197:2-45, 0197:2-46, 0197:2-48, 0197:2-50
 host key flag - strict, 0197:2-46
 Host Name Referenced by Application Socket or Association, 0177:2-733
 Host Name Still Referenced in IP Link Table, 0177:2-662
 Host table is full, 0177:2-618
 Host table must contain IP link addresses, 0177:2-626
 host=epap-a, 0188:4-22, 0188:4-31, 0190:4-22, 0190:4-31, 0193:4-22, 0193:4-31
 Hostname must be unique, 0177:2-617
 hosts.xml, 0197:2-45, 0197:2-46, 0197:2-48, 0197:2-49, 0197:2-50
 hot air blower, 0224:4-16
 hot-swap, 0347:5-82
 hot-swapping FAP components, 0338:2-6
 Hourly Maintenance Measurements, 0338:4-91
 Hourly Maintenance Report, 0183:4-15, 0188:3-11, 0188:5-3, 0190:5-3, 0193:5-4
 Hourly measurement collection in progress, 0177:2-116
 hourly status message report
 Simplifying BIP (Board ID PROM) for Eagle STP Boards (EAGLE 23.1), 0347:5-81
 how to activate G-Flex, 0188:1-2
 how to remove EOAP shelf, 0338:5-71, 2970:6-18
 HRN, 0193:1-12
 HRNs, 0193:2-18
 HS Clock A for card failed, B normal, 0338:3-218
 HS Clock B for card failed, A normal, 0338:3-220
 HS Master Timing, 0224:5-83
 HSOP, 0025:4-4
 Htap, 0224:4-10
 Htapped, 0095:6-4, 0224:4-15, 2969:6-4
 HTML output, 0178:3-3
 http web server, 0178:3-3, 0183:3-2
 hub

Master Index

description, 0212:4-47, 0212:4-50, 0243:2-13
front LEDs, 0212:4-48, 0212:4-50, 0243:A-18
front view, 0212:4-47
FRU, 0096:5-2, 2712:5-2
overview, 0096:2-6, 2712:2-5
rear view, 0212:4-48
replacement procedure, 0096:5-7, 2712:5-6
HVAC requirements, 0095:2-6, 2969:2-6
HW cannot support purchased TPS rate, 0338:3-607
HW limiting TPS rate alarm cleared, 0338:3-606

I

I/O architecture, MPS Server, 0212:4-28
I/O connectors, 0212:3-27, 0212:3-32
I/O devices, 0145:4-2
i2000 Hardware Reference, 0243:1-19
IAM, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-10
IAM message, 0190:2-7, 0190:2-8
Icon, FTRA, 0197:2-13
icons, 0193:1-9
ID, 0348:1-11
id, 0348:3-36, 0348:3-40, 0348:3-44, 0348:3-46
ID must be specified, 0177:2-412
identical point codes, 0183:2-13
identify active EPAP, 0190:5-2, 0195:4-2
identify error message requests, 0190:5-12
Idle Port Logout, 0178:3-81, 0183:3-111
Idle Terminal Port Logout (21.0), 0347:3-69
Idle Timeout, 0178:3-108, 0183:3-138
idletimeout, 0348:3-9
IETF M3UA for "A" Link Connectivity (Release 28.1), 0347:3-71
IETF Protocol Update (Release 28.0), 0347:3-72
IETF Protocol Update (Release 28.1) (IP7 Release 6.0), 0347:3-72
IETF SCTP for "A" Link Connectivity to SCP/HLR/MGC, 0347:3-73
If AUTO=yes, then DUPLEX and SPEED are not allowed, 0177:2-619
If DIR=BKWD, SDATE/STIME must be > EDATE/ETIME, 0177:2-779
If Domain name is specified, RSTDMAIN is not valid, 0177:2-624
If GTIXLAT is 22, NAI and NP cannot be specified, 0177:2-721
If GTIXLAT is 24, NAI and NP must be specified, 0177:2-721
If GWSA=OFF then GWSD must also be OFF, 0177:2-134
If IO or ETT specified, BOTH opt. Parmes must be specified, 0177:2-363
If IPADDR is specified SUBMASK is required, 0177:2-622
If NDIGITS = 0 then PREFIX parameter is invalid, 0177:2-34
If NGTI is 2, NNP and NNAI cannot be specified, 0177:2-765
If NGTI is 4, NNP and NNAI must be specified, 0177:2-765
If NGTI is 4, PC cannot be ANSI, 0177:2-835
If OAP parameter not specified as ALL, FORCE=YES required, 0177:2-588
If PARM is specified, PVALUE must be specified, 0177:2-620
If SDATE=EDATE, then ETIME after or same as STIME, 0177:2-405
If specified BPS must be 1984000 when Linkclass = Unchan, 0177:2-802
If specified, BPS must be 2048000 for LIME1ATM Card, 0177:2-497

If specified, BPS must be 56000 for Multi Port LIM, 0177:2-421
 If TIMER is specified, TVALUE must be specified, 0177:2-619
 IGTTLS - Intermediate GTT Load Sharing, 0099:1-2, 0099:1-3, 0099:2-3, 0099:2-16, 0099:2-43, 0099:2-47,
 0099:2-138, 0099:A-3, 0099:A-4, 0099:A-6, 0099:A-7, 0099:A-8, 0099:A-9, 0099:A-10, 0099:A-11,
 0099:A-14, 0099:A-15, 0099:A-16
 IGTTLS Feature
 Activating, 0099:A-3
 Turning off, 0099:A-14
 ILA, 0097:6-7, 0212:3-18, 0212:3-19, 0212:3-21, 0212:3-37, 0212:3-56, 0212:3-57, 0224:2-3, 0224:A-6,
 0243:1-38, 0243:A-3, 0338:A-17, 0338:A-22
 Illegal Address Error, 0338:3-503
 Illegal Address Error has Cleared, 0338:3-501
 Illegal attempt to delete yourself, 0177:2-102
 IMEI, 0195:1-10
 Check_IMEI Message Handling, 0195:2-15
 Example Individual IMEI Table, 0195:2-5
 Logic for IMEIs in Multiple Lists, 0195:2-5
 IMEI Blocks, 0348:2-23
 IMEI table, 0195:2-4
 impact on other features
 Multiple Point Code Support (EAGLE 26.05), 0347:4-147
 Import File to PDB, 0183:3-98
 import / export traffic, 0190:2-41
 imported numbers, 0190:1-1
 Improved Routing Management (20.0), 0347:3-80
 IMSI, 0188:1-1, 0188:1-11, 0188:2-1, 0190:1-11, 0190:2-2, 0190:2-45, 0193:1-12, 0195:1-11, 0348:1-11,
 0348:2-3
 imsi, 0348:3-16, 0348:3-17, 0348:3-23, 0348:3-25, 0348:3-28, 0348:3-33
 IMSI (E.212) Routing, 0188:2-4
 IMSI incomplete, 0188:2-33
 IMSI menu, 0183:3-60, 0183:3-76, 0183:3-81
 IMSI number, 0188:4-1, 0190:4-1
 IMSI numbers, 0188:3-2
 IMSIs, 0348:2-20
 IMT, 0212:3-7, 0212:3-19, 0212:3-28, 0212:3-32, 0212:3-90, 0224:2-3, 0243:1-37, 0243:1-38
 IMT allowed, 0338:3-174
 IMT Bus States, 0338:3-9
 IMT Cables, 0224:5-7
 IMT command changes
 Flash Memory Management (23.0), 0347:3-5
 IMT connectors, 0212:3-28, 0212:3-32
 IMT Fault Isolation (22.0), 0347:3-80
 IMT fault test in progress, 0177:2-440
 IMT inhibited, 0338:3-175
 IMT interface circuits, 0212:3-63
 IMT statistics collection in progress - Repeat later, 0177:2-444
 IMT Subsystem Alarms (20.0), 0347:3-81
 IMT System Alarm Level Determination, 0338:3-9
 IN, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-11, 0288:3-22, 0348:1-11
 in, 0100:3-119, 0100:3-158, 0100:3-431, 0100:3-441
 IN Platforms (PPSMS Servers), 0347:5-20
 Inactivity, 0183:3-138, 0183:3-141

Master Index

INAP, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-11, 0348:1-11
INAP-based Number Portability (INP) (26.05), 0347:3-81
 enhanced commands, 0347:3-83
 hardware requirements, 0347:3-82
 New Commands, 0347:3-82
IN-based MNP, 0190:2-5
IN-based solution, 0193:2-1
Incermental Downloading, 0195:2-13
incoherent, 0190:3-15, 0193:3-9, 0195:3-14
incoherent DSM database, 0183:2-8
incoherent EPAP RTDB, 0188:5-14
Incompatible HW for provisioned slot, 0338:3-176
incomplete IMSI, 0188:2-33
inconsistent, 0190:3-15, 0193:3-9, 0195:3-14
Inconsistent DSM Card Alarm, 0178:2-19, 0183:2-32
inconsistent RTDB, 0188:5-14
Incorrect DB version (<database>, <disk>, <MASP status>), 0177:2-417
Incorrect feature configuration, 0338:3-128
Incorrect information unit, expecting card location - <parm>, 0177:2-24
Incorrect information unit, expecting IP address - <parm>, 0177:2-21
Incorrect information unit, expecting mnemonic - <parm>, 0177:2-22
Incorrect information unit, expecting number - <parm>, 0177:2-21
Incorrect information unit, expecting number or * - <parm>, 0177:2-23
Incorrect information unit, expecting number or none - <parm>, 0177:2-25
Incorrect information unit, expecting number or range - <parm>, 0177:2-21
Incorrect information unit, expecting point code - <parm>, 0177:2-22
Incorrect information unit, expecting string - <parm>, 0177:2-22
Incorrect information unit, translation type - <parm>, 0177:2-23
Incorrect input, expecting number, * or range - <parm>, 0177:2-25
Incorrect Motherboard - CPU, 0338:3-551
Incorrect port configuration, 0338:3-373
incorrect results and errors, 0188:2-33
Increase Gateway Screening Screen Sets to 255 (22.0), 0347:3-87
Increase the Number of Mated Application Entries (22.0), 0347:3-106
Increased GTT Transactions (21.0), 0347:3-106
Increased Linkset Capacity, 0347:3-85
Increased Linkset Capacity (Release 28.0), 0347:3-85
Increased number of translations, 0188:2-28
Increasing
 LRN Quantities on the Eagle, 0288:3-75
 NPANXX Quantities on the Eagle, 0288:3-75
Increasing the FTA (File Transfer Area)
 Security Log Increase (EAGLE 26.05), 0347:5-73
Increasing the Size of the Service Provider ID Table (23.2), 0347:3-106
Incremental Downloading, 0188:2-12, 0193:2-9
incremental loading, 0188:2-27, 0190:2-39
 TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-139
incremental loading from EPAP, 0188:2-25
incremental loading, DSM, 0178:2-17, 0183:2-29
Incremental update, 0188:2-27
incremental update, 0190:2-39
incremental updates, 0188:2-26, 0190:2-38

INCSLP, 0288:3-52, 0288:3-55, 0288:3-57
 IND, 0288:4-13, 0288:4-14, 0288:4-15, 0288:4-16, 0288:4-18, 0288:4-19
 IND cannot be greater than 3, 0177:2-302
 IND parameter must be 6 or 10, 0177:2-453
 indicator lights
 tape drive, 0212:4-21
 indirect routing, 0190:2-6
 INE, 0190:2-10, 0190:2-11, 0193:1-12
 information messages, 0178:3-115, 0178:3-116
 informational banner messages, 0183:2-26, 0183:3-145
 Inh EIR SS request already outstanding, 0338:3-653
 Inh LNP SS request already outstanding, 0338:3-810, 0338:3-820
 inh-alm, 0145:6-371, 0188:3-13, 0190:3-17, 0190:5-12, 0193:3-11, 0195:3-17
 inh-card, 0145:6-377, 0188:3-12, 0188:4-6, 0188:4-28, 0188:5-7, 0188:5-8, 0190:3-15, 0190:4-7, 0190:4-27,
 0190:5-7, 0190:5-8, 0193:3-9, 0193:4-7, 0193:4-28, 0193:5-10, 0193:5-11, 0195:3-14, 0195:4-7, 0195:4-8
 inhfepalm, 0100:3-122
 inhibit LIMs, 0190:5-6, 0193:5-9, 0195:4-6
 inhibit loading DSM card, 0188:5-12
 Inhibit rejected, target terminal is not equipped, 0177:2-237
 inhibited alarms, 0145:4-3
 inhibiting
 DSM, rmv-card, 2339:8-3
 mated application subsystem, 2339:8-4
 inh-imt, 0145:6-378
 inh-map-ss, 0145:6-379
 inh-map-ss command, 2339:8-4
 inh-slk, 0145:6-382
 inh-trm, 0145:6-383
 INIT=YES only valid with BID record, 0177:2-97
 init-card, 0145:6-384, 0188:4-8, 0188:4-39, 0190:4-8, 0190:4-39, 0193:4-9, 0193:4-44
 init-card command, 0197:2-45, 0197:2-48, 0197:2-49
 init-flash, 0145:6-390
 Initial Command Response Timeout, 0177:2-574
 initial configuration steps, 0178:5-26, 0183:5-34
 initial ELAP-LSMS connection, 0178:2-10
 initial implementation, 2970:4-4
 Initial Platform Manufacture, 0178:5-26, 0183:5-34
 Initialization, 0178:5-8
 initialization
 ELAP, 0178:5-8
 EPAP, 0183:5-7
 Initialization - ELAP, 0288:2-40
 Initialization - ELAP 5.0, 0288:2-45
 initializing DSM cards, 0190:2-37
 Initializing the FTRA, 0197:2-13
 Initializing window, 0197:2-13
 Initiate Upgrade, 0178:5-22, 0183:5-25
 init-imt-gpl, 0145:6-395
 init-mux, 0145:6-396
 init-network, 0145:6-397
 init-oap, 0145:6-400
 init-sys, 0119:2-16, 0145:6-401, 0188:4-4, 0188:4-12, 0190:4-5, 0190:4-13, 0193:4-5, 0193:4-13

Master Index

Init-sys already in progress at another terminal, 0177:2-105
init-sys command
 caution, 0188:4-4, 0188:4-12, 0190:4-5, 0190:4-13, 0193:4-5, 0193:4-13
 re-entering, 0188:4-4, 0188:4-12, 0190:4-5, 0190:4-13, 0193:4-5, 0193:4-13
INN, 0193:1-12
inoperative, 0190:5-2, 0195:4-2
inoperative Ethernet connection, 0188:5-12
INP, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-11, 0348:1-11, 0348:2-4
INP Activation Unsuccessful due to Insufficient Database, 0193:5-14
INP Alarms
 Card Related MPS Alarms, 0193:5-18
 DSM-EPAP Link, 0193:5-16
 MPS (EPAP) Alarms, 0193:5-16
INP and LNP are mutually exclusive, 0177:2-689
INP capability point code configuring, 0193:4-36
INP Considerations, 0193:2-10
INP database, 0193:2-2
INP Enabled, but Database Exceeds DSM Memory, 0193:5-13
INP Enabled, but DSM Memory Insufficient for Database, 0193:5-12
INP Enabled, but DSM Memory Less Than 1 GB, 0193:5-12
INP Enabled, but DSM Not Connected to EPAP, 0193:5-12
INP Enabled, Normal Operating Sequence, 0193:5-11
INP Feature, 0193:2-6
INP feature, 0025:6-1
 status reporting, 0183:4-9
INP Feature Activation, 0193:4-1
INP feature must be ON, 0177:2-555
INP Measurements, 0193:5-24
INP Message Protocol, 0193:2-20
INP Message Relay, 0193:2-10, 0193:2-20, 0193:2-21
INP Not Enabled at First, but then Activated on DSM, 0193:5-13
INP Not Enabled, DSM Running in TSM Emulation, 0193:5-11
INP number normalization, 0193:2-2
INP Number Normalization (26.3), 0347:3-86
 Description, 0347:3-86
 enhanced commands, 0347:3-86
 Hardware Requirements, 0347:3-86
INP or EIR feature must be ON, 0177:2-768
INP Query, 0193:2-21, 0193:2-22
INP Related Alarms, 0193:5-14
INP Service Selectors, 0193:4-42
INP Status Reporting, 0193:5-7
INP Subsystem Alarms, 0193:5-20
INP subsystem is offline in database, 0177:2-574
INP Subsystem Related UIMs, 0193:5-23
INP Subsystem UIMs, 0193:5-23
INP UAMs, 0193:5-14
 Card Related MPS Alarms, 0193:5-18
 DSM-EPAP Link, 0193:5-16
 MPS (EPAP) Alarms, 0193:5-16
 Subsystem Alarms, 0193:5-20, 0193:5-21
INP VSCCP, 0193:5-5

Input parameter - use of parameter not supported by this implementation (C<col>), 0177:2-508
 Input parameter '<parm>' - missing (C<col>), 0177:2-507
 Input parameter argument - flow-thru command string too long (C<col>), 0177:2-505
 Input parameter argument - not valid or superfluous (C<col>), 0177:2-508
 Input parameter argument - point code range error (C<col>), 0177:2-506
 Input parameter argument - range error (C<col>), 0177:2-505, 0177:2-506
 Input parameter argument - version range error (C<col>), 0177:2-504
 Input syntax
 punctuation error (C<col>), 0177:2-500
 input/output interfaces, 0193:2-2
 inserting removable cartridge, 0142:2-8
 Inserting the 2.3 Gbyte Removable Cartridge, 0338:2-14
 inspection, post-installation, 0095:6-13, 2969:6-13
 Install, 0188:4-29, 0190:4-29, 0193:4-29
 install
 card into EOAP shelf, 0338:5-75, 2970:6-22
 clock connection cable, 0224:C-36, 2970:3-41
 clock in/out cable, 2970:3-40
 cooling duct, 2970:3-17
 fan power cables, 2970:3-39
 mounting brackets, 2970:3-20
 replacement fan assembly, 0338:5-95, 0338:A-85, 2970:6-44
 terminal cables, 2970:3-45
 Install Replacement Fan Assembly, 0338:A-85
 Installation Elements, 0224:3-17
 Installation Manuals, 0212:1-18, 0243:1-19
 Installation Support, 0188:1-7
 installation, MPS, 0096:2-14, 2712:2-12
 Installer's Cable Running List, 0224:2-8, 0224:C-4, 0243:C-4
 Installing
 FTRA software, 0197:2-4
 Unix, 0197:2-9
 Windows, 0197:2-5
 Java 2 Runtime Environment software, 0197:2-5, 0197:2-8
 installing
 heavy duty frame, 0095:4-2, 2969:4-2
 Tekelec 1000 chassis in a frame, 0095:5-5, 2969:5-4
 UAL software, 2970:4-4
 Installing Java Policy File, 0178:5-7, 0183:5-6
 InstallShield Wizard, 0197:2-5
 instance table, 0348:2-5
 Insufficient #SCCP cards to support LIM - use FORCE=YES, 0177:2-610
 insufficient DSM memory, 0188:5-11
 insufficient memory alarm, 0193:5-7
 Insufficient memory for LNP, 0338:3-526
 Insufficient memory for provisioning, 0338:3-350
 Insufficient SCCP Service, 0190:5-6, 0193:5-9
 insufficient SCCP service, 0188:5-6
 integer identification (iid), 0348:3-3
 Integer value must be less than 65535, 0177:2-313
 Integrated Eagle STP/G-Flex Node, 0188:2-16
 Integrated LIM Appliques (ILAs), 0212:3-18

Master Index

Integrated LIM-AINF Card

New Hardware (EAGLE 23.1), 0347:4-192

Integrated Sentinel, 0025:5-6, 0212:2-20, 0212:5-8

Eagle Support, 0097:1-3, 0097:6-2, 0097:6-4, 0097:6-10, 0097:6-11, 0097:6-13, 0097:6-14, 0097:6-19, 0097:6-22, 0097:6-27

Integrated Sentinel (ESP Frame Side), 0025:5-8, 0212:2-23

Integrated Sentinel EAGLE STP Side, 0212:1-6

Integrated Sentinel Hardware Overview, 0212:5-9

Integrated Serial Communications Controller (ISCC), 0212:3-64, 0212:3-65, 0212:3-67, 0212:3-68

Intelligent Network-based solution, 0193:2-1

intercepting MAP messages, 0190:2-5

Interdependencies, 0224:5-84

Interface, 0212:3-103

interface

accessing ELAP GUI, 2712:A-1

accessing ELAP text, 2712:A-6

accessing EPAP GUI, 0096:A-1

accessing EPAP text, 0096:A-4

MPS Server SCSI, 0212:4-28

Quad FastEthernet Network Interface card, 0212:4-31

SAI/P card, 0212:4-31, 0212:4-43

Intermed GTT Load sharing feature must be on, 0177:2-430

Intermediate GTT Load Sharing, 0099:1-2, 0099:1-3, 0099:2-3, 0099:2-16, 0099:2-43, 0099:2-47, 0099:2-138, 0099:A-3, 0099:A-4, 0099:A-6, 0099:A-7, 0099:A-8, 0099:A-9, 0099:A-10, 0099:A-11, 0099:A-14, 0099:A-15, 0099:A-16

Intermediate GTT Loadsharing (Release 28.1), 0347:3-107

internal point codes, 0100:3-4

internal SNAI, 0193:2-7

international, 0193:2-11

international DNs and IMSIs, 0188:2-31

international entity number, 0188:2-29

international format, 0193:2-11

International Mobile Equipment Identity, 0195:1-1

International Mobile Station Identifier, 0190:2-2

International Mobile Subscriber Identity, 0188:2-1

international MSISDNs, 0190:2-54

international number, 0190:2-6, 0193:2-6, 0193:2-7

international numbers, 0188:2-31

International PC, 0193:2-17

International PC is identical to international CPC, 0177:2-70

International Spare network indicator values, 0120:2-7

International Telecommunications Union, 0188:1-1

international version, 0193:2-2

Internet Browsers, 0183:5-2

Internet Explorer, 0178:5-3, 0183:5-2

Internet Protocol host table, 0190:3-18, 0193:3-12

Inter-processor Message Transport, 0025:3-5, 0212:2-6

Interprocessor Message Transport, 0212:3-97, 0224:5-7

Interprocessor Message Transport (IMT), 0212:3-7, 0212:3-9, 0212:3-61, 0224:5-7

interprocessor message transport (IMT) interface, 0212:3-87, 0212:3-93, 0212:3-100

Interrogating Network Entity, 0190:2-10, 0190:2-11

Interval Index, 0288:4-2, 0288:4-3, 0288:4-4, 0288:4-5, 0288:4-13, 0288:4-18, 0288:4-20, 0288:4-21, 0288:4-27, 0288:4-28

intl, 0193:2-11, 0193:2-22

Introduction, 0188:1-1, 0193:1-1, 0212:1-1, 0212:2-2, 0288:2-2

Introduction to Data Model, 0348:2-4

Introduction to EIR, 0195:1-1

Introduction to G-Port, 0190:1-1

Introduction to Platform Services, 0348:2-3

Intrusion Alert, 0178:3-82, 0183:3-111

intrusion alert, 0145:4-18

Intrusion Alert (21.0), 0347:3-109

INTVL, 0288:4-3, 0288:4-5, 0288:4-13, 0288:4-14, 0288:4-15, 0288:4-16, 0288:4-18, 0288:4-19, 0288:4-20, 0288:4-22, 0288:4-23, 0288:4-25, 0288:4-26, 0288:4-27, 0288:4-28, 0288:4-29

Invalid APPL selection for SERIAL init card command, 0177:2-631

Invalid BAUD value specified, 0177:2-46

Invalid card location, 0177:2-11

Invalid card TYPE and APPL load type combination, 0177:2-29

Invalid card type for this command, 0177:2-81

Invalid character in IP address - <parm>, 0177:2-16

Invalid CLLI, 0177:2-134

Invalid combination - EDATE with STIME, 0177:2-407

Invalid combination of ADDR and PADDR specified, 0177:2-301

Invalid combination of parameters for a default routing key, 0177:2-702

Invalid combination of parameters for a partial routing key, 0177:2-700

Invalid combination of PSTNCAT and PSTNID values, 0177:2-723

Invalid combination of TYPE and DATA parameters, 0177:2-757

Invalid combination of TYPE, UENG, and CTX parameters, 0177:2-756

Invalid compression level is specified in the client configuration file - Error code 626, 0197:2-109

Invalid destination application ID, 0177:2-78

Invalid destination table, 0177:2-10

Invalid digits in IS41 MAP Digits parm, 0338:3-774, 0338:D-5

Invalid digits in MAP MSISDN parameter, 0338:3-948

invalid DN, 0193:2-11

Invalid Domain name, 0177:2-620

Invalid drive specified, 0177:2-89

Invalid ENTTYPE for this TYPE, 0177:2-111

Invalid FC value specified, 0177:2-46

Invalid Feature Access Key, 0177:2-531

Invalid file length, 0177:2-125

Invalid filename entered, 0177:2-124

Invalid FTP Password warning window, 0197:2-24

Invalid FTP User Name warning window, 0197:2-23

Invalid GPL type for this command, 0177:2-107

Invalid H0/H1 or NH0/NH1 specified, 0177:2-487

invalid hardware configuration, 0190:2-51

Invalid hardware for EISCOPY to be on, 0177:2-706

Invalid Hostname, 0177:2-615

Invalid INTRVL value specified, 0177:2-408

Invalid IP Address warning window, 0197:2-22, 0197:2-52, 0197:2-53

Invalid IP database configuration, 0177:2-834

Invalid IPADDR, 0177:2-306

Invalid Length for Map IMEI Parameter, 0338:3-739

Master Index

Invalid length of conditioned digits, 0338:3-894
Invalid length of prefixed digits, 0338:3-951
Invalid LINK for APPL, 0177:2-249
Invalid link speed combination within linkset, 0177:2-35
Invalid linkset type for card, 0177:2-39
Invalid Loopback selection for LIME1ATM, 0177:2-342
Invalid name for adapter type, 0177:2-735
Invalid NCAI parameter has been entered, 0177:2-373
Invalid OAM card type for TSC sync, 0338:3-134, 0338:3-135
Invalid OAM drive, 0177:2-10
Invalid OAM HW config or an HMUX card is out of service, 0177:2-683
Invalid offset, 0177:2-496
Invalid originating application ID, 0177:2-78
Invalid parameter, 0177:2-309
Invalid parameter combination for SI, 0177:2-650
Invalid parameter combination specified, 0177:2-53
Invalid parameter for CCS7ITU or IPLIMI, 0177:2-520
Invalid parameter for ITU-N 24bit point code, 0177:2-360
Invalid parameter for SCCP, 0177:2-518
Invalid parameter for SS7ANSI, ATMANSI, IPLIM, or SS7IPGW, 0177:2-519
Invalid parameter for VSCCP, 0177:2-520
Invalid parameter specified for report type, 0177:2-441
Invalid parameters for ACTION=COPY, 0177:2-514
Invalid Part Number, 0177:2-529
Invalid password. Keyboard is locked. Enter UNLOCK command, 0177:2-332
Invalid PERIOD for this TYPE, 0177:2-110
Invalid point code, 0177:2-135
Invalid PRTY value specified, 0177:2-46
Invalid PVN, 0177:2-705
Invalid PVNMASK, 0177:2-717
Invalid SCSI device syntax, 0177:2-124
Invalid socket/association ratio for card type, 0177:2-462
Invalid source table, 0177:2-9
Invalid STP Name Error Message window, 0197:2-20
Invalid STP Name warning window, 0197:2-20
Invalid STP Password warning window, 0197:2-23
Invalid STP User Name warning window, 0197:2-22
Invalid Subnet Mask, 0177:2-615
Invalid system, 0177:2-10
Invalid System serial number, 0177:2-578
Invalid system serial number in database, 0177:2-531
Invalid table Id, 0177:2-125
Invalid timing source for channel bridging, 0177:2-799
Invalid TRM value for SEAS TDM port, 0177:2-317
Invalid TYPE, 0177:2-121
Invalid userID/password combination, 0177:2-329
inventory
 additional server, 0095:5-2, 2969:5-1
 frame, 0095:4-2, 2969:4-2
INW Allowed card to DDL crossload, 0338:3-851
INW Card failed to DDL crossload, 0338:3-850
INW Card failed to reset, 0338:3-847

INW Card reset command issued, 0338:3-840
 INW Detected card loaded, 0338:3-842
 INW Failed to assert DDL inhibition, 0338:3-848
 INW Failed to remove DDL inhibition, 0338:3-849
 INW MAIN card as last to be reset, 0338:3-838
 INW Need to reset/remove/inhibit card, 0338:3-846
 INW Removed DDL inhibition, 0338:3-845
 INW Waiting for card loading validation, 0338:3-841
 IP, 0188:1-11, 0190:1-11, 0190:2-37, 0193:1-12, 0195:1-11, 0212:3-19, 0348:1-11
 IP - reporting EPAP maintenance data, 0188:2-11
 IP Address, 0197:2-17, 0197:2-18, 0197:2-51, 0197:2-122, 0197:2-123, 0197:2-124
 Backup - FTRA 2.0, 0197:2-22
 Backup - FTRA 2.0 or greater, 0197:2-18
 IPSM, 0197:2-48, 0197:2-49
 Primary - FTRA 2.0, 0197:2-22
 Primary - FTRA 2.0 or greater, 0197:2-18
 IP address, 0197:2-18
 IP Address - FTRA 1.0, 0197:2-22
 IP Address Field, 0197:2-52
 Backup - FTRA 2.0 or greater, 0197:2-18, 0197:2-22
 Primary - FTRA 2.0 or greater, 0197:2-17, 0197:2-22
 IP Address Field - FTRA 1.0, 0197:2-17, 0197:2-22
 IP Address found in host table, 0177:2-831
 IP address must be unique, 0177:2-625
 IP Address requires 4 octets in the range 1 . . . 254 - <parm>, 0177:2-12
 IP Address still referenced by the Def Router, 0177:2-579
 IP Address warning message, 0197:2-45
 IP addresses
 configure customer (provisioning) network, 0178:5-18, 0183:5-20
 configure DSM network, 0178:5-19, 0183:5-21
 configure ELAP Sync network, 0178:5-18
 configure EPAP Sync network, 0183:5-20
 default for DSM networks, 0178:2-7, 0183:2-9
 default for ELAP Sync network, 0178:2-8
 default for EPAP Sync network, 0183:2-9
 default router, 0178:5-18, 0183:5-20
 Dialup PPP network, 0178:2-9
 DSM networks, 0178:2-7, 0183:2-9
 ELAP Sync network, 0178:2-8
 EPAP Sync network, 0183:2-9
 provisioning (customer) network netmask, 0178:5-18, 0183:5-20
 sample network, 0178:2-7
 IP application routing key, 0100:3-3
 IP application servers, 0100:3-4
 IP application socket, 0100:3-3
 IP associations, 0100:3-3
 IP card, 0100:3-3
 IP communications, 0193:2-9
 IP communications link
 Measurements Platform, 0142:4-136
 IP connection
 FTRA and STP

Master Index

- secure, 0197:2-19, 0197:2-24
- IP connection available, 0338:3-165
- IP Connection Available/ Unavailable alarms, 0178:4-16, 0183:4-18
- IP Connection Congestion Timeout, 0338:3-833
- IP Connection Failed, 0338:3-741
- IP Connection manually removed, 0338:3-168
- IP Connection Refused, 0338:3-834
- IP connection, cannot resolve RHOST, 0338:3-835
- IP host, 0100:3-3, 0142:4-139, 0142:4-158
- IP host table, 0190:3-18, 0193:3-12
- IP link, 0100:3-3, 0142:4-137, 0142:4-138, 0142:4-158
- IP Link A is down, 0338:3-600
- IP Link A is up, 0338:3-602
- IP link alarms, 0190:3-14, 0193:3-7
- IP Link B is down, 0338:3-603
- IP Link B is up, 0338:3-605
- IP link established, 0190:5-2, 0195:4-2
- IP Multicast, 0190:2-37, 0193:2-9
- IP Multicast - downloading GSM database, 0188:2-12
- IP multicasting, 0188:2-12
- IP Node Address never entered or Card DB corrupt, 0177:2-306
- IP options
 - drkq, 0100:3-122
 - getcomm, 0100:3-122
 - inhfepalm, 0100:3-122
 - ipgwabate, 0100:3-122
 - iplimabate, 0100:3-122
 - sctpcsum, 0100:3-122, 0100:3-426, 0100:3-455
 - setcomm, 0100:3-122
 - snmpcont, 0100:3-122
 - srkq, 0100:3-122
 - sync, 0100:3-115, 0100:3-122
 - trapcomm, 0100:3-122
- IP protocol option, 0100:3-115
- IP Route table full, 0177:2-638
- IP routes, 0100:3-3
- IP Security Enhancements - Eagle OAM
 - Activating, 0142:A-12
 - Deactivating, 0142:A-38
- IP Services Module, 0142:4-154, 0142:4-164
- IP User Interface
 - Telnet Support, 0347:3-128
- IP User Interface Controlled Feature
 - Activating, 0142:A-3
 - Deactivating, 0142:A-38
- IP User Interface Feature, 0197:2-3
- IP7 connection congested, 0338:3-166
- IP7 connection unavailable, 0338:3-162
- IP7 Front End, 0212:4-4, 0212:4-5, 0212:4-6, 0212:4-9, 0212:4-44, 0243:A-17
- IP7 Secure Gateway, 0025:1-4, 0212:1-6, 0224:1-9
- IP7 Secure Gateway Options, 0100:3-3
- IP7 Transport Feature (26.1), 0347:3-117

Changed Commands, 0347:3-118
 New Features, 0347:3-117
 IPADDR already assigned to another TCP/IP link, 0177:2-275
 IPADDR and IPRTE cannot be the same address, 0177:2-271
 IPADDR assigned to a TCP/IP link, 0177:2-262
 IPADDR assigned to a TCP/IP node, 0177:2-260
 IPADDR assigned to a TCP/IP router, 0177:2-275
 IPADDR not assigned to a TCP/IP link, 0177:2-261
 IPADDR not assigned to any TCP/IP link, 0177:2-269
 IPADDR not assigned to specified LOC, 0177:2-267
 IPADDR w/o IPRTE must match first 2 octets of TCP/IP link, 0177:2-265
 IPADDR w/o IPRTE must match first 3 octets of TCP/IP link, 0177:2-265
 IPADDR w/o IPRTE must match first octet of TCP/IP link, 0177:2-264
 ipaddr=192.168.122.nnn, 0188:4-23, 0188:4-31, 0190:4-22, 0190:4-31, 0193:4-22, 0193:4-31
 IPAPPL already assigned to specified LOC, 0177:2-266
 IPAPPL on Node not assigned to specified LOC, 0177:2-268
 IPAPPL on node not connected to any TCP/IP link, 0177:2-270
 ipgwabate, 0100:3-122
 IPGWI
 activate signaling link, act-slk, 0100:3-67, 0100:3-119, 0100:3-136, 0100:3-158, 0100:3-178,
 0100:3-179, 0100:3-200, 0100:3-201, 0100:3-306, 0100:3-309, 0100:3-329, 0100:3-333
 display card status, rept-stat-card, 0100:3-117, 0100:3-132, 0100:3-156
 display signaling link status, rept-stat-slk, 0100:3-116, 0100:3-119, 0100:3-131, 0100:3-136,
 0100:3-154, 0100:3-158, 0100:3-178, 0100:3-200, 0100:3-306, 0100:3-329, 0100:3-431, 0100:3-441
 ipgwi, 0025:3-20, 0100:2-4, 0100:2-22
 IPGWI link must be in a single link linkset, 0177:2-668
 IPGWx Linkset
 Configuring, 0100:3-35
 Mate - Configuring, 0100:3-55
 IPISUP Feature must be on, 0177:2-634
 IPLIM
 activate signaling link, act-slk, 0100:3-67, 0100:3-119, 0100:3-136
 display card status, rept-stat-card, 0100:3-132, 0100:3-156
 display signaling link status, rept-stat-slk, 0100:3-119, 0100:3-131, 0100:3-136, 0100:3-154,
 0100:3-431, 0100:3-441
 iplim, 0025:3-20, 0100:2-3
 IPLIM Protocol Support Enhancement (Release 28.1) (IP7 Release 6.0), 0347:3-122
 iplimabate, 0100:3-122
 iplimi, 0025:3-20, 0100:2-3
 IPLIML2 is only valid for IPLIMx SLK, 0177:2-492
 IPLIMx connections cannot be resident in AS, 0177:2-527
 IPLIMx to 8 Points (Release 29.1) (IP7 Release 7.1), 0347:3-123
 IPM, 0178:5-26, 0183:5-34
 IPMX, 0243:1-38
 IPMX backplane connector, 0243:B-15
 IPMX backplane connectors, 0243:B-20
 IPMX/HMUX Card Replacement, 0338:A-10
 IPPORT already assigned, 0177:2-263
 IPPORT can only be specified if IPADDR is specified, 0177:2-263
 IPPORT on node not assigned to specified LOC, 0177:2-268
 IPPORT on Node not connected to any TCP/IP link, 0177:2-269
 IPRTE address assigned to TCP/IP link, 0177:2-273

Master Index

IPRTE address must use first 2 octets of Class B TCP/IP Link, 0177:2-274
IPRTE address must use first 3 octets of Class C TCP/IP Link, 0177:2-274
IPRTE address must use first octet of Class A TCP/IP Link, 0177:2-273
IPSM, 0142:4-154, 0142:4-164, 0142:4-165, 0142:B-2, 0142:B-9, 0197:2-3, 0197:2-45, 0197:2-47, 0197:2-48, 0197:2-49, 0197:2-123, 0197:2-124
IPSM card not equipped, 0177:2-130
IPSM card(s) must be inhibited to enable telnet feature, 0177:2-755
IPSM IP Address, 0197:2-48, 0197:2-49
IPTPS must be divisible by 10, 0177:2-795
IPTPS not allowed for non-IPGWx linksets, 0177:2-793
IPTPS required for IPGWx linksets, 0177:2-793
IS-41, 0188:1-1, 0188:1-11
IS-41 LNP Qry rejected
 WNP is OFF, 0338:3-906
IS-41 to GSM Migration Call Flows, 0190:2-20
IS-41 to GSM Migration feature, 0348:2-4
IS-41 to GSM Migration Protocol, 0190:2-62
IS412GSM must be provisioned before SERVERPFX, 0177:2-819
IS-ANR, 0348:1-11
ISCC Interface Loopback Test (22.0), 0347:3-135
ISCC loopback failed, 0338:3-803
ISCC loopback in progress, 0338:3-805
ISCC loopback success, 0338:3-802
ISDN, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-11, 0348:1-11
IS-NR, 0188:1-11, 0193:1-12, 0348:1-11
Isolation sheet, 0224:3-20
isolator pad, 0095:4-4, 2969:4-4
ISUP, 0193:1-12
ISUP Normalization, 0100:2-40
ISUP normalization feature must be enabled to set NORM=YES, 0177:2-724
ISUP NP with EPAP Call Flows, 0190:2-28
ISUP NP with EPAP feature must be enabled, 0177:2-824
ISUP NP With EPAP for All Other Cases, 0190:2-31
ISUP variant provisioning, 0100:3-4
ISUPMT/TUPMT already exists in given SR, 0177:2-218
ISUPMT/TUPMT does not exist in given SR, 0177:2-218
ISVM, 0288:3-22
ITU, 0188:1-1, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-11, 0348:1-11
ITU ANSI translation not supported, 0338:3-663
ITU Duplicate Point Code Routing (26.05), 0347:3-156
 Enhanced Commands, 0347:3-157
ITU Duplicate Point Code Support, 0183:2-13
ITU entries not allowed when ANSIGFLEX is on, 0177:2-812
ITU Gateway Measurements Enhancements (26.05), 0347:3-163
 Enhanced Commands, 0347:3-165
 New Measurements Reports, 0347:3-163
ITU GWY
 CGB buffer full, 0338:3-734
 CPC conversion failure, 0338:3-724
 GRS buffer full, 0338:3-732
 HOH1 conversion failure, 0338:3-728
 Invalid ISUP msg structure, 0338:3-731

- OPC conversion failure, 0338:3-726
- rcvd msg type cannot convert, 0338:3-729
- RSC buffer full, 0338:3-733
- ITU international spare point code, 0098:2-8, 0098:2-11, 0098:2-23, 0098:3-8, 0098:3-10, 0098:3-15, 0098:3-20, 0098:3-21, 0098:4-9, 0098:4-11, 0098:4-18, 0098:4-25, 0098:4-27, 0098:6-10, 0098:6-12, 0098:6-19, 0098:6-26, 0098:6-27, 0098:6-28, 0098:6-29, 0098:7-10, 0098:7-11, 0098:7-12, 0098:7-17, 0098:7-24, 0098:7-25, 0098:8-9, 0098:8-13, 0098:8-14, 0098:8-22, 0098:8-23, 0098:8-27, 0098:8-30, 0098:8-31, 0098:9-13, 0098:9-14, 0098:9-23, 0098:9-30, 0098:9-31, 0098:9-32, 0098:11-9, 0098:11-13, 0098:11-14, 0098:11-15, 0098:11-23, 0098:11-27, 0098:11-30, 0098:11-31, 0098:11-32, 0098:12-13, 0098:12-14, 0098:12-23, 0098:12-29, 0098:12-30, 0098:12-31
- ITU MTP Restart (26.0), 0347:3-157
 - Changed Commands, 0347:3-158
 - Limitations, 0347:3-160
 - Measurements, 0347:3-159
 - Product Description, 0347:3-158
 - UIMs, 0347:3-159
 - Upgrade Considerations, 0347:3-158
- ITU National and International Spare Point Code Support feature, 0120:2-7, 0120:2-43, 0120:2-44, 0120:2-49, 0120:2-50, 0120:2-83, 0120:2-85, 0120:2-91, 0120:2-100, 0120:2-193, 0120:2-229, 0120:3-19, 0120:3-77
 - activating, 0120:2-42, 0120:2-51
- ITU national duplicate PC, 0188:4-9, 0190:4-10, 0193:4-10
- ITU national point code, 0188:4-9, 0190:4-10, 0193:4-10
- ITU National Point Code must be full point code, 0177:2-688
- ITU network
 - cluster management, 0120:2-125
- ITU Number Portability, 0193:2-1
- ITU PC parameters are invalid for ANSI cards, 0177:2-520
- ITU point codes are not supported when DOMAIN=X25, 0177:2-144
- ITU SLS enhancement
 - bit rotation, 0120:3-30
 - CIC bit, 0120:3-31
- ITU SLS Enhancements (26.0), 0347:3-160
 - Changed Commands, 0347:3-161
 - Restrictions, 0347:3-161
 - Upgrade Considerations, 0347:3-161
- ITU-ANSI-China SCCP Conversion, 0099:1-2, 0099:2-3, 0099:2-6, 0099:2-7, 0099:2-16, 0099:2-17, 0099:2-30, 0099:2-33, 0099:2-40, 0099:2-43, 0099:2-44, 0099:2-47, 0099:2-48, 0099:2-69, 0099:2-71, 0099:2-82, 0099:2-86, 0099:2-92, 0099:2-118, 0099:2-124, 0099:2-162, 0099:2-163, 0099:2-171, 0099:2-172, 0099:2-179, 0099:2-181, 0099:2-193, 0099:2-194, 0099:3-2, 0099:3-21, 0099:3-23, 0099:3-28, 0099:3-32, 0099:3-53, 0099:3-54, 0099:3-55, 0099:3-58, 0099:3-62, 0099:4-2, 0099:4-27, 0099:4-30, 0099:4-34, 0099:4-35, 0099:4-38, 0099:4-39, 0099:4-54, 0099:4-57, 0099:4-60, 0099:4-63, 0099:A-36, 0099:A-37, 0099:A-38, 0099:A-39, 0099:A-41, 0099:A-42
 - options
 - changing, 0099:2-193, 0099:2-195
- ITUDUPPC, 0188:4-9, 0190:4-10, 0193:4-10
- ITU-I, 0188:2-21
- ITU-I Networks Option - TFCs
 - Configuring, 0120:3-276, 0120:3-278
- ITU-INTL site id not defined, 0177:2-315
- ITU-N, 0188:2-21
- ITU-N Networks Option - TFCs

Master Index

- Configuring, 0120:3-276, 0120:3-278
- ITU-NATL site id not defined, 0177:2-315
- ITUTFR parameter is only valid for ITU link sets, 0177:2-668
- ITU-TFR Procedure (26.1), 0347:3-162
 - Changed Commands, 0347:3-163
 - UIMs, 0347:3-162
 - Upgrade Considerations, 0347:3-162

J

- J-8, 0224:5-64, 0224:5-73
- J-9, 0224:5-64, 0224:5-73
- Java, 0178:5-3, 0183:5-3
- Java 2 Runtime Environment, 0197:2-2, 0197:2-4, 0197:2-5, 0197:2-7, 0197:2-8, 0197:2-9
 - software, installing, 0197:2-5, 0197:2-8
- Java applet, 0183:3-2, 0183:3-6
- Java Plug-In, 0178:5-4
- Java Policy File, 0178:5-7
- Java virtual machine, 0183:5-3
- JIPDIGITS - Jurisdiction Information Parameter Digits, 0288:3-52
- JIPPRV - Jurisdiction Information Parameter, 0288:3-52
- Job Routing Server (JRS)
 - description, 0178:2-11
- JRE - Java Runtime Environment, 0197:2-2, 0197:2-9
- JRE_HOME environment variable, 0197:2-1, 0197:2-7, 0197:2-9
- jumper board, 0224:4-6
- jumper board (FAP), 0338:2-7
- jumper, diode, 0338:2-8
- jumper, P71, 0338:2-8, 0338:2-10
- jumper, P72, 0338:2-8, 0338:2-10
- Jurisdiction Information Parameter - JIPPRV, 0288:3-52
- Jurisdiction Information Parameter Digits - JIPDIGITS, 0288:3-52

K

- KB, 0348:1-11
- Key Fingerprint
 - DSA, 0197:2-48, 0197:2-49
 - Public
 - EAGLE 5 SAS, 0197:2-19, 0197:2-48, 0197:2-49
- key sequences
 - KSR terminal, 0145:4-10
 - VT320 terminal, 0145:4-10
- Key values
 - DIR, TTA, TTI, NP, NAI already exist, 0177:2-748
 - DIR, TTA, TTI, NP, NAI does not exist, 0177:2-748
- keyboard functions, 0145:4-10
- Keyboard is locked. Enter UNLOCK command, 0177:2-3
- Keyboard is not locked, 0177:2-333
- keys, secure shell encryption, 0178:5-21, 0183:5-24
- keywords, command, 0145:4-9
- KSR, 0348:1-11

KSR function on VT320 terminals, 0145:4-5
 KSR mode, 0347:3-129
 KSR Terminal Feature (20.0), 0347:3-166
 KSR terminal type, 0142:4-55
 KSR terminals
 function on VT320 devices, 0145:4-5
 key sequences, 0145:4-10

L

L parameter cannot be used in combination with LOC, 0177:2-443
 L2STATS not valid for IPGWI, 0177:2-670
 L2STATS not valid for SS7IPGW, 0177:2-652
 L2TSET cannot be specified if card application is SS7GX25, 0177:2-251
 l2tset must be 1-10 for ANSI links, 11-20 for ITU, 0177:2-40
 label
 cables, 0224:2-8, 0224:C-4, 0243:C-4
 fan assembly, 0095:B-3, 0095:B-6, 2969:B-3, 2969:B-6
 hard disk drive
 on part, 0095:B-9, 0095:B-11, 0095:B-12, 0095:B-14, 0095:B-15, 0095:B-18, 2969:B-9, 2969:B-11, 2969:B-12, 2969:B-14, 2969:B-17
 PCI card
 on card, 0095:B-12, 2969:B-12
 Label each cable, 0224:4-21
 Label Kit, 0212:3-135
 label kit, 0224:2-10
 LAN, 0212:4-47, 0212:4-50, 0243:2-13, 0348:1-11
 LAN feature must be ON, 0177:2-247
 Large System # Links Controlled Feature
 Enabling, 0097:2-134, 0100:3-98, 0120:3-10
 Large System (27.2), 0347:4-1
 Changed Commands, 0347:4-2
 Hardware Required, 0347:4-1
 Limitations, 0347:4-3
 Upgrade Considerations, 0347:4-3
 Large System (Phase 3)—1500 Links (Release 29.0), 0347:4-4
 Large System—Phase 2 (Release 28.0), 0347:4-3
 Last entry in given SR is ref'd by another screen, 0177:2-205
 Last route to DPC in use by GTT, 0177:2-142
 Latching versus Non-latching LFS Tests
 Multiple LFS Tests (EAGLE 26.0), 0347:4-140
 layered design, 0025:6-4, 0096:2-3
 layout
 MPS frame, 0212:4-13
 layout, frame, 0095:4-4, 2969:4-4
 LBP cannot exceed previously defined NEI LBP value, 0177:2-390
 LBP has already been provisioned, 0177:2-388
 LBP must have been previously defined in database, 0177:2-392
 LBP or ALL parameter must be specified exclusively, 0177:2-392
 LC already in use, 0177:2-296
 LC can only be specified when TYPE=PVC, 0177:2-288
 LC greater than maximum PVCs for link, 0177:2-295

Master Index

LC must be specified when TYPE=PVC, 0177:2-288
LCA (Logic Cell Array), 0212:3-65
LED
 DCM, 0224:A-8
 DSM, 0224:A-8
LED, alarm, 0096:3-11, 2712:3-8
LEDs, 0224:4-24, 0224:A-1, 0243:A-1, 0338:5-6, 2970:7-3
 BM (backplane monitor), 0338:5-21, 2970:7-20
 drive power, 0338:5-8, 2970:7-5
 fan assembly
 Active, 0338:5-100, 0338:A-90, 2970:3-67, 2970:3-72, 2970:6-49
 Alarm, 0338:5-100, 0338:A-90, 2970:3-67, 2970:3-72, 2970:6-49
 Minor, 0338:5-100, 0338:A-90, 2970:3-67, 2970:3-72, 2970:6-49
 Garrett Magnum Hubs, 0243:A-16
 hub front, 0212:4-48, 0212:4-50, 0243:A-18
 MPS Server, 0025:6-12, 0212:4-28, 0212:4-32
 MPS Server alarm, 0212:4-32
 Netra t 1400, 0212:4-37, 0243:A-15
 Telect Braker Panel, 0243:A-14
LEDs, OP/MAINT, 0338:2-7
LEDs, PWR A, 0338:2-7
LEDs, PWR B, 0338:2-7
Length of EGTA must be equal to length of GTA, 0177:2-165
level
 DSM database, 0178:4-5, 0183:2-30, 0183:4-4
Level 1 Alarm Threshold level must be less than Level 2, 0177:2-829
level 2 timers
 changing, 0120:3-219
level 3 MSU discrimination
 ANSI/ITU MTP Gateway (20.0), 0347:2-36
level 3 timers
 changing, 0120:3-222
LFS command in progress, 0177:2-394
LFS data is only valid for OCTET and ALTERNATE patterns, 0177:2-395
LFS feature must be ON, 0177:2-375
LFS must not be running on requested link, 0177:2-399
LFS test is completing, cannot be canceled, 0177:2-394
LFS test terminated with OAM switch over, 0338:3-720
LHOST and ALHOST must refer to different IP addresses, 0177:2-583
LHOST and ALHOST must refer to IP address on the same card, 0177:2-583
LHOST has open socket or association, 0177:2-527, 0177:2-528
LHOST/ALHOST location not found, 0177:2-461
LIDB, 0288:3-22
Lighting, 0095:2-6, 2969:2-6
lighting, 0095:2-6, 0212:6-3, 2969:2-6
LIM, 0188:1-11, 0190:1-11, 0193:1-12, 0195:1-11, 0212:3-21, 0224:2-3, 0243:1-38, 0348:1-11
LIM(s) have been denied EROUTE service, 0338:3-590
LIM(s) have been denied SCCP service, 0338:3-423
LIM(s) have been denied STPLAN service, 0338:3-228
LIM, MIM, and MPL Changeout Time, 0338:A-16
LIM-AINF, 0212:3-56, 0224:2-3, 0243:1-38
LIM-ATM, 0097:6-7, 0224:2-3, 0243:1-38

LIM-ATM-, 0212:3-58, 0212:3-69
 LIMATM, 0097:6-7
 LIMCH, 0097:6-7
 LIM-DS0, 0097:6-7
 LIMDS0, 0097:6-7
 limds0, 0097:2-11
 LIM-DS0A, 0224:2-3, 0243:1-38
 LIME1, 0097:6-7
 LIME1ATM, 0097:6-7
 limit to PDBI connections, 0183:2-25, 0348:2-10, 0348:3-8
 limitations
 Calling Name Conversion Facility (CNCF) (23.1), 0347:2-45
 Eagle Application Support for E1 (26.3), 0347:2-109
 Enhanced Bulk Download (25.0), 0347:2-151
 GR-376 Interface (26.0), 0347:3-30
 GSM MAP Screening (26.1), 0347:3-45
 ITU MTP Restart (26.0), 0347:3-160
 Large System (27.2), 0347:4-3
 Multiple LFS Tests (EAGLE 26.0), 0347:4-143
 Multiple Point Code Support (EAGLE 26.05), 0347:4-151
 Number Pooling / Efficient Data Representation (EDR) (EAGLE 26.1), 0347:4-203
 PCS 1900 LNP Query (EAGLE 26.0), 0347:5-8
 Security Log Increase (EAGLE 26.05), 0347:5-74
 Stand-alone Eagle G-Flex Relay Function, 0347:3-19
 Support for LSMS Audit Enhancements (EAGLE 26.1), 0347:5-106
 Thresholding of UIM Messages (EAGLE 25.0), 0347:5-133
 TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-150
 Weighted SCP Load Balancing (Eagle 27.2), 0347:5-177
 LIM-OCU, 0097:6-7
 LIMOCU, 0097:6-7
 limocu, 0097:2-11
 LIMs, 0188:2-24, 0190:2-51
 LIMs denied SCCP service, 0190:5-6, 0193:5-9, 0195:4-6
 LIMT1, 0097:6-7
 LIM-V.35, 0097:6-7, 0212:3-56
 LIMV35, 0097:6-7
 limv35, 0097:2-11
 Link, 0212:3-20
 link alarms, 0190:3-14, 0193:3-7
 Link assigned to card, 0177:2-30
 link capacity exceeds limit allow by feature key, 0177:2-543
 link congestion, 0190:5-2, 0193:5-3, 0195:4-2
 link diagnostics
 Link Fault Sectionalization (21.0), 0347:4-14
 Link expected IP TPS threshold exceeded, 0338:3-197
 Link Failure Status Information (22.0), 0347:4-7
 Link Fault Sectionalization, 0338:3-63
 Hardware Configuration, 0338:3-64
 Test Details, 0338:3-66
 Test Indicators, 0338:3-66
 Test Report, 0338:3-66
 Link Fault Sectionalization (21.0), 0347:4-11

Master Index

- Commands, 0347:4-16
- Hardware Configuration, 0347:4-15
- Link Diagnostics, 0347:4-14
- Link Fault Sectionalization Test Indicators, 0347:4-15
- Remote Loopback Testing for DSOA, 0347:4-13
- Remote Loopback Testing for OCU, 0347:4-14
- link fault sectionalization test, 0338:3-63
- Link Fault Sectionalization Test Indicators
 - Link Fault Sectionalization (21.0), 0347:4-15
- link fault sectionalization test procedure, 0338:3-68
- link fault sectionalization test, commands, 0338:3-67
- link fault sectionalization test, configuring data, 0338:3-67
- link fault sectionalization test, hardware configuration, 0338:3-64
- link fault sectionalization test, indicators, 0338:3-66
- link fault sectionalization test, report, 0338:3-66
- link fault sectionalization test, restrictions, 0338:3-64
- link fault sectionalization test, starting, 0338:3-68
- link fault sectionalization test, stopping, 0338:3-69
- Link Interface Module, 0025:3-8, 0188:2-24, 0190:2-51, 0212:2-11
- Link Interface Module (LIM), 0224:5-81
- link interface module (LIM), 0212:3-19
- Link Interface Module (LIM) measurements, 0338:4-47
- Link Interface Modules (LIMs), 0212:3-9
- Link IP TPS normal, 0338:3-201
- Link is in test mode, 0177:2-29
- Link is invalid for card location, 0177:2-548
- Link is unequipped in the database, 0177:2-150
- Link Maintenance Commands
 - act-cdl, 0338:3-75
 - act-lbp, 0338:3-67
 - chg-lbp, 0338:3-67
 - dact-cdl, 0338:3-75
 - dact-lbp, 0338:3-67
 - dlt-lbp, 0338:3-67
 - ent-lbp, 0338:3-67
 - rept-stat-cdl, 0338:3-75
 - rept-stat-lfs, 0338:3-67
 - rept-stat-tstslk, 0338:3-75
 - rtrv-lbp, 0338:3-67
 - tst-slkl, 0338:3-71, 0338:3-75
- Link Maintenance Enhancements, 0338:3-69
 - Command Driven Loopback, 0338:3-70
 - Commands, 0338:3-75
 - Test Indicators, 0338:3-70, 0338:3-72
 - Test Signaling Link, 0338:3-71
 - tst-slkl Loopback Test Details, 0338:3-72
- Link Maintenance Unsolicited Output Message Group, 0338:D-6
- LINK must be A if card type is LIMATM or LIME1ATM, 0177:2-510
- Link must be cancelled before executing this command, 0177:2-271
- Link must be removed from X.25 route(s), 0177:2-251
- Link must be SAAL to execute command, 0177:2-399
- Link must be SS7 to display Level 2 stats, 0177:2-398

Link must be SS7 to execute command, 0177:2-398
 Link must not be active to execute command, 0177:2-397
 Link not assigned to SS7-X.25 card, 0177:2-295
 Link not equipped, 0177:2-294
 Link not Monitored, 0338:3-587
 Link Parameter may only be a or b for SE-HSL, 0177:2-804
 LINK parameter valid only when ENTTYPE=LINK, 0177:2-119
 Link set argument - not valid (C<col>), 0177:2-501
 Link set is not equipped, 0177:2-157
 Link set with IPGWAPC=YES requires SS7IPGW/IPGWI GPL, 0177:2-650
 Link Status alarms, DSM-ELAP, 0178:4-16
 Link Status alarms, DSM-EPAP, 0183:4-18
 Link Status Reporting (21.0), 0347:4-19
 Link test command in progress, 0177:2-790
 Link test command not in progress, 0177:2-790
 Link test must not be running on requested link, 0177:2-788
 LINKCLASS=UCH is not valid for even numbered card loc, 0177:2-802
 linkinfo, 0145:9-31
 Links assigned to linkset, 0177:2-137
 Links on specified linkset are in-service, 0177:2-38
 Linkset
 GSM MAP Screening
 Configuring, 0097:5-43, 0097:5-53, 0097:5-54, 0097:5-55
 IPGWx
 Configuring, 0100:3-35
 Mate IPGWx - Configuring, 0100:3-55
 linkset
 adding, 0120:3-6, 0120:3-17
 changing, 0120:3-74
 removing, 0120:3-63
 route, 0120:3-7
 Linkset already assigned to route, 0177:2-141
 Linkset already defined, 0177:2-138
 Linkset APC/SAPC is already being used, 0177:2-137
 Linkset assigned to route must have at least one link, 0177:2-40
 Linkset cannot be the mate of another linkset, 0177:2-781
 Linkset cannot reference self as mate, 0177:2-781
 Linkset does not reference MATELSN, 0177:2-793
 Linkset IP TPS normal, 0338:3-200
 Linkset IP TPS threshold exceeded, 0338:3-195
 Linkset is unequipped, 0177:2-142
 Linkset not assigned in route table, 0177:2-140
 Linkset not defined, 0177:2-138
 Linkset referenced by route, 0177:2-139
 Linkset SAPC referenced by route, 0177:2-256
 Linkset SLK requires ITUN APC/SAPC to be 14bit or 24bit only, 0177:2-559
 Linkset table full, 0177:2-138
 Linkset Type used for cluster route cannot be A or E, 0177:2-139
 linkset with MULTGC=YES requires IPGWI/IPLIMI GPL, 0177:2-725
 linksets, 0120:3-3
 linksets assigned, 0188:4-8, 0190:4-10, 0193:4-10
 list alarms data strings, 0178:4-11

Master Index

- List All Authorized PDBA Client IPs, 0183:3-91
- List All Running Processes, 0178:3-74, 0183:3-44
- List ELAP Software Processes, 0178:3-65
- List EPAP Software Processes, 0183:3-37
- list pass commands for target location, 0188:3-17
- List PDB Backups, 0183:3-95
- list supported pass commands, 0190:3-21, 0193:3-15
- LMC connector, 0224:B-53, 0243:B-23
- LNP, 0188:1-11, 0188:2-3, 0190:1-1, 0190:1-11, 0193:1-12, 0195:1-11, 0348:1-11
 - Database after LSMS-Based Operation or RTDB Copy - Distributing, 0288:2-134
 - ELAP Configuration feature, 0288:2-4, 0288:2-124, 0288:2-128, 0288:2-129
 - Feature Activation Overview, 0288:2-4
 - Feature on the EAGLE 5 SAS - Activating, 0288:2-123
 - measurements, 0025:4-8
 - option - WSMSC10DIG, 0288:3-79
 - provisioning, 0178:2-10
 - provisioning data collection sources, 0178:2-11
 - Service - WSMSC, 0288:3-79
 - Short Message Service (SMS) - Activation, 0288:3-79
 - SMS Feature - Deactivating, 0288:3-84
- LNP 48 Million Numbers feature, 0025:6-2
- LNP ACG node overload, 0338:3-547
- LNP Administration Priority - ADMHIPRI, 0288:3-52
- LNP AIN Query Enhancement (26.0), 0347:4-50
 - Changed Commands, 0347:4-50
- LNP and GPORT features are mutually exclusive, 0177:2-707
- LNP audit
 - TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-145
- LNP Basic, 0142:4-23, 0142:4-37, 0288:1-2
- LNP data, overview, 2339:1-1, 2339:2-4
- LNP Database, 0025:4-6
- LNP database
 - alarms, 2339:8-3
- LNP Database Administration, 0142:4-23, 0142:4-37, 0288:1-2
- LNP database audit - internal error, 0338:3-756
- LNP database audit is disabled, 0338:3-813
- LNP database corrupted, 0338:3-531, 0338:3-608, 0338:3-609
- LNP database has been corrected, 0338:3-543
- LNP Database IMPORT started, 0338:3-762
- LNP database is inconsistent, 0338:3-536
- LNP Database Unsolicited Output Message Group, 0338:D-25
- LNP Day Meas. Discarded for NPANXX, 0338:3-883
- LNP DB Audit — End of Audit Report
 - Support 12 Million Ported Numbers (EAGLE 24.0), 0347:5-97
- LNP DTH Measurements Discarded for DPC, 0338:3-836
- LNP ELAP CFG feat incompatible with SCCP/EBDADCM/EBDABLM appl, 0177:2-743
- LNP ELAP Configuration and WNP features must be ON, 0177:2-580
- LNP ELAP Configuration feature
 - enable, 0145:6-134
 - turn off, 0145:5-88
- LNP ELAP Configuration feature must be ON, 0177:2-533
- LNP feature must be ON, 0177:2-435

LNP feature must be on before LNP ELAP Config can be on, 0177:2-742
 LNP feature, how to turn on, 0145:6-131
 LNP Incremental Loading, 0338:3-889
 LNP Maintenance, 0025:4-7
 LNP Measurements Enhancements (25.0), 0347:4-50
 Changed Files, 0347:4-54
 Commands, 0347:4-54
 Message Relay Measurements per SSP, 0347:4-50
 Upgrade Considerations, 0347:4-54
 LNP measurements, extracting from FTA, 0145:5-8
 LNP Option
 ADMHIPRI, 0288:3-52
 CCP, 0288:3-53
 FRCSMPLX, 0288:3-52
 GTWYSTP, 0288:3-52
 JIPPDIGTS, 0288:3-52
 JIPPRV, 0288:3-52
 SERVPORT, 0288:3-53
 WQREDRCT, 0288:3-53
 WSMSC10DIG, 0288:3-53
 LNP or EIR must be enabled or INP must be ON, 0177:2-770
 LNP or INP feature must be ON, 0177:2-691
 LNP ported LRNs 150K Qty Feat Requires at least DSM2GB, 0177:2-638
 LNP Ported LRNs Capacity Normal, 0338:3-358
 LNP Ported LRNs exceeds Feat. Capacity, 0338:3-357
 LNP ported NPANXXs 300K Qty Feat Requires at least DSM2GB, 0177:2-638
 LNP Ported NPAs Capacity Normal, 0338:3-360
 LNP Ported NPAs exceeds Feat. Capacity, 0338:3-359
 LNP ported TNs 12million Qty Feat Req at least TSM/DSM1GB, 0177:2-536
 LNP ported TNs 24million Qty Feat Require at least DSM2GB, 0177:2-536
 LNP ported TNs 36million Qty Feat Require at least DSM3GB, 0177:2-536
 LNP ported TNs 48 to 228 M Qty Feat Req at least DSM4GB, 0177:2-537
 LNP ported TNs 4million Qty Feat Require at least TSM512MB, 0177:2-535
 LNP ported TNs 6million Qty Feat Require at least TSM768MB, 0177:2-535
 LNP ported TNs 8million Qty Feat Require at least TSM1GB, 0177:2-535
 LNP Ported TNs Capacity Normal, 0338:3-356
 LNP Ported TNs exceeds Feat. Capacity, 0338:3-355
 LNP Query Service (LNPQS), 0025:4-4
 LNP rcvd query with Message Relay TT, 0338:3-761
 LNP rcvd query with undefined TT/SERV, 0338:3-759
 LNP received query from unknown CGPA PC, 0338:3-758
 LNP Response to STPLAN (26.0), 0347:4-56
 LNP self-ID commands
 LNP—Changes to Existing Commands (22.0), 0347:4-60
 LNP Service, 0178:3-42, 0178:3-44, 0178:3-45, 0288:3-22, 0288:3-23, 0288:3-25, 0288:3-30, 0288:3-32,
 0288:3-33, 0288:3-36, 0288:3-37, 0288:3-59
 LNP Service commands
 Eagle Initiated OAP User Interface (24.0), 0347:2-119
 LNP Short Message Service (Release 28.2), 0347:4-89
 LNP Short Message Service (SMS) - Activation, 0288:3-79
 LNP SS Appl table is full, 0177:2-473
 LNP Subscription, 0142:4-23, 0142:4-37

Master Index

LNP subsystem alarms

- LNP—Auto Inhibit/Uninhibit Alarms, 0347:4-75
- LNP Subsystem Application, 0288:3-42, 0288:3-43, 0288:3-46, 0288:3-50, 0288:3-51, 0347:4-88
- LNP Subsystem is available, 0338:3-530
- LNP Subsystem is disabled, 0338:3-546
- LNP Subsystem is not available, 0338:3-528
- LNP subsystem is offline in database, 0177:2-436
- LNP Subsystem is removed, 0338:3-545
- LNP Subsystem normal, card(s) abnormal, 0338:3-529
- LNP telephone number alarm thresholds - changing, 0288:3-86
- LNP Translation Type, 0288:3-22, 0288:3-30, 0288:3-32, 0288:3-59, 0288:3-62, 0288:3-63, 0347:4-87
- LNP translation types - mapping, 0288:3-59
- LNP TT SERV table is full, 0177:2-473
- LNP updates allowed
 - loading mode stability, 0338:3-888
- LNP updates inhibited
 - loading mode stability, 0338:3-887
- LNP—10 Digit Telephone Number Subscription Commands (22.0), 0347:4-56
- LNP—Allow Subsystem Command (22.0), 0347:4-57
- LNP—Auto Inhibit/Uninhibit Alarms
 - LNP Subsystem Alarms, 0347:4-75
 - LNP—New Unsolicited Alarm Messages (UAMs) (22.0), 0347:4-74
- LNP—Automatic Call Gapping (22.0), 0347:4-57
- LNP—Automatic Call Gapping (Release 22.0)
 - Area Code, 0347:4-57
- LNP—Automatic Call Gapping Commands (22.0), 0347:4-58
- LNP—Call Completion to Ported Number (CCPN) (22.0), 0347:4-59
- LNP—Changes to Existing Commands (22.0), 0347:4-60
 - LNP—chg-feat and rtrv-feat Commands, 0347:4-61
 - LNP—Mated Application Commands, 0347:4-60
 - LNP—Self ID Commands, 0347:4-60
- LNP—clr-disk-stats Command (Release 22.0), 0347:4-61
- LNP—Degraded Mode (22.0), 0347:4-61
- LNP—Destination Point Code Exception Report (23.1), 0347:4-63
- LNP—disp-disk-stats Command (22.0), 0347:4-63
- LNP—Eagle LNP Configuration (22.0), 0347:4-64
- LNP—Impact of LNP on Other Features (22.0), 0347:4-67
 - Database Transport Access (DTA), 0347:4-68
 - Gateway Screening, 0347:4-67
 - STPLAN, 0347:4-68
 - Translation Type Mapping, 0347:4-68
- LNP—Inhibit Subsystem Command (22.0), 0347:4-68
- LNP—Location Routing Number Commands (22.0), 0347:4-69
- LNP—LRN Measurements
 - LNP—Measurements (22.0), 0347:4-71
- LNP—Mapping LNP Translation Type Commands (22.0), 0347:4-69
- LNP—Measurements (22.0), 0347:4-70
 - LNP—LRN Measurements, 0347:4-71
 - LNP—System Wide Measurements, 0347:4-70
 - NPANXX Measurements, 0347:4-71
 - SSP Measurements, 0347:4-71
- LNP—Message Relay (22.0), 0347:4-72

- LNP—MSU Trap and Trace Command (22.0), 0347:4-73
- LNP—MTP and SCCP Management to Support LNP (22.0), 0347:4-73
- LNP—New LNP Input and Output Groups (22.0), 0347:4-74
- LNP—New Unsolicited Alarm Messages (UAMs) (22.0), 0347:4-74
 - LNP—Auto Inhibit/Uninhibit Alarms, 0347:4-74
- LNP—New Unsolicited Information Messages (UIMs) (22.0), 0347:4-75
- LNP—NPANXX Commands (22.0), 0347:4-76
- LNP—Query Routed as Final Global Title Translation (22.0), 0347:4-76
- LNP—Query Routed as Non-Final Global Title Translation (22.0), 0347:4-82
- LNP—Report LNP Status Command (22.0), 0347:4-84
- LNP—Rerouting Messages for the Local Subsystem (22.0), 0347:4-84
- LNP—Service Commands (22.0), 0347:4-87
- LNP—Service Provider Commands (22.0), 0347:4-87
- LNP—Split NPA Commands (22.0), 0347:4-88
- LNP—Subsystem Application Commands (22.0), 0347:4-88
- LNP—System Options Commands (22.0), 0347:4-89
- LNP—System Wide Measurements
 - LNP—Measurements (22.0), 0347:4-70
- load balancing, 0190:2-36
- load balancing high-traffic situations, 0188:2-11
- Load button, 0197:2-58, 0197:2-66, 0197:2-75
- Load Mode Status, 0188:5-3, 0190:5-3, 0193:5-4, 0195:4-3
- loading
 - DSM incremental, 0178:2-17, 0183:2-29
 - mode, DSM unstable loading, 0178:4-7, 0183:4-6
 - mode, support status reporting, 0183:4-9
- loading DSM card, 0188:5-12
- Loading failed
 - bad checksum returned, 0338:3-207
 - data load timeout, 0338:3-209
 - data read Error, 0338:3-205
 - disk read failed, 0338:3-214
 - disk read prep error, 0338:3-212
 - disk read response error, 0338:3-213
 - GPL format error, 0338:3-211
 - GPL load timeout, 0338:3-208
 - invalid GPL, 0338:3-210
 - table not found, 0338:3-204
- loading incrementally, 0190:2-39
- Loading Mode Support, 0188:5-6, 0190:5-6, 0193:5-8, 0195:4-6
- loading mode support, 0188:2-25
- Loading Mode Support Status Reporting, 0188:5-5, 0190:5-5, 0193:5-7, 0195:4-4
- Loading Mode unstable due to maint. baseline not established, 0177:2-469
- Loading Mode unstable due to SCCP service is deficient, 0177:2-470
- Loading mode unstable. System's LIM service is unavailable, 0177:2-469
- LOC and CLASS cannot be specified together, 0177:2-515
- LOC and E1PORT parameter combination must be specified, 0177:2-780
- LOC and LINK must be specified when PERIOD=ALL, 0177:2-115
- LOC and PORT must be specified to display Level2 stats, 0177:2-398
- LOC and PORT parameter combination must be specified, 0177:2-392
- LOC and T1PORT parameter combination must be specified, 0177:2-781
- LOC has maximum number of LFS Tests already in progress, 0177:2-401

Master Index

LOC is invalid for specified report TYPE, 0177:2-307
LOC is not LFS capable, 0177:2-387
LOC must be LIMDS0 or LIMOCU with SS7ANSI or CCS7ITU, 0177:2-396
LOC must be specified, 0177:2-146
LOC must be specified when TYPE=PVC or SVCA, 0177:2-289
LOC must not be specified when TYPE=SVCR, 0177:2-289
LOC not allowed with MODE=STATIC, 0177:2-656
LOC not assigned an X.25 signaling link, 0177:2-300
loc parameter, 0188:4-16, 0190:4-17, 0193:4-17, 0195:3-11
LOC parameter not valid for this ENTTYPE, 0177:2-119
loc=1103, 0188:4-15, 0188:4-22, 0188:4-30, 0190:4-16, 0190:4-22, 0190:4-30, 0193:4-16, 0193:4-22, 0193:4-30
local ELAP, 0178:5-27, 0288:2-57
local EPAP, 0183:5-35
local link congestion
 ANSI/ITU MTP Gateway (20.0), 0347:2-38
 network routing, 0120:2-177
Local Maintenance Center (LMC), 0212:3-26
local maintenance center (LMC) alarm connector, 0212:3-26
local maintenance center cable installation, 0224:5-87
Local Memory Validation, 0188:2-23, 0190:2-50, 0193:5-5
Local Number Portability, 0188:2-3, 0190:1-1
Local Number Portability (LNP 48 Million Numbers feature, 0178:2-2
local number portability (LNP), 2339:2-2
Local Provisioning menu, 0178:3-48
local provisioning terminal, 0188:2-21, 0190:2-35
Local Provisioning Terminal, connecting, 0096:A-3
Local Provisioning Utility, 0178:3-48
Local Subsystem is available, 0338:3-507
Local Subsystem is disabled, 0338:3-509
Local Subsystem is not available, 0338:3-508
Local Subsystem is removed, 0338:3-510
Local Subsystem normal, card(s) abnormal, 0338:3-511
Local Subsystems (LNP and Toll-Free)
 Multiple Point Code Support (EAGLE 26.05), 0347:4-147
Location invalid for hardware configuration, 0177:2-48
Location of G-Flex Node in Wireless Network, 0188:2-18
Location of Integrated STP/G-Flex Node in Wireless Network, 0188:2-17
Location Routing Number, 0288:3-59, 0288:4-2, 0347:4-57
Location type cannot receive messages, 0177:2-78
lock, 0145:6-406
LOCREQ rcvd - IS412GSM not provisioned, 0338:3-772
Log
 Connectivity Test, 0197:2-33, 0197:2-34, 0197:2-35, 0197:2-36, 0197:2-37
 window, File Menu, 0197:2-34, 0197:2-35
 Retrieve Tables, 0197:2-13, 0197:2-56, 0197:2-67, 0197:2-68, 0197:2-69, 0197:2-70, 0197:2-72, 0197:2-73
 window, File Menu, 0197:2-70, 0197:2-71
 System, 0197:2-13, 0197:2-99, 0197:2-100, 0197:2-101, 0197:2-102, 0197:2-103
 closing, 0197:2-99, 0197:2-103
 window, 0197:2-99, 0197:2-100, 0197:2-101, 0197:2-102, 0197:2-103
 File menu, 0197:2-99, 0197:2-100

Update Tables, 0197:2-13, 0197:2-79, 0197:2-80, 0197:2-83, 0197:2-84, 0197:2-85, 0197:2-86,
 0197:2-89, 0197:2-90, 0197:2-91, 0197:2-92, 0197:2-93, 0197:2-94, 0197:2-95, 0197:2-96, 0197:2-97
 window, 0197:2-84, 0197:2-90, 0197:2-94, 0197:2-95, 0197:2-96, 0197:2-97, 0197:2-98
 Commit Command Completed, 0197:2-90
 File Menu, 0197:2-94, 0197:2-95
 log file
 audit, 2339:5-37
 bulk load, 2339:6-20
 used for automatic resynchronization, 2339:4-2
 user-initiated resynchronization, 2339:4-19
 log file format, PDBA debug, 0348:2-15
 Log Viewer, 0178:3-69, 0183:3-32
 log viewer navigation commands, 0178:3-70, 0183:3-33
 LOGBUFROVFL-SECULOG - upload required, 0338:3-252
 Logic Cell Array (LCA), 0212:3-68
 Logic for IMEIs in Multiple Lists, 0195:2-5
 LOGIC GROUND, 0224:4-20
 Logic Ground, 0224:4-14, 0224:4-17
 Logic ground, 0224:5-7
 logic ground, 0224:4-18, 0224:4-20
 logic ground cable, 0224:4-19
 logic grounds, 0224:4-19
 Logical Channel to Network Management Mapping
 X.25/SS7 Gateway Feature (Eagle 20.0), 0347:5-184
 logical link between MSISDN number and IMSI, 0188:4-1, 0190:4-1
 login, 0145:6-407
 procedure for password expired, 0145:4-21
 procedure for User ID-password already being used, 0145:4-22
 procedure for User ID-password not accepted, 0145:4-20
 procedure to change password at first login, 0145:4-20
 procedure to log into system, 0145:4-19
 security checks, 0145:4-17
 Login Failure Message (21.0), 0347:4-92
 Login Message Text, 0178:3-109, 0183:3-139
 login names
 change passwords for, 0178:5-21, 0183:5-24
 login screen, 0178:3-4, 0183:3-4
 Login Success or Failure Tracking (21.0), 0347:4-92
 Login Tracking, 0178:3-82, 0183:3-111
 logout, 0145:6-408
 Logout menu, 0178:3-111, 0183:3-141
 Logout on Communications Failures (22.0), 0347:4-93
 Error Messages, 0347:4-94
 logout procedure, 0145:4-23
 logs
 log viewer navigation commands, 0178:3-70, 0183:3-33
 Logs menu, 0183:3-107
 Look in: Field
 Select Starting Directory window, 0197:2-54
 Select window, 0197:2-82
 Loopback in progress, 0177:2-399
 Loopback invalid, 0338:3-817

Master Index

- Loopback prevented, 0338:3-816
- loss of connectivity, 0188:2-11, 0188:2-27, 0190:2-37
- Lower bound exceeds upper bound of range - %, 0177:2-20
- Lower bound exceeds upper bound of range - <parm>, 0177:2-24
- LPU, 0178:3-48
- LPU Commands, 0178:B-2
- LRN, 0288:4-2
- LRN Quantities on the Eagle - Increasing, 0288:3-75
- LRN Table Increase (26.1), 0347:4-95
 - Changed Commands, 0347:4-95
 - Upgrade Considerations, 0347:4-110
- LSL parameters not valid for card type, 0177:2-510, 0177:2-511
- LSMS, 0348:1-11
 - command line interface (lsmsclaa), 2339:5-32
 - connection to ELAP for provisioning, 0178:2-5, 0178:2-10, 0178:2-11
 - Creating an EMS Configuration Component, 0288:2-76
 - data, 2339:1-1, 2339:2-4
 - Deleting an EMS Configuration Component, 0288:2-86
 - ELAP connection for provisioning, 0178:2-10
 - EMS Configuration Component, 0288:2-76
 - EMS Routing, 0288:2-88
 - existing connection to ELAP, 0178:2-11
 - hardware platform, 0025:4-10
 - initial ELAP connection to, 0178:2-10
 - Manually Verifying and Restarting the Eagle Agents, 0288:2-140
 - Modify EMS Routing, 0288:2-88, 0288:2-91
 - Modifying an EMS Configuration Component, 0288:2-82
 - primary connection to ELAP, 0178:2-10
 - Viewing an EMS Configuration Component, 0288:2-84
- LSMS BLM-Based Operations
 - Removing the BLM, 0288:2-26
 - Removing the DCM, 0288:2-23
- LSMS bulk download cancelled at LSMS, 0338:3-982
- LSMS bulk download complete, 0338:3-981
- LSMS bulk download in progress, 0338:3-980
- LSMS bulk load complete, 0338:3-127
- LSMS bulk load required, 0338:3-126
- LSMS Connection, 0178:3-8
- LSMS Connection menu, 0178:3-31
- LSMS HS Audit menu, 0178:3-25
- LSMS HS Bulk Download, 0178:3-28
- LSMS is at min. service limit, 0338:3-472
- LSMS is available, 0338:3-460
- LSMS is unavailable, 0338:3-461
- LSMS parameter requires LNP feature, 0177:2-607
- LSMS Q.3 association available, 0338:3-468
- LSMS Q.3 association unavailable, 0338:3-465
- LSMS-Based Operation - Distributing the LNP Database, 0288:2-134
- LSN and LINK parms cannot be specified together, 0177:2-118
- LSN and LOC cannot be specified together, 0177:2-117
- LSN must be provided with ALL=NO, 0177:2-131
- LSN must be specified, 0177:2-120, 0177:2-411

LSN parameter not valid for type-enttype combination, 0177:2-120
 LSRESTRICT Option, 0120:3-94, 0120:3-269, 0120:3-270, 0120:3-271, 0120:3-273
 LSS, 0188:1-11, 0190:1-11, 0193:1-13, 0195:1-11
 No Map IMEI Parameter present, 0338:3-740
 LSUSEALM not allowed for non-IPGWx linksets, 0177:2-794
 LVL, 0288:4-13, 0288:4-14, 0288:4-15, 0288:4-16, 0288:4-18, 0288:4-19
 Lvl 1 Removable detected during upgrade, 0177:2-523

M

M2PA on IPLIMx (Release 29.1) (IP7 Release 7.1), 0347:4-95
 M2PATSET requires M2PA adapter type, 0177:2-539
 MA, 0348:1-11
 main board, 0188:5-5, 0190:2-50
 main board configuration, 0188:2-23
 main DSM network, 0178:2-7, 0183:2-9, 0190:2-38
 main ground, 0095:6-5, 2969:6-5
 Main Ground Bar, 0224:4-16
 main menu, 0183:3-12
 main power feeds, checking, 0096:3-16, 2712:3-13
 Main Screen, 0183:3-5
 Maintenance, 0188:2-23, 0190:2-50
 80% Threshold of Support, 0195:4-6
 Actions Taken When the System is in an Unstable Loading Mode, 0195:4-7
 Card Related MPS Alarms, 0193:5-18, 0195:4-15
 Conditions That Create an Unstable Loading Mode, 0195:4-6
 DSM Code Loading, 0195:4-5
 DSM Memory Capacity Status Reporting, 0195:4-4
 DSM Status Messages – When Sent, 0195:4-3
 DSM Status Reporting to the EPAP, 0195:4-3
 DSM Status Requests, 0195:4-2
 DSM-EPAP Link Alarms, 0193:5-16, 0195:4-13
 EIR Alarms, 0195:4-12
 EIR Status Reporting, 0195:4-4
 EIR UIMs, 0195:4-18
 EPAP Application Data Loading, 0195:4-5
 EPAP Maintenance Blocks, 0195:4-2
 Insufficient SCCP Service, 0195:4-6
 Loading Mode Support Status Reporting, 0195:4-4
 MPS (EPAP) Alarms, 0193:5-16, 0195:4-13
 Non-EIR Data Initialization, 0195:4-5
 State Transitions during Start-Up, 0195:4-8
 Subsystem Alarms, 0193:5-20, 0193:5-21, 0195:4-17
 System Status Reporting, 0195:4-4
 Using the force Option, 0195:4-8
 VSCCP Capacity, 0195:4-6
 maintenance
 High Speed Master Timing (26.0), 0347:3-64
 monthly, 0096:3-2, 0096:3-8, 2712:3-2, 2712:3-6
 overview, 0096:3-1, 2712:3-1
 Temporary Alarm Inhibiting and Offline Functions (EAGLE 25.0), 0347:5-126
 TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-139

Master Index

Maintenance and Administration Communication Application Processor card, 0188:2-25
Maintenance and Administration Subsystem, 0025:3-4, 0212:2-4
maintenance and administration subsystem
 overview, 0100:1-10, 0120:1-10, 0142:1-10
Maintenance and Administration Subsystem (MAS), 0212:3-18
Maintenance and Administration Subsystem Processor (MASP), 0224:5-81
Maintenance and Administration Subsystem Processors See MASP cards, 0145:4-2
maintenance and measurement interface, 0188:3-8
Maintenance and Measurements, 0188:5-1, 0190:5-1, 0193:5-1, 0195:4-1
maintenance and measurements, 0188:1-2
Maintenance and Measurements User Interface, 0190:3-10
maintenance application traffic, 0188:2-13, 0190:2-42, 0193:2-13
maintenance baseline, 0188:5-7
maintenance blocks, 0188:2-12, 0188:5-2, 0190:5-2, 0193:2-9, 0195:2-13, 0195:4-2
Maintenance Blocks, ELAP
 contents of, 0178:4-2
 description, 0178:4-2
Maintenance Blocks, EPAP
 contents of, 0183:4-2
 description, 0183:4-2
Maintenance Commands, 0188:2-25, 0190:2-51
Maintenance Disk and Alarm (MDAL) Card Replacement, 0338:A-3
maintenance disk and alarm card (MDAL), 0212:3-46
Maintenance Disk and Alarm card See MDAL card, 0145:4-2
maintenance information, 0193:2-14
Maintenance Interface System (MIS), 0212:3-141
Maintenance Log, 0178:3-62
Maintenance Manual, 0224:1-6
Maintenance Menu, 0178:3-16, 0183:3-17
maintenance releases, 0188:1-8, 0190:1-8, 0195:1-7
maintenance reporting mechanism, 0188:2-15
Maintenance Requirements, 0193:5-1
Maintenance software, 0338:1-15
Maintenance Status Reports, 0338:4-125
Maintenance strategy, 0338:1-15, 0338:1-16
maintenance task, 0178:3-7
maintenance terminal, 0190:2-47, 0193:2-17
maintenance, EPAP
 task overview, 0183:2-8
Major Alarm, 0212:3-5, 0338:3-3
Major alarm, 0183:3-7
major alarms, 0145:4-3, 0338:2-7
Major Application Alarm, 0183:4-17
Major Application Errors, 0096:4-3, 2712:4-3
Major Application Failure(s), 0338:3-486
Major customer trouble detected, 0338:3-142
Major failures detected on both IMTs, 0338:3-192
Major holdover clock trouble detected, 0338:3-147
Major IMT failure detected, 0338:3-183
Major Platform Alarm, 0183:4-16
Major Platform Errors, 0096:4-2, 2712:4-2
Major Platform Failure(s), 0338:3-485

major problem, 0224:1-21, 0243:1-22, 0347:1-12
 major software releases, 0188:1-8
 Making a Backup of the Database to the Removable Cartridge, 0338:2-15
 Manage Data menu, 0183:3-59, 0195:5-3
 Manage Log Files, 0178:3-64
 Manage Log Files menu, 0183:3-35
 Manage Unused UserIDs, 0178:3-82, 0183:3-111
 Management of Unused User IDs (21.0), 0347:4-110
 managing
 audit, 2339:5-13, 2339:5-18
 bulk load, 2339:6-5
 resynchronization, 2339:4-2, 2339:6-2
 user-initiated resynchronization, 2339:4-6
 manual
 admonishments, 0100:1-8, 0120:1-8, 0142:1-8
 organization, 0100:1-2, 0120:1-2, 0142:1-2, 0121:3-44
 related publications, 0025:1-8, 0100:1-3, 0120:1-3, 0142:1-3, 0177:1-3, 0224:1-13, 0243:1-12, 0338:1-4, 2712:1-4, 2970:1-2
 manual audience, 0193:1-2
 Manual Deactivation of SRST Message (21.0), 0347:4-111
 Manual Organization, 0188:1-2, 0190:1-2, 0193:1-2, 0195:1-2
 manual, related publications, 0348:1-2
 Manually Verifying and Restarting the Eagle Agents on the LSMS, 0288:2-140
 manuals
 Alarms Reference and User's Manual, 0212:1-18, 0243:1-18
 Data Collection Applications Manual, 0212:1-18, 0243:1-18
 Feature Guide, 0212:1-17, 0243:1-18
 Feature Notice, 0212:1-17, 0243:1-18
 hardware and installation manuals, 0212:1-18, 0243:1-19
 list of Sentinel, 0212:1-17, 0243:1-18
 Release Notice, 0212:1-18, 0243:1-18
 System Administrator's Guide, 0212:1-18, 0243:1-18
 technical reference documents, 0212:1-19, 0243:1-19
 User's Manual, 0212:1-18, 0243:1-18
 MAP, 0188:1-11, 0188:2-3, 0190:1-11, 0193:1-13, 0195:1-11, 0348:1-11
 Map entry must be solitary, 0177:2-429
 MAP messages, 0190:1-1
 MAP Operation Code, 0347:5-19
 MAP Phase Determination, 0190:2-55
 Map Screening cannot Duplicate MSU, 0338:3-911
 Map Screening cannot forward MSU, 0338:3-690, 0338:3-909
 MAP Table Increase (Release 29.0), 0347:4-111
 Map with STP True PC has LNP/INP/EIR SS-APPL assigned, 0177:2-493
 Mapping LNP translation types, 0288:3-59
 marking
 cable holes, 0095:4-5, 2969:4-5
 frame layout, 0095:4-4, 2969:4-4
 MAS, 0188:1-11, 0190:1-11, 0193:1-13, 0195:1-11, 0212:3-18
 MAS Communication Application Processor (MCAP) Card Replacement, 0338:A-5
 MAS communications application processor (MCAP), 0224:5-81
 Masking tape, 0224:3-20
 masking tape, 0095:4-3, 2969:4-3

Master Index

masonry drill-bit, 0095:4-3, 0224:3-20, 2969:4-3
MASP, 0025:3-4, 0212:2-5, 0212:3-19, 0224:5-84
MASP became active, 0338:3-95
MASP became standby, 0338:3-96
MASP cards, 0145:4-2
master clock
 High Speed Master Timing (26.0), 0347:3-60
Master Timing, 0224:5-81
matching prefix, 0193:2-19
Matching routing key already entered for AS, 0177:2-734
Mate already exists for linkset, 0177:2-785
Mate Applications, 0099:2-44, 0099:3-2, 0099:4-2
Mate IPGWx Linkset - Configuring, 0100:3-55
Mate linkset not defined, 0177:2-792
Mate parameters
 MPC, MSSN, MateRC are required together, 0177:2-429
Mate PC / SSN cannot be given when MULT=SOL, 0177:2-172
Mate PC / SSN cannot be same as PC / SSN, 0177:2-175
mate platform, 0188:2-10
Mate Relative Cost (MateRC) required if MPC / MSSN is entered, 0177:2-426
mated application, 0193:4-38
mated application commands
 LNP—Changes to Existing Commands (22.0), 0347:4-60
Mated Application Considerations, 0188:2-18, 0190:2-47, 0193:2-17
mated application subsystem
 allowing, alw-map-ss, 2339:8-4
 inhibiting, inh-map-ss, 2339:8-4
mated application table, 0188:2-18, 0190:2-47
Mated Applications, 0099:2-40
mated EPAP servers, 0188:2-10
mated EPAP system, 0193:2-4
mated gateways, 0100:3-7, 0120:3-6
Mated linksets must contain only SS7IPGW or IPGWI links, 0177:2-782
Mated linksets must have APCs of same network type, 0177:2-782
mated MPS servers, 0193:2-4, 0195:2-9
mated pair configuration, 0188:2-10, 0190:2-35
Mated STPs
 X.25 gateway routing, 0097:2-9
Matrix Controller Automatic, 0212:3-144
MAU, 0212:3-96, 0224:5-21, 0224:5-23, 0224:5-142
MAU (Media Access Unit), 0224:2-13, 0243:1-5
Max IP connections exceeded, 0177:2-622
Max number combined LSLs and ATM HSLs already entered, 0177:2-511
Max number of cards of application type already exist, 0177:2-614
Max number of DEFINED MSGCODEs per variant is exceeded, 0177:2-346
Max number of DEFINED PARMCODEs per variant is exceeded, 0177:2-346
Max number of entries exist in FTP Server table, 0177:2-338
Max number of FTPSERV table entries exist for this APP, 0177:2-339
Max number of STC cards per shelf is entered, 0177:2-705
Max Packet Size must be 128 when N1 is equal to 1080, 0177:2-281
Max sockets per routing key exceeded, 0177:2-622
Maximum Account Inactivity, 0178:3-108, 0183:3-138

Maximum allowed Prefix values already entered for feature, 0177:2-821
 Maximum Concurrent Logins, 0178:3-109, 0183:3-139
 Maximum Concurrent User Logins, 0178:3-109, 0183:3-139
 Maximum Failed User Logins, 0178:3-108, 0183:3-138
 maximum number length, 0190:2-6
 Maximum number of applications already assigned, 0177:2-477
 Maximum Number of CDPNNAs already provisioned, 0177:2-91
 Maximum number of CDPNPFs already provisioned, 0177:2-80
 Maximum number of connections already provisioned for AS, 0177:2-737
 Maximum number of CPCs defined (96), 0177:2-381
 maximum number of digits allowed in MGT, 0188:2-33
 Maximum number of link tests already in progress, 0177:2-400
 Maximum number of links are assigned to this linkset, 0177:2-41
 Maximum number of Mated Applications (MAP) exceeded, 0177:2-427
 Maximum number of PPSMSGTAs already provisioned, 0177:2-464
 Maximum number of rules exceeded in screen set, 0177:2-207
 Maximum number of screen sets exceeded, 0177:2-207
 Maximum of 10 unique CCNCs allowed, 0177:2-553
 Maximum Password Age, 0178:3-108, 0183:3-138
 Maximum RContexts per AS exceeded, 0177:2-800
 maximum SAPC entries exceeded, 0177:2-750
 Maximum SVCAs already defined for link, 0177:2-287
 Maximum weight, 0095:2-7, 0212:6-5, 2969:2-7
 May not change adjacent point code type, 0177:2-136
 May not modify both T21 and IT23 timers, 0177:2-65
 May not specify both LOC and STAT, 0177:2-147
 May not specify both LSN and PST, 0177:2-157
 May not specify Filename when ALL=YES, 0177:2-93
 MB, 0348:1-11
 MCA, 0212:3-144
 MCAP, 0188:1-11, 0188:2-25, 0190:1-11, 0193:1-13, 0195:1-11, 0197:2-3, 0338:A-5
 MCAP card
 High Speed Master Timing (26.0), 0347:3-63
 MCCMNC, 0188:3-4
 mccmnc=, 0188:4-37
 MCP card must be IS-ANR Restrict to enable measplatform, 0177:2-156
 MCPM, 0142:2-57, 0142:2-63, 0142:2-82, 0142:2-85, 0142:2-93, 0142:2-97, 0142:3-50, 0142:3-69,
 0142:4-127, 0142:4-129, 0142:4-132, 0142:4-133, 0142:4-134, 0142:4-137, 0142:4-138, 0142:4-155,
 0142:4-165, 0142:A-30
 MDAL, 0212:3-19, 0212:3-21, 0212:3-37
 MDAL alarm cleared, 0338:3-172
 MDAL backplane connectors, 0224:B-57
 MDAL card
 function of, 0145:4-2
 removable cartridge drive, 0145:4-2
 MDAL LEDs, 0338:3-4
 MDAL not responding, 0338:3-171
 MDM, 0348:1-11
 MDN, 0188:1-12, 0188:2-1, 0190:1-11
 MEA, 0188:1-11, 0188:2-24, 0190:1-11, 0190:2-51, 0193:1-13, 0193:5-6, 0195:1-11
 Meas for Enh GSM MAP Screening not supported on EOAM, 0177:2-810
 Meas Platform feature must be ON, 0177:2-304

Master Index

MEAS Platform must be enabled, 0177:2-458
Meas sync not allowed from old version, 0338:3-691
Measurement Collection & Polling Module, 0142:4-127, 0142:4-132
Measurement collection in progress, Retry later, 0177:2-746
Measurement Preparation in progress, Retry later, 0177:2-639
Measurement Reports, 0188:5-18, 0190:5-20, 0193:5-26, 0195:4-23
 Availability, 0338:4-42
 Component, 0338:4-21
 Daily Availability, 0338:4-37
 Daily Maintenance, 0338:4-50
 Day-To-Hour Availability, 0338:4-40
 Day-to-Hour Maintenance, 0338:4-78
 Gateway, 0338:4-107
 Hourly Maintenance, 0338:4-91
 Maintenance Status, 0338:4-125
 Network Management, 0338:4-29
 Record Base, 0338:4-118
 STP System Totals, 0338:4-13
Measurements
 OAM Based, 0188:5-16, 0338:4-4
 Optional 15-Minute, 0338:4-10
 Platform, 0338:4-5
measurements, 0188:5-17, 0190:3-13
 Group Ticket Voucher (23.0), 0347:3-38
 ITU MTP Restart (26.0), 0347:3-159
 MTP Restart (EAGLE 21.0), 0347:4-134
 Multiple Point Code Support (EAGLE 26.05), 0347:4-148
Measurements data copy failure, 0338:3-902
Measurements Enhancements (22.0), 0347:4-112
Measurements not inhibited, 0177:2-56
Measurements Platform, 0097:5-39, 0142:2-57, 0142:2-81, 0142:2-93, 0142:4-129, 0142:4-131, 0142:4-132, 0142:4-140, 0142:4-144, 0142:4-148, 0142:4-150, 0142:4-164, 0142:A-29, 0338:4-5
Measurements Platform IP Security, 0212:2-13
Measurements Platform option, 0097:5-39, 0142:2-57, 0142:2-81, 0142:2-93, 0142:4-136, 0142:4-140, 0142:A-29
Measurements Platform—Phase 1 (Release 28.0), 0347:4-115
Measurements subsystem available, 0338:3-597
Measurements subsystem unavailable, 0338:3-596
measurements terminal
 configuring, 0142:4-121
measurements, extracting LNP from FTA, 0145:5-8
Media Access Unit, 0212:3-96
Media Access Unit (MAU), 0212:3-95, 0224:2-13, 0243:1-5
MEI Block Data, 0348:4-13
Memory, 0096:3-16, 2712:3-13
memory
 MPS Server for ELAP support, 0212:4-27
 MPS Server for EPAP support, 0212:4-27
Memory Applique, 0212:3-91
memory boundaries, 0188:5-5
memory insufficient, 0188:5-11
memory requirements, 0190:5-5, 0193:5-7, 0195:4-4

- memory, DSM
 - capacity status reporting, 0178:4-7, 0183:4-9
 - daughterboard continual validation, 0178:4-6
 - daughterboard local verification, 0183:4-5
 - daughterboard real-time verification, 0183:4-5
- Menu
 - Commands, 0197:2-13
 - Connectivity Test Log
 - File, 0197:2-34
 - Edit
 - FTP-Based Table Retrieve Application, 0197:2-16, 0197:2-80
 - Exit, 0197:2-13
 - File
 - Command File Editor window, 0197:2-89
 - Connectivity Test Log window, 0197:2-34, 0197:2-35
 - FTP-Based Table Retrieve Application window, 0197:2-14
 - Retrieve Tables Log window, 0197:2-70, 0197:2-71
 - System Log window, 0197:2-99, 0197:2-100
 - Update Tables Log window, 0197:2-94, 0197:2-95
 - FTP Server Configuration, 0197:2-13, 0197:2-51
 - Browse button, 0197:2-52, 0197:2-53
 - Set button, 0197:2-52
 - FTP-Based Table Retrieve Application, 0197:2-51
 - Help
 - FTP-Based Table Retrieve Application, 0197:2-104
 - Retrieve Tables Log
 - File, 0197:2-70
 - STP Connection Configuration, 0197:2-13, 0197:2-16
 - View
 - FTP-Based Table Retrieve Application, 0197:2-72, 0197:2-95, 0197:2-100
- Menu Format, 0178:5-11
- Menu Section, 0183:3-10
- menu section, 0178:3-2, 0178:3-9, 0183:3-2
- menus, ELAP user interface
 - configuration, 0178:5-13
 - see also configuration menu
 - default values for prompts, 0178:5-11
 - Escape key to exit operations, 0178:5-11
 - responding to prompts, 0178:5-11
- menus, EPAP user interface
 - configuration
 - see also configuration menu
 - default values for prompts, 0183:5-13
 - Escape key to exit operations, 0183:5-13
 - responding to prompts, 0183:5-13
- Message
 - Command In Progress, Cannot Close Window, 0197:2-88
 - IP Address warning, 0197:2-45
 - Must Enter Command Script File Name, 0197:2-84
 - Processing Validate Request, Please Wait, 0197:2-84, 0197:2-90
 - Update Tables processing completed without errors, 0197:2-89
- message box, 0178:3-8, 0183:3-8

Master Index

message conversion

Calling Name Conversion Facility (CNCF) (23.1), 0347:2-52

X.25/SS7 Gateway Feature (Eagle 20.0), 0347:5-180

Message Discrimination, 0190:2-53, 0190:2-58

Message discrimination, 0193:2-20

Message Forwarding, 0188:2-33

Message History, 0178:3-9, 0183:3-8

message relay, 0190:2-5, 0348:2-4

Message Relay (MR) Function, 0025:4-5

message relay function, 0190:1-1

Message Relay Global Title Translation, 0288:3-38, 0288:3-59, 0288:3-60, 0288:3-61

Message Relay GT address, 0190:2-11, 0190:2-12

Message Relay Measurements per SSP

LNP Measurements Enhancements (25.0), 0347:4-50

Message Relay messages, 0190:2-47

message routing

MTP Restart (EAGLE 21.0), 0347:4-133

Message Signaling Unit, 0188:2-25, 0190:2-51

Message threshold argument - not valid (C<col>), 0177:2-502

messages, 0178:3-115, 0178:3-116

Abort Transaction, 0348:3-14

Begin Transaction, 0348:3-11

Connect, 0348:3-8

Create Network Entity, 0348:3-36

Create Subscription, 0348:3-15

Delete Network Entity, 0348:3-44

Delete Subscription, 0348:3-28

Disconnect, 0348:3-10

Dump Connections, 0348:3-52

End Transaction, 0348:3-13

PDBA Status Query, 0348:3-51

Retrieve Network Entity, 0348:3-46

Retrieve Subscription Data, 0348:3-30

Switchover, 0348:3-48

Update Network Entity, 0348:3-40

Update Subscription, 0348:3-22

Messages for Local Subsystems, 0195:2-14

messages, ELAP user interface error

format, 0178:5-12

list of, 0178:3-112

messages, EPAP user interface error

format, 0183:5-14

list of, 0183:3-142

messages, PDBI request/ response

see also request message and response message

common response format, 0348:3-3

common response messages, 0348:3-5

data element format, 0348:3-3

definitions, 0348:3-2

descriptions, 0348:3-8

integer identification (iid), 0348:3-3

optional parameter format, 0348:3-3

Method A
 update EOAP, 2970:4-23, 2970:4-35
 Method B
 update EOAP, 2970:4-25, 2970:4-36
 MF or MV parms must be kept in an ordered list starting at 1, 0177:2-345
 MGMT terminal type, 0142:4-55
 MGT, 0188:1-12, 0190:1-12, 0193:1-13, 0195:1-11
 MGT (E.214) Routing, 0188:2-3
 MGT2IMSI conversion table, 0188:2-32
 MGTT - Global Title Translation Modification, 0099:1-2, 0099:1-3, 0099:2-6, 0099:2-7, 0099:2-15,
 0099:2-43, 0099:2-46, 0099:2-47, 0099:2-48, 0099:3-22, 0099:3-23, 0099:3-26, 0099:3-27, 0099:3-32,
 0099:3-34, 0099:3-53, 0099:3-54, 0099:3-57, 0099:3-58, 0099:3-61, 0099:3-64, 0099:4-30, 0099:4-33,
 0099:4-34, 0099:4-38, 0099:4-57, 0099:4-59, 0099:4-60, 0099:4-63, 0099:A-39
 MGTT cannot be ON if any SCCP card less than 586 processor, 0177:2-316
 MGT-to-IMSI reconversion, 0188:2-33
 MIM
 E1T1, 0097:6-7
 MIN, 0188:1-12, 0188:2-1, 0190:1-12, 0195:1-11, 0348:1-11
 minimum LSMS / Eagle Ethernet facility
 Enhanced Bulk Download (25.0), 0347:2-149
 Minor Alarm, 0212:3-5, 0338:3-3
 Minor alarm, 0183:3-7
 minor alarms, 0145:4-3, 0338:2-7
 Minor Application Alarm, 0183:4-17
 Minor Application Errors, 0096:4-4, 2712:4-4
 Minor Application Failure(s), 0338:3-488
 Minor customer trouble detected, 0338:3-143
 Minor holdover clock trouble detected, 0338:3-148
 Minor IMT failure detected, 0338:3-180
 Minor Platform Alarm, 0183:4-17
 Minor Platform Errors, 0096:4-3, 2712:4-3
 Minor Platform Failure(s), 0338:3-487
 minor problem, 0224:1-22, 0243:1-23, 0347:1-13
 Minutes argument - not valid (C<col>), 0177:2-503
 Minutes out of range, 0177:2-99
 MIS, 0212:3-139, 0224:A-24
 Miscellaneous Command Adjustments (26.0), 0347:4-119
 Activate Echo to a Terminal, 0347:4-119
 Cancelling rtrv and rept-stat Commands, 0347:4-120
 Changed Commands, 0347:4-119
 Miscellaneous Command Adjustments (26.1), 0347:4-121
 Different Database Level Alarm Repetition When UAM 34 Has Been Raised, 0347:4-121
 Ent-/Chg-GTT Failure Message Shows Overlap, 0347:4-121
 Miscellaneous Frame, 0212:3-127
 Miscellaneous frame, 0224:3-27
 Miscellaneous Frame (MF), 0212:3-4
 miscellaneous frame (MF), 0212:3-14
 Miscellenous Commands, 0178:B-17
 mismatch of data, 0190:2-47
 Mismatch of Equipment and Attributes, 0188:2-24, 0190:2-51, 0193:5-6
 Missing argument assignment operator, 0177:2-6

Master Index

Missing authentication context, encountered during the SSH user authorization - Error code 641, 0197:2-111

Missing command identifier, 0177:2-5

Missing information unit separator, 0177:2-19

Missing mandatory parameter, 0178:B-19

Missing mandatory parameter - <parm>, 0177:2-6

Missing modifier separator, 0177:2-5

Missing parameter, 0177:2-154

Missing parameter - BC, 0177:2-86

Missing parameter - CARD, LOC or IMT, 0177:2-86

Missing parameter - DA or DR, 0177:2-86

Missing parameter - DPADDR or DR, 0177:2-305

Missing parameter block separator, 0177:2-4

Missing parameter identifier, 0177:2-7

Mixed Networks Using the ANSI/ITU Gateway Feature

Point-to-Point Connectivity for ITU Point Codes, 0347:5-12

Mixed point code types are not allowed, 0177:2-208

MMI, 0188:1-12, 0190:1-12, 0195:1-11, 0348:1-11

Mnemonic argument is undefined, 0177:2-175

MNP, 0188:1-12, 0188:2-2, 0190:1-12, 0190:2-2, 0193:1-13, 0193:2-1, 0195:1-11, 0348:1-11

MNP Circular Route Detected, 0338:3-907

MNPSMS feature, 0347:5-20

MNP-SRF, 0190:2-7, 0190:2-45, 0190:2-56, 0190:2-60

MNP-SRFA, 0190:2-11, 0190:2-12

MNP-SRFB, 0190:2-10, 0190:2-12

MO drive, 0025:4-10

MO Forward Short Message (MO FSM), 0347:5-19

MO Removable Cartridge, 0338:2-11

MO Removable Cartridge Description, 0338:2-10

MO SMS feature must be activated, 0177:2-540, 0177:2-542

MO/MT Call to a Number Not Known to be Ported (Direct Routing), 0190:2-9

MO_FSM, 0348:1-11

Mobile Application Part, 0188:2-3

Mobile Directory Number, 0188:2-1

Mobile Identification Number, 0188:2-1

Mobile Number Portability, 0188:2-2, 0190:1-1, 0190:2-2, 0193:2-1

Mobile Originated FSM from Contract, 0190:2-13

Mobile Originated FSM from Prepaid, 0190:2-15

Mobile Originated Short Message Service message (MO SMS), 0347:5-19

Mobile Originated/Terminated Call to an Exported Number (Direct Routing), 0190:2-8

Mobile Station International Integrated Services Digital Network, 0188:2-1

Mobile Station international ISDN number, 0190:2-2

mobile subscriber, 0190:2-45

Mobile Subscriber Integrated Services Digital Network (MSISDN), 0347:5-19, 0347:5-20

Mobile Subscriber Integrated Services Digital Network (MSISDN) number (i.e. phone number), 0347:5-20

Mobile Switching Center, 0188:2-1

Mobile Switching Center (MSC), 0347:5-19

Mobile Switching Centers, 0188:1-1

Mobile Terminated Call, 0188:2-6

Mobile Terminated Call by Indirect Routing, 0190:2-7

Mobile Terminated Call to Non-porting or Imported Number (Indirect Routing), 0190:2-7

- mode
 - DSM unstable loading, 0178:4-7, 0183:4-6
 - loading, support status reporting, 0183:4-9
- modem, 0224:5-107
- modem for PPP connection, 0178:2-9
- modem for remote access, 0188:2-21
- Modem Not Working, 0338:3-60, 0338:3-61
- modems, 0025:4-10
- modems, verifying, 0096:3-10, 2712:3-7
- Modification of security log not allowed, 0177:2-433
- Modify Authorized PDBA Client IP, 0183:3-89
- Modify button, 0197:2-18, 0197:2-38, 0197:2-39
- Modify EMS Routing, 0288:2-88
- Modify Group menu, 0178:3-98
- Modify System Defaults menu, 0178:3-108, 0183:3-138
- Modify UI Group, 0183:3-128
- Modify User, 0183:3-115
- Modify User screen, 0178:3-85
- Modify Warning window, 0197:2-41
- Modifying an EMS Configuration Component, 0288:2-82
- Modifying an Existing STP Configuration Record, 0197:2-38, 0197:2-45, 0197:2-50
- Month out of range, 0177:2-100
- monthly maintenance, 0096:3-2, 0096:3-8, 2712:3-2, 2712:3-6
- Monthly Procedures, 0338:2-24
- More than one of CARD, LOC and IMT specified, 0177:2-87
- Motherboard BIP invalid, 0338:3-177
- Motherboard BIP valid, 0338:3-178
- motherboard, verification of DSM, 0183:4-4
- mounting bracket
 - 8-Port Connector Box, 0212:4-12
- mounting brackets
 - EOAP shelf, 0338:5-72, 2970:6-20
- Mouse-over check, 0183:3-11
- mouse-over check, 0178:3-11
- MPC and MSSN must be defined for new MULT val, 0177:2-180
- MPC does not exist in routing table, 0177:2-176
- MPC entered, MSSN must also be given, 0177:2-176
- MPC feature must be enabled, 0177:2-666
- MPC network type does not match PC network type, 0177:2-176
- MPC/MSSN pair already exists, 0177:2-178
- MPL, 0097:6-7, 0212:3-21, 0212:3-37
- MPS, 0188:1-12, 0188:2-7, 0190:1-12, 0193:1-13, 0195:1-11, 0348:1-11
 - definition, 0178:2-2
 - hardware platform, 0178:2-3
 - installation, 0096:2-14, 2712:2-12
 - introduction, 0096:2-2, 2712:2-2
 - overview
 - layered design, 0025:6-4, 0096:2-3
 - terminology, 0096:2-4, 2712:2-3
 - platform alarms, 0178:4-14, 0183:4-16
 - system hardware configuration, 0025:6-4, 0096:2-5, 2712:2-5
 - system software configuration, 0025:6-6, 0096:2-10, 2712:2-10

Master Index

- upgrade, 0096:2-14, 2712:2-12
- MPS (EPAP) Alarm, 0193:5-16, 0195:4-13
- MPS alarms, general recovery procedure instructions, 0096:3-19, 2712:3-18
- MPS available, 0338:3-336
- MPS Available alarm, 0178:4-15, 0183:4-17
- MPS database size, 0188:5-2
- MPS frame
 - front view, 0212:4-13
 - rear view, 0212:4-13
- MPS hardware
 - Field Replaceable Units (FRUs), 0096:5-2, 0096:5-3, 0096:5-4, 2712:5-2, 2712:5-3, 2712:5-4
 - frame layout, 0212:4-13
 - list of equipment, 0025:6-2
 - overview, 0212:4-12
- MPS hardware platform, 0183:2-2
- MPS Health Check Procedure, 0288:2-74
- MPS Host Servers, 0212:4-25
- MPS must be either 128 or 256, 0177:2-298
- MPS on Netra, 0025:6-10
- MPS Platform, 0096:3-17, 2712:3-14
- MPS platform, 0193:2-2, 0195:2-8
- MPS RTDB Audit, 0178:2-19, 0183:2-31
- MPS Server
 - see also MPS system
 - alarm card
 - description, 0025:6-12, 0212:4-28
 - CD-ROM, 0212:4-27
 - component specifications, 0025:6-11
 - CPU specifications, 0212:4-27
 - DVD-ROM, 0212:4-27
 - front detail view, 0212:4-22, 0212:4-30
 - front view, 0212:4-25
 - I/O architecture, 0212:4-28
 - LEDs, 0025:6-12, 0212:4-28, 0212:4-32
 - memory to support EPAP and ELAP, 0212:4-27
 - Netra t 1400, 0212:4-25
 - networking ports, 0212:4-28
 - operating system, 0212:4-28
 - overview, 0025:6-10, 0212:4-25
 - parallel ports, 0212:4-28
 - Quad FastEthernet Network Interface card, 0212:4-31
 - rear detail view, 0212:4-22, 0212:4-30
 - rear view, 0212:4-26
 - SCSI disks, 0212:4-27
 - SCSI interface, 0212:4-28
 - serial ports, 0212:4-28
 - serial ports SAI/P card, 0212:4-31, 0212:4-43
 - storage components, 0212:4-27
 - tape drive, 0212:4-27, 0212:4-29
- MPS server, 0347:2-2
- MPS Server, power down procedure, 0096:5-8, 2712:5-7
- MPS system

see also MPS Server
 additional features, 0025:6-11, 0212:4-28
 component specifications, 0025:6-11
 Ethernet hub description, 0212:4-47, 0212:4-50
 list of hardware components, 0025:6-2
 supported features, 0025:6-1
 MPS unavailable, 0338:3-337
 MPS/EPAP 4.0, 0025:1-6, 0212:1-8, 0212:4-11
 MPS/EPAP Platform, 0193:2-2
 MPS/EPAP platform, 0193:2-7, 0195:2-12
 MPS/EPAP Platforms for Provisioning EIR, 0195:2-9
 MPS/EPAP Platforms for Provisioning G-Flex, 0188:2-9
 MPS/EPAP Platforms for Provisioning G-Port, 0190:2-34
 MPS/EPAP Platforms for Provisioning INP, 0193:2-3
 MPS-to-DSM Data Validation, 0178:2-19, 0183:2-32
 MR, 0193:1-13
 MRN table is full, 0177:2-350
 MSAR=ONLY must be specified exclusively, 0177:2-381
 MSC, 0188:1-1, 0188:1-12, 0188:2-1, 0190:1-12, 0193:1-13, 0195:1-11, 0348:1-11
 MSGCODE and PARMCODE must both be DEFINED, 0177:2-345
 MSIN truncated, 0188:2-33
 MSISDN, 0188:1-12, 0188:2-1, 0190:1-12, 0190:2-2, 0190:2-7, 0193:1-13, 0195:1-11, 0348:1-12, 0348:2-3
 MSISDN number, 0188:1-1, 0188:4-1, 0190:2-53, 0190:4-1
 MSISDN numbers, 0188:3-2
 MSISDN / MIN / MDN (E.164) Routing, 0188:2-5
 MSISDN / MIN / MDN global title routing, 0188:2-6
 MSRN, 0188:1-12, 0190:1-12, 0193:1-13, 0195:1-11
 MSRNNAI and MSRNNP parameters must be entered together, 0177:2-711
 MSSN or MATERC entered, MPC must also be given, 0177:2-178
 MSU, 0188:1-12, 0190:1-12, 0193:1-13, 0195:1-11, 0348:1-12
 MSU measurements, 0188:5-17
 MSU reception threshold exceeded, 0338:3-800
 MSU routing
 ANSI/ITU MTP Gateway (20.0), 0347:2-37
 MSU Trap and Trace Command, 0188:3-1, 0190:3-1, 0193:3-15
 MSU trapped, 0188:3-1
 MSU trigger, 0190:3-2, 0193:3-15
 msucount, 0145:9-36
 msuroute, 0145:9-68
 MSUs, 0188:2-25, 0190:2-51
 msutrace, 0145:9-73
 MT SMS Delivery for Migrated or New GSM only Subscriber
 SMSRequest First, 0190:2-28
 SRI-for-SM First, 0190:2-27
 MT SMS Delivery for Non-Migrated IS-41 Subscriber
 SMSRequest First, 0190:2-27
 SRI-for-SM First, 0190:2-25
 MT_FSM, 0348:1-12
 MTP, 0188:1-12, 0190:1-12, 0193:1-13, 0195:1-11
 Changeback T5 timeout, 0338:3-713
 link bypassed SLT phase, 0338:3-705
 MTP Adj PC not in routing table, 0338:3-637

Master Index

MTP and other MRN Message Format Improvements (21.0), 0347:4-123
MTP Circular Route Detection (21.0), 0347:4-128
MTP envelopes, 0097:2-4, 0347:5-180
MTP Invalid TFA received, 0338:3-793
MTP Invalid TFR received, 0338:3-794
MTP MAP Screening
 Configuring, 0097:5-37, 0097:5-41, 0097:5-42
MTP Message Received for Network 255, 0338:3-638
MTP rcvd invalid H0/H1 code, 0338:3-614
MTP rcvd invalid TFC - status 0, 0338:3-613
MTP rcvd Transfer Controlled (TFC), 0338:3-612
MTP rcvd unknown DPC, 0338:3-615
MTP rcvd UPU - User SCCP, Cause invalid, 0338:3-959
MTP rcvd User Part Unavailable, 0338:3-610, 0338:3-959
MTP requirements
 Types of Routing Strategies Available, 0347:4-175
MTP Restart (EAGLE 21.0), 0347:4-131
 Alarms, 0347:4-135
 Aligning Signaling Links in a fully Restarting Node, 0347:4-134
 Event Reporting, 0347:4-134
 Existing Commands, 0347:4-135
 Measurements, 0347:4-134
 Message Routing, 0347:4-133
 New Commands, 0347:4-136
MTP Restart Indicator must be off to execute this command, 0177:2-525
MTP restart option not valid for IPGWAPC linksets, 0177:2-633
MTP RSTRT rcvd unexpected user traffic, 0338:3-721
MTP Screening, 0098:2-2
MTPDPCQ cannot be increased while x-list storage is full, 0177:2-381
MTPDPCQ cannot be less than no. of destinations provisioned, 0177:2-385
MTPDPCQ cannot exceed available space in the dstn table, 0177:2-380
MTPRSE parameter is only valid if ITUMTPRS feature is ON, 0177:2-660
MTPRSE parameter is only valid if MTPRS feature is ON, 0177:2-357
MTPRSI is only valid if MTPRS or ITUMTPRS feature is ON, 0177:2-356
MTPRSIT parameter is only valid if MTPRS feature is ON, 0177:2-357
MTPT10ALT cannot be less than level-3 timer T10, 0177:2-397
MTPXLQ cannot exceed available space in the dstn table, 0177:2-365
MTPXLxx parameters are only valid if CRMD feature is ON, 0177:2-365
MTS, 0348:1-12
MTSU, 0348:1-12
MTT, 0348:1-12
MULTCC entry already exists in the GSM Options CC list, 0177:2-547
MULTCC entry cannot be NONE, 0177:2-439
MULTCC entry does not exist, 0177:2-585
MULTCC list is full, 0177:2-585
MULTGC=YES not allowed if ITUDUPPC feature is OFF, 0177:2-723
MULTGC=YES requires IPGWI or IPLIMI links, 0177:2-713
MULTGC=YES requires ITU-N or ITU-I point code, 0177:2-731
Multi, 0212:3-19
multicast hardware, 0190:2-39
multicast updates, 0188:2-21, 0190:2-33
Multi-Platform Server (MPS) Systems, 0025:6-1, 0212:2-24

- multiple alarm conditions, 0178:4-4, 0183:4-3
- Multiple Capability Point Codes (EAGLE 21.0), 0347:4-136
- multiple DSMs, 0188:2-26
- Multiple Flash Download (Release 29.0), 0347:4-139
- Multiple LFS Tests (EAGLE 26.0), 0347:4-140
 - Changed Commands, 0347:4-142
 - Latching versus Non-latching LFS Tests, 0347:4-140
 - Limitations, 0347:4-143
 - New Commands, 0347:4-142
- Multiple Linksets between Two Nodes
 - Multiple Point Code Support (EAGLE 26.05), 0347:4-146
- multiple point code support, 0120:2-55
 - Local Number Portability, 0120:2-60
- Multiple Point Code Support (EAGLE 26.05), 0347:4-143
 - Enhanced Commands, 0347:4-149
 - Impact on Other Features, 0347:4-147
 - Limitations, 0347:4-151
 - Local Subsystems (LNP and Toll-Free), 0347:4-147
 - Measurements, 0347:4-148
 - Multiple Linksets between Two Nodes, 0347:4-146
 - New Commands, 0347:4-149
 - Provisioning Multiple Point Codes, 0347:4-150
 - Replacing Two STP Pairs with One Eagle Pair, 0347:4-144
 - UIMs, 0347:4-150
 - Upgrade Considerations, 0347:4-150
- Multiple Session Connectivity, 0348:2-13
- Multiple Sessions per User, 0178:3-81, 0183:3-111
- multiple trigger criteria, 0188:3-1, 0190:3-2, 0193:3-15
- Multi-Port LIM, 0142:3-62
- Multi-Port LIM (EAGLE 27.1)
 - Changed Commands, 0347:4-152
 - Hardware Requirements, 0347:4-154
 - Upgrade Considerations, 0347:4-154
- Multi-Port LIM (Release 27.1) (IP7 Release 6.0), 0347:4-151
- Multi-Port LIM(EAGLE 27.1), 0347:4-151
- Multi-Purpose Server, 0025:1-6, 0193:2-2, 0195:2-8, 0212:1-8, 0212:4-11, 0243:1-11
- Multi-Purpose Server (MPS)
 - New Hardware (EAGLE 26.05), 0347:4-193
- Multi-Purpose Server (MPS) hardware, 0188:2-7
- Must be in upgrade phase 3 or full function mode, 0177:2-424
- Must enter at least one PC /RC pair, 0177:2-457
- Must Enter Command Script File Name message, 0197:2-84
- Must specify ALL=YES to delete all files, 0177:2-93
- Must specify application and version, 0177:2-95
- Must specify either
 - ENTRY or ROW with COLUMN, 0177:2-496
- Must specify either SNAME or ASNAME, 0177:2-734
- Must specify NC when NI is specified for ORIGININC, 0177:2-494
- MySQL Backup menu, 0178:5-23, 0183:5-26

N

N1 must be either 1080 or 2104, 0177:2-297
NA entry already equipped, 0177:2-753
NA entry not found, 0177:2-754
NACTION must be specified (FORWARD, DUPLICATE, or DUPDISC), 0177:2-456
NACTION parameter must be FORWARD, DUPLICATE, or DUPDISC, 0177:2-455
Nagle's Algorithm, 0100:2-39
NAI, 0188:2-22, 0193:1-13, 0193:2-11
NAI and NAIV must not be specified together, 0177:2-562
NAI entries per TT-NP combination has reached allowed max, 0177:2-567
NAI value, 0193:2-11
NAI values, 0193:2-2, 0193:2-7
NAIV, 0193:1-13
NAK, 0348:1-12
Name field, 0178:3-7, 0183:3-7, 0183:3-9
NAME not valid with ACTION=RESET, 0177:2-310
national, 0193:2-11
national database, 0193:2-16
National Indicator bit, 0188:2-21
national MSISDNs, 0190:2-54
national number, 0188:2-31
National PC is identical to national CPC, 0177:2-70
National PCs, 0193:2-17
National Spare Network Indicator Support (EAGLE 22.2), 0347:4-154
 Changed Commands, 0347:4-155
 Disabled States, 0347:4-155
 Enabled States, 0347:4-155
 Gateway STP Impact, 0347:4-155
National Spare Network Indicator Support (EAGLE 24.0), 0347:4-156
 Changed Commands, 0347:4-157
 Disabled States, 0347:4-157
 Enabled States, 0347:4-156
 Gateway STP Impact, 0347:4-157
National Spare network indicator values, 0120:2-7
National/Local Numbers to International Numbers Conversion Logic, 0188:2-31
natl, 0193:2-11, 0193:2-22
navigation commands, ELAP log viewer, 0178:3-70
navigation commands, EPAP log viewer, 0183:3-33
NC, 0188:1-12, 0190:1-12, 0193:1-13, 0195:1-11
NC cannot be zero when NI is less than 6, 0177:2-209
NC is invalid, 0177:2-214
NC is invalid for type-enttype combo, 0177:2-515
NCAI param is only valid if both feat CRMD and NCR are ON, 0177:2-374
NCAI required if cluster members have different route set, 0177:2-378
NCDPNPFX already exists in INPOPTS Table, 0177:2-73
NCGSR shouldn't be specified when CDSR is specified, 0177:2-808
ncice, 0100:3-260, 0100:3-269, 0100:3-279
NCICE unspecified, NCICS must be less than or equal to CICE, 0177:2-652
ncics, 0100:3-260, 0100:3-269, 0100:3-279
NCICS must be less than or equal to NCICE, 0177:2-648
NCICS unspecified, NCICE must be greater than or equal to CICS, 0177:2-661
NCM is invalid, 0177:2-215

NCM must be * when using Network Routing, 0177:2-414
 NCPC, 0120:2-92
 NCPCA, 0120:2-92
 NCPCI, 0120:2-92
 NCPCN, 0120:2-92
 NCPCx and CPCx type must match, 0177:2-375
 NCPCx cannot be specified without CPCx, 0177:2-376
 NCR must be enabled to enter NCAI param, 0177:2-358
 ND, 0288:4-5, 0288:4-20, 0288:4-22, 0288:4-23, 0288:4-25, 0288:4-26, 0288:4-27, 0288:4-28, 0288:4-29
 ND parameter must be 3 or 6-10, 0177:2-449
 NDC, 0188:1-12, 0190:1-12, 0193:1-13, 0195:1-11
 NDC Q.3 association is available, 0338:3-257
 NDC Q.3 association is unavailable, 0338:3-256
 NDC Subsystem is available, 0338:3-260
 NDC Subsystem is not available, 0338:3-258
 NDC System not configured, 0177:2-636
 NDFTACT must be specified (FORWARD, DUPLICATE, or DUPDISC), 0177:2-455
 NDFTACT parameter must be FORWARD, DUPLICATE, or DUPDISC, 0177:2-340
 NDGT parameter is invalid for VGTT, 0177:2-717
 NDGT parameter not permitted with ALIAS, 0177:2-193
 NDIGITS parameter mandatory with PREFIX parameter, 0177:2-34
 NE, 0193:1-13, 0348:1-12
 NEBS, 0193:1-13, 0224:3-33, 0348:1-12
 NEBS Compliance (EAGLE 20.0), 0347:4-158
 NEI LBP has already been defined for the CCS7 link, 0177:2-390
 NEI LBP must be defined as the last link element, 0177:2-391
 neonly, 0348:3-31
 Nested Cluster Routing (EAGLE 26.0), 0347:4-159
 Administration, 0347:4-161
 Changed Commands, 0347:4-172
 General Requirements, 0347:4-162
 Nested Clusters and Cluster Members, 0347:4-159
 Upgrade Considerations, 0347:4-172
 Nested Clusters and Cluster Members
 Nested Cluster Routing (EAGLE 26.0), 0347:4-159
 netmask IP address, 0178:5-18, 0183:5-20
 Netra t 1400
 see also MPS Server
 front view, 0212:4-25
 LEDs, 0212:4-32
 rear view, 0212:4-26
 Netscape, 0183:5-2
 netstat, 0145:9-90
 netstat -a | grep 21, 0197:2-122
 Network, 0243:A-13
 network, 0338:5-22, 2970:7-21
 complex, 0120:3-8
 configuration, 0025:6-8, 0096:2-16, 2712:2-14
 interfaces, 0025:6-8, 0096:2-17, 2712:2-15
 MPS Server ports, 0212:4-28
 Quad FastEthernet Network Interface card, 0212:4-31
 syscheck, 0096:3-16, 2712:3-13

Master Index

- types, 0120:2-2
- network addresses, 0188:2-15, 0190:2-44, 0193:2-15
- Network Appearance table full, 0177:2-798
- Network appearances, 0100:3-4
- Network Connections, 0188:2-12, 0190:2-40, 0193:2-12
- network connections, 0348:2-8
- network element data
 - automatic resynchronization of, 2339:4-2
- Network Entities, 0348:2-17
- Network Entity menu, 0183:3-72
- network installations, 0193:1-2
- Network latency, 0197:2-125
- Network Management Measurements, 0338:4-29
- network number portability, 0193:2-1
- network operators, 0190:1-1
- Network Perspectives, 0188:2-16, 0190:2-45
- network routing, 0120:2-174
 - administration, 0120:2-180
 - broadcast transfer messages, 0120:2-177
 - circular routing, 0120:2-178
 - local link congestion, 0120:2-177
 - point code availability, 0120:2-176
 - reception of an RCx message, 0120:2-180
 - reception of an RSx message, 0120:2-179
 - reception of transfer messages, 0120:2-179
 - remote congestion, 0120:2-177
 - response method transfer messages, 0120:2-177
 - route availability, 0120:2-176
 - route management, 0120:2-177
 - routing strategies, 0120:2-174
- Network Routing (EAGLE 26.0)
 - Types of Routing Strategies Available, 0347:4-174
- Network Routing is only valid if the NRT feature is ON, 0177:2-413
- network routing point code, 0120:2-3
- Network Security Enhancements (Release 29.0), 0347:4-182
- Network Security Enhancements Controlled Feature
 - Activating, 0142:A-3
 - Deactivating, 0142:A-38
- Network Security Enhancements feature must be ON, 0177:2-498
- Network Surveillance Enhancements, 0347:4-190
- Network Surveillance Enhancements (Release 28.0), 0347:4-190
- network time protocol
 - configuring, 0096:2-19, 2712:2-17
 - in Tekelec 1000 AS platforms, 0096:2-19
 - in Tekelec 1100 AS platforms, 2712:2-17
 - overview, 0096:2-20, 2712:2-17
- network values, 0178:5-26, 0183:5-34, 0288:2-56
- Network with DPC and Group Codes, 0183:2-14
- network, customer
 - description, 0183:2-10
- network, customer (provisioning)
 - configure IP addresses, 0178:5-18, 0183:5-20

- description, 0178:2-9
- network, Dialup PPP
 - description, 0178:2-9, 0183:2-10
 - IP addresses, 0178:2-9
 - modem for, 0178:2-9
 - remote dial-in serial port configuration, 0178:2-9
- network, ELAP Sync
 - configure IP addresses, 0178:5-18
 - description, 0178:2-4, 0178:2-8
 - IP addresses, 0178:2-8
- network, EPAP Sync
 - configure IP addresses, 0183:5-20
 - description, 0183:2-4, 0183:2-9
 - IP addresses, 0183:2-9
- network, Ethernet
 - 100BASE-T, 0178:2-7, 0178:2-8, 0183:2-9
 - 10BASE-T, 0178:2-7, 0183:2-9
 - DSM networks, 0178:2-4, 0178:2-7, 0183:2-4, 0183:2-9
 - ELAP Sync network, 0178:2-8
 - EPAP Sync network, 0183:2-9
- Network/Cluster cannot have alias DPC members, 0177:2-377
- Network/Cluster DSTNs are not supported in the X.25 domain, 0177:2-371
- networks
 - RFC 1587 standard, 0178:2-7, 0288:2-29
 - sample IP addresses for, 0178:2-7
- networks, DSM
 - configure IP addresses, 0178:5-19, 0183:5-21
 - description, 0178:2-4, 0178:2-7, 0183:2-4, 0183:2-9
 - IP addresses, 0178:2-7, 0183:2-9
 - troubleshooting reports, 0183:4-14
- new administration commands
 - Thresholding of UIM Messages (EAGLE 25.0), 0347:5-132
- New CIC range overlaps an existing routing key, 0177:2-648
- New class name cannot be the same as an existing class name, 0177:2-126
- new commands
 - 48 Million Numbers (27.0), 0347:2-14
 - CDU for DSM (26.05), 0347:2-63
 - Eagle Application Support for E1 (26.3), 0347:2-106
 - Enhanced Bulk Download (25.0), 0347:2-150
 - Enhanced GTT (26.0), 0347:2-155
 - Flash Memory Management (23.0), 0347:3-4
 - G-Port MNP (26.2), 0347:3-20
 - GSM MAP Screening (26.1), 0347:3-42
 - INAP-based Number Portability (INP) (26.05), 0347:3-82
 - MTP Restart (EAGLE 21.0), 0347:4-136
 - Multiple LFS Tests (EAGLE 26.0), 0347:4-142
 - Multiple Point Code Support (EAGLE 26.05), 0347:4-149
 - Selective Alarm Inhibiting (EAGLE 22.0), 0347:5-76
 - Stand-alone Eagle G-Flex Relay Function, 0347:3-13
 - Support for LSMS Audit Enhancements (EAGLE 26.1), 0347:5-101, 0347:5-105
 - Translation Type Mapping (EAGLE 21.0), 0347:5-135
- New connection type must be different from existing, 0177:2-297

Master Index

New Control Shelf Backplane (EAGLE 23.0), 0347:4-191
New digits valid (DV) must not match old DV indication, 0177:2-483
new features
 IP7 Transport Feature (26.1), 0347:3-117
new GPLs
 Enhanced Bulk Download (25.0), 0347:2-147
New H0/H1 matches existing wild carded H0/H1 in given SR, 0177:2-210
New Hardware (EAGLE 23.1)
 Integrated LIM-AINF Card, 0347:4-192
New Hardware (EAGLE 26.05), 0347:4-193
 Multi-Purpose Server (MPS), 0347:4-193
new measurement reports
 ITU Gateway Measurements Enhancements (26.05), 0347:3-163
New PC and RC must be entered as a pair, 0177:2-457
New PC does not exist in the routing table, 0177:2-180
New Pegs for Per SSP G-Port Measurements, 0190:5-19
New Pegs for Per SSP INP Measurements, 0193:5-25
New Pegs for Per System and Per SSP G-Port Measurements, 0190:5-19
New Pegs for Per System EIR Measurements, 0195:4-23
New Pegs for Per System G-Port Measurements, 0190:5-18
New Pegs for Per System INP Measurements, 0193:5-25
New Translation Type already in LNP database, 0177:2-475
New Translation Type Name already in LNP database, 0177:2-475
new UAMs/UIMs
 Group Ticket Voucher for SCCP Cards (27.0), 0347:3-40
new UIMs
 TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-147
New User Default Groups, 0178:3-109, 0183:3-139
new / changed commands
 High-Speed Multiplexer (HMUX) (27.2), 0347:3-67
New / existing NSFI=AFTPC requires new / existing SSN=1, 0177:2-210
New / existing PC does not exist in the remote PC table, 0177:2-178
New / existing RI must be GT for new / existing XLAT=DPCNGT, 0177:2-179
newline, 0348:3-9
NEXT requires this term issued last valid RTRV-LOG command, 0177:2-778
NGT, 0288:3-59, 0288:3-61, 0288:3-63
NGT can only be specified when XLAT=DPC or DPCNGT, 0177:2-786
NGT can only be specified when XLAT=DPCNGT, 0177:2-181
NGT must be specified for new values of XLAT/RI, 0177:2-181
NGT must be specified when XLAT=DPCNGT, 0177:2-197
NGTI only valid when PC and GTTSN are different domains, 0177:2-764
NGTI only valid when PC and TYPE are different domains, 0177:2-775
NH0 and NH1 cannot be specified for NSI greater than 2, 0177:2-201
NH0 and NH1 cannot be specified for SI greater than 2, 0177:2-211
NH0 and NH1 must be specified for given NSI, 0177:2-210
NH1 must be wild card if NH0 is wild card, 0177:2-212
NI is invalid, 0177:2-213
NI is invalid for type-enttype combo, 0177:2-515
NI parameter may not be specified for ITU linksets, 0177:2-573
NI required, 0177:2-123
NI, ZONE, MSA or NPC cannot be C - more than one exists, 0177:2-204
NI, ZONE, MSA or NPC cannot be C for existing blocked SR, 0177:2-205

NI, ZONE, MSA or NPC must be C when creating new blocked SR, 0177:2-220
 NIC and SI must be specified for given H0 and H1, 0177:2-242
 NIC does not exist for given SR, 0177:2-219
 NIC must be specified for given SI, 0177:2-219
 NIC, SI, and H0/H1 entry already exists in given SR, 0177:2-241
 NIC, SI, H0/H1, & PRI entry already exist in given SR, 0177:2-489
 NMULTCC and MULTCC parameters must be entered together, 0177:2-101
 NMULTCC entry already exists in the GSM Options MULTCC list, 0177:2-557
 nnai, 0348:3-38, 0348:3-42
 NNGT, 0288:3-59, 0288:3-60, 0288:3-63
 NNIC, NSI, and NH0/NH1 entry already exists in given SR, 0177:2-217
 nnp, 0348:3-38, 0348:3-42
 NNP, NNAI, NPDD/S, NSDD/S, NNGT, RMGTT invalid if MGTT is OFF, 0177:2-343
 No active LFS Test on the specified link, 0177:2-394
 No available primary MCP, 0177:2-470
 No buffer space available - Error code 55, 0197:2-120
 No change requested, 0177:2-648
 No Entry found, 0177:2-619
 No File Transfer Area on removable cartridge, 0177:2-96
 No key is available on the SSH client on the EAGLE 5 SAS - Error code 668, 0197:2-114
 No match on ACTNAME parameter during retrieve, 0177:2-595
 No match on AREA or SSA parameter during retrieve, 0177:2-221
 No match on DESTFLD parameter during retrieve, 0177:2-409
 No match on EPRI parameter during retrieve, 0177:2-221
 No match on H0 parameter during retrieve, 0177:2-222
 No match on H1 parameter during retrieve, 0177:2-222
 No match on ID or SP parameter during retrieve, 0177:2-222
 No match on NC parameter during retrieve, 0177:2-223
 No match on NCM parameter during retrieve, 0177:2-223
 No match on NI parameter during retrieve, 0177:2-224
 No match on NIC parameter during retrieve, 0177:2-224
 No match on NPC parameter during retrieve, 0177:2-225
 No match on NSFI parameter during retrieve, 0177:2-225
 No match on NSR parameter during retrieve, 0177:2-225
 No match on PCST parameter during retrieve, 0177:2-799
 No match on PRI parameter during retrieve, 0177:2-226
 No match on REDIRECT parameter during retrieve, 0177:2-312
 No match on RI parameter during retrieve, 0177:2-226
 No match on SCCPMT parameter during retrieve, 0177:2-409
 No match on SCMGFD parameter during retrieve, 0177:2-410
 No match on SI parameter during retrieve, 0177:2-226
 No match on SSN parameter during retrieve, 0177:2-227
 No match on TYPE parameter during retrieve, 0177:2-227
 No match on ZONE or MSA parameter during retrieve, 0177:2-227
 No MIC of TYPE=ALL exists, 0177:2-451
 No MIC with the same service and digits exists, 0177:2-452
 No obits to display, 0177:2-160
 No optional parameters may be specified if FORCE=YES, 0177:2-267
 No other optional parameters may be specified with "ALL", 0177:2-592
 No other optional parms can be entered with SRCSET, 0177:2-621
 No other parameters are permitted with the NEXT parameter, 0177:2-778
 No Reportable Downtime on Network Restart

Master Index

Upgrade Procedure Enhancements (Eagle 22.0), 0347:5-163
No test link message is sent, 0177:2-152
No troubles to display, 0177:2-160
No user associated with OAP terminal, 0177:2-386
No value expected for '<parm>' parameter (C<col>), 0177:2-507
Node is no longer isolated, 0338:3-391
Node isolated due to SLK failures, 0338:3-389
nodes in different countries, 0183:2-13
non oxidizing grease, 0224:4-16, 0224:4-18
Non-ANSI Point Code Support (EAGLE 20.0), 0347:4-193
Non-Call Related Message for Non-Ported Number (Indirect Routing), 0190:2-10
Non-Call Related Message for Ported Number (Indirect Routing), 0190:2-11
Non-Call Related Message for Ported or Non-Ported Number (Direct Routing), 0190:2-12
non-call related messages, 0190:1-1, 0190:2-5
non-call-related message, 0190:2-45
none, 0193:2-11, 0348:3-8
NONE is a reserved name and cannot be used for a TTN, 0177:2-482
None terminal type, 0142:4-55
Non-EIR Data Initialization, 0195:4-5
Non-Generation of Duplicate SEAS Autonomous Messages (EAGLE 22.0), 0347:4-193
Non-G-Flex Data Initialization, 0188:5-6
Non-G-Port Data Initialization, 0190:5-6
Non-GSM Data Initialization, 0193:5-8
Non-Integrated Sentinel Solutions, 0212:2-29
non-ported case, 0190:2-12
non-standard values, 0193:2-19
NORM=YES not supported for specified PSTNCAT / PSTNID values, 0177:2-722
Normal GTT processin, 0347:5-20
normal retransmission
 Preventive Cyclic Retransmission (PCR) (EAGLE 20.0), 0347:5-28
normal transaction mode, 0348:3-9
Not compatible with SCCP Conversion feature, 0177:2-764
Notification of Congestion Level Increase (EAGLE 22.0), 0347:4-194
Notification of Inability to Perform a Global Title Translation (EAGLE 22.0), 0347:4-195
Notification of Link Set Outage (EAGLE 22.0), 0347:4-195
Notification of Link Set Recovery (EAGLE 22.0), 0347:4-195
Notification of Locally Initiated Database Copy (EAGLE 22.0), 0347:4-196
Notification of MTP-Level Routing Error (EAGLE 22.0), 0347:4-197
Notification of Recovery from Link Congestion (EAGLE 22.0), 0347:4-197
notification, database maintenance required, 2339:3-3
notifications, 2339:4-2, 2339:4-3
NP, 0188:1-12, 0188:2-22, 0190:1-12, 0193:1-13, 0195:1-11
NP and NAI must be specified as DFLT together, 0177:2-573
NP and NPV must not be specified together, 0177:2-562
NP database lookup, 0190:2-7
NP HLR, 0348:2-3
NP ported TNs 2million Qty Feat Requires at least TSM256MB, 0177:2-639
NP(V) and NAI(V) must be specified for given GTI value, 0177:2-564
NP(V) and NAI(V) must not be specified for given GTI value, 0177:2-563
NPA, 0188:1-12, 0190:1-12, 0193:1-13
NPANXX, 0347:4-76, 0347:4-88
NPANXX Measurements

LNP—Measurements (22.0), 0347:4-71
 NPANXX Quantities on the Eagle - Increasing, 0288:3-75
 NPA-NXX Split / Delete, 0178:3-59
 NPA-NXX Split menu, 0178:3-58
 NPA-NXX Split screen, 0178:3-46
 npcfmti option, 0188:4-10, 0190:4-11, 0193:4-11
 npcst parameter, 0098:2-11, 0098:3-21, 0098:4-27, 0098:6-28, 0098:6-29, 0098:7-25, 0098:8-27, 0098:8-31, 0098:9-32, 0098:11-27, 0098:11-31, 0098:11-32, 0098:12-31, 0119:5-7, 0119:5-15, 0119:5-33, 0119:5-43, 0119:5-55, 0119:5-71, 0119:5-103, 0119:5-118
 NPCx cannot be specified without PCx, 0177:2-814
 NPDB, 0188:1-12, 0190:1-12, 0193:1-13, 0195:1-11
 NPPMSGTA already exists in GSMOPTS Table, 0177:2-465
 NPV, 0188:1-12, 0190:1-12, 0193:1-13, 0195:1-12
 NRGTA, 0288:3-59, 0288:3-60, 0288:3-61, 0288:3-63
 NSAP parameter requires LNP feature, 0177:2-605
 NSD, 0188:1-12, 0190:1-12, 0193:1-13, 0195:1-12
 NSD Systems, 0212:1-5
 NSFI / NSR cannot be specified, 0177:2-229
 NSFI and NSR do not reference an existing screen, 0177:2-230
 NSFI is invalid, 0177:2-487
 NSFI must be FAIL, 0177:2-229
 NSFI must be specified, 0177:2-228
 NSFI must be STOP, 0177:2-229
 NSFI must be STOP if ACTNAME is specified, 0177:2-591
 NSFI must be STOP if COPY or REDIRECT are specified, 0177:2-199
 NSFI must not be FAIL, 0177:2-228
 NSI must be specified for given NNIC, 0177:2-230
 nslookup, 0145:9-101
 NSNAI = NONE only allowed when NSERV = INPQ, 0177:2-712
 NSNAI must be specified when NSERV = INPMR, 0177:2-700
 NSR cannot be specified if ACTNAME is specified, 0177:2-591
 NSR cannot be specified if COPY or REDIRECT are specified, 0177:2-209
 NSR cannot be specified when NSFI is STOP or FAIL, 0177:2-232
 NSR must be specified for given NSFI, 0177:2-231
 nstall, 0188:4-21, 0190:4-20, 0190:4-21, 0193:4-21
 NSTAT, 0195:5-33, 0195:5-35, 0195:5-37, 0288:3-46, 0288:3-49, 0288:3-51
 NTP
 configuring, 0096:2-19, 2712:2-17
 in Tekelec 1000 AS platforms, 0096:2-19
 in Tekelec 1100 AS platforms, 2712:2-17
 overview, 0096:2-20, 2712:2-17
 NTP server, 0178:5-26, 0183:5-34
 NTP Time Available, 0338:3-584
 NTP Time Unavailable, 0338:3-583
 ntt, 0348:3-38, 0348:3-42
 NTT can only be specified when XLAT=DPC or DPCNGT, 0177:2-786
 NTT can only be specified when XLAT=DPCNGT, 0177:2-569
 NTT must be specified for new values of XLAT/RI, 0177:2-572
 NTT must be specified when XLAT=DPCNGT, 0177:2-569
 null, 0348:3-9
 num, 0348:3-32, 0348:3-34, 0348:3-47
 NUM exceeds maximum table size, 0177:2-183

Master Index

Number Conditioning, 0190:2-54, 0190:2-63
Number conditioning, 0188:2-28, 0193:2-20
number conditioning, 0193:2-2, 0193:2-7, 0193:2-11, 0193:2-19
number conditioning error, 0193:2-19
number conversion triggered, 0188:2-31
number normalization, 0193:2-2, 0193:2-7, 0193:2-11
Number of PREFIX digits cannot exceed NDIGITS parameter, 0177:2-35
Number out of range, 0177:2-162
Number Pooling (EAGLE 24.0), 0347:4-198
 Changed Commands, 0347:4-198
Number Pooling / Efficient Data Representation (EDR) (EAGLE 26.1), 0347:4-199
 Changed Commands, 0347:4-203
 Limitations, 0347:4-203
 Overview, 0347:4-200
 Upgrade Considerations, 0347:4-202
Number Portability, 0188:2-22
number portability, 0190:1-1, 0190:2-2, 0193:2-1
Number Portability Administration Center (NPAC), 0178:2-11, 2339:1-1, 2339:2-2
number portability translations, 0193:2-6
Number Prefixes menu, 0183:3-104
Numbering, 0188:2-22, 0190:2-49
numbering capability, 0190:3-3
numbering plan, 0188:2-1, 0188:2-31, 0188:2-32
NZO is not valid for this TYPE, 0177:2-123

O

OA&M IP Security feature disabled, 0338:3-291
OA&M IP Security feature is OFF, 0338:3-505
OA&M IP Security feature is ON, 0338:3-506
OAI, 0188:1-12, 0190:1-12, 0195:1-12
OAM, 0188:1-12, 0190:1-12, 0193:1-13, 0348:1-12
OAM application, 0188:5-5
OAM code, 0188:5-5
OAM IP Security Enhancements Controlled Feature - EAGLE 5 SAS
 Activating, 0142:A-12
 Deactivating, 0142:A-38
OAM provisioning, 0188:2-15, 0190:2-43, 0193:2-14
OAM reboot during bulk download
 Enhanced Bulk Download (25.0), 0347:2-150
OAM switchove, 0347:5-10
OAP, 0188:1-12, 0190:1-12, 0193:1-13, 0195:1-12, 0212:3-26, 0348:1-12, 2970:3-5
OAP Alarm (OAPALM), 0212:3-26
OAP alarm installation, 0224:5-87
OAP CFG required before OAP update, 0177:2-608
OAP commands
 Eagle Initiated OAP User Interface (24.0), 0347:2-118
OAP filesystem full, 0338:3-474
OAP frame, 0224:3-27
OAP GPL
 change trial to approved version, 0142:3-149
OAP Hostname required before OAP update, 0177:2-608

OAP IP Address required before OAP update, 0177:2-609
 OAP is available, 0338:3-456
 OAP parameter
 chg-oap-config, 2970:4-12
 OAP terminal type, 0142:4-55
 OAP terminals available, 0338:3-456
 OAP terminals inhibited, 0338:3-451
 OAP Unavailable, 0338:3-429
 OAP Upgrade Enhancement (EAGLE 27.2), 0347:4-203
 OAP Year 2000 Compliance
 Year 2000 Compliance (Eagle 23.1), 0347:5-194
 OAPALM, 0212:3-26
 OAPF, 0212:3-146, 0212:4-46
 Obit Message for Abort of Card Loading, 0193:5-10, 0195:4-8
 Obit Message for Card Loading Abort, 0188:5-8, 0190:5-8
 Obituaries, 0338:3-54
 Occurrence argument - not valid (C<col>), 0177:2-503
 Octet 1 is out of range, 1 . . . 223 - <parm>, 0177:2-12
 Octet 1 missing - <parm>, 0177:2-14
 Octet 2 is out of range, 1 . . . 254 - <parm>, 0177:2-13
 Octet 2 missing - <parm>, 0177:2-14
 Octet 3 is out of range, 1 . . . 254 - <parm>, 0177:2-13
 Octet 3 missing - <parm>, 0177:2-15
 Octet 4 is out of range, 1 . . . 254 - <parm>, 0177:2-13
 Octet 4 missing - <parm>, 0177:2-15
 octet addresses, 0190:2-44
 OCTET and ALTERNATE are not valid for non-latching test, 0177:2-396
 octets, 0188:2-15, 0193:2-15
 changing ELAP Sync network IP address third, 0178:5-18
 changing EPAP Sync network IP address third, 0183:5-20
 DSM network IP address, 0178:2-7, 0183:2-9
 ELAP Sync network IP address, 0178:2-8
 EPAP Sync network IP address, 0183:2-9
 OCU, 0212:3-68
 OEM-Based Network Elements, 0212:2-30
 OEM-Based Peripheral Components, 0212:2-31
 OEM-Based Products, 0212:1-8
 OEM-Based Products and Elements, 0212:2-24
 OEM-Based Servers, 0212:2-30
 Office Channel Unit (OCU), 0212:3-65
 On-demand report currently being printed, 0177:2-122
 One SEAS TDM Port unavailable, 0338:3-457
 one-inch diameter hole, 0095:4-5, 0224:3-15, 2969:4-5
 Online Cartridge Formatting (EAGLE 20.0), 0347:4-204
 Only 4 ports with sys maint. output group ON are allowed, 0177:2-155
 Only 6 message relay services can be assigned, 0177:2-486
 Only IPGW routes are allowed for private PCs, 0177:2-803
 only one ITU-I APC/SAPC allowed per linkset, 0177:2-750
 Only one of BYTE, WORD or DWORD may be entered, 0177:2-88
 Only one of IPADDR, IPAPPL, IPRTE, or LOC can be specified, 0177:2-270
 Only one of IPAPPL or IPPORT may be specified, 0177:2-266
 Only one of NCPC / A, NCPCI, or NCPCN / N24 may be specified, 0177:2-67

Master Index

Only one of PPCN or PCN24 may be specified, 0177:2-279
Only one optional parameter may be specified, 0177:2-261
Only one Source and Destination may be specified, 0177:2-90
Only one SS7IPGW or IPGWI link allowed in mated linkset, 0177:2-629
Only PARMCODE=0 (EOP) can have MINLEN=0, 0177:2-344
Only SNAME, ASNAME or RCONTEXT allowed for default rtkey, 0177:2-734
Only two E1 ports allowed for Linkclass equals unchan, 0177:2-724
on-site MPS, 0178:5-27, 0183:5-35, 0288:2-57
OOBM, 2969:A-3
OOS-MT-DSBLD, 0195:5-33, 0288:3-46, 0288:3-50, 0348:1-12
OOS-MT-DSBLD (out of service maintenance disabled), 0347:3-129
OOS-MT-DSBLD state, 2970:4-7, 2970:4-18, 2970:4-30
OP/MAINT LED, 0338:2-7
OPC, CICS, CICE are not allowed with SI unless SI is 4, 5, or 13, 0177:2-636
OPC, CICS, CICE are required if SI is 4, 5, or 13, 0177:2-635
opc/opca, 0100:3-223, 0100:3-224, 0100:3-235, 0100:3-252, 0100:3-260, 0100:3-268, 0100:3-278
OPCODE already exists, 0177:2-676
OPCODE and OPNAME shouldn't be specified together, 0177:2-719
open, 0100:3-191
OPEN must be NO to change an Association or its AS/Rtkey, 0177:2-741
OPEN must be NO to change or delete socket, 0177:2-623
Open sockets cannot have same lhost/lport, 0177:2-667
openSSH 3.0.2p1, 0197:2-107, 0197:2-108, 0197:2-109, 0197:2-110, 0197:2-111, 0197:2-112, 0197:2-113,
0197:2-115, 0197:2-116, 0197:2-117, 0197:2-118, 0197:2-122
Operating system, 0197:2-2
 Windows 2000, 0197:2-7
 Windows 98, 0197:2-7
 Windows NT, 0197:2-7
operating system, Solaris 7, 0212:4-28
Operation Code
 GSM MAP Screening
 Adding, 0097:5-64, 0097:5-74, 0097:5-75, 0097:5-76, 0097:5-77
 Changing, 0097:5-82, 0097:5-88, 0097:5-89, 0097:5-90, 0097:5-91
 Removing, 0097:5-78, 0097:5-81
Operations Support System Application Processor frame (OAPF), 0212:3-4
Operations Support System Application Processors (OAP), 0212:3-3
Operations Support System Applications Processor, 0212:1-9, 0212:2-25
operations system support applications processor frame (OAPF), 0212:3-16
operations, Escape key to exit user interface, 0178:5-11, 0183:5-13
operator provisioning system, 0193:2-16
operator's provisioning system, 0190:2-32
OPNAME already used, 0177:2-676
OPNAME does not exist in the database, 0177:2-677
OPS, 0188:1-12, 0188:2-7, 0190:2-32, 0193:1-14, 0193:2-16
optical disk drives, 0025:4-10
Optimal Routing, 0190:2-11
Option
 DISCARDTFCL, 0120:3-276, 0120:3-277
 DISCARDTFCLN, 0120:3-276, 0120:3-277
 LSRESTRICT, 0120:3-94, 0120:3-269, 0120:3-270, 0120:3-271, 0120:3-273
 Restricted Linkset - Configuring, 0120:3-269, 0120:3-274, 0120:3-275
Option for Subsystem Prohibit (Release 29.0), 0347:4-204

Optional 15-Minute Measurements, 0338:4-10
 optional parameter format, 0348:3-3
 Options
 TFCs on ITU-I Networks - Configuring Options
 TFCs on ITU-N Networks - Configuring, 0120:3-276, 0120:3-278
 options
 changing
 SCCP Class 1 Sequencing, 0099:2-20, 0099:2-196, 0099:2-197, 0099:2-198, 0099:2-199
 options, audit and reconcile, 2339:5-9
 orange flag, 0224:4-24
 Ordered routes cannot be assigned to cluster members, 0177:2-378
 Ordered routes cannot be changed for cluster members, 0177:2-382
 Ordered routes cannot be deleted from cluster members, 0177:2-379
 organization of manual, 0193:1-2
 original number range owner network, 0190:2-7
 original telephone number, 0193:2-1
 originating MSC, 0347:5-19
 Origination point code, 0190:3-2, 0193:3-16
 OS, 0348:1-12
 OTID, 0193:1-14
 Out of band management, 2969:A-3
 Out of Band Management Card, 2969:A-3
 OUTGRP and SNUM/ENUM combination invalid, 0177:2-779
 out-of-memory condition, 0188:2-11
 out-of-sync, 0188:2-18
 out-of-sync condition, 0188:2-19
 out-of-sync data, 0190:2-47
 out-of-sync DSM database, 0183:2-8
 output banner format, 0145:4-15
 output groups, unsolicited messages, 0145:4-15
 Output Message Format, 0338:3-35
 output messages, types of, 0145:4-14
 overhead rack support, attaching, 0095:4-19, 2969:4-19
 overlapping database updates, 0188:2-21
 overlapping point codes, 0183:2-13
 overload controls, 0188:2-22
 Override GTT, 0178:3-44
 Override GTT menu, 0178:3-55
 Overview, 0188:1-1, 0190:1-1, 0195:1-1, 0212:1-3, 0212:3-43
 Activating the LNP Feature, 0288:2-4
 ELAP Software Configuration, 0288:2-33
 ELAP User Interfaces, 0288:2-33
 overview
 database partitions, 0100:1-11, 0120:1-11, 0142:1-11
 fixed disk drive, 0100:1-12, 0120:1-12, 0142:1-12
 maintenance and administration subsystem, 0100:1-10, 0120:1-10, 0142:1-10
 Number Pooling / Efficient Data Representation (EDR) (EAGLE 26.1), 0347:4-200
 removable cartridge, 0100:1-13, 0120:1-13, 0142:1-13
 Overview of ELAP UI, 0178:5-2
 Overview of EPAP to DSM Communications, 0188:2-11, 0190:2-37, 0193:2-8
 Overview of EPAP UI, 0183:3-2, 0183:5-2
 Overview of INP, 0193:1-1

Master Index

Overview of LSMS Hardware Components, 0025:4-11
Overview Sentinel Products, 0212:5-3
overview, Tekelec 1000 AS platform software, 0096:2-1
overview, Tekelec 1100 AS platform software, 2712:2-1

P

P, 0224:B-51, 0224:C-49, 0243:B-22, 0243:C-50
P Address still referenced by static IP Routes, 0177:2-580
P/N 000-0028-01, 0224:A-21
P/N 502-0040-01, 2970:3-24
P/N 502-0085-01, 0224:4-20
P/N 551-0022-02, 2969:7-4
P/N 551-0022-03, 2969:7-4
P/N 654-0075-01 gray tinted Lexan rear covers (with round holes), 0224:3-37
P/N 658-0374-01 (Label - General Purpose Frame), 0224:3-28
P/N 658-0604-01, 0224:2-10
P/N 658-0604-02, 0224:2-10
P/N 658-0604-03, 0224:2-10
P/N 690-0108-07, 0224:4-16
P/N 690-0131-01, 0095:6-8, 0224:4-20, 2969:6-8
P/N 803-0229-01, 0224:C-7, 0243:C-7
P/N 804-0165-01, 0224:A-7
P/N 804-0166-01, 0224:A-32
P/N 804-0173-01, 0224:A-28
P/N 804-0175-01, 0224:A-24
P/N 804-0219-01, 0224:3-16, 0224:3-18, 0224:3-19
P/N 804-0228-01, 0095:6-3, 0095:6-8, 0224:4-20, 2969:6-3, 2969:6-8
P/N 804-0229-01 window clear heat shrink, 0224:4-16
P/N 804-0817-02, 0095:6-8, 0224:4-9, 0224:4-19, 0224:4-20, 0224:4-21, 2969:6-8
P/N 804-0977-01 long barrel lug, 0224:4-16
P/N 804-1671-02, 0243:2-64
P/N 830-0226-xx, 0224:5-83
P/N 830-0425-01, 0212:3-96
P/N 830-0543-01, 0224:5-113, 0224:C-20, 0243:C-19
P/N 830-0609-01, 0224:C-29
P/N 830-0657-xx, 2970:3-41
P/N 830-0709-xx, 2970:3-29
P/N 830-0846-01, 0224:5-83
P/N 830-0873-xx), 0224:5-83
P/N 840-0017-02, 0224:3-33
P/N 840-1125-03, 2969:7-4
P/N 840-1133-01, 2969:7-4
P/N 850-0188-01, 0224:A-20
P/N 850-0330-03, 0212:3-21, 0212:3-22, 0212:3-26, 0212:3-27, 0212:3-43, 0224:B-3, 0224:B-4, 0224:B-18, 0243:B-2, 0243:B-3
P/N 850-0330-03/04, 0224:B-3, 0243:B-2
P/N 850-0330-05, 0224:5-22, 0224:B-3, 0224:B-4, 0224:B-19, 0243:B-2, 0243:B-3
P/N 850-0330-05/06, 0224:B-3, 0224:B-19, 0224:C-29, 0243:B-2
P/N 850-0356-01, 0224:B-25, 0224:B-61, 0243:B-9, 0243:B-24
P/N 850-0356-03, 0224:B-26, 0224:B-27, 0224:B-61, 0243:B-24
P/N 850-0356-03 Extension Shelf Back Plane, 0212:3-14

P / N 850-0488-xx, 2970:3-41
 P / N 870-0243-08, 0224:B-37
 P / N 870-0259-02, 0224:3-33
 P / N 870-0773-XX, 0224:A-23, 0243:A-10
 P / N 870-0774-10, 0224:1-5
 P / N 870-0774-xx, 0224:A-29, 0224:A-31
 P / N 870-1008-xx, 0212:3-93, 0224:A-4
 P / N 870-1009-xx, 0224:5-134, 0224:A-9, 0224:A-25, 0224:A-26, 0243:A-11, 0243:A-12, 0338:A-21,
 0338:A-24, 0338:A-25, 0338:A-26
 P / N 870-1010-xx, 0224:A-27
 P / N 870-1011-xx, 0224:A-5
 P / N 870-1012-xx, 0224:A-33
 P / N 870-1013-xx, 0224:A-22, 0243:A-9
 P / N 870-1014-xx, 0224:A-6, 0243:A-3, 0338:A-22
 P / N 870-1171-03, 0224:A-20
 P / N 870-1293-xx, 0224:A-6, 0243:A-3, 0338:A-22
 P / N 870-1307-04, 0224:A-22, 0243:A-9
 P / N 870-1379-xx, 0224:5-120, 0224:A-6, 0224:A-11, 0224:A-12, 0243:A-3, 0243:A-5, 0338:A-22,
 0338:A-23
 P / N 870-1484-xx, 0224:A-6, 0243:A-3, 0338:A-22
 P / N 870-1488-xx, 0243:A-3, 0338:A-22
 P / N 870-1606-01, 0212:3-119, 0212:3-130, 0224:2-10, 0224:5-154, 0224:5-155
 P / N 870-1824-01, 0224:5-63, 0338:A-78
 P / N 870-1915-01, 0224:2-10
 P / N 870-1965-04, 0224:1-5
 P / N 870-1984-01, 0224:5-25
 P / N 870-2049-01, 0224:A-6, 0243:A-3, 0338:A-22
 P / N 870-2320, 0224:4-35
 P / N 870-2320-01, 0224:2-10, 0224:4-6, 0224:4-9
 P / N 870-2360-01, 0224:1-5
 P / N 870-2594-01, 0243:2-64
 P / N 870-2595-01, 0243:2-64
 P / N 870-2706-02, 2969:7-5
 P / N 870-2707-01, 2969:7-5
 P / N 870-2708-01, 2969:7-5
 P / N 870-2754-01, 2969:7-5
 P / N 870-2754-02, 2969:7-5
 P / N 870-2785-01, 2969:7-4
 P / N 870-2787-01, 2969:7-4
 P / N 870-2790-01, 2969:7-5
 P / N 870-2795-01, 2969:7-5
 P / N 870-2795-02, 2969:7-5
 P / N 870-2798-01, 2969:7-5
 P / N 870-2799-01, 2969:7-5
 P / N 890-1037-01, 0212:3-104
 P / N 890-1038-01, 0224:5-68
 packaging, documentation, 0178:1-8, 0183:1-8, 0348:1-8
 Packet drop, 0197:2-125
 parallel ports, MPS Server, 0212:4-28
 parameter
 AIPADDR
 chg-oap-config, 2970:4-11

Master Index

ANAME
 chg-oap-config, 2970:4-11

ANMASK
 chg-oap-config, 2970:4-11

AROUTER
 chg-oap-config, 2970:4-11

BIPADDR
 chg-oap-config, 2970:4-11

BNAME
 chg-oap-config, 2970:4-11

BNMASK
 chg-oap-config, 2970:4-11

BROUTER
 chg-oap-config, 2970:4-11

CFG
 chg-oap-config, 2970:4-11

CPCTYPE
 chg-sid, 0193:4-36

FORCE
 chg-oap-config, 2970:4-12

OAP
 chg-oap-config, 2970:4-12

PCI
 chg-sid, 0188:4-11, 0190:4-12, 0193:4-12

PCN
 chg-sid, 0188:4-11, 0190:4-12, 0193:4-12

TRM
 chg-trm, 2970:4-4

TYPE
 chg-trm, 2970:4-4

Parameter AINTVL is not allowed, 0177:2-448

Parameter AINTVL is required, 0177:2-447

Parameter combination invalid, 0177:2-442

Parameter DRTN or AINTVL is required, 0177:2-450

Parameter DRTN or INTVL is required, 0177:2-451

Parameter INTVL is not allowed, 0177:2-447

Parameter INTVL is required, 0177:2-447

Parameter ND is not allowed, 0177:2-446

Parameter ND, DRTN, INTVL, or AINTVL is required, 0177:2-450

Parameter PCST / NPCST is not allowed with C for blocked SR, 0177:2-798

parameters for DCM signaling links, 0120:3-7

Parameters inconsistent on re-entering of command, 0177:2-659

Parameters ND, INTVL, and AINTVL are required, 0177:2-445

Parameters not valid for card type, 0177:2-42

Parameters SERV and DGTS are not allowed for TYPE=ALL, 0177:2-445

Parameters SERV and DGTS are required, 0177:2-446

parameters, command, 0145:4-9

PARMCODE is supported in a message, cannot be NOTDEFINED, 0177:2-346

Parse Failed
 reasons for, 0348:3-5
 response message, 0348:3-5
 return code, 0348:3-5

part number
 air filter, 0095:B-3, 2969:B-3
 fan assembly, 0095:B-3, 0095:B-6, 2969:B-3, 2969:B-6
 hard disk drive, 0095:B-9, 0095:B-11, 0095:B-12, 0095:B-14, 0095:B-15, 0095:B-18, 2969:B-9, 2969:B-11, 2969:B-12, 2969:B-14, 2969:B-17
 locating, 0095:B-2, 2969:B-2
 PCI card, 0095:B-12, 2969:B-12
 Part Number does not belong to an On / Off Feature, 0177:2-579
 Part numbers
 air filters, 2969:7-4
 fan assemblies, 2969:7-4
 Hard drives, 2969:7-4
 part numbers, 0096:5-2, 2712:5-2
 part numbers, documentation, 0178:1-8, 0183:1-8, 0348:1-7
 Partial point codes are not allowed, 0177:2-59
 Partial Routing Keys, 0100:2-27
 Partition specified invalid for target disk, 0177:2-148
 pass, 0145:6-409, 0188:3-14, 0188:4-6, 0188:4-7, 0188:4-26, 0188:4-34, 0190:3-18, 0190:4-6, 0190:4-7, 0190:4-25, 0190:4-34, 0193:3-12, 0193:4-6, 0193:4-7, 0193:4-26, 0193:4-34
 cmd="arp", 0188:3-16, 0190:3-20, 0193:3-14
 cmd="help", 0188:3-17, 0190:3-21, 0193:3-15
 cmd="netstat", 0188:3-15, 0190:3-19, 0193:3-13
 cmd="nslookup", 0188:3-15, 0190:3-19, 0193:3-14
 cmd="Ping", 0188:3-14, 0190:3-18, 0193:3-13
 pass command, 0347:3-30
 pass: cmd="netstat" command, 0183:4-14
 pass: cmd="Ping" command, 0183:4-14
 pass:loc=xxxx
 cmd="netstat -p tcp" EAGLE 5 SAS command, 0197:2-124
 cmd="ping yy.yy.yy.yy" EAGLE 5 SAS command, 0197:2-123
 Pass-Through Commands, 0145:2-9, 0145:9-1
 password
 change at first login, 0145:4-20
 change expired at login, 0145:4-21
 changing, 0142:4-48
 Password Age, 0178:3-108, 0183:3-138
 Password Aging (EAGLE 21.0), 0347:5-1
 Password cannot contain userID, 0177:2-331
 password complexity checking, 0178:3-108, 0183:3-138
 Password does not contain enough alphabetic characters, 0177:2-326
 Password does not contain enough characters, 0177:2-103
 Password does not contain enough numeric characters, 0177:2-327
 Password does not contain enough punctuation characters, 0177:2-328
 Password Encryption (EAGLE 21.0), 0347:5-2
 Password operations not allowed on a non-secure terminal, 0177:2-314
 Password Requirements (EAGLE 21.0), 0347:5-2
 Password Reuse, 0178:3-111, 0183:3-141
 Password Reuse Limit, 0178:3-108, 0183:3-138
 Password too long, 12 maximum, 0177:2-103
 Password verification failed, 0177:2-104
 passwords
 change for ELAP login names, 0178:5-21

Master Index

change for EPAP login names, 0183:5-24
passwords, changing, 0095:6-16, 2969:6-16
passwords, rules for administering, 0145:4-17
Path Field, 0197:2-52
path parameter, 0197:2-52
Pattern contains invalid characters, 0177:2-72
Pattern has odd number of characters, 0177:2-73
PC, 0193:1-14, 0288:3-59, 0288:3-63, 0348:1-12
pc, 0348:3-37, 0348:3-41
PC already exists in CSPC group, 0177:2-169
PC already exists in the MRN entity set, 0177:2-350
PC and RC must be entered as a pair, 0177:2-350
PC cannot match the SID, 0177:2-431
PC does not exist in CSPC group, 0177:2-170
PC does not match existing entry in given SR, 0177:2-489
PC must already exist in the MRN table, 0177:2-364
PC must match NPCFMTI set in CHG-STPOPTS, 0177:2-431
PC network type does not match existing PC network type, 0177:2-342
PC /CLLI does not match current PC /CLLI of the STP, 0177:2-134
PC /SSN already exists in given SR, 0177:2-237
PC /SSN does not exist as a mated application, 0177:2-184
PC /SSN does not exist in given SR, 0177:2-236
PC /SSN must be given with Action FORWARD, DUPLICATE, DUPDISC, 0177:2-459
PC /SSN must be specified if FORCE is specified, 0177:2-460
PC /SSN /RI /SCCPMT already exists in given SR, 0177:2-215
PC /SSN /RI /SCCPMT does not exist in given SR, 0177:2-216
PC /SSN /SCMG already exists in given SR, 0177:2-216
PC /SSN /SCMGFID does not exist in given SR, 0177:2-217
PCA, 0288:3-38, 0288:3-59, 0288:3-61, 0288:3-63
PCI card
 label, 0095:B-12, 2969:B-12
 part number, 0095:B-12, 2969:B-12
 replace, 0095:7-37, 2969:7-39
PCI cards
 Quad FastEthernet Network Interface card, 0212:4-31
 SAI/P, 0212:4-31, 0212:4-43
PCI parameter
 chg-sid, 0188:4-11, 0190:4-12, 0193:4-12
PCI slots, 0212:4-35
PCN parameter
 chg-sid, 0188:4-11, 0190:4-12, 0193:4-12
PCRN1 and PCRN2 parameters are invalid if ECM=BASIC, 0177:2-37
PCS 1900 LNP Query (EAGLE 26.0), 0347:5-2
 Changed Commands, 0347:5-6
 Feature Functions, 0347:5-3
 Limitations, 0347:5-8
 PLNPQS Details, 0347:5-3
PCS 1900 number portability, 0288:3-22
pcst parameter, 0098:2-8, 0098:2-11, 0098:2-23, 0098:3-10, 0098:3-15, 0098:3-21, 0098:4-11, 0098:4-18,
 0098:4-27, 0098:6-12, 0098:6-19, 0098:6-28, 0098:6-29, 0098:7-12, 0098:7-17, 0098:7-25, 0098:8-9,
 0098:8-13, 0098:8-14, 0098:8-22, 0098:8-23, 0098:8-27, 0098:8-30, 0098:8-31, 0098:9-14, 0098:9-23,
 0098:9-32, 0098:11-9, 0098:11-14, 0098:11-15, 0098:11-23, 0098:11-27, 0098:11-31, 0098:11-32,

0098:12-14, 0098:12-23, 0098:12-31, 0119:5-3, 0119:5-5, 0119:5-7, 0119:5-8, 0119:5-11, 0119:5-15,
 0119:5-23, 0119:5-27, 0119:5-33, 0119:5-37, 0119:5-39, 0119:5-43, 0119:5-44, 0119:5-49, 0119:5-55,
 0119:5-60, 0119:5-66, 0119:5-71, 0119:5-94, 0119:5-100, 0119:5-103, 0119:5-109, 0119:5-116, 0119:5-118
 pctype, 0348:3-37, 0348:3-40
 PCx specified does not exist as a True Point Code, 0177:2-814
 PCx, NPCx, CPCx or NCPCx must not be equal, 0177:2-382
 PDB, 0188:1-12, 0188:2-7, 0190:1-12, 0193:1-14, 0348:1-12
 description of, 0183:2-8
 PDB Backup menu, 0183:5-27
 PDB/DN table, 0347:5-20
 PDBA, 0188:1-12, 0190:1-12, 0193:2-5, 0195:1-12, 0195:2-11, 0348:1-12
 connection with PDBI client, 0348:3-8
 disconnect client from, 0348:3-10
 dump connection information for debug, 0348:3-52
 general description, 0183:2-2
 import/ export and debug log file formats, 0348:2-15
 overview, 0183:2-8
 replication, 0348:2-7
 switch Active/ Standby status, 0348:3-48
 well-known port, 0348:3-2, 0348:3-8
 PDBA / Maintenance menu, 0183:3-94
 PDBA Area, 0183:3-9
 PDBA DSM Report screen, 0183:3-92
 PDBA import/ export traffic, 0190:2-41
 PDBA menu, 0183:3-52
 PDBA replication, 0348:3-48
 PDBA Status Query, 0348:3-51
 request message, 0348:3-51
 response message, 0348:3-52, 0348:3-68, 0348:3-71
 response return codes, 0348:3-52
 status command, 0348:3-51
 PDBA, restarting, 0096:A-15
 PDBI, 0188:1-12, 0188:2-6, 0188:2-28, 0190:1-12, 0190:2-32, 0190:2-40, 0193:1-14, 0193:2-5, 0195:1-12,
 0195:2-11, 0348:1-12
 client connection with PDBA, 0348:3-8
 connection, 0348:3-8
 connection security, 0348:2-11
 description, 0348:2-1, 0348:2-10
 limit, 0183:2-25, 0348:2-10, 0348:3-8
 overview, 0183:2-8, 0348:3-2
 related publication, 0183:2-8
 request/ response messages
 see also request message and response message
 descriptions, 0348:3-8
 sample sessions
 abort transaction, 0348:4-8
 create Network Entities, 0348:4-2
 create simple subscription data, 0348:4-3
 queries with multiple responses, 0348:4-7
 simple queries, 0348:4-5
 update request in read transaction, 0348:4-9
 update subscription data, 0348:4-4

Master Index

write transaction to Standby PDBA, 0348:4-10
System Architecture, 0348:2-7
PDBI Network Entity, 0183:2-14
PDS, 0120:2-90
PDS data, 0347:5-11
PDU, 2969:3-13
Pegs for both Per System and Per SSP, 0190:5-19
Pegs for G-Flex, 0188:5-17
Pegs per SSP measurement peg counts, 0190:5-19
performance impact
 act-oap-config parameters, 2970:4-13
PERIOD must be 1 hour boundary for report type, 0177:2-116
PERIOD must be 1/2 hour boundary, 0177:2-121
Period must be 1/4 hour boundary, 0177:2-600
Peripheral Maintenance, 0193:5-5
Perl errors, 0178:B-21
Perl Statements and Functions, 0178:B-22
Perm feature key cannot be turned off for the feature, 0177:2-534
Permanently On controlled features, list of, 0145:5-88
Permission is denied by the server due to authentication failure - Error code 633, 0197:2-110
Persisten Device States, 0120:2-90
Persistent device state tbl corrupt, 0338:3-138
Persistent device state tbl diff version, 0338:3-139
Persistent Device States (Release 29.0), 0347:5-10
personal safety, 0188:1-8, 0190:1-8, 0193:1-9, 0195:1-8
PFS, 0188:1-12, 0190:1-12, 0193:1-14, 0195:1-12
PID, 0348:1-12
ping, 0145:9-103
ping parameter, 0188:4-26, 0188:4-34, 0190:4-25, 0190:4-34, 0193:4-26, 0193:4-34
ping -s zz.zz.zz.zz command, 0197:2-123
Ping Test
 CDU for DSM (26.05), 0347:2-62
pink lug, 0224:4-16
PIP and GN parameters
 Calling Name Conversion Facility (CNCF) (23.1), 0347:2-48
planing your site, 0193:3-1, 0195:3-1
platform, 0025:4-10
 alarms, MPS, 0178:4-14, 0183:4-16
 MPS hardware, 0178:2-3
Platform Menu, 0178:3-71, 0178:5-22, 0183:3-41, 0183:5-25
Platform Menu Exit, 0178:5-24
Platform Services, 0348:2-3
platform, MPS hardware, 0183:2-2
PLMN, 0188:1-12, 0190:1-12, 0190:2-45, 0193:1-14
PLNP feature must be ON, 0177:2-485
PLNPQS details
 PCS 1900 LNP Query (EAGLE 26.0), 0347:5-3
PLXO, 0212:3-143
PMTC, 0188:1-12, 0190:1-12, 0193:1-14, 0193:5-5, 0195:1-12
POI, 0193:1-14, 0193:2-16
Point Code, 0195:5-23, 0195:5-25, 0288:3-38, 0288:3-40, 0288:3-59, 0288:3-60
point code, 0188:4-11, 0190:4-12, 0193:4-12

- adding, 0120:3-5
- adding to the self identification of the EAGLE 5 SAS, 0120:2-81
- alternate, 0120:2-2
- cluster destination, 0120:2-3
- destination, 0120:2-3
- formats, 0120:2-4
- full, 0120:2-3
- network routing, 0120:2-3
- true, 0120:2-2
- Point code already exists in given SR, 0177:2-235
- point code availability
 - network routing, 0120:2-176
- Point code defined as an alias, 0177:2-132
- Point code does not exist in given SR, 0177:2-232
- Point code does not exist in the remote point code table, 0177:2-172
- Point code does not exist in the routing table, 0177:2-171
- Point code matches a STP capability point code, 0177:2-60
- Point code matches a STP point code, 0177:2-61
- Point code matches a STP secondary point code., 0177:2-787
- Point Code must be the STP True point code, 0177:2-484
- Point code must exist within the group, 0177:2-260
- Point code network type does not match TT network type, 0177:2-193
- Point code not defined, 0177:2-282
- Point code not equipped, 0177:2-159
- Point code out of range, 0177:2-62, 0177:2-238
- Point Code Subtype Prefix not supported, 0177:2-761
- point code subtype prefixes, 0145:A-12
- Point Code type does not match GTT Set network domain, 0177:2-570
- point codes, 0193:2-17
- Point codes contain invalid wild card combinations, 0177:2-203
- point of interconnection, 0193:2-16
- Point-to-Multipoint, 0100:2-22
- Point-to-Point, 0100:2-21
- Point-to-Point Connectivity for ITU Point Codes, 0347:5-12
 - Mixed Networks Using the ANSI/ITU Gateway Feature, 0347:5-12
- point-to-point network, 0183:2-9
- Point-to-Point Protocol (PPP)
 - for Dialup PPP network, 0178:2-9, 0183:2-10
 - modem for, 0178:2-9
- Policy File, 0178:5-7
- Pop-up check, 0183:3-11
- pop-up check, 0178:3-11
- PORT A LSET, 0195:5-16
- PORT B LSET, 0195:5-16
- Port B not supported for device, 0177:2-628
- Port is channel bridged with its master port, 0177:2-546
- port labels and functions, 2970:2-7, 2970:3-29
- Port must be inhibited to change comm. attributes, 0177:2-45
- PORT must be specified, 0177:2-412
- PORT must not be specified when TYPE=SVCR, 0177:2-289
- Port not valid for card or application type, 0177:2-663
- PORT parameter invalid for DEV selected, 0177:2-411

Master Index

- port Parameter, Summary of Range Values for, 0145:A-2
- port, PDBA well-known, 0348:3-2, 0348:3-8
- port, remote dial-in, 0178:2-9
- Portability Check for Mobile Originated SMS, 0190:2-18
- Portability Check for Mobile Originated SMS (MNP SMS), 0347:5-19
- Portability Check for Mobile Originated SMS (Release 29.1), 0347:5-19
- portability cluster, 0190:2-45
- portability type, 0348:3-18
- ported case, 0190:2-12
- ported number lengths, 0193:2-2
- ported numbers, 0190:1-1, 0190:2-6
- ported subscriber, 0190:2-45
- Ported subscriber SMSC matches Home SMSC Addr, 0338:3-771
- ported-in numbers, 0193:2-10
- ported-out subscriber, 0347:5-19
- porting process, 0190:2-45
- ports
 - 8-Port Connector Box, serial, 0212:4-31, 0212:4-38, 0212:4-43
 - MPS Server networking, 0212:4-28
 - MPS Server parallel, 0212:4-28
 - MPS Server serial, 0212:4-28
 - SAI/P card, 0212:4-31, 0212:4-43
- post-installation inspection, 0095:6-13, 2969:6-13
- Power, 0224:4-9
- power cable, 0224:4-9
 - CD-ROM drive
 - troubleshoot, 0338:5-8, 2970:7-5
 - hard drive
 - troubleshoot, 0338:5-8, 2970:7-5
- power cable installation, 0224:5-7
- power cables, 0224:4-13
- power connectors, 0224:B-62, 0243:B-25
- Power Converter Unit, 0212:3-54, 0212:3-63, 0212:3-98
- Power Distribution, 0212:3-31
- power distribution panel, 0096:2-10
- Power distribution unit, 2969:3-13
- Power Down of In-Service Eagle System, 0338:3-76
- Power Relay Unit, 0096:3-16, 2712:3-13
- power requirements, 0095:2-10, 0212:6-8, 2969:2-10
- power sequencers, 0025:4-10
- power source verification, 0224:5-162
- Power Supply card
 - Embedded OAP (24.0), 0347:2-132
- power supply card
 - troubleshoot, 0338:5-7, 0338:5-18, 2970:7-4, 2970:7-17
- power up
 - EOAP, 0338:5-84, 2970:6-31
- Power Up of the Eagle System, 0338:3-80
- power up procedure, 0224:5-163
- power, checking main feeds, 0096:3-16, 2712:3-13
- PP SMS, 0348:1-12, 0348:3-20
- PPP, 0193:1-14, 0348:1-12

- PPSMS feature, 0347:5-20
- PPSMS Provisioning and Activation, 0190:4-40
- PPSMS Without G-Port MNP, 0190:2-62
- PPSMSGTA doesn't exist in GSMOPTS Table, 0177:2-464
- PPSMSGTA must be specified when NPPSMSGTA is specified, 0177:2-464
- PPSMSGTA must not be NONE, 0177:2-463
- prefix, 0193:2-2
- prefix digits, 0193:2-11
- PREFIX parameter mandatory with NDIGITS parameter, 0177:2-35
- prefix removal, 0193:2-18
- prefixed CDPN, 0193:2-18
- prefixes, point code subtype, 0145:A-12
- pre-installation requirements, 0095:2-5, 2969:2-5
- prepaid 1, 0348:2-22
- prepaid 2, 0348:2-22
- Prepaid Short Message Service, 0190:2-3
- Pre-Paid SMS Intercept - Phase 1, 0347:5-24
- Prepaid SMS Intercept Ph1 feature must be ON, 0177:2-551
- prepaid type, 0348:3-18
- preparing
 - floor for heavy duty frame, 0095:4-3, 2969:4-3
- Preventing Dust Buildups, 0338:2-40
- Preventive Cyclic Retransmission (PCR) (EAGLE 20.0)
 - Derivations for N1 and N2, 0347:5-32
 - Example of Basic Error Correction vs. PCR, 0347:5-29
 - Forced Retransmission, 0347:5-30
 - Normal Retransmission, 0347:5-28
- Preventive Maintenance, 0338:1-3
- preventive maintenance, 0096:3-2, 2712:3-2
- primary
 - DSM, 0178:2-21, 0178:4-2, 0183:4-2
 - LSMS to ELAP connection, 0178:2-10
- primary DSM, 0183:2-34, 0188:2-15, 0188:5-2, 0190:5-2, 0195:4-2
- Primary INP Functions, 0193:2-20
- Primary IP Address - FTRA 2.0, 0197:2-22
- Primary IP Address - FTRA 2.0 or greater, 0197:2-18
- Primary IP Address Field - FTRA 2.0 or greater, 0197:2-17, 0197:2-22
- Primary PC/SSN pair already exists, 0177:2-180
- Primary remote PC does not exist in routing table, 0177:2-185
- print, 0178:B-22
- Print window
 - Cancel button
 - Update Tables Log, 0197:2-97
 - Connectivity Test Log, 0197:2-36
 - Retrieve Tables Log, 0197:2-72, 0197:2-73
 - System Log, 0197:2-101
 - Update Tables Log, 0197:2-96
- Printer Inspection, 0338:2-22
- Printer Not Working, 0338:3-57
- Printer terminal type, 0142:4-55
- printers
 - configuration of, 0145:4-3

Master Index

- connection to TDM, 0145:4-5
- directing, 0145:4-15
- Printing
 - Connectivity Test Log, 0197:2-34, 0197:2-36
 - Retrieve Tables Log, 0197:2-70, 0197:2-72
 - System Log, 0197:2-99, 0197:2-101
 - Update Tables Log, 0197:2-94, 0197:2-96
- priorities, alarm, 0178:4-3, 0183:4-2
- Priority Processing of Network Management Messages (EAGLE 21.0), 0347:5-34
- private networks, 0188:2-13
- Private PC not allowed for non-IPGW linkset, 0177:2-801
- private point code, 0120:2-8, 0120:2-91, 0120:2-142, 0120:2-161, 0120:2-181, 0120:2-191, 0120:2-193, 0120:2-226, 0120:2-227, 0120:2-229, 0120:3-17, 0120:3-45, 0120:3-75, 0120:3-121, 0120:3-154, 0120:3-158, 0120:3-164, 0120:3-168, 0120:3-172, 0120:3-174, 0120:3-176, 0120:3-207, 0120:3-212
- private spare point code, 0120:3-114, 0120:3-121
- private virtual network, 0097:6-8, 0097:6-13
- probe-scsi, 0338:5-12, 2970:7-10
- Problem-Major, 0212:1-21, 2970:1-9
- Problem-Minor, 0212:1-22, 2970:1-9
- problems
 - critical, 0224:1-21, 0243:1-22, 0347:1-12
 - major, 0224:1-21, 0243:1-22, 0347:1-12
 - minor, 0224:1-22, 0243:1-23, 0347:1-13
 - power source
 - no cPCI power, 0338:5-7, 2970:7-4
 - no drive power, 0338:5-8, 2970:7-5
 - no fan power, 0338:5-7, 2970:7-4
 - processor card
 - LEDs normal but no Ethernet access, 0338:5-22, 2970:7-21
 - RUN LED is GREEN but ports not functioning, 0338:5-21, 2970:7-20
 - scsi/drive, 0338:5-9, 2970:7-6
 - drives detected but system will not boot, 0338:5-12, 2970:7-10
 - system has power but will not boot, 0338:5-9, 2970:7-6
 - serial card, 0338:5-22, 2970:7-22
 - ports 1 or 2 not working, 0338:5-24, 2970:7-24
 - ports 3,4,5, or 6 not working, 0338:5-23, 2970:7-22
 - ports 7,8,9, or 10 not working, 0338:5-24, 2970:7-23
- Problems - contacting the Customer Care Center, 0097:1-10, 0098:1-10, 0099:1-8, 0100:1-9, 0119:1-11, 0120:1-8, 0142:1-8, 0197:2-3, 0197:2-5, 0197:2-48, 0197:2-105, 0197:2-106, 0197:2-107, 0197:2-108, 0197:2-109, 0197:2-110, 0197:2-111, 0197:2-112, 0197:2-113, 0197:2-114, 0197:2-115, 0197:2-116, 0197:2-117, 0197:2-118, 0197:2-119, 0197:2-120, 0197:2-121, 0288:1-9
- problems, detecting and reporting, 0096:3-11, 2712:3-8
- Problem Solution, 0212:5-8
- problem Solution, 0212:5-8
- Procedure
 - Activating Controlled Features, 0197:2-3
 - Activating the Eagle OA&M IP Security Enhancements Controlled Feature, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
 - Activating the LNP Feature on the EAGLE 5 SAS, 0288:2-123
 - Activating the LNP Short Message Service (SMS) Feature, 0288:3-79
 - Adding a DSM, 0288:2-17
 - Bulk Load, 0288:2-92

Configuring ELAP, 0288:2-58
 Configuring ELAP 5.0, 0288:2-56
 Configuring the DSM Ethernet Link to the MPS, 0288:2-28
 Connectivity Test - I, 0197:2-122
 Connectivity Test - II, 0197:2-123
 Copy an RTDB from the Mate ELAP, 0288:2-108
 Copy RTDB from Remote Mated NE, 0288:2-115
 Creating an EMS Configuration Component, 0288:2-76
 Deleting an EMS Configuration Component, 0288:2-86
 Disabling Bulk Load, 0288:2-139
 Distributing an RTDB LNP Database to DSMs, 0288:2-135
 Distributing the LNP Database after LSMS-Based Operation or RTDB Copy, 0288:2-134
 ELAP 5.0 Configuration, 0288:2-45
 ELAP Configuration, 0288:2-56
 FTP Server Verification, 0197:2-122
 Increasing the LRN and NPANXX Quantities on the Eagle, 0288:3-75
 Modify EMS Routing, 0288:2-88
 Modifying an EMS Configuration Component, 0288:2-82
 MPS Health Check, 0288:2-74
 SFTP Server Verification, 0197:2-122
 SSHD Server Verification, 0197:2-122
 View EMS Routing, 0288:2-91
 Viewing an EMS Configuration Component, 0288:2-84
 procedure
 breaker panel alarm card replacement, 0096:5-2
 breaker panel replacement, 0096:5-5, 2712:5-5
 Configuring the EOAP from the System Terminal, 2970:4-11
 disk drive replacement, 0096:5-11, 2712:5-9
 hub replacement, 0096:5-7, 2712:5-6
 MPS Server Power Down, 0096:5-8, 2712:5-7
 Tekelec 1000 AS main unit replacement, 0096:5-11
 Tekelec 1100 AS main unit replacement, 2712:5-10
 procedures
 Extracting LNP Measurements from the FTA, 0145:5-8
 log into system, 0145:4-19
 logout, 0145:4-23
 procedures, login
 change password at first login, 0145:4-20
 password expired, 0145:4-21
 User ID-password already being used, 0145:4-22
 User ID-password not accepted, 0145:4-20
 process architecture view, 0183:3-3
 Process Control menu, 0178:3-14, 0183:3-14, 0183:3-55
 Processing Retrieve Request
 Update Tables Log window, 0197:2-84
 Processing Validate Request, Please Wait message, 0197:2-84, 0197:2-90
 processor card, 0338:5-22, 2970:7-21
 troubleshoot, 0338:5-7, 0338:5-20, 2970:7-4, 2970:7-19
 Processor speed, 0197:2-2
 Processor timeout error, 0177:2-662
 processor, MPS Server CPU, 0212:4-27
 Product Description, 0188:2-2

Master Index

- product description
 - ITU MTP Restart (26.0), 0347:3-158
- Production Control, 0224:1-20, 0224:3-4, 0243:1-21
- Program Update Unsolicited Output Message Group, 0338:D-26
- Prohibit Removing the Last Route to a Destination if that Destination is being Referenced by Mated Applications or Concerned Signaling Point Code Groups (EAGLE 22.0), 0347:5-37
- Prohibit the Assigning of a Linkset with Linkset Types A or E to a Cluster Route (EAGLE 22.0), 0347:5-38
- prompts
 - default value format, 0178:5-11, 0183:5-13
 - ELAP user interface menus, 0178:5-11
 - EPAP user interface menus, 0183:5-13
 - Escape key to exit operations, 0178:5-11, 0183:5-13
- Prompts and Default Values, 0178:5-11
- protocol details
 - Enhanced GTT (26.0), 0347:2-155
- Protocol Troubleshooting, 0197:2-125
- Protocol wrong type for socket - Error code 41, 0197:2-119
- Protocol, Point-to-Point (PPP), 0178:2-9, 0183:2-10
- provide redundancy, 0190:2-38
- Provides discrimination of messages that need its functionality, 0188:2-28
- provision DSM cards, 0193:2-5, 0195:2-10
- provision EIR data, 0195:2-10
- provision INP data, 0193:2-5
- provision new selectors for G-Flex, 0188:3-5
- provisioned prefix, 0193:2-11
- provisioning
 - ELAP Able / Unable status, 0178:2-10
 - ELAP-to-DSM description, 0178:2-17
 - LNP, 0178:2-10
 - LSMS-ELAP connection, 0178:2-5, 0178:2-10
 - NPAC and local data collection at LSMS, 0178:2-11
- Provisioning a Mated Application, 0099:2-78
- Provisioning an MRN Group, 0099:2-137
- Provisioning Database, 0188:2-7, 0188:2-21, 0193:2-4, 0195:2-9
- Provisioning database, 0190:2-33
- Provisioning Database Application, 0193:2-5, 0195:2-11
- Provisioning Database Interface, 0188:2-6, 0188:2-28, 0190:2-32, 0190:2-40
- provisioning DSM cards, 0190:2-35
- Provisioning Hierarchy, 0188:3-3, 0190:3-3
- Provisioning Hierarchy for G-Port Database, 0190:3-2
- Provisioning Hierarchy for the G-Flex Database, 0188:3-2
- Provisioning INP Number Normalization, 0193:2-18
- Provisioning INPQ Service NAI, 0193:2-19
- provisioning link congestion, 0188:5-2, 0190:5-2, 0193:5-3, 0195:4-2
- Provisioning Multiple Point Codes
 - Multiple Point Code Support (EAGLE 26.05), 0347:4-150
- Provisioning of Routing Number Prefix of Node (HOMERN), 0193:2-18
- Provisioning Range for Gateway Screening (EAGLE 22.0), 0347:5-38
- provisioning system, 0193:2-16
- provisioning terminal, 0190:2-35
- Provisioning the Secure EAGLE 5 SAS Host Key, 0197:2-45

provisioning traffic situations, 0190:5-2, 0195:4-2
 provisioning values, 0178:5-26, 0183:5-34
 provisioning, DSM
 description, 0183:2-27
 model, 0183:2-29
 task overview, 0183:2-8
 Provlk, 0193:1-14
 ps, 0197:2-122
 ps -ef|grep sshd, 0197:2-105
 ps -f|grep sshd, 0197:2-122
 PSEL parameter requires LNP feature, 0177:2-607
 PST/AST/SST possible values, 0145:A-3
 PSTN is not defined, 0177:2-344
 PSTN presentation data, 0100:3-4
 PSTNCAT=0 requires PSTNID=0, 0177:2-713
 PSTNCAT=1 requires ITU-I or ITU-N point code, 0177:2-714
 PT, 0348:1-12
 pt, 0348:3-18, 0348:3-20, 0348:3-24, 0348:3-26, 0348:3-31
 pt parameter, 0348:3-18, 0348:3-20
 Public Host Key Fingerprint
 EAGLE 5 SAS, 0197:2-45, 0197:2-46, 0197:2-48, 0197:2-50
 Public Key Fingerprint
 EAGLE 5 SAS, 0197:2-19, 0197:2-48, 0197:2-49
 Public Land Mobile Network, 0190:2-45
 publications, Sentinel, 0212:1-17, 0243:1-18
 PuTTY client program, 0142:1-2, 0142:B-1, 0142:B-2
 PuTTY Configuration Window, 0142:B-2, 0142:B-3, 0142:B-5, 0142:B-6, 0142:B-7
 PVC, 0097:2-4, 0347:5-179
 PVC plus SVC cannot be greater than 255, 0177:2-298
 PVC plus SVC must be at least 1, 0177:2-298
 PVN, 0097:6-8, 0097:6-13, 0097:6-14, 0097:6-15
 PVN and PVNMASK must be specified together, 0177:2-703
 PVN and PVNMASK must not be the same, 0177:2-703
 PVN subnet mask, 0097:6-14, 0097:6-15
 PWR A LED, 0338:2-7
 PWR B LED, 0338:2-7

Q

QH and HH cannot be specified together, 0177:2-601
 QH cannot be specified unless 15 min meas is turned on, 0177:2-600
 QH or HH is not valid for this TYPE, 0177:2-123
 QH or HH must be specified when PERIOD=SPECIFIC, 0177:2-114
 QH, HH, or DAY cannot be specified when PERIOD=ACTIVE, 0177:2-113
 QH, HH, or DAY cannot be specified when PERIOD=ALL, 0177:2-114
 QH, HH, or DAY cannot be specified when PERIOD=LAST, 0177:2-113
 QR, 0288:4-13, 0288:4-14, 0288:4-15, 0288:4-16, 0288:4-18, 0288:4-19
 QS, 0193:1-14
 Quad FastEthernet card, 0212:4-35
 Quad FastEthernet Network Interface card
 description, 0212:4-31
 Quantity control feature capacity exceeded, 0177:2-344

Master Index

Quarterly Procedures, 0338:2-38
query/response, 0348:2-4
Quick Test
 CDU for DSM (26.05), 0347:2-62
Quoted string too long (C<col>), 0177:2-506

R

Rack Alarm (RALMx), 0212:3-26
rack alarm and row alarm cable routing, 0224:5-11
rack alarm cable installation, 0224:5-87
rack alarm connectors, 0224:B-64
rack and row alarm connector, 0212:3-26
rack horns, 0224:4-17
rack, overhead, 0095:4-19, 2969:4-19
Radio Frequency Interference (RFI), 0212:3-31
RAID, 0193:1-14
Raised Floor, 0224:3-14
Raised floor, 0224:3-24
raised floor, 0224:3-16
 additional preparations, 0095:4-5, 2969:4-5
 anchor assembly
 for anchoring to slab, 0095:4-10, 2969:4-10
 for use with support channel, 0095:4-14, 2969:4-14
 anchor assembly for use with support channel and spring nut, 0095:4-17, 2969:4-17
 anchor with support channel, 0095:4-13, 2969:4-13
 anchor with support channel and spring nut, 0095:4-16, 2969:4-16
 create cable and anchor holes, 0095:4-5, 2969:4-5
RAM, 0197:2-2
ramp, 0224:3-5
Random SLS Generation, 0347:5-45
Random SLS Generation (Release 28.0), 0347:5-45
RC Already Equipped, 0177:2-754
RC is required if no other optional parameters are provided, 0177:2-423
RCVRY-E1F
 FAC-E1 available, 0338:3-499
RCVRY-LINK-CGST
 congestion has cleared, 0338:3-343
 congestion level 2 to 1, 0338:3-342
 congestion level 3 to 2, 0338:3-341
 discard has cleared, 0338:3-349
 discard level 2 to 1, 0338:3-348
 discard level 3 to 2, 0338:3-347
RCVRY-LKF
 link available, 0338:3-292
RCVRY-LKSTO
 Alarm clr'd by deleting SLK, 0338:3-512
 Link set allowed, 0338:3-400
RCVRY-MTPLP-RST
 Circ rte status cleared, 0338:3-428
RCVRY-MTP-RSTRT MTP Restart completed, 0338:3-723
RDCT must be in lowest priority action slot, 0177:2-594

Read NETOPTS table failed, 0177:2-706
 read transaction
 abort, 0348:3-14
 begin, 0348:3-11
 end, 0348:3-13
 Read-only file system - Error code 30, 0197:2-121
 Real time clock battery low, 0338:3-129
 Real time clock battery restored, 0338:3-130
 RealTime Database, 0193:2-4, 0195:2-9
 Realtime Database, 0188:2-7
 real-time database, 0193:2-5, 0195:2-11
 Real-Time Memory Validation, 0188:2-24, 0190:2-50
 Real-time Memory Validation, 0193:5-5
 rear covers, 0224:3-26, 0224:3-37
 rear view
 hub, 0212:4-48
 MPS frame layout, 0212:4-13
 MPS Server, 0212:4-26
 MPS Server detail, 0212:4-22, 0212:4-30
 Reboot MPS menu, 0178:3-77, 0178:5-23, 0183:3-48, 0183:5-26
 Received wrong display mode, 0177:2-161
 Receiving, 0224:3-4
 Receiving INP Data from a National Database, 0193:2-16
 reception of an RCx message
 network routing, 0120:2-180
 reception of an RSx message
 network routing, 0120:2-179
 reception of transfer messages
 network routing, 0120:2-179
 recipient network, 0190:2-45
 Recommended Tools, 0224:3-11, 0224:3-14, 0224:5-7, 0224:5-21, 0224:5-85, 0224:5-108, 0224:5-121
 recommended tools
 installing heavy duty frame, 0095:4-3, 2969:4-3
 Recommended Tools and Materials, 0224:4-14
 reconcile
 stages, 2339:5-11, 2339:5-12
 reconnect cables to EOAP shelf, 0338:5-77, 2970:6-24
 Record Base Measurements, 0338:4-118
 Record, STP configuration, 0197:2-16
 RECOVERED is allowed only in channel bridging mode, 0177:2-545
 recovery of system, 0183:3-47
 recovery, overview, 0096:3-19, 2712:3-18
 Rectifier Voltage Inspection / Recording, 0338:2-41
 RECVY-NMTSK-DSCD
 SNM Discard Abated, 0338:3-386
 red and white flag, 0224:4-24
 REDIRECT can only be specified with ANSI point codes, 0177:2-312
 Redirect function data has already been entered, 0177:2-276
 Redirect function data has not been entered, 0177:2-276
 redundancy, 0190:2-38
 re-entering init-sys command, 0188:4-4, 0188:4-12, 0190:4-5, 0190:4-13, 0193:4-5, 0193:4-13
 references

Master Index

- document, 2970:1-17
- Refresh button, 0197:2-18, 0197:2-25, 0197:2-27, 0197:2-29, 0197:2-31, 0197:2-41
- regulatory compliance, 0095:2-4, 2969:2-4
- regulatory obligations, 0190:1-1, 0190:2-2
- reinitialize system, 0188:4-12, 0190:4-13, 0193:4-13
- Rejection threshold argument - not valid (C<col>), 0177:2-502
- Related Publications, 0188:1-2, 0190:1-2, 0193:1-2, 0195:1-2, 0212:1-12
- related publications, 0145:1-3
- Relative Cost (RC) is required for PC / SSN and MPC / MSSN, 0177:2-427
- Relative Cost (RC) of true MPC must be less than RC of mate, 0177:2-428
- Relative Cost (RC) of true PC must be less than RC of mate, 0177:2-428
- relative humidity, 0095:2-6, 2969:2-6
- release 30.2 or greater - EAGLE 5 SAS, 0197:2-3, 0197:2-19, 0197:2-24
- Release Not Compatible Error - Retrieve Tables Log window, 0197:2-59
- Release Notice, 0212:1-18, 0243:1-18
- Reliable Multicast Transport Protocol, 0193:2-9
- Reliable Multicast Transport Protocol-II, 0188:2-12, 0190:2-37
- reload
 - DSM, 0178:2-17, 0183:2-29
 - DSM continuous, 0178:2-18, 0183:2-30
 - DSM database levels, 0183:2-30
- reload multiple DSMs, 0190:2-38
- Reload RTDB from PDBA, 0183:3-27
- Reload RTDB from Remote, 0178:3-37, 0183:3-28
- reload traffic, 0188:2-27
- reloading multiple DSMs, 0188:2-26
- remote access, 0025:6-7, 0096:2-13, 0190:2-35, 2712:2-11
- remote application not found, 0177:2-438
- remote congestion
 - network routing, 0120:2-177
- remote dial-in port, 0178:2-9
- remote ELAP, 0178:5-27, 0288:2-57
- remote EPAP, 0183:5-35
- remote EPAP / PDBA user interface terminal, 0188:2-16
- remote link congestion
 - ANSI/ITU MTP Gateway (20.0), 0347:2-39
- remote loopback points
 - adding, 0120:3-241, 0120:3-247
 - changing, 0120:3-250
- Remote Loopback Testing for DSOA
 - Link Fault Sectionalization (21.0), 0347:4-13
- Remote Loopback Testing for DSOA (EAGLE 21.0), 0347:5-45
- Remote Loopback Testing for OCU
 - Link Fault Sectionalization (21.0), 0347:4-14
- Remote Loopback Testing for OCU (EAGLE 21.0), 0347:5-46
- Remote Maintenance Center (RMC) - Appendix B, page B-3, 0224:5-87
- remote maintenance center (RMC) alarm connector, 0212:3-26
- remote maintenance center cable installation, 0224:5-87
- Remote point code does not exist in MAP table, 0177:2-185
- Remote point code table is full, 0177:2-186
- removable cartridge, 0142:2-5
 - formatting, 0142:2-79

- inserting, 0142:2-8
- overview, 0100:1-13, 0120:1-13, 0142:1-13
- removing, 0142:2-9
- restoring system data, 0142:2-73
- write enabling, 0142:2-7
- write protecting, 0142:2-6
- Removable cartridge contains Eagle data (use FORCE=YES), 0177:2-57
- Removable cartridge database level is not compatible, 0177:2-613
- removable cartridge disk drives, 0145:4-2
- Removable cartridge is inaccessible (internal problem), 0177:2-416
- Removable cartridge is not a MEAS disk, 0177:2-416
- Removable cartridge is not a system disk, 0177:2-415
- Removable cartridge is not inserted, 0177:2-415
- Removable cartridge not inserted, 0177:2-58
- Removable in unknown upgrade mode, 0177:2-524
- Removable is from previously aborted upgrade, 0177:2-525
- Removable media drives assembly, 2969:7-4
- removal of prefix, 0193:2-18
- removal of RN prefixes, 0193:2-18
- remove
 - cables from EOAP shelf, 0338:5-67, 2970:6-14
 - cards from EOAP shelf, 0338:5-70, 2970:6-17
 - EOAP card cage, 0338:5-71, 2970:6-18
 - fan assembly, 0338:5-93, 0338:A-83, 2970:6-42
 - grill and filter, 2970:3-14
- Remove Authorized PDBA Client IP, 0183:3-90
- Remove button, 0197:2-58, 0197:2-64
- Remove External NTP Server, 0178:5-25, 0183:5-29
- Remove Fan Assembly, 0338:A-83
- Removing
 - BLM Applied to LSMS BLM-Based Operations, 0288:2-26
 - DCM Applied to LSMS BLM-Based Operations, 0288:2-23
 - SCCP Card, 0288:2-21
- removing
 - destination point code, 0120:2-214
 - IPSM, 0142:4-164
 - linkset containing SS7 signaling links, 0120:3-63
 - MCPM, 0142:4-132
 - removable cartridge, 0142:2-9
 - route, 0120:3-189
 - shelf, 0142:4-92
 - signaling link, 0100:3-105, 0120:3-145
 - SS7 LIM, 0097:6-27, 0142:4-105
 - user, 0142:4-33
- Removing a Blocked DPC Screen, 0098:8-21, 0119:5-49
- Removing a Blocked OPC Screen, 0098:11-22, 0119:5-100
- Removing a Destination Point Code, 0119:2-21
- Removing a Gateway Linkset, 0119:5-136
- Removing a Global Title Translation, 0099:3-43, 0119:4-15
- Removing a GLS Card, 0098:2-50
- Removing a GSM MAP Screening Entry, 0097:5-115, 0097:5-123, 0097:5-124
- Removing a GSM MAP Screening Operation Code, 0097:5-78, 0097:5-81

Master Index

Removing a GSM Subsystem Number Screening Entry, 0097:5-62, 0097:5-63
Removing a GTT Selector, 0099:4-17
Removing a GTT Set, 0099:4-8
Removing a Linkset Containing SS7 Signaling Links, 0119:3-11
Removing a Linkset Containing X.25 Signaling Links, 0097:2-54
Removing a Mapped SS7 Message Translation Type, 0099:2-64
Removing a Mated Application, 0099:2-108, 0119:4-5, 0119:6-5
Removing a Screen Set, 0098:13-12
Removing a TCP/IP Data Link, 0097:3-39
Removing a TCP/IP Node, 0097:3-47
Removing a Translation Type, 0099:3-12
Removing ACG Manual Initiated Controls, 0288:4-25
Removing an ACG Node Overload Control Level, 0288:4-16
Removing an ACM, 0097:3-28
Removing an Allowed Affected Point Code Screen, 0098:3-14, 0119:5-5
Removing an Allowed Called Party Address, 0098:4-17
Removing an Allowed Called Party Address Screen, 0119:5-11
Removing an Allowed Calling Party Address Screen, 0098:6-18, 0119:5-27
Removing an Allowed DPC Screen, 0098:9-22, 0119:5-66
Removing an Allowed ISUP Message Type Screen, 0098:15-16
Removing an Allowed OPC Screen, 0098:12-22, 0119:5-116
Removing an Allowed SIO Screen, 0098:10-20, 0119:5-84
Removing an Allowed Translation Type Screen, 0098:5-11, 0119:5-20
Removing an Application Socket, 0100:3-187
Removing an ASM-SCCP Card, 0195:5-10
Removing an DCM, 0100:3-26, 0100:3-166
Removing an IP Card, 0100:3-26, 0100:3-166
Removing an MRN Group or MRN Group Entry, 0099:2-149
Removing an SCCP Card, 0099:2-58
Removing an SS7 Signaling Link, 0119:3-33
Removing an X.25 Gateway Destination, 0097:2-31
Removing an X.25 LIM, 0097:2-18
Removing an X.25 Route, 0097:2-113
Removing an X.25 Signaling Link, 0097:2-91
Removing Concerned Signaling Point Codes, 0099:2-75
removing diode boards, 0338:2-9
Removing Global Title Address Information, 0099:4-49, 0119:6-14
Removing the 2.3 Gbyte Removable Cartridge, 0338:2-14
REP cannot be specified when DUR=PERM, 0177:2-302
REP is only valid if LFST is defined as LLT, 0177:2-389
REP must be greater than prev. and less than subsequent REP, 0177:2-387
REP must be zero if link element to be tested is NEI, 0177:2-388
rep parameter, 0188:3-2
REP parameter must be specified, 0177:2-396
Repair and Return Shipping Instructions, 0212:1-27, 0224:1-26, 0243:1-27, 2970:1-14
repairing database, 0142:2-48
repetition parameter, 0188:3-2
replace
 air filter, 0095:7-18, 2969:7-18
 Ethernet switch, 0095:7-4, 2969:7-7
 fan assembly, 0095:7-20, 0338:5-92, 0338:A-82, 2969:7-20, 2969:7-22, 2970:6-41
 fan filter and grill, 0338:5-97, 0338:A-88, 2970:6-46

- hard disk drive, 0095:7-23, 2969:7-24
- hard drive card, 0338:5-102, 0338:5-103, 2970:6-51, 2970:6-52
- PCI card, 0095:7-37, 2969:7-39
- power supply card, 0338:5-115, 2970:6-66
- processor card, 0338:5-121, 2970:6-73
- Replace tiles, 0224:3-15
- replace TSM card with DSM card, 0188:4-21, 0188:4-29, 0190:4-20, 0190:4-21, 0190:4-29, 0193:4-21, 0193:4-29
- replacement
 - breaker panel, 0096:5-5, 2712:5-5
 - breaker panel alarm card, 0096:5-2
 - disk drive, 0096:5-11, 2712:5-9
 - hub, 0096:5-7, 2712:5-6
 - Tekelec 1000 AS main unit, 0096:5-11
 - Tekelec 1100 AS main unit, 2712:5-10
- Replacement cables list, 0338:A-97
- Replacement of GT with entity address, 0188:2-29
- Replacement parts list, 0338:A-93
- replacing
 - serial I/O card (EOAP), 0338:5-130, 2970:6-85
 - two STP pairs with one pair, 0120:2-56
- replacing FAP components, 0338:2-6
- Replacing Two STP Pairs with One Eagle Pair
 - Multiple Point Code Support (EAGLE 26.05), 0347:4-144
- REPLERR, 0183:3-9
- replicated database, 0348:2-7
- Replication, 0348:3-51
- replication, 0348:2-7, 0348:3-48
- report DSM failure, 0188:5-12
- Report generation failure, 0338:3-903
- Report Parameters, 0338:4-12
- Report parameters, 0338:4-12
- Report transfer failure FTP Server, 0338:3-904
- reporting
 - DSM memory capacity status, 0178:4-7, 0183:4-9
 - DSM system status, 0183:4-8
 - DSM/ ELAP IP link alarm totals, 0178:4-13
 - DSM/ ELAP link alarms, 0178:4-12
 - G-Flex status, 0183:4-9
 - G-Port status, 0183:4-9
 - INP status, 0183:4-9
 - loading mode support status, 0183:4-9
 - provisioning system status, 0183:4-8
 - RTDB level and status, 0178:4-9, 0183:4-11
- Reporting Functions, 0025:4-7
- Reports, 0338:4-13
- reports, DSM troubleshooting, 0183:4-14
- REPT COND
 - IMT GPL reloading, 0338:3-743
 - system alive, 0338:3-715
- REPT EVT
 - IMT GPL reloading, 0338:3-742

Master Index

Incremental Loading, 0338:3-954
REPT-ALMINH
 alarm output enabled, 0338:3-371
 alarm output PERM inhibited, 0338:3-370
 alarm output TEMP inhibited, 0338:3-372
REPT-E1F
 FAC-E1 10E-3 BER failed, 0338:3-498
 FAC-E1 AIS detected, 0338:3-496
 FAC-E1 Far End failure, 0338:3-497
 FAC-E1 LOF failure, 0338:3-495
 FAC-E1 LOS failure, 0338:3-494
rept-ftp-meas, 0145:7-2, 0195:3-17
rept-imt-info, 0145:7-6
rept-imt-lvl1, 0145:7-27
rept-imt-lvl2, 0145:7-39
REPT-LFK
 LM Timer NO-CREDIT expired, 0338:3-325
REPT-LINK-CGST
 congestion level 0 to 1, 0338:3-338
 congestion level 1 to 2, 0338:3-339
 congestion level 2 to 3, 0338:3-340
 discard level 0 to 1, 0338:3-344
 discard level 1 to 2, 0338:3-345
 discard level 2 to 3, 0338:3-346
REPT-LINK-MANUAV
 local blocked, 0338:3-320
REPT-LKF
 ABN - rcvd 2 of 3 invalid BSN, 0338:3-306
 ABN - rcvd 2 of 3 invalid FIB, 0338:3-307
 APF - failed proving period, 0338:3-301
 APF - lvl-2 T1 expd (not ready), 0338:3-298
 APF - lvl-2 T1 expd (ready), 0338:3-297
 APF - lvl-2 T2 expired, 0338:3-300
 APF - lvl-2 T3 expired, 0338:3-299
 COO - rcvd changeover order, 0338:3-310
 FAC - DS1 LCD failure, 0338:3-334
 FAC - DS1 LOF failure, 0338:3-333
 false congestion restart, 0338:3-311
 HWP -too many link interrupts, 0338:3-294
 link test failed, 0338:3-317
 lost data, 0338:3-295
 MTP link restart delayed, 0338:3-312
 not aligned, 0338:3-323
 OSA - received SIE, 0338:3-304
 OSA - received SIN, 0338:3-303
 OSA - received SIO, 0338:3-302
 OSA - received SIOS, 0338:3-305
 rcvd SSCOP END-mgmnt initiated, 0338:3-331
 rcvd SSCOP END-out of service, 0338:3-329
 rcvd SSCOP END-protocol error, 0338:3-330
 remote blocked, 0338:3-318, 0338:3-319
 remote congestion timeout, 0338:3-308

- remote FE loopback, 0338:3-315
- remote NE loopback, 0338:3-293, 0338:3-316
- RMI remote inhibited, 0338:3-321
- X25 link unavailable, 0338:3-313
- XDA - excess acknowledge delay, 0338:3-309
- XDA-Timer NO-RESPONSE expired, 0338:3-326, 0338:3-333, 0338:3-334
- XER - ISERM threshold exceeded, 0338:3-335
- XER - SUERM threshold exceeded, 0338:3-296
- REPT-LKSTO
 - Link set prohibited, 0338:3-401
- rept-meas, 0145:7-43, 0188:3-11, 0190:3-13, 0193:3-7
- REPT-MTPERR
 - MTP rcvd invalid SIO, 0338:3-639
- REPT-MTPLP-DET
 - Circ rte det(cong), 0338:3-403
- REPT-MTPLP-SUST
 - Sustained circ rte(cong), 0338:3-405
- REPT-MTP-RSTRT MTP Restart started, 0338:3-722
- REPT-NMTSK-DSCD
 - SNM Discard Onset, 0338:3-385
- REPT-OVSZMSG
 - MTP MSU too large to route, 0338:3-818
 - SCCP MSU too large to rte, 0338:3-819
- rept-stat-alm, 0145:7-57, 0188:3-11, 0190:3-15, 0193:3-8, 0195:3-13
- rept-stat-alm command, 0178:4-4, 0178:4-13, 0183:4-3, 0183:4-13
- rept-stat-applsock, 0145:7-63
- rept-stat-as, 0145:7-64
- rept-stat-asp, 0145:7-66
- rept-stat-assoc, 0145:7-67
- rept-stat-card, 0145:7-69, 0188:4-5, 0188:4-6, 0188:4-7, 0188:4-8, 0188:4-19, 0188:4-25, 0188:4-28, 0188:4-34, 0188:4-39, 0190:4-5, 0190:4-6, 0190:4-7, 0190:4-8, 0190:4-19, 0190:4-25, 0190:4-28, 0190:4-34, 0190:4-39, 0193:4-5, 0193:4-6, 0193:4-7, 0193:4-9, 0193:4-19, 0193:4-25, 0193:4-28, 0193:4-34, 0193:4-44, stat=nr, 0188:4-27, 0190:4-27, 0193:4-27
- rept-stat-card command, 0347:3-30
- rept-stat-cdl, 0145:7-92
- rept-stat-cdt, 0145:7-93
- rept-stat-clk, 0145:7-94
- REPT-STAT-CLK Enhancements for Clocking (Release 28.2), 0347:5-47
- rept-stat-cluster, 0145:7-99
- rept-stat-db, 0145:7-106, 0188:3-11, 0190:3-15, 0193:3-9, 0195:3-14
- rept-stat-db command, 0178:4-9, 0183:4-11
- rept-stat-dlk, 0145:7-123
- rept-stat-dstn, 0145:7-124
- rept-stat-epap, 0188:2-25, 0188:3-10, 0188:5-2, 0188:5-4, 0190:2-51, 0190:3-12, 0190:5-2, 0190:5-4, 0190:5-12, 0193:3-5, 0193:5-2, 0193:5-7, 0195:3-12, 0195:4-2, 0195:4-4
- rept-stat-epap command
 - description, 0183:4-11
 - DSM memory capacity status reporting, 0183:4-9
- rept-stat-eroute, 0145:7-133, 0145:7-136, 0145:7-232
- rept-stat-gpl, 0145:7-141, 0188:3-12, 0190:3-16, 0193:3-10, 0195:3-16
- rept-stat-imt, 0145:7-151
- rept-stat-iptps, 0145:7-153

Master Index

- rept-stat-lfs, 0145:7-157
- rept-stat-lnp, 0145:7-159
- rept-stat-ls, 0145:7-165
- rept-stat-lsms, 0145:7-168
- rept-stat-meas, 0142:2-57, 0142:2-63, 0142:2-82, 0142:2-85, 0142:2-93, 0142:2-97, 0142:3-50, 0142:3-69,
0142:4-137, 0142:4-139, 0145:7-169
- rept-stat-mps, 0145:7-171
- rept-stat-mps command
 - description, 0178:4-10
 - DSM memory capacity status reporting, 0178:4-7
 - list alarm categories and data strings, 0178:4-11
 - list multiple alarm conditions, 0178:4-4, 0183:4-3
- rept-stat-mux, 0145:7-183
- rept-stat-ndc, 0145:7-184
- rept-stat-ndc command, 0347:3-29
- rept-stat-rte, 0119:3-36, 0145:7-185
- rept-stat-rtkey, 0145:7-194
- rept-stat-sccp, 0145:7-195, 0188:3-9, 0188:5-2, 0188:5-4, 0190:3-11, 0190:5-2, 0190:5-4, 0193:3-4,
0193:4-43, 0193:5-2, 0193:5-6, 0193:5-7, 0195:3-11, 0195:4-2, 0195:4-4
- rept-stat-sccp command, 2339:8-5
 - description, 0183:4-9
 - G-Flex / G-Port / INP status reporting, 0183:4-9
 - system status reporting, 0183:4-8
- rept-stat-seas, 0145:7-212, 2970:6-12, 2970:6-32, 2970:6-52, 2970:6-73, 2970:6-75
- rept-stat-seculog, 0145:7-213
- rept-stat-slan, 0145:7-216
- rept-stat-slk, 0119:3-33, 0145:7-219, 0188:4-5, 0188:4-20, 0190:4-6, 0190:4-20, 0193:4-6, 0193:4-20
- rept-stat-sys, 0145:7-228, 0188:3-9, 0188:5-4, 0188:5-5, 0190:3-11, 0190:5-4, 0190:5-5, 0190:5-7, 0193:3-4,
0193:5-6, 0193:5-7, 0193:5-10, 0195:3-10, 0195:4-4, 0195:4-7
- rept-stat-sys command
 - description, 0183:4-9
 - loading mode support status reporting, 0183:4-9
- rept-stat-trbl, 0145:7-235, 0188:3-11, 0190:3-14, 0193:3-7, 0195:3-13
- rept-stat-trbl command, 0178:4-4, 0178:4-12, 0183:4-3, 0183:4-13
- REPT-STAT-TRBL Enhancement (Release 29.0), 0347:5-48
- rept-stat-trm, 0145:7-239
- rept-stat-trstslk, 0145:7-241
- rept-stat-user, 0145:7-243
- rept-stat-xlist, 0145:7-244
- REPT-T1F
 - FAC-T1 Alarm, 0338:3-482, 0338:3-492, 0338:3-500
 - FAC-T1 available, 0338:3-493
 - FAC-T1 LOF failure, 0338:3-490
 - FAC-T1 LOS failure, 0338:3-489
 - FAC-T1 Remote Alarm, 0338:3-491
- rept-x25-meas, 0145:7-245
- REPT-XLST-TIMO
 - X-LIST entry expired, 0338:3-792
- request ID (iid), 0348:3-3
- request message
 - Abort Transaction, 0348:3-15
 - Begin Transaction, 0348:3-11

- Connect, 0348:3-8
- Create Network Entity, 0348:3-36
- Create Subscription
 - one IMSI and one to eight DNs, 0348:3-16
 - one or more DNs on same NE with no IMSI, 0348:3-17
 - porting a block of DNs, 0348:3-20
 - single IMSI with no DN, 0348:3-15
- Delete Network Entity, 0348:3-44
- Delete Subscription
 - delete DN block, 0348:3-29
 - delete IMSI, 0348:3-28
 - delete single DN, 0348:3-28
- Disconnect, 0348:3-10
- Dump Connections, 0348:3-53
- End Transaction, 0348:3-13
- integer identification (iid), 0348:3-3
- optional parameter format, 0348:3-3
- PDBA Status Query, 0348:3-51
- Retrieve Network Entity
 - for all NEs, 0348:3-47
 - for NE range, 0348:3-46
 - for specific IMSI, 0348:3-46
- Retrieve Subscription Data
 - retrieve data for DN range, 0348:3-31
 - retrieve data for IMSI range, 0348:3-34
 - retrieve data for specific DN, 0348:3-30
 - retrieve data for specific IMSI, 0348:3-33
- Switchover, 0348:3-50
- Update Network Entity, 0348:3-40
- Update Subscription
 - modify data of single DN, 0348:3-23
 - modify information for DN block, 0348:3-25
 - modify SP for specific IMSI, 0348:3-23
 - move existing DN to existing IMSI, 0348:3-25
- Request To Send (RTS), 0212:3-67
- Requested link must not be in command driven loopback, 0177:2-789
- Required Network Address Information, 0178:5-9, 0288:2-41
- Requirements
 - ATM or E1 LIM card(s), 0224:5-83
 - backplane (P / N 850-0330-04), 0224:5-83
 - backplane (P / N 850-0330-05), 0224:5-83
 - Feature Matrix, 0224:5-83
 - Hardware, 0197:2-2
 - Unix Workstation, 0197:2-2
 - Windows Workstation, 0197:2-2
 - Software, 0197:2-2
 - Unix Workstation, 0197:2-2
 - Windows Workstation, 0197:2-2
 - software release 26.0 or later, 0224:5-83
 - T1 or E1 clock source (RS 422), 0224:5-83
 - TDM card 870-0774-06 or 870-0774-08 or later, 0224:5-83
- requirements

Master Index

- pre-installation, 0095:2-5, 2969:2-5
- Requires C-linksets parameter tfatcabmlq to be set to 0, 0177:2-820
- rerouting global title translation traffic to mate, 2339:8-4
- reserve a subsystem number, 0193:4-39
- Reset button, 0197:2-58, 0197:2-65
- Reset User Password, 0178:3-95, 0183:3-125
- RESETCHAR not valid with ACTION=CREATE, 0177:2-310
- RESETCHAR not valid with ACTION=RENAME, 0177:2-311
- Response, 0212:1-23, 2970:1-10
- response message
 - Abort Transaction, 0348:3-15
 - Bad Arguments, 0348:3-6
 - Begin Transaction, 0348:3-13
 - common format, 0348:3-3
 - common responses, 0348:3-5
 - Connect, 0348:3-10
 - Create Network Entity, 0348:3-39
 - Create Subscription, 0348:3-15, 0348:3-22, 0348:3-57, 0348:3-60, 0348:3-64
 - data element format, 0348:3-3
 - Delete Network Entity, 0348:3-45
 - Delete Subscription, 0348:3-29
 - Disconnect, 0348:3-11
 - Dump Connections, 0348:3-53
 - End Transaction, 0348:3-14
 - integer identification (iid), 0348:3-3
 - Parse Failed, 0348:3-5
 - PDBA Status Query, 0348:3-52, 0348:3-68, 0348:3-71
 - Retrieve Network Entity, 0348:3-47
 - Retrieve Subscription Data, 0348:3-34, 0348:3-66
 - Switchover, 0348:3-50
 - Update Network Entity, 0348:3-44
 - Update Subscription, 0348:3-27
- Response Messages, 0145:4-15
- response method transfer messages
 - network routing, 0120:2-177
- Response to Commands Issued Prior to Login (EAGLE 21.0), 0347:5-49
- restart signaling link alignment delay, 0120:3-25
- restart, DSM warm, 0178:2-18
- restarting PDBA, 0096:A-15
- Restarting the Eagle Agents on the LSMS, 0288:2-140
- restore
 - Database Management Command Functions (20.0), 0347:2-84
- restore device state option
 - configuring, 0142:4-176
- Restore RTDB, 0178:3-39
- Restore the PDB, 0183:3-97
- Restore the RTDB, 0183:3-29
- restoring
 - database
 - from backup partition of fixed disk, 0142:2-39
 - from removable cartridge, 0142:2-43
 - system data, 0142:2-73

- system data from removable cartridge, 0142:2-73
- restoring the database, 0142:2-39
- Restricted Linkset Option
 - Configuring, 0120:3-269, 0120:3-274, 0120:3-275
- restrictions
 - ITU SLS Enhancements (26.0), 0347:3-161
- resynchronization
 - automatic, 2339:2-5, 2339:2-8, 2339:4-2
 - basic phases, 2339:2-11
 - LSMS and network element, 2339:2-7
 - managing, 2339:4-2, 2339:6-2
 - procedures, basic phases, 2339:3-6
 - user-initiated, 2339:2-5, 2339:2-8, 2339:4-2
 - after bulk load, 2339:6-10
 - user-initiated resynchronization
 - aborting, 2339:4-11
- Retrieve button, 0197:2-56, 0197:2-58, 0197:2-66, 0197:2-67
- Retrieve Database Tables from an STP, 0197:2-56
- Retrieve DN, 0183:3-67
- Retrieve DN Block, 0183:3-71
- Retrieve from Local Database button, 0197:2-56, 0197:2-58, 0197:2-66
- Retrieve from STP button, 0197:2-56, 0197:2-58, 0197:2-67
- retrieve G-Flex-specific system options, 0188:3-5
- Retrieve Group screen, 0178:3-102
- Retrieve IMSI, 0183:3-63, 0183:3-80, 0183:3-83
- Retrieve LNP 10-digit Subscription, 0178:B-16
- Retrieve LNP Subscription, 0178:3-52
- Retrieve Network Entity, 0183:3-75, 0348:3-46
 - command, 0348:3-46
 - request message
 - for all NEs, 0348:3-47
 - for NE range, 0348:3-46
 - for specific IMSI, 0348:3-46
 - response message, 0348:3-47
 - response return codes, 0348:3-47
- Retrieve RTDB Records, 0178:3-41
- Retrieve Subscription Data, 0348:3-30
 - command, 0348:3-30
 - PDBI sample session with multiple responses, 0348:4-7
 - PDBI sample session, simple queries, 0348:4-5
 - request message
 - retrieve data for DN range, 0348:3-31
 - retrieve data for IMSI range, 0348:3-34
 - retrieve data for specific DNI, 0348:3-30
 - retrieve data for specific IMSI, 0348:3-33
 - response message, 0348:3-34, 0348:3-66
 - response return codes, 0348:3-36, 0348:3-67, 0348:3-70, 0348:3-72
- Retrieve Tables
 - Command List Box, 0197:2-56, 0197:2-58, 0197:2-60, 0197:2-64, 0197:2-65
 - Selected Commands Box, 0197:2-56, 0197:2-58, 0197:2-62, 0197:2-64, 0197:2-65, 0197:2-66
- Retrieve Tables Log, 0197:2-13, 0197:2-56, 0197:2-67, 0197:2-68, 0197:2-69, 0197:2-70, 0197:2-72, 0197:2-73

Master Index

- Clearing the Display, 0197:2-70, 0197:2-71
- closing, 0197:2-70, 0197:2-74
- File Menu, 0197:2-70
- Print window, 0197:2-72, 0197:2-73
- Printing, 0197:2-70, 0197:2-72
- Save window, 0197:2-73, 0197:2-74
- saved file confirmation window, 0197:2-74
- saving to a file, 0197:2-70, 0197:2-73
- Retrieve Tables Log window, 0197:2-67, 0197:2-68, 0197:2-69, 0197:2-70, 0197:2-71, 0197:2-72, 0197:2-73, 0197:2-74
 - File Menu, 0197:2-70, 0197:2-71
 - Processing Retrieve Request, 0197:2-67
 - Release Not Compatible Error, 0197:2-59
 - with Errors, 0197:2-70
 - without Errors, 0197:2-69
- Retrieve Tables window, 0197:2-4, 0197:2-56, 0197:2-57, 0197:2-60, 0197:2-75
 - Add button, 0197:2-58, 0197:2-62
 - Close button, 0197:2-58
 - description, 0197:2-58
 - GTT Warning window, 0197:2-56
 - Load button, 0197:2-58, 0197:2-66, 0197:2-75
 - Remove button, 0197:2-58, 0197:2-64
 - Reset button, 0197:2-58, 0197:2-65
 - Retrieve button, 0197:2-56, 0197:2-58, 0197:2-66, 0197:2-67
 - Retrieve from Local Database button, 0197:2-56, 0197:2-58, 0197:2-66
 - Retrieve from STP button, 0197:2-56, 0197:2-58, 0197:2-67
 - Store button, 0197:2-58, 0197:2-65, 0197:2-75
- Retrieve Trouble Report, 0338:3-47
- Retrieve UI Group, 0183:3-131
- Retrieve UI User, 0183:3-121
- Retrieve User screen, 0178:3-92
- Retrieving EAGLE 5 SAS database tables, 0197:2-1, 0197:2-4
- return cables, 0224:4-12
- return codes
 - Abort Transaction, 0348:3-15
 - Bad Arguments, 0348:3-6
 - Begin Transaction, 0348:3-13
 - Connect, 0348:3-10
 - Create Network Entity, 0348:3-39
 - Create Subscription, 0348:3-22, 0348:3-57, 0348:3-60, 0348:3-64
 - Delete Network Entity, 0348:3-45
 - Delete Subscription, 0348:3-29
 - Disconnect, 0348:3-11
 - Dump Connections, 0348:3-53
 - End Transaction, 0348:3-14
 - Parse Failed, 0348:3-5
 - PDBA Status Query, 0348:3-52
 - Retrieve Network Entity, 0348:3-47
 - Retrieve Subscription Data, 0348:3-36, 0348:3-67, 0348:3-70, 0348:3-72
 - Switchover response message, 0348:3-50
 - Update Network Entity, 0348:3-44
 - Update Subscription, 0348:3-27

Return key, 0178:5-26, 0183:5-34
 Return Material Authorization, 0095:B-1, 2969:B-1
 return shipment, 0095:7-23, 0095:B-22, 0212:1-28, 0224:1-27, 0224:3-10, 0243:1-28, 2969:7-22, 2969:7-24, 2969:7-38, 2969:B-20, 2970:1-15
 return shipping instructions, 0095:B-21, 2969:B-19
 Returning a Crate, 0212:1-28, 0224:1-26, 0243:1-27, 2970:1-14
 Reuse Limit, 0178:3-108, 0183:3-138
 Revocation of security admin userID not allowed, 0177:2-330
 Revoke Failed User, 0178:3-82, 0183:3-112
 Revoke / Restore User, 0178:3-81, 0183:3-111
 Revoking a User ID (EAGLE 21.0), 0347:5-50
 RFC, 0348:1-12
 RFC 1587, 0183:2-9
 RFC 1587 network standard, 0178:2-7, 0288:2-29
 RGTA, 0288:3-59, 0288:3-61, 0288:3-63
 RI, 0193:1-14, 0288:3-60, 0348:1-12
 ri, 0348:3-37, 0348:3-41
 RI must be GT when specifying NGT, 0177:2-785
 RI must be GT when specifying NTT, 0177:2-786
 RI must be SSN when CCGT is YES, 0177:2-571
 RI=GT must be specified when XLAT=DPCNGT, 0177:2-197
 risk of electric shock, 0095:6-2, 0224:4-14, 2969:6-2
 RLE and LFST must be specified when database is not used, 0177:2-395
 rls-alm, 0145:7-247
 RMA, obtaining, 0095:B-1, 2969:B-1
 RMC connector, 0224:B-65, 0243:B-26
 RMIN must be less than or equal to RMAX, 0177:2-490
 RMTP, 0188:1-12, 0190:1-13, 0193:1-14, 0193:2-9, 0195:1-12, 0348:1-12
 description, 0183:2-8
 RMTP channel, 0188:2-27
 RMTP channels, 0190:2-38
 RMTP multicast, 0193:2-4, 0195:2-10
 RMTP-II, 0188:2-12, 0190:2-37
 rmv-card, 0119:3-11, 0119:3-33, 0145:7-248
 rmv-card command, 2339:8-3
 rmv-imt, 0145:7-249
 rmv-trm, 0145:7-251
 RN, 0193:1-14, 0193:2-22, 0348:1-12
 rn, 0348:3-19, 0348:3-21, 0348:3-24, 0348:3-26, 0348:3-32
 RN already exists in HOMERN Table, 0177:2-692
 RN does not exist in HOMERN Table, 0177:2-692
 RN or SP address (Entity ID), 0190:3-2, 0193:3-15
 RN Prefix Deletion, 0190:2-53
 RN prefixes, 0190:2-48, 0193:2-18
 RN+DN, 0193:2-22
 RNIDN, 0190:1-13, 0193:1-14, 0193:2-21
 RNNDN, 0190:1-13, 0193:1-14, 0193:2-21
 RNSDN, 0190:1-13, 0193:1-14, 0193:2-21, 0195:1-12
 roaming number, 0190:2-8
 roles, ELAP
 Active/Standby, 0178:2-5
 Active/Standby switchover, 0178:2-5

Master Index

- roles, EPAP
 - Active/Standby, 0183:2-4
 - switchover, 0183:2-6
- Rotary impact drill, 0224:3-20
- rotary impact drill, 0095:4-3, 2969:4-3
- route
 - adding, 0120:3-153, 0120:3-164, 0120:3-172, 0120:3-181
 - changing, 0120:3-206
 - clock connection cable, 2970:3-42
 - removing, 0120:3-189
 - terminal cable, 2970:3-46
- route availability
 - network routing, 0120:2-176
- Route is allowed, 0338:3-395
- Route is prohibited, 0338:3-397
- Route is restricted, 0338:3-396
- route management
 - network routing, 0120:2-177
- Route on SSN, 0188:2-34
- route signaling messages, 0188:2-2
- route table, 0188:2-19, 0190:2-47, 0193:2-17
- Route table is full, 0177:2-143
- route-on-gt, 0188:2-30
- router IP address, default, 0178:5-18, 0183:5-20
- routers, 0212:4-48, 0243:A-17
- Routes
 - 5000, 0120:2-23
- routes and linksets assigned to the DPCs, 0188:4-8, 0190:4-10, 0193:4-10
- Routes of equal cost cannot exist for X.25 destinations, 0177:2-373
- Routeset is empty, 0177:2-143
- Routeset is full, 0177:2-140
- Routeset must be empty, 0177:2-141
- Routesets
 - 6000, 0120:2-23
 - 7000, 0120:2-23
 - 8000, 0120:2-23
- Routesets Feature Quantity must be increased, 0177:2-532
- Routing Context parameter is required for SUA, 0177:2-760
- Routing Key Lookup Hierarchy, 0100:2-29
- Routing key not found, 0177:2-627
- Routing Key table full, 0177:2-627
- Routing Key Tables, 0100:2-27
- Routing Number, 0190:2-7
- routing number prefixes, 0190:4-37, 0193:4-41
- routing options, 0190:2-6
- Row Alarm (ROW ALM), 0212:3-26
- row alarm cable installation, 0224:5-87
- ROW ALM, 0212:3-26
- RS232 connection, 0193:2-6, 0195:2-12
- RS-232 I/O ports, 0190:5-17, 0193:5-24
- RS232 serial port, 0188:2-20
- RS232 terminal ports, 0347:3-128

RS-485, 0212:3-106
 rspsize, 0348:3-8
 rst-card, 0145:7-252
 rst-card command, 0197:2-45, 2339:8-3
 rst-dstn, 0145:7-254
 rst-imt, 0145:7-255
 rst-trm, 0145:7-256
 RTDB, 0188:1-13, 0188:2-7, 0190:1-13, 0193:1-14, 0195:1-12, 0348:1-12, 0348:2-1
 Audit alarms, 0178:4-16, 0183:4-19
 Copy - Distributing the LNP Database, 0288:2-134
 Copy from Remote Mated NE Procedure, 0288:2-115
 Copy from the Mate ELAP Procedure, 0288:2-108
 Copying, 0288:2-104
 Copying from ELAP on Remote Mated NE, 0288:2-105
 Copying from Mated ELAP, 0288:2-104
 Distributing, LNP Database to DSMs, 0288:2-135
 Distributing, Returning to Normal Service, 0288:2-135
 EPAP database view, 0183:2-8
 rept-stat-db command to view database level and status, 0178:4-9, 0183:4-11
 task, 0183:2-8, 0183:2-27
 Verifying Status, 0288:2-105
 Verifying Status at the Eagle Terminal, 0288:2-106
 Verifying Status at the ELAP User Interface, 0288:2-106
 RTDB / Maintenance menu, 0178:3-36, 0183:3-26
 RTDB Audit Alarms, 0183:4-19
 RTDB Audit menu, 0178:3-24, 0183:3-21
 RTDB Backup menu, 0178:5-24, 0183:5-27
 RTDB database, 0188:2-21
 RTDB database capacity alarm cleared, 0338:3-559
 RTDB database capacity is 100% full, 0338:3-552
 RTDB database capacity is 80 full%, 0338:3-558
 RTDB database corrupted, 0338:3-553
 RTDB database has been corrected, 0338:3-557
 RTDB database incoherent, 0338:3-560
 RTDB database is inconsistent, 0338:3-555
 RTDB inconsistent, 0188:5-14
 RTDB Menu, 0178:3-34, 0183:3-24
 RTDB reload required, 0338:3-563
 RTDB resynchronization in progress, 0338:3-562
 RTDB Table FAK Capacity Normal, 0338:3-363
 RTDB Table Level 1 FAK Cap Exceeded, 0338:3-362
 RTDB Table Level 2 FAK Cap Exceeded, 0338:3-361
 RTDB transactional database engine, 0190:2-34
 rtrv commands, 0197:2-58, 0197:2-75, 0197:2-77
 rtrv_entity command, 0348:3-46
 rtrv_sub command, 0348:3-30
 rtrv-acg-mic, 0145:7-257
 rtrv-acg-noc, 0145:7-259
 rtrv-appl-rtkey, 0145:7-260
 rtrv-appl-sock, 0145:7-270
 rtrv-as, 0145:7-273
 rtrv-asp, 0145:7-274

Master Index

rtrv-assoc, 0145:7-275
rtrv-atm-lps, 0145:7-279
rtrv-atm-prm, 0145:7-285
rtrv-attr-seculog, 0145:7-286
rtrv-bip, 0145:7-286
rtrv-card, 0119:3-24, 0145:7-290, 0188:3-12, 0188:4-5, 0188:4-6, 0188:4-7, 0188:4-16, 0188:4-20, 0188:4-22, 0188:4-27, 0188:4-28, 0188:4-31, 0190:3-16, 0190:4-5, 0190:4-6, 0190:4-7, 0190:4-16, 0190:4-20, 0190:4-22, 0190:4-27, 0190:4-28, 0190:4-31, 0193:3-9, 0193:4-5, 0193:4-6, 0193:4-7, 0193:4-16, 0193:4-20, 0193:4-22, 0193:4-27, 0193:4-28, 0193:4-31, 0195:3-14
rtrv-card EAGLE 5 SAS command, 0197:2-3
rtrv-cmd, 0145:7-295
rtrv-cmdclass, 0145:7-298
rtrv-cspc, 0145:7-299, 0193:3-11, 0193:4-8, 0193:4-37
rtrv-ctrl-feat, 0119:2-2, 0119:2-12, 0119:2-18, 0119:4-2, 0119:4-9, 0119:6-2, 0145:7-301
rtrv-ctrl-feat EAGLE 5 SAS command, 0197:2-3, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-105
rtrv-data-rtddb, 0145:8-48
rtrv-dcmps, 0145:7-305
rtrv-dlk, 0145:7-306
rtrv-dstn, 0119:2-2, 0119:2-12, 0119:2-18, 0145:7-308, 0188:4-4, 0188:4-5, 0188:4-9, 0188:4-11, 0188:4-13, 0190:4-4, 0190:4-5, 0190:4-10, 0190:4-12, 0190:4-14, 0193:4-4, 0193:4-5, 0193:4-10, 0193:4-12, 0193:4-14
rtrv-e1, 0145:7-337
rtrv-eisopts, 0145:7-340
rtrv-feat, 0119:2-2, 0119:2-7, 0119:2-12, 0119:2-18, 0119:5-3, 0119:5-8, 0119:5-17, 0119:5-23, 0119:5-37, 0119:5-44, 0119:5-60, 0119:5-76, 0119:5-94, 0119:5-109, 0119:5-124, 0119:5-150, 0145:7-340, 0190:3-3, 0193:3-3, 0195:3-2
 4000 Routesets (23.0), 0347:2-6
 Calling Name Conversion Facility (CNCF) (23.1), 0347:2-44
 Retrieve Feature Status Command, 0188:3-4, 0190:3-4, 0193:3-4, 0195:3-2
rtrv-feat EAGLE 5 SAS command, 0197:2-56
rtrv-ftp-serv, 0142:4-140, 0145:7-342
rtrv-ftp-serv EAGLE 5 SAS command, 0197:2-119
rtrv-gpl, 0145:7-345, 0188:3-12, 0190:3-16, 0193:3-10, 0195:3-16
rtrv-gsmmap-scrn, 0145:7-353
rtrv-gsmopts, 0145:7-358
 Retrieve EIR System Options Command, 0195:3-5
 Retrieve G-Flex System Options Command, 0188:3-5
 Retrieve G-Port System Options Command, 0190:3-6
rtrv-gsms-opcode, 0145:7-362
rtrv-gsmssn-scrn, 0145:7-365
rtrv-gta, 0145:7-366
rtrv-gta EAGLE 5 SAS command, 0197:2-56, 0197:2-61, 0197:2-67
rtrv-gtt, 0119:4-9, 0145:7-375, 0145:7-376
rtrv-gtt EAGLE 5 SAS command, 0197:2-56, 0197:2-61, 0197:2-67
rtrv-gttset, 0119:6-9, 0119:6-15, 0145:7-387
rtrv-gttset EAGLE 5 SAS command, 0197:2-56, 0197:2-61, 0197:2-67
rtrv-gttset, 0145:7-390
rtrv-gttset EAGLE 5 SAS command, 0197:2-56, 0197:2-61, 0197:2-67
rtrv-gtw-stp, 0145:7-392
rtrv-gtwy-acthresh, 0145:7-393
rtrv-gtwy-prmtrs, 0145:7-394
rtrv-gws-actset, 0145:7-395
rtrv-gws-redirect, 0145:7-396

rtrv-homern, 0145:7-398, 0190:4-8, 0190:4-37, 0193:3-3, 0193:4-8, 0193:4-41
 rtrv-home-smisc, 0145:7-397
 rtrv-inpopts, 0145:7-399, 0193:3-11, 0193:4-8, 0193:4-41
 rtrv-ip-card, 0145:7-400, 0188:3-14, 0188:4-6, 0188:4-7, 0188:4-24, 0188:4-32, 0190:3-17, 0190:4-6,
 0190:4-7, 0190:4-23, 0190:4-32, 0193:3-12, 0193:4-6, 0193:4-7, 0193:4-23, 0193:4-32
 rtrv-ip-host, 0145:7-402, 0188:3-14, 0188:4-6, 0188:4-7, 0188:4-22, 0188:4-23, 0188:4-31, 0188:4-32,
 0190:3-18, 0190:4-6, 0190:4-7, 0190:4-22, 0190:4-23, 0190:4-31, 0190:4-32, 0193:3-12, 0193:4-6, 0193:4-7,
 0193:4-22, 0193:4-23, 0193:4-31, 0193:4-32
 rtrv-ip-lnk, 0142:4-138, 0142:4-158, 0145:7-403, 0188:3-14, 0188:4-6, 0188:4-7, 0188:4-24, 0188:4-25,
 0188:4-33, 0188:4-34, 0190:3-18, 0190:4-6, 0190:4-7, 0190:4-24, 0190:4-25, 0190:4-33, 0190:4-34,
 0193:3-12, 0193:4-6, 0193:4-7, 0193:4-24, 0193:4-25, 0193:4-33, 0193:4-34
 rtrv-ip-lnk command, 0197:2-48, 0197:2-49
 rtrv-ip-node, 0145:7-405, 0145:7-409
 rtrv-ip-rte, 0145:7-408
 rtrv-isupvar-attrb, 0145:7-409
 rtrv-l2t, 0145:7-412
 rtrv-l3t, 0145:7-414
 rtrv-lbp, 0145:7-416
 rtrv-lnp-dbts, 0145:7-419
 rtrv-lnp-dpcer, 0145:7-420
 rtrv-lnp-lrn, 0145:7-423
 rtrv-lnp-npanxx, 0145:7-426
 rtrv-lnpopts, 0145:7-442
 rtrv-lnp-serv, 0145:7-429
 rtrv-lnp-sp, 0145:7-430
 rtrv-lnp-sub, 0145:7-432
 rtrv-lnp-tnrpt, 0145:7-437
 rtrv-lnp-ttmap, 0145:7-439
 rtrv-log, 0145:7-443
 rtrv-log command, 0338:3-52
 RTRV-LOG command already in progress, 0177:2-406
 rtrv-ls, 0145:7-453, 0188:4-5, 0188:4-15, 0190:4-5, 0190:4-15, 0193:4-5, 0193:4-15
 rtrv-m2pa-tset, 0145:7-473
 rtrv-map, 0119:4-2, 0119:6-2, 0145:7-474, 0188:4-5, 0188:4-10, 0188:4-19, 0190:4-5, 0190:4-12, 0190:4-19,
 0193:3-9, 0193:4-5, 0193:4-8, 0193:4-12, 0193:4-19, 0193:4-38
 rtrv-measopts, 0145:7-481, 0195:3-17
 rtrv-meas-sched, 0145:7-479
 rtrv-mem, 0145:7-483
 rtrv-mrn, 0145:7-485
 rtrv-na, 0145:7-488
 rtrv-netopts, 0145:7-489
 rtrv-oap-config, 0145:7-489
 rtrv-oap-config command, 2970:4-18, 2970:4-30
 rtrv-prefix, 0145:7-502
 rtrv-pstn-pres, 0145:7-504
 rtrv-rmt-appl, 0145:7-505
 rtrv-rte, 0145:7-506, 0188:4-4, 0188:4-5, 0188:4-9, 0188:4-11, 0188:4-18, 0190:4-4, 0190:4-5, 0190:4-11,
 0190:4-12, 0190:4-18, 0193:4-4, 0193:4-5, 0193:4-11, 0193:4-12, 0193:4-18
 rtrv-scr-aftpc, 0145:7-520
 rtrv-scr-blkdpc, 0145:7-525
 rtrv-scr-blkopc, 0145:7-531
 rtrv-scr-cdpa, 0145:7-537

Master Index

rtrv-scr-cgpa, 0145:7-543
rtrv-scr-destfld, 0145:7-548
rtrv-scr-dpc, 0145:7-554
rtrv-scr-isup, 0145:7-559
rtrv-scr-opc, 0145:7-562
rtrv-scrset, 0145:7-575
rtrv-scr-sio, 0145:7-568
rtrv-scr-tt, 0145:7-572
rtrv-secu-dflt, 0145:7-579
rtrv-secu-dflt EAGLE 5 SAS command, 0197:2-23
rtrv-seculog, 0145:7-587
rtrv-secu-trm, 0145:7-581
rtrv-secu-user, 0145:7-583
rtrv-serial-num, 0145:7-593
rtrv-sg-opts, 0145:7-593
rtrv-shlf, 0145:7-595
rtrv-sid, 0119:2-12, 0119:2-16, 0145:7-596, 0188:4-4, 0188:4-5, 0188:4-9, 0188:4-13, 0190:4-4, 0190:4-5, 0190:4-10, 0190:4-14, 0193:3-3, 0193:4-4, 0193:4-5, 0193:4-8, 0193:4-10, 0193:4-14, 0193:4-36
rtrv-slk, 0188:4-5, 0188:4-17, 0190:4-5, 0190:4-17, 0193:4-5, 0193:4-17
rtrv-slt, 0145:7-609
rtrv-spc, 0145:7-611
rtrv-split-npa, 0145:7-615
rtrv-srvsel, 0145:7-616, 0188:4-8, 0188:4-38, 0190:4-8, 0190:4-38, 0193:3-3, 0193:4-9, 0193:4-43
 Retrieve EIR Service Selector Command, 0195:3-7
 Retrieve G-Flex Service Selector Command, 0188:3-7, 0190:3-8
rtrv-ss7opts, 0145:7-623
rtrv-ss-appl, 0145:7-622, 0193:4-8, 0193:4-39, 0195:3-16
rtrv-stpopts, 0119:2-2, 0145:7-624, 0188:4-4, 0188:4-10, 0188:4-36, 0190:3-4, 0190:4-4, 0190:4-11, 0190:4-36, 0193:3-3, 0193:4-4, 0193:4-11, 0193:4-40
rtrv-subnetid, 0145:7-629
rtrv-t1, 0145:7-630
rtrv-tbl-capacity, 0145:7-633
RTRV-TBL-CAPACITY Enhancement (Release 29.0), 0347:5-48
rtrv-th-sccp, 0145:7-635, 0145:7-636
rtrv-trbl, 0145:7-637
rtrv-trbltx, 0145:7-638
rtrv-trbltx command, 0338:3-53
rtrv-trbltx report, 0338:3-53
rtrv-trm, 0145:7-644
rtrv-trm command, 0197:2-47, 0197:2-48
rtrv-trm EAGLE 5 SAS command, 0197:2-67
rtrv-tt, 0119:4-9, 0119:4-16, 0145:7-660
rtrv-tt EAGLE 5 SAS command, 0197:2-56, 0197:2-61, 0197:2-67
rtrv-ttmap, 0145:7-663
rtrv-uaps, 0145:7-665
rtrv-uim-acthresh, 0145:7-669
rtrv-user, 0145:7-670
rtrv-x25-dstn, 0145:7-674
rtrv-x25-rte, 0145:7-675
rtrv-x25-slk, 0145:7-679
Run Health Check menu, 0178:3-72, 0183:3-42
run VSCCP GPL, 0190:5-1, 0195:4-1

S

S/ESHELF can only be entered, when report = hmutex is set, 0177:2-720
 S/ESLOT cannot be set to 9 or 10, 0177:2-542
 SADDR and EADDR must have the same number of digits, 0177:2-678
 SADDR must be specified when EGMS feature is OFF, 0177:2-810
 SADDR, NPV and NAIV must be specified together, 0177:2-718
 safety, 0095:2-1, 2969:2-1, 2969:7-2
 Safety glasses, 0224:3-20
 safety glasses, 0095:4-3, 2969:4-3
 SAI/P card
 description, 0212:4-31, 0212:4-43
 Same link management, 0097:2-8
 same link management
 X.25/SS7 Gateway Feature (Eagle 20.0), 0347:5-184
 same true point code, 0183:2-13
 sample PDBI sessions
 see sessions, PDBI sample
 SAP
 technical reference documents, 0212:1-19, 0243:1-19
 SAPC allowed for ITU-I or ITU-N linkset only, 0177:2-751
 SAPC entry not found for the linkset, 0177:2-749
 SAPC entry preset for the linkset, 0177:2-751
 SAS, 0193:1-14, 0195:1-1
 SATA hard drives, 2969:7-4
 Save button
 Retrieve Tables Log
 Save window, 0197:2-74
 System Log Save window, 0197:2-103
 Update Tables Log Save window, 0197:2-98
 Save window
 Cancel button
 System Log, 0197:2-103
 Update Tables Log, 0197:2-98
 Connectivity Test Log, 0197:2-37
 Retrieve Tables Log, 0197:2-73, 0197:2-74
 System Log, 0197:2-102, 0197:2-103
 Update Tables Log, 0197:2-97, 0197:2-98
 Saved File Confirmation window
 Connectivity Test Log, 0197:2-37, 0197:2-38
 Retrieve Tables Log, 0197:2-74
 System Log, 0197:2-103
 Update Tables Log, 0197:2-98
 savelogs, 0096:A-7, 2712:A-9
 Savelogs Procedure, 0096:A-7, 2712:A-9
 Saving to a file
 Connectivity Test Log, 0197:2-34, 0197:2-37
 Retrieve Tables Log, 0197:2-70, 0197:2-73
 System Log, 0197:2-99, 0197:2-102
 Update Tables Log, 0197:2-94, 0197:2-97
 scalar localtime, 0178:B-22
 SCCP, 0099:2-26, 0099:2-58, 0188:1-13, 0190:1-13, 0193:1-14, 0195:1-12, 0348:1-12
 SCCP Alarm Thresholds - Changing, 0099:2-200

Master Index

SCCP appl provisioned with ASM card type, 0177:2-553
SCCP capacity normal, card(s) abnormal, 0338:3-415
SCCP Card - Removing, 0288:2-21
SCCP card must have at least 586 processor, 0177:2-437
SCCP CdPA, 0347:5-19
SCCP Class 1 Sequencing
 class1seq parameter, 0099:2-20, 0099:2-196, 0099:2-197
 options
 changing, 0099:2-20, 0099:2-196, 0099:2-197, 0099:2-198, 0099:2-199
SCCP Conversion
 ANSI-ITU-China, 0099:1-2, 0099:2-3, 0099:2-6, 0099:2-7, 0099:2-16, 0099:2-17, 0099:2-30, 0099:2-33, 0099:2-40, 0099:2-43, 0099:2-44, 0099:2-47, 0099:2-48, 0099:2-69, 0099:2-71, 0099:2-82, 0099:2-86, 0099:2-92, 0099:2-118, 0099:2-124, 0099:2-162, 0099:2-163, 0099:2-171, 0099:2-172, 0099:2-179, 0099:2-181, 0099:2-193, 0099:2-194, 0099:3-2, 0099:3-21, 0099:3-23, 0099:3-28, 0099:3-32, 0099:3-53, 0099:3-54, 0099:3-55, 0099:3-58, 0099:3-62, 0099:4-2, 0099:4-27, 0099:4-30, 0099:4-34, 0099:4-35, 0099:4-38, 0099:4-39, 0099:4-54, 0099:4-57, 0099:4-60, 0099:4-63, 0099:A-36, 0099:A-37, 0099:A-38, 0099:A-39, 0099:A-41, 0099:A-42
 changing options, 0099:2-193, 0099:2-195
SCCP Conversion Feature
 ANSI-ITU-China
 Activating, 0099:A-36, 0099:A-43, 0099:A-44, 0099:A-45, 0099:A-46
SCCP Conversion feature must be enabled, 0177:2-763
SCCP Conversion feature requires at least TSM Hardware, 0177:2-777
SCCP did not route - bad translation, 0338:3-666, 0338:3-865
SCCP did not route - DPC congested, 0338:3-670, 0338:3-871, 0338:3-873
SCCP did not route - DPC not in MAP tbl, 0338:3-671, 0338:3-873
SCCP did not route - DPC OOS, 0338:3-667, 0338:3-831, 0338:3-868
SCCP did not route - SS congested, 0338:3-673, 0338:3-876
SCCP did not route - SS not in MAP tbl, 0338:3-674, 0338:3-878
SCCP did not route - SS OOS, 0338:3-672, 0338:3-875
SCCP Encode Failure, 0338:3-880, 0338:3-881
SCCP envelopes, 0097:2-4, 0347:5-180
SCCP is available, 0338:3-414
SCCP is not available, 0338:3-418
SCCP is removed, 0338:3-422
SCCP maintenance block, 0188:2-23, 0190:2-50
SCCP Message Type Screening (EAGLE 22.0), 0347:5-53
SCCP not configured, 0177:2-151
SCCP portion, 0193:2-21
SCCP rcvd GSM Map Opcode w/ forbid param, 0338:3-898
SCCP rcvd inv Cld Party - bad GT ind, 0338:3-652, 0338:3-860
SCCP rcvd inv Cld Party - bad network, 0338:3-656, 0338:3-861
SCCP rcvd inv Cld Party - no SSN, 0338:3-657, 0338:3-862
SCCP rcvd inv GT - bad Translation Type, 0338:3-665
SCCP rcvd inv GT - invalid selectors, 0338:3-863
SCCP rcvd inv LSS - bad SSN, 0338:3-683, 0338:3-867
SCCP rcvd inv msg class, 0338:3-648
SCCP rcvd inv msg length, 0338:3-647
SCCP rcvd inv SCMG - bad AFTPC, 0338:3-684
SCCP rcvd inv SCMG - bad length, 0338:3-687
SCCP rcvd inv SCMG - bad msg type, 0338:3-688
SCCP rcvd inv SCMG - bad subsystem, 0338:3-686

SCCP rcvd inv SCMG - invalid SOR, 0338:3-704
 SCCP rcvd invalid UDTS msg, 0338:3-640
 SCCP rcvd invalid XUDT msg, 0338:3-642
 SCCP rcvd invalid XUDTS/LUDTS msg, 0338:3-643
 SCCP rcvd undefined Map Op-Code, 0338:3-900
 SCCP rcvd unknown msg type, 0338:3-646
 SCCP rsp did not route - bad Selectors, 0338:3-662
 SCCP rsp did not route - bad Xlation, 0338:3-660
 SCCP rsp did not route - invalid GTI, 0338:3-658
 SCCP rsp did not route - invalid TT, 0338:3-659
 SCCP rsp did not route - no SSN in msg or DB, 0338:3-664
 SCCP rsp did not route - SSP not True PC, 0338:3-661
 SCCP screen set is too large, 0338:3-693
 SCCP Screening, 0098:2-2
 SCCP services, 0188:2-24
 SCCP Subsystem Management, 0025:4-6
 SCCP XUDT(S) msg
 inv segmentation parm, 0338:3-746
 SCCP XUDT/LUDT msg
 Hop Counter violation, 0338:3-744
 inv opt portion len, 0338:3-745
 SCCP-CNV
 Unable to convert ANSI CDPA GT, 0338:3-675
 Unable to convert ANSI CGPA GT, 0338:3-677
 Unable to convert ITU CDPA GT, 0338:3-679
 Unable to convert ITU CGPA GT, 0338:3-681
 SCCPCNV must be ON before TCAPCNV can be ON, 0177:2-521
 SCCPCNV, TCAPCNV must be disabled, 0177:2-776
 SCCPMT must be specified as 9, 10, 17, 18, or *, 0177:2-182
 SCCS Interface Support (EAGLE 21.0), 0347:5-54
 SCF, 0193:1-14
 Scheduled transfer failure, 0338:3-905
 SCM, 0193:1-14, 0193:5-6
 SCMG, 0195:1-12
 SCMGFID is invalid, 0177:2-211
 Scope and Audience, 0025:1-1, 0188:1-2, 0190:1-2, 0193:1-2, 0195:1-2, 0212:1-4, 0212:3-44
 SCP, 0188:1-13, 0190:1-13, 0193:1-14, 0195:1-12
 Screen Resolution, 0178:5-3, 0183:5-2
 Screen set name already exists, 0177:2-240
 Screen set name is referenced by a link set, 0177:2-240
 Screen set name not defined, 0177:2-143
 screen workspace, 0178:3-4, 0183:3-4
 Screening action can not be ATIERR for the given OPNAME, 0177:2-681
 screws, 0224:5-69, 2970:3-13
 scroll by messages, 0178:3-115, 0183:3-145
 SCSI
 disks, MPS Server, 0212:4-27
 MPS Server interface, 0212:4-28
 sctp, 0145:9-107
 SCTP Association or SLK provisioned
 Card supports 2 links, 0177:2-533
 SCTP checksum algorithm option, 0100:3-426, 0100:3-455

Master Index

SCTP Retransmission Control (Release 28.1), 0347:5-60
SCTP Retransmission Control (Release 28.1) (IP7 Release 6.0), 0347:5-60
sctpcsum, 0100:3-122, 0100:3-426, 0100:3-455
SDATE must be earlier or equal to EDATE, 0177:2-432
SDATE+STIME must be before current date-time, 0177:2-406
SDS, 0188:1-13, 0190:1-13, 0195:1-12
SDS command ent-trace, 0188:3-1
SEAC, 0348:1-12
SEAC CLI parameter requires SEAS feature, 0177:2-604
SEAC CLI required before OAP update, 0177:2-611
SEAS compliance
 Enhancements to GWS Reject Messages (25.0), 0347:2-166
SEAS Enhancements (EAGLE 26.0), 0347:5-62
 Affected Commands, 0347:5-63
SEAS Enhancements, Autonomous Messages (EAGLE 22.0), 0347:5-68
SEAS Error Messages Index, 0177:3-1
SEAS feature or LNP feature is not configured, 0177:2-348
SEAS Gateway Audit Command (CHK-UNREF-ENT) (EAGLE 22.0), 0347:5-69
SEAS Gateway Linksets cannot be deleted locally, 0177:2-404
SEAS Gateway Screen Set Names cannot be changed locally, 0177:2-404
SEAS Interface Support (EAGLE 21.0), 0347:5-70
SEAS is at min service limit, 0338:3-443
SEAS is available, 0338:3-454
SEAS is removed, 0338:3-455
SEAS PVC unavailable, 0338:3-436
SEAS Subsystem has not been provisioned, 0177:2-317
SEAS UAL session unavailable, 0338:3-440
SEAS UAL unavailable, 0338:3-432
SEAS unavailable, 0338:3-447
SEAS Verify Signaling Route-Set Status and SCCP Application Status Command (VFY-SRSAPST)
 (EAGLE 22.0), 0347:5-72
SEAS X.25 Link is available, 0338:3-442
SEAS X.25 Link unavailable, 0338:3-434
SEAS X.25 mode required before OAP update, 0177:2-612
SEAS X.25 packet size required before OAP update, 0177:2-612
SECMTPMATE - rcvd mate PC on non C-link, 0338:3-955
SECMTPSID - rcvd MSU with OPC = SID, 0338:3-956
SECMTPSNM - no rte to OPC / AFTPC, 0338:3-957
secondary point codes, 0120:2-3
 configuring, 0120:2-63
Seconds out of range, 0177:2-107
SECSCCPSCMG - no rte to AFTPC, 0338:3-958
secure connection, 0197:2-3, 0197:2-19, 0197:2-45
Secure Connection Box - FTRA 2.0 or greater, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-45, 0197:2-50,
 0197:2-51
Secure EAGLE 5 SAS Host Key Provisioning, 0197:2-45
Secure FTP server, 0197:2-51
Secure Host Key - EAGLE 5 SAS
 Provisioning, 0197:2-45
secure IP connection between FTRA and STP, 0197:2-19, 0197:2-24
secure shell encryption key exchange, 0178:5-21, 0183:5-24
secure telnet connection, 0142:1-2, 0142:B-1

- setup with the PuTTY client program, 0142:1-2, 0142:B-1
- security, 0096:2-16, 2712:2-14
- Security Administration, 0197:2-48
- Security Administration Unsolicited Output Message Group, 0338:D-26
- security defaults
 - changing, 0142:4-7
- security log characteristics
 - changing, 0142:4-17
- Security log command already in progress, 0177:2-434
- Security log exception cleared, 0338:3-254
- Security log failed, 0338:3-255
- Security Log Increase (EAGLE 26.05), 0347:5-72
 - Enhanced Commands, 0347:5-73
 - Increasing the FTA (File Transfer Area), 0347:5-73
 - limitations, 0347:5-74
 - Upgrade Considerations, 0347:5-73
- Security tables may not be altered, 0177:2-496
- security, PDBI connection, 0348:2-11
- Seismic Frame, 0224:3-24
- Select button, 0197:2-18, 0197:2-27, 0197:2-29
 - Select Starting Directory window, 0197:2-54
 - Select window, 0197:2-81, 0197:2-82
- Select Mate menu, 0178:3-13, 0183:3-13
- Select Other PDBA, 0183:3-53
- Select Starting Directory window, 0197:2-52, 0197:2-53, 0197:2-54
 - Cancel button, 0197:2-54
 - Select button, 0197:2-54
- Select Time Zone, 0178:5-20, 0183:5-23, 0183:A-1
- Select Time Zone menu, 0178:5-20, 0183:5-23, 0183:A-1
- Select window
 - Cancel button, 0197:2-81, 0197:2-82
 - description, 0197:2-82
 - Select button, 0197:2-81, 0197:2-82
 - Update Tables, 0197:2-79, 0197:2-80, 0197:2-81, 0197:2-82
- Selected Commands
 - Box, 0197:2-56, 0197:2-58, 0197:2-62, 0197:2-64, 0197:2-65, 0197:2-66
 - Adding a Command, 0197:2-62
 - Adding a Range of Commands, 0197:2-63
 - Adding Multiple Commands, 0197:2-63
 - Command Selected Removed, 0197:2-65
 - Command Selected to be Removed, 0197:2-64
 - Field, Retrieve Tables window, 0197:2-58
- Selected STP, 0197:2-1, 0197:2-4, 0197:2-43, 0197:2-56, 0197:2-58, 0197:2-65, 0197:2-66, 0197:2-67, 0197:2-79, 0197:2-80, 0197:2-85, 0197:2-86, 0197:2-87, 0197:2-89
 - Sending a Command File, 0197:2-86
- Selecting
 - Command, 0197:2-60
 - Current STP, 0197:2-4, 0197:2-42
 - Multiple Commands, 0197:2-62
 - Range of Commands, 0197:2-61
- Selective Alarm Inhibiting (EAGLE 22.0), 0347:5-74
 - Changed Commands, 0347:5-76

Master Index

New Commands, 0347:5-76
Selective Homing of EPAP RTDBs (Release 29.0), 0347:5-78
selector-specified service numbering plan, 0188:2-32
self identification of system, 0188:4-9, 0190:4-10, 0193:4-10
self identification of the EAGLE 5 SAS
 adding a point code, 0120:2-81
 changing, 0120:2-90
Semi-Annual Procedures, 0338:2-42
Send Raw PDBI Commands, 0183:3-85
send status message, 0188:2-26
Sending a Command File to the Selected STP, 0197:2-86
Sending EAGLE 5 SAS command files, 0197:2-4
send-msg, 0145:8-53
Sentinel Data Collection Subsystem, ANSI ISUP CDR Data Feed document, 0243:1-19
Sentinel Data Collection Subsystem, ITU ISUP CDR Data Feed document, 0243:1-19
Sentinel Data Collection Subsystem, LIDB TDR Data Feed document, 0243:1-20
Sentinel Data Collection Subsystem, Peg Counter Data Feed File Format document, 0243:1-20
Sentinel Frames, 0025:5-4, 0212:5-4
Sentinel Products, 0212:5-1
Sentinel publications, 0212:1-17, 0243:1-18
Sentinel Server Frames, 0025:5-5
Sentinel Site Collector Frame with Flight Recorders, 0212:1-9
Sentinel Transport Card, 0097:6-3, 0097:6-4, 0097:6-5, 0097:6-6, 0097:6-7, 0097:6-8, 0097:6-9, 0097:6-10, 0097:6-11, 0097:6-15, 0097:6-16, 0097:6-19, 0097:6-20, 0097:6-23, 0097:6-24, 0097:6-25, 0097:6-26, 0097:6-27, 0097:6-28, 0097:6-30
 dual-slot, 0097:6-4, 0097:6-7, 0097:6-8, 0097:6-19, 0097:6-21, 0097:6-23
 single-slot, 0097:6-4, 0097:6-7, 0097:6-8, 0097:6-19, 0097:6-21, 0097:6-23
Sentinel Transport Cards, 0025:5-8, 0212:2-22
sequential steps to activate G-Flex, 0188:4-1, 0190:4-1
sequential steps to activate INP, 0193:4-1
Serial card
 Embedded OAP (24.0), 0347:2-132
 serial card, 0338:5-22, 2970:7-21, 2970:7-22
 serial communication, 0025:6-6, 0096:2-10, 2712:2-10
 serial I/O card (EOAP), 0338:5-130, 2970:6-85
 replacement, 0338:5-130, 2970:6-85
SERIAL param valid only with APPL param, 0177:2-630
serial port connectors, 0212:3-27
serial ports
 8-Port Connector Box, 0212:4-31, 0212:4-38, 0212:4-43
 MPS Server, 0212:4-28
 SAI/P card, 0212:4-31, 0212:4-43
SERV, 0288:3-22, 0288:3-23, 0288:3-24, 0288:3-25, 0288:3-29, 0288:3-30, 0288:3-31, 0288:3-32, 0288:3-33, 0288:3-36, 0288:3-37, 0288:3-59, 0288:3-62, 0288:4-5, 0288:4-20, 0288:4-22, 0288:4-23, 0288:4-25, 0288:4-26, 0288:4-27, 0288:4-28, 0288:4-29
SERV has not been assigned a true TT, 0177:2-472
SERV must not be GFLEX when SNAI = RNIDN/RNNDN/RNSDN, 0177:2-698
Server
 FTP - FTRA 2.0, 0197:2-51
 FTP, Configuration, 0197:2-4
 Secure FTP - FTRA 2.0, 0197:2-51
server, 0025:4-10, 0100:3-191

- command line, connecting to, 2712:A-3
- Server, MPS
 - see MPS Server
- service interruption, 0193:1-9
- service interruptions, 0188:1-8, 0190:1-8, 0195:1-8
- service NAI values, 0193:2-2
- Service Nature of Address Indicator, 0193:2-7
- service numbering plan, 0188:2-32
- Service parameters within error messages, 0178:B-19
- Service Provider, 0288:3-52, 0347:4-87
- Service Provider ID, 0288:3-52
- service provider number portability, 0190:1-1, 0190:2-2, 0193:2-1
- Service Providers, 0178:3-47
- service selector table, 0188:5-5
- Service Selector Table is full, 0177:2-555
- service selectors, 0193:4-42
- Service Type is already in LNP database, 0177:2-474
- Service type is not in LNP database, 0177:2-475
- serviceability
 - Enhanced Bulk Download (25.0), 0347:2-147
- Serviceability Hints, 0188:2-18, 0190:2-47, 0193:2-16
- SERVPORT, 0288:3-53
- Session Idle Timeout, 0178:3-108, 0183:3-138
- session inactivity, 0178:3-5
- Sessions per User, 0183:3-111
- sessions, PDBI sample
 - abort transaction, 0348:4-8
 - create Network Entities, 0348:4-2
 - create simple subscription data, 0348:4-3
 - queries with multiple responses, 0348:4-7
 - simple queries, 0348:4-5
 - update request in read transaction, 0348:4-9
 - update subscription data, 0348:4-4
 - write transaction to Standby PDBA, 0348:4-10
- Set button, 0197:2-55
 - FTP Server Configuration Menu, 0197:2-52
- Set Log Levels, 0183:3-108
- Set SERVERPFX to NONE before disabling IS412GSM, 0177:2-819
- set trace, 0190:3-2, 0193:3-16
- setcomm, 0100:3-122
- set-date, 0145:7-681
- set-gtwy-acthresh, 0145:7-681
- set-mem, 0145:8-56, 0188:3-13
- set-scrrej-prmtrs, 0145:7-683
- set-time, 0145:7-683
- setting
 - EAGLE 5 SAS clock and date, 0142:4-3
- Setting the Maximum Number of Gateway Screening Rejected Messages, 0119:5-149
- Setting the Threshold for Reporting Gateway Screening Activity, 0119:5-148
- Setting Up an ELAP Workstation, 0178:5-3, 0288:2-33
- Setting Up Workstation, 0178:5-3, 0183:5-2
- set-uim-acthresh, 0145:7-685

Master Index

setup secure telnet connection with the PuTTY client program, 0142:1-2, 0142:B-1

SFTP client channel open failure - Error code 695, 0197:2-118

SFTP client channel read failure - Error code 693, 0197:2-118

SFTP client channel write failure - Error code 694, 0197:2-118

SFTP Client Errors, 0197:2-106

SFTP client packet send failure - Error code 597, 0197:2-106

SFTP Connection Errors, 0197:2-118

SFTP Error Codes, 0197:2-105

SFTP Errors, 0197:2-106

SFTP packet read failure - Error code 599, 0197:2-106

SFTP protocol error - Error code 600, 0197:2-107

SFTP received a invalid ID in the response received during a read operation on remote directory - Error code 608, 0197:2-107

SFTP Server, 0197:2-115, 0197:2-118, 0197:2-122

SFTP Server Verification procedure, 0197:2-122

SFTP Setup Errors, 0197:2-118

SFTP/SSH Error Codes, 0197:2-105

SFTP: Handle mismatch error - Error code 609, 0197:2-107

shelf

- adding, 0120:3-4, 0142:4-90
- removing, 0142:4-92

Shelf Clock Connectors, 0212:3-28

Shelf ID out of range, 0177:2-51

Shelf location 1100 is reserved for the control shelf, 0177:2-76

Shelf location already equipped, 0177:2-77

Shelf location not equipped, 0177:2-31

Shell command prompt, 0197:2-75

shipping container, 0224:1-20, 0224:3-4, 0224:3-5, 0224:3-6, 0224:3-7, 0243:1-21

Shipping Manager, 0224:3-10

shipping, return instructions, 0095:B-21, 2969:B-19

Short Message Service (SMS) - LNP - Activation, 0288:3-79

Short Message Service Center (SMSC), 0347:5-19

short synchronization, 2339:4-2

si, 0100:3-252

SI does not exist for given SR, 0177:2-241

side, 0348:3-50

side panel, 0224:3-33

Signal Transfer Point, 0188:2-2, 0190:1-1

Signaling Application System, 0188:1-1, 0195:1-1

signaling link

- adding, 0120:3-5, 0120:3-6, 0120:3-130, 0120:C-34
- card types, 0120:3-5
- configure for E1 card, 0120:A-10
- parameters for DCMs, 0120:3-7
- removing, 0100:3-105, 0120:3-145
- verify, 0120:3-6

Signaling link is not provisioned for the card, 0177:2-726

signaling link selection conversion

- 5-8 Bit Sequencing Assurance (24.0), 0347:2-18

signaling link test message

- changing, 0120:3-228

signaling links, 1500, 0100:3-98, 0120:3-10

Signaling Point (SP) Entity ID, 0193:2-16
 signaling points, 0193:4-37
 Signaling Relay Function, 0190:1-1
 Signaling Transfer Point, Local Area Network (SLAN), 0212:6-10
 Signaling/ Cellular Generic Hardware Reference, 0212:1-18, 0243:1-19
 SIM, 0188:1-13, 0188:2-2, 0190:1-13, 0190:2-2, 0193:1-14, 0195:1-12
 Simple Subscription Data Creation with Single Txnmode, 0348:4-11
 Simplex Mode
 FRCSMPLX, 0288:3-52
 Simplex Mode Menu, 0178:3-20
 Simplifying BIP (Board ID PROM) for Eagle STP Boards (EAGLE 23.1), 0347:5-80
 Changed Commands, 0347:5-80
 Hourly Status Message Report, 0347:5-81
 Single DNs, 0348:2-20
 Single IMEI Data, 0348:4-12
 Single IMEIs, 0348:2-22
 single instance table, 0348:2-5
 Single Slot EDCM (SSEDCM), 0347:5-82
 single slot EDCM card, 0347:5-82
 Single Slot Enhanced DCM (SSEDCM) (Release 28.1], 0347:5-82
 single transaction mode, 0348:3-9
 single-slot STC, 0097:6-4, 0097:6-7, 0097:6-8, 0097:6-19, 0097:6-21, 0097:6-23
 SIO does not exist in given SR, 0177:2-240
 Site Collector Frames, 0025:5-4, 0212:5-6
 site engineering, 0212:6-1
 Site PC, CPCs and NCPs must be full point codes, 0177:2-371
 site planning, 0193:3-1, 0195:3-1
 Site point code is already being used, 0177:2-71
 site requirements, 2970:1-16
 Site SPC must be a full point code, 0177:2-646
 sizes of converted numbers, 0188:2-32
 slab floor
 anchor assembly, 0095:4-7, 2969:4-7
 slab floor, anchoring frame, 0095:4-6, 2969:4-6
 SLAN DLK ping test completed, 0338:3-775
 SLK Inhibit Denied, 0338:3-796
 SLK Inhibit Response Timeout, 0338:3-797
 SLK IPLIML2 requires linkset MTPRSE setting to be no, 0177:2-491
 SLK Level-3 T19 timer expired, 0338:3-795
 SLK Uninhibit Denied, 0338:3-798
 SLK Uninhibit Response Timeout, 0338:3-799
 SLKUSEALM not allowed for non-IPGWx linksets, 0177:2-794
 SLSCI is only valid for ANSI link sets, 0177:2-369
 SLSOCBIT parameter is only valid for ITU link sets, 0177:2-664
 SLSOCBIT parameter not permitted if SLSOCB feature is off, 0177:2-664
 SLRSRB parameter is only valid for ITU Link Sets, 0177:2-665
 SLTC aborted
 unable to perform the test, 0338:3-710
 SLTC failure
 bad data pattern, 0338:3-703
 failed link, 0338:3-708
 invalid Point Code (DPC), 0338:3-707

Master Index

- invalid Point Code (OPC), 0338:3-700
- invalid SLC, 0338:3-701
- no response, 0338:3-702
- SLTC success
 - manual test passed, 0338:3-709
- SLTSET and ENABLED cannot be specified together, 0177:2-73
- Small Computer System Interface Buses, 0025:3-5, 0212:2-6
- SMS, 0188:1-13, 0190:1-13, 0193:1-14, 0195:1-12, 0348:1-12
- SMS (Short Message Service) - LNP - Activation, 0288:3-79
- SMS Feature - LNP - Deactivating, 0288:3-84
- SMS Prepaid Intercept Message Handling, 0190:2-60
- SMSC, 0193:1-14, 0348:1-13
- SMSC ADDR to be deleted does not exist in database, 0177:2-541
- SMSC Address already exists, 0177:2-541
- SNAI, 0193:1-15, 0193:2-7, 0193:2-11
- SNAI & SNP must be specified when SERV is not INPQ/EIR, 0177:2-697
- sname, 0100:3-252
- SNAME must be specified, 0177:2-410
- SNCC, 0348:1-13
- SNM Overload Abated, 0338:3-388
- SNM Overload Onset, 0338:3-387
- snmpcont, 0100:3-122
- SNP, 0188:1-13, 0190:1-13, 0193:1-15, 0195:1-12
- socket connection, 0348:3-8
- Socket connection parameters must be unique, 0177:2-618
- Socket name already exists, 0177:2-617
- Socket Name not defined, 0177:2-628
- Socket name not found, 0177:2-616
- Socket operation on non-socket - Error code 50, 0197:2-119
- Socket Table full, 0177:2-621
- sockrtt, 0145:9-116
- sockstate, 0145:9-118
- Software
 - FTRA
 - Installing, 0197:2-4
 - Unix, 0197:2-9
 - Windows, 0197:2-5
 - Java 2 Runtime Environment
 - installing, 0197:2-5, 0197:2-8
- Software caused the connection to abort - Error code 53, 0197:2-119
- Software Configuration, 0178:5-1, 0183:5-1
- software release, 0190:1-8, 0195:1-7
- software releases, 0188:1-8, 0190:1-8, 0195:1-7
- Software Requirements, 0197:2-2
 - Unix Workstation, 0197:2-2
 - Windows Workstation, 0197:2-2
- software, MPS system configuration, 0025:6-6, 0096:2-10, 2712:2-10
- Solaris 7 operating system, 0212:4-28
- SOR, 0193:1-15
- Source address/location must be specified, 0177:2-443
- Source and destination combination is not allowed, 0177:2-596
- Source and destination disks not compatible, 0177:2-354

Source database version is not compatible, 0177:2-408
 Source drive not coherent, 0177:2-355
 Source location must specify the active fixed disk, 0177:2-352
 Source parameter not supported, 0177:2-66
 SP, 0188:1-13, 0190:1-13, 0193:1-15, 0195:1-12, 0288:3-52, 0288:3-54, 0288:3-55, 0288:3-57, 0347:4-87, 0348:1-13, 0348:2-3
 sp, 0348:3-16, 0348:3-17, 0348:3-19, 0348:3-21, 0348:3-23, 0348:3-24, 0348:3-26, 0348:3-32, 0348:3-34
 space requirements, 0095:2-7, 0212:6-3, 2969:2-7
 spare card storage shelf, 0212:3-14
 Spare Inventory Rotation, 0338:2-42
 Spare point code
 14-bit ITU national, 0098:2-8, 0098:2-11, 0098:2-23, 0098:3-8, 0098:3-10, 0098:3-15, 0098:3-20, 0098:3-21, 0098:4-9, 0098:4-11, 0098:4-18, 0098:4-25, 0098:4-27, 0098:6-10, 0098:6-12, 0098:6-19, 0098:6-26, 0098:6-27, 0098:6-28, 0098:6-29, 0098:7-10, 0098:7-11, 0098:7-12, 0098:7-17, 0098:7-24, 0098:7-25, 0098:8-9, 0098:8-13, 0098:8-14, 0098:8-22, 0098:8-23, 0098:8-27, 0098:8-30, 0098:8-31, 0098:9-13, 0098:9-14, 0098:9-23, 0098:9-30, 0098:9-31, 0098:9-32, 0098:11-9, 0098:11-13, 0098:11-14, 0098:11-15, 0098:11-23, 0098:11-27, 0098:11-30, 0098:11-31, 0098:11-32, 0098:12-13, 0098:12-14, 0098:12-23, 0098:12-29, 0098:12-30, 0098:12-31
 ITU international, 0098:2-8, 0098:2-11, 0098:2-23, 0098:3-8, 0098:3-10, 0098:3-15, 0098:3-20, 0098:3-21, 0098:4-9, 0098:4-11, 0098:4-18, 0098:4-25, 0098:4-27, 0098:6-10, 0098:6-12, 0098:6-19, 0098:6-26, 0098:6-27, 0098:6-28, 0098:6-29, 0098:7-10, 0098:7-11, 0098:7-12, 0098:7-17, 0098:7-24, 0098:7-25, 0098:8-9, 0098:8-13, 0098:8-14, 0098:8-22, 0098:8-23, 0098:8-27, 0098:8-30, 0098:8-31, 0098:9-13, 0098:9-14, 0098:9-23, 0098:9-30, 0098:9-31, 0098:9-32, 0098:11-9, 0098:11-13, 0098:11-14, 0098:11-15, 0098:11-23, 0098:11-27, 0098:11-30, 0098:11-31, 0098:11-32, 0098:12-13, 0098:12-14, 0098:12-23, 0098:12-29, 0098:12-30, 0098:12-31
 spare point code, 0120:2-7, 0120:2-55, 0120:2-81, 0120:2-82, 0120:2-83, 0120:2-91, 0120:2-94, 0120:2-100, 0120:2-104, 0120:2-193, 0120:2-198, 0120:2-228, 0120:2-236, 0120:3-17, 0120:3-74, 0120:3-121
 Spare Point Code Feature must be enabled, 0177:2-773
 Spare Point Code Feature not compatible with TALI socket, 0177:2-774
 Spare Point Codes not supported with adapter type, 0177:2-774
 SPC, 0188:1-13, 0190:1-13, 0193:1-15, 0195:1-12
 SPC & DPC must be the same network type, 0177:2-647
 SPC and NSPC may not be equal, 0177:2-643
 SPC does not exist, 0177:2-645
 SPC may not be referenced in the STP's route table, 0177:2-646
 SPC may not exist as a TPC or CPC in the SID table, 0177:2-644
 SPC may not exist as a TPC, CPC, or DPC in the route table, 0177:2-644
 SPC may not exist in the STP's route table, 0177:2-644
 SPC must be a full point code, 0177:2-647
 special prefix, 0193:2-2, 0193:2-7, 0193:2-11
 special prefixes, 0193:2-2
 Specific SSN already exists, 0177:2-767
 specifications
 MPS Server component, 0025:6-11
 MPS Server CPU, 0212:4-27
 tape drive, 0212:4-27
 Specified APPL or LOC not supported with DATA parameter, 0177:2-660
 Specified AS name not found, 0177:2-737
 Specified BC exceeds max allowed (96), 0177:2-88
 Specified BPS is invalid, 0177:2-516
 Specified card cannot be the Active MASP, 0177:2-699
 Specified cards A, B interface IP Address must be assigned, 0177:2-577

Master Index

Specified Fahrenheit values convert to same Celsius value, 0177:2-834
Specified LOC is invalid, 0177:2-152
Specified LPSET contains default values and not configurable, 0177:2-513
Specified OAP does not exist, 0177:2-588
Specified OAP not available, 0177:2-587
Specified Port is not valid for Card and APPL Type, 0177:2-421
Specified UID is reserved for system use, 0177:2-434
specifies G-Flex service selectors, 0188:3-6
specify G-Flex selectors, 0188:3-6
specify ITU national PC format, 0188:4-10, 0190:4-11, 0193:4-11
speed=10, 0188:4-24, 0188:4-33, 0190:4-24, 0190:4-33, 0193:4-24, 0193:4-33
split, 0100:3-260, 0100:3-269, 0100:3-279
Split Allowed CGPA Table (EAGLE 22.0), 0347:5-85
SPLIT must be greater than CICS, 0177:2-651
SPLIT must be less than or equal to CICE, 0177:2-652
Split NPANXX, 0347:4-88
Split of Allowed SIO Table (Release 22.0), 0347:5-86
SPLIT, NCICS, NCICE are not allowed with SI unless SI is 4, 5, or 13, 0177:2-654
SPLIT, RC, NCICS, NCICE or attributes required, 0177:2-654
SR or NSR does not reference an existing SR, 0177:2-242
SRAM, 0212:3-91
SRC and DEST must be specified, 0177:2-90
SRCLPSET and LPSET cannot be equal, 0177:2-514
SRCSET and SET cannot be equal, 0177:2-719
SRCTSET and TSET cannot be equal, 0177:2-539
SRF, 0190:1-1, 0190:1-13, 0193:1-15, 0195:1-12, 0348:1-13
SRFADDR, SRFNAI & SRFNP parameters must be entered together, 0177:2-710
SRF-based MNP, 0190:2-5
srfimsi, 0348:3-39, 0348:3-42
SRI, 0190:1-13, 0193:1-15, 0195:1-12, 0348:1-13
SRI Redirect Feature must be enabled, 0177:2-816
SRI-MNP, 0190:2-48
srkq, 0100:3-122
SRKQ + DRKQ exceed max allowed rtkey limit, 0177:2-656
SRM or MRC cannot be entered for a solitary entry, 0177:2-426
SRM=YES cannot be entered with ITU point code types, 0177:2-174
srvsel commands, 0188:3-5, 0190:3-6, 0193:3-3, 0195:3-6
SRVSEL of ITU found, but not allowed with ANSIGFLEX, 0177:2-811
SS7, 0188:1-13, 0190:1-13, 0195:1-12
SS7 address does not exist in X.25 destination table, 0177:2-290
SS7 and IP7, LIM, MIM, and MPL Card Replacement, 0338:A-17
SS7 Destination assigned to non-SS7 linkset, 0177:2-254
SS7 LIM, MIM, and MPL Card Replacement, 0338:A-17
SS7 linksets, 0120:3-3
SS7 Message Rejection Due to Screening (EAGLE 22.0), 0347:5-86
SS7 over High-Speed Signaling Link (EAGLE 23.0), 0347:5-87
SS7 parameters cannot be specified for IP7 link, 0177:2-629
SS7 signaling links, 0097:6-4, 0097:6-7, 0097:6-21
SS7ANSI, 0097:6-7, 0097:6-20
ss7gx25, 0097:2-11
SS7IPGW
 activate signaling link, act-slk, 0100:3-67, 0100:3-119, 0100:3-136, 0100:3-158, 0100:3-178,

0100:3-179, 0100:3-200, 0100:3-201, 0100:3-306, 0100:3-309, 0100:3-329, 0100:3-333, 0188:4-19,
 0188:4-20, 0188:4-35, 0190:4-19, 0190:4-35, 0193:4-19, 0193:4-20, 0193:4-35
 display card status, rept-stat-card, 0100:3-117, 0100:3-132, 0100:3-156
 display signaling link status, rept-stat-slk, 0100:3-116, 0100:3-119, 0100:3-131, 0100:3-136,
 0100:3-154, 0100:3-158, 0100:3-178, 0100:3-179, 0100:3-200, 0100:3-201, 0100:3-307, 0100:3-309,
 0100:3-329, 0100:3-333, 0100:3-431, 0100:3-441, 0188:4-20, 0190:4-20, 0193:4-20
 ss7ipgw, 0025:3-20, 0100:2-4, 0100:2-22
 SS7IPGW / IPGWI cards must be inhibited to change SYNC, 0177:2-661
 SS7-Over-IP Gateway for Point-to-Point Links (EAGLE 1.0), 0347:5-88
 SSEL parameter requires LNP feature, 0177:2-606
 SSF, 0193:1-15
 SSH, 0195:1-12
 SSH Client Errors, 0197:2-109
 SSH Connection Errors, 0197:2-118
 SSH Error Codes, 0197:2-105
 SSH failure to open the channel for the SSH connection with the server - Error code 628, 0197:2-109
 SSH failure to setup the channel for the SSH connection with the server - Error code 629, 0197:2-109
 SSH failure to setup the IO with the server - Error code 627, 0197:2-109
 SSH failure to verify the SSH client host key - Error code 630, 0197:2-109
 SSH Host Keys Loaded, 0338:3-978
 SSH Host Keys Regenerated, 0338:3-977
 SSH Secure Shell, 0195:1-12
 SSH Setup Errors, 0197:2-118
 SSH user authentication failure - Error code 631, 0197:2-110
 SSH, the Secure Shell: The Definitive Guide, 0197:2-125
 SSH/SFTP Error Codes, 0197:2-105
 SSH/SFTP tried to close a connection that is already closed - Error code 678, 0197:2-116
 SSH/SFTP tried to set the packet size twice - Error code 680, 0197:2-117
 SSH_FXP_READLINK request failure - Error code 613, 0197:2-108
 SSH_FXP_REALPATH request failure - Error code 612, 0197:2-108
 SSHD Server, 0197:2-115, 0197:2-118, 0197:2-122
 SSHD Server Verification procedure, 0197:2-122
 sshotools.xml, 0197:2-116
 SSN, 0099:2-90, 0099:2-112, 0099:3-29, 0099:3-59, 0099:4-36, 0099:4-61, 0188:1-13, 0190:1-13, 0193:1-15,
 0195:1-12, 0195:5-23, 0195:5-24, 0195:5-26, 0195:5-30, 0195:5-31, 0195:5-33, 0195:5-35, 0195:5-37,
 0195:5-38, 0195:5-40, 0195:5-46, 0195:5-51, 0288:3-38, 0288:3-39, 0288:3-41, 0288:3-43, 0288:3-45,
 0288:3-46, 0288:3-49, 0288:3-50, 0288:3-51, 0348:1-13
 ssn, 0097:2-25, 0100:3-252, 0348:3-38, 0348:3-41
 SSN can only be specified when XLAT=DPCSSN, 0177:2-188
 SSN cannot be specified without a point code, 0177:2-188
 SSN discrimination, 0188:2-22
 SSN does not exist for given remote point code, 0177:2-187
 SSN for ITU-I and ITU-N True Point Codes must be the same, 0177:2-771
 SSN is not allowed unless SI is 3, 0177:2-624
 SSN must be 1 if NSFI=AFTPC, 0177:2-198
 SSN must be in SS-APPL table when PC is true point code, 0177:2-581
 SSN must be specified for new values of XLAT/RI, 0177:2-181
 SSN must be specified when XLAT=DPCSSN, 0177:2-197
 SSN not allowed with OPC, CICS, and CICE, 0177:2-635
 SSN required if SI is 3, 0177:2-620
 SSN value must be LNP SSN or INP SSN, 0177:2-574
 SSN / TYPE combination already exists, 0177:2-675

Master Index

SSN /TYPE combination does not exist, 0177:2-675
SSNE should be greater than SSN, 0177:2-437
SSNs, 0347:5-20
SSO parameter is not compatible with True PC, 0177:2-538
SSP, 0188:1-13, 0190:1-13, 0193:1-15, 0195:1-12
SSP measurements
 LNP—Measurements (22.0), 0347:4-71
SSP point code, 0188:3-2
SSPI/SSPN, 0190:3-2, 0193:3-16
SST possible values, 0145:A-3
ST, 0193:1-15
ST3, 0224:A-28
Stage 1 loading, 0188:2-27
stage 1 loading, 0190:2-39
Stages of INP Execution, 0193:2-21
Stand-Alone Eagle G-Flex Relay Function, 0188:2-17
Stand-alone Eagle G-Flex Relay Function
 enhanced commands, 0347:3-16
 limitations, 0347:3-19
 new commands, 0347:3-13
 upgrade considerations, 0347:3-18
standard, RFC 1587 network, 0178:2-7, 0288:2-29
STANDBY, 0178:3-7, 0183:3-7, 0183:3-9
standby, 0190:5-2, 0195:4-2
standby database, 0348:2-7
Standby ELAP
 see Active / Standby
standby EPAP, 0190:2-35, 0190:2-42, 0190:3-15, 0193:2-4, 0193:3-9, 0195:3-14
standby EPAP RTDB, 0190:2-35
standby MASP, 0347:5-11
Standby MASP allowed, 0338:3-593
Standby MASP has not finished initializing, 0177:2-163
Standby MASP inhibited, 0338:3-592
Standby MASP is inhibited, 0177:2-699
Standby MASP is isolated, 0177:2-162
Standby MASP is not available, 0177:2-407
standby mode, 0188:2-8
Standby OAM must be equipped with E586 hardware, 0177:2-554
Standby TDM failure, 0338:3-136
Standby TDM failure cleared, 0338:3-137
Standby TDM in unknown upgrade mode, 0177:2-524
Start ELAP Software, 0178:3-14
Start EPAP Software, 0183:3-14
Start PDBA Software, 0183:3-55
Starting address/location must be specified, 0177:2-442
starting bulk load, 2339:6-9
Starting the FTRA application, 0197:2-4
STAT, 0099:2-90, 0099:2-112, 0099:3-29, 0099:3-59, 0099:4-36, 0099:4-61, 0195:5-23, 0195:5-24, 0195:5-26,
 0195:5-30, 0195:5-31, 0195:5-33, 0195:5-35, 0195:5-37, 0195:5-38, 0288:3-38, 0288:3-39, 0288:3-41,
 0288:3-43, 0288:3-45, 0288:3-46, 0288:3-49, 0288:3-50, 0288:3-51
State Transitions during Start-Up, 0188:5-8, 0190:5-8, 0193:5-11, 0195:4-8
statistics, 0188:2-25

status

- DSM memory capacity, 0178:4-7, 0183:4-9
- DSM Status Requests, 0178:4-4, 0183:4-3
- DSM-ELAP Link alarms, 0178:4-16
- DSM-EPAP Link alarms, 0183:4-18
- ELAP Able/Unable, 0178:2-10
- ELAP-to-DSM connection, 0178:4-16
- EPAP-to-DSM connection, 0183:4-18
- Hourly Maintenance Report, 0183:4-15
- reporting, DSM system, 0183:4-8
- reporting, G-Flex, 0183:4-9
- reporting, G-Port, 0183:4-9
- reporting, INP, 0183:4-9
- reporting, loading mode support, 0183:4-9
- status command, 0348:3-51
- Status field, 0178:3-7, 0183:3-7, 0183:3-9
- Status Indicators (SI), 0212:3-142
- status message, 0190:2-38
- status messages, 0188:2-11
- status of DSMs, 0188:5-3
- Status Refresh Time
 - , 0183:3-139
- status reporting and alarms, EPAP, 0348:2-9
- STC, 0097:6-3, 0097:6-4, 0097:6-5, 0097:6-6, 0097:6-7, 0097:6-8, 0097:6-9, 0097:6-10, 0097:6-11, 0097:6-15, 0097:6-16, 0097:6-19, 0097:6-20, 0097:6-23, 0097:6-24, 0097:6-25, 0097:6-26, 0097:6-27, 0097:6-28, 0097:6-30
 - dual-slot, 0097:6-4, 0097:6-7, 0097:6-8, 0097:6-19, 0097:6-21, 0097:6-23
 - single-slot, 0097:6-4, 0097:6-7, 0097:6-8, 0097:6-19, 0097:6-21, 0097:6-23
- STC Network Available, 0338:3-575
- STC Network Unavailable, 0338:3-574
- Stdby security log - upload required, 0338:3-253
- steps to activate G-Flex, 0188:4-1, 0190:4-1
- steps to activate INP, 0193:4-1
- STIME must be earlier or equal to ETIME, 0177:2-433
- stop bits, 0338:5-64, 2970:4-7, 2970:6-11
- Stop button, Update Validation Complete window, 0197:2-85
- Stop ELAP Software, 0178:3-15
- Stop EPAP Software, 0183:3-15
- Stop on error box
 - Update Tables window, 0197:2-80, 0197:2-83, 0197:2-92, 0197:2-93, 0197:2-94
- Stop on error box Checked
 - Command File Selected
 - Update Tables window, 0197:2-83
- Stop PDDBA Software, 0183:3-56
- Stop Without Sending or Editing a Command File, 0197:2-87
- storage components, MPS Server, 0212:4-27
- Store button, 0197:2-58, 0197:2-65, 0197:2-75
- STP, 0188:1-13, 0188:2-2, 0190:1-1, 0190:1-13, 0193:1-15, 0195:1-13, 0348:1-13
 - FTRA IP connection
 - secure, 0197:2-19, 0197:2-24
 - Retrieve Database Tables, 0197:2-56
 - selecting current, 0197:2-4

Master Index

STP Added window, 0197:2-24
STP administrative updates, 0188:2-25
STP audit requirement, 0188:2-25
STP Configuration Record, 0197:2-16, 0197:2-17, 0197:2-18, 0197:2-20, 0197:2-25, 0197:2-27, 0197:2-29, 0197:2-30, 0197:2-31, 0197:2-32, 0197:2-33, 0197:2-38, 0197:2-39, 0197:2-40, 0197:2-41, 0197:2-42, 0197:2-44, 0197:2-45, 0197:2-50
 Adding, 0197:2-20, 0197:2-50
 Deleting, 0197:2-41
 Displaying, 0197:2-25
 FTRA 1.0, 0197:2-31
 FTRA 2.0, 0197:2-31, 0197:2-32
 Modifying, 0197:2-38, 0197:2-45, 0197:2-50
 testing, 0197:2-33
STP Configuration Record - FTRA 1.0
 Adding, 0197:2-20, 0197:2-21, 0197:2-22, 0197:2-23, 0197:2-24
STP Configuration Record - FTRA 2.0
 Adding, 0197:2-20, 0197:2-21, 0197:2-22, 0197:2-23, 0197:2-24
STP Connection Configuration, 0197:2-1
 Database, 0197:2-16, 0197:2-18, 0197:2-19, 0197:2-20, 0197:2-24, 0197:2-42
 Menu, 0197:2-13, 0197:2-16
 Menu window, 0197:2-16, 0197:2-17, 0197:2-18, 0197:2-20, 0197:2-25, 0197:2-29, 0197:2-33, 0197:2-38, 0197:2-41, 0197:2-42, 0197:2-43, 0197:2-106, 0197:2-123, 0197:2-124
 FTRA 1.0, 0197:2-16
 FTRA 2.0, 0197:2-51
 FTRA 2.0 or greater, 0197:2-16, 0197:2-17
STP Connection Configuration Menu
 Add button, 0197:2-1, 0197:2-18, 0197:2-20, 0197:2-24
 Close button, 0197:2-18, 0197:2-27, 0197:2-29
 Delete button, 0197:2-18, 0197:2-27, 0197:2-29, 0197:2-42
 FTP Password Field, 0197:2-18, 0197:2-24
 FTP UserName Field, 0197:2-18, 0197:2-23
 IP Address, 0197:2-18, 0197:2-123, 0197:2-124
 Backup - FTRA 2.0, 0197:2-22
 Backup - FTRA 2.0 or greater, 0197:2-18
 Primary - FTRA 2.0, 0197:2-22
 Primary - FTRA 2.0 or greater, 0197:2-18
 IP Address - FTRA 1.0, 0197:2-22
 IP Address Field
 Backup - FTRA 2.0 or greater, 0197:2-18, 0197:2-22
 Primary - FTRA 2.0 or greater, 0197:2-17, 0197:2-22
 IP Address Field - FTRA 1.0, 0197:2-17, 0197:2-22
 Modify button, 0197:2-18, 0197:2-38, 0197:2-39
 Refresh button, 0197:2-18, 0197:2-25, 0197:2-27, 0197:2-29, 0197:2-31, 0197:2-41
 Secure Connection Box - FTRA 2.0 or greater, 0197:2-19, 0197:2-24, 0197:2-40, 0197:2-45, 0197:2-50, 0197:2-51
 Select button, 0197:2-18, 0197:2-29
STP Name drop down list, 0197:2-18, 0197:2-25
 FTRA 1.0, 0197:2-25, 0197:2-27
 FTRA 2.0, 0197:2-25, 0197:2-26, 0197:2-27, 0197:2-28
STP Name Field, 0197:2-4, 0197:2-17, 0197:2-18, 0197:2-20, 0197:2-25, 0197:2-29
 STP name typed
 FTRA 1.0, 0197:2-29

FTRA 2.0, 0197:2-29, 0197:2-30
 STP Password Field, 0197:2-18, 0197:2-23
 STP UserName Field, 0197:2-18, 0197:2-22
 Test button, 0197:2-18, 0197:2-27, 0197:2-29, 0197:2-33
 Use STP and FTP UserNames, Passwords for all STPs Box, 0197:2-19, 0197:2-20, 0197:2-38,
 0197:2-39, 0197:2-40
 STP Connectivity Test, 0197:2-1
 STP Data Modified window, 0197:2-39, 0197:2-41
 STP database updates, 0188:5-7
 STP database updates sent, 0188:2-20
 STP functions, 0188:2-17
 STP LAN Feature (EAGLE 20.0), 0347:5-89
 STP Name, 0197:2-17, 0197:2-18, 0197:2-19, 0197:2-20, 0197:2-24, 0197:2-25, 0197:2-26, 0197:2-27,
 0197:2-29, 0197:2-32, 0197:2-38, 0197:2-42, 0197:2-43, 0197:2-44
 entering, 0197:2-29
 STP Name does not exist error message, 0197:2-32
 STP Name drop down list, 0197:2-18, 0197:2-25
 FTRA 1.0, 0197:2-25, 0197:2-27
 FTRA 2.0, 0197:2-25, 0197:2-26, 0197:2-27, 0197:2-28
 STP Name Field, 0197:2-4, 0197:2-17, 0197:2-18, 0197:2-20, 0197:2-25, 0197:2-29
 STP name typed
 FTRA 1.0, 0197:2-29
 FTRA 2.0, 0197:2-29, 0197:2-30
 STP options HMUXABUS or HMUXBBUS must be set=yes, 0177:2-720
 STP pair replacement
 multiple point code support, 0120:2-56
 STP Password Field, 0197:2-18, 0197:2-23
 STP Selection Change window, 0197:2-18, 0197:2-43, 0197:2-44
 STP System Totals (SYSTOT) Measurements, 0338:4-13
 STP True PC and EIR subsystem do not exist in MAP table, 0177:2-768
 STP True PC and INP SSN do not exist in MAP table, 0177:2-691
 STP True PC and LNP SSN do not exist in MAP table, 0177:2-494
 STP True PC does not exist in MAP table, 0177:2-493
 STP UserName Field, 0197:2-18, 0197:2-22
 STPLAN
 LNP—Impact of LNP on Other Features (22.0), 0347:4-68
 STPLAN capacity normal, card(s) abnormal, 0338:3-227
 STPLAN connection available, 0338:3-233
 STPLAN connection unavailable, 0338:3-231
 STPLAN is available, 0338:3-226
 STPLAN is removed, 0338:3-230
 STPLAN not available, 0338:3-229
 STPLAN Port to DCM (EAGLE 26.0), 0347:5-91
 hardware requirements, 0347:5-91
 STPLAN with Default Router (EAGLE 23.0), 0347:5-92
 changed commands, 0347:5-94
 STPOPTS HMUXTVG must be turned on for this feature, 0177:2-537
 Stratum-3 (ST3), 0212:3-139, 0212:3-143
 strict host key checking, 0197:2-46
 strict host key flag, 0197:2-46
 String Data Dump, 0338:3-692, 0338:3-736
 String pattern nonconformance, alphabetic - <parm>, 0177:2-17

Master Index

String pattern nonconformance, alphanumeric - <parm>, 0177:2-17
String pattern nonconformance, numeric - <parm>, 0177:2-18
String-Based Messages, 0348:2-10
sub, 0193:2-11, 0193:2-22
SUBNETDLEN must be set before Subnet ID may be entered, 0177:2-827
SUBNETID already exists in SUBNETID table, 0177:2-824
SUBNETID does not exist in SUBNETID table, 0177:2-824
SUBNETID table is full, 0177:2-823
SUBNETIDLEN may only be changed if SUBNETID table is empty, 0177:2-826
Subpath Field, 0197:2-52
subscriber, 0193:2-11
Subscriber Data Provisioning, 0188:2-6, 0190:2-32
Subscriber Data Provisioning Architecture, 0188:2-7, 0190:2-32
subscriber data provisioning architecture, 0190:2-32
subscriber database lookup, 0193:2-20
Subscriber Identity Module, 0188:2-2, 0190:2-2
subscription network, 0190:2-7
subscription version, 2339:5-10
Subscriptions menu, 0178:3-41, 0178:3-49
subsystem alarms, 0188:5-14
Subsystem Application, 0195:5-23, 0195:5-27, 0195:5-29, 0195:5-30, 0195:5-32, 0195:5-33, 0195:5-37,
0288:3-38, 0288:3-42, 0288:3-43, 0288:3-46, 0288:3-50, 0288:3-51
Subsystem must be in opposite state of change, 0177:2-478
Subsystem must be inhibited before it can be deleted, 0177:2-479
Subsystem must be inhibited before it can be OFFLINE, 0177:2-478
Subsystem Number, 0195:5-23, 0195:5-24, 0195:5-30, 0288:3-38, 0288:3-39, 0288:3-43, 0347:4-88
subsystem numbers, 0188:2-18
Subsystem Related UIMs, 0193:5-23
Subsystem Relative Cost (RC) must be less than its mate, 0177:2-427
Subsystem table for MPC is full, 0177:2-177
Subsystem table for primary remote point code is full, 0177:2-186
subsystem to entity mapping, 0188:2-31
Subsystem UIMs, 0193:5-23
Success message, 0178:B-19
sufficient memory, 0188:5-11
Sun Microsystems, 0197:2-5, 0197:2-9
Sun StorEdge
 D1000 Disk Systems, 0025:4-10
Sun Ultra
 Enterprise 450 servers, 0025:4-10
Sun Ultra 5
 standard hardware component, 0025:4-10
Support - contacting the Customer Care Center, 0097:1-10, 0098:1-10, 0099:1-8, 0100:1-9, 0119:1-11,
0120:1-8, 0142:1-8, 0197:2-3, 0197:2-5, 0197:2-48, 0197:2-105, 0197:2-106, 0197:2-107, 0197:2-108,
0197:2-109, 0197:2-110, 0197:2-111, 0197:2-112, 0197:2-113, 0197:2-114, 0197:2-115, 0197:2-116,
0197:2-117, 0197:2-118, 0197:2-119, 0197:2-120, 0197:2-121, 0288:1-9
Support 12 Million Ported Numbers (EAGLE 24.0), 0347:5-95
 LNP DB Audit — End of Audit Report, 0347:5-97
Support 12 Million Ported Numbers (EAGLE 25.0), 0347:5-97
Support Changing the Linkset Name, 0347:5-98
Support for LSMS Audit Enhancements (EAGLE 26.1
 limitations, 0347:5-106

- Support for LSMS Audit Enhancements (EAGLE 26.1), 0347:5-99, 0347:5-105
 - Auditing the Eagle via High-Speed Audit, 0347:5-100
 - component interaction scenario, 0347:5-102
 - new commands, 0347:5-101, 0347:5-105
 - over OAP serial channel, 0347:5-105
 - via enhanced bulk download, 0347:5-105
- Support for Matching Self-ID Rule in SEAS CHG-SID (EAGLE 22.0), 0347:5-106
- Support for Provisioning Multiple EPAPs (Release 29.0), 0347:5-107
- Support for Secure Gateway Functionality through IP7 7.0 (Release 29.0), 0347:5-110
- Support for the CLLI Parameter for Adding or Changing Linksets (EAGLE 22.0), 0347:5-110
- Support for the New Linkset Name Parameter for Changing the Attributes of a Route (EAGLE 22.0), 0347:5-111
- Support for Up to 41 IPLIMx DCMs (IP7 2.2), 0347:5-112
- Support LSMS Disaster Recovery (EAGLE 23.1), 0347:5-112
 - auditing OAP database, 0347:5-113
- Support of E1 Interface for SS7 Signaling Links (Optional) (EAGLE 22.2), 0347:5-113
- Support of E1 Interface for SS7 Signaling Links (Optional) (EAGLE 24.0), 0347:5-113
 - upgrade considerations, 0347:5-114
- Support of E1 Master Clock Interface for SS7 Signaling Links (Optional) (EAGLE 22.2), 0347:5-114
- Suppression of Gateway Measurements on Non-Gateway Linksets (EAGLE 25.0), 0347:5-114
- SVC-Automatic, 0097:2-4, 0347:5-179
- SVC-Incoming, 0097:2-4
- SVCR, 0347:5-179
- Swap Space, 0096:3-16, 2712:3-13
- switch
 - replace, 0095:7-4, 2969:7-7
- switch telephone service, 0193:2-1
- switchactn, 0348:3-8
- Switchover, 0348:3-48
 - command, 0348:3-48
 - request message, 0348:3-50
 - response message, 0348:3-50
 - response return codes, 0348:3-50
- switchover command, 0348:3-48
- switchover operation, 0347:5-11
- Switchover PDBA Status, 0183:3-54
- switchover, ELAP
 - Active/Standby, 0178:2-5
- switchover, EPAP
 - Active/Standby, 0183:2-6
- sync, 0100:3-115, 0100:3-122
- Sync network, ELAP
 - configure IP addresses, 0178:5-18
 - description, 0178:2-4, 0178:2-8
 - IP addresses, 0178:2-8
- Sync network, EPAP
 - configure IP addresses, 0183:5-20
 - description, 0183:2-4, 0183:2-9
 - IP addresses, 0183:2-9
- synchronizes the RTDBs, 0188:2-13
- Synchronous DSM Report, 0348:4-15
- syntax checking, 0178:3-11, 0183:3-11

Master Index

- Syntax Error Found, 0177:2-632
- syscheck, 0096:3-11, 2712:3-8
 - running
 - using the GUI, 0096:A-5, 2712:A-6
 - using the syscheck login, 0096:A-7, 2712:A-8
- syscheck, overview, 0096:3-15, 2712:3-12
- system
 - hardware verification, DSM, 0183:4-4
 - status reporting, DSM, 0183:4-8
- system administration procedures, 0142:4-1
- System Administrator's Guide, 0212:1-18, 0243:1-18
- System Alarm Levels, 0338:3-3
- System Architecture, 0348:2-6
- system architecture, PDBI/ PDBA/ EPAP, 0348:2-6
- System busy - Repeat later, 0177:2-420
- System busy - try again later, 0177:2-147
- System Clock, 0025:3-12, 0212:2-15
- system clock connectors, 0212:3-26, 0212:3-32
- system clocks
 - High Speed Master Timing (26.0), 0347:3-60
- System Configuration Manager, 0193:5-6
- System Debug Services (SDS) Commands, 0188:3-1, 0190:3-1, 0193:3-15
- system environment variable, 0197:2-7
- System error - revert to mandatory in-pattern specification, 0177:2-18
- System error - software - an attempted buffer overrun has been detected by the SEAS UPL parser (C<col>), 0177:2-508
- System Ground, 0224:4-17
- system hardware verification, DSM, 0178:4-5
- System Health Check
 - status and alarm reporting, 0178:4-2, 0183:4-1
- System IP TPS normal, 0338:3-199
- System IP TPS threshold exceeded, 0338:3-194
- System Log, 0197:2-13, 0197:2-99, 0197:2-100, 0197:2-101, 0197:2-102, 0197:2-103
 - Clearing the Display, 0197:2-99, 0197:2-100
 - closing, 0197:2-99, 0197:2-103
 - Print window, 0197:2-101
 - Printing, 0197:2-99, 0197:2-101
 - Save window, 0197:2-102, 0197:2-103
 - saved file confirmation window, 0197:2-103
 - saving to a file, 0197:2-99, 0197:2-102
- System Log window, 0197:2-99, 0197:2-100, 0197:2-101, 0197:2-102, 0197:2-103
 - Cancel button, 0197:2-101
 - File menu, 0197:2-99, 0197:2-100
- System maintenance log, 0338:1-16
- System Maintenance Unsolicited Output Message Group, 0338:D-2
- System Meas limit exceeded for LSONISMT, 0338:3-645
- System Meas. Limit exceeded for LRN, 0338:3-964
- System Meas. Limit exceeded for LSDESTNI, 0338:3-650
- System Meas. Limit exceeded for LSORIGNI, 0338:3-649
- System Meas. Limit exceeded for NPANXX, 0338:3-965
- System Meas. Limit exceeded for ORIGNI/ NINC, 0338:3-651
- system point code, 0188:4-10, 0190:4-11, 0193:4-11

system recovery, 0183:3-47
 System release alarm cleared, 0338:3-215
 System release GPL(s) not approved, 0338:3-216
 System release version unknown, 0338:3-217
 System Reports Analysis, 0338:2-17
 system requirements
 48 Million Numbers (27.0), 0347:2-12
 System SCCP TPS Capacity Exceeded, 0338:3-548
 System SCCP TPS Threshold exceeded, 0338:3-416
 system security
 command classes, 0145:4-17
 intrusion alert, 0145:4-18
 login security checks, 0145:4-17
 system self-identification, 0188:4-9, 0190:4-10, 0193:4-10
 System serial number entered is invalid, 0177:2-561
 system serial number has not be locked, 0177:2-483
 System serial number is already locked in database, 0177:2-561, 0177:2-578
 System Status Reporting, 0188:5-4, 0190:5-4, 0193:5-6, 0195:4-4
 System total reports, 0338:4-13
 system unit
 front view, 0212:4-37
 System-Wide GSM MAP Screening Options
 Changing, 0097:5-56, 0097:5-58

T

T<#> (domain) must be between <min> and <max>, 0177:2-414
 T1 4-link monitor configuration window, 0212:B-3
 T1 card location is unequipped, 0177:2-320
 T1 is assigned to card, 0177:2-321
 T1 MIM, 0097:6-7
 T1 monitor applique, 0212:B-2
 T1 Port test command in progress, 0177:2-582
 T1 Port test command not in progress, 0177:2-717
 T1 TS value must be specified in the range (0-23), 0177:2-324
 T-1000, 0025:5-1, 0212:5-3
 T1000 Fan Orientation Wiring Diagram, 0243:C-83
 T1100
 specifications, 2969:3-9
 T1PORT specified by T1LOC is not equipped, 0177:2-322
 Table copy command already in process, 0177:2-9
 Table Expansion
 XGTT, 0099:2-43, 0099:2-47, 0099:2-48, 0099:3-26, 0099:4-32, 0099:4-33, 0099:A-17, 0099:A-18,
 0099:A-19, 0099:A-20, 0099:A-21, 0099:A-23, 0099:A-24, 0099:A-25, 0099:A-26, 0099:A-39
 XGTT - Enabling, 0099:A-17
 XMAP, 0099:2-43, 0099:2-46, 0099:2-48, 0099:2-84, 0099:2-85, 0099:2-121, 0099:A-27, 0099:A-28,
 0099:A-29, 0099:A-30, 0099:A-31, 0099:A-33, 0099:A-34, 0099:A-35, 0099:A-39
 XMAP - Enabling, 0099:A-27
 Table full - a maximum of 256 TYPE=SD MICs are allowed, 0177:2-450
 Table is full, no more entries allowed, 0177:2-343
 TALI "A" Link Connectivit, 0347:5-115
 TALON Development Kit, Release 2.0 (IP7 2.0), 0347:5-118

Master Index

Tape, 0212:4-35
tape drive
 description, 0212:4-29
 specification, 0212:4-27
Target bus must be inhibited, 0177:2-441
Target card is not a DSM card with VSCCP appl, 0177:2-796
Target card is not in Active state, 0177:2-796
Target drive capacity must be sufficient to perform request, 0177:2-591
Task Scheduler
 Windows, 0197:2-75, 0197:2-77
tasks, EPAP
 descriptions, 0183:2-27
 overview, 0183:2-8
TCAP, 0097:1-2, 0097:2-2, 0188:1-13, 0190:1-13, 0193:1-15, 0195:1-13
TCOA, 0224:A-32
TCP, 0188:1-13, 0190:1-13, 0193:1-15, 0195:1-13, 0348:1-13
TCP Out of Order, 0197:2-125
TCP Packet Delay, 0197:2-125
TCP Packet Error, 0197:2-125
TCP Packet Errors, 0197:2-125
TCP Packet Loss, 0197:2-125
TCP/IP data link, 0347:5-10
TCP/IP Link Provisioning, 0097:6-5
TCP/IP parameters, 0142:4-138
TCP/IP socket, 0188:2-11, 0190:2-37
TDM, 0193:1-15, 0195:5-16, 0197:2-3, 0212:3-18, 0212:3-21, 0212:3-37, 0224:2-5, 0243:1-39, 0348:1-13, 2970:4-4
TDM card
 as part of MASP, 0145:4-2
 connection of terminals and printers to, 0145:4-5
TDM does not support Global Timing Interface, 0177:2-316
TDM fixed disk, 0188:2-20
TDM fixed disks, 0190:2-52
TDM technical specifications, 0212:3-54
TDM-GTI, 0224:2-5
TDM-resident data tables, 0188:5-5, 0190:5-5, 0193:5-8, 0195:4-5
Technical Assistance - contacting the Customer Care Center, 0097:1-10, 0098:1-10, 0099:1-8, 0100:1-9, 0119:1-11, 0120:1-8, 0142:1-8, 0197:2-3, 0197:2-5, 0197:2-48, 0197:2-105, 0197:2-106, 0197:2-107, 0197:2-108, 0197:2-109, 0197:2-110, 0197:2-111, 0197:2-112, 0197:2-113, 0197:2-114, 0197:2-115, 0197:2-116, 0197:2-117, 0197:2-118, 0197:2-119, 0197:2-120, 0197:2-121, 0288:1-9
Technical Assistance Centers, 0183:1-9, 0188:1-9, 0338:1-10
Technical Reference Documents, 0212:1-19, 0243:1-19
Technical Services, 0190:1-9, 0212:1-21, 0243:1-22
Tekelec 1000, 0025:1-6, 0212:4-11
 Manual, 0243:1-9
Tekelec 1000 Application Server Hardware Manual, 0243:1-9, 0243:1-19
Tekelec 1000 Applications Server, 0025:1-6, 0025:5-1, 0212:5-3
Tekelec 1000 APS, 0212:1-8
Tekelec 1000 AS main unit, replacement procedure, 0096:5-11
Tekelec 1100 AS main unit, replacement procedure, 2712:5-10
Tekelec Customer Care Center, 0224:1-22, 0243:1-23
Tekelec Signaling Products Hardware Manual, 0243:1-19

Tekelec Signaling Products Hardware Manual, 0212:1-18
 Tekelec Signaling Products Integrated Applications Installation Manual, 0212:1-18, 0243:1-19
 Tekelec Signalling Products Systems, 0025:1-2
 Tekelec Technical Services, 0195:1-8, 0212:1-23
 emergency response, 0347:1-13, 2339:1-14
 Tekeled 1000/1100, 0025:1-6
 Telephone Number, 0288:3-59, 0288:4-2, 0288:4-4, 0347:4-88
 telnet, 0193:2-6
 TELNET cannot be specified unless the IPSM card is equipped, 0177:2-145
 telnet client, 0347:3-128
 telnet connection - secure, 0142:1-2, 0142:B-1
 setup with the PuTTY client program, 0142:1-2, 0142:B-1
 TELNET Feature must be activated first, 0177:2-145
 telnet server, 0197:2-45
 telnet session, 0347:3-128
 Telnet terminal connection successful, 0338:3-689, 0338:3-974
 Telnet terminal type, 0142:4-55
 Telnet terminal TYPE can only be set to TELNET or NONE, 0177:2-126
 Telnet terminals, 0197:2-18, 0197:2-48, 0197:2-67
 telnet terminals, 0145:4-6
 Telnet to MPS, 0178:3-80, 0183:3-51
 Temp Key(s) expiration alarm cleared, 0338:3-479
 Temp Key(s) expiring soon, 0338:3-480
 Temp Key(s) have expired, 0338:3-481
 Temperature Alarm Thresholds - HC MIM - Changing, 0120:3-279
 temperature requirements, 0095:2-6, 2969:2-6
 temperature, checking, 0096:3-16, 2712:3-14
 template, frame, 0095:4-4, 2969:4-4
 Temporary Alarm Inhibiting and Offline Functions (EAGLE 25.0), 0347:5-119
 administration, 0347:5-124
 alarm system functionality, 0347:5-120
 changed commands, 0347:5-128
 customer use scenario, 0347:5-121
 maintenance, 0347:5-126
 Temporary FAK Alarm
 Clearing, 0099:A-12, 0142:A-36
 Temporary feature key is not allowed for the feature, 0177:2-468
 temporary key is un-available, 0177:2-577
 Ten GTA Lengths are supported per GTTSET, 0177:2-716
 Ten GTA Lengths are supported per TT, 0177:2-715
 Terminal already echoing to specified terminal, 0177:2-102
 Terminal Authority Violation, 0177:2-3
 terminal cable installation, 0224:5-107
 Terminal Cables, 0224:5-107
 terminal cables
 install, 2970:3-45
 route, 2970:3-46
 terminal characteristics
 changing, 0142:4-51
 terminal command class assignment
 changing, 0142:4-72
 terminal configuration

Master Index

- displaying, rtrv-trm, 2970:4-16, 2970:4-28
- Terminal Disk Module (TDM), 0224:5-81, 0338:A-47
- terminal disk module See TDM card, 0145:4-2
- Terminal enabled, 0338:3-131, 0338:3-975
- Terminal failed, 0338:3-133, 0338:3-976
- Terminal Id not entered, 0177:2-149
- terminal interfaces, 0188:3-2
- Terminal is currently inhibited, 0177:2-100
- Terminal is currently out of service, 0177:2-101
- Terminal is not equipped, 0177:2-150, 0177:2-161
- Terminal Not Responding, 0338:3-55
- Terminal Processor, 0212:3-52
- Terminal temporarily disabled. Excessive LOGIN failures, 0177:2-331
- Terminal temporarily disabled. Excessive UNLOCK failures, 0177:2-334
- Terminal type
 - EMSALM, 0142:4-56
 - KSR, 0142:4-55
 - MGMT, 0142:4-55
 - None, 0142:4-55
 - OAP, 0142:4-55
 - Printer, 0142:4-55
 - Telnet, 0142:4-55
 - VT320, 0142:4-55
- Terminals
 - EAGLE 5 SAS
 - Telnet, 0197:2-18, 0197:2-48, 0197:2-67
- terminals
 - arrow key operations, 0145:4-12
 - configuration of, 0145:4-3
 - connection to TDM, 0145:4-5
 - directing unsolicited messages to, 0145:4-15
 - EMSALM, 0145:4-8
 - telnet, 0145:4-6
 - VT320, 0145:4-3
- Terminals 1-16 cannot be set to TYPE=TELNET, 0177:2-128
- Terminate Active Sessions, 0178:3-107
- Terminate Active UI Sessions, 0183:3-137
- terminate connection, 0348:3-9
- Termination of Alarm, 0224:5-85
- terminology
 - MPS, 0096:2-4, 2712:2-3
 - Tekelec 1000 AS core platform, 0096:2-5
 - Tekelec 1100 AS core platform, 2712:2-4
- test
 - fan operation, 0338:5-99, 2970:3-71, 2970:6-48
 - fan operation (GR-376 EOAP), 0338:A-89
- Test and Maintenance Features, 0212:3-98
- Test button, 0197:2-18, 0197:2-27, 0197:2-29, 0197:2-33
- Test E1 and T1 Ports, 0338:3-72
- Test Fan Operation and Fan Alarm, 0338:A-89
- test mode, 0338:3-81
- Testing an STP Configuration Record, 0197:2-33

testing diodes, 0338:2-8
 text-based configuration, 0178:5-26, 0183:5-34
 text-based UI, 0178:3-2, 0178:5-26, 0183:2-27, 0183:3-2, 0183:5-2, 0183:5-34
 text-based User Interface, 0183:3-2
 TFA/ TFR pacing rate
 configuring, 0120:3-235
 TFATCABMLQ is invalid for C-link sets, 0177:2-373
 tfatcabmlq parameter, 0119:3-16, 0120:3-22, 0120:3-76, 0120:3-96, 0120:3-269, 0120:3-270, 0120:3-272
 TFATCABMLQ value exceeds number of links in link set, 0177:2-370
 TFATFRPR must be in increments of 100 msec, 0177:2-393
 TFCs
 ITU-I Networks Option - Configuring, 0120:3-276, 0120:3-278
 ITU-N Networks Option - Configuring, 0120:3-276, 0120:3-278
 The address family is not supported - Error code 47, 0197:2-119
 The address is already in use - Error code 48, 0197:2-119
 The alarms are already inhibited for this device, 0177:2-521
 The authentication method is NULL in the client software - Error code 632, 0197:2-110
 The Channel card must be on the same shelf as its E1 card., 0177:2-730
 The Channel card must be on the same shelf as its T1 card., 0177:2-318
 The CNCF feature must be on if CNCF is specified, 0177:2-593
 The connection timed out - Error code 60, 0197:2-120
 The connection timed out when SSH tried to connect to SSHD - Error code 682, 0197:2-118
 The connection was refused - Error code 61, 0197:2-120
 The connection was reset by the peer - Error code 54, 0197:2-120
 The current LSMS and the associated NSAP, PSEL and SSEL required, 0177:2-587
 The debug levels allowed for SSH protocol in openSSH is 0-9 - Error code 624, 0197:2-109
 The E1PORT at the specified location is already equipped, 0177:2-728
 The E1PORT at the specified location is not equipped, 0177:2-729
 The FEATURE/ ANSIGFLEX option combination is invalid, 0177:2-811
 The file name is already specified - Error code 596, 0197:2-106
 The Gateway Linkset specified already exists, 0177:2-403
 The Gateway Linkset table is full, 0177:2-401
 The GSM MAP Screening table is full, 0177:2-683
 The host is down - Error code 67, 0197:2-121
 The host was not specified in the SSH client on the EAGLE 5 SAS - Error code 659, 0197:2-113
 The hostname was not specified in the SSH client on the EAGLE 5 SAS - Error code 661, 0197:2-114
 The last active serial port cannot be inhibited, 0177:2-539
 The linkset is provisioned locally, 0177:2-402
 The linkset specified does not exist in the linkset table, 0177:2-403
 The linkset specified is not a Gateway Linkset, 0177:2-402
 The maximum number of SPCs has already been defined, 0177:2-646
 The maximum number of users is already defined, 0177:2-75
 The MPC feature must be ON before ITUDUPPC can be ON, 0177:2-672
 The network channel is down - Error code 691, 0197:2-118
 The network dropped the connection on reset - Error code 52, 0197:2-119
 The network has reset - Error code 685, 0197:2-118
 The network is down - Error code 62, 0197:2-121
 The network is unreachable - Error code 51, 0197:2-119
 The NONE value is not allowed in this case, 0177:2-551
 The NSFI / RI combination is invalid, 0177:2-201
 The NSFI is invalid for this screen type, 0177:2-203
 The operation is not supported on the socket - Error code 45, 0197:2-119

Master Index

The protocol family is not supported - Error code 46, 0197:2-119
The protocol is not available - Error code 42, 0197:2-119
The protocol is not supported - Error code 43l, 0197:2-119
The requested address cannot be assigned - Error code 49, 0197:2-119
The secure connection was closed by the remote server - Error code 669, 0197:2-115
The SFTP client failed to read the data from the file descriptor - Error code 616, 0197:2-108
The SFTP client received more data than expected - Error code 615, 0197:2-108
The SFTP connection is closed - Error code 598, 0197:2-106
The SFTP/SSH connection has been reset by the peer - Error code 687, 0197:2-118
The socket is already connected - Error code 56, 0197:2-120
The socket is not connected - Error code 57, 0197:2-120
The socket type is not supported - Error code 44, 0197:2-119
The SPC already exists, 0177:2-645
The specified card cannot be inhibited, 0177:2-153
The specified LOC only supports SLTC loopbacks, 0177:2-321
The specified overload level has already been defined, 0177:2-453
The specified overload level is not defined, 0177:2-444
The specified SLC is in use, 0177:2-43
The specified user identification is already defined, 0177:2-74
The specified user identification is not defined, 0177:2-75
The SSH client key length is invalid - Error code 667, 0197:2-114
The SSH client was unable to load the cipher type on the EAGLE 5 SAS - Error code 663, 0197:2-114
The SSH connection was refused by the remote server - Error code 683, 0197:2-118
The SSH/SFTP client on the EAGLE 5 SAS failed to read from the remote side - Error code 674, 0197:2-116
The SSH/SFTP client on the EAGLE 5 SAS failed to write to the remote side - Error code 679, 0197:2-117
The SSH/SFTP connection has been aborted - Error code 686, 0197:2-118
The SSH/SFTP socket is already connected - Error code 689, 0197:2-118
The SSH/SFTP socket is not connected - Error code 690, 0197:2-118
The SSHD server is unreachable - Error code 684, 0197:2-118
The SSHD/SFTP server connection host is down - Error code 692, 0197:2-118
The sum of the values for NPCFMTI must be equal to 14, 0177:2-572
The T1PORT at the specified location is already equipped, 0177:2-318
The T1PORT at the specified location is not equipped, 0177:2-319
The terminal state request was unanswered, 0177:2-47
Theory of Operation, 0025:3-14
There is a link already assigned to this port, 0177:2-43
There is no route to the host - Error code 65, 0197:2-121
third-party software
 Embedded OAP (24.0), 0347:2-139
This command is not valid when EGTT is ON, 0177:2-564
This function is not yet supported, 0177:2-196
THRES parameter valid only with CONVERTNET/CONVERTSTP, 0177:2-525
threshold monitoring, 0188:2-24, 0190:2-51
Thresholding of UIM Messages (EAGLE 25.0), 0347:5-129
 Changed Event Log Command, 0347:5-132
 creation of UIMs, 0347:5-129
 limitations, 0347:5-133
 new database administration commands, 0347:5-132
 upgrade considerations, 0347:5-132
Tie-wrap, 0224:4-17

Time Slot Counter, 0097:6-6
 Time Slot Counter Synchronization, 0025:3-14, 0097:6-6, 0097:6-10, 0097:6-11, 0212:2-18
 Time Stamping, 0097:6-6
 time zone
 select for ELAP, 0178:5-20
 select for EPAP, 0183:5-23, 0183:A-1
 UNIX files, 0178:1-2, 0178:5-20, 0178:A-1, 0183:5-23, 0183:A-1
 Timeout, 0177:2-439, 0183:3-138
 timeout, 0348:2-14, 0348:3-12, 0348:3-16, 0348:3-17, 0348:3-19, 0348:3-21, 0348:3-23, 0348:3-24,
 0348:3-25, 0348:3-26, 0348:3-28, 0348:3-29, 0348:3-39, 0348:3-43, 0348:3-45, 0348:3-49, 0348:3-50,
 0348:3-54, 0348:3-55, 0348:3-58, 0348:3-59, 0348:3-61, 0348:3-62
 timers
 default values, 0120:3-25
 Timeslot 16 on the E1 is in use, CAS = ON not allowed, 0177:2-729
 Timestamp Invalid, 0338:3-588
 Timestamp Valid, 0338:3-589
 Timing, 0212:3-115
 Timing Source must be specified if CHANBRDG=ON is specified, 0177:2-545
 Timing Systems Eagle STP/IP7 SG, 0025:3-12, 0212:2-15
 tinned ground, 0224:4-17
 TKLC, 0348:1-13
 TLNP and CNCF cannot be in the same action set, 0177:2-598
 TLNP and RDCT cannot be in the same action set, 0177:2-597
 TLNP feature must be ON, 0177:2-597
 TM Adaptation Layer Type 5 Common Part, 0338:1-18
 To change or delete SERV, it must have no LNP aliases, 0177:2-481
 To disable CRITALMINH, critical alarms cannot be inhibited, 0177:2-522
 TOCA, 0212:3-139, 0212:3-143, 0224:2-5, 0224:5-109, 0243:1-39
 TOCA Card, 0212:3-144
 TOLA Card, 0224:5-109
 Too many associations per card, 0177:2-740
 Too many associations per SLK, 0177:2-739
 Too many errors in this command, 0177:2-4
 Too many IP connection states per card, 0177:2-833
 Too many IP connections per card, 0177:2-621
 Too many nested cluster dstn entered, 0177:2-358
 Too many octets specified, only require 4 - <parm>, 0177:2-15
 too many parameters entered, 0177:2-417
 Too many parameters specified for <parm> block (C<col>), 0177:2-501
 Too many references: can't splice - Error code 59, 0197:2-120
 Too many sockets per SLK, 0177:2-629
 tools and equipment
 EOAP shelf, 2970:3-12, 2970:3-19, 2970:3-57, 2970:3-61, 2970:3-62
 tools required for FRU replacement, 0095:7-3, 2969:7-6
 tools, recommended
 installing heavy duty frame, 0095:4-3, 2969:4-3
 to install heavy duty frame, 0095:4-3, 2969:4-3
 Total Ethernet Capacity is greater than 100% for IP Node, 0177:2-263
 Total IPTPS for all linksets can't exceed system TPS limit, 0177:2-794
 TPC, 0193:1-15
 trace, 0190:3-2, 0193:3-16
 trace set on SCCP cards, 0188:3-2

Master Index

- traceroute, 0145:9-122
- track downloads in progress, 0188:5-3
- Traffic Measurements
 - Measurement periods, 0338:4-12
- traffic situations, 0188:2-11, 0190:5-2, 0195:4-2
- transaction
 - abort read, 0348:3-14
 - abort write, 0348:3-14
 - begin read, 0348:3-11
 - begin write, 0348:3-11
 - end read, 0348:3-13
 - end write, 0348:3-13
 - write, not active for PDBA switchover, 0348:3-48
- transaction boundaries, 0348:3-9
- transaction modes, 0348:3-9
- Transaction Service Module, 0338:A-30
- Transaction Services Module (TSM), 0212:3-99, 0338:A-30
- transition card, 0338:5-24, 2970:7-23
- transitions of DSM card, 0190:5-8, 0195:4-8
- Translation, 0212:3-20
- Translation PC is Eagle's, 0338:3-949
- Translation PC type is ANSI, 0338:3-950
- Translation Service Module (TSM), 0212:3-19
- Translation Service Modules (TSMs), 0212:3-9, 0212:3-18, 0212:3-28
- Translation Services Module, 0025:3-10, 0212:2-14
- Translation Type, 0188:2-22, 0288:3-22, 0288:3-23, 0288:3-25, 0288:3-30, 0288:3-32, 0288:3-33, 0288:3-59, 0288:3-60, 0347:4-87
- Translation TYPE already exists, 0177:2-191
- Translation TYPE defined as an alias, 0177:2-191
- Translation TYPE has an alias, 0177:2-194
- Translation Type is already in LNP database, 0177:2-474
- Translation TYPE is referenced by GTT entry, 0177:2-194
- Translation type mapping, 0099:2-40, 0099:2-44, 0099:3-2, 0099:4-2
- translation type mapping
 - LNP—Impact of LNP on Other Features (22.0), 0347:4-68
- Translation Type Mapping (EAGLE 21.0), 0347:5-134
 - new commands, 0347:5-135
- Translation TYPE must be specified, 0177:2-195
- Translation Type Name, 0288:3-22, 0288:3-23, 0288:3-32
- Translation Type Name is not in the LNP database, 0177:2-476
- Translation Type referenced in LNP database, 0177:2-476
- Translation TYPE specified does not exist, 0177:2-192
- Translation TYPEI already exists, 0177:2-685
- Translation TYPEI specified does not exist, 0177:2-687
- Translation TYPEN already exists, 0177:2-684
- Translation TYPEN specified does not exist, 0177:2-687
- Translation TYPEN24 already exists, 0177:2-552
- Translation TYPEN24 specified does not exist, 0177:2-684
- Translation Types, 0099:3-2
- translations, 0193:2-6
- Transport Log Params, 0183:3-102
- trap messages, 0190:3-2, 0193:3-15

- trap on CdPA GTA, 0188:3-2
- trap on CgPA SPC, 0188:3-2
- trap on E.214 MGT, 0188:3-2
- trap-and-trace function, 0190:3-1, 0193:3-15
- trap-and-trace MSUs on SCCP card, 0188:3-1
- trapcomm, 0100:3-122
- TRBL Queue is full, 0338:3-757
- trigger criteria, 0188:3-1, 0188:3-2, 0190:3-2, 0193:3-16
- trigger on DN and IMSI, 0188:3-1
- Triggerless LNP (EAGLE 24.0), 0347:5-136
 - commands, 0347:5-136
- TRM must be specified, 0177:2-418
- TRM parameter
 - chg-trm, 2970:4-4
- TRM parameter not valid for type-enttype combo, 0177:2-117
- troubleshoot
 - power cable
 - hard drive, 2970:7-5
- Trouble Detection, 0338:3-4
- troubleshoot
 - CD-ROM drive
 - power cable, 0338:5-8, 2970:7-5
 - hard drive card, 0338:5-8, 2970:7-5
 - power cable
 - hard drive, 0338:5-8
 - power supply card, 0338:5-7, 0338:5-18, 2970:7-4, 2970:7-17
 - processor card, 0338:5-7, 0338:5-20, 2970:7-4, 2970:7-19
- troubleshoot network interface and routing configuration, 0188:3-15
- troubleshoot private EPAP/DSM IP network, 0188:3-14
- troubleshooting network interface and routing configuration, 0190:3-19, 0193:3-13
- troubleshooting private EPAP/DSM IP network, 0190:3-18, 0193:3-13
- troubleshooting, DSM network
 - pass: cmd="netstat" command, 0183:4-14
 - pass: cmd="Ping" command, 0183:4-14
- Troubleshooting Procedures, 0197:2-122
- True PC already exists in MAP table, 0177:2-495
- true point code, 0120:2-2, 0188:4-8, 0190:4-10, 0193:4-10
- True Point Code can only have one mate, 0177:2-430
- True Point Code may not be routed to self, 0177:2-429
- truncated MSIN, 0188:2-33
- Try Double Quoting Parameter with '_', 0177:2-26
- TS not allowed when SEHSL feature has set Linkclass = Unchan, 0177:2-802
- TS value on the E1 already in use by a signaling link, 0177:2-727
- TS value on the T1 already in use by a signaling link, 0177:2-323
- TSC, 0097:6-6
- TSC Synchronization, 0097:6-6
- TSCSYNC must be ON before E5IS can be ON, 0177:2-704
- TSET parameter only valid if MODE = DCE, 0177:2-44
- TSM, 0188:1-13, 0190:1-14, 0195:1-13, 0212:3-21, 0212:3-37, 0224:2-5, 0224:B-20, 0243:1-39, 0243:B-4, 0347:4-61, 0348:1-13
- TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-137
 - changed commands, 0347:5-147

Master Index

- dependencies, 0347:5-150
- hardware requirements, 0347:5-149
- incremental loading, 0347:5-139
- limitations, 0347:5-150
- LNP audit, 0347:5-145
- maintenance, 0347:5-139
- new UIMs, 0347:5-147
- upgrade considerations, 0347:5-149
- warm restart, 0347:5-137
- TSM-GLS card replacement, 0338:A-34
- tst-bip, 0145:7-687
- tst-disk, 0145:7-688
- tst-dlk, 0145:7-691
- tst-e1, 0145:7-693, 0145:7-702, 0338:3-75
- tst-imt, 0145:7-695
- tst-slk, 0145:7-697
- tst-slk command, 0338:3-71
- tst-slk Support, 0338:3-71, 0338:3-72
- tst-t1, 0338:3-75
- TT, 0188:1-13, 0188:2-22, 0190:1-14, 0193:1-15, 0195:1-13, 0288:3-22, 0288:3-24, 0288:3-25, 0288:3-29, 0288:3-30, 0288:3-31, 0288:3-32, 0288:3-33, 0288:3-36, 0288:3-37, 0288:3-59, 0288:3-61, 0288:3-62, 0288:3-63
- tt map table full for LSN specified, 0177:2-361
- tt map table is full, 0177:2-361
- TT Mapping is not provisioned for this link set, 0177:2-362
- TT must be specified when enttype=tt, 0177:2-108
- TT parameter valid only when ENTTYPE=TT, 0177:2-118
- TT, TTN, & DV parameters are not allowed with ALIAS, 0177:2-480
- TTA cannot be specified for a direction of ITOA, 0177:2-746
- TTA must be specified for a direction of ATOI, 0177:2-721
- TTDM card
 - High Speed Master Timing (26.0), 0347:3-61
- TTI must be specified for a direction of ITOA, 0177:2-747
- TTI, NP, NAI cannot be specified for a direction of ATOI, 0177:2-835
- TTN, 0288:3-22, 0288:3-23, 0288:3-24, 0288:3-25, 0288:3-29, 0288:3-30, 0288:3-31, 0288:3-33, 0288:3-36, 0288:3-37, 0288:3-62
- TTN already in use, 0177:2-192
- TTN and TYPE do not correspond to each other, 0177:2-195
- TTN specified does not exist, 0177:2-192
- TUP must use DPC / SI route key if DPC is ANSI, 0177:2-669
- turn off
 - controlled features, 0145:5-87
 - LNP ELAP Configuration feature, 0145:5-88
- Turn off EISCOPY before changing PVN and PVNMask, 0177:2-584, 0177:2-732
- turn on
 - controlled features, 0145:5-87
 - LNP ELAP Configuration feature, 0145:5-88
 - LNP feature, 0145:6-131
- Turning Off the IGTTLS Feature, 0099:A-14
- turning On and Off Controlled Features, 0100:6-10
- TVG granter failed, 0338:3-376
- TVG granter recovered (Eagle system), 0338:3-378

two hole lug, 0224:4-9
 Two OAP terminals are already configured, 0177:2-347
 Two UIMs for One MSU, 0193:2-19
 two-character group code, 0183:2-14
 Two-Point IPLIMx (Eagle 27.1), 0347:5-159
 enhanced commands, 0347:5-159
 TXCO, 0212:3-143
 txnmode, 0348:3-9, 0348:3-16
 TYPE, 0195:5-16, 0288:4-5, 0288:4-20, 0288:4-21, 0288:4-22, 0288:4-23, 0288:4-25, 0288:4-26, 0288:4-27,
 0288:4-28, 0288:4-29
 type, 0348:3-12, 0348:3-31, 0348:3-36, 0348:3-40, 0348:3-44, 0348:3-46, 0348:3-53
 TYPE = SCCS and PRTY=NONE combination not allowed, 0177:2-51
 TYPE = VT320 and PRTY=NONE combination not allowed, 0177:2-47
 TYPE and SNUM/ENUM combination invalid, 0177:2-779
 TYPE does not exist in given SR, 0177:2-243
 TYPE matches existing TYPE in given SR, 0177:2-243
 Type of Service, 0100:2-39
 TYPE parameter
 chg-trm, 2970:4-4
 TYPE parameter value is invalid for this card, 0177:2-759
 type=dsm, 0188:4-15, 0188:4-22, 0188:4-30, 0190:4-16, 0190:4-22, 0190:4-30, 0193:4-16, 0193:4-22,
 0193:4-30
 types of networks, 0120:2-2
 Types of Routing Strategies Available
 Applications, 0347:4-174
 Changed Commands, 0347:4-181
 MTP Requirements, 0347:4-175
 Network Routing (EAGLE 26.0), 0347:4-174
 types of subscriber numbers, 0188:2-3

U

ualog, 0145:9-129
 UAM, 0188:1-13, 0190:1-14, 0193:1-15, 0195:1-13, 0348:1-13
 UAM 0368, 0288:3-83
 UAM 0429, 2339:8-4
 UAM 0431, 2339:8-4
 UAM formats, 0188:5-12
 UAM identifier, 0188:5-2
 UAM Troubleshooting Procedures, 0338:3-81
 UAMs
 alarm categories, 0178:4-15
 clearing alarm, 0178:4-15, 0183:4-18
 ELAP application, 0178:4-15
 ELAP-DSM, 0178:4-16
 MPS platform, 0178:4-15
 RTDB Audit, 0178:4-16, 0183:4-19
 UAMs from EPAP, 0188:5-12
 UAMs messages, 0195:4-12
 UAMs, EPAP
 description, 0183:4-18
 ublk-slk, 0145:7-703

Master Index

UDB, 0188:1-13, 0190:1-14, 0195:1-13
UDP, 0188:2-11, 0190:2-37, 0193:1-15, 0193:2-8, 0348:1-13
UDP - sending DSM status messages, 0188:2-11
UDP echo, 0097:3-13
UDT, 0193:1-15, 0195:1-13
UDT message, 0347:5-20
UDT Unit Data Transfer, 0195:1-13
UDTS, 0193:1-15, 0193:2-21
UDTS messages, 0188:2-22
UDTS Unit Data Transfer Service, 0195:1-13
UENG parameter is invalid for this card, 0177:2-757
UENG register must be specified, 0177:2-756
UIM, 0188:1-13, 0190:1-14, 0193:1-15, 0195:1-13, 0347:5-20, 0348:1-13
UIM - Unsolicited Information Message
 EAGLE 5 SAS, 0197:2-48, 0197:2-49, 0197:2-67
UIM 1493, 0197:2-48, 0197:2-49
UIM 1494, 0197:2-48, 0197:2-49
UIM issued, 0188:2-32
UIM message, 0188:2-18, 0190:2-47
UIM messages, 0188:5-15, 0190:5-15
UIM number does not exist in STP Trouble Text Table, 0177:2-586
UIM number does not exist in UIM Threshold table, 0177:2-484
UIM Redirect Unsolicited Output Message Group, 0338:D-26
UIM threshold
 configuring, 0142:4-116
UIM Troubleshooting Procedures, 0338:3-81
UIMs, 0193:5-23
 ITU MTP Restart (26.0), 0347:3-159
 ITU-TFR Procedure (26.1), 0347:3-162
 Multiple Point Code Support (EAGLE 26.05), 0347:4-150
Unable to access database. Severe database failure, 0177:2-171
Unable to access DB level, 0177:2-33
Unable to change adapter when assigned to an AS, 0177:2-738
Unable to change Network/Cluster dstn NCAI param, 0177:2-359
Unable to communicate with card at location, 0177:2-105
Unable to determine current connect status of card <card>, 0177:2-420
Unable to read the selected log, 0177:2-406
Unauthorized IP Access Message, 0183:3-139
Undefined, 0177:2-836
Undefined - Error code 601, 0197:2-107
Undefined SFTP/SSH error - Error code 643, 0197:2-111
Understanding Network Time Protocol, 0183:2-12
Understanding Universal Time Coordinated, 0183:2-11
Unexpected character(s) <data> after <parm> (C<col>), 0177:2-500
Unexpected disk access timeout, 0338:3-735
Unexpected response message error, 0177:2-662
Unexpected SSH_FXP_NAME - Error code 611, 0197:2-107
unexpected SSH_FXP_NAME - Error code 614, 0197:2-108
Unexpected SSH_FXP_STATUS error - Error code 644, 0197:2-111
Unexpected SSH2_FXP_ATTRS - Error code 610, 0197:2-107
unhb-alm, 0145:7-705, 0188:3-13, 0190:3-17, 0190:5-12, 0193:3-11, 0195:3-17
unhb-slk, 0145:7-710

Unistrut, 0224:3-19
 Unistrut Overhead, 0224:3-24
 Unit Data Transfer Service, 0193:2-21
 unit separator bracket, 0224:3-26
 universal time coordinated, 0096:2-19, 2712:2-17
 UNIX
 time zone files, 0178:1-2, 0178:5-20, 0178:A-1, 0183:5-23, 0183:A-1
 Unix Workstation Requirements, 0197:2-2
 Unknown cipher number on the SSH client on the EAGLE 5 SAS - Error code 666, 0197:2-114
 Unknown command, 0177:2-151
 Unknown hardware configuration, 0177:2-484
 Unknown LSN, 0177:2-121
 unlock, 0145:7-712
 Unneeded information found, 0177:2-20
 unpacking, 0224:3-4
 unpacking frame, 0095:4-2, 2969:4-2
 Unrecognized command, 0177:2-5
 Unrecognized parameter identifier, 0177:2-7
 Unsolicited Alarm Messages, 0338:3-10
 Unsolicited Information Message, 0193:5-23
 Unsolicited Information Messages, 0178:4-14, 0338:3-25
 Calling Name Conversion Facility (CNCF) (23.1), 0347:2-59
 unsolicited messages
 definition, 0145:4-15
 output groups, 0145:4-15
 Unsolicited Output Message Groups
 Application Subsystem, 0338:D-15
 Card, 0338:D-12
 Clock, 0338:D-23
 Database, 0338:D-27
 GTT, 0338:D-19
 GWS, 0338:D-21
 Link Maintenance, 0338:D-6
 LNP Database, 0338:D-25
 Measurements Maintenance, 0338:D-24
 Monitor, 0338:D-28
 MPS, 0338:D-27
 Program Update, 0338:D-26
 SEAS Maintenance, 0338:D-29
 Security Administration, 0338:D-26
 SLAN, 0338:D-28
 System Maintenance, 0338:D-2
 UIM Redirect, 0338:D-26
 Unstable Loading Mode, 0188:2-24, 0190:2-51, 0193:5-6
 unstable loading mode, 0193:5-6, 0193:5-7
 unstable loading mode, DSM, 0178:4-7, 0183:4-6
 Unsuccessful Delivery of Mobile Originated FSM, 0190:2-17
 Unsupported value - Error code 35, 0197:2-121
 Unuploaded security log entries exist on standby fixed disk, 0177:2-433
 Unused UserIDs, 0183:3-111
 Up to 8 SS7IPGW or IPGWI links allowed in un-mated linkset, 0177:2-784
 upd_entity command, 0348:3-40

Master Index

- upd_sub command, 0348:3-22
- Update a block entry of IMEIs, 0348:3-59
- Update a single entry IMEI, 0348:3-58
- Update Commands, 0178:B-2
- Update DN, 0183:3-66
- Update DN Block, 0183:3-70
- Update EOAP
 - Method A, 2970:4-23, 2970:4-35
 - Method B, 2970:4-25, 2970:4-36
- update EOAP configuration, 2970:4-23, 2970:4-34
- Update IMEI Data, 0348:3-58, 0348:3-61
- Update IMSI, 0183:3-62, 0183:3-78, 0183:3-82
- Update LNP 10-Digit Subscription, 0178:B-2
- Update LNP Location Routing Number, 0178:B-8
- Update LNP NPANXX, 0178:B-5
- Update LNP Subscription, 0178:3-49
- Update Network Entity, 0183:3-74, 0348:3-40
 - command, 0348:3-40
 - request message, 0348:3-40
 - response message, 0348:3-44
 - response return codes, 0348:3-44
- Update NPA-NXX Records, 0178:3-53
- Update NPA-NXX Split Records, 0178:3-58
- Update Override GTT Records, 0178:3-55
- Update Split NPANXX, 0178:B-12
- Update Subscription, 0348:3-22
 - command, 0348:3-22
 - PDBI sample session, 0348:4-4
 - request message
 - modify data of single DN, 0348:3-23
 - modify information for DN block, 0348:3-25
 - modify SP for specific IMSI, 0348:3-23
 - move existing DN to existing IMSI, 0348:3-25
 - response message, 0348:3-27
 - response return codes, 0348:3-27
- Update Tables Log, 0197:2-13, 0197:2-79, 0197:2-80, 0197:2-83, 0197:2-84, 0197:2-85, 0197:2-86, 0197:2-89, 0197:2-90, 0197:2-91, 0197:2-92, 0197:2-93, 0197:2-94, 0197:2-95, 0197:2-96, 0197:2-97
 - Clearing the Display, 0197:2-94, 0197:2-95
 - closing, 0197:2-94, 0197:2-98
 - Print window, 0197:2-96
 - Printing, 0197:2-94, 0197:2-96
 - Save window, 0197:2-97, 0197:2-98
 - saved file confirmation window, 0197:2-98
 - saving to a file, 0197:2-94, 0197:2-97
- Update Tables Log window, 0197:2-84, 0197:2-90, 0197:2-94, 0197:2-95, 0197:2-96, 0197:2-97, 0197:2-98
 - Commit Command Completed, 0197:2-90
 - File Menu, 0197:2-94
 - File menu, 0197:2-94, 0197:2-95
 - Processing Retrieve Request, 0197:2-84
- Update Tables processing completed without errors message, 0197:2-89
- Update Tables window, 0197:2-4, 0197:2-79, 0197:2-80, 0197:2-81, 0197:2-82, 0197:2-83, 0197:2-88, 0197:2-89, 0197:2-92, 0197:2-93, 0197:2-94

- Browse button, 0197:2-80, 0197:2-81
- Close button, 0197:2-80
- Command File field, 0197:2-81, 0197:2-82, 0197:2-84
- Command File Selected, 0197:2-81
 - Stop on error box Checked, 0197:2-83
- description, 0197:2-80
- Select window, description, 0197:2-82
- Update Validation Complete Window
 - Update Tables
 - Update Validation Complete, 0197:2-84, 0197:2-85, 0197:2-86
- Update Validation Complete window, 0197:2-79, 0197:2-85, 0197:2-87, 0197:2-88
 - with errors Window
 - Update Tables
 - Update Validation Complete with errors, 0197:2-86
- Validate button, 0197:2-79, 0197:2-80, 0197:2-84
- Update Validation Complete window, 0197:2-79, 0197:2-84, 0197:2-85, 0197:2-86, 0197:2-87, 0197:2-88
 - description, 0197:2-85
 - with errors, 0197:2-86
 - without errors, 0197:2-86
- Updates, 0224:1-19
- Updates allowed
 - loading stability, 0338:3-953
- Updates inhibited
 - loading stability, 0338:3-952
- updates, documentation, 0178:1-8, 0183:1-8, 0348:1-7
- updating
 - EOAP, 2970:4-13
- Updating Database Tables in the Selected STP, 0197:2-79
- upgrade, 0096:2-14, 2712:2-12
- upgrade considerations
 - , 0347:2-152
 - 48 Million Numbers (27.0), 0347:2-13
 - Eagle Application Support for E1 (26.3), 0347:2-109
 - Enhanced Bulk Download (25.0), 0347:2-150
 - Enhanced GTT (26.0), 0347:2-155
 - G-Port MNP (26.2), 0347:3-25
 - Group Ticket Voucher for SCCP Cards (27.0), 0347:3-41
 - GSM MAP Screening (26.1), 0347:3-42
 - GTT by TT Measurements and GR-376 Enhancements (26.0), 0347:3-50
 - ITU MTP Restart (26.0), 0347:3-158
 - ITU SLS Enhancements (26.0), 0347:3-161
 - ITU-TFR Procedure (26.1), 0347:3-162
 - Large System (27.2), 0347:4-3
 - LNP Measurements Enhancements (25.0), 0347:4-54
 - LRN Table Increase (26.1), 0347:4-110
 - Multiple Point Code Support (EAGLE 26.05), 0347:4-150
 - Multi-Port LIM (EAGLE 27.1), 0347:4-154
 - Nested Cluster Routing (EAGLE 26.0), 0347:4-172
 - Number Pooling / Efficient Data Representation (EDR) (EAGLE 26.1), 0347:4-202
 - Security Log Increase (EAGLE 26.05), 0347:5-73
 - Stand-alone Eagle G-Flex Relay Function, 0347:3-18
 - Support of E1 Interface for SS7 Signaling Links (Optional) (EAGLE 24.0), 0347:5-114

Master Index

- Thresholding of UIM Messages (EAGLE 25.0), 0347:5-132
- TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-149
- Variable Length GTT (Eagle 26.1), 0347:5-171
- Weighted SCP Load Balancing (Eagle 27.2), 0347:5-176
- upgrade procedure
 - High-Speed Multiplexer (HMUX) (27.2), 0347:3-69
- Upgrade Procedure Enhancements (Eagle 22.0), 0347:5-162
 - No Reportable Downtime on Network Restart, 0347:5-163
- Upgrading the Application Processor of the Main Assemblies from the Intel 286/386 to the Intel 486 Microprocessor (Eagle 20.0), 0347:5-165
- upload process, 0190:2-39
- UPU, 0195:1-13
- UPU User Part Unavailable, 0195:1-13
- Use DFILE when specifying STBL, 0177:2-91
- Use DTBL when specifying SFILE, 0177:2-92
- Use IMT Bus Instead of MBUS (Eagle 23.0), 0347:5-166
- Use REPT-STAT-MPS when LNP ELAP Configuration is ON, 0177:2-744
- Use SFILE when specifying DTBL, 0177:2-92
- Use STBL when specifying DFILE, 0177:2-92
- Use STP and FTP UserNames, Passwords for all STPs Box, 0197:2-19, 0197:2-20, 0197:2-38, 0197:2-39, 0197:2-40
- Use type=local or remove ipaddr from IPLNK table, 0177:2-831
- Use type=remote or enter ipaddr in IPLNK table, 0177:2-830
- user
 - adding, 0142:4-21
 - removing, 0142:4-33
- user administration, 0096:2-21, 2712:2-19
- User Administration menu, 0178:3-81, 0183:3-111
- user console
 - Embedded OAP (24.0), 0347:2-138
- User currently logged on, 0177:2-104
- User Datagram Protocol, 0188:2-11, 0193:2-8
- User Default Groups, 0178:3-109, 0183:3-139
- user environment variables, 0197:2-7
- user file name, 0183:3-100
- User Guide Conventions, 0197:2-1
- User IDs
 - already in use at login, 0145:4-22
 - not accepted at login, 0145:4-20
 - rules for administering, 0145:4-17
- user information
 - changing, 0142:4-35
- user interface, 0188:1-2, 0190:3-1
- user interface for maintenance and measurements, 0190:3-10, 0193:3-1, 0195:3-9
- user interface terminal, 0188:2-16
- user interface traffic, 0190:2-41
- user interface, ELAP
 - error message format, 0178:5-12
 - Escape key to exit operations, 0178:5-11
 - list of error messages, 0178:3-112
- user interface, EPAP
 - error message format, 0183:5-14

- Escape key to exit operations, 0183:5-13
- list of error messages, 0183:3-142
- User Interfaces, 0178:3-2
- User Login, 0178:5-13
- User login failure - Error code 633, 0197:2-106
- User Logins, 0178:3-109, 0183:3-138, 0183:3-139
- User Names See User IDs, 0145:4-16
- user session, log into system for, 0145:4-19
- User Sessions, 0183:3-111
- User's Manual, 0212:1-18, 0243:1-18
- user-defined LNP services, 0288:3-22
- UserID already logged on (or is logging on) another terminal, 0177:2-325
- UserID has become obsolete and cannot be used, 0177:2-325
- UserID has been revoked, 0177:2-325
- UserIDs, 0183:3-111
- user-initiated
 - aborting, 2339:4-11
- User-Initiated Keyboard Locking (Eagle 22.0), 0347:5-166
- user-initiated resynchronization, 2339:4-2
 - log file, 2339:4-18, 2339:4-19
 - managing, 2339:4-6
 - overview, 2339:2-5, 2339:2-8
 - procedure, 2339:4-6
 - timeline, 2339:4-4
- Users menu, 0178:3-82, 0183:3-112
- Using force Option, 0188:5-8, 0190:5-8, 0193:5-11
- Using the DPC/SSN Parameters and GTA Range in Displaying Global Title Translations (Eagle 22.0), 0347:5-169
- Using the FTRA application, 0197:2-4
- UTC, 0096:2-19, 2712:2-17
- utility GPL
 - change trial to approved version, 0142:3-146

V

- V.35, 0212:3-68, 0224:5-12
- V.35 4-link monitor configuration window, 0212:B-7
- V.35 applique, 0212:3-66, 0212:3-67
- V.35 monitor applique, 0212:B-7
- Vacuum cleaner, 0224:3-20
- vacuum cleaner, 0095:4-3, 2969:4-3
- Validate button
 - Update Tables, 0197:2-80, 0197:2-84
 - Update Tables window, 0197:2-79
- validate user input, 0183:3-11
- Validating command files, 0197:2-2
- validation
 - DSM daughterboard continual memory, 0178:4-6
- Validation of G-Flex Hardware Configuration, 0188:2-23
- Validation of G-Port Hardware Configuration, 0190:2-50
- validity status, 0188:2-23
- Value <data> for <parm> parameter is not valid (C<col>), 0177:2-499

Master Index

Value <data> for <parm> parameter not consistent with a previous parameter (C<col>), 0177:2-499
Value <data> not supported for <parm> parameter in this implementation (C<col>), 0177:2-498
Value <data> out of range for <parm> parameter (C<col>), 0177:2-501
Variable
 environment
 FTRA_HOME, 0197:2-1, 0197:2-7, 0197:2-9
 JRE_HOME, 0197:2-1, 0197:2-7, 0197:2-9
 system environment, 0197:2-7, 0197:2-9
 user environment, 0197:2-7, 0197:2-9
Variable Length GTT (Eagle 26.1), 0347:5-169
 alarms, 0347:5-172
 changed commands, 0347:5-171
 hardware requirements, 0347:5-172
 upgrade consideration, 0347:5-171
Variable number of digits, 0188:2-29
variable number of digits, 0188:3-2
Variable-Length Global Title Translation, 0099:1-2, 0099:1-3, 0099:2-3, 0099:2-6, 0099:2-7, 0099:2-12, 0099:2-13, 0099:2-14, 0099:2-15, 0099:2-34, 0099:2-42, 0099:2-44, 0099:2-48, 0099:3-4, 0099:3-5, 0099:3-6, 0099:3-7, 0099:3-21, 0099:3-22, 0099:3-31, 0099:3-32, 0099:3-44, 0099:3-45, 0099:3-52, 0099:3-54, 0099:3-61, 0099:4-4, 0099:4-5, 0099:4-7, 0099:4-8, 0099:4-14, 0099:4-23, 0099:4-27, 0099:4-38, 0099:4-50, 0099:4-54, 0099:4-55, 0099:4-63, 0099:A-39
variable-length numbers, 0193:2-2
varying length numbers, 0190:2-6
VCI values 0...4 and 6...31 are reserved, 0177:2-509
VCXO, 0212:3-143
VENDID already exists in VENDID table, 0177:2-815
VENDID does not exist in VENDID table, 0177:2-815
VENDID table is full, 0177:2-814
VENDIDLEN may only be changed if VENDID table is empty, 0177:2-817
VENDIDLEN must be set before Vendor ID may be entered, 0177:2-826
Verbose Output, 0096:3-17, 2712:3-14
verification, 0224:4-22
 DMS motherboard, 0183:4-4
 DSM daughterboard local memory, 0183:4-5
 DSM daughterboard real-time memory, 0183:4-5
 DSM system hardware, 0183:4-4
verification, DSM system hardware, 0178:4-5
verify and correct IP stack ARP tables, 0188:3-16, 0190:3-20, 0193:3-14
verify IS-NR card status, 0188:4-19, 0188:4-25, 0188:4-34, 0190:4-19, 0190:4-25, 0190:4-34, 0193:4-19, 0193:4-25, 0193:4-34
verify new link parameters, 0188:4-25, 0188:4-34, 0190:4-25, 0190:4-34, 0193:4-25, 0193:4-34
Verifying
 RTDB Status, 0288:2-105
 RTDB Status at the Eagle Terminal, 0288:2-106
 RTDB Status at the ELAP User Interface, 0288:2-106
verifying
 DSM card status, 2339:8-5
verifying database, 0142:2-10
verifying modems, 0096:3-10, 2712:3-7
Versant, 0188:2-21, 0190:2-33
Versant database, 0188:2-9
version, 0348:3-8

Version level, 0197:2-104
 Version not supported, 0177:2-751
 Version parameter not supported for either SUA or M2PA, 0177:2-752
 vfy-lnp-refnum, 0145:8-58
 VGTT - Variable-Length Global Title Translation, 0099:1-2, 0099:1-3, 0099:2-3, 0099:2-6, 0099:2-7, 0099:2-12, 0099:2-13, 0099:2-14, 0099:2-15, 0099:2-34, 0099:2-42, 0099:2-44, 0099:2-48, 0099:3-4, 0099:3-5, 0099:3-6, 0099:3-7, 0099:3-21, 0099:3-22, 0099:3-31, 0099:3-32, 0099:3-44, 0099:3-45, 0099:3-52, 0099:3-54, 0099:3-61, 0099:4-4, 0099:4-5, 0099:4-7, 0099:4-8, 0099:4-14, 0099:4-23, 0099:4-27, 0099:4-38, 0099:4-50, 0099:4-54, 0099:4-55, 0099:4-63, 0099:A-39
 VGTT cannot be On if any SCCP card has a 486 processor, 0177:2-688
 view
 hub front, 0212:4-47
 hub rear, 0212:4-48
 MPS frame front, 0212:4-13
 MPS frame rear, 0212:4-13
 MPS Server front, 0212:4-25
 MPS Server front detail, 0212:4-22, 0212:4-30
 MPS Server rear, 0212:4-26
 MPS Server rear detail, 0212:4-22, 0212:4-30
 Netra t 1400 front, 0212:4-25
 Netra t 1400 rear, 0212:4-26
 View Allowed menu, 0178:3-31
 View Any File menu, 0178:3-65, 0183:3-36
 View Command Log, 0183:3-107
 View EMS Routing, 0288:2-91
 View Enabled, 0178:3-28
 View Enabled menu, 0178:3-24, 0178:3-26
 View LNP QTY, 0178:3-36
 view logs files, 0178:3-62
 View Logs menu, 0178:3-61, 0183:3-31
 View menu
 FTP-Based Table Retrieve Application, 0197:2-72, 0197:2-95, 0197:2-100
 View PDBA Debug Log, 0183:3-107
 View PDBA Error Log, 0183:3-107
 View PDBA Number Prefixes, 0183:3-105
 View PDBA Status, 0183:3-57
 View RTDB Status, 0178:3-35, 0183:3-24
 View Simplex Mode, 0178:3-20
 View Status, 0183:3-18
 View Status screen, 0178:3-17
 View System Log, 0178:3-75
 View System Log screen, 0183:3-45
 View Window viewer, 0178:3-62
 Viewing an EMS Configuration Component, 0288:2-84
 Viewing log files, 0197:2-2
 VIOL, 0178:3-7, 0183:3-7, 0183:5-6
 Violation status, 0183:5-6
 Visitor Location Register, 0188:2-3
 Visual Alarms, 0338:3-4
 VLR, 0188:1-13, 0188:2-3, 0190:1-14, 0193:1-15, 0195:1-13
 VLRA, 0188:2-3
 VMSC, 0188:1-13, 0190:1-14, 0193:1-15, 0195:1-13, 0348:1-13

Master Index

VMSCA, 0190:2-9
voltages, checking, 0096:3-16, 2712:3-13
VPN Systems, 0212:4-17
VSCCP, 0188:1-13, 0188:2-10, 0190:1-14, 0190:2-36, 0193:1-15, 0193:5-5, 0195:1-13, 0348:1-13
VSCCP application, 0188:2-23, 0190:2-50
VSCCP Capacity, 0188:5-6, 0190:5-6, 0193:5-9, 0195:4-6
VSCCP cards have insufficient extended memory, 0177:2-554
VSCCP GPL, 0188:5-1, 0188:5-5, 0190:5-1, 0195:4-1
VSCCP services, 0188:5-8
VT320 terminal type, 0142:4-55
VT320 terminals, 0145:4-3
 key sequences, 0145:4-10
 KSR function on, 0145:4-5
VT-520, 0338:5-22, 2970:7-21
VxWorks, 0188:1-13, 0190:1-14, 0195:1-13
VxWorks OS, 0188:2-10, 0190:2-36
VxWorks Signalling Connection Port, 0193:5-5

W

Waiting for duplex mode in provisioning subsystem, 0177:2-77
WAN connection, 0347:3-128
warm restart
 TSM Warm Restart and Incremental Loading (EAGLE 26.0), 0347:5-137
Warm Restart capable Feature must be enabled, 0177:2-253
warm restart, DSM, 0178:2-18
Warning icon, 0188:1-8, 0190:1-8, 0193:1-9
Warning Message When LIMs Added with Insufficient TSMs (Eagle 25.0), 0347:5-174
web server, 0183:3-2
web-based user interface, 0178:3-2
Weekly Procedures, 0338:2-20
weight, 2969:3-9
Weighted SCP Load Balancing (Eagle 27.2), 0347:5-175
 alarms, 0347:5-176
 enhanced commands, 0347:5-176
 hardware requirements, 0347:5-176
 limitations, 0347:5-177
 upgrade considerations, 0347:5-176
weights, 0212:6-5
well-known port, PDBA, 0348:3-2, 0348:3-8
When REXMIT=BSD is specified, an RTT cannot be assigned, 0177:2-340
When REXMIT=FIXED or MOD is specified, an RTT must be assigned, 0177:2-341
When type=DEFAULT, other allowed parameters are SNAME/LOC, 0177:2-703
When type=full, DPC and SI must be specified, 0177:2-713
When type=partial or default, specify attributes, 0177:2-702
When type=partial or default, SPLIT/ RESIZE are not supported, 0177:2-702
Wild card entries are not allowed in this command, 0177:2-196
Wildcard SSN already exists, 0177:2-767
Wildcard / Asterisk combination invalid for direction, 0177:2-747
Wildcard / Asterisk invalid for direction of BOTH, 0177:2-747
Wildcard / Asterisk required for TTI, NP, NAI if DIR is ITOA, 0177:2-748
Window

- About FTRA, 0197:2-13, 0197:2-104
- Command Complete Connectivity Test, 0197:2-34
- Command File Editor, 0197:2-85, 0197:2-87, 0197:2-88, 0197:2-89
 - File Menu, 0197:2-89
 - Invalid Command, 0197:2-88
- Command File Editor window
 - File Menu, 0197:2-89
- Commands Menu, 0197:2-58, 0197:2-65, 0197:2-80
- Connectivity Test Log, 0197:2-33, 0197:2-34, 0197:2-35, 0197:2-36, 0197:2-37, 0197:2-38, 0197:2-46, 0197:2-49, 0197:2-50
 - closing, 0197:2-34, 0197:2-38
 - File Menu, 0197:2-34, 0197:2-35
 - Print, 0197:2-36
 - Save, 0197:2-37
 - Saved file confirmation, 0197:2-37, 0197:2-38
 - with errors, 0197:2-34
 - with no errors, 0197:2-33
- Exit, 0197:2-14, 0197:2-15
- Exit Confirmation, 0197:2-14
- FTP Server Configuration Menu, 0197:2-23, 0197:2-51, 0197:2-52, 0197:2-105, 0197:2-108, 0197:2-122, 0197:2-123
- FTP Server Data Set, 0197:2-55
- FTP-Based Table Retrieve Application, 0197:2-13, 0197:2-14, 0197:2-20, 0197:2-33, 0197:2-38, 0197:2-41, 0197:2-60, 0197:2-71, 0197:2-72, 0197:2-73, 0197:2-80, 0197:2-95, 0197:2-96, 0197:2-97, 0197:2-100, 0197:2-101, 0197:2-102, 0197:2-104
- GTT Warning, 0197:2-56
- Initializing, 0197:2-13
- Invalid FTP Password warning, 0197:2-24
- Invalid FTP User Name warning, 0197:2-23
- Invalid IP Address warning, 0197:2-22, 0197:2-52, 0197:2-53
- Invalid STP Name Error Message, 0197:2-20
- Invalid STP Name warning, 0197:2-20
- Invalid STP Password warning, 0197:2-23
- Invalid STP User Name warning, 0197:2-22
- Modify Warning, 0197:2-41
- Print
 - Retrieve Tables Log, 0197:2-73
 - Update Tables Log, 0197:2-97
- Retrieve Tables, 0197:2-4, 0197:2-56, 0197:2-57, 0197:2-60, 0197:2-75
 - Add button, 0197:2-58, 0197:2-62
 - Close button, 0197:2-58
 - Command Complete, 0197:2-56, 0197:2-67, 0197:2-68
 - Command List Field, 0197:2-58
 - description, 0197:2-58
 - GTT Warning, 0197:2-56
 - Load button, 0197:2-58, 0197:2-66, 0197:2-75
 - Remove button, 0197:2-58, 0197:2-64
 - Reset button, 0197:2-58, 0197:2-65
 - Retrieve button, 0197:2-56, 0197:2-58, 0197:2-66, 0197:2-67
 - Retrieve from Local Database button, 0197:2-56, 0197:2-58, 0197:2-66
 - Retrieve from STP button, 0197:2-56, 0197:2-58, 0197:2-67
 - Selected Commands Field, 0197:2-58

Master Index

- Store button, 0197:2-58, 0197:2-65, 0197:2-75
- Retrieve Tables Log, 0197:2-67, 0197:2-68, 0197:2-69, 0197:2-70, 0197:2-71, 0197:2-72, 0197:2-73, 0197:2-74
 - closing, 0197:2-70, 0197:2-74
 - File Menu, 0197:2-70, 0197:2-71
 - Print, 0197:2-72, 0197:2-73
 - Processing Retrieve Request, 0197:2-67
 - Release Not Compatible Error, 0197:2-59
 - Save, 0197:2-73, 0197:2-74
 - Saved file confirmation, 0197:2-74
 - with Errors, 0197:2-70
 - without Errors, 0197:2-69
- Save
 - Retrieve Tables window, 0197:2-74
- Select
 - File Name: Field, 0197:2-82
 - Files of type: Field, 0197:2-82
 - Look in: Field, 0197:2-82
 - Update Tables, 0197:2-79, 0197:2-80, 0197:2-81, 0197:2-82
- Select Starting Directory, 0197:2-52, 0197:2-53, 0197:2-54
 - File Name: Field, 0197:2-54
 - Files of type: Field, 0197:2-54
 - Look in: Field, 0197:2-54
- Select, description, 0197:2-82
- STP Added, 0197:2-24
- STP Connection Configuration Menu, 0197:2-16, 0197:2-17, 0197:2-18, 0197:2-20, 0197:2-25, 0197:2-29, 0197:2-33, 0197:2-38, 0197:2-41, 0197:2-42, 0197:2-43, 0197:2-106, 0197:2-123, 0197:2-124
 - FTRA 1.0, 0197:2-16
 - FTRA 2.0, 0197:2-51
 - FTRA 2.0 or greater, 0197:2-16, 0197:2-17
- STP Data Deleted, 0197:2-42
- STP Data Modified, 0197:2-39, 0197:2-41
- STP Selection Change, 0197:2-18, 0197:2-43, 0197:2-44
- System Log, 0197:2-99, 0197:2-100, 0197:2-101, 0197:2-102, 0197:2-103
 - closing, 0197:2-99, 0197:2-103
 - File Menu, 0197:2-99, 0197:2-100
 - Print, 0197:2-101
 - Print window
 - Cancel button, 0197:2-101
 - Save, 0197:2-102, 0197:2-103
 - Saved file confirmation, 0197:2-103
- Update Tables, 0197:2-4, 0197:2-79, 0197:2-80, 0197:2-81, 0197:2-82, 0197:2-83, 0197:2-88, 0197:2-89, 0197:2-92, 0197:2-93, 0197:2-94
 - Browse button, 0197:2-80, 0197:2-81
 - Close button, 0197:2-80
 - Command Complete, 0197:2-85, 0197:2-86, 0197:2-89
 - Command File field, 0197:2-81, 0197:2-82, 0197:2-84
 - Command File Selected, 0197:2-81
 - Command List Field, 0197:2-80
 - description, 0197:2-80
 - Select, description, 0197:2-82

- Stop on error box, 0197:2-80, 0197:2-83, 0197:2-92, 0197:2-93, 0197:2-94
- Update Validation Complete, 0197:2-85
- Validate button, 0197:2-79, 0197:2-80, 0197:2-84
- Update Tables Log, 0197:2-84, 0197:2-90, 0197:2-94, 0197:2-95, 0197:2-96, 0197:2-97, 0197:2-98
 - closing, 0197:2-94, 0197:2-98
 - Commit Command Completed, 0197:2-90
 - File Menu, 0197:2-94, 0197:2-95
 - Print, 0197:2-96
 - Processing Retrieve Request, 0197:2-84
 - Save, 0197:2-97, 0197:2-98
 - Saved file confirmation, 0197:2-98
- Update Validation Complete, 0197:2-79, 0197:2-84, 0197:2-85, 0197:2-86, 0197:2-87, 0197:2-88
 - Commit button, 0197:2-85, 0197:2-86
 - description, 0197:2-85
 - Edit button, 0197:2-85, 0197:2-86, 0197:2-87, 0197:2-88
 - Stop button, 0197:2-85
 - with errors, 0197:2-86
 - without errors, 0197:2-86
- Windows 2000 operating system, 0197:2-7
- Windows 98 operating system, 0197:2-7
- Windows Explorer, 0197:2-5, 0197:2-6
- Windows NT operating system, 0197:2-7
- Windows Task Scheduler, 0197:2-75, 0197:2-77
- Windows Workstation Requirements, 0197:2-2
- wireless network, 0188:2-17
- Wireless number portability - WNP, 0288:3-22
- Wireless Query Redirect - WQREDRCT, 0288:3-53
- Wireless short message service center - WSMSC, 0288:3-22
- Wireless Short Message Service Center 10 Digits - WSMSC10DIG, 0288:3-53
- WNP - Wireless number portability, 0288:3-22
- WNP feature must be ON, 0177:2-589
- work area section, 0178:3-2, 0183:3-2
- Workspace Section, 0183:3-10
- workspace section, 0178:3-10
- Workspace Syntax Checking, 0183:3-11
- WQREDRCT - Wireless Query Redirect, 0288:3-53
- Wrist Strap Test, 0338:2-37
- write enabling removable cartridge, 0142:2-7
- write protecting removable cartridge, 0142:2-6
- write transaction
 - abort, 0348:3-14
 - begin, 0348:3-11
 - end, 0348:3-13
 - not active for PDBA switchover, 0348:3-48
- WSMSC - Wireless short message service center, 0288:3-22
- WSMSC feature must be Activated, 0177:2-581
- WSMSC LNP service, 0288:3-79
- WSMSC10DIG - Wireless Short Message Service Center 10 Digits, 0288:3-53
- WSMSC10DIG LNP option, 0288:3-79

X

- X.25
 - Connectivity, 0097:2-3
 - X.25 address already exists in X.25 destination table, 0177:2-284
 - X.25 address cannot be referenced by route, 0177:2-284
 - X.25 address does not exist in X.25 destination table, 0177:2-285
 - X.25 Address must contain at least four digits, 0177:2-281
 - X.25 connection control, 0097:2-7
 - X.25/SS7 Gateway Feature (Eagle 20.0), 0347:5-183
 - X.25 Destination assigned to non-X.25 linkset, 0177:2-254
 - X.25 destination table is full, 0177:2-285
 - X.25 Gateway Destinations, 0097:2-9
 - X.25 Gateway feature, 0097:1-2
 - X.25 gateway routing
 - X.25/SS7 Gateway Feature (Eagle 20.0), 0347:5-181
 - X.25 LIM replacement, 0338:A-27
 - X.25 LIMs, 0097:2-9
 - X.25 linksets, 0097:2-9
 - X.25 message conversion
 - SS7 to X.25, 0338:B-4
 - X.25 to SS7, 0338:B-2
 - X.25 mode parameter requires SEAS feature, 0177:2-605
 - X.25 packet size parameter requires SEAS feature, 0177:2-604
 - X.25 route table is full, 0177:2-294
 - X.25 Routes, 0097:2-9
 - X.25 Signaling Link Parameters, 0097:2-9
 - X.25 signaling links, 0097:2-9
 - X.25/SS7 Gateway Feature (Eagle 20.0), 0347:5-178
 - Address Mapping, 0347:5-181
 - Connection Determination, 0347:5-182
 - Logical Channel to Network Management Mapping, 0347:5-184
 - Message Conversion, 0347:5-180
 - same link management, 0347:5-184
 - X.25 Connection Control, 0347:5-183
 - X.25 Gateway Routing, 0347:5-181
 - X.25/SS7 IS41 Rev. A Gateway
 - Overview, 0097:2-2
 - X.25/SS7 Message Conversion, 0338:B-1, 0338:D-1, 0338:E-1, 0338:F-1
 - X25 logical channels available, 0338:3-234
 - X25 no logical channels available, 0338:3-235
 - X252000, 0097:2-25
 - X25G, 0097:2-25
 - X25G Feature must be ON before X252000 can be ON, 0177:2-657
 - xaddr, 0097:2-25
 - XGTT requires at least a 586 processor for SCCP GPLs, 0177:2-466
 - XGTT requires both OAMs running on GPSPMII cards, 0177:2-467
 - XGTT Table Expansion, 0099:2-43, 0099:2-47, 0099:2-48, 0099:3-26, 0099:4-32, 0099:4-33, 0099:A-17, 0099:A-18, 0099:A-19, 0099:A-20, 0099:A-21, 0099:A-23, 0099:A-24, 0099:A-25, 0099:A-26, 0099:A-39
 - XGTT Table Expansion Feature
 - Enabling, 0099:A-17
 - XGTT with 1 million entries requires DSM cards for SCCP GPLs, 0177:2-467
 - XLAT, 0288:3-60

XLAT must be DPCSSN and RI must be SSN if PC is the True PC, 0177:2-589
X-LIST DPC is not allowed, 0177:2-50
X-LIST occupancy below threshold, 0338:3-409
X-LIST occupancy threshold exceeded, 0338:3-407
X-LIST space full condition abated, 0338:3-427
X-LIST space full-entry(s) discarded, 0338:3-425
XMAP requires at least a 586 processor for SCCP GPLs, 0177:2-467
XMAP requires both OAMs running on GPSMII cards, 0177:2-468
XMAP Table Expansion, 0099:2-43, 0099:2-46, 0099:2-48, 0099:2-84, 0099:2-85, 0099:2-121, 0099:A-27,
0099:A-28, 0099:A-29, 0099:A-30, 0099:A-31, 0099:A-33, 0099:A-34, 0099:A-35, 0099:A-39
XMAP Table Expansion Feature
Enabling, 0099:A-27

Y

Year 2000 Compliance (Eagle 23.1)
OAP Year 2000 Compliance, 0347:5-194

Master Index