
First Alert

USER'S MANUAL

BATTERY OPERATED CARBON MONOXIDE ALARM WITH SILENCE FEATURE



Printed in Mexico M08-0140-004 **P** 06/07

IMPORTANT! PLEASE READ CAREFULLY AND SAVE. This user's manual contains important information about your Carbon

Monoxide (CO) Alarm's operation. If you are installing this CO Alarm for use by others, you must leave this manual-or a copy of it-with the end user.

TABLE OF CONTENTS

h	ntroduction			
	Basic Safety Information			
	How Your CO Alarm Works			
	Understanding Your CO Alarm			
h	nstallation			
	Where to Install CO Alarms			
	Where CO Alarms Should NOT Be Installed			
	How to Install Your CO Alarm			
Н	f Your CO Alarm Sounds			
	If the Alarm Signal Sounds			
	Using the Silence Feature			
Т	Festing and Maintenance			
	Weekly Testing			
	Regular Maintenance			
What You Need To Know About CO				
	What is CO?			
	Symptoms of CO Poisoning			
	Finding the Source of CO After an Alarm			
	How Can I Protect My Family?			
	Potential Sources of CO in the Home			
F	Regulatory Information for CO Alarms			
G	General Limitations Of CO Alarms			

Troubleshooting Guide5-6 © 2007 BRK Brands, Inc., a Jarden Corporation company (NYSE: JAH)

3901 Liberty Street Road, Aurora, IL 60504-8122 All rights reserved

Consumer Affairs: (800) 323-9005 www.brkelectronics.com • www.firstalert.com

INTRODUCTION

BASIC SAFETY INFORMATION

- **IMPORTANT!** Dangers, Warnings, and Cautions alert you to important operating instructions or to potentially hazardous situations. Pay special attention to these items.
- THIS IS NOT A SMOKE ALARM! This CO Alarm is designed to detect carbon monoxide from ANY source of combustion. It is NOT designed to detect smoke, fire, or any other gas. • This CO Alarm is approved for use in single-family residences.

It is NOT designed for marine use.

ACAUTION!

- This CO Alarm will only indicate the presence of carbon monoxide gas at the sensor. Carbon monoxide gas may be present in other areas. AWARNING!
- The Silence Feature is for your convenience only and will not correct a CO problem. Always check your home for a potential problem after any alarm. Failure to do so can result in injury or death.
- NEVER ignore your Carbon Monoxide Alarm if it alarms. Refer to "If Your CO Alarm Sounds" for more information. Failure to do so can result in injury or death.
- Test the CO Alarm once a week. If the CO Alarm ever fails to test correctly, have it replaced immediately! If the CO Alarm is not working properly, it cannot alert you to a proble
- This product is intended for use in ordinary indoor locations of family living units. It is not designed to measure CO levels in compliance with Occupational Safety and Health Administration (OSHA) commer cial or industrial standards. Individuals with medical conditions that nay make them more sensitive to carbon monoxide may conside using warning devices which provide audible and visual signals for carbon monoxide concentrations under 30 ppm. For additional nformation on carbon monoxide and your medical condition contact your physician.

HOW YOUR CO ALARM WORKS


GENERAL INFORMATION

AWARNING!

This CO Alarm does not operate without working batteries. ing the batteries, or failure to replace them at the end of their ervice life, removes your protection

A CO Alarm measures the CO levels in the air. It will alarm if CO levels rise quickly (if the heat exchanger on your furnace breaks, for example), or if CO is consistently present (a slow CO leak on a fuel-burning appliance). This Carbon Monoxide Alarm features a permanently installed sensor and an 85 dB alarm horn. It also has a silence feature to temporarily guiet the alarm

THE PARTS OF YOUR CO ALARM



- 1 Open door here Test/Silence Button
- 3 POWER/ALARM Light (RED)
- 4 Battery Compartment 5 (Behind Cover) Alarm Horn: 85dB audible alarm for test, alarm, and unit malfunction warning.

UNDERSTANDING YOUR CO ALARM

WELCOME CHIRP

Horn chirps and light blinks once when batteries are first connected ALARM RECEIVING BATTERY POWER

LOW BATTERY WARNING

Light flashes every minute. Horn is silent

The light continues to flash (RED) and the horn also "chirps" once every minute. This warning should last for up to 30 days, but you should replace the batteries as soon as possible.

DURING TESTING Light flashes Red in sync with the horn pattern (4 beeps, pause, 4 beeps), simulating a CO Alarm condition.

CO ALARM

Sensor has detected enough CO to trigger an alarm. Light flashes rapidly and horn sounds loudly (repeating 4 beeps, pause). See "If Your CO Alarr ounds" for details. During an alarm, move everyone to a source of fresh air. DO NOT move the CO Alarm!


CO ALARM REQUIRES SERVICE (MALFUNCTION SIGNAL)

The light flashes (RED) and the horn sounds 3 quick "chirps" every minute. CO Alarm needs to be replaced.

INSTALLATION

WHERE TO INSTALL CO ALARMS The National Fire Protection Association (NFPA) recommends that a CO Alarm

should be centrally located outside of each separate sleeping area in the immediate vicinity of the bedrooms. For added protection, install additional CO Alarms in each separate bedroom, and on every level of your home. If your bedroom hallway is longer than 40 feet (12 meters), install a CO Alarm at BOTH ends of the hallway



REQUIRED TO MEET NFPA RECOMMENDATIONS SUGGESTED AREAS FOR INSTALLING ADDITIONAL CO ALARMS

In a Single-level Home

- Install at least one CO Alarm near or within each separate sleeping area. For added protection, install an additional CO Alarm at least 20 feet 6 meters) away from the furnace or fuel burning heat source.
- In a Multi-level Home Install at least one CO Alarm near or within each separate sleeping area.
- For added protection, install at least one CO Alarm on each level of the
- For added protection, install an additional CO Alarm at least 20 feet 6 meters) away from the furnace or fuel burning heat source. In Mobile Homes:
- Install CO Alarms on inside walls ONLY. Uninsulated outside walls and oofs of mobile homes often transfer heat and cold from outdoors. The Alarm should be located at least 152 mm (6 inches) from all exterior walls and at least 305 mm (12 inches) from supply or return vents.

WHERE CO ALARMS SHOULD NOT BE INSTALLED

- DO NOT LOCATE THIS CO ALARM: • In garages, kitchens, furnace rooms, or in any extremely dusty, dirty or
- greasy areas. Within 5 feet (1.5 meters) of any cooking appliance
- In extremely humid areas. This alarm should be at least 10 feet (3 meters) from a bath or shower, sauna, humidifier, vaporizer, dishwasher, laundry room, utility room or other source of high humidity.
- In areas where temperature is colder than 40° F (4° C) or hotter than 100° F (38° C). These areas include unconditioned crawl spaces, unfinished attics, uninsulated or poorly insulated ceilings, porches, and garages.
- In turbulent air, like near ceiling fans, heat vents, air conditioners, fresh air returns, or open windows. Blowing air may prevent CO from reaching the sensors. Outside the Mobile Home.
- In direct sunlight.

AWARNING!

- This CO Alarm is designed for use inside a single-family home or apartment. It is not meant to be used in common lobbies, hallways or basements of multi-family buildings unless working CO Alarms are also installed in each family living unit. CO Alarms in common areas may not be heard from inside individual family living units.
- This CO Alarm alone is not a suitable substitute for complete detection systems in places which house many people, like hotels or dormitories, unless a CO Alarm is also placed in each unit.
- DO NOT use this CO Alarm in warehouses, industrial or commercial buildings, special-purpose non-residential buildings, or airplanes. This CO Alarm is specifically designed for residential use, and may

2

HOW TO INSTALL YOUR CO ALARM

Read "Where To Install Your CO Alarm" before starting Before you start installation, find the pair of self-adhesive labels included with this CO Alarm. On each label write in the phone number of your emer-gency responder (like 911) and a qualified appliance technician. Place one label near the CO Alarm, and the other label in the "fresh air" location you plan to go if the alarm sounds.

INSTALLING THE AA BATTERIES

- Flip the battery door down to op Install both AA batteries (included) inside the battery compartment as indicated Make sure the "+" and "ends of each battery are aligned properly. A chirp will be issued.
- 3. Close the battery door.

TO MOUNT ON THE WALL Tools you will need: pencil, drill with 3/16" or 5mm drill bit,

- flathead screwdriver, hamm Choose a location on the wall. Do not install the Alarm closer than 4" 102 mm) from where the wall meets the ceiling
- Hold the mounting guide template against the wall, and make a mark side each keyhole where you will drill your mounting hole as shown in
- the diagram below. 3. Use a 3/16" (5 mm) drill bit to drill through the marks you made for the mounting holes
- Insert the plastic screw anchors into the mounting holes until they are
- flush with the wall. If necessary, tap them gently with a hamme 5. Insert the screws into the anchors until the screwhead is 1/8 inch (3 mm)
- way from the wall
- 6. Slide the CO Alarm onto the screws until you feel it click into place.
- 7. Test the CO Alarm as described in "Weekly Testing."

IF YOUR CO ALARM SOUNDS

AWARNING Actuation of your CO Alarm indicates the presence of carbon monoxide (CO) which can kill you. In other words, when your CO Alarm sounds, you must not ignore it!

- **IF THE ALARM SIGNAL SOUNDS:**
- . Operate the Test/Silence button
- . Call your emergency services, fire department or 911. Write down the number of your local emergency service here:
- 3. Immediately move to fresh air-outdoors or by an open door or window. Do a head count to check that all persons are accounted for. Do not re-enter the premises, or move away from the open door or window until the emergency services responder has arrived, the premises have been aired out, and your CO Alarm remains in its normal condition
- 4. After following steps 1-3, if your CO Alarm reactivates within a 24-hour period, repeat steps 1-3 and call a qualified appliance technication inves-igate for sources of CO from fuel-burning equipment and appliances, and inspect for proper operation of this equipment. If problems are identified during this inspection have the equipment serviced immediately. Note any combustion equipment not inspected by the technician, and consult the manufacturers' instructions, or contact the manufacturers directly, for more information about CO safety and this equipment. Make sure that motor vehicles are not, and have not, been operating in an attached garage or adjacent to the residence. Write down the number of a qualified appliance technician here:

"ALARM-MOVE TO FRESH AIR" If you hear the alarm horn and the Red light is flashing, move everyone to a source of fresh air. DO NOT disconnect the batteries from the CO Alarm!

AWARNING! Alarms have various limitations. See "General Limitations of CO Alarms" for details.

USING THE SILENCE FEATURE

AWARNING!

- The Silence Feature is for your convenience only and will not correct a CO problem. Always check your home for a potential problem after any alarm. Failure to do so can result in injury or
- NEVER remove the batteries from your CO Alarm to silence the horn. Use the silence feature. Removing the batteries removes your protection! See "If Your CO Alarm Sounds" for details on esponding to an alarm

The Silence Feature is intended to temporarily silence your CO Alarm's alarm horn while you correct the problem—it will not correct a CO problem. While the alarm is silenced it will continue to monitor the air for CO.

When CO reaches alarm levels the alarm will sound- repeating horn pattern 4 beeps, a pause, 4 beeps, etc. Press and hold the Test/Silence button until the horn is silent. The initial Silence cycle will last approximately 4 minutes. NOTE: After initial 4-minute Silence cycle, the CO Alarm re-evaluates present CO levels and responds accordingly. If CO levels remain potentially danger-ous—or start rising higher—the horn will start sounding again.

While the detector is silenced If the CO Alarn

If the CO Alarm	This means
ls silent for only 4 minutes, then starts sounding loudly—4 beeps, pause, 4 beeps, pause	CO levels are still potentially dangerous.
If the CO Alarm	This means
Remains silent after you pressed the Test/Silence button	CO levels are dropping.

SILENCING THE LOW BATTERY WARNING

This silence feature can temporarily quiet the low battery warning "chirp" for the Test/Silence button. The LED will flash twice, acknowledging that the low battery silence feature has been activated.

After 8 hours, the low battery "chirp" will resume. Replace the batteries as soon as possible: this unit will not operate without battery power To deactivate this feature: Press the Test/Silence button again. The unit will go into Test Mode and the low battery warning will resume (LED flashes and init sounds "chirp" once a minute.) If you cannot silence the low battery warning, replace the batteries

Mounting Guide Template

2.5 inches (64 mm)

3

TESTING & MAINTENANCE

WEEKLY TESTING

AWARNING!

• Test the CO Alarm once a week. If the CO Alarm ever fails to test correctly, have it replaced immediately! If the CO Alarm is not working properly, it cannot alert you to a problem

DO NOT stand close to the Alarm when the horn is sounding Exposure at close range may be harmful to your hearing. When testing, step away when horn starts sounding.

Push and hold the Test/Silence button on the cover until the LED flashes. The rm horn will sound 4 beeps, a pause, then 4 beeps. The ALARM (RED) light

The alarm sequence should last 5-6 seconds. If it does not alarm, make sure fresh batteries are correctly installed, and test it again. If the unit still does not alarm, replace it immediately

If the alarm does not test properly:

1. Make sure that fresh batteries are installed correctly. Be sure the Alarm is clean and dust-free.

3. Install fresh AA batteries* and test the Alarm again. **AWARNING!**

DO NOT try fixing the Alarm yourself - this will void your warranty! If the CO Alarm is still not operating properly, and it is still under warranty, please see "How to Obtain Warranty Service" in the Limited

Warranty. Install a new CO Alarm immediately. The Test/Silence button is the only proper way to test the CO Alarm. NEVER use vehicle exhaust! Exhaust may cause permanent damage

and voids your warranty. *For a list of acceptable replacement batteries, see "Regular Maintenance."

REGULAR MAINTENANCE

To keep the CO Alarm in good working order

• Test it every week using the Test/Silence button. Vacuum the CO Alarm cover once a month, using the soft brush attachment. Never use water, cleaners, or solvents, since these may damage

the unit. Test the CO Alarm again after vacuuming. Replace the batteries when the CO Alarm "chirps" about every minute (the low battery warning).

The low battery warning should last for 30 days, but you should replace the battery immediately to continue your protection

Choosing a replacement battery:

This CO Alarm requires two standard AA batteries. The following batteries are acceptable as replacements: Energizer E91. These replacement batteries are commonly available at local retail stores.

IMPORTANT!

Use only the replacement batteries listed. The unit may not operate properly with other batteries. Never use rechargeable batteries since they may not provide a constant charge.

ACAUTION! DO NOT spray cleaning chemicals or insect sprays directly on or near the CO Alarm. DO NOT paint over the CO Alarm. Doing so may cause ing chemicals or insect sprays directly on or near

ent damage

IMPORTANT! Household cleaners, aerosol chemicals, and other contaminants can affect the sensor. When using any of these materials near the CO Alarm, make sure the room is well ventilated.

WHAT YOU NEED TO KNOW ABOUT CO

WHAT IS CO?

CO is an invisible, odorless, tasteless gas produced when fossil fuels do not burn completely, or are exposed to heat (usually fire). Electrical appliances typically do not produce CO.

These fuels include: Wood, coal, charcoal, oil, natural gas, gasoline, kerosene, and propane.

Common appliances are often sources of CO. If they are not properly maintained, are improperly ventilated, or malfunction, CO levels can rise quickly. CO is a real danger now that homes are more energy efficient. "Air-tight" homes with added insulation, sealed windows, and other weatherproofing can "trap" CO inside

SYMPTOMS OF CO POISONING

These symptoms are related to CO POISONING and should be discussed with ALL household members

Mild Exposure: Slight headache, nausea, vomiting, fatigue ("flu-like" symptoms).

Medium Exposure: hrobbing headache, drowsiness, confusion, fast heart rate

Extreme Exposure: Convulsions, unconsciousness, heart and lung failure. Exposure to carbon monoxide can cause brain damage, death

AWARNING!

Some individuals are more sensitive to CO than others, including people with cardiac or respiratory problems, infants, unborn babies, pregnant mothers, or elderly people can be more quickly and severely affected by CO. Members of sensitive populations should consult their doctors fo advice on taking additional precautions.

FINDING THE SOURCE OF CO AFTER AN ALARM

Carbon monoxide is an odorless, invisible gas, which often makes it difficult to locate the source of CO after an alarm. These are a few of the factors that can make it difficult to locate sources of CO:

• House well ventilated before the investigator arrives.

Problem caused by "backdrafting."

 Transient CO problem caused by special circumstances. Because CO may dissipate by the time an investigator arrives, it may be difficult to locate the source of CO. BRK Brands, Inc. shall not be obligated to pay for any carbon monoxide investigation or service call.

HOW CAN I PROTECT MY FAMILY?

A CO Alarm is an excellent means of protection. It monitors the air and sounds a loud alarm before carbon monoxide levels become threatening for average, healthy adults.

A CO Alarm is not a substitute for proper maintenance of home appliances. To help prevent CO problems and reduce the risk of CO poisoning:

 Clean chimneys and flues yearly. Keep them free of debris, leaves, and nests for proper air flow. Also, have a professional check for rust and corrosion, cracks, or separations. These conditions can prevent proper air movement and cause backdrafting. Never "cap" or cover a chimney n any way that would block air flow.


 Test and maintain all fuel-burning equipment annually. Many local gas or oil companies and HVAC companies offer appliance inspections for a provide for a second sec nominal fee.

 Make regular visual inspections of all fuel-burning appliances. Check appli ances for excessive rust and scaling. Also check the flame on the burner and pilot lights. The flame should be blue. A yellow flame means fuel is not being burned completely and CO may be present. Keep the blower door on the furnace closed. Use vents or fans when they are available on all uel-burning appliances. Make sure appliances are vented to the outside Do not grill or barbecue indoors, or in garages or on screen porches. Check for exhaust backflow from CO sources. Check the draft hood

on an operating furnace for a backdraft. Look for cracks on furnace heat exchangers. Check the house or garage on the other side of shared wall.

 Keen windows and doors open slightly. If you suspect that CO is escaping into your home, open a window or a door. Opening windows and doors can significantly decrease CO levels.

In addition, familiarize yourself with all enclosed materials. Read this manual in its entirety, and make sure you understand what to do if your CO Alarm sounds.



Fuel-burning appliances like: portable heater, gas or wood burning fireplace gas kitchen range or cooktop, gas clothes dryer. **Damaged or insufficient venting:** corroded or disconnected water heater vent pipe, leaking chimney pipe or flue, or cracked heat exchanger, blocked or clogged chimney opening.

Improper use of appliance/device: operating a barbecue grill or vehicle in an enclosed area (like a garage or screened porch). Transient CO Problems: "transient" or on-again-off-again CO problems can be caused by outdoor conditions and other special circumstances

WHAT LEVELS OF CO CAUSE AN ALARM? Underwriters Laboratories Inc. Standard UL2034 requires residential CO Alarms to sound when exposed to levels of CO and exposure times as described below. They are measured in parts per million (ppm) of CO over time (in minutes)

UL2034 Required Alarm Points*:

- If the alarm is exposed to 400 ppm of CO, IT MUST ALARM BETWEEN 4 and 15 MINUTES.
- If the alarm is exposed to 150 ppm of CO, IT MUST ALARM BETWEEN 10 and 50 MINUTES.
- If the alarm is exposed to 70 ppm of CO, IT MUST ALARM BETWEEN 60 and 240 MINUTES.

* Approximately 10% COHb exposure at levels of 10% to 95% Relative Humidity (RH)

The unit is designed not to alarm when exposed to a constant level of 30 ppm for 30 days.

IMPORTANT!

CO Alarms are designed to alarm before there is an immediate life threat. Since you cannot see or smell CO, never assume it's not present.

 An exposure to 100 ppm of CO for 20 minutes may not affect average healthy adults, but after 4 hours the same level may cause headaches. An exposure to 400 ppm of CO may cause headaches in average, healthy adults after 35 minutes, but can cause death after 2 hours.

IMPORTANT!

This CO Alarm measures exposure to CO over time. It alarms if CO levels are extremely high in a short period of time, or if CO levels reach a certain minimum over a long period of time. The CO Alarm generally sounds an alarm before the onset of symptoms in average, healthy adults.

GENERAL LIMITATIONS OF CO ALARMS

This CO Alarm is intended for residential use. It is not intended for use in industrial applications where Occupational Safety and Health Administration (OSHA) requirements for carbon monoxide detectors must be met.

CO alarms may not waken all individuals. If children or others do not readily waken to the sound of the CO alarm, or if there are infants or family members with mobility limitations, make sure that someone is assigned to assist them in the event of an emergency.

CO Alarms will not work without power. This alarm requires two standard AA batteries to operate.

CO Alarms for Solar or Wind Energy users and battery backup power systems: AC powered CO Alarms should only be operated with true or pure sine wave inverters. Operating this Alarm with most battery-powered UPS (uninterruptible power supply) products or square wave or "quasi sine wave nverters will damage the Alarm. If you are not sure about your inverter or UPS type, please consult with the manufacturer to verify

This CO Alarm will not sense carbon monoxide that does not reach the sensor. This CO Alarm will only sense CO at the sensor. CO may be preser in other areas. Doors or other obstructions may affect the rate at which CO reaches the CO Alarm. For this reason, if bedroom doors are usually closed at night, we recommend you install a CO Alarm in each bedroom and in the allway between them.

CO Alarms may not sense CO on another level of the home. For example a CO Alarm on the second level, near the bedrooms, may not sense CO in the basement. For this reason, one CO Alarm may not give adequate warning. Complete coverage is recommended. Place CO Alarms on each level of the

For your records, please record:

5

First Alert® is a registered trademark of the First Alert Trust

Date Purchased

Date Installed:

Where Purchased:

Month/Year

home. Since these conditions can come and go, they are also hard to recreate during a CO investigation. **REGULATORY INFORMATION FOR CO ALARMS**

The following conditions can result in transient CO situations:

conditions such as:

fresh air

fireplace).

water heaters.

the above situations.

1. Excessive spillage or reverse venting of fuel appliances caused by outdoor

• Negative pressure differential resulting from the use of exhaust fans.

• Several appliances running at the same time competing for limited

• Vent pipe connections vibrating loose from clothes dryers, furnaces, or

• Obstructions in or unconventional vent pipe designs which can amplify

2. Extended operation of unvented fuel burning devices (range, oven,

3. Temperature inversions, which can trap exhaust close to the ground.

4. Car idling in an open or closed attached garage, or near a home.

These conditions are dangerous because they can trap exhaust in your

Wind direction and/or velocity, including high, gusty winds. Heavy air in the vent pipes (cold/humid air with extended periods between cycles).

Why is this important? Because you need to be warned of a potential CO problem while you can still react in time. In many reported cases of CO exposure, victims may be aware that they are not feeling well, but become disoriented and can no longer react well enough to exit the building or get help. Also, young children and pets may be the first affected. The average healthy adult might not feel any symptoms when the CO Alarm sounds. However, people with cardiac or respiratory problems, infants, unborn babies, pregnant mothers, or elderly people can be more quickly and severely affected by CO. If you experience even mild symptoms of CO poisoning, consult your doctor immediately!

Standards: Underwriters Laboratories Inc. Single and Multiple Station carbon monoxide alarms UL2034.

According to Underwriters Laboratories Inc. UL2034, Section 1-1.2: "Carbon monoxide alarms covered by these requirements are intended to respond to the presence of carbon monoxide from sources such as, but not limited to exhaust from internal-combustion engines, abnormal operation of fuel-fired appliances, and fireplaces. CO Alarms are intended to alarm at carbon monoxide levels below those that could cause a loss of ability to react to the dangers of Carbon Monoxide exposure." This CO Alarm monitors the air at the Alarm, and is designed to alarm before CO levels become life threatening. This allows you precious time to leave the house and correct the problem. This is only possible if Alarms are located, installed, and maintained as described in this manual.

Gas Detection at Typical Temperature and Humidity Ranges: The CO Alarm is not formulated to detect CO levels below 30 ppm typically. UL tested for false alarm resistance to Methane (500 ppm), Butane (300 ppm), Heptane (500 ppm), Ethyl Acetate (200 ppm), Isopropyl Alcohol (200 ppm) and Carbon Dioxide (5000 ppm). Values measure gas and vapor concentrations in parts per million

Audible Alarm: 85 dB minimum at 10 feet (3 meters)

CO Alarms may not be heard. The alarm horn loudness meets or exceeds current UL standards of 85 dB at 10 feet (3 meters). However, if the CO Alarm

is installed outside the bedroom, it may not wake up a sound sleeper or one who has recently used drugs or has been drinking alcoholic beverages. This is especially true if the door is closed or only partly open. Even persons who are awake may not hear the alarm horn if the sound is blocked by distance or closed doors. Noise from traffic, stereo, radio, television, air conditioner, or other appliances may also prevent alert persons from hearing the alarm horn. This CO Alarm is not intended for people who are hearing impaired.

CO Alarms are not a substitute for a smoke alarm. Although fire is a source of carbon monoxide, this CO Alarm does not sense smoke or fire. This CO Alarm senses CO that may be escaping unnoticed from malfunctioning furnaces, appliances, or other sources. Early warning of fire requires the installeting of amende alarms. installation of smoke alarms.

CO Alarms are not a substitute for life insurance. Though these CO Alarms warn against increasing CO levels, BRK Brands, Inc. does not warrant or imply in any way that they will protect lives from CO poisoning. Homeowners and renters must still insure their lives.

CO Alarms have a limited life. Although the CO Alarm and all of its parts have passed many stringent lests and are designed to be as reliable as possible, any of these parts could fail at any time. Therefore, you must test your CO Alarm weekly.

CO Alarms are not foolproof. Like all other electronic devices, CO Alarms have limitations. They can only detect CO that reaches their sensors. They may not give early warning to rising CO levels if the CO is coming from a remote part of the home, away from the CO Alarm.

TROUBLESHOOTING GUIDE				
PROBLEM	THIS MEANS	YOU SHOULD		
The light continues to flash (RED) and the horn "chirps" once every minute.	Low battery warning.	Install 2 new AA batteries*.		
The light flashes (RED) and the horn sounds 3 quick "chirps" every minute.	MALFUNCTION SIGNAL. CO Alarm needs to be replaced.	CO Alarms under warranty should be returned to manufacturer for replacement. See "Limited Warranty" for details.		
CO Alarm goes back into alarm 4 minutes after you press the Test/Silence button.	CO levels indicate a potentially dangerous situation.	IF YOU ARE FEELING SYMPTOMS OF CO POISONING, EVACUATE your home and call 911 or the Fire Department. If not, press the Test/Silence button again and keep ventilating your home.		
CO Alarm sounds frequently even though no high levels of CO are revealed in an investigation.	The CO Alarm may be improperly located. Refer to "Where to Install CO Alarms."	Relocate your alarm. If frequent alarms continue, have home rechecked for potential CO problems. You may be experiencing an intermittent CO problem.		

*For a list of acceptable replacement batteries, see "Page 4: Regular Maintenance." If you have any questions that cannot be answered by reading this manual, call Consumer Affairs at 1-800-323-9005

LIMITED WARRANTY

BRK Brands, Inc. ("BRK") the maker of BRK® brand and First Alert® brand products, warrants that for a period of five years from the date of purchase, this product will be free from defects in material and workmanship. BRK, at its option, will repair or replace this product or any component of the product found to be defective during the warranty period. Replacement will be made with a new or remanufactured product or component. If the product is no longer available, replacement may be made with a similar product of equal or greater value. This is your exclusive warranty.

This warranty is valid for the original retail purchaser from the date of initial retail purchase and is not transferable. Keep the original sales receipt. Proof of purchase is required to obtain warranty performance. BRK dealers, service centers, or retail stores selling BRK products do not have the right to alter, modify or any way change the terms and conditions of this warranty.

This warranty does not cover normal wear of parts or damage resulting from any of the following: negligent use or misuse of the product, use on improper voltage or current, use contrary to the operating instructions, disassembly, repair or alteration by anyone other than BRK or an authorized service center. Further, the warranty does not cover acts of God, such as fire, flood, hurricanes and tornadoes or any batteries that are included with this unit. BRK shall not be liable for any incidental or consequential damages caused by the breach of any express or implied warranty. Except to the extent prohibited by applicable law, any implied warranty. Consequential damages caused on a particular purpose is limited in duration to the duration of the above warranty. Some states provinces, or jurisdictions do not allow the exclusion or limitation of incidental or consequential damages or limitations on how long an implied warranty lasts, so

the above limitations or exclusion may not apply to you. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state, or province to province. How to Obtain Warranty Service:

Replacement date is five years after installation:

indicate the need to immediately replace the Alarm.

NOTE: End of Life Signal — Once the unit reaches the end of its lifecycle, the MALFUNCTION SIGNAL will sound once a minute to

6

Month/Yea

Printed in Mexico M08-0140-004 P 06/07

Service: If service is required, do not return the product to your retailer. In order to obtain warranty service, contact the Consumer Affairs Division at 1-800-323-9005, 7:30 AM to 5:00 PM, Central Standard Time, Monday through Friday. To assist in serving you, please have the model number and date of purchase available when calling. For Warranty Service return to: 25 Spur Drive, El Paso, TX 79906

Battery: BRK Brands, Inc. makes no warranty, express or implied, written or oral, including that of merchantability or fitness for any particular purpose, with