



PowerSure Personal XT 450 - 700 - 1250 VA

COMPREHENSIVE POWER PROTECTION FOR STAND-ALONE SYSTEM



NEW

PowerSure Personal XT

COMPREHENSIVE POWER PROTECTION FOR STAND-ALONE SYSTEM



Thanks to the new PowerSure Personal XT you can have continuous cost-effective power protection in your office or home.

It is specifically designed to protect PCs, Workstations, Network Nodes and also Fax, Scanners and Audio/Video equipment.

If the mains supply fails or moves outside an acceptable level, the PowerSure Personal XT offers up to 20 minutes of battery back up (depending on the actual load), giving ample time to protect the equipment and save files through Liebert's WEB based Multilink Software.

Benefits

- Protection up to 1250 VA
- Small Dimensions
- Plug and Play Operation
- Up to 4 output sockets
- Direct and Remote Monitoring
- MultiLink Software included
- Communication cable included
- Attractive design
- Phone, modem, data-lines surge suppression sockets

Applications

- PCs
- Workstations
- Small Servers and Network Nodes
- Fax
- Scanners
- Audio/Video equipment

MultiLink Software

- Multilink Software is the world's first UPS Software to be written in Java
- Operating with any Liebert UPS (including the Personal XT), it protects the network PCs or Servers from crashes caused by power failure
- Prevents the loss of valuable data by performing unattended, orderly shutdown on one computer or multiple networked computers with optional license kit
- Configurable responses to UPS status changes
- Notification via alphanumeric pagers, e-mail and on-screen messages
- It runs as part of an enterprise-wide SNMP solution or as stand alone shutdown management for a single file server
- Supports both serial interface and contact closure interface
- Manage and monitor UPSs over the network with optional license kit





Major Features

■ Protection up to 1250 VA

The PowerSure Personal XT is available in 3 power ratings: 450, 700, 1250 VA and covers all the applications from single PCs to network nodes through multiple workstation.

■ The smallest ups in its range


The high frequency design of the PowerSure Personal XT results in a very compact UPS. It can operate on your desk or on the floor, in vertical or horizontal position, protecting your computer equipment and your data using very little space.

■ Plug and play

The PowerSure Personal XT is very easy to use: the simple operation and the two LEDs provide you clear and complete information about the UPS status.

■ Everything you need is in the box

The PowerSure Personal XT comes complete with: UPS and User Manual, two output power cords communication cable, Multilink software CD, and warranty card.



■ Little maintenance

The PowerSure Personal XT requires very little maintenance: only the 5-years battery requires replacement. An automatic battery test verifies battery conditions and, if they are bad, a specific alarm is activated.

■ Output connection flexibility

The PowerSure Personal XT is equipped with up to four UPS protected output sockets to allow the maximum of flexibility in connecting several loads.

■ Phone and network surge suppression sockets

Surge sockets protect sensible hardware against voltage surges coming from lines (such as modem, fax, phone, network connections) which can seriously damage comms ports, motherboards, etc...

■ Direct and remote monitoring

The DB9 communication port and Multilink Software (provided) allow you to monitor your PowerSure Personal XT or to shut down your PC directly through the cable (provided) or remotely through the Net.

■ More features

Standard features include automatic battery test and "autorestart" function (the UPS automatically restarts when mains comes back after an extended outage and full discharge of the battery). Audible and visual alarms for mains failure, low battery, UPS overload, short circuit, and over temperature are available.


■ Attractive design

The PowerSure Personal XT, with its ergonomic shape was specifically designed to be an attractive addition to any office or home.

General Features

Model	450 VA - 270 W	700 VA - 420 W	1250 VA - 750 W
Power rating	Off-Line		
Technology	230 VAC (197 - 262 VAC)		
Input			
Voltage	230 VAC (197 - 262 VAC)		
Frequency	50Hz \pm 4Hz; 60Hz \pm 4Hz		
Amperage (maximum)	2.6 A 4.0 A 7.0 A		
Output			
Voltage	230 VAC \pm 10%		
Frequency	50Hz/60Hz \pm 1Hz		
Wave form	STEP		
Battery			
Type	Valve-regulated, nonspillable, lead acid		
Quantity x Voltage x Rating	(1) x 12V x 7 Ah	(1) x 12V x 9 Ah	(2) x 12V x 7 Ah
Approved Battery Manufacturers	CSB, Panasonic, BB Battery and Yuasa		
Transfer Time	< 10ms typical		
Operating Back up time	> 10 minutes		
Recharge time	8hr up to 90%		
Connections			
Input sockets	1 x EN60320/C14		
Output sockets	3 x EN60320/C13	3 x EN60320/C13	4 x EN60320/C13
DB9 Communication port	Yes		
Surge Suppression Sockets	Yes		
Physical			
Dimensions wxhxd (mm)	80*176,5*233	80*176,5*233	92*238*283
Shipping Dimensions wxhxd (mm)	155*270*300	155*270*300	192*347*390
Net Weight, Kg	3.5	3.6	6.5
Gros Weight, Kg	4.5	4.6	7.9
Operating Environment			
Operation temperature	0°C to 40°C		
Storage Temperature	-15°C to 40°C		
Operation humidity	20% to 90%		
Packaging			
N° of output cables	2		
Multilink software	CD Included		
Multilink communication	Cable Included		
Standard warranty	2 years		
Warranty extension (1 or 3 years)	Available		

While every precaution has been taken to ensure accuracy and completeness in this brochure, Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions. © 2000 Liebert Corporation. All rights reserved throughout the world. Specifications subject to change without notice. All names referred to are trademarks or registered trademarks of their respective owners.



Liebert HIROSS UPS Headquarters
Via Gioacchino Rossini,6
20098 - S.Giuliano Milanese (MI)
tel.+39 02 98250 1 fax +39 02 98250337
info.ups@liebert-hiross.com

Liebert HIROSS Services Headquarters
Via Gioacchino Rossini,6
20098 - S.Giuliano Milanese (MI)
tel.+39.02 98250 1 fax +39 02 98250338
service@liebert-hiross.com

Liebert HIROSS United Kingdom
Globe Park - Marlow - Bucks - SL71YG
tel.+44 1628 403232 fax +44 1628 403293