

## Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an \* are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

| Brand *                | Lexmark                          | Logo                         |
|------------------------|----------------------------------|------------------------------|
| Company name *         | Lexmark International, Inc.      | I DAZNA A DIZ                |
| Contact information *  | Nadia Martin (USA)               | <b>LEXM</b> ARK <sub>™</sub> |
| Internet site *        | www.lexmark.se / www.lexmark.com |                              |
| Additional information |                                  |                              |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. |  |  |  |  |  |  |
|--|--|--|--|--|--|--|
| Type of product *  | Single Function Color Laser Printer                          |  |  |  |  |  |
| Commercial name *  | Lexmark CS410dn, Lexmark CS410dtn, Lexmark CS410n            |  |  |  |  |  |
| Model number *   | CS410dn, CS410dtn, CS410n                                    |  |  |  |  |  |
| Issue date *   | Rev. February 26, 2014                                       |  |  |  |  |  |
| Intended market *  | ☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other |  |  |  |  |  |
| Additional information   |  |  |  |  |  |  |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

| Quality | Control   | Requireme | nt met |
|---------|---|-----------|--------|
| Item    |   | Yes       | No     |
| QC1 *   | The company enforces an internal quality control scheme to ensure the correctness of this eco declaration   |           |        |
| QC2 *   | The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org). |           |        |

| Model number * | CS410dn, CS410dtn, CS410n |      |         |
|----------------|---------------------------|------|---------|
| Issue date *   | Rev. February 26, 2014    | Logo | LEXMARK |

| Product | t environmental attributes - Legal requirements   | Require     | emen | t met |
|---------|---|-------------|------|-------|
| Item    |   | Yes         | No   | n.a.  |
| P1      | Hazardous substances and preparations   |             |      |       |
| P1.1*   | Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)   |             |      |       |
| P1.2*   | Products do not contain Asbestos (see legal reference).  Comment: Legal reference has no maximum concentration value.   |             |      |       |
| P1.3*   | Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.  |             |      |       |
| P1.4*   | Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).   | $\boxtimes$ |      |       |
| P1.5*   | Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).  |             |      |       |
| P1.6*   | Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.  |             |      |       |
| P1.7*   | Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)  |             |      |       |
| P1.8*   | Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference).  Comment: Legal reference has no maximum concentration values.  |             |      |       |
| P1.9*   | Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference).  Comment: Max limit in legal reference when tested according to EN1811:1998.   |             |      |       |
| P1.10*  | REACH Article 33 information about substances in articles is available at (add URL or mail contact):<br>REACH Program Manager, HOD9237, 740 W. New Circle Rd., Lexington, KY 40550  |             |      |       |
| P2      | Batteries   |             |      |       |
| P2.1*   | If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference) |             |      |       |
| P2.2*   | Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)  |             |      |       |
| P2.3*   | Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)   |             |      |       |
| P3      | Safety, EMC connection to the telephone network and labeling  |             |      |       |
| P3.1*   | The product complies with legally required safety standards as specified (see legal reference).   |             | П    |       |
| P3.2*   | The product complies with legally required standards for electromagnetic compatibility (see legal reference).   |             |      |       |
| P3.3*   | If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).   |             |      |       |
| P3.4*   | The product is labeled to show conformance with applicable legal requirements (see legal reference).  | $\square$   | П    | П     |
| P4      | Consumable materials  |             |      |       |
| P4.1*   | If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).   |             |      |       |
| P4.2*   | If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).  |             |      |       |
| P4.3*   | If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the  |             | ∺    | +     |
|         | product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).   |             |      |       |
| P5      | Product packaging   |             |      |       |
| P5.1*   | Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.   | t 🔀         |      |       |
| P5.2*   | Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).   | $\boxtimes$ |      |       |
| P5.3*   | The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference).  Comment: Legal reference has no maximum concentration values.   | I 🔀         |      |       |
| I       | Comment. Legal reference has no maximum concentration values.   |             |      |       |

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

| Model number *  | CS410dn, CS410dtn, CS410n   |        |                 |
|-----------------|---|--------|-----------------|
| Issue date *    | Rev. February 26, 2014  | Logo   | <b>LEXMARK</b>  |
|                 |   |        |                 |
| Product environ | mental attributes - Market requirements - Environmental conscious | desian | Requirement met |

| Product | environmental attributes - Market requirements - Environmental conscious design   | Require     | ment                    | met            |
|---------|---|-------------|-------------------------|----------------|
| Item    | *=mandatory to fill in. Additional information regarding each item may be found under P14.  | Yes         | No                      | n.a.           |
| P6      | Treatment information   |             |                         |                |
| P6.1*   | Information for recyclers/treatment facilities is available (see legal reference).  | $\boxtimes$ |                         |                |
| P7      | Design Disassembly, recycling   |             |                         |                |
| P7.1*   | Parts that have to be treated separately are easily separable   | $\square$   | $\Box$                  |                |
| P7.2*   | Plastic materials in covers/housing have no surface coating.  |             | T                       |                |
| P7.3*   | Plastic parts >100g consist of one material or of easily separable materials.   |             | Ħ                       | Ħ              |
| P7.4*   | Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.   |             | Ħ                       | Ħ              |
| P7.5    | Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  |             | Ħ                       | П              |
| P7.6*   | Labels are easily separable. (This requirement does not apply to safety/regulatory labels).   |             | Ħ                       | Ħ              |
|         | Product lifetime  |             |                         |                |
| P7.7*   | Upgrading can be done e.g. with processor, memory, cards or drives  |             |                         | П              |
| P7.8*   | Upgrading can be done using commonly available tools  |             | Ħ                       | Ħ              |
| P7.9.   | Spare parts are available after end of production for: 5 years  |             |                         | П              |
| P7.10   | Service is available after end of production for: 5 years   | _           |                         | Ħ              |
|         | Material and substance requirements   |             |                         |                |
| P7.11*  | Product cover/housing material type:  Material type: HIPS Material type: PC/ABS   |             |                         |                |
| P7.12   | Material type: ABS Material type: HIPS Material type: PC/ABS Electrical cable insulation materials of power cables are PVC free.  |             | $\square$               |                |
| P7.13   | Electrical cable insulation materials of signal cables are PVC free   |             | $\overline{\mathbb{X}}$ | H              |
| P7.14   | All cover/housing plastic parts >25g are free from chlorine and bromine.  |             |                         | +              |
| P7.15   | All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See  |             |                         | $\blacksquare$ |
|         | Note B2)  |             |                         |                |
| P7.16   | Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:  |             |                         |                |
| P7.17   | Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #:              |             |                         |                |
|         | Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16)   |             |                         |                |
| P7.18   | Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations is concentrations above 0.1%:  | า 🔲         |                         |                |
|         | Comment: No legal limits exist, this is a market requirement.  1. Chemical name: , CAS #:  2. Chemical name: , CAS #:  3. Chemical name: , CAS #:   |             |                         |                |
|         | Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40), FR(17), FR(16), FR(50)   |             |                         |                |
| P7.19   | Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) |             |                         |                |
| P7.20   | Of total plastic parts' weight >25g, recycled material content is <i>up to 11</i> %.  |             |                         |                |
| P7.21   | Of total plastic parts' weight >25g, biobased material content is %.  |             |                         |                |
| P7.22   | Light sources are free from mercury   | $\boxtimes$ |                         |                |
| P8      | If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg  Batteries mg  |             |                         |                |
| P8.1*   | Battery chemical composition: Lithium Manganese Dioxide, LiMnO2   |             |                         |                |
| P8.2    | Batteries meet the requirements of the following voluntary program/s:   |             |                         | Ħ              |

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

| Model number * | CS410dn, CS410dtn, CS410n |      |   |         |
|----------------|---------------------------|------|---|---------|
| Issue date *   | Rev. February 26, 2014    | Logo | ] | LEXMARK |

| Tempton  | Product environmental attributes - Market requirements (continued) Requirement met |                          |                                  |                   |      |                        |              |                   |
|--|--|--------------------------|----------------------------------|-------------------|------|------------------------|--------------|-------------------|
| For the product the following power levels or energy consumptions are reported:   Energy mode *  | Item   |                          |                                  |                   |      |                        | Yes N        | lo n.a.           |
| Power level at 100 V AC   Power level at 1           | e, i   |                          |                                  |                   |      |                        |              |                   |
| 100 V AC   | 9.1 For the product the  | e following power levels | or energy consum                 | ptions are report | ted: |                        |              |                   |
| Ready Mode   26.8 W   27.4 W   27.0 W   Energy Star I E V2.0   | Energy mode *  |                          |                                  |                   | at   |                        | for ener     | gy                |
| Siep Mode   2.9 W   2.9 W   2.9 W   Energy Star I E V2.0   | Printing   | <b>537</b> W             | <b>529</b> W                     | <b>504</b> W      |      | Corporate Standard     |              |                   |
| Hibernate Mode  0.35 W 0.37 W 0.39 W EC 62301    Continued of Mode         | Ready Mode   | 26.8 W                   | <b>27.4</b> W                    | <b>27.0</b> W     |      | Energy Star I E V2.0   |              |                   |
| Off Mode    O.0 W   O.0 W   IEC 62301  | Sleep Mode   | 2.9 W                    | 2.9 W                            | 2.9 W             |      | Energy Star I E V2.0   |              |                   |
| EPS No-load  | Hibernate Mode   | 0.35 W                   | 0.37 W                           | 0.39 W            |      | IEC 62301              |              |                   |
| EPS No-load   W   W   W   W   W   W   W   W   W  | Off Mode   | 0.0 W                    | 0.0 W                            | <i>0.0</i> W      |      | IEC 62301              |              |                   |
| (External power supply / charger plugged in the wall outlet but disconnected from the product.)  PTEC Typical Energy Consumption  TEC¹ Typical Energy Consumption  ETEC * Rybical Energy Star I E V2.0  Display resolution *: Megapixels  Print Speed * : 32 Images per minute  Energy Star I E V2.0  Default time to enter energy save mode: 30 minutes  Energy Star I E V2.0  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s: ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment  Others specify: RAL-UZ 122/RAL-UZ 171  P10 Emissions  Noise emission - Declared according to ISO 9296  P10.1 Mode Mode description  Declared A-weighted sound pressure level L <sub>p/Am</sub> (dB)  Operator position  Bystander positions  Desktop Operator attended)  Operator obstition  Bystander positions  Desktop Operator attended)  Operator obstition  Bystander positions  Operator position  Bystander positions  Operator obstition  Bystander positions  Operator obstition  Bystander positions  Operator obstition  Bystander position  Conference of the product over the mode of the product over the mode of the product over the mode of the product over |  | W                        | W                                | W                 |      |                        |              |                   |
| charger plugged in the wall outlet but disconnected from the product.)  PTEC * Typical Energy Consumption  TEC * Typical Energy Consumption  ETEC * Typical Energy Consumption   | EPS No-load  | EPS No-load W W W        |                                  |                   |      |                        |              |                   |
| Typical Energy Consumption  TEC * Typical Energy Consumption  ETEC * Typical Energy Star I E V2.0  Display resolution*: Megapixels  ETEC * Typical Energy Star I E V2.0  Display resolution*: Megapixels  Energy Star I E V2.0  Default time to enter energy save mode: 30 minutes  Energy Star I E V2.0  Default time to enter energy save function is provided with the product.  P9.2* Information about the energy save function is provided with the product.  Energy Star I E V2.0  Desaur I Energy Star I Ev2.0  Desaur I Energ         | (External power supply / charger plugged in the wall outlet but disconnected from  |                          |                                  |                   |      |                        |              |                   |
| Typical Energy Consumption  ETEC * Annual Energy Consumption   | • • = =  | W                        | W                                | W                 |      |                        |              |                   |
| Annual Energy Consumption  Display resolution*: Megapixels  Print Speed * : 32 Images per minute  Default time to enter energy save mode: 30 minutes  Pin Information about the energy save function is provided with the product.  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 122/RAL-UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared A-weighted sound power level L <sub>WAd</sub> (B)  Operator position Bystander positions  Desktop Onerator position Desk side Operator attended)  Idle * Ready * 3.2  |  | 2.5 kWh/week             | 2.4 kWh/week                     | 2.4 kWh/week      |      | Energy Star I E V2.0   |              |                   |
| Print Speed * : 32 Images per minute  Default time to enter energy save mode: 30 minutes  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s:  |  | kWh/year                 | kWh/year                         | kWh/ye            | ar   |                        |              |                   |
| Default time to enter energy save mode: 30 minutes  P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s:  | Display resolution* : M  | egapixels                | l                                | · ·               |      |                        |              |                   |
| P9.2* Information about the energy save function is provided with the product.  P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 122/RAL-UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared A-weighted sound power level L <sub>WAd</sub> (B)  Operator position Desktop or Desk side Operator attended) Operation Deplex Mono Printing, Normal Mode 6.6 51  Other mode Duplex Mono Printing, Quiet Mode 6.2 48  Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)   | Print Speed * : 32 Image   | es per minute            |                                  |                   |      | ISO 24734 (US Letter)  |              |                   |
| P9.3* The product meets the energy requirements of the following voluntary program/s:  ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 122/RAL-UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode Mode description Declared A-weighted sound pressure level L <sub>pAm</sub> (dB)  Declared A-weighted sound pressure level L <sub>pAm</sub> (dB)  Operator position Desktop Operator attended)  Idle * Ready * 3.2 (only if product is not operator attended)  Other mode Duplex Mono Printing, Normal Mode * 6.6 51  Other mode Duplex Mono Printing, Quiet Mode 6.2 48  Measured according to: SO7779 ECMA-74  Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)   | Default time to enter energy sa  | ave mode: 30 minutes     |                                  |                   |      | Energy Star I E V2.0   |              | $-\frac{1}{\Box}$ |
| ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 122/RAL-UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode  | P9.2* Information about  | the energy save function | on is provided with t            | he product.       |      |                        |              |                   |
| ENERGY STAR® version: 2.0 Tier: Product category: Imaging Equipment Others specify: RAL-UZ 122/RAL-UZ 171  P10 Emissions  Noise emission – Declared according to ISO 9296  P10.1 Mode  | P9.3* The product meets  | the energy requiremen    | nts of the following             | voluntary prograr | m/s: |                        |              |                   |
| $ \begin{array}{ c c c c c } \hline \textbf{Noise emission} - \textbf{Declared according to ISO 9296} \\ \hline \textbf{P10.1} & \textbf{Mode} & \textbf{Mode description} & \textbf{Declared A-weighted sound power} \\ \hline \textbf{Idle} & *\textbf{Ready} & *\textbf{3.2} & \textbf{16} \\ \hline \textbf{Operation} & *\textbf{Duplex Mono Printing, Normal Mode} & *\textbf{6.6} & \textbf{51} \\ \hline \textbf{Other mode} & \textbf{Duplex Mono Printing, Quiet Mode} & \textbf{6.2} & \textbf{48} \\ \hline \textbf{Measured according to:} & \textbf{ISO7779} & \textbf{ECMA-74} \\ \hline \textbf{Other} & (\text{only if not covered by ECMA-74 with L_{pAm} measurement distance} & \textbf{m}) \\ \hline \end{array} $  | ENERGY STAR®   | version: 2.0 Tier: Prod  | luct category: <mark>Imag</mark> |                   |      |                        |              |                   |
| $ \begin{array}{ c c c c c c }\hline P10.1 & Mode & Mode description & Declared & Declared A-weighted sound pressure level $L_{pAm}$ (dB) \\ \hline & & & & & & & & & & & & & & & & & &$   |  |                          |                                  |                   |      |                        |              |                   |
| $\begin{array}{c ccccccccccccccccccccccccccccccccccc$  |  |                          | ISO 9296                         | Deeleved          | 1    | Declared A weighte     | -d           | 1                 |
|  | P10.1 Mode   | viode description        |                                  | A-weighted        |      | 9                      |              |                   |
| Desktop   Only if product is not operator attended   |  |                          |                                  | •                 | Oper | rator position Bystar  | nder positio | ns                |
| Idle * Ready * 3.2 16 Operation * Duplex Mono Printing, Normal Mode * 6.6 51 Other mode Duplex Mono Printing, Quiet Mode 6.2 48  Measured according to: SO7779 ECMA-74 Other (only if not covered by ECMA-74 with LpAm measurement distance m)   |  |                          |                                  | WAU ( )           |      | Desktop                |              | $\preceq$         |
| Operation * Duplex Mono Printing, Normal Mode * 6.6 51  Other mode Duplex Mono Printing, Quiet Mode 6.2 48  Measured according to: ISO7779 ECMA-74  Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)  |  |                          |                                  |                   |      | Or I lock cide   \ \ \ | •            |                   |
| Other mode   Duplex Mono Printing, Quiet Mode 6.2 48  Measured according to:  ISO7779  ECMA-74  Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)  |  | •                        |                                  |                   |      |                        |              |                   |
| Measured according to: SISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)  |  |                          |                                  |                   |      |                        |              |                   |
| Other (only if not covered by ECMA-74 with L <sub>pAm</sub> measurement distance m)  |  |                          | •                                | 6.2               |      | 48                     |              |                   |
|  | Measured according   | _                        |                                  | Iby FCMA 74 with  | hl.  | measurement distance   | m)           |                   |
| T10.2 The product meets the acoustic hoise requirements of the following voluntary program/s. RAL-UZ 122/RAL- 1×1 1 1 1 1  | P10.2 The product meets  |                          |                                  |                   |      |                        |              | $\neg$            |

| Model number * | CS410dn, CS410dtn, CS410n |      |          |
|----------------|---------------------------|------|----------|
| Issue date *   | Rev. February 26, 2014    | Logo | LEXMARK. |

| Product       | environmental attributes - Market requirements (continued)   | Require     | ment            | met         |
|---------------|--|-------------|-----------------|-------------|
| Item          |  | Yes         | No              | n.a.        |
|               | Chemical emissions from printing products  |             |                 |             |
| P10.3*        | Test performed according to ECMA-328 (ISO/IEC 28360) standard, other specify: RAL-UZ 122/RAL-UZ 171  |             |                 |             |
| P10.4         | Typical emission rate (print phase) is (mg/h):  Dust <1.8 Ozone <0.06 Styrene 0.55 Benzene <0.07 TVOC 18   |             |                 |             |
| P10.5         | Chemical emission requirements of the following voluntary program/s RAL-UZ 122/RAL-UZ 171 are met for:   |             |                 |             |
|               | Dust ☑ Ozone ☑ Styrene ☑ Benzene ☑ TVOC ☑  |             |                 |             |
| B             | Electromagnetic emissions  |             |                 |             |
| P10.6         | Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary program/s:  | Ш           | Ш               | Ш           |
| P11           | Consumable materials for printing products   |             | _               |             |
| P11.1*        | A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).   |             | Щ.              | Щ.          |
| P11.2*        | Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.  |             | <u> </u>        | <u> </u>    |
| P11.3*        | 2-sided (duplex) printing/copying is an integrated product function.   | $\boxtimes$ |                 |             |
| P12           | Ergonomics for computing products  |             |                 |             |
| P12.1*        | The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.  |             |                 | $\boxtimes$ |
| P12.2*        | The physical input device meets the requirements of ISO 9995 and ISO 9241-410.   |             |                 | $\boxtimes$ |
| P13           | Packaging and documentation  |             |                 |             |
| P13.1*        | Product packaging material type(s): Corrugated weight (kg): 2.542  |             |                 |             |
|               | Product packaging material type(s): <i>Polystyrene, expanded</i> Product packaging material type(s): <i>High Density Polyethylene</i> weight (kg): <i>0.204</i> weight (kg): <i>0.277</i>                        |             |                 |             |
|               | Low Density Polyethylene, expanded – 0.204 kg  |             |                 |             |
| P13.2*        | Product plastic packaging is free from PVC.  | $\boxtimes$ |                 |             |
| P13.3*        | Specify media for user and product documentation (tick box):  Electronic , Paper , Other .   |             |                 |             |
| P13.4*        | For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0%  |             |                 |             |
| Rev.<br>P13.5 | User and product documentation do not contain chlorine bleached paper  |             |                 |             |
| P14           | Additional information (See Note B4)   |             |                 |             |
| P1. 1         | This product uses RoHS exemptions for lead used in small amounts for specific applications.  |             |                 |             |
| P2.1          | The battery contained within this product should be disposed of properly with the product. The product is properly lad disposal symbol and instructions for such disposal is listed in the product User's Guide. | eled with   | h the W         | /EEE        |
| P2.3          | The battery contained within this product meets the exception listed. The battery is not intended to be removed by the however, is designed for easy removal by recyclers and service providers.                 | ne custom   | ner;            |             |
| P7.14         | A small amount of bromine may be present in covers due to sourcing post consumer recycled content. No bromine we in the processing of these parts.   | ıs intentic | onally o        | ıdded       |
| P7.20         | Per IEEE 1680.2 PCR calculation.   |             |                 |             |
| P9.1          | Information provided in P9.1 is for products with firmware FW LW30.VY2.P300 or higher. Print speed listed is Letter; A The following table provides energy data for products with lower levels of firmware:      | \4 speed i  | is <b>30</b> pp | m.          |
|               |  |             |                 |             |
|               |  |             |                 |             |

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

| P9 E                    | nergy consumption                                 | on  |                            |                            |   |  |
|-------------------------|---|---|----------------------------|----------------------------|---|--|
| 9.1 F                   | or the product the t                              | following power levels                                      | or energy consumpt         | tions are reported:        |   |  |
| Energy mode             | *   | Power level at<br>100 V AC                                  | Power level at<br>115 V AC | Power level at<br>230 V AC | Reference / Standard for energy modes and test method *     |  |
| Printing                |   | 537 W   | 529 W                      | 504 W                      | Corporate Standard  |  |
| Ready Mode              | ,   | 26.6 W  | 27.9 W                     | 25.0 W                     | Energy Star I E V1.2  |  |
| Sleep Mode              |   | 4.8 W   | 4.9 W                      | 4.9 W                      | Energy Star I E V1.2  |  |
| Hibernate M             | ode   | 0.35 W  | 0.37 W                     | 0.39 W                     | IEC 62301   |  |
| Off Mode                |   | 0.0 W   | 0.0 W                      | 0.0 W                      | IEC 62301   |  |
|                         |   | W   | W                          | W                          |   |  |
| EPS No-load             |   | W   | W                          | W                          |   |  |
|                         | ver supply /<br>ged in the wall<br>connected from |   |                            |                            |   |  |
| PTEC *<br>Typical Energ | gy Consumption                                    | W   | W                          | W                          |   |  |
| TEC * Typical Energ     | gy Consumption                                    | 2.7 kWh/week  | 2.6 kWh/week               | 2.6 kWh/week               | Energy Star I E V1.2  |  |
| ETEC * Annual Energ     | gy Consumption                                    | kWh/year  | kWh/year                   | kWh/year                   |   |  |
| Display resol           | ution* : Me                                       | gapixels  |                            |                            |   |  |
| Print Speed *           | : 32 Images                                       | per minute  |                            |                            | Corporate Standard  |  |
| Default time t          | to enter energy sav                               | e mode: 30 minutes  |                            |                            | Energy Star I E V1.2  | <del>                                     </del> |
| P9.2* II                | nformation about th                               | e energy save function                                      | n is provided with the     | e product.                 |   |  |
| E                       |   | he energy requiremen<br>ersion: 1.2 Tier: 1 Pro<br>. UZ 122 |                            |                            |   |  |
| Duplex da               | ta does not a <sub>l</sub>                        | oply to the CS41  | On model.                  |                            |   |  |
|                         |   | d in P10.4 is for a<br>Ozone – <0.06 i                      |                            |                            | nzene – <0.07 mg/h; Dust –<:                                | 1.8 mg/h ; and TVOC – 10 mg/h                    |
| Duplex is I             | not an integra                                    | ited product fun  | ction of the CS            | 5410n model.               |   |  |
|                         | for CS410n a<br>for CS410dtn                      | nd CS410dn disp   | olayed in 13.1             |                            |   |  |
| Product po              | ackaging mat                                      | erial type(s): Co<br>erial type(s): Po                      | -                          |                            | kg): 0.304  |  |
| Low Densi               |   | erial type(s): Hig<br>ne, expanded –                        |                            | yethylene weigl            | nt (kg): 0.277  |  |
| Additiona               | l company inf                                     |   |                            |                            | may be found at http://lexm<br>nay be found at http://lexma |  |
| Lexmark S               | weden is con                                      | nected to REPA  | and El-kretsen             | ı                          |   |  |

## Legal references Europe Annex B

| Reference  | Declaration item             |
|--|------------------------------|
| 2002/95/EC (ROHS Directive)  | P1.1, P4.1                   |
| REACH, Annex XVII  | P1.6, P1.8, P4.2             |
| REACH, Annex XVII  | P1.4                         |
| REACH, Annex XVII  | P1.2                         |
| REACH, Annex XVII  | P1.7                         |
| REACH, Annex XVII  | P1.9                         |
| Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000  | P1.3                         |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002 | P1.5                         |
| 2006/66/EC (Battery and accumulators Directive)  | P2.1, P2.2, P2,3, P3.4, P8.1 |
| 2006/95/EC (Low Voltage Directive)   | P3.1, 3.4                    |
| 2004/108/EEC (New EMC Directive)   | P3.2, 3.4                    |
| 1999/5/EC (R&TTE Directive)  | P3.3, 3.4                    |
| "REACH" Regulation (1907/2006), annex VII  | P1.10                        |
| (EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)                       | P4.3                         |
| REACH article 31, annex II   | P4.3                         |
| 2004/12/EC (Directive on packaging and packaging waste)  | P5.1                         |
| (97/129/EC) (Commission Decision on Identification<br>System for Packaging Materials               | P5.2                         |
| 2037/2000/EC Regulation on Substances that Deplete the Ozone Layer                                 | P5.3                         |
| 2002/96/EC (WEEE directive)  | P3.4, P6.1                   |
| (EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)                       | P7.19                        |