

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5F1 Morrisville, North Carolina 27560 alcarter@lenovo.com	lenovo
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	t.html
Additional information	The latest version of this document can be found at	
	http://www.lenovo.com/social_responsibility/us/en/datasheets_	notebooks.html

	ased on product specification or test results based obtained from sample testing), that the product ts given in this declaration.
Type of product *	Notebook Computer
Commercial name *	Lenovo S41-35, Lenovo S41-75
Model number *	80JW,80JR
Issue date *	2015-05-13
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).		

Model n	umber *	80JW,80JR			
Issue da	te *	2015-05-13 Logo	lend	vo	
Product	t environ	mental attributes - Legal requirements	Require	ment	t met
Item			Yes	No	n.a.
P1		ous substances and preparations			
P1.1*	chromiu	s do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent m, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See erence and Note B1)			
P1.2*	Products	s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.	\square		
P1.3*	Products hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.			
P1.4*	Products terpheny	s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated /l (PCT) in preparations (see legal reference).	\boxtimes		
P1.5*		s do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in n containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\boxtimes		
P1.6*	Textile a Tris-(azi	nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). nt: Legal reference has no maximum concentration values.			
P1.7*	Textile a	ind leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split c amines. (See legal reference and Note B1)			\square
P1.8*	Wooden pentach	binatic annues. (See legal reference and Note BT) boden parts do not contain arsenic and chromium as a wood preservation treatment as well as ntachlorophenol and derivatives (see legal reference). Imment: Legal reference has no maximum concentration values.			\square
P1.9*	Parts wi microgra	h direct and prolonged skin contact do not release nickel in concentrations above 0.5 m/cm²/week (see legal reference). nt: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): ww.lenovo.com/social_responsibility/us/en/materials.html	\square		
P2	Batterie	S			
P2.1*	more that marked	oduct contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is I in user manual. (See legal reference)			
P2.2*	Button c	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			
P2.3*	Batteries design c	s and accumulators are easily removable by either users or service providers (as dependent on the of the product). Exception: Batteries that are permanently installed for safety, performance, medica ntegrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety,	EMC connection to the telephone network and labeling			
P3.1*	The pro	duct complies with legally required safety standards as specified (see legal reference).	\boxtimes		
P3.2*	The proo	duct complies with legally required standards for electromagnetic compatibility (see legal e).	\boxtimes		
P3.3*	with lega	ct is intended for connection to a public telecom network or contains a radio transmitter, it complies ally required standards for radio and telecommunication devices (see legal reference).	; 🖂		
P3.4*	The pro	duct is labeled to show conformance with applicable legal requirements (see legal reference).	\square		
P4		nable materials			
P4.1*	legal ref	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see erence and Note B1).			
P4.2*		er is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\square
P4.3*	product/	/toner formulation/preparation is classified as hazardous according to applicable regulations, the packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these nents is available (see legal reference).			
P5		packaging			
P5.1*	hexavale	ng and packaging components do not contain more than 0.01% lead, mercury, cadmium an ent chromium by weight of these together.	d 🔀		
P5.2*		ackaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).			
P5.3*	Protocol	duct packaging material is free from ozone depleting substances as specified in the Montrea (see legal reference). nt: Legal reference has no maximum concentration values.	al 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model nı		80JW,80JR			
ssue dat	te *	2015-05-13 Logo	leno	vo	
Product		mental attributes - Market requirements - Environmental conscious design	Require	ment	met
tem		atory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a
P6		nt information			
P6.1*	Informati	on for recyclers/treatment facilities is available (see legal reference).			
P7	Design				
		mbly, recycling It have to be treated separately are easily separable			
P7.1*					
P7.2*		naterials in covers/housing have no surface coating.	<u> </u>		
P7.3*		arts >100g consist of one material or of easily separable materials.			
P7.4*	•	arts >25g have material codes according to ISO 11469 referring ISO 1043.	\square		
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly available tools.		\square	
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
	Product	lifetime			
P7.7*	Upgradir	ig can be done e.g. with processor, memory, cards or drives		\boxtimes	
P7.8*	Upgradir	g can be done using commonly available tools	\boxtimes		
P7.9.	Spare pa	arts are available after end of production for: 5 years			
P7.10		s available after end of production for: 5 years			
		and substance requirements			
P7.11*		cover/housing material type:			
	Material	type: AL-5052 Material type: Material type:			
P7.12	Electrica	I cable insulation materials of power cables are PVC free.	\boxtimes		
P7.13	Electrica	I cable insulation materials of signal cables are PVC free	\square		
P7.14	All cover	/housing plastic parts >25g are free from chlorine and bromine.		Ē	
P7.15	All printe	d circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (Se	e 🗌		
	Note B2				
P7.16		tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:	\boxtimes		
P7.17	Alt. 1 Chemica	l specifications of flame retardants in printed circuit boards >25g (without components): additive) □, TBBPA (reactive) ⊠, Other; chemical name: , CAS #:			
P7.18		I specifications of flame retardants in printed circuit boards (without components) >25g according 3-4: Brominated Epoxy Resin See P14			
	concentr Commer 1. Chem 2. Chem 3. Chem 4. Chem 5. Chem 7. Chem 8. Chem 10. Cher 11. Cher 12. Cher 13. Cher 14. Cher Alt. 2 Chemica	etarded plastic parts >25g contain the following flame retardant substances/preparations i ations above 0.1%: tt: No legal limits exist, this is a market requirement. ical name: <i>FR3002</i> , CAS #: <i>107-13-1</i> , Supplier: <i>BAYBLEND</i> ical name: <i>FR3002</i> , CAS #: <i>100-42-5</i> , Supplier: <i>BAYBLEND</i> ical name: <i>FR3002</i> , CAS #: <i>100-42-5</i> , Supplier: <i>BAYBLEND</i> ical name: <i>FR3002</i> , CAS #: <i>100-40-3</i> , Supplier: <i>BAYBLEND</i> ical name: <i>FR3002</i> , CAS #: <i>100-41-4</i> , Supplier: <i>BAYBLEND</i> ical name: <i>FR3002</i> , CAS #: <i>100-41-4</i> , Supplier: <i>BAYBLEND</i> ical name: <i>FR3002</i> , CAS #: <i>108-95-2</i> , Supplier: <i>BAYBLEND</i> ical name: <i>FR3002</i> , CAS #: <i>08-90-7</i> , Supplier: <i>BAYBLEND</i> ical name: <i>FR3002</i> , CAS #: <i>08-90-7</i> , Supplier: <i>BAYBLEND</i> ical name: <i>FR3002</i> , CAS #: <i>09-07</i> , Supplier: <i>BAYBLEND</i> ical name: <i>FR3002</i> , CAS #: <i>25971-63-5</i> , Supplier: <i>Mitsubishi</i> nical name: <i>TMB1615</i> , CAS #: <i>2903-56-9</i> , Supplier: <i>Mitsubishi</i> nical name: <i>BM5225X</i> , CAS #: <i>13983-17-0</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>14807-96-6</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>14803-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sabic</i> nical name: <i>BM5225X</i> , CAS #: <i>13463-67-7</i> , Supplier: <i>Sab</i>	n 🖂		
P7.19		arts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45,			

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

P7.20	Of total plastic parts' weight >25g, recycled material content is 2%.			
P7.21	Of total plastic parts' weight >25g, biobased material content is 0%.			
P7.22	Light sources are free from mercury		\boxtimes	
	If mercury is used specify: Number of lamps: and max. mercury content per lamp:	mg		
P8	Batteries			
P8.1*	Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide			
P8.2	Batteries meet the requirements of the following voluntary program/s: US RBRC			

Model number *	BOJV	N,80JR						
	2015-0					Logo	lenovo	
Product environme Item	ntal attri	<mark>butes - Market ı</mark>	<mark>requirements (</mark>	continued)			Requirement Yes No	t me n.a
P9 Energy cor								
		blowing power leve						
Energy mode *	F	100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Sta method *	ndard for e	nergy modes and test	
Peak (On-max)		W	W	W	Full load			\square
Category I1								
Short Idle State - WOL	L Enabled	5.436 W	5.628 W	5.532 W	Use for ENERG	GY STAR V	/6 registration(P _{idle})	
Long Idle State - WOL	. Enabled	3.168 W	3.204 W	3.552 W	Use for ENERG	SY STAR V	6 registration(P _{idle})	
Sleep (S3) - WOL Ena	bled	NA W	NA W	NA W	Use for ENERG	SY STAR V	6 registration (P _{sleep})	
Sleep (S3) - WOL Disa	abled	0.48 W	0.48 W	0.552 W	Reference			
Off (S5) - WOL Enable	ed	NAW	NA W	NA W	Use for ENER	SY STAR V	6 registration(Poff)	
Off (S5) - WOL Disable		0.144 W	0.156 W	0.216 W	Use for EuP		• • • • • •	H
EPS No-load (External power supply plugged in the wall outle disconnected from the	/ charger et but	0.143 W	0.147 W	0.208 W				
PTEC * Typical Energy Consum	nption	W	W	W				
TEC * Typical Energy Consum	nption	0.363 kWh/week	0.373 kWh/week	0.381 kWh/week	=E _{TEC} /12			
ETEC * Annual Energy Consum	nption	18.85 kWh/year	19.41 kWh/year	19.82 kWh/year	E _{TEC} = (8760/10 + P _{long_Idle} x 0.1		x 0.25 + P _{sleep} x 0.35 _{lle} x 0.30)	
		Poff: Off Mode(S5	5) - WOL Enabled; I	P _{sleep} : Sleep Mode(S3) - WOL Enabled	; P _{idle} : Idle	State - WOL Enabled	
Display resolution* : 1.	. <mark>049</mark> Mega	pixels						
Print Speed * :	Imag	jes per minute						
Default time to enter en	nergy save	mode: 30 minutes	3					
		energy save funct		th the product.				Ϋ́Ξ
	STAR® vei	e energy requirem rsion: Version 6.1			gram/s: oduct category: /	1		
P10 Emissions								
		eclared according t	o ISO 9296	Dealarad		Doclared A	woighted	T
P10.1 Mode		de description		Declared A-weighted		Declared A	evel $L_{p{\sf Am}}$ (dB)	
				sound power level L_{WAd} (B) Operator po	sition 🔀	Bystander positions	
Idle	*	HDD:Idle		* 2.9		20	operator attended)	
Operation Other mode	*	HDD: Operating		* 4.0		32		
				l				-
		to: 🛛 ISO7779 🗌 Other			with L _{pAm} measu	urement dis	tance m)	
P10.2 The produc	t meets th	e acoustic noise re	equirements of the	e following volunt	ary program/s:			\square

Model nu	ımber *	80JW,80JR				
Issue dat	te *	2015-05-13	Logo	leno	10.	
Product	environr	nental attributes - Market requirements (continued)		Require	ment	met
Item				Yes	No	n.a.
	Chemic	al emissions from printing products				
P10.3*	Test per	formed according to ECMA-328 (ISO/IEC 28360) standard, other specify:				\square
P10.4	Typical e	emission rate (print phase) is (mg/h):				\boxtimes
		Dust Ozone Styrene Benzene TVOC				
P10.5	Chemica	al emission requirements of the following voluntary program/s are met for :	_			\boxtimes
			TVOC			
		nagnetic emissions				
P10.6	Compute program	er display meets the requirement for low frequency electromagnetic fields of the foll /s: MPR-II (3 pin AC adapter only)	owing voluntary	\square		
P11	Consum	nable materials for printing products				
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	ired (see P4.3).			\boxtimes
P11.2*	Paper c EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets th 1.	e requirements o	f		\square
P11.3*	2-sided	(duplex) printing/copying is an integrated product function.				\square
P12	Ergono	nics for computing products				
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technolo	gies.			\square
P12.2*	The phy	sical input device meets the requirements of ISO 9995 and ISO 9241-410.				
P13	Packagi	ng and documentation				
P13.1*	Product Product	packaging material type(s): weight (kg): packaging material type(s): weight (kg):				
P13.2*		packaging material type(s): weight (kg): plastic packaging is free from PVC.				
P13.2 P13.3*		media for user and product documentation (tick box):		\boxtimes		<u> </u>
P13.3"	Electron	ic 🔀, Paper 🔀, Other 🗌				
P13.4*	For pape	er user and product documentation, please specify contained percentage of post-co	nsumer recycled			
	fiber:	%				
P14		nal information (See Note B4)				
	informat knowled provided informat		nt is provided base te such information	ed on sup on. The in	plier's format	
P9		ergy Star Qualified Notebooks & Tablet Computers for the latest information:				
	http://w	ww.energystar.gov/index.cfm?fuseaction=find_a_product.showProductGroup	%pgw_code=CC)		

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo S41-35, Lenovo S41-75	Logo
Model Number	80JW,80JR	
Issue Date	2015-05-13	lenovo
Additional information		

Product environmental attributes	
year of manufacture: 2015	
disabled and if the system is tested with switchable graphics mode with UMA driving the display:	rds (dGfx) are
E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics car enabled:	ds (dGfx) are
Category (according to ErP Lot 3): <i>B</i> Etec: 10.54	
idle state power demand (Watts);	3.37
sleep mode power demand (Watts);	0.57
sleep mode with WOL enabled power demand (Watts) (where enabled);	0.61
off mode power demand (Watts);	0.23
off mode with WOL enabled power demand (Watts) (where enabled);	0.23
internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): 10% 20% 50% 100% Average	
external power supply efficiency (if applicable):	
Average*: 45W:87.58%,87.60%,88.32% 65W:89.18%,89.04%,89.92% *internal note: show values for all available external power supplies	
the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):	300 cycles
the measurement methodology used to determine information mentioned in points (I) – internal PSU efficiency:	
the measurement methodology used to determine information mentioned in points (m) – external PSU efficiency:	
	2015 E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cat disabled and if the system is tested with switchable graphics mode with UMA driving the display: Category (according to ErP Lot 3): A Etec: 13.05 E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics car enabled: Category (according to ErP Lot 3): B Etec: 10.54 idle state power demand (Watts); sleep mode power demand (Watts); sleep mode power demand (Watts); off mode power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): 10% 20% 50% 10% 20% 50%, 100% Average*: 45W:87.58%, 87.60%, 88.32% "internal note: show values for all available external power supplies the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): <i>NA</i>

(p-3) the measurement methodology used to determine information mentioned in points (o) – loadingcycles batteries:
IEC 61960 measurement methodology
(p-4) the measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:
IEC 62623 / IEC EN50564:2011 measurement methodology
(q) sequence of steps for achieving a stable condition with respect to power demand::
IEC 62623 / IEC EN50564:2011 measurement methodology
(r) description of how sleep and/or off mode was selected or programmed:
Based on user manual
(s) sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:
Based on user manual
(t) the duration of idle state condition before the computer automatically reaches sleep mode , or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 25
(u) the length of time after a period of user inactivity in which the computer automatically reaches a
power mode that has a lower power demand requirement than sleep mode (in minutes): NA
(v) the length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10
(w) information on the energy-saving potential of power management functionality:
Based on user manual
(x) user information on how to enable the power management functionality:
Based on user manual
(z) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:
230V/50Hz, Total Harmonic Distortion <2 %
Addition Notebook Battery Information:
Yes No n/a This notebook computer is operated by battery/ies that cannot be accessed and replace by a non-professional user.
(Battery not user (Battery user
replaceable) replaceable) The battery[ies] in this product cannot be easily replaced by use themselves
Additional information