## 1 ) Right-angle Wall-mount Type

Model :	A22S3WN	A22N3WN
Item :	LCD Digital Signage-Standalone (single)type	LCD Digital Signage-Network type
Product Pictures :		
Display Para	ameter:	
LCD	AUO/	LG/CMO/BOE/SEC

Brand :							
Display	TFT-LED Backlight						
Method :			IF	I-LED BACKII	giit		
Size :	18.5 "	21.5 "	23.6 "	32 "	42 "	47 "	55 "
Display	409*230	476*267m	521*293m	735*433	930*523	1070*622	1210*680
Area :	mm	m	m	733 433	930 323	mm	mm
Brightness :	250cd/m 2	250cd/m2	250cd/m2	360cd/m 2	400cd/m2	400cd/m 2	500cd/m2
Resolution :	1366*768	1920*108 0	1920*1080	1366*768	1920*1080	1920*108 0	1920*1080
Aspect Ratio :				16:9			
View Angle :	178°	178°	178°	178°	178°	178°	178°
Power  Consumpti  on:	23W	25W	30W	50W	65W	80W	110W
Housing :							
Product Size :	*	53*35.5*4. 5CM	*	79*48.5* 7CM	103*62.5*7 CM	*	*

Material :	Aluminum frame+cold rolled steel+ tempered glass			
Color :	Black standard , color can custom			
Installation :	Horizontal/vertical Wall mount type			
Hardware:				
System Structure:	Embedded System	Embedded Linux system、Android system		
Hardware Configurati on :	STKM6M48AAD/V59 main board、4G SD card、Stereo speaker(2×5W)	1.CPU A20 , dual-core 1.2GHz,DDR 1G DDR3 ;  Built-in NAND FLASH 4G(Extensible) ; Stereo  speaker ( 2×5W ) 2.Sigma8653 ; onboard 256MB  DDR2 ; compatible SATA DOM and SATA HDD ;  Stereo speaker ( 2×5W )		
Function :	<ul> <li>Support multiple OSD language,         Chinese, English, French, Spanish         etc. OSD</li> <li>Support to rotate video         program : single loop/all         program loop playback</li> <li>Support play record : automatic         record file name, generate         working records.</li> <li>Support to continue displaying</li> </ul>	> Integrated network advertising system, embedded with Linux system, the background operation system support windows XP/windows 2003/windows 7 and etc.		

- when suffered from power failure
- Support picture move-transition,scaling-transition,slide-translation
- Support picture/video playing time: 5S 10S...60S
- Support scrolling marquee displaying
- Support to set different sound volume during different time period
- Support playing play list: playing the play list program,you can make the play list at first
- Support classify playback: just play video,picture,audio or play video/picture/audio at the same time
- Support to split screen into several smaller window,playing different content

- Support to split screen, user can setting display area or the number of display area.
- Support inter-cut playing, timed playing, cycle playing, playing time can be regulated to any second through remote control.
- Support WIFI,3G,LAN
- Support classified user management, support film source approval function.
- Support wireless remote control, wired control, local control.
- Support real time marquee, different marquee playing.
- Support remote control display and rotate playback.
- Support remote control power on/off and timed power on/off.
- Support display failure detecting, when terminal appear failure, control centers will display failure details, failure position, failure cause and etc.
- Support watchdog function, can monitoring and rectify in time.

- Support set on/off automatically:
   when unplug USB after 30s
   automatically power off. During
   20s countdown period time,once
   you plug USB or enter menu, the
   countdown will stop.
- Protect function:with
   lock,support set password
   when enter menu
- Support set time and date
- Support set the on/off automatically(up to 5 time intervals)
- Support timing method:everyday, from Monday toFriday, Saturday, Sunday
- Support inter cut playing program: inter cut the number from 1 to 9 program
- Support to display stationcaption on the corner of screen
- Display setting: setting

- Support update program synchronize through network signal, support SD card or USB update program.
- > Support media file preview.
- Support mix playing with split screen , support manual setting split screen display video, picture, LOGO, time and etc.
- Support cycle playing program, you can setting playing time.
- Support real time inter-cut playing, display video, marquee.
- Reduce management cost, support remote control system update.
- Support live broadcasting, obtaining information from internet.
- Support to manage playing reports and daily records, serving user to get efficient data.
- Supported to build up secondary server to reduce network delaying, thus enhance the stability of the whole system.
- Support to resume updating programs from breaking point, and can start downloading

	brightness, contrast,	programs according schedule		
	sharpness,backlight, color and	> Support auto power off mode and standby		
	etc.	mode, extend product device lifespan		
	> Support automatically copy:from	> Support plug-and-play, avoid virus, power on		
	one USB to another USB	stability and fast		
	> Display MP3 lyrics : copy the	> Support timer function		
	MP3 lyrics to USB and named the	<ul> <li>Support OSD language: Chinese, English</li> </ul>		
	MP3 files			
	> Support different volume at			
	different time			
	> Power on logo can custom			
Interface :	CF ×1、SD ×1、USB ×1 input	USB ×2、LAN×1 、support WiFi		
Optional :	LOGO print optional LOGO print optional			
Playing deta	ails:			
Picture	IDEC DIAD CIE DIAC			
Format :	JPEG , BMP , GIF , PNG			
Video	MDECT (MCD.) MDECC (DMC)			
Format :	MPEG1 ( VCD ), MPEG2 ( DVD ), MPEG4 , AVI , VOB , RMVB , DAT , XVID , MOV			
Audio	14D2 14/14			
Format :	MP3 , WMA			
Other detail	s:			

Packing	Product ×1, Power cable ×1, Key ×2, Remote control ×1, User manual ×1, Warranty
List :	card ×1、Wall mount ×1
Operating	
Temperatu	Indoor working temperature : 0°C~40°C storage temperature : -20°C~60°C
re :	
	All the information are our product standard, exact dimension or parameter depend on
Nata	the actual product.SHENZHEN CMAC SCIEN AND TECHNOLOGY LTD Reserves the right to
Note :	the interpretation of the product as well as to the timing changes of the contents of the
	above right.

## 2 ) Round-angle Wall-mount Type

Model :	A22S3AN	A22N3AN
Item :	LCD Digital Signage-Standalone	LCD Digital Signage-Network type
item .	(single) type	ECD Digital Signage-Network type



Product

Pictures :



**Display Parameter:** 

Brand :	AUO/LG/CMO/BOE/SEC						
Display  Method:	TFT-LED Backlight						
Size :	18.5 "	21.5 "	23.6 "	32 "	42 "	47 "	55 "
Display	409*230m	476*267m	521*293m	725*422	020*522	1070*622	1210*68
Area :	m	m	m	735*433	930*523	mm	0mm
Brightness :	250cd/m2	250cd/m2	250cd/m2	360cd/m2	400cd/m2	400cd/m2	500cd/m 2
Resolution	1366*768	1920*108	1920*108	1366*768	1920*108	1920*108	1920*10
:	1300 708	0	0	1300 708	0	0	80
Aspect Ratio :				16:9			
View Angle :	178°	178°	178°	178°	178°	178°	178°
Power  Consumpti  on:	23W	25W	30W	50W	65W	80W	110W
Housing :							
Product Size :	*	53*35.5*4. 5CM	*	79*48.5*7C M	103*62.5* 7CM	*	*
Material :	Aluminum frame+cold rolled steel+tempered glass						

Color :	Black standard, color can custom				
Installation :	Horizontal/vertical wall mount type				
Hardware					
System Structure:	Embedded system	Embedded Linux system、Android			
Hardware Configurati on :	STKM6M48AAD/V59 main board、SD card 4G、Stereo speaker (2×5W)  DDR2; compatible SATA DOM and SATA HI  Stereo speaker (2×5W)				
Function :	<ul> <li>Support multiple OSD language,         Chinese, English, French, Spanish         etc. OSD</li> <li>Support to rotate video         program : single loop/all         program loop playback</li> <li>Support play record : automatic         record file name, generate         working records.</li> <li>Support to continue displaying         when suffered from power</li> </ul>	embedded with Linux system, the background operation system support windows XP/windows 2003/windows 7 and etc.  > Support to update program from distance, and manage terminal setting, program editing, release management ,user management,system management.			

- failure
- Support picture move-transition,scaling-transition,slide-translation
- Support picture/video playing time: 5S 10S...60S
- Support scrolling marquee displaying
- Support to set different sound volume during different time period
- Support playing play list: playing the play list program,you can make the play list at first
- Support classify playback: just play video,picture,audio or play video/picture/audio at the same time
- Support to split screen into several smaller window,playing different content
- Support set on/off automatically:

- display area or the number of display area.
- Support inter-cut playing, timed playing, cycle playing, playing time can be regulated to any second through remote control.
- Support WIFI,3G,LAN
- Support classified user management, support film source approval function.
- Support wireless remote control, wired control, local control.
- Support real time marquee, different marquee playing.
- Support remote control display and rotate playback.
- Support remote control power on/off and timed power on/off.
- Support display failure detecting, when terminal appear failure, control centers will display failure details, failure position, failure cause and etc.
- Support watchdog function, can monitoring and rectify in time.
- Support update program synchronize

when unplug USB after 30s automatically power off. During 20s countdown period time,once you plug USB or enter menu, the countdown will stop.

- Protect function:with
   lock,support set password
   when enter menu
- Support set time and date
- Support set the on/off automatically(up to 5 time intervals)
- Support timing method:everyday, from Monday toFriday, Saturday, Sunday
- Support inter cut playing program: inter cut the number from 1 to 9 program
- Support to display station caption on the corner of screen
- Display setting: setting brightness,contrast,

- through network signal, support SD card or USB update program.
- Support media file preview.
- Support mix playing with split screen , support manual setting split screen display video, picture, LOGO, time and etc.
- Support cycle playing program, you can setting playing time.
- Support real time inter-cut playing, display video, marquee.
- Reduce management cost, support remote control system update.
- Support live broadcasting, obtaining information from internet.
- Support to manage playing reports and daily records, serving user to get efficient data.
- Supported to build up secondary server to reduce network delaying, thus enhance the stability of the whole system.
- Support to resume updating programs from breaking point, and can start downloading programs according schedule

	sharpness, backlight, color and	> Support auto power off mode and standby	
	etc.	mode, extend product device lifespan	
	> Support automatically copy:from	<ul><li>Support plug-and-play, avoid virus, power on</li></ul>	
	one USB to another USB	stability and fast	
	> Display MP3 lyrics : copy the	> Support timer function	
	MP3 lyrics to USB and named the	<ul><li>Support OSD language: Chinese, English</li></ul>	
	MP3 files		
	> Support different volume at		
	different time		
	> Power on logo can custom		
Interface :	CF ×1、SD ×1、USB ×1 input	USB ×2、LAN×1 、support WiFi	
Optional :	LOGOO print optional : LOGO print optional		
Playing deta	ails:		
Picture	IDEC DAD CIE DAIC		
Format :	JPEG , BMP , GIF , PNG		
Video	MDEG1 ( VCD ) MDEG2 ( DVD ) MA	DECA ANT MOR DAMME DAT WITH MON	
Format :	WIFEGT ( VCD ), WIFEGZ ( DVD ), MI	PEG4 , AVI , VOB , RMVB , DAT , XVID , MOV	
Audio	NADO NANAA		
Format :	MP3 , WMA		
Other detail	ls:		
Packing	Product ×1、Power cable ×1、 Key ×	2、Remote control ×1、User manual ×1、Warranty	

List :	card ×1、Wall mount ×1
Operating	
Temperatu	Indoor working temperature : 0°C~40°C storage temperature : -20°C~60°C
re :	
	All the information are our product standard, exact dimension or parameter depend on
Nata	the actual product.SHENZHEN CMAC SCIEN AND TECHNOLOGY LTD Reserves the right to
Note :	the interpretation of the product as well as to the timing changes of the contents of the
	above right.