

speco technologies®

Indoor Color Dome Camera For Wall Or Ceiling Mounting



(Internal 3-way mount)

VL-644DC

The perfect solution for your everyday color dome requirements. The VL-644DC provides a crisp picture under normal lighting conditions. When ceiling mounted, the VL-644DC is fully adjustable both horizontally and vertically. It features a 1/4" format CCD sensor with a 2.9mm lens which is suitable for most applications. The video output features a BNC fitting for secure connections. Please provide your own regulated 12-volt DC power supply or use our PSW-5. Includes unique internal 3-way gimble, making the unit perfect for both wall and ceiling mounting. Also available in white: VL-644DC/W.

Specifications

Resolution	420 lines
Min. Illumination	1 lux
Pick Up Device	1/4" image sensor interline transfer 542 (H) x 492 (V)
Lens	2.9mm
S/N Ration	Better than 48dB
Shutter Control	1/60 to 1/100,000 Sec
Shutter Steps	256 Step
Sync System	Internal Sync.
Power Source	12V DC regulated supply recommended
Consumption Current	80mA
Gamma Correction	0.45
Operating Temperature	4°F-131°F / 30 to 90% RH
Video Out	Composite 1.0 V.P.P / 75OHM
Weight	10.5 oz.
Dimensions	4" L x 4" W x 3" H

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880