

The Epson EB-G6550WU Full HD projector for the office is ideal for medium to large meeting rooms. Business presentations are delivered with rich, vivid colours - even in daylight. This is thanks to Epson's 3LCD technology enabling an equally high White and Colour Light Output of 5,200 lumens, and a WUXGA resolution.

The Epson EB-G6550WU boasts superior picture quality, ensuring the best possible projection for important presentations. The Colour Uniformity function compensates for unequal colour distribution by adjusting the intensity of RGB on individual areas of the screen.

New and innovative features are designed to offer the best possible presenting tools. The projector can be rotated vertically by 360 degrees so the projection image can be easily moved around the room.

In addition, Frame Interpolation makes sure video footage is sharper and images are clearer with smoother, more fluid screen movement.

The Epson EB-G6550WU is easy to set up and use, thanks to a variety of userfriendly installation features. Pixel alignment, for example, enables the user to align pictures easily and effectively during set up for clear, correct images. With edge blending, a large, widescreen image can be projected from a number of projectors working together seamlessly. Its powerful zoom lens, as well as manual vertical keystone correction and centred lens, make it quick and easy to set up in a variety of positions without picture blurring or distortion.

With the HDMI input, you can connect a variety of high definition devices to deliver Full HD content effortlessly.

For simpler integration, this model is also compatible with the Epson EB-G5 series lenses¹.

KEY FEATURES

- 5,200lm White and Colour Light Output
- WUXGA screen resolution
- Full HD 3LCD technology
- 360° vertical rotation of projection
- Easy installation features





PRODUCT SPECIFICATIONS

| TECHNOLOGY | |
|---------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Projection System | 3LCD Technology, RGB liquid crystal shutter |
| LCD Panel | 0,76 inch with C2 Fine |
| IMAGE | |
| Color Light Output | 5.200 lumen - 3.952 lumen (economy) |
| /hite Light Output 5.200 lumen - 3.952 lumen (economy) | |
| lesolution WUXGA, 1920 x 1200, 16:10 | |
| Contrast Ratio | 5.000 : 1 |
| Lamp | 380 W, 2.500 h durability, 4.000 h durability (economy mode) |
| Keystone Correction | Manual vertical: ± 30 °, Manual horizontal ± 30 ° |
| OPTICAL | |
| Projection Ratio | 1,26 - 2,30:1 |
| Zoom | Manual, Factor: 1 - 1,8 |
| Projection Size | 50 inches - 300 inches |
| Projection Distance Wide | 1,4 m - 8,4 m (300 inch screen) |
| Projection Distance Tele | 2,5 m - 15 m (300 inch screen) |
| Projection Lens F Number | 1,65 - 2,55 |
| Focal Distance | 21,28 mm - 37,94 mm |
| Focus | Manual |
| CONNECTIVITY | |
| Interfaces | RS-232C, Ethernet interface (100 Base-TX / 10 Base-T), Wireless LAN IEEE 802.11b/g/n |
| | (optional), VGA in, VGA out, HDMI in, Display Port, Composite in, BNC in, S-Video in, Stere |
| | mini jack audio out, Stereo mini jack audio in (4x), Cinch audio out |
| ADVANCED FEATURES | |
| Security | Kensington lock, Security bar |
| Features | Frame interpolation, Freeze image, Instant on/off, Network administration, Network image |
| | |
| | transmission, Split-Screen-Function |
| Video Color Modes | transmission, Split-Screen-Function Dynamic, Photo, Presentation, sRGB, DICOM SIM |
| Video Color Modes | |
| | |
| GENERAL | Dynamic, Photo, Presentation, sRGB, DICOM SIM |
| GENERAL Energy Use | Dynamic, Photo, Presentation, sRGB, DICOM SIM 504 W, 405 W (economy), 0,41 W (standby) |
| GENERAL Energy Use Product dimensions | Dynamic, Photo, Presentation, sRGB, DICOM SIM 504 W, 405 W (economy), 0,41 W (standby) 505 x 144 x 382 (Width x Depth x Height) |
| GENERAL Energy Use Product dimensions Product weight | Dynamic, Photo, Presentation, sRGB, DICOM SIM 504 W, 405 W (economy), 0,41 W (standby) 505 x 144 x 382 (Width x Depth x Height) 9,7 kg |
| GENERAL Energy Use Product dimensions Product weight Noise Level | Dynamic, Photo, Presentation, sRGB, DICOM SIM 504 W, 405 W (economy), 0,41 W (standby) 505 x 144 x 382 (Width x Depth x Height) 9,7 kg Normal: 39 dB (A) - Economy: 31 dB (A) |
| GENERAL Energy Use Product dimensions Product weight Noise Level Included Software | Dynamic, Photo, Presentation, sRGB, DICOM SIM 504 W, 405 W (economy), 0,41 W (standby) 505 x 144 x 382 (Width x Depth x Height) 9,7 kg Normal: 39 dB (A) - Economy: 31 dB (A) EasyMP Multi PC Projection, EasyMP Network Projection |

LOGISTICS INFORMATION

| ѕки | V11H513040 |
|---------|---------------|
| Barcode | 8715946513843 |

Epson EB-G6550WU

WHAT'S IN THE BOX

- Cable cover
- Computer cable
- HDMI Cable Clamp
- Lens cap
- Power cable
- User manual (CD)
- Remote control incl. batteries

OPTIONAL ACCESSORIES

- Lamp ELPLP76 EB-G6xxx Series V13H010L76
- Ceiling Mount ELPMB22 White V12H003B22
- Quick Wireless Connect USB key ELPAP09 V12H005M09
- Adapter ELPAP07 Wireless LAN b/g/n V12H418P13ZA

1. Except ELPLS05 lens

