

CyberPower®

Model #: 6050

UPC: 649532760503

MSRP: \$14.99



The CyberPower 6050 surge suppressor is an all-purpose electronic surge strip with one built-in RJ-11 port and 1500 joule MOV technology. RJ-11 ports allow for protection of telecommunication devices such as phones, faxes, modems, and DSL lines, while MOV technology safely guards the surge suppressor and connected electronics against line abnormalities and lightning surges. This surge protector is ideal for personal computers, stereo electronics, phones/answering machines, and all other consumer electronics. The 6050 is also equipped with EMI/RFI filters that block unwanted line noise from all connected electronics. CyberPower fully stands behind its products with a lifetime product warranty and Connected Equipment Guarantee of \$45,000.

- MOV (Metal Oxide Varistor) - MOV technology allows normal current to pass through the device, while diverting any surge/spikes through the ground circuit. This safely protects all connected electronics along with the surge suppressor itself.
- Transformer-spaced Outlets - Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- EMI/RFI Shielding - Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or “humming” that occurs over telephone lines or stereo electronics.
- ISO & Safety Certifications - All CyberPower’s manufacturing facilities are ISO-9001 Quality Tested. Our products are also UL Listed and CSA Certified.
- Keyhole Mounting Slots – Convenient mounting slots are located on the back on the surge suppressor.
- Sturdy ABS Case – Constructed of impact-resistant composite material for maximum durability.

Technical Specifications

General	
Model #	6050
Input	
Voltage	110/120V Nominal
Plug Type	NEMA 5-15P
Plug Style	Right-angle
Cord Length	4 ft
Output	
Outlets - Total	6
Outlets - Widely Spaced	1 x NEMA 5-15R
Outlets - Normal Spaced	5 x NEMA 5-15R
Surge Protection and Filtering	
Surge Suppression	1500 Joules
Phone Protection (RJ11)	One-in/One-out
Ethernet Protection (RJ45)	None
Coax Protection (RG6)	None
Maximum Surge Current	60,000 Amps
Maximum Surge Current H-N	30,000 Amps
Maximum Surge Current H-G	15,000 Amps
Maximum Surge Current N-G	15,000 Amps
Maximum Surge Voltage	6,000V
Clamping Voltage	330 V
Response Time	<1 ns
EMI/RFI Filtration	EMI/RFI 150KHz to 100MHz
Attenuation	Up to 40dB
Indicators	
Indicator Lights	Power (Red); Surge (Red)
Physical	
Dimensions (WxHxD)	11.5" x 2" x 1.5"
Weight	0.9375 lbs.
Color	Black
Warranty	
Product Warranty	Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$45,000