



DVB MONITOR V2 KVARTA USER'S MANUAL



Contents

1. INTRODUCTION	4
1.1. About KVARTA	4
1.2. About DVB	4
2. DVB MONITOR Kvarta	4
2.1. INCLUDED ACCESSORIES	4
2.2. GENERAL SPECIFICATIONS OF THE DVB MONITOR	5
3. Getting connected.....	6
3.1. Connecting to the embedded web site	6
3.2. LED Indication.....	6
3.3. Back panel	6
4. CONFIGURATION AND OPERATION.....	7
4.1. STREAMING mode (SCAN OFF) - single carrier measurements and streaming	7
4.1.1. RF Configuration.....	7
4.1.2. Streaming configuration.....	8
4.1.3. RF Measurements.....	9
4.1.4. Constellation diagram	10
4.2. MONITORING mode (SCAN ON) – multiple carrier monitoring and alarms	11
4.2.1. RF Configuration.....	11
4.2.2. Monitoring status	12
4.2.3. RF alarms	13
4.2.4. MPEG alarms	14
4.2.5. Active Alarms.....	14
4.3. Log	15
4.3.1. Alarms log.....	15
4.3.2. Stream log	15
4.4. Advanced Configuration	16
4.4.1. E-mail client configuration	16
4.4.2. SNMP configuration	16
4.4.3. Programs configuration.....	17
4.4.4. RTSP configuration	17
4.4.5. Remuxer Configuration	18
4.4.6. VLAN	18
4.5. Charts	19
5. GLOSSARY	20

APPENDIX A - DVB MONITOR ASCII COMMAND SET	21
A.1. DEFAULT VALUES.....	21
A.2. Configuration and special files on the device	21
a. config.ini – Keeps all configuration information (windows configuration file).....	21
b. freq.txt – Keeps monitoring frequencies (comma separated file)	21
c. programs.txt – Keeps programs on the device (comma separated file)	21
d. help.txt – ASCII commands description file.....	21
e. ***.mib – SNMP MIB file.....	21
A.3. ASCII COMMANDS	21

** Depends on the model*

1. INTRODUCTION

1.1. About KVARTA

For more than 10 years, Kvarita has been developing products for Broadcasters and CATV providers. Our devices are used by major radio and television broadcasters and regulatory agencies.

Broadcasting is our passion. We know what you want and we have designed many devices, which are perfectly adapted to your needs. These include RDS encoders, FM Radio monitors and CATV systems. KVARTA has a reputation for excellence and innovation among its clients and partners.

Our CATV, DVB Monitoring devices and RDS/RBDS encoders are growing in popularity due to their reliability, quality and functionality at exceptional prices. All of our products have been designed for professional broadcast use and are fully meet the standards. Our devices incorporate embedded web site and SNMP communication.

1.2. About DVB

Digital Video Broadcasting (DVB) is a suite of internationally accepted open standards for digital television. DVB standards are maintained by the DVB Project, an international industry consortium with more than 270 members, and they are published by a Joint Technical Committee (JTC) of European Telecommunications Standards Institute (ETSI), European Committee for Electrotechnical Standardization (CENELEC) and European Broadcasting Union (EBU).

2. DVB MONITOR Kvarita

2.1.INCLUDED ACCESSORIES

In your package, you should receive:

- Your DVB MONITOR
- Quick start notice
- AC main power cord
- Straight ethernet cable

2.2.GENERAL SPECIFICATIONS OF THE DVB MONITOR

<u>Communication ports</u>	
Ethernet	100baseT – Web Server and UDP/TCP (SNMP/ASCII)
<u>Frequency range and Modulation</u>	
Frequency Range	46 MHz - 1004 MHz
Analog TV	NTSC , PAL/SECAM
Digital TV	DVB-T, DVB-H, DVB-C
<u>Demodulator</u>	
DVB-T	ETSI EN 300 744
DVB-H	ETSI EN 300 744 Annex F
DVB-C	ETSI EN 300 429 and ITU J.83 Annex A/C
Supports	QPSK/16/32/64/128/256QAM
Bandwidth	6MHz/7MHz/8MHz
Symbols rate	1MS/S-7MS/S
COFDM	2k,4k,8k
<u>Measurements</u>	
Standard	ETSI TR 101 290 V1.2.1
Level	30dBuV - 100dBuV (± 2 dBuV)
MER	19dB - 45dB (± 2 dB)
C/N	19dB - 40dB (± 2 dB)
SNR	19dB - 55dB (± 2 dB)
BER (DVB-C)	1E-1~ 1E-7
CBER,VBER (DVB-T)	1E-1~ 1E-7
<u>MPEG Decoding</u>	
Tables	PAT,PMT,SDT,TDT,TOT
Alarms	Service Audio/Video alarms with e-mail notifications and SNMP traps
<u>Monitoring</u>	
Alarms	Carrier count, Level(low, high), SNR(low), C/N(low), MER(low), BER(high), CBER(high), VBER(high), PAT/PMT/Audio/Video missing alarm
Log, E-mail, SNMP traps	Available
<u>Power Supply</u>	
Supply voltage	230V (115V optional)
Voltage tolerance	+/- 10%
Main AC frequency	45-65 Hz
Fuse	0.8A
Consumption	10 VA
<u>Mechanical aspects</u>	
Height	1U (44,5 mm)
Width	483 mm
Depth	220 mm
Net weight	2,5 kg
<u>Info</u>	
Updates	Available
Front panel LEDs	Power supply, LAN, Analog, DVB-C, DVB-T

3. Getting connected

3.1. Connecting to the embedded web site

1. Connect the Ethernet cable between the RJ45 and the network..
2. Open a Web browser (Mozilla ,Internet Explorer, ...) and enter the encoder's IP address (Default: **192.168.2.3**) you just set in the previous step. Log in with the default username and password (admin/admin). The home page of the embedded web site is displayed:

KVARTA

* DVB STREAMER * 192.168.2.3 * STREAMING *

IP Config	General	Remote Ports	Status	Restart	Update
DVB	IP Configuration				
Advanced	General IP Configuration				
Charts	IP:	<input type="text" value="192.168.2.3"/>	Time sync:	<input type="text" value="Enabled"/>	
VIDEO	Subnet mask:	<input type="text" value="255.255.255.0"/>	Time server IP:	<input type="text" value="212.70.148.11"/>	
	Default gateway:	<input type="text" value="192.168.2.1"/>	Username:	<input type="text" value="admin"/>	
	DHCP:	<input type="text" value="Disabled"/>	Password:	<input type="text" value="*****"/>	
	Web server:	<input type="text" value="Enabled"/>	Web server filter:	<input type="text" value="0.0.0.0"/>	
	Web server port:	<input type="text" value="80"/>	Local time:	<input type="text" value="+03:00"/>	
	<input type="button" value="Save"/>				

Copyright © Kvarita Soft Ltd. 2013**

NOTE: Your computer should have IP address which is in the same network.

3.2.LED Indication

POWER – Indicates that power supply is available.

LAN – Indicates LAN connection ON/OFF.

ANALOG - Indicates analog reception (blinking indicates parameter out of range or bad reception)

DVB-C - Indicates DVB-C reception (blinking indicates parameter out of range or bad reception)

DVB-T - Indicates DVB-T reception (blinking indicates parameter out of range or bad reception)

3.3.Back panel

Micro SD – 2GB containing configuration and web site files

LAN – Ethernet connection

IN A – RF input A

IN B – RF input B

IEC Connector – AC Power Supply connection 230V (115V optional)



NOTE: COM Port not available in DVB Monitor v2

4. CONFIGURATION AND OPERATION

4.1. STREAMING mode (SCAN OFF) - single carrier measurements and streaming

4.1.1. RF Configuration

- Open the embedded web page and click **DVB -> Config**
- Scan mode should be off as it is in the picture below
- Select the modulation type Analog/DVB-C/DVB-T ¹
- Type the center frequency of the monitored carrier
- Click Save & Tune
- Connect the RF Antenna or CATV source to IN A or IN B
- Select the appropriate Input (A or B) used for the type of modulation Analog/DVB-C/DVB-T
- Configure other relative settings like Bandwidth, Symbol Rate, Constellation and Spectrum.
- Click the Save button below the settings to store the configuration



* DVB STREAMER * 192.168.2.3 * STREAMING *

IP Config	Config	Stream	Status	Alarms	Log	
DVB	<h3>RF Configuration</h3>					
Advanced	NOTE: Streaming mode. Select "Scanning ON" to enter monitoring mode.					
Charts	Tuner mode					
VIDEO	Scanning: <input type="text" value="OFF"/>					
	RF Configuration					
	Mode	Frequency				
	DVB-C	154.000 xxx.xxx MHz			<input type="button" value="Save & Tune"/> <input type="button" value="Prev"/> <input type="button" value="Next"/>	
	Analog TV Settings		DVB-C Settings		DVB-T Settings	
	Input:	A	Input:	A	Input:	B
	Color:	PAL/NTSC	Bandwidth:	8 MHz	Bandwidth:	8 MHz
	Transmission:	AIR	Symbol rate:	6900	Spectrum:	NORMAL
	System:	I	Constellation:	128 QAM		
	Spectrum:	NORMAL	Spectrum:	NORMAL		
	<input type="button" value="Save"/>		<input type="button" value="Save"/>		<input type="button" value="Save"/>	

Copyright © Kvarita Soft Ltd. 2013**

¹ Depends on the DVB Monitor model

4.1.2. Streaming configuration

- Open the embedded web page and click **DVB -> Stream**
- Select the protocol **UDP/RTP/RTSP/OFF**
- Select the type of MPEG TS : **MPTS** - Multi Program Transport Stream, **SPTS** – Single Program Transport Stream
- For SPTS select up to 5 services on the same frequency to be streamed



* DVB STREAMER * 192.168.2.3 * STREAMING *

IP Config

DVB

Advanced

Charts

VIDEO

Config
Stream
Status
Alarms
Log

DVB Configuration

Stream Configuration

Protocol	Mode	
UDP	SPTS - Single Program Transport Stream	<input type="button" value="Save"/>

SPTS Configuration Total bitrate: 12.9 Mbps

Service	Destination	Bitrate	
Eurosport HD	233.1.2.3:5441	7688 kbps	<input type="button" value="Update"/> <input type="button" value="Del"/>
NatGeo HD	233.1.2.4:5441	5249 kbps	<input type="button" value="Update"/> <input type="button" value="Del"/> <input type="button" value="Add"/>

Program List

Name	SID	Frequency	DVB
BNT 1	4340	154.000	DVB-C
bTV	4360	154.000	DVB-C
Nova TV	4380	154.000	DVB-C
bTV Action	4400	154.000	DVB-C
EK	4420	154.000	DVB-C
EK Carevec	4440	154.000	DVB-C
TV 7	4500	154.000	DVB-C
Eurosport HD	4120	146.000	DVB-C
NatGeo HD	4140	146.000	DVB-C

- For MPTS just select the destination address for the IP stream



* DVB STREAMER * 192.168.2.3 * STREAMING *

IP Config

DVB

Advanced

Charts

VIDEO

Config
Stream
Status
Alarms
Log

DVB Configuration

Stream Configuration

Protocol	Mode	
UDP	MPTS - Multi Program Transport Stream	<input type="button" value="Save"/>

MPTS Configuration

Source	Destination	Bitrate	
DVB-C, 146.000 MHz	233.1.2.3:5441	44.5 Mbps	<input type="button" value="Save"/>

Service Description (TS ID: 4001)

Service	Name	Provider	Running Status	Free/CA
4120	Eurosport HD	CoresNet	running	free
4140	NatGeo HD	CoresNet	running	free
4160	Planeta HD	SatelliteBG	running	free
4180	BNT 1 HD	BNT	running	free

4.1.3. RF Measurements

- Checking the status and measured values
- Click **DVB -> Status -> RF Status**
- This web page constantly displays the measured RF parameters – Demodulator lock, FEC Lock, C/N, MER, BER and other measurements depending on the modulation type.

* DVB STREAMER * 192.168.2.3 * STREAMING *

IP Config | **DVB** | Advanced | Charts | VIDEO

Config | Stream | **Status** | Alarms | Log

DVB Status

RF Status | MPEG

DVB-C Status	
Frequency:	146.000 MHz (Input A)
Mode:	DVB-C (SR:6900 128QAM)
Level:	65 dBµV
Demodulator lock:	<input checked="" type="checkbox"/>
FEC lock:	<input checked="" type="checkbox"/>
C/N:	36.9 dB
MER:	42.8 dB
BER:	<1.0E-7

Copyright © Kvarta Soft Ltd. 2013**

- Click the **DVB-> Status -> MPEG**
- This page displays various MPEG tables PAT , PMT, SDT, TDT, CAT, TOT (Click F5 to reload tables)
- You can also add or remove alarms for specific PIDs in the MPEG transport stream

* DVB STREAMER * 192.168.2.3 * STREAMING *

IP Config | **DVB** | Advanced | Charts | VIDEO

Config | Stream | **Status** | Alarms | Log

DVB Status

RF Status | MPEG

PAT | PMT | SDT | (REFRESH)


PAT (TS ID: 4001)	
Service	PMT PID
0 (NIT)	16
4120 (Eurosport HD)	4120
4140 (NatGeo HD)	4140
4160 (Planeta HD)	4160
4180 (BNT 1 HD)	4180

Copyright © Kvarta Soft Ltd. 2013**

4.1.4. Constellation diagram

- Click the **Charts** button in the side menu and the constellation diagram will be displayed

Constellation Diagram



NOTE: This is available only for single frequency measurement.

4.2. MONITORING mode (SCAN ON) – multiple carrier monitoring and alarms

4.2.1. RF Configuration

- Open the embedded web page and click **DVB -> Config**
- Select Scanning ON to enable monitoring mode



* DVB STREAMER * 192.168.2.3 * MONITORING *

IP Config

DVB

Advanced

Charts

VIDEO

Config

Stream

Status

Alarms

Log

RF Configuration

NOTE: Monitoring mode. Select "Scanning OFF" to enter streaming mode.

Tuner mode

Scanning:

Auto install programs:

Scanning: [FREQ.TXT](#)

ATV		DVB-C		DVB-T	
1.	<input type="text" value="111.250"/> MHz <input type="button" value="Update"/>	1.	<input type="text" value="154.000"/> MHz <input type="button" value="Update"/>	1.	<input type="text" value="514.000"/> MHz <input type="button" value="Update"/>
2.	<input type="text" value="110-140"/> MHz <input type="button" value="Update"/>	2.	<input type="text" value="146.000"/> MHz <input type="button" value="Update"/>	2.	<input type="text" value="698.000"/> MHz <input type="button" value="Update"/>
3.	<input type="text"/> MHz <input type="button" value="Add"/>	3.	<input type="text" value="162.000"/> MHz <input type="button" value="Update"/>	3.	<input type="text" value="770.000"/> MHz <input type="button" value="Update"/>
		4.	<input type="text" value="170.000"/> MHz <input type="button" value="Update"/>	4.	<input type="text"/> MHz <input type="button" value="Add"/>
		5.	<input type="text" value="650-700"/> MHz <input type="button" value="Update"/>		
		6.	<input type="text"/> MHz <input type="button" value="Add"/>		

- Enter frequency range or exact carrier frequency for faster scanning
NOTE: You can enter both scan range and exact frequencies. For example: 150-180 this will scan from 150 MHz to 180 MHz
- Click Save & Tune
- Connect the RF Antenna or CATV source to IN A or IN B
- Select the appropriate Input (A or B) used for the type of modulation Analog/DVB-C/DVB-T
- Configure other relative settings like Bandwidth, Symbol Rate, Constellation and Spectrum.
- Click the Save button below the settings to store the configuration

4.2.2. Monitoring status

- Check the status and measured values for the configured scan ranges and frequencies
- Click **DVB -> Status** to check RF parameters and carriers found

Config	Stream	Status	Alarms	Log
--------	--------	---------------	--------	-----

DVB Status

Scan summary						
	In	Type	Time	Duration	Carriers found	
	A	Analog TV	10:55:53	5 seconds	5 carriers	
	A	DVB-C	10:55:46	33 seconds	10 carriers	
	B	DVB-T	10:55:48	2 seconds	0 carriers	
Analog TV Carriers (Input A)						
N	Frequency		Level	SNR		
1	111.250 MHz		65 dBµV	41.0 dB		
2	111.250 MHz		64 dBµV	39.5 dB		
3	119.250 MHz		67 dBµV	41.5 dB		
4	127.250 MHz		65 dBµV	41.0 dB		
5	135.250 MHz		67 dBµV	41.0 dB		
DVB-C Carriers (Input A)						
N	Frequency		Level	CNR	MER	BER
1	154.000 MHz SR:6900 128QAM		65 dBµV	36.8 dB	42.3 dB	<1.0E-7
2	146.000 MHz SR:6895 128QAM		66 dBµV	36.6 dB	42.3 dB	<1.0E-7
3	162.000 MHz SR:6905 128QAM		66 dBµV	36.6 dB	42.2 dB	<1.0E-7
4	170.000 MHz SR:6900 128QAM		66 dBµV	36.5 dB	42.0 dB	<1.0E-7
5	650.000 MHz SR:6900 128QAM		55 dBµV	31.2 dB	33.6 dB	1.3E-6
6	658.000 MHz SR:6900 128QAM		56 dBµV	36.1 dB	40.6 dB	<1.0E-7
7	666.000 MHz SR:6900 128QAM		55 dBµV	35.6 dB	40.9 dB	<1.0E-7
8	674.000 MHz SR:6900 128QAM		59 dBµV	34.6 dB	38.8 dB	<1.0E-7
9	682.000 MHz SR:6900 128QAM		57 dBµV	35.9 dB	41.3 dB	<1.0E-7
10	698.000 MHz SR:6900 128QAM		57 dBµV	31.8 dB	34.1 dB	<1.0E-7

4.2.3. RF alarms

NOTE: Alarms are only working while the device is in monitoring mode. (SCAN ON)

- Click **DVB -> Alarms -> RF Alarms**
- Click the tick next to the alarm to enable it.

Config	Stream	Status	Alarms	Log
--------	--------	--------	---------------	-----

DVB Alarms

RF Alarms		MPEG Alarms		Active Alarms			
Analog TV		DVB-C		DVB-T			
Carriers:	<input type="text" value="2"/> carriers	<input checked="" type="checkbox"/>	Carriers:	<input type="text" value="0"/> carriers	<input type="checkbox"/>		
Timeout:	<input type="text" value="600"/> sec.	<input type="checkbox"/>	Timeout:	<input type="text" value="200"/> sec.	<input checked="" type="checkbox"/>		
Level LOW:	<input type="text" value="50"/> dBμV	<input checked="" type="checkbox"/>	Level LOW:	<input type="text" value="60"/> dBμV	<input checked="" type="checkbox"/>		
Level HIGH:	<input type="text" value="100"/> dBμV	<input type="checkbox"/>	Level HIGH:	<input type="text" value="100"/> dBμV	<input type="checkbox"/>		
SNR LOW:	<input type="text" value="20"/> dB	<input type="checkbox"/>	C/N LOW:	<input type="text" value="20"/> dB	<input type="checkbox"/>		
<input type="button" value="Save"/>		MER LOW:	<input type="text" value="20"/> dB	<input type="checkbox"/>	MER LOW:	<input type="text" value="20"/> dB	<input type="checkbox"/>
		BER HIGH:	<input type="text" value=">1.0E-7"/>	<input type="checkbox"/>	VBER HIGH:	<input type="text" value=">1.0E-7"/>	<input type="checkbox"/>
		<input type="button" value="Save"/>		CBER HIGH:	<input type="text" value=">1.0E-3"/>	<input type="checkbox"/>	<input type="button" value="Save"/>
Misc.		Alarm					
All alarm checks:	<input type="text" value="1"/>						
ATV carrier lost:	<input checked="" type="checkbox"/>						
DVB-C carrier lost:	<input checked="" type="checkbox"/>						
DVB-T carrier lost:	<input checked="" type="checkbox"/>						
<input type="button" value="Save"/>							

NOTE: Carriers alarm is the minimum number of carriers.

NOTE: Timeout alarm is the maximum time spent scanning.

4.2.4. MPEG alarms

- Click **DVB -> Alarms -> MPEG Alarms**
- An alarm will be triggered if data for the specified service is missing for more than 3 seconds.
- The DVB Monitor automatically searches for Audio or Video PID and if such not found an alarm is triggered.



DVB Alarms

RF Alarms | **MPEG Alarms** | Active Alarms

MPEG Monitoring Settings

Type	Value	Alarm
Program alarm timeout:	3 sec.	<input checked="" type="checkbox"/>

Program List

Name	SID	Frequency	DVB	Alarm	
BNT 1	4340	154.000	DVB-C	AUDIO	<input type="button" value="UPDATE"/>
bTV	4360	154.000	DVB-C	AUDIO&VIDEO	<input type="button" value="UPDATE"/>
Nova TV	4380	154.000	DVB-C	AUDIO	<input type="button" value="UPDATE"/>
bTV Action	4400	154.000	DVB-C	NONE	<input type="button" value="UPDATE"/>

4.2.5. Active Alarms

- Click **DVB -> Alarms -> Active Alarms**
- You can see all currently active alarms with just one click.



DVB Alarms

RF Alarms | MPEG Alarms | **Active Alarms**

Active Alarms

Alarm	Mode	Frequency	Value	Threshold
LEVEL: LOW	DVB-C	650.000 MHz	55 dBuV	60 dBuV
LEVEL: LOW	DVB-C	658.000 MHz	56 dBuV	60 dBuV
LEVEL: LOW	DVB-C	666.000 MHz	55 dBuV	60 dBuV
LEVEL: LOW	DVB-C	674.000 MHz	58 dBuV	60 dBuV
LEVEL: LOW	DVB-C	682.000 MHz	57 dBuV	60 dBuV
LEVEL: LOW	DVB-C	698.000 MHz	57 dBuV	60 dBuV
CARRIER: LOST	DVB-T	514.000 MHz	-	-
CARRIER: LOST	DVB-T	698.000 MHz	-	-
CARRIER: LOST	DVB-T	770.000 MHz	-	-
VIDEO PID: NONE	DVB-C	162.000 MHz	radio Veselina E,SID:1084	-

4.3. Log

4.3.1. Alarms log

- Click **DVB-Monitor -> Log -> Alarms log**
- Displays log with 20 of the latest alarms.



* DVB STREAMER * 192.168.2.3 * MONITORING *

IP Config

DVB

Advanced

Charts

VIDEO

Config
Stream
Status
Alarms
Log

Log

Alarms log
Stream log

Logged alarms		
Time	Message	E-mail
09/05/2013 12:57:14	LEVEL: LOW # DVB-C # 650MHz # 55 dBuV	Sent
09/05/2013 12:57:15	LEVEL: LOW # DVB-C # 658MHz # 56 dBuV	Sent
09/05/2013 12:57:15	LEVEL: LOW # DVB-C # 666MHz # 55 dBuV	Sent
09/05/2013 12:57:16	LEVEL: LOW # DVB-C # 674MHz # 58 dBuV	Sent
09/05/2013 12:57:16	LEVEL: LOW # DVB-C # 682MHz # 57 dBuV	Sent
09/05/2013 12:57:17	LEVEL: LOW # DVB-C # 698MHz # 57 dBuV	Sent
09/05/2013 12:57:19	CARRIER: LOST # DVB-T # 514MHz # -	Sent
09/05/2013 12:57:20	CARRIER: LOST # DVB-T # 698MHz # -	Sent
09/05/2013 12:57:21	CARRIER: LOST # DVB-T # 770MHz # -	Sent
09/05/2013 13:03:59	VIDEO PID: NONE # DVB-C # 162MHz # radio Veselina E,SID:1084	Sent

Copyright © Kvarata Soft Ltd. 2013**

4.3.2. Stream log

- Click **DVB-Monitor -> Log -> Stream log**
- Displays log with 20 of the latest stream changes.



* DVB STREAMER * 192.168.2.3 * STREAMING *

IP Config

DVB

Advanced

Charts

VIDEO

Config
Stream
Status
Alarms
Log

Log

Alarms log
Stream log

Logged stream events	
Time	Message
09/05/2013 13:10:26	UDP # MPTS # 233.1.2.3:5441
09/05/2013 13:10:33	UDP # SPTS # (2)
09/05/2013 13:10:33	UDP # SPTS # 233.1.2.3:5441 # (1/2) Eurosport HD
09/05/2013 13:10:33	UDP # SPTS # 233.1.2.4:5441 # (2/2) NatGeo HD
09/05/2013 13:10:37	UDP # SPTS # (3)
09/05/2013 13:10:37	UDP # SPTS # 233.1.2.5:5441 # (3/3) NatGeo HD
09/05/2013 13:10:39	UDP # SPTS # 233.1.2.5:5441 # (3/3) Planeta HD

Copyright © Kvarata Soft Ltd. 2013***

4.4. Advanced Configuration

4.4.1. E-mail client configuration

NOTE: DVB Monitor supports Login authentication (no SSL). For assistance, please, contact us.

- Click **E-mail** in the side menu
- Set appropriate SMTP server and authentication configuration
- Configure e-mail parameter and subject (can include alarm text using the macro <ALARM>)

E-mail Configuration

SMTP Client	
SMTP ALARM:	Enabled ▾
Server:	smtp.yourmailserver.com
Port:	587
Authentication:	Enabled ▾
Username:	username
Password:	••••••••
DNS by DHCP:	Enabled ▾
DNS:	8.8.8.8
E-mail	
From:	you@xxxx.com
To:	you@xxxx.com
Cc:	
Bcc:	
Subject:	DVB STREAMER - <ALARM> Use <ALARM> to insert alarm message.
Text:	Sent by: DVB STREAMER
<input type="button" value="Save"/> <input type="button" value="Test Message"/>	

4.4.2. SNMP configuration

NOTE: Please, contact us for more support at support@kvarta.net

SNMP Configuration	
SNMP:	Enabled ▾
Read only community:	000000000000
Read write community:	private
Traps server IP:	0.0.0.0
Traps port:	162
Traps community:	public
<input type="button" value="Save"/>	

4.4.3. Programs configuration

- Click **Advanced** -> **Programs** to configure programs.
- programs.m3u can be loaded in VLC for video monitoring
- You can add/edit/delete all parameters for the services found in the multiplex.

Programs	RTSP	Remux	SNMP	VLAN	E-mail
-----------------	------	-------	------	------	--------

Program List Configuration

Program list: programs.txt programs.m3u						
N	Name	SID	Frequency	DVB	Update	Remove
0	BNT 1	4340	154.000	DVB-C ▾	UPDATE	REMOVE
1	bTV	4360	154.000	DVB-C ▾	UPDATE	REMOVE
2	Nova TV	4380	154.000	DVB-C ▾	UPDATE	REMOVE
3	bTV Action	4400	154.000	DVB-C ▾	UPDATE	REMOVE
4	EK	4420	154.000	DVB-C ▾	UPDATE	REMOVE
5	EK Carevec	4440	154.000	DVB-C ▾	UPDATE	REMOVE
6	TV 7	4500	154.000	DVB-C ▾	UPDATE	REMOVE
7		0	100.000	DVB-C ▾	ADD	
DELETE ALL						

4.4.4. RTSP configuration

- Click **Advanced** -> **RTSP** to enter real time streaming protocol specific configuration
- The device URL can be used if the device is behind router
- programs.m3u can be loaded in VLC for video monitoring

NOTE: You should be in Streaming mode and RTSP should be the protocol. Only one RTSP client is supported.



* DVB STREAMER * 192.168.2.3 * STREAMING *

IP Config	Programs	RTSP	Remux	SNMP	VLAN	E-mail
DVB	RTSP Configuration					
Advanced	RTSP Port: <input type="text" value="554"/>		Playlist: programs.m3u			
Charts	RTSP Filter: <input type="text" value="0.0.0.0"/>		Device URL: <input type="text"/>			
VIDEO	<input type="button" value="Save"/>					

Copyright © Kvarita Soft Ltd. 2013*

4.4.5. Remuxer Configuration

- Click **Advanced** -> **Remux** to enter SPTS remultiplexer specific configuration
- You can reconfigure the output SID, PIDs, Service Name, Provider Name, etc.

NOTE: It is only working in Streaming mode and SPTS streams.

Programs	RTSP	Remux	SNMP	VLAN	E-mail
----------	------	--------------	------	------	--------

Remultiplexer

BNT 1

SPTS Configuration			
Source	Remultiplexer	Destination	
BNT 1	ON	233.5.5.5:5401	Update
SDT Table	EIT Table	TDT Table	
ON	OFF	ON	Update
Remultiplexer Configuration			
PAT Configuration		PMT Configuration	
RESET CONFIG			
IN SID	OUT SID	IN PCR PID	OUT PCR PID
4340(BNT 1)	4340	4341	4341
	SAVE		SAVE
IN TS ID	OUT TS ID	IN PID	OUT PID
4002	4002	4341	4341
	SAVE		SAVE
IN PMT PID	OUT PMT PID		
4340	4340	4344	4344
	SAVE	4342	4342
	SAVE		SAVE
SDT Configuration			
IN NET ID	OUT NET ID		
0	0		SAVE
IN SERVICE	OUT SERVICE		
BNT 1	BNT 1		SAVE
IN PROVIDER	OUT PROVIDER		
CoresNet	CoresNet		SAVE

4.4.6. VLAN

- Click **Advanced** -> **VLAN** to configure VLAN settings for the output streams or the management





* DVB STREAMER * 192.168.2.3 * STREAMING *

IP Config	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td>Programs</td> <td>RTSP</td> <td>Remux</td> <td>SNMP</td> <td>VLAN</td> <td>E-mail</td> </tr> </table>	Programs	RTSP	Remux	SNMP	VLAN	E-mail				
Programs	RTSP	Remux	SNMP	VLAN	E-mail						
DVB	<h3>VLAN Configuration</h3>										
Advanced	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr style="background-color: #e6f2ff;"> <th colspan="2">Outgoing VLAN Configuration</th> </tr> </thead> <tbody> <tr> <td>Outgoing VLAN:</td> <td>Disabled</td> </tr> <tr> <td>Management VLAN:</td> <td>0</td> </tr> <tr> <td>Streams VLAN:</td> <td>Stream</td> </tr> <tr> <td colspan="2" style="text-align: center;">Save</td> </tr> </tbody> </table>	Outgoing VLAN Configuration		Outgoing VLAN:	Disabled	Management VLAN:	0	Streams VLAN:	Stream	Save	
Outgoing VLAN Configuration											
Outgoing VLAN:	Disabled										
Management VLAN:	0										
Streams VLAN:	Stream										
Save											
Charts											
VIDEO											

Copyright © Kvarta Soft Ltd. 2013*

4.5. Charts

- Click **Charts** in the side menu to view a graphical representation of the RF parameters (works only in scan mode)



5. GLOSSARY

DVB – Digital Video Broadcasting

DVB-C – Digital Video Broadcasting - Cable

DVB-T – Digital Video Broadcasting – Terrestrial

SNMP – Simple Network Management Protocol

SMTP – Simple Mail Transfer Protocol

PID – Packet Identification

PAT – Program Allocation Table

PMT – Program Map Table

NIT – Network Identification Table

TDT – Time and Date Table

TOT – Time Offset Table

SDT – Service Description Table

CAT – Conditional Access Table

APPENDIX A - DVB MONITOR ASCII COMMAND SET

A.1. DEFAULT VALUES

Parameter	Default Value
IP	192.168.2.3
Mask	255.255.255.0
Gateway	192.168.2.1
DHCP	Disabled
Web Server	Enabled
Web Server : <username>,<password>	admin,admin
CT synchronization:	Enabled
Time server IP :	129.6.15.28

A.2. Configuration and special files on the device

- a. **config.ini** - Keeps all configuration information (windows configuration file)
- b. **freq.txt** - Keeps monitoring frequencies (comma separated file)
- c. **programs.txt** - Keeps programs on the device (comma separated file)
- d. **help.txt** - ASCII commands description file
- e. *****.mib** - SNMP MIB file

A.3. ASCII COMMANDS

```
-- *****
-- Device Model: DVB MENTOR 0.05B (10/05/2013)
-- Auto-generated file!
-- Definitions apply to DVB MENTOR
-- Supported ASCII COMMANDS
-- for more information support@kvarta.net
-- Kvarta Soft Ltd (www.kvarta.net)
-- *****

--
-- The 'GENERAL' group;
--

IP                               read-write      IP Address
```

MASK	read-write	Sub. network mask
GATEWAY	read-write	Gateway IP Address
DHCP	read-write	DHCP Enable/Disable
DNS	read-write	DNS Server IP
DNS_BY_DHCP	read-write	DNS Server by DHCP
CT_SERVER_ON	read-write	Clock time server used
CT_SERVER_IP	read-write	Clock time server (RFC-868)
CT_OFFSET	read-write	Clock time offset
LOG	read-write	Logs All Ip connections
USERNAME	read-write	Set/Display username
PASSWORD	read-write	Set/Display password
TCP_TIMEOUT	read-write	Timeout in seconds if no
communication,close socket		
VLAN_ON	read-write	Outgoing VLAN On/Off
TCP_VLAN	read-write	Management VLAN
MODEL	read-only	Device model
VERSION	read-only	Firmware version
DEVICE_NAME	read-write	Name of the device (Location)
WEB_SNMP_SERVER	read-only	SNMP Server On/Off
WEB_SMTP_AUTH	read-only	E-mail authentication On/Off
WEB_SMTP_ALARM	read-only	E-mail alarms On/Off
MAC	read-only	Reads the MAC address
CURRENT_IP	read-only	Reads the current IP address
CURRENT_MASK	read-only	Reads the current sub. network
mask		
CURRENT_GATEWAY	read-only	Reads the current gateway IP
address		
DHCP_STATUS	read-only	Reads DHCP status
UPDATE_AVAILABLE	read-only	Reads if there is update
available		
UPDATE_START	write-only	Starts un update
--		
-- The 'WEB' group;		
--		
WEB.SERVER	read-write	Embedded Web Server On/Off
WEB.PORT	read-write	TCP port of the web
server (Default:80)		
WEB.FILTER	read-write	Allowed HOST IP to connect to
the web server		
WEB.VLAN	read-write	VLAN of the web server
--		
-- The 'FTP' group;		
--		
FTP.SERVER	read-write	Embedded FTP Server On/Off
FTP.PORT	read-write	TCP port of the FTP
server (Default:21)		
FTP.FILTER	read-write	Allowed HOST IP to connect to
the web server		
FTP.VLAN	read-write	VLAN of the FTP server
--		
-- The 'TCP' table;		
--		
TCP(???) .TYPE	read-write	Remote port TCP/UDP/OFF
TCP(???) .PORT	read-write	Remote port TCP/UDP port
number		
TCP(???) .FILTER	read-write	Remote port input IP filter

```

TCP(???) .PROTOCOL          read-write          Remote port protocol
ASCII/SNMP
TCP(???) .VLAN              read-write          Remote port VLAN
--
-- The 'SNMP' group;
--

SNMP.SERVER                 read-write          SNMP Server On/Off
SNMP.TRAP_PORT              read-write          SNMP Traps destinatio port
SNMP.RO_PASSWORD            read-write          SNMP read only community
string
SNMP.RW_PASSWORD            read-write          SNMP read write community
string
SNMP.TRAP_PASSWORD          read-write          SNMP trap password
SNMP.TRAP_SERVER1           read-write          SNMP trap server(1) IP
SNMP.TRAP_SERVER2           read-write          SNMP trap server(2) IP
SNMP.TRAP_SERVER3           read-write          SNMP trap server(3) IP
SNMP.TRAP_SERVER4           read-write          SNMP trap server(4) IP
--
-- The 'SMTP' group;
--

SMTP.SEND                   COMMAND            SMTP Send e-mail command
SMTP.ALARM                  read-write          SMTP e-mail alarms
Enable/Disable
SMTP.SERVER                  read-write          SMTP server url address
SMTP.PORT                   read-write          SMTP server port
SMTP.AUTH                   read-write          SMTP authentication
enable/disable
SMTP.USER                   read-write          SMTP authentication username
SMTP.PASSWORD                read-write          SMTP authentication password
SMTP.FROM                    read-write          E-mail From address
SMTP.TO                      read-write          E-mail To address
SMTP.CC                      read-write          E-mail CC address
SMTP.BCC                     read-write          E-mail BCC address
SMTP.SUBJECT                 read-write          E-mail subject.Macro <ALARM>
can be used.
SMTP.TEXT                    read-write          E-mail signature
--
-- The 'TUNER' group;
--

TUNER_MODE                  read-write          Tuner mode Analog/DVB-C/DVB-T
FREQUENCY                   read-write          Tune frequency
SCAN                         read-write          Set SCAN On(Monitoring) or
Off(Streaming)
AUTO_INSTALL                 read-write          Automatically install new
programs during scan
ATV_INPUT                   read-write          Input 0=A or 1-B
ATV_COLOR                   read-write          0-PAL_NTSC or 1-SECAM
ATV_SPECTRUM                read-write          0-Normal; 1-Invert
ATV_TRANS                   read-write          0-Terrestrial; 1-Cable
ATV_SYS                     read-write          0-B;1-GH;2-M;3-N;4-I;5-DK;6-
L;7-LP;
DVBT_INPUT                  read-write          Input 0-A or 1-B
DVBT_BW                     read-write          Default bandwidth
6/7/8(default)
DVBT_SPECTRUM               read-write          0-Normal, 1-Inverted
DVBC_INPUT                  read-write          Input 0-A or 1-B

```

```

DVBC_BW                read-write      Default bandwidth
6/7/8 (default)
DVBC_QAM               read-write      Default constellation
16/32/64/128/256
DVBC_SYMBOLS           read-write      Default symbol rate 1000 -
7000
DVBC_SPECTRUM          read-write      0-Normal, 1-Inverted
TUNE_SAVE              COMMAND       Save tuner configuration
TUNE_NEXT              COMMAND       Go to next carrier
TUNE_PREV              COMMAND       Go to previous carrier
ALARM_CHECK            read-write      Alarm checks before sending e-
mail or snmp trap.

--
-- The 'FREQUENCY_FILE' group;
--

FREQUENCY_FILE.FILENAME read-write      Filename of the frequency file
FREQUENCY_FILE.SAVE     COMMAND       Saves all monitoring
frequencies.
FREQUENCY_FILE.LOAD     COMMAND       Loads all monitoring
frequencies from file.

--
-- The 'F' table;
--

F(???) .ATV            read-write      Set frequency or scan range
F(???) .DVBC           read-write      Set frequency or scan range
F(???) .DVBT           read-write      Set frequency or scan range

--
-- The 'ATV' group;
--

ATV.EXPECTED           read-write      Expected carriers during
monitoring
ATV.EXPECTED_ON        read-write      Carrier count alarm On/Off
ATV.TIMEOUT            read-write      Scan timeout in seconds
ATV.TIMEOUT_ON         read-write      Scan timeout alarm On/Off
ATV.LEVEL_LOW          read-write      Low level threshold in dBuV
ATV.LEVEL_LOW_ON       read-write      Low level alarm On/Off
ATV.LEVEL_HIGH         read-write      High level threshold in dBuV
ATV.LEVEL_HIGH_ON      read-write      High level alarm On/Off
ATV.SNR_LOW            read-write      SNR low level threshold in dB
ATV.SNR_LOW_ON         read-write      SNR low level alarm On/Off
ATV.LOST_ON            read-write      Carrier lost alarm On/Off

--
-- The 'DVBC' group;
--

DVBC.EXPECTED          read-write      Expected carriers during
monitoring
DVBC.EXPECTED_ON       read-write      Carrier count alarm On/Off
DVBC.TIMEOUT           read-write      Scan timeout in seconds
DVBC.TIMEOUT_ON        read-write      Scan timeout alarm On/Off
DVBC.LEVEL_LOW         read-write      Low level threshold in dBuV
DVBC.LEVEL_LOW_ON      read-write      Low level alarm On/Off
DVBC.LEVEL_HIGH        read-write      High level threshold in dBuV
DVBC.LEVEL_HIGH_ON     read-write      High level alarm On/Off
DVBC.CNR_LOW           read-write      SNR low level threshold in dB
DVBC.CNR_LOW_ON        read-write      SNR low level alarm On/Off

```

```

DVBC.MER_LOW                read-write    MER low threshold in dB
DVBC.MER_LOW_ON            read-write    MER low alarm On/Off
DVBC.BER_HIGH              read-write    BER high threshold 0=1e-
7,1=1e-6 ...max 7
DVBC.BER_HIGH_ON          read-write    BER high alarm On/Off
DVBC.LOST_ON              read-write    Carrier lost alarm On/Off

--
-- The 'DVBT' group;
--

DVBT.EXPECTED              read-write    Expected carriers during
monitoring
DVBT.EXPECTED_ON          read-write    Carrier count alarm On/Off
DVBT.TIMEOUT              read-write    Scan timeout in seconds
DVBT.TIMEOUT_ON          read-write    Scan timeout alarm On/Off
DVBT.LEVEL_LOW            read-write    Low level threshold in dBuV
DVBT.LEVEL_LOW_ON        read-write    Low level alarm On/Off
DVBT.LEVEL_HIGH          read-write    High level threshold in dBuV
DVBT.LEVEL_HIGH_ON       read-write    High level alarm On/Off
DVBT.CNR_LOW             read-write    SNR low level threshold in dB
DVBT.CNR_LOW_ON         read-write    SNR low level alarm On/Off
DVBT.MER_LOW             read-write    MER low threshold in dB
DVBT.MER_LOW_ON         read-write    MER low alarm On/Off
DVBT.VBER_HIGH           read-write    VBER high threshold 0=1e-
7,1=1e-6 ...max 7
DVBT.VBER_HIGH_ON       read-write    VBER high alarm On/Off
DVBT.CBER_HIGH           read-write    CBER high threshold 0=1e-
7,1=1e-6 ...max 7
DVBT.CBER_HIGH_ON       read-write    CBER high alarm On/Off
DVBT.LOST_ON            read-write    Carrier lost alarm On/Off

--
-- The 'MPEG' group;
--

MPEG.PID_TIMEOUT          read-write    MPEG alarm timeout in seconds
MPEG.PID_TIMEOUT_ON      read-write    MPEG alarms On/Off

--
-- The 'RTSP' group;
--

RTSP.PORT                 read-write    RTSP port configuration
(Default:554)
RTSP.FILTER               read-write    RTSP input IP filter
RTSP.ADDRESS              read-write    RTSP address if device behind
router(Default:empty string) uses current IP
RTSP.PROG                 write-only    Select RTSP program to stream

--
-- The 'STREAMING' group;
--

STREAM_PROTOCOL           read-write    Select streaming protocol
OFF/UDP/RTP/RTSP
STREAM_TYPE               read-write    Select MPEG TS stream type
MPTS/SPTS
STREAM_COUNT              read-write    Select stream count for SPTS
only
STREAM_VLAN               read-write    Select default streaming VLAN

--

```

```

-- The 'PROGRAMS' group;
--

PROGRAMS.REMOVE          COMMAND          Command to delete all programs
from the list
PROGRAMS.DELETE         COMMAND          Command to delete all programs
from the list
PROGRAMS.SAVE           COMMAND          Command to save programs to
programs.txt file
PROGRAMS.LOAD           COMMAND          Command to load programs from
programs.txt file
PROGRAMS.NEW            COMMAND          Command to create new program
--
-- The 'P' table;
--
P(???).INDEX           read-write      Program index in the list
P(???).SID             read-write      Program SID number
P(???).FREQ            read-write      Program frequency
P(???).NAME            read-write      Program service name
P(???).DVB_MODE        read-write      Program DVB mode DVB-C/DVB-T
P(???).ALARM           read-write      Program alarm type
none/audio/video
P(???).REMOVE          COMMAND          Command to remove the program
from the list
P(???).DELETE          COMMAND          Command to remove the program
--
-- The 'S' table;
--

S(???).RESET           COMMAND          Reset remuxer settings
S(???).ADDRESS         read-write      Stream destination IP address
and port
S(???).SID             read-write      Streaming sid number
S(???).VLAN            read-write      Streaming VLAN
S(???).REMUX           read-write      Streaming remuxer On/Off
S(???).SDT_EN          read-write      Stream SDT table On/Off
S(???).EIT_EN          read-write      Stream EIT table On/Off
S(???).TDT_EN          read-write      Stream TDT table On/Off
S(???).OUT_SID         read-write      Stream REMUX ouput SID
S(???).OUT_TS          read-write      Stream REMUX ouput TS
S(???).OUT_PMT_PID     read-write      Stream REMUX ouput PMT PID
S(???).OUT_NET_ID      read-write      Stream REMUX ouput NET ID
S(???).OUT_PCR_PID     read-write      Stream REMUX ouput PCR PID
S(???).OUT_SNAME       read-write      Stream REMUX ouput service
name
S(???).OUT_PNAME       read-write      Stream REMUX ouput provider
name
S(???).ES_COUNT        read-write      Stream REMUX elementary
streams count
S(???).IN_PID(???)    read-write      Stream REMUX input elementary
stream PID
S(???).OUT_PID(???)   read-write      Stream REMUX output elementary
stream PID
S(???).DELETE          COMMAND          Command to delete the SPTS
stream
S(???).ADD             COMMAND          Command to add new SPTS stream
--
-- The 'COMMANDS' group;
--

RESET                  COMMAND          Software reboot of the device

```