

Model #: RS-1215-20T

Tripp Lite Power Strip - 1U Rackmount Multi-Outlet Power Strip

Highlights

- Designed for standard 19-in. racks (1U high)
- 12 NEMA5-15/20R outlets (6 front/6 rear)
- 15-ft. cord with locking NEMA L5-20P input plug
- 20A circuit breaker



Description

Tripp Lite's RS-1215-20T Power Strip offers 20A capacity AC power distribution in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for rackmount, wallmount and under-counter installation. Uses only 1 rack space (1U) when installed in any 19-in. rack meeting EIA standards. Unfiltered electrical pass-through makes RS-1215-20T ideal for distributing alternate waveform UPS or generator power in rack enclosures, network closets and more. Includes 12 NEMA5-15/20R outlets (6 front/6 rear), 15-ft. AC power cord with locking NEMA L5-20P input plug and lighted switch with cover that prevents risk of accidental turn-off.

PLUG/OUTLETS: Input: NEMA L5-20P Output: 12 x NEMA5-15/20R (6 front/6 rear)

ELECTRICAL: 120V AC, 50/60Hz, 20A (Requires NEMA 5-20R wall receptacle)

FORMAT: 19-in. rackmount (uses 1 rack space/1U), wallmount, under-counter and more

Applications

 Multiple-outlet power distribution for multiple loads in 19-in. rackmount, wallmount and under-counter applications, such as internetworking, PC systems, telecommunications, audio/video, security, sound reinforcement and more. Ideal for distribution of UPS, generator or commercially derived AC power to protected equipment.

Features

- Versatile all-metal cabinet with detachable mounting flanges allows rackmount, wallmount, undercounter and other creative mounting options
- Uses one rack space (1U) in standard 19-in. rack ("zero U" mounting possible in many racks)
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 12 x NEMA5-15/20R output receptacles (6 front/6 rear)
- 15-ft. AC cord with NEMA L5-20P input plug
- · Lighted power switch confirms power on/off status
- Snap-in switch guard prevents accidental turn-off
- 20A electrical capacity with circuit breaker
- 120V AC, 50/60Hz electrical compatibility

Specifications

Frequency compatibility 50/60 Hz DUTPUT 20 NEMA 5-15/20R Dutlet quantity / type 12 NEMA 5-15/20R Deveload protection 20 A Cloub breaker NPUT Imput conduction type Input cond length (t.) 15 Recommended Electrical 20A 120V dedicated line Services Lighted power switch LCbS ALARS & SWITCHES Vers Switches Lighted power switch Locking switch cover Yes PHYSICAL 5.7 Shipping weight (tbg) 6 Shipping Jimensions 6.7 Shipping Jimensions 5.7 x 52.1 x 24.1 Unit weight (kg) 2.4 Unit weight (kg) 2.4 Unit weight (kg) 2.4 Unit weight (kg) 2.4 Material construction Steel Form factors supported 1/U rackmount, wailmount Mauting accessories 1/U rackmount flanges Receptale Color Biack CERTIFICATIONS Kurnount flanges Receptale Color Biack	SYSTEM OVERVIEW	
DUTPUT OUTEVIT OUTEVIT OUTEVIT OUTEVIT INDUCTION I	Voltage compatibility	120V
Dutlet quantity / type 12 NEMA 5-16/20R Diverload protection 20A circuit breaker NPUT Implement Connection type Input cond length (ft.) 15 Recommende Electrical 20A 120V dedicated line Service 20A 120V dedicated line Service Lipted power switch LEDS ALARMS & SWITCHES Ves Switches Lighted power switch Locking switch (vp) 6 Shipping weight (hs) 6 Shipping Dimensions 2.25 x 20.5 x 9.5 Shipping Dimensions 5.7 x 52.1 x 24.1 Mit Weight (hs) 5.4 Unit weight (hs) 4.3 x 44.4 x 11.4 Material of construction Stel Grund Electrone Stel Mounting accessories 1/U rackmount, wallmount Mounting accessories 1/U rackmount, Mallmount Receptacle Color Back CERTIFICATIONE Lecongnized (USA)/CUR (Canada)	Frequency compatibility	50/60 Hz
Overlaad protection 20A circuit breaker NPUT Input connection type NEMA L5-20P Input cord length (ft.) 15 Recommended Electrical 20A 120V dedicated line Service 20A 120V dedicated line Service Lighted power switch Locking switch cover Yes PHYSICAL Shipping weight (lbs) Shipping Dimensions 2.7 Shipping Dimensions 2.25 x 20.5 x 9.5 Shipping Dimensions 5.7 x 52.1 x 24.1 Unit weight (lbs) 5.4 Unit weight (lbs) 1.5 (1U) x 17.5 x 4.5 Unit derice of construction Steel Form factors supported 1U rackmount flanges Receptale Color Black Cellen cord color Black Celtrecord color	OUTPUT	
NPUT NEMA L5-20P input condiength (ft.) 15 Recommended Electrical service 20A 120V dedicated line Service Ughted power switch LEDS ALARMS & SWITCHES Ves Switches Ughted power switch Locking switch cover Yes PHYSICAL 2.7 Shipping weight (hg) 2.7 Shipping Dimensions 2.25 x 20.5 x 9.5 Shipping Dimensions 5.7 x 52.1 x 24.1 Unit weight (hg) 2.4 Unit weight (hg) 2.4 Unit weight (hg) 2.4 Unit weight (hg) 2.4 Unit weight (hg) 3.44.4 x 11.4 Material of construction Sleel Form factors supported Un ackmount flanges Receptace Color Black Recentace Color B	Outlet quantity / type	12 NEMA 5-15/20R
Input connection type NEMA L5-20P Input cord length (t.) 15 Recommended Electrical Service 20A 120V dedicated line Service 20A 120V dedicated line Service Uighted power switch LEDS ALARMS & SWITCHES Ves Switches Uighted power switch Lecking switch cover Yes PHYSICAL 5 Shipping weight (kg) 6 Shipping Dimensions 2.25 x 20.5 x 9.5 Shipping Dimensions 5.7 x 52.1 x 24.1 WhVD(rm) 5.4 Unit weight (kg) 2.4 Vind LDimensions (HWD/cm) 4.3 x 44.4 x 11.4 Material of construction Steel Form factors supported U ackmount, wallmount Mouting accessories U ackmount flanges Receptacle Color Black Coline cord color back Black CentricCATIONS UL-recognized (USA)/cUR (Canada)	Overload protection	20A circuit breaker
Input cord length (h.) 15 Recommended Electrical Service 20A 120V dedicated line Service 20A 120V dedicated line ELEDS ALARMS & SWITCHES Electrical Switches Lighted power switch Ves PHYSICAL PHYSICAL 5 Shipping weight (lbs) 6 Shipping Dimensions 2.25 x 20.5 x 9.5 Shipping Dimensions 5.7 x 52.1 x 24.1 Shipping Dimensions 5.4 Unit weight (lbs) 5.4. Unit weight (lbs) 5.4. Unit Dimensions (HWD/rm) 1.75 (1U) x 17.5 x 4.5 Woldman accessories 1.0 ackmount, wallmount Woldman accessories 1.0 ackmount, wallmount Receptacle Color Black Celtriticutode Black	INPUT	
Recommended Electrical Service 20A 120V dedicated line Service 20A 120V dedicated line Service Ves Switch cover Yes PHYSICAL 6 Shipping weight (bg) 6. Shipping meight (kg) 2.7 Shipping Dimensions 2.25 x 20.5 x 9.5 Shipping Dimensions 5.7 x 52.1 x 24.1 Unit weight (bs) 5.4 Unit weight (kg) 2.4 Unit weight (kg) 2.4 Unit weight (kg) 3. x 44.4 x 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories 1U rackmount, flanges Receptacle Color Black Centricot color Black	Input connection type	NEMA L5-20P
Service Identify a construction of the service of the se	Input cord length (ft.)	15
Switches Lighted power switch Locking switch cover Yes PHYSICAL 6 Shipping weight (lbs) 6 Shipping meight (kg) 2.7 Shipping Dimensions 2.25 x 20.5 x 9.5 Shipping Dimensions 5.7 x 52.1 x 24.1 Unit weight (lbs) 5.4 Unit weight (kg) 2.4 Unit bimensions (HWD/in) 1.75 (1U) x 17.5 x 4.5 Unit Dimensions (HWD/in) 4.3 x 44.4 x 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories 1U rackmount flanges Receptacle Color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY Vercent supported	Recommended Electrical Service	20A 120V dedicated line
Locking switch cover Yes PHYSICAL 6 Shipping weight (lbs) 6 Shipping weight (kg) 2.7 Shipping Dimensions 2.25 x 20.5 x 9.5 Shipping Dimensions 2.7 x 52.1 x 24.1 Unit weight (lbs) 5.4 Unit weight (kg) 2.4 Unit weight (kg) 2.4 Unit Dimensions (HWD/in) 1.75 (1U) x 17.5 x 4.5 Unit Dimensions (HWD/in) 4.3 x 44.4 x 11.4 Material of construction Steel Form factors supported 1U rackmount manges Included Black CERTFICATIONS Black CERTFICATIONS UL-recognized (USA)/cUR (Canada)	LEDS ALARMS & SWITCHES	
PHYSICAL Shipping weight (lbs) 6 Shipping weight (kg) 2.7 Shipping Dimensions 2.25 x 20.5 x 9.5 Shipping Dimensions 5.7 x 52.1 x 24.1 Unit weight (lbs) 5.4 Unit weight (kg) 2.4 Unit Dimensions (HWD/in) 1.75 (1U) x 17.5 x 4.5 Unit Dimensions (HWD/m) 4.3 x 44.4 x 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories included 1U rackmount flanges Receptacle Color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY UL-recognized (USA)/cUR (Canada)	Switches	Lighted power switch
Shipping weight (lbs) 6 Shipping weight (kg) 2.7 Shipping Dimensions 2.25 × 20.5 × 9.5 Shipping Dimensions 5.7 × 52.1 × 24.1 WWD/cm) 5.7 × 52.1 × 24.1 Unit weight (lbs) 5.4 Unit weight (kg) 2.4 Unit Dimensions (HWD/in) 1.75 (1U) × 17.5 × 4.5 Unit Dimensions (HWD/in) 4.3 × 44.4 × 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories included 1U rackmount flanges Cline cord color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY UL-recognized (USA)/cUR (Canada)	Locking switch cover	Yes
Shipping weight (kg) 2.7 Shipping Dimensions 2.25 x 20.5 x 9.5 (HWD/in) 2.25 x 20.1 x 24.1 Unit weight (lbs) 5.7 x 52.1 x 24.1 Unit weight (kg) 2.4 Unit weight (kg) 2.4 Unit weight (kg) 1.75 (1U) x 17.5 x 4.5 Unit Dimensions (HWD/in) 1.75 (1U) x 17.5 x 4.5 Unit Dimensions (HWD/cm) 4.3 x 44.4 x 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories 1U rackmount flanges CERTIFICATIONS Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY UL-recognized (USA)/cUR (Canada)	PHYSICAL	
Shipping Dimensions 2.25 x 20.5 x 9.5 Shipping Dimensions 5.7 x 52.1 x 24.1 Unit weight (lbs) 5.4 Unit weight (kg) 2.4 Unit Dimensions (HWD/in) 1.75 (1U) x 17.5 x 4.5 Unit Dimensions (HWD/cm) 4.3 x 44.4 x 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories 1U rackmount flanges Receptacle Color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY Intercompliated (USA)/cUR (Canada)	Shipping weight (lbs)	6
(HWD/in) Shipping Dimensions Shipping Dimensions S.7 x 52.1 x 24.1 Unit weight (lbs) S.4 Unit weight (kg) 2.4 Unit Dimensions (HWD/in) 1.75 (1U) x 17.5 x 4.5 Unit Dimensions (HWD/cm) 4.3 x 44.4 x 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories included 1U rackmount flanges Receptacle Color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY I	Shipping weight (kg)	2.7
(HWD/cm) 5.4 Unit weight (lbs) 5.4 Unit weight (kg) 2.4 Unit Dimensions (HWD/in) 1.75 (1U) × 17.5 × 4.5 Unit Dimensions (HWD/cm) 4.3 × 44.4 × 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories included 1U rackmount flanges Receptacle Color Black AC line cord color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada)	Shipping Dimensions (HWD/in)	2.25 x 20.5 x 9.5
Unit weight (kg) 2.4 Unit Dimensions (HWD/in) 1.75 (1U) x 17.5 x 4.5 Unit Dimensions (HWD/cm) 4.3 x 44.4 x 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories included 1U rackmount flanges Receptacle Color Black AC line cord color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY IU	Shipping Dimensions (HWD/cm)	5.7 x 52.1 x 24.1
Unit Dimensions (HWD/in) 1.75 (1U) x 17.5 x 4.5 Unit Dimensions (HWD/cm) 4.3 x 44.4 x 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories included 1U rackmount flanges Receptacle Color Black AC line cord color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY IU-recognized (USA)/cUR (Canada)	Unit weight (Ibs)	5.4
Unit Dimensions (HWD/cm) 4.3 x 44.4 x 11.4 Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories included 1U rackmount flanges Receptacle Color Black AC line cord color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY UL-recognized (USA)/cUR (Canada)	Unit weight (kg)	2.4
Material of construction Steel Form factors supported 1U rackmount, wallmount Mounting accessories included 1U rackmount flanges Receptacle Color Black AC line cord color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY VUL-recognized (USA)/cUR (Canada)	Unit Dimensions (HWD/in)	1.75 (1U) x 17.5 x 4.5
Form factors supported 1U rackmount, wallmount Mounting accessories included 1U rackmount flanges Receptacle Color Black AC line cord color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY VIII rackmount (VIIII)	Unit Dimensions (HWD/cm)	4.3 x 44.4 x 11.4
Mounting accessories included 1U rackmount flanges Receptacle Color Black AC line cord color Black CERTIFICATIONS UL-recognized (USA)/cUR (Canada) WARRANTY Image: Center of the second se	Material of construction	Steel
included Black Receptacle Color Black AC line cord color Black CERTIFICATIONS Approvals UL-recognized (USA)/cUR (Canada)	Form factors supported	1U rackmount, wallmount
AC line cord color Black CERTIFICATIONS Approvals UL-recognized (USA)/cUR (Canada) WARRANTY	Mounting accessories included	1U rackmount flanges
CERTIFICATIONS Approvals UL-recognized (USA)/cUR (Canada) WARRANTY	Receptacle Color	Black
Approvals UL-recognized (USA)/cUR (Canada) WARRANTY	AC line cord color	Black
WARRANTY	CERTIFICATIONS	
	Approvals	UL-recognized (USA)/cUR (Canada)
Product Warranty Period Lifetime	WARRANTY	
	Product Warranty Period	Lifetime

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3133.

©2009 Tripp Lite. All Rights Reserved.