



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: SK6-0

6-Outlet, Direct Plug-In Surge Suppressor

Highlights

- 6 outlets/direct plug-in
- 750 joule rating
- \$10,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)



Description

The SK6-0 Surge Suppressor from Tripp Lite is ideal for protecting audio/video devices and printers. This direct plug-in surge suppressor features 6 outlets and 750 joules of surge energy absorption. \$10,000 [Ultimate Lifetime Insurance](#) (USA & Canada only).

Applications

- Personal computers, CAD/CAM/CAE workstations, network nodes, file servers, point-of-sale terminals, audio/visual devices, and more.

Package Includes

- SK6-0 Surge Suppressor
- Warranty information
- Instruction manual

Features

- 6 outlets; direct plug-in
- Surge energy absorption: 750 joules; 27,000 amps
- Lifetime warranty with \$10,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

Specifications

| OVERVIEW | |
|---------------------------------|-------------|
| Intended Application | Home/Office |
| SYSTEM OVERVIEW | |
| Voltage compatibility | 120 VAC |
| Frequency compatibility | 50/60 Hz |
| OUTPUT | |
| Output volt amp capacity (amps) | 15 |
| Output watts | 1800 |

| | |
|-------------------------------------|--|
| Outlet quantity / type | 6 NEMA 5-15R |
| Transformer accommodation | Holds up to 4 large transformer plugs |
| INPUT | |
| Input connection type | NEMA 5-15P input plug |
| Input cord length (ft.) | Direct plug-in |
| Recommended Electrical Service | 120V (110-125V) |
| SURGE / NOISE SUPPRESSION | |
| Protection modes | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression |
| AC suppression joule rating | 750 joules |
| Clamping voltage (RMS) | 150V |
| AC suppression response time | < 1 ns |
| AC suppression surge current rating | 27,000 amps |
| UL1499 let through rating | 330V - UL Verified |
| Immunity | Conforms to IEE 587 / ANSI C62.41 |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | No |
| Cable (Coax) Protection | No |
| Network (Ethernet) Protection | No |
| PHYSICAL | |
| Unit Dimensions (HWD/in) | 4.25 x 3.5 x 1.25 |
| Unit Dimensions (HWD/cm) | 10.8 x 8.9 x 3.2 |
| Material of construction | Plastic |
| Integrated keyhole mounting tabs | Direct plug-in suppressor mounts directly to a wall receptacle |
| Receptacle Color | Gray |
| Style | Direct plug-in |
| CERTIFICATIONS | |
| UL1449 1998 Rev. (AC Suppression) | UL1449 |
| Approvals | Exceeds IEEE 587 category A&B specifications |
| WARRANTY | |
| Product Warranty Period | Lifetime |
| Connected Equipment Coverage | \$10,000 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=119.