

Telephone: +(773) 869 1234



Model #: SS7619-15

Tripp Lite Power Strip with Surge Suppression - Multiple outlets wherever you need them

Highlights

- 24 outlets
- 15-ft. cord
- 72-in. length
- 450-joule rating



Description

The SS7619-15 6-ft. power strip with AC surge suppression offers a convenient method of horizontal or vertical power distribution in equipment racks, computer rooms, workbenches, raceways and more. Includes 24 NEMA 5-15R output receptacles with 2.795-in. center-to-center spacing, 15-ft. AC line cord and adjustable mounting clips for installation in a wide variety of applications. Protects connected equipment from transient surges and line noise with built-in surge suppression rated at 450 joules. Corded, multi-outlet strip reduces cabling clutter and enables the connection of multiple electrical devices to a single AC wall socket. Features rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15A resettable circuit breaker and attractive gray color scheme.

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 24 NEMA 5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: 6-ft. corded vertical/raceway power distribution strip

SURGE SUPPRESSION: 450 joules

Applications

. Offers outlet power distribution with surge suppression for multiple loads in equipment racks, computer rooms, workbenches and raceways in a variety of internetworking, telecommunications, audio/video and live sound applications.

Package Includes

- SS7619-15 Power Strip/Surge Suppressor
- Set of adjustable mounting clips
- Warranty information
- Instruction manual

Features

- Long 6-ft./72-in. strip offers convenient power distribution and surge suppression in equipment racks, computer rooms, workbenches, raceways and more
- Includes 24 NEMA 5-15R output receptacles with 2.795-in. center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff

- Adjustable mounting clips support installation in a variety of applications
- UL1363/1449400V (USA), cUL (Canada)
- 15A power handling capacity with circuit breaker
- 450-joule AC surge suppression
- 15-ft. AC line cord

Specifications

OVERVIEW		
Intended Application	Computer Networking, Industrial/Factory Floor	
SYSTEM OVERVIEW		
Voltage compatibility	120 VAC	
Frequency compatibility	50/60 Hz	
OUTPUT		
Output volt amp capacity (amps)	15A	
Output watts	1800	
Outlet quantity / type	24 NEMA 5-15R	
Outlet spacing	2.795-in. (center to center)	
INPUT		
Input connection type	NEMA 5-15P	
Input cord gauge, type	14 gauge, SJT	
Input cord length (ft.)	15	
Input cord length (m)	4.6	
Recommended Electrical Service	120V	
LEDS ALARMS & SWITCHES		
Switches	Lighted two-position power switch controls power to all outlets	
Locking switch cover	Transparent locking switch cover prevents accidental shutoff	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	450 joules	
UL1499 let through rating	400VUL Verified	
DATALINE SURGE SUPPRESSION		
Telephone/DSL Protection	No	
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Unit Dimensions (HWD/in)	72 x 1.5 x 1.5	
Unit Dimensions (HWD/cm)	182.9 x 3.8 x 3.8	
Material of construction	Metal	
Mounting accessories included	Set of adjustable mounting clamps	
Receptacle Color	Black	
AC line cord color	Black	
Style	Strip	
CERTIFICATIONS		

UL1449 1998 Rev. (AC Suppression)	UL1449	
UL1363 (Power Tap)	UL1363	
cUL / CSA (Canada)	cUL	
WARRANTY		
Product Warranty Period	Lifetime	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=1949.

©2009 Tripp Lite. All Rights Reserved.