



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: TLM626TEL15

Protect It! Surge Suppressor



Highlights

- 6 right-angle outlets / 15 ft. cord
- 1208 joule rating
- Tel/DSL surge protection (1 line)
- \$75,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

Description

Tripp Lite's TLM626TEL15 surge suppressor offers complete AC and Tel/DSL line surge suppression for comprehensive protection of workstations, personal computers, home stereos, televisions, VCRs, DVD players and other sensitive electronics. Heavy grade AC surge suppression shields connected equipment from damage and performance problems due to transient surges. Set of RJ-11 telephone line suppression jacks protect a single dialup modem, DSL modem, fax or phone line. TLM626TEL15 offers 6 right-angle outlets, a 15 foot power cord and diagnostic LEDs to warn of wiring problems and suppressor damage. AC surge suppression rated at 1208 joules shields equipment from surges and line noise. Rugged metal housing with 2 designated transformer plug outlets offers convenient protection of desktop computer equipment and accessories. Lifetime warranty with \$75,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only).

PLUG/OUTLETS: Input - 15 ft. AC line cord with NEMA 5-15P plug/Output - 6 NEMA 5-15R right-angle outlets

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle)

FORMAT: Metal strip

SUPPRESSION: AC: 150V RMS Clamping/1208 joules/330V UL1449

Applications

- Ideal for personal computers, TV/VCR/DVD, stereos and lamps/lighting

Package Includes

- TLM626TEL15 surge suppressor
- 6 ft. RJ-11 phone cord
- Instruction manual and warranty information

Features

- 6 right-angle outlets
- 15 ft. cord
- Built-in RJ-11 jacks prevent surges from damaging your telephone/DSL/modem/fax equipment; 6 ft. telephone cord included
- Surge suppression rating: 1208 joules
- EMI/RFI noise filtering

- 15 amp resettable circuit breaker protects against overload
- Diagnostic LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
- Convenient keyhole slots allow secure mounting on wall or desk
- Can accommodate up to 2 transformers without blocking adjacent outlets
- Rugged metal case provides extra safety and durability
- Illuminated power switch
- \$75,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only) covers connected equipment
- Lifetime product warranty

Specifications

OVERVIEW	
Intended Application	Home/Office
SYSTEM OVERVIEW	
Voltage compatibility	120V AC
Frequency compatibility	50/60 Hz
OUTPUT	
Output volt amp capacity (amps)	15
Output watts	1800
Outlet quantity / type	6 NEMA 5-15R
Outlet orientation	Single row of outlets
Overload protection	15A resettable combo switch / circuit breaker
Transformer accommodation	Supports 2 large transformers without covering adjacent outlets
INPUT	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	15 ft.
Input cord length (m)	4.5
Recommended Electrical Service	120V (110-125V)
LEDS ALARMS & SWITCHES	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
Switches	Combination AC circuit breaker and 2 position on/off power switch
SURGE / NOISE SUPPRESSION	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	1208 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 20dB
DATALINE SURGE SUPPRESSION	
Telephone/DSL Protection	Yes
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	No
Network (Ethernet) Protection	No

PHYSICAL	
Shipping weight (lbs)	2.5
Shipping weight (kg)	1.1
Shipping Dimensions (HWD/in)	2.25 x 15 x 6
Shipping Dimensions (HWD/cm)	5.7 x 38.1 x 15.2
Unit weight (lbs)	1.8
Unit weight (kg)	.8
Unit Dimensions (HWD/in)	1.5 x 12.25 x 2.25
Unit Dimensions (HWD/cm)	3.8 x 31.1 x 5.7
Material of construction	Metal
Form factors supported	Supports floor / wall / desktop placement
Integrated keyhole mounting tabs	Keyhole slots enable mounting to a variety of surfaces
Receptacle Color	Light Gray
AC line cord color	Black
Style	Strip
CERTIFICATIONS	
Additional International Approvals	Complies with RoHS (Restriction of Hazardous Substances Directive)
UL1449 1998 Rev. (AC Suppression)	UL1449
UL1363 (Power Tap)	UL1363
FCC Part 68 (Communications)	FCC Part 68
cUL / CSA (Canada)	cUL
Approvals	Exceeds IEEE 587 category A&B specifications
WARRANTY	
Product Warranty Period	Lifetime
Connected Equipment Coverage	\$75,000

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=3295.