



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: TLP606

### Protect It! Surge Suppressor



#### Highlights

- 6 outlet / 6-ft. cord
- 750 joule rating
- \$20,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

#### Description

Tripp Lite's TLP606 offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. Built-in AC surge suppression shields connected equipment from damage and performance problems due to transient surges. TLP606 offers 6 total outlets, 6 foot cord and diagnostic LED to warn of suppressor damage. AC suppression rated at 750 joules shields equipment from surges and line noise. Attractive white suppressor housing with keyhole mounting tabs offer convenient protection of desktop computer equipment and accessories. \$20,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 6 NEMA5-15R/6-ft. AC line cord

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/750 joules/330V UL1449

#### Applications

- Ideal for any desktop, network or home computing application requiring AC line protection

#### Package Includes

- TLP606 surge suppressor
- Instruction manual with warranty information

#### Features

- 6 outlets
- 6-ft. cord
- Surge suppression rating: 750 joules
- EMI/RFI noise filtering
- 15 amp resettable circuit breaker
- Green protection LED
- Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression
- Can accommodate 1 large transformer plug without covering remaining outlets, 3 total transformers

- Keyhole support for wall mounting
- Lighted power switch
- \$20,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)
- Lifetime product warranty

## Specifications

| OVERVIEW                        |                                                                                                                    |
|---------------------------------|--------------------------------------------------------------------------------------------------------------------|
| Intended Application            | Home/Office                                                                                                        |
| SYSTEM OVERVIEW                 |                                                                                                                    |
| Voltage compatibility           | 120 V AC                                                                                                           |
| Frequency compatibility         | 50/60 Hz                                                                                                           |
| OUTPUT                          |                                                                                                                    |
| Output volt amp capacity (amps) | 15                                                                                                                 |
| Output watts                    | 1800                                                                                                               |
| Outlet quantity / type          | 6 NEMA 5-15R                                                                                                       |
| Outlet orientation              | Single row of 6 outlets                                                                                            |
| Overload protection             | 15A resettable illuminated combo switch / circuit breaker                                                          |
| Transformer accommodation       | Supports 1 large transformer plug accessory without covering remaining outlets, accepts up to 3 transformers total |
| INPUT                           |                                                                                                                    |
| Input connection type           | NEMA 5-15P                                                                                                         |
| Input cord gauge, type          | 14 gauge, SJT                                                                                                      |
| Input cord length (ft.)         | 6 ft.                                                                                                              |
| Input cord length (m)           | 1.8                                                                                                                |
| Recommended Electrical Service  | 120V (110-125V)                                                                                                    |
| LEDS ALARMS & SWITCHES          |                                                                                                                    |
| Diagnostic LEDs                 | Built-in LED confirms suppressor "protection present" (green) status                                               |
| Switches                        | Combination AC circuit breaker and 2 position red illuminated on/off power switch                                  |
| SURGE / NOISE SUPPRESSION       |                                                                                                                    |
| Protection modes                | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                                 |
| AC suppression joule rating     | 750 joules                                                                                                         |
| Clamping voltage (RMS)          | 150V                                                                                                               |
| AC suppression response time    | < 1 ns                                                                                                             |
| UL1499 let through rating       | 330V - UL Verified                                                                                                 |
| DATALINE SURGE SUPPRESSION      |                                                                                                                    |
| Telephone/DSL Protection        | No                                                                                                                 |
| Cable (Coax) Protection         | No                                                                                                                 |
| Network (Ethernet) Protection   | No                                                                                                                 |
| PHYSICAL                        |                                                                                                                    |
| Shipping weight (lbs)           | 1                                                                                                                  |
| Shipping weight (kg)            | 0.5                                                                                                                |
| Shipping Dimensions (HWD/in)    | 13 x 4.75 x 1.9                                                                                                    |

|                                          |                                              |
|------------------------------------------|----------------------------------------------|
| <b>Shipping Dimensions (HWD/cm)</b>      | 33 x 12.1 x 4.8                              |
| <b>Unit weight (lbs)</b>                 | 0.8                                          |
| <b>Unit weight (kg)</b>                  | 0.4                                          |
| <b>Unit Dimensions (HWD/in)</b>          | 10.5 x 1.5 x 1.5                             |
| <b>Unit Dimensions (HWD/cm)</b>          | 26.7 x 3.8 x 3.8                             |
| <b>Material of construction</b>          | Plastic                                      |
| <b>Integrated keyhole mounting tabs</b>  | Keyhole mounting tabs enable wall mounting   |
| <b>AC line cord color</b>                | Gray                                         |
| <b>Style</b>                             | Strip                                        |
| <b>CERTIFICATIONS</b>                    |                                              |
| <b>UL1449 1998 Rev. (AC Suppression)</b> | UL1449                                       |
| <b>UL1363 (Power Tap)</b>                | UL1363                                       |
| <b>cUL / CSA (Canada)</b>                | cUL                                          |
| <b>Approvals</b>                         | Exceeds IEEE 587 category A&B specifications |
| <b>WARRANTY</b>                          |                                              |
| <b>Product Warranty Period</b>           | Lifetime                                     |
| <b>Connected Equipment Coverage</b>      | \$20,000                                     |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2632](http://www.tripplite.com/en/products/model.cfm?txtModelID=2632).