



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: TLP808TELV

### Protect It! Surge Suppressor



### Highlights

- 8 outlets / 8-ft. cord
- 3500 joule rating
- Coaxial surge protection
- Modem/fax surge protection
- \$150,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)

### Description

Tripp Lite's TLP808TELV surge suppressor has 8 outlets, an 8-ft. cord with a space-saving right-angle plug, and diagnostic LEDs. The unit has a surge suppression rating of 3500 joules to handle the strongest surges. Built-in RJ11 jacks prevent surges from damaging your modem/fax/phone equipment. Built-in Type F coax jacks prevent surges from damaging your cable/satellite equipment. \$150,000 [Ultimate Lifetime Insurance](#) (USA & Canada only).

### Applications

- Ideal for home computers, TV/VCR/DVD players, stereos and other important electrical equipment

### Package Includes

- TLP808TEL
- 6-ft. telephone cord
- Instruction manual with warranty information

### Features

- 8 outlets with integrated child safety covers; charcoal gray housing
- 8-ft. cord with space-saving right-angle plug
- Built-in RJ11 jacks (1 in/2 out) prevent surges from damaging your modem/fax/phone equipment; 6-ft. telephone cord included
- Built-in Type F coax jacks prevent surges from damaging your cable/satellite equipment; 6-ft. coax cable included
- Surge suppression rating: 3500 joules
- EMI/RFI noise filtering
- Can accommodate up to 3 transformers without blocking remaining outlets
- \$150,000 [Ultimate Lifetime Insurance](#) (USA & Canada only)
- Diagnostic LEDs indicate protection present & ground present
- Audible alarm notifies user when the unit is damaged and needs to be replaced
- Keyhole supports for wall mounting
- Lighted power switch
- Lifetime product warranty

### Specifications

<b>OVERVIEW</b>	
Intended Application	Home/Office, Audio/Video
<b>SYSTEM OVERVIEW</b>	
Voltage compatibility	120 VAC
Frequency compatibility	50/60 Hz
<b>OUTPUT</b>	
Output volt amp capacity (amps)	15
Output watts	1800
Outlet quantity / type	8 NEMA 5-15R
Outlet orientation	Single row of 5, plus a second row of 3 for transformer accommodation
Outlet safety covers	Includes built-in sliding outlet safety covers
Transformer accommodation	Supports 3 large transformer plug accessories without covering remaining outlets, accepts up to 6 transformers total
<b>INPUT</b>	
Input connection type	NEMA 5-15P
Input cord gauge, type	14 gauge, SJT
Input cord length (ft.)	8 ft.
Input cord length (m)	2.4
Recommended Electrical Service	120V (110-125V)
Input plug features	Space-saving right angle input plug
<b>LEDS ALARMS &amp; SWITCHES</b>	
Diagnostic LEDs	Built-in LEDs confirm suppressor "protection present" (green) and "grounded" (red) status
Alarms	Audible alarm sounds to indicate damage to suppression components
Switches	Combination AC circuit breaker and 2 position red illuminated on/off power switch
<b>SURGE / NOISE SUPPRESSION</b>	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression
AC suppression joule rating	3500 joules
Clamping voltage (RMS)	150V
AC suppression response time	< 1 ns
UL1499 let through rating	330V - UL Verified
EMI / RFI filtering	Up to 40 dB
<b>DATALINE SURGE SUPPRESSION</b>	
Telephone/DSL Protection	Yes
Telephone/DSL Protection Details	1 line
Cable (Coax) Protection	Yes
Cable (Coax) Protection Details	1 line
Network (Ethernet) Protection	No
<b>PHYSICAL</b>	
Shipping weight (lbs)	2.5
Shipping weight (kg)	1.1

<b>Shipping Dimensions (HWD/in)</b>	2.5 x 14.75 x 8.75
<b>Shipping Dimensions (HWD/cm)</b>	6.4 x 37.5 x 22.2
<b>Unit weight (lbs)</b>	1.6
<b>Unit weight (kg)</b>	0.7
<b>Unit Dimensions (HWD/in)</b>	1.6 x 9.25 x 4.25
<b>Unit Dimensions (HWD/cm)</b>	4.1 x 23.5 x 10.8
<b>Material of construction</b>	Plastic
<b>Integrated keyhole mounting tabs</b>	Keyhole mounting tabs enable wall mounting
<b>AC line cord color</b>	Gray
<b>Style</b>	Strip
<b>SPECIAL FEATURES</b>	
<b>Additional Information</b>	Pair of phone line output jacks serve as a line splitter to enable the protection of two devices sharing a single dialup phone line
<b>CERTIFICATIONS</b>	
<b>UL1449 1998 Rev. (AC Suppression)</b>	UL1449
<b>UL1363 (Power Tap)</b>	UL1363
<b>UL497A (Communications)</b>	UL497A
<b>FCC Part 68 (Communications)</b>	FCC Part 68
<b>cUL / CSA (Canada)</b>	cUL
<b>Industry Canada (Communications)</b>	Industry Canada
<b>Approvals</b>	Exceeds IEEE 587 category A&B specifications
<b>WARRANTY</b>	
<b>Product Warranty Period</b>	Lifetime
<b>Connected Equipment Coverage</b>	\$150,000
<b>Data Recovery Warranty</b>	Included

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=142](http://www.tripplite.com/en/products/model.cfm?txtModelID=142).