



Model #: 1010HT

UPC: 649532010103

MSRP: \$69.99



The CyberPower 1010HT Home Theater Surge Suppressor is a high performance audio/video surge protector, offering 4200 Joules and 10 outlets of MOV protection. Exclusive Signal Scrubber™ is a line conditioning technology that independently filters audio/video signals and delivers a true experience for high-end audio/video enthusiasts. RJ-11 ports protect phone/fax/modem/DSL equipment; RJ-45 ports protect network connected equipment such as computers, hubs, and routers; 3 (three) RG-6 gold-plated coax ports guard cable modems, cable TV lines, and DSS equipment. All 10 outlets are “transistor-friendly,” which allow for the connection of bulky DC transformers that are found on many popular electronic devices. EMI/RFI filtering blocks electro-magnetic and radio interferences from entering your equipment, and MOV technology ensures the protection off all connected electronics, and the surge suppressor itself. CyberPower fully stands behind its products with a lifetime product warranty and Connected Equipment Guarantee of \$250,000.

- Signal Scrubber™ - Audio and video signals are isolated, and then independently filtered to guard against component cross-contamination and improve signal quality. The result is pure sound with expansive dynamic range, precise picture quality, and enhanced color depth.
- MOV (Metal Oxide Varistor) - MOV technology allows normal current to pass through the device, while diverting any surge/spikes through the ground circuit. This safely protects all connected electronics along with the surge suppressor itself.
- Transformer-spaced Outlets - Widely spaced outlets allow you to conveniently add large transformer-based plugs without compromising the utility of other outlets.
- EMI/RFI Shielding - Provides shielding against electromagnetic interference & radio frequency signals. Most commonly, this is used to prevent line noise or “humming” that occurs over telephone lines or stereo electronics.
- ISO & Safety Certifications - All CyberPower’s manufacturing facilities are ISO-9001 Quality Tested. Our products are also UL Listed and CSA Certified.
- Keyhole Mounting Slots – Convenient mounting slots are located on the back on the surge suppressor.
- Sturdy ABS Case – Constructed of impact-resistant composite material for maximum durability.

Technical Specifications

General	
Model #	1010HT
Input	
Voltage	110/120V Nominal
Plug Type	NEMA 5-15P
Plug Style	Right-angle
Cord Length	7 ft
Output	
Outlets - Total	10
Outlets - Widely Spaced	10 x NEMA 5-15R
Outlets - Normal Spaced	None
Surge Protection and Filtering	
Surge Suppression	4200 Joules
Phone Protection (RJ11)	One-in/Two-out
Ethernet Protection (RJ45)	One-in/One-out
Coax Protection (RG6)	Three-in/Three-Out
Maximum Surge Current	150,000 Amps
Maximum Surge Current H-N	110,000 Amps
Maximum Surge Current H-G	20,000 Amps
Maximum Surge Current N-G	20,000 Amps
Maximum Surge Voltage	6,000V
Clamping Voltage	330 V
Response Time	<1 ns
EMI/RFI Filtration	EMI/RFI 100KHz to 100MHz
Attenuation	Up to 50dB
Indicators	
Indicator Lights	Power (Red); Surge (Red); Ground (Green)
Physical	
Dimensions (WxHxD)	14.5" x 4" x 2.25"
Weight	3.35 lbs.
Color	Silver
Warranty	
Product Warranty	Lifetime
Connected Equipment Guarantee	Lifetime
CEG Amount	\$250,000