

Sky Rose FL-200

USER MANUAL





F8000010


Catalogue



I	Warning	1
II	Statement	1
III	Safety Precautions	1
IV	Technology Parameter	2
V	Warning for Replace Lam	3
VI	Warning for Operation	4
VII	Sketch map of Connection	4
VIII	Menu Function	5
IX	Channels Control	6

CAUTION ! Avoid looking directly into the light source
EYEDAMAGES ! (meant especially for epileptics) !

 12m  **CAUTION! BE CAREFUL OF FIRE**
PLEASE FAR FROM TINDER 12M

WARNING !
MINIMUM DISTANCE OF INFLAMMABLE
MATERIALS FROM THE SURFACE 12M.
MAXIMUM TEMPERATURE OF THE
EXTERNAL SURFACE 100°C.

 **Ta=35°C Tc=100°C** 

Warning

To reduce the risk of electrical shock or fire, do not expose this unit to rain or moisture.

Do not spill water or other liquids into or on to your unit.

During long periods of non-use, disconnect the unit's main power.

It should be installed in a well-ventilated place, at a distance of 50 centimeters or more with the walls.

At the same time, please check if the fan and ventilation holes are unobstructed.

Statement

The product has perfect performance and integrity packing. All users should be strictly comply with the warning and operating instructions as stated. Or we aren't in charge of any result by misusing. Any damage resulting by misuse is not within the company's warranty. Any fault or problem caused by Note: All information is subject to change without prior notice.

Safety Precautions

In order to guarantee the product's life, please don't put in the damp places or even the environment over 40degrees.

Always mount this unit in safe and stable matter.

The qualified professionals are allowed to carry out the lamp installation, operation and maintenance, but they must guarantee to operate in strict accordance with the instructions referred to.

Using lamp, the change rate of Power voltage should be within +10%, If the voltage is too high, it will shorten the light's life; if it's not enough, the lamp will be dark.

Please restart it after turning off light for 20 minutes until full-cooling. Frequent switching will reduce the life span of lamps and bulbs; intermittent use will improve the life of bulbs and lamps.

In order to make sure the product is used well, please read the Manual carefully

Production

We are introducing the new Sky Rose FL-2000, with very good affordable prices. And this Sky Rose FL-2000 is suitable for outdoor lighting purposes, these products are provided with a movable head that supports in light reaching a distant area. We provide these lights with the adjustable angle, and with multi Beam lighting.

Features:

Energy saving design
Excellent illumination
Longer service life
User Manual

Specifications:

Outdoor Sky Rose FL-2000 (2000W-7000W)
1.Light source: XHA2-7kW
2.Be distance :2-6HP
3.Waterproof: IP44

Technical specification:

Voltage: AC220W 50-60HZ
Working currency: 11 A
Light source: XHA2-7kW
Color Temperature: 6000K
Cover: Aluminum cover with insulated paint coat
Waterproof: IP44
Chassis: Alloy external painting
Beam Angle: 9degree
Extend the distance: 3-6HP
The level of degree: 90-120 degrees
Horizontal: 110 degree
Vertical: 40 °
Packing Size: 73x85x123cm
Weight: 73kg