

Shenzhen Golden Security Technology Co.,Lt: 由 Foxit PDF Editor 编辑

Add:8 floor, Huashenghui General Building, Jinhai Road, Xixiang St., Bao'an District, Shenzhen. Guanddor

版权所有 (c) by Foxit Software Company, 2003 - 2009 仅用于评估。

Tel: +86-(0)755-23080566 Fax: +86-(0)755--25872283 Mobile: 8618620365904

Website: www.cameralarms.com Alibaba web: http://alarm-camera.en.alibaba.com Global sources : http://www.globalsources.com/camera-alarm.co

E-mail: iris@cameralarms.com MSN:iris.security@hotmail.com skype:liris.security



Security Products, 2L06, AsiaWorld-Expo • Hong Kong October 12-15, 2013



Quotation **Picture** Model Number: GS-G110E GSM alarm system (900/1800,850/1900mhz) **Promotion** 1. 8 wired and 100 wireless defense zones; GSM sim card network, quad-band, 850/900/1800/1900mhz 2.LCD screen with time clock display 3, Voice prompt for all operations, English/Spanish/French for choice 4,store 6 phone numbers: when it is alarming, alarm system will make alarm call to these numbers automatically; 13 6,Can store 3 SMS numbers: when alarming, system will send alarming SMS message automatically; 7,10-second voice message recording; Standard packing list 8.comfortable keypad with cover preventing kids to press. One main unit 9,Users can make calls by using keypad on alarm panel, work like a telephone; One wireless door/window sensor 10, One-key-control function: Away Arm, Home Arm, Remote Arm; One wireless PIR sensor Two remote controllers 11,SOS, fire, gas, door, hall, window, balcony, and boundary places alarm; One wired siren One AC adapter 12,2-way intercom 13, Wireless coding: easy to add additional wireless accessories; 14,Built-in AAA NI-HI rechargeable battery: make alarm sounds when power off; 15, Comply with CCC safety standard and GB12663-2001 national standard. Price (USD) Sample: FOB Shenzhen \$56 10 to 100sets:\$53 101 to 200sets:\$49

		Quotation		1			
Piceture	Model Number:GS-G180E	GSM +PSTN alarm system (900	<mark>/1800</mark> 由 Foxit PDF Editor 編辑				
Golden Security	1.Touch keypad; Large LCD display	r; Internal antenna	版权所有 (c) by Foxit Software (仅用于评估。	.ompany, 2003 - 2009			
SCHOOL PORT AND A STATE OF THE	2.GSM+PSTN dual network.						
2 3 0. 8 0. 1 4 5 5 8 8 9 0 0	3. 30 wireless zones + 8 wired zones	s					
	4.Supports 15s' monitoring via phor	ne call					
	5.Alarm SMS include alarm zone and sensors name						
	6.Support wireless "ding-dong" doorbell function						
	7.Alarm priority, Reset, activate and disable alarm call and alarm SMS						
Standard Package: One alarm host	8. Work with Ademco Contact ID protocol and supports uploading to monitoring center (alarm/arm information, status information, AC power off and recover, host and sensor low voltage notice)						
One wireless door/window magnetic contact One PIR motion sensor	9. Arm\ Disarm the system in 5 ways: remote SMS message, remote phone call, Main Host (Keypad), Wireless Keypad (optional), Keychain Remotes. (PSTN alarm don't support SMS)						
Two remote controllers One AC adapter	10.SMS Message of host and sensor in low battery or energy will be sent to preset phone No.						
One English user manual Nice package:	11. Multi-languages version for choice: English/French/German/Spanish/Italian/Russian/Danish/Dutch/Turkish/ Swedish and all languages available if you can help in translation						
1 2 B o. A .8	Advantages: 1.touch keypad 4.large LCD	2. internal antenna and nice look. 5. ABS fire-proof material	3.Many language version available 6. GSM+PSTN dual-network				
7-890,%0.	Price(USD)Sample:FOB ShenZhen\$	-					
600	20 to 100 sets:\$81						
10	101 to 200sets:\$78						

		Quota	ation	La company to the second		
Picture	Model Number:GS-G81	GSM alarm system	(900/1800,850/1900mhz)	由 Foxit PDF Editor 编辑		
	1.Keypad , blue backlight	s; blue LCD displays Da	ate, Day of the week, Time and	版权所有 (c) by Foxit Software Company, 2003 - 2009 c 仅用于评估。		
www.cameralarms.com	2. Concise icons menu . S	Suitable for every marke	et all over the world.			
			alarm and SMS alarm at the saype. Automatically switch to G	ame time, SM dialing when telephone line is cut.		
1			4 sensors) and 1 dedicated zon ds per zone). Supports 2 wired			
5. 6 phone numbers can be preset and will dial in sequence. Every mobile phone number can be set for phone call alarm or SMS alarm.						
	6. Intelligent logic analysi	s technology, correspo	nding zone number can be dis	played on LCD screen.		
	7.Arm\ Disarm the system by 5 ways: SMS, Main Host (Keypad), Wireless Keypad (optional), Keychain Remotes, and phone calls. (PSTN alarm don't support SMS)					
	8.Work in AC\DC power, 1	I10V TO 240 v outside բ	power and DC12V backup batte	ery. Host low-voltage alerts.		
1* main unit 1* PIR motion sensor	9.Door\window status sel	f-check and "Ding Don	g" doorbell can be completed a	as optional functions.		
1* indoor siren 1* door magnetic sensor	10.Support CID uploading to CMS (Center monitoring Station)					
2* remote controllers	11. Built-in Lithium backu low power,no external po	phone cable cut, no SIM card, alarm host				
	10 to 50sets : \$50					
	51 to 200 sets : \$49					

		Quotation	de uppertu Add			
Picture	Model Number:GS-G60E	GSM alarm system	由 Foxit PDF Editor 编辑 整切系方 (-) by Soviet Software Society 2002 2002			
Ficture	Main functions:	Gow diami system	版权所有 (c) by Foxit Software Company, 2003 - 2009 仅用于评估。			
	1.An advanced and reliable comr	munication technology, dialing alarm				
	2.8 wired, 99 wireless defense zo	nes				
	3.Remote control intelligent code	e, up to 5 wireless remote controls				
	4.LCD display, built-in calendar of	clock, operates easily				
(2 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	5.Full voice prompts, installation	setting and daily operation are more easi	ily			
CONTRACTOR	6.Arm and disarm, and siren on/o	off are could be controlled by SMS instruc	ction			
	7.SMS prompt of low power					
	8.SMS prompt of AC power broke	en and recover				
	9.Built-in intercom speaker, can	achieve duplex intercom function				
	14.Up to 2 SMS numbers to notify	y you of abnormal conditions				
	15.10 seconds artificially recordi	ng message				
	10.Built-in wireless transmitter m	nodule, wireless siren and smart home sys	stem can be linked			
Standard packing list	11.Preset 2 groups timing arm ar	nd disarm time				
One main unit	12.Calls out up to 6 phone numb	ers to notify you of abnormal conditions				
One wireless door sensor	13.Call out up to 2 phone numbers to notify the receiving alarm center					
	14.Up to 2 SMS numbers to notify	y you of abnormal conditions				
One wireless PIR sensor	15.10 seconds artificially recordi	ng message				
Two remote controllers	16.Built-in digital voice, voice bro	padcast alarm situation automatically				
One White siren	18.Multiple defense zones includ	ling instant, delay, 24 hours, bypass				
One AC adapter	17.All arm and disarm function c	ould be realized by one key				
	GS-G60E					
One English user manual	19.Wireless coding: adding new	accessories convenient, safe and efficien	ıt			
	Price: Sample(USD): FOB Shenzi	nen \$68				
	10 to 50sets :\$63					
	51 to 200sets:\$59					

		Quotation			1			
				由 Foxit PDF Editor 编辑				
Picture	Model Number:GS-G82	GSM / PSTN/ GSM+PSTN alarm s	ystem (three vers	版权所有 (c) by Foxit Software C	ompany, 2003 - 2009			
	1. Touch Screen, white cold	or , internal		仅用于评估。	I			
COLORS SCURITY 093:041 123:03 20 1 2 3 0.6	2. LCD Screen displays Dat							
7 8 9 sert		3. 29 wireless zones (Each zone supports up to 4 sensors) and 2 dedicated zones for remotes (Supports up to 4 remotes or wireless keypads per zone)						
	4. Intelligent logic analysis	technology, corresponding zone and	d sensor name ca	n be displayed.				
	5. Can dial up to 5 phone n	umbers in sequence						
	6. Support seperated wirele button.	ess doorbell, and will sound chord "	Ding-Dong" from	alarm hot panel when you press doorbell				
	ain Remotes, or even remotely by							
	8. Available in both AC\DC with Low-voltage Indicators							
	9. Learning sensors to alarm host, very easy operation.							
	10. Store up to 100 alarm records(alarm history) and 100 arm\disarm records(arm/disarm operation history)							
	11. Support CID uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function							
Standard packing list	12. Non-volatile chip, inforr	mation stored automatically when of	f power					
One alarm host	13. Check door\window sta sound fast "bi bi bi")	atus automatically (This is when the	system is disarme	ed only, if a door is opened, it will				
One intelligent wireless door/window	14. AC FAILURE NOTIFICA	TION to CID Center monitoring station	on(Optional func	tion)				
magnetic contact	15. Support wireless "ding-	-dong" doorbell function						
One intelligent wireless PIR sensor								
One indoor siren	Price (USD) Sample: FOB	Shenzhen \$97						
Two remote controllers	10 to 50sets : \$95							
One English user manual	51 to 200 sets : \$91							

		Quotatio	n	la a company to the second				
Picture	Model Number:GS-G80AE	GSM alarm system	(900/1800,850/1900mhz)	由 Foxit PDF Editor 编辑	2002 2000			
	1. Touch Screen		(,	版权所有 (c) by Foxit Software Com 仅用于评估。	ipany, 2003 - 2009			
	2. LCD Screen displays Date	, Day of the week, Time,	and current Armed Status					
11	3. Supported Languages: Sir	mple Chinese\ Traditiona	al Chinese\ English\ German	\ French\ Russian\Danish and more.				
	4. 29 wireless zones (Each z remotes or wireless keypads		nsors) and 2 dedicated zone	es for remotes (Supports up to 4				
10.03 MON CO 00 M M	5. 8 more wired zones(Option	nal), <mark>add</mark> US \$2.5 cost						
	6. Intelligent logic analysis to	echnology, correspondii	ng zone and sensor name ca	an be displayed.				
	7. Support seperated wireles button.	s doorbell, and will sou	nd chord "Ding-Dong" from	alarm hot panel when you press doorbell				
	8. Can dial up to 5 phone nu	mbers in sequence						
	9. Record up to a 10 second	greeting for the auto-dia	aler, Then play the greeting l	back.				
	10. Arm\ Disarm the system by: SMS, Main Host(Keypad), Wireless Keypad, Keychain Remotes, or even remotely by							
	phones. (PSTN alarm don't support SMS)							
	4	11. Available in both AC\DC with Low-voltage Indicators						
Standard packing list	12. Learning sensors to alarm host, very easy operation.							
One main unit	13. Store up to 100 alarm records(alarm history) and 100 arm\disarm records(arm/disarm operation history)							
One wireless door sensor	14. Support CID uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function							
One wireless PIR sensor	15. Non-volatile chip, inform	15. Non-volatile chip, information stored automatically when off power						
Two remote controllers	16. Check door\window status automatically (This is when the system is disarmed only, if a door is opened, it will sound fast "bi bi bi")							
One strobe siren	17. AC FAILURE NOTIFICATI	ON to CID Center monit	oring station(Optional fund	ction)				
One AC adapter	18. Support wireless "ding-dong" doorbell function (Optional)							
One English user manual	GSM frequency:							
White version	GS-G80AE GSM900/1800MHZ							
	GS-G80AEA GSM850/1900MHZ							
	Price (USD) Sample: FOB Shen	zhen \$89						
0.52 m/m (0.52 5)	10 to 50sets : \$88							
	51 to 200 sets : \$85							
	Note:GS-G80AE has 868mhz vei	rsion						

		Quotation		1				
Picture	Model Number:GS-G80CE	GSM alarm system	(900/1800,850/1900	由 Foxit PDF Editor 编辑 版权所有 (c) by Foxit Software Company, 2003 - :	2009			
	1.Touch keypad, blue backligh				2003			
	2. Concise icons guided LCD display. Suitable for every market all over the world.							
6	3. 2 /4 Band GSM net-work. Su alarm event type. Automatical			te time, SMS includes zone number and				
	-	ne supports up to 4 sensor e). Supports 2 wired zones	-	s for remotes (Supports up to 10 remotes				
1 2 3 4	5. Can preset up to 6 phone no SMS alarm.	umbers and dial in sequend	ce. Every mobile phone i	number can be set for phone call alarm or				
4 5 6 8 7 8 9 SET CL. S. CEAN ENT	6. Intelligent logic analysis ted	chnology, corresponding zo	one number can be displ	ayed on LCD screen.				
	7.Record up to a 10 second gi	reeting for phone call alarm	s which can be heard w	hen answering the alarm call.				
	8.Arm\ Disarm the system by sphone calls. (PSTN alarm dor		eypad), Wireless Keypad	(optional), Keychain Remotes, and				
	9.Available in AC\DC, Low-vol	tage alerts.						
	10. "One-Key" arm, studies sensors to alarm host, very easy operation.							
	11. Non-volatile chip, informat	tion stored automatically w	hen off power.					
	12.Door\window status self-check and "Ding Dong" doorbell can be completed as optional functions.							
Standard packing list	13.8 zone electrical appliance control and 8 groups of scene control can be completed as optional functions.							
One main unit	14.Support CID uploading to 0	CMS (Center monitoring Sta	ation)					
One wireless door/window magnetic sensor	15.Disconnection alarm, auto	priority to occupy the telep	hone and monitoring fu	nction to hear what is happening.				
One wireless PIR sensor	16. Built-in Lithium backup ba low power,no external power			phone cable cut, no SIM card, alarm host				
One wireless strobe siren								
Two remote controllers	Price (USD) Sample: FOB She	enzhen \$85						
	10 to 50sets : \$82							
	51 to 200 sets : \$78							

		Quotatio	n	de consein Add				
Picture	Model Number:GS-G70E	GSM alarm system	(900/1800,850/1900mh	由 Foxit PDF Editor 编辑 版权所有 (c) by Foxit Software Cor	mpany 2003 - 2000			
11	1. Color LCD screen, keypad with blue light 仅用于评估。							
	2Support ADEMCO Conta	2Support ADEMCO Contact ID protocol uploading to CMS(Center monitoring Station)						
	3. Maximum 30 wireless zones, support 8 more wired zones, add US \$2.5 cost .							
		4. LCD display with calender, available in English/Chinese/Germany/Russian/French and Japanese etc. Non-volatile chip, information stored automatically when power off.						
	5. One-key arm operation,V	Vith learning code progran	nme method,it's easy to ope	rate				
	6.Preset 5 Telephone & 5 S	SMS number to inform alar	m					
	7. Switch to Backup recha	rgeable battery when the p	oower is failure or cut by intr	ruder.				
Standard packing list	8. 5 methods Arm/Disarm: SMS	Remote Controller, Host K	eypad, Remote Keypad(option	ons),Telephone/Mobile phone and GSM				
One main unit	9. Internal & external anten	na for your options						
One wireless door sensor	10. It will use GSM and has	capability for <mark>land line</mark> wh	ere GSM is not possible					
One wireless PIR sensor	11. External power failure a	11. External power failure and external power return informed via SMS						
Two remote controllers	12. 2 ²⁰ wireless address encode reduce the rate of same code greatly.							
One Wireless strobe siren	13. Learning code wireless	13. Learning code wireless accessories.						
One AC adapter	14. SMS control & program	14. SMS control & program						
One English user manual	15. SMS modifies wireless	zones name.						
Specification of main unit:	16. Internal MIC or external	high sensitivity MIC (option	onal)					
Output power: DC12V	17. Working with monitorin	g center, such as police s	tation					
Input power: AC110V to 220V,	220V,5 GSM frequency:							
Working hours of standby	GS-G70E GSM900/1800MHZ							
More than 15 hours	GS-G70EA GSM850/1900M	IHZ						
Wireless frequency for above a	Price (USD) Sample: FOB Shenzhen \$85							
315MHZ/433MHZ	10 to 50sets : \$83							
Note:GS-G70E has 868mhz version	51 to 200 sets : \$80							

uotation				
曲 Foxit PDF Editor 編辑 版权所有 (c) by Foxit Software Company, 2003 - 2009				
仅用于评估■				
h off mode, Intelligent mode and Emergency mode				
ctor, gas detector and other 24h working sensors.				
user at home. The zone for put PIR motion sensor, door sensor which user e sensor in intelligent zone be triggered, it will not alarming.				
receiving alarm phone call				
ng.				
call.				
ntrol solely.				
9*.Anti-phone line cut alarm function.				
10. Switch to Backup rechargeable battery automatically when power is failure or cut by intruder.				
11.Support doorbell functions: Detector will be Door Bell when disarmed				
12.With learning code programme method,it's easy to operate				
receiving alarm phone call ng. call. ntrol solely. be Door Bell when disarmed				

		Quotation	In a second to MAIR				
- 11.			曲 Foxit PDF Editor 編輯				
Picture	Model Number:GS-T08E	PSTN alarm system	版权所有 (c) by Foxit Software Company, 2003 - 2009				
	1,100 wireless and 8 wire defense zones	s.	仅用于评估。				
	2,Blue backlighting graphic display.						
(X (3,6 groups of voice alarm phones (mobi	ile phone), and 2 groups of phones in ala	arm receipt center.				
C C C C C	4,Built-in perpetual calendar and clock;	auto record alarm history by time seque	ence.				
	5,Message recording playback: human	recording, synchronous playback for rec	cording effect in audition.				
	6,More defense modes: remote defense	, keypad defense, and non-local remote	defense by telephone; stay-in defense, timing defense, and				
	7,Programming of defense zone type: al 24-hour and bypass alarm modes.	Il zones could be programmed via keypa	d for immediate, delayed,				
	8,Alarm Position Programming: Intellige alarm, window alarm, balcony alarm, an		alarm, fire alarm, gas leak, magnetic contact alarm, hall				
	9,Timing arm and disarm: console featu	ires automatic timing arm and disarm.					
	10,Two arm models:						
Technical parameters:	1)home alarm model:console music a	1)home alarm model:console music and voice alarm, external siren mute					
a)Input Voltage: DC12V 500mA	2) home away arm model:console voice alarm, loud external siren alarm.						
b)Standby Current: 50mA	11,Password Recovery: Whether the console is in defense or withdrawal, the lost password can be recovered.						
c)Alarm Current: 450mA max	12,Intelligent learning code: intelligent learning code, newly added with detector which is prompt and efficient, and convenient						
e)Output current: DC12V 150mA	13,Event Log Query: console automatic withdrawal and alarm events.	ally records 45 pieces of all information	concerning defense,				
f)Wireless Frequency: 315/433MHz	14,Line priority alarm: the console will on matter incoming or outgoing ca		arm in case of the alarm during ongoing call,				
g)Coding Method: 2262 IC / 4.7MΩ	15,Phone disconnection detection: auto of telephone lines.	omatic detection and alarm warning in lin	ne disconnection, for anti-sabotage				
h)Alarm noise: 110dB	16,Remote control: through remote phone (cell phone) dial-up, many operations could be realized, like defense, withdrawal and onsite monitoring by the console in the remote control form.						
i)Back-up Battery: AAA 7.2V	17.Console is equipped with battery box, with optional AAA NI-HM rechargeable battery.Console meets 3C safety standards and national standard GB12663-2001						
j)Environment Temperature:	18,Compatible with internationally accepted protocol of alarm receipt center: Ademco Contact ID alarm communication protocol.						
-20℃ ~ +55℃	Price (USD) Sample: FOB Shenzhen \$38						
	10 to 50sets :\$35						
	51 to 200 sets : \$32						

	Quotation			
Picture	Model Number:GS-T01A PSTN alarm system			
	1. LED display, 15 wireless zones, can work with up to 60 wireless sensors (each zone supports up to 4 sensors)			
	2.You can connect wired & wireless PIR sensor, door/window contact, smoke detector, gas leakage detector, glass break sensor, emergency button etc. Each wireless zone can match numberless wireless sensors.			
The state of the s	3. With 13 working LEDs and control keyboard on the mainframe.			
**	4. You can record your voice in the mainframe in advance and will call you or the police and play the voice while alarming.			
	5.Can Auto-dial 6 phone No. while alarming.			
	6.You can call the mainframe at any time and listen what happened in the alarm area,			
	and you can arm/disarm and program the system by control keyboard on the mainframe & phone			
	7Support ADEMCO Contact ID protocol uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function			
	8.With voice reminder & password protection while the system is working.			
	9. Remote monitor and check the alarm zones by phone.			
	10. Arm mode: immediate arm, delayed arm and partial arm.			
	11. Can set the ring times of alarm mainframe. When there is coming call, the mainframe can get through it automatically after checking the preset ring times.			
One package includes:	12. Can choose to set/cancel the alarm function of cutting telephone line.			
One main unit	13. Switch to Backup rechargeable battery automatically when power is failure or cut by intruder.			
One wireless door sensor	11. When the system alarms, it can report and follow up the latest alarm zones.			
One wireless PIR sensor	14. Can send alarm signals to monitoring center through telephone network, such as the police station.			
Two remote controllers				
One strobe siren	Price (USD) Sample: FOB Shenzhen \$45			
One AC adapter	10 to 50sets :\$42			
One English user manual	51 to 200 sets : \$39			
	Note:GS-T01A has 868mhz version			

Quotation					
Picture	Model Number:GS-T01B PSTN alarm system				
	Remark:				
1 2 3 A	The difference between GS-T01A and GS-T01B: GS-T01B has following extra features:				
7 8 9 ser	1) LCD display				
	2) With year/week /time/armed status				
	3) Available to display in the following languages: English, Chinese, German, Russian, French, Japanese etc.				
1* main unit 1* PIR motion sensor 1* indoor siren	4) 30 wireless zones, can work with up to 120 wireless sensors (each zone supports up to 4 sensors)				
1* door magnetic sensor 2* remote controllers	5)Support ADEMCO Contact ID protocol uploading to CMS(Center monitoring Station)				
	All the functions and specification are same except for above				
	Price (USD) Sample: FOB Shenzhen \$60				
	10 to 50sets :\$58				
	51 to 200 sets : \$55				
	Note:GS-T01B has 868mhz version				

		Quotation			
		MMS Alarm System			
Picture	Model Number:GS-M22E	MMS Alarm system	(900/1800,850/1900mhz)		
	*With camera & PIR itself				
	*Can send MMS to your mobile pho	ne.			
	*Can Send picture to your E-mail.				
	*Can match wireless detectors/sens	sors with alarm host by	learning code.		
	*Build-in 2G SD card to store picture	es(In standard package	e,there is no SD card)		
	1. Built-in 300,000 pixels night visio	n digital camera,suitab	le fo night use.		
	2. Support 2G SD card , convenient	for long-term storage	of image evidence.		
	3. Support PIR motion detecting wit	h photo-taking.			
	4. Support SMS, MMS,phone,E-mail to alarm.				
5. Image size is adjustable: QCIF(160×128)、CIF(320×240)、VGA(640×480) 6. Can pre-set arm / disarm time,convenient for user or alarm center to control.					
Technical parameter	8. 16 wireless zones,each can be pr	grammed independent	ly,eg : arm,disarm and 24-hour arm.		
Static Current: 40 mA	9. Can set 5 user phone numbers ,can listen-in when alarming.				
Power Supply: 9-12 V	10.Can set 2 email address: send scene image alarm info to E-mial.				
Support PHASE2/2 & protoco	11.Support GSM / CDMA mobile phone to receive SMS alarm and send SMS commands to control the system.				
Receive Coding: ASK	12.Can send scene color images to mibile phone immediately after alarming .				
Receive Frequency: 315/43 MHz	14.User can remotely listen-in by calling the host.Can hear the voice at the scene .				
Remote Control Distance :30	13.Can capture scene color photos	and send to user by se	ending SMS command.		
Detectors: 16	14.Built-in Li battery, AC-DC shift, a	utomatically recharge			
	15.Password operation ensure the s	security of system.			
	16.Support Real-Time Clock adjustr	nent, SD card image st	ored with time, convenient for inquire.		
	17.Wireless system, no need to set where there is no wired network.	wire and easy to instal	I. Special suitable for garage, storeroom, and other places		
	Price (USD) Sample: FOB Shenzhei	n \$90			
	10 to 50sets :\$87				
	51 to 200 sets : \$82				

	Quotation
Picture	3G Video ALARM SYSTEM Model Number:GS-98A 850/900/1900/2100MHZ
NEW	1. Camera can send alarm messages by SMS, video call, voice call
	2.Max 15 wireless alarm sensors can be added.
	3.Support to record the alarming image to the camera
	4.Wireless remote control: it can arm ,disarm or send emergency alarm
	5.Up to 11 telephone numbers can be pre-stored in the system
	6.Including the intensity detection and infrared lighting functions
	7. Motion detection function within 6m
	8.using high sensitivity MIC, can make calls within 7m.
Standard Paking:	9.you can call the video phone to check the video of monitoring
one alarm host	10.3G standard:WCDMA,Built-in 2GB TF card
one wireless door sensor	Price (USD) Sample: FOB Shenzhen \$119
	5 to 50sets :\$117
	51 to 100sets:\$115
	101 sets to 200 sets:112
Picture	Model Number:GS-98B 850/900/1900/2100MHZ
NEW	1. Camera can send alarm messages by SMS, video call, voice call
	2.Max 15 wireless alarm sensors can be added.
	3.Support to record the alarming image to the camera
	4.Wireless remote control: it can arm ,disarm or send emergency alarm
	5.Up to 11 telephone numbers can be pre-stored in the system
	6.Including the intensity detection and infrared lighting functions
	7. Built-in PIR detection function within 6m
	O union blob consistivity MIC con make calls within 7m
	8.using high sensitivity MIC, can make calls within 7m.
Standard Paking:	9.you can call the video phone to check the video of monitoring
Standard Paking: one alarm host	
	9.you can call the video phone to check the video of monitoring
one alarm host	9.you can call the video phone to check the video of monitoring 10.3G standard:WCDMA,The outer TF card
one alarm host one wireless door sensor	9.you can call the video phone to check the video of monitoring 10.3G standard:WCDMA,The outer TF card Price (USD) Sample: FOB Shenzhen \$112

Quotation			
Picture	Model Number:GS-6828 850/900/1900/2100MHZ		
NEW	1. Camera can send alarm messages by SMS, video call, voice call		
	2.Max 15 wireless alarm sensors can be added.		
	3.Support to record the alarming image to the camera		
	4.Wireless remote control: it can arm ,disarm or send emergency alarm		
	5.Up to 11 telephone numbers can be pre-stored in the system		
	6.Including the intensity detection and infrared lighting functions		
	7. Built-in PIR detection function within 6m		
	8.Built-in MIC and speaker,enables two-way intercom and on-site shouting function		
Standard Paking:	9.you can call the video phone to check the video of monitoring		
one alarm host	10.3G standard:WCDMA		
one wireless door sensor	11.The outer TF card		
two remote controller	12.3G frequency:850/900/1900/2100MHZ		
	Price (USD) Sample: FOB Shenzhen \$129		
	5 to 50sets :\$125		
	51 to 100sets:\$122		
	101 sets to 200 sets:119		