Otodor® Swing Door Opener [For Interior Swing Door Use Only] Applications						
Model		Door type	Market	Application	Do not use for:	
Opener set DM-50 DM-50A* DM-50B*		Interior: up to 42" wide 100 Lbs. Hollow door or Solid door: In-swing & Out-swing Left or Right.	DIY-Retailer, Distributor / Dealer	Medical, Home Health Care, Public Restrooms, Senior homes & Offices.	Commercial, Mall. Front Door, Back door or any Exterior doors.	
DM-100 DM-100A*	T ~	Interior: up to 42" wide 100 Lbs. Hollow door or Solid door: In-swing & Out-swing Left or Right.	DIY-Retailer, Distributor / Dealer	Medical, Home Health Care, Public Restrooms, Senior homes, & Offices.	Commercial, Mall. Front door, Back door or any Exterior doors.	
DM-150 DM-150A* DM-150B*	Electric Strike ES-201 + Transmitter 4B-201 with AC adapter & Hardware	Exterior: up to 42" wide & 100 Lbs. In-swing &	Installers, Builders, Distributors. Note:	Garage swing door, Home front door, Side door, Back door, Medical & Nursing homes, Health Care, Senior homes, & Offices.	Commercial, Mall. Exterior doors with positive pressure and a strong wind factor.	
Optional Ad	cessories	<u> </u>	<u> </u>	<u> </u>	. L	
Model	Description Applications					
4B-201	4 Button transmitter	One transmitter can program up to 4 openers or combination of the garage door openers or lighting controls, (optional modules required) Operate by 12V alkaline battery				
WM-201	2 Button transmitter with wall mount bracket	One transmitter can program up to 2 openers or a combination of the garage door openers and lighting controls, (optional module required) Operate by 12V alkaline battery				
PS-201	Motion sensor	Detects human movement then opens the door, the door will close automatically based on the timer setting Operated by 9V DC battery				
KP-434	KeyPad Transmitter	Keyless remote control. Built-in password to open and close the door automatically Operated by CR-2032 lithium batteries				
MC-201		24V Operation. Holding force is 100 Lbs. Otodor DM-001 can control up to 4 units of MC-201 (= 400 Lbs). Mounting brackets, screws and connection wire with connector included.				
ES-201	Electric Strike	24V Operation. Controlled by Otodor DM-001. Included are the connection wire with connectors. This item only sell to the locksmiths or installers as they have experience and required skills to modify the door frame during installation.				
WB-201	Wall mount transmitter	Wall mount transmitter, built in with battery Operated by 12V alkaline battery				
UP-500	UPS power back up	120VAC input / output (or 220 or 240V for different countries) 500VA. Users can buy this item for back up from computer stores				
		_				
	stand alone					
Version						
DM-001	Original Design, refer to user manual for details. Skylink will not only offer the operator stand alone, only offer: DM-50, DM-50B, DM-100, DM-100A, DM-150, DM-150A and DM-150B (a set of opener).					
DM-001A	Add on feature to DM-001: When the door is opened manually, the door will be closed automatically after 10 seconds to 50 seconds (depending on timer setting). Application: A door will automatically close after being opened manually or opened by the transmitter or wall button switch (availability: upon request)					
DM-001B	Add on feature to DM-001 and DM-001A: When manually pushing the door open approx.1 inch, the door will continue to completely open automatically Application: Easy for wheelchairers or walkers to open the door. When they push the door slightly, the door will automatically open (availability: upon request)					