

# Thermo Scientific FHT 1377 GN-2 PackEye

## Radiation Detection Backpacks

The new Thermo Scientific™ FHT 1377 GN-2 PackEye is for the rapid, high sensitive detection and location of gamma and neutron radioactive sources with He-3 free neutron detector technology.

- Natural Background Rejection (NBR) indicates artificial sources - no false alarm from NORM and natural background changes
- Green flashing LED = Natural radiation (even at increased level)  
Red LED = Artificial radiation
- Non He-3 technology with high neutron detection sensitivity superior to He-3 Packeye neutron detection sensitivity
- User friendly via LED status and level indication and optional PDA with GPS function
- Very light weight at 7.5 kg (FHT 1377 GN-2, gamma/neutron), 5 kg (FHT 1377 G, gamma only)
- Low power consumption provides 30 hours of operation time from a full charge.



The Thermo Scientific™ FHT 1377 GN-2 PackEye provides survey teams with a tool for effectively addressing the problems of orphaned sources, radiation contamination, and sources for malicious intent.

By virtue of the proprietary NBR-technology (Natural Background Rejection) extremely low contributions of artificial gamma radiation are quickly detected, even with larger fluctuations of the natural gamma background radiation.

The NBR measurement method has been developed by Thermo Fisher Scientific for extremely fast discrimination between natural and artificial gamma radiation. Worldwide, more than 10,000 devices based on this technology are in use.

Unlike conventional spectroscopic based gamma identification systems, the systems using NBR do not require the presence and resolution of gamma spectral peaks, and unlike Sodium Iodide detectors, NBR

detectors are stable at varying temperatures and for many years of real field use, with no regular reoptimization or stabilization with sources required.

Because of this flexibility, NBR can also definitively distinguish artificial high energy beta sources and heavily shielded gamma ray sources from fluctuating natural background sources.

Thus alarm levels in the order of 1  $\mu\text{R}/\text{h}$  are achieved for SNM or heavily shielded industrial sources in outdoor environment. Such sources may be used in Radiation Dispersal Devices (RDD's) known as "dirty bombs".

Artificial gamma radiation sources are identified in seconds by operators with basic training levels. Presence of artificial gamma radiation is simply indicated by a red flashing light and an audible alarm.

Non He3



**Thermo**  
SCIENTIFIC

## Alarm indication

In addition to the detection of artificial gamma radiation a sigma based net count rate gamma alarm is active as well. Within a preset count rate range this alarm level is constantly and automatically updated according to the present background level. Once an alarm had been triggered the location of the source can be traced by using the Acoustic Search Mode and/or LED bar indication. For stealth operation or in a noisy environment a standard earphone can be used. Optionally data display, alarm indication and data storage can be performed with the help of a PDA with Bluetooth™ communication.

## Neutron detection

The detection of neutron sources is performed with the help of 2 ea. flat Li-6 scintillation detectors with an new proprietary measurement technique, allowing minimal crosstalk and the setting of a very low net alarm threshold level. The PackEye FHT 1377 GN-2 exceeds the neutron detection sensitivity of the well accepted and widely distributed predecessor FHT 1377 comprising 2 ea. He-3 counter tubes (2.5 bar, 2" dia., active length 14"). A neutron source with an activity of 20.000 n/s can typically be detected in a distance of 3 m (10 ft).

## Remote Monitoring with optional PDA

The optional PDA (425505091) allows remote monitoring, so that the PackEye can be sealed in a watertight rugged case (4255085) and used as a portal monitor on a tripod stand (4255086), on a boat or as a vehicle mounted mobile detection system. The PDA offers additional information like the short term history / finder mode to enable the most effective searches. The PDA also displays live accurate gamma dose rates and neutron count rates that can be stored together with GPS data.



## Technical specification of the Thermo Scientific FHT 1377 GN-2 PackEye

	FHT 1377 GN-2	FHT 1377 G
<b>Order Number</b>	<b>4255061</b>	<b>4255056</b>
<b>Gamma detector</b>	NBR-detector FHZ 672 E (advanced version) with preamplifier and controller type 681	
<b>Gamma energy range / sensitivity</b>	20 keV to 3 MeV / > 30 cps / $\mu$ Rem/h [3000 cps / $\mu$ Sv/h] at 662 keV	
<b>Artificial gamma alarm</b>	Typically better than 20 % of natural background	
<b>Neutron detectors</b>	2 ea. Li-6 doped flat scintillation detectors ea. 22 x 23 x 2.3 cm	-----
<b>Neutron efficiency (Cf-252)</b>	40 cps per n / s/cm <sup>2</sup>	-----
<b>User Interface</b>	LED based indicator unit at the belt. Optional PDA with Thermo PackEye software and GPS function	
<b>Signal update</b>	100 ms	
<b>Power supply</b>	Rechargeable NiMH - power pack (7.2 V)	
<b>Operation time</b>	approx. 30 h	approx. 60 - 70 h
<b>Weight</b>	approx. 7.5 kg	approx. 5 kg
<b>Accessory aluminum case</b>	1 ea. user manual, 1 ea. USB connection cable with driver software, 1 ea. RS 232 serial connection cable, 1 ea. rain cover for backpack, 1 ea. earphone, 2 ea. rechargeable battery packs (one in exchange), 1 ea. charger for 120/240 V AC and 12 V DC, 1 ea. package of black bands to secure the cables and belts of the backpack.	
<b>Accessories for immediate indication of artificial gamma alarm (NBR)</b>	Exempt check source Cs-137 3.7 kBq (0.1 $\mu$ Ci), sealed in a 1" resin chip Lutetium Test Adapter 50 g 50 Bq/g, 62 mm dia. disc (aluminum housing)	<b>SM149479010</b> <b>4254948</b>

## thermoscientific.com

© 2014 Thermo Fisher Scientific Inc. All rights reserved. Bluetooth is a trademark of Bluetooth SIG, Inc., Bellevue, Washington, U.S.A. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Results may vary under different operating conditions. Thermo Fisher Scientific makes no warranties, expressed or implied, in this product summary. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representatives for details

### Europe, Africa Middle East & Countries Not Listed

Frauenauracher Strasse 96 +49 (0) 9131 998-236  
D 91056 Erlangen, Germany +49 (0) 9131 998-172 fax  
customerservice.eid.erlangen@thermofisher.com

### China

7th Floor, Tower West, Yonghe Plaza +86 10 8419 3588  
No. 28 Andingem E. Street, Beijing, 100007 China +86 10 8419 3581 fax  
info.eid.china@thermofisher.com

### Singapore

11 Biopolis Way, Helios, Units #12-07/08 +65 6478 9728  
Singapore 138667 +65 6478 9505 fax  
info.eid.singapore@thermofisher.com

### USA, Canada, Mexico, Central & South America

27 Forge Parkway +1 (508) 553 1700  
Franklin, MA 02038 USA +1 (800) 274 4212 US toll-free  
customerservice.rmsi@thermofisher.com +1 (508) 520 2815 fax

### India

Plot No. C-327, T.T.C. Industrial Area, Pawne +91-22-41578800  
Navi Mumbai 400 705, India +91-22-41578801 fax  
info.eid.india@thermofisher.com

### United Kingdom

Wade Road, Basingstoke, +44 (0) 1256 693960  
Hampshire RG24 8PW United Kingdom 44 (0) 1256 334994 fax  
customerservice.eid.beenham@thermofisher.com

**Thermo**  
SCIENTIFIC

A Thermo Fisher Scientific Brand