



VAPORTEK™

*...the electronic wall cabinet system
that deodorizes with an
"element" of style!*

INSTRUCTIONS FOR USE

The Vaportronic can be used freestanding or mounted to walls with supplied tape or screws. See instructions below.

Mounting Unit With Tape:

- Insert pointed end of paper clip (supplied) into hole at bottom of unit to disengage cover. Lift up cover.
- Install D-cell battery as indicated and, if desired, lift off switch cover for "On/Off" function and adjust pulsing fan (see below). Lower cover and press to close securely.
- Remove backing from one side of double-backed mounting tape (supplied) and press onto back of cabinet.
- Remove remaining backing from tape.
- Allow enough clearance above unit for hinged cover to lift open. Apply unit to clean, smooth surface and press firmly for 30 seconds. Be sure even contact with surface has been made.

Mounting Unit With Screws:

- Using template supplied, mark holes for desired unit placement. Allow enough clearance above unit for hinged cover to lift open. Drill holes and install anchors and screws. Do not screw in completely.
- Insert pointed end of paper clip (supplied) into hole at bottom of unit to disengage cover. Lift up cover.
- Insert D-cell battery as indicated and, if desired, lift off switch cover for "On/Off" function and adjust pulsing fan (see below).
- Remove knockouts from screw holes in back of cabinet. Align holes over screws, press back and lower to seat unit into screw slots. Gently tighten screws.
- Lower unit cover and press to close securely.

PULSING FAN OPERATION

The Vaportronic is designed so that pulsing fan operation is set at the factory for one minute "on," one minute "off," with "off" cycles adjustable up to 30 minutes. The factory setting provides the highest level of deodorization, and initial treatment should begin at that level. Programmable pulsing fan operation may be adjusted by inserting a Phillips screwdriver into the recessed adjustment dial and turning. Turning dial clockwise decreases frequency of pulsing fan operation.

DEODORIZING ELEMENT INSTALLATION

By inserting from one to five disks, rate of output can be customized to meet specific user demands.

- Open protective bag containing deodorizing disk element by tearing at indicated notch.
- Insert disk(s) into slots, gently pressing down and back to prevent element interference with fan.
- Do not allow disks to contact surfaces other than element holder. Such contact may damage unit case and other finishes.
- Wash hands promptly to remove any residue from element. Keep out of reach of children.

SPECIFICATIONS

- Product #90-2600.
- Refill disks available in a variety of aromas (#34-7600 Series).
- Requires one D-cell battery (alkaline suggested).
- "On/Off" switch; flashing green LED operation indicator.
- Pin-lock mechanism for maximum security and ease of servicing.
- Weights less than one pound.

One-Year Limited Warranty

(For U.S. & Canadian Residents Only)

This unit will be repaired and/or replaced at no charge if it is found to be defective in materials or workmanship for up to one year after the original purchase date. Please keep your receipt in case any warranty claim may arise, as proof of purchase will be required for warranty claims.

This warranty does not cover: damage caused by accident, abuse or mishandling; damage caused by the use of non-Vaportek replacement disks, aromatic oils or parts; defective batteries; units that have been taken apart or subject to unauthorized repair, or units not used in accordance with instructions. Any damages determined to be from these causes will be repaired at owner's expense.

To obtain service, contact your dealer. Service may also be obtained by sending your unit, postage paid, to the Vaportek Factory Service Center. Vaportek is not responsible for damage in shipping or for lost shipments. Vaportek reserves the right to change prices, specifications, or to delete models without notice or obligation.

This warranty gives you specific legal rights. You may have other rights which vary from state to state.

Thank you for purchasing the Vaportronic deodorizing wall cabinet. For customer service, please call (800)237-6367 between 8:00 a.m.-4:00 p.m. CST.

VAPORTEK 

...the leader in air treatment technology

Vaportek Factory Service Center

W226 N6339 Village Drive, Sussex, WI 53089

Assembled in the U.S.A. of domestic and imported parts.

#50-0006