



User Manual
*Instruction guide and owner's manual
professional loudspeaker series*



■ Volume Control Pro-50mp | Pro-100mp

Instructions:

TRUAUDIO's Professional Loudspeakers Series of products are designed for commercial applications. This volume control works best when use with 25v, 70v or 100v speakers (transformer). TRUAUDIO offer's a full line of these speakers. With the proper design and installation, these products can be used in a residential system. If you have any questions please call for our free tech support, 888-858-1555.

Connecting the Volume Control:

Step #1 Locate the speaker wire and identify which wire comes from the amplifier (25v, 70v, 100v) and which wire goes to the speaker(s). eliminate loose strands.

Step #2 Strip about 1/4" of the insulation off the ends of all wires. Twist the exposed ends to

Step #3 Connect the leads from the Amplifier to the volume control connector labeled "IN". Insert the (+) and (-) into the corresponding openings. Tighten the screws firmly, making sure that the exposed wire is engaged, not the insulation! CAREFUL not to over-tighten the terminal screws!

Step #4 Connect the wire going to the speaker (s) to the connector labeled "OUT". Make sure to Observe the polarity (+,-)

Step #5 Install the completed volume control into the electrical box, rough-in ring, etc. Insert carefully not to put strain on the wire or connector.

