Solving Minor Problems Yourself			
Problem	Possible Causes	Solution	
Iron does not work or is not heating up	Temperature control (H) set to minimum	Turn the temperature control to the desired position	
	Connection problems	Check that the plug is inserted into the mains socket correctly	
	The automatic shut-off system has been activated (*)	Move the iron gently from side to side to re-start it	
Iron is not steaming	There is no water in the tank (D)	Fill the water tank	
	The steam regulator (A) is in the 🙀 position	Set the steam regulator to the relevant position	
Water is dripping from the holes in the soleplate	Temperature control (H) setting is too low.	Set the temperature control within the steam area (between the "••" and "max") or turn the steam regulator (A) to	
	Steam regulator (A) is set too high in conjunction with a low temperature.	Turn the steam regulator to a lower setting.	
	You have pressed the shot of steam button (L) repeatedly without waiting for 5 seconds between each press	Wait 5 seconds between each press of the jet of steam button	
	Water has been left in the tank (D) when the soleplate was cold, with the steam regulator (A) set at $\sqrt{2}$ or $\sqrt{2}$	Always empty the tank after ironing and set the steam regulator to XX after ironing and when filling the tank	
	Distilled water has not been used (see "Filling the water tank" section) or other products such as fragrant water have been added to the tank	Mix distilled water with tap water as directed in the "Filling the water tank" section and never add any other products to the water tank	
	No water in the tank.	Add water to the water tank.	
Spray does not work.	Obstructed mechanism.	Contact an Authorised Technical Service Centre.	
The iron begins to smoke when switched on.	During first use: Certain components on the appliance have been lightly greased at the factory and may produce a little smoke when initially heated.	This is completely normal and will stop after a short while.	
Deposits come out through the holes in the soleplate	Traces of lime scale are coming out of the steam chamber	Carry out a cleaning cycle (see "self cleaning" section)	
Flashing lamp on top of handle (*)	Auto-shut off has been activated.	Move the iron gently fromside to side to re-start it. The lamp will then flash once before it re-heats	

* Model dependent

You can download this manual from the local homepages of Bosch

Thank you for buying the TDA56 steam iron from Bosch. These instructions contain valuable information about the unique features of this iron and some hints to make ironing easier for you. **Please visit <u>www.bosch-home.co.uk</u> for more product information or to register your product, just follow the link to the Online guarantee registration.**

Important

This appliance has been designed exclusively for domestic use and must not be used for industrial purposes. Carefully read through the operating instructions for the appliance and safeguard them for future reference.

General safety instructions

- The iron must not be left unattended while it is connected to the supply mains.
- Remove the plug from the socket before filling the appliance with water or before pouring out the remaining water after use.
- The appliance must be used and placed on a stable

TDA56.. sensi**xx** B4



BOSCH

Customer Service

Great Britain

Bosch Customer Service Grand Union House Old Wolverton Road Milton Keynes MK12 5PT UK +44 (0)844 892 8923 IRL +353 (0)1450 2655 www.bosch-home.co.uk

006 TDA56..GB/09/12

- This appliance is to be connected and used in accordance with the information stated on its characteristics plate.
- This appliance must be connected to an earthed socket. If it is absolutely necessary to use an extension cable, make sure that it is suitable for 16A and has a socket with an earth connection.
- If the safety fuse fitted in the appliance blows, the appliance will be rendered inoperative. To restore normal operation the appliance will have to be taken to an authorised Technical Service Centre.
- In order to avoid that, under unfavourable mains conditions, phenomena like transient voltage drops or lighting fluctuations can happen, it is recommended that the iron is connected to a power supply system with a maximum impedance of 0.27Ω . If necessary, the user can ask the public power supply company for the system impedance at the interface point.
- The appliance must never be placed directly under the tap to fill the water tank.
- Unplug the appliance from the mains supply after each use, or if a fault is suspected.
- The electrical plug must not be removed from the socket by pulling the cable.
- Never immerse the iron in water or any other fluid.
- Do not leave the appliance exposed to weather conditions (rain,

GUARANTEE TERMS

The terms of the guarantee for this appliance are in accordance with that stated by our representative for the country in which it is sold. Details of those conditions can be obtained from the retailer from whom the appliance was purchased. The SALES RECEIPT must be presented when making any claims against the terms of this guarantee. We reserve the right to make technical modifications.

Operating instructions

Environmental Care

This iron has been redesigned according to ecological criteria, related to the sustainable development, analyzing its whole lifecycle - from material selection to its later reusing or recycling - evaluating the improvement possibilities, from a technical, economical and environmental point of view.

Before throwing a used appliance away, you should make it noticeably inoperable e.g. cut off the mains lead and be certain to dispose of it in accordance with current laws and regulations. Your retailer, town council or local council can give you detailed information about these.



- surface.
- When placed on its stand, make sure that the surface on which the stand is placed is stable.
- The iron should not be used if it has been dropped, if there are visible signs of damage or if it is leaking water. It must be checked by an authorized Technical Service Centre before it can be used again.
- With the aim of avoiding dangerous situations, any work or repair that the appliance may need, e.g. replacing a faulty mains cable, must only be carried out by qualified personnel from an Authorised Technical Service Centre.
- This appliance can be used by children aged from 8 years and above and persons with reduced physical, sensory or mental capabilities or lack of experience and knowledge if they have been given supervision or instruction concerning use of the appliance in a safe way and understand the hazards involved. Children shall not play with the appliance. Cleaning and user maintenance shall not be made by children without supervision.
- Keep the iron and its cord out of reach of children less than 8 years of age when it is energized or cooling down.
- CAUTION. Hot surface. Surface is liable to get hot during use.

sun, frost, etc.).

Tips to help you save energy

Steam production consumes the most energy. To help minimise the energy used, follow the advice below:

- Start by ironing the fabrics that require the lowest ironing temperature.
- Regulate the steam according to the selected ironing temperature.
- Only use steam if necessary. If possible, use the spray function instead.
- Try to Iron the fabrics while they are still damp and reduce the steam setting. Steam will be generated from the fabrics rather than the iron. If you tumble dry your fabrics before ironing them, set the tumble drier to the 'iron dry' programme.
- If the fabrics are damp enough, turn off the steam regulator completely.
- Stand the iron upright during pauses. Resting it horizontally with the steam regulator on generates wasted steam.



European Directive 2012/19/EU concerning used electrical and electronic appliances (waste electrical and electronic equipment - WEEE).

The guideline determines the framework for the

return and recycling of used appliances as applicable throughout the EU.

Before using the Iron for the first time

Please carry out the following steps:

- 1. Remove the protective cover from the soleplate before using the iron.
- 2. While the iron is unplugged, fill the water tank (D) with tap water
- 3. Plug the appliance into the mains and set the temperature control (H) to the "•••" position by lining it up with the pointer (G) on the iron.
- 4. When the iron has reached the correct temperature (the pilot lamp "I" will goes out), set the steam regulator (A) to the maximum position $\widehat{\mathcal{D}}$.
- 5. Hold the iron horizontally and repeatedly press the shot of steam button (L). Any residue should come out of the soleplate (E). It may smoke and smell – this is normal and will cease after a short while.
- 6. If necessary, carefully clean the soleplate down with a dry, folded cloth.

Using Your Iron



Filling the water tank

Set the steam regulator (A) to the \bigotimes position and i unplug the iron from the mains!

1. Place the iron at an angle of 45° with the point facing upwards. 2. Fill the water tank (D) via the water tank inlet but never above the "max" mark (F).

Use only clean water from the tap without mixing anything with it. The addition of other liquids, such as perfume, will damage the appliance.

Do not use condensation water from tumble dryers, air conditioners or similar appliances. This appliance has been designed to use normal tap water.

To prolong the optimum steam function, mix tap water with distilled water 1:1. If the tap water in your district is very hard, mix tap water with distilled water 1:2.

You can inquire about the water hardness with your local water supplier.



Spray

This can be used to remove stubborn wrinkles.

- 1. Do not use the spray function with silk as staining may occur.
- 2. Make sure that there is water in the tank (D).
- 3. When ironing, press the spray button (M) and water will spray out of the spray outlet (C) onto the garment.

After finishing each ironing session

- 1. Unplug the iron from the mains socket.
- 2. Set the steam regulator (A) to the $\overset{\infty}{\longrightarrow}$ position.
- 3. Slide open the water tank cover (B).
- 4. Hold the iron with the point facing down and shake it gently until all the water has come out.
- 5. If the iron is only slightly soiled, pull out the plug and allow the soleplate to cool down. Wipe the housing and the soleplate with a damp cloth only.
- If synthetic cloth melts due to too high temperature on the soleplate, switch off the steam and rub off the residue immediately with a thickly folded, dry cotton cloth.
- 6. Coil the power cable (J) loosely around the heel of the iron, before storing

Setting the temperature

The temperature control (H) adjusts the temperature of the soleplate (E).

1. Check the temperature instructions shown on the care label of the garment you are ironing and set the temperature control (H) to the corresponding position by lining it up with the pointer (G) on the iron:



- 2. If you are unsure what type of material the garment is made from, start ironing on the lowest temperature setting and increase accordingly. If the garment is made from mixed fabrics, set the temperature for the most delicate material.
- 3. For silk, woollen or synthetic materials iron the reverse side of the fabric to prevent shiny patches. Avoid using the spray function to prevent stains.
- 4. Sort your garments based on their care labels, always starting with clothes that have to be ironed at the lowest temperature.
- 5. The pilot lamp (I) will stay lit while the iron is heating up and go out once the selected temperature has been reached. Wait a few seconds after the lamp goes out before you start ironing. Once the iron is ready, you can continue to iron even if the pilot lamp comes on again.
- 6. If your iron has auto shut-off and the pilot light (K) is flashing, the auto shut-off has activated. Gently move the iron side to side to restart it.
- 2. Set the temperature selector to the "max" position and plug in the iron.
- 3. After the necessary warm-up period, the pilot light (I) goes out. Then, unplug the iron (very important!).
- 4. Hold the iron over a sink. Press the "clean" button (O) until approximately one third of the water capacity of the tank is evaporated. Boiling water and steam will come out, carrying scale or deposits that might be there.
- 5. Release the "clean" button, and gently shake the iron for some seconds.
- 6. Repeat the steps 4 and 5 three times until the tank is empty. Then plug the iron in and heat it up again until the remaining water has evaporated.
- 7. Unplug the iron and let the soleplate (E) cool down. Wipe the soleplate with a damp cotton cloth only.

C. anti-calc cartridge (Model dependent)

The anti-calc cartridge has been designed to reduce the buildup of scale produced during steam ironing, helping to extend the useful life of your iron. Nevertheless, the "anti-calc" cartridge cannot remove all of the scale that is produced naturally over time.

Additional Features

Ironing with steam

The steam regulator (A) is used to adjust the amount of steam produced when ironing.

- 1. Make sure that there is water in the tank (D).
- 2. Adjust the temperature setting and then set the steam regulator according to the table below. Steam will automatically be produced:

Temperature Setting	Steam Regulator Setting
••• to "max"	ŝ
••	()

Note: At a temperature setting of "•", the soleplate is not hot enough to produce steam so the steam regulator should be set to the \bigotimes position to avoid water dripping from the soleplate (E). Tip: for better ironing results, iron the last strokes without steam to dry the garment.

\$

\$

Ironing with shot of steam

This can be used to remove stubborn wrinkles or to press in a sharp crease or pleat. It cannot be used on a synthetic setting for delicate items.

- 1. Set the temperature control (H) to the "•••" or "max" position. 2. Set the steam regulator (A) to the $\overline{0}$ position.
- 3. Press the shot of steam button (L) on the handle repeatedly at intervals of 5 seconds.

Vertical steaming with shot of steam

This can be used to remove creases from hanging clothes, curtains etc. It cannot be used on a synthetic setting for delicate items.

WARNING! Do not vertical steam while the item is being worn. Never spray or aim steam at people or animals!

- 1. Make sure that there is water in the tank (D).
- 2. Set te temperature control (H) to the "..." or "max" position and the steam regulator (A) to the \bigcirc position.
- 3. Hold the iron in an upright position about 15 cm away from the garment being steamed.
- 4. Press the shot of steam button (L) on the handle at intervals of 5 seconds, however, after 4 jets of steam, wait for 10 seconds to allow for continued steam production.

Ironing without steam

This function enables the iron to be used for dry ironing.

- 1. Set the steam regulator (A) to the $\overset{\infty}{\infty}$ position.
- 2. Select an appropriate temperature for the type of material being ironed.

Fabric protection soleplate cover "Protect"

(Model dependent)

The fabric protector is used for steam-ironing delicate garments at maximum temperature without damaging them. Use of the protector also does away with the need for a cloth to prevent shine on dark materials.

It is advisable to first iron a small section on the inside of the garment to see if it is suitable.

To attach the fabric protection soleplate cover to the iron, place the tip of the iron into the end of the fabric protector and press the rear of the protector upward until you hear a click. To release the fabric protector, pull down on the clip at the rear and remove



The protective cover can be purchased from After-sales or the Bosch eShop..

7. Store the iron in an upright position.

10 Self Cleaning

The self clean function helps remove lime scale that has built up around the steam valve.

This should be performed once every 3 or 4 uses.

- 1. When the iron is cold, slide the steam regulator (A) between the \mathfrak{K} and \mathfrak{K} positions in quick succession about 3 or 4 times to help loosen any lime scale and clean the valve inside.
- 2. Heat up the iron. Before starting ironing, hold the iron horizontally over a sink and press the jet of steam button (L) 3 or 4 times. This will help force out any lime scale and dirt deposits through the holes in the soleplate (E).

11 Multiple de-scaling system

This range of irons is equipped with the following descaling features "AntiCalc".

A. self-clean

Each time you use the steam regulator (A), the "self-clean" system cleans the mechanism of any scale deposits.

B. Calc'nclean (Model dependent)

The "calc'nclean" function helps to remove scale particles out of the steam chamber. Use this function approximately every 2 weeks, if the water in your area is very hard.

1. Unplug the iron from the mains socket, set the steam regulator (A) to the \bigotimes position and fill the water tank (D) with water.

Anti-drip system "Drip Stop"

(Model dependent)

Some irons in this range are equipped with an anti-drip system.

This will automatically stop the iron producing steam when the selected temperature setting is too low to prevent water from dripping out of the soleplate. You may hear a clicking sound when this system is in operation.

Auto shut-off "secure"

(Model dependent)

Some irons in this range are equipped with an auto-shut off system.

The "secure" auto shut-off function switches off the iron automatically when it is not being used, thus helping to prevent accidents and saving energy. When the appliance is first plugged in, this function will be inactive for the first 2 minutes to allow it to reach the set temperature.

If during ironing, the iron is not moved for a certain length of time, the iron will automatically switch off. The length of time will depend on the position the iron has been left in:

Horizontally (flat) or on its side:	30 seconds
Vertically (upright):	8 minutes

The pilot light on the top of the handle (K) will flash when auto shut-off has been activated. To switch the iron back on, move it gently from side to side. The light will stop flashing

Name of accessory: Accessory code Protect cover soleplate (After-sales) (online shop) 464851 TDZ1510

Cleaning and Maintenance

Attention ! Risk of burns !

For general cleaning, follow the information below:

Problem	Solution
Dirty/lightly marked iron body or soleplate	Clean the body of iron or soleplate with a damp cloth then dry it.
Mark develops on soleplate during use	Set the iron to its maximum temperature setting. Rub the iron a few times over with a dry cotton cloth folded several times.
Heavily stained soleplate	While the iron is cold, iron a linen cloth soaked in white vinegar. Then dampen a cloth with water and wipe the soleplate clean and dry thoroughly.

DO NOT de-scale or clean the water tank with cleaning products or solvents, as these could cause the iron to drip when using the steam function.

DO NOT use a "professional steam cleaner" for cleaning the appliance.

DO NOT use sharp objects or abrasive products to clean the soleplate or any other part of the appliance. To keep the soleplate in good condition, do not allow it to come into contact with metal objects.