

Department of School & Mass Education, Govt. Of Odisha



Implementation of e Vidyalaya Project in 4000 Govt. & Govt. aided Schools of Odisha

This is to certify that the following items/Human Resources have been duly delivered and installed/deployed in our school and all equipment/items are in proper condition for implementation of ICT lab with following details.

IMPLEMENTATION PARTNER IL&F5 Education & Technology Services Ltd.								Please tick whichever is applicable											
	U	DISE CODE		4			2	1		2	1	0	4	2	1	0	3		
	1	Date	T		1		2	1	0	7	2	0	1	4					
School Name	5	1	T	H	A	٠,	0		H	1	G	H							
Village	5	C	H	0	0	L	H	A	1.					-	+	-			
Block	A	T	-	S	t	T	1		-	0			-		-	-	-		
District	N	100	A	L	1	1					X.	2 2	ļ		+-	-	T N 20		
	C	0	-	T	A	<u>_</u>	K	1		1.15				-	_	_			
Address	A	7	-	S	t	T	4	A	<u>L</u>	٥	,	N	- L	A	L	1			
-	e	U	T	7	A	0	K												
Name of Head Master/ Mistress(HM)	S	A	R	A	D	A		P	R	A	S	A	D						
···istress(mv)	T	R	1	P	B	T	H	Y			•								
HM Contact No.	9	2	3	8	9	8	L	1	2	8									
Name of School Coordinator	A	M	B	1	R	A		2	A	R	A	N	9	1					
School Coordinator's Contact no.	8	q	0	8	2	2	1	8	9	9	100					1921	1		
Implementation partner's School Code	0	A	Z	3	_	C	U	T	A	-	0	9	2	3			-		
Room Dimension (in feet)	Length:		19				#	Breadth		19						Please Tick			
Sr. no.	Ma	Item ake & Mod	lel	Qty.				Please Tick											
1 1		Desktop Acer Make		1	X86 Architecture 3.2 Ghz or higher Processor with 4 dedicated cores, RAM 4GB or higher expandable to 16GB, 500 GB HDD, 19-inch or Higher LED Monitor, Built-in audio, 300 Watt Desktop Speaker, DVD Writer, 10/100/1000BaseT Ethernet, 104 Key Keyboard and Optical Mouse With at least 2 Free Full Height PCI slots.														
		Serial no.			U	X	V	8	5	S		0	-	9	D	5	2		
					8	0	2	5	7		r vi					4			
		Desktop(Stand by) Acer Make			expar	dable to	16GB, 50 ker, DVD \	hz or high 0 GB HDD Writer,10/ ouse With), 19-inch (100/100	or Highe OBaseT E	r LED Mo thernet, 1	nitor, Bu 104 Key K	ilt-In au	dio, 300	Watt	Plea	se Tick		
1	Serial no.		1 2 3 3 3	1	U	X	V	8	2	2		0	l	8	D	5	2		
					7	9		4	3		44. (c)	edy as				42			

	U DISE CODE	-			2	1		2	1		11	2	1	Please	Tick
3	Shared Computing Device N-computing	2	single hos Virtualizat output. S\ length)). F access de Each user	ed Comput t PC through ion softwork /GA Monit Power con- vice should should has substantia (eyboard, a	gh a share are, acce for output sumption d be integ ave indep	ess device it and RJ4 n of each grated with pendent comments of	ting PC-Shes with sp 45 Connectors de access de ith Host Podesktop en the host	peaker of ction Por evice sho C via CAT nvironme PC (Boot	{which indutput, PS, t, with 5 and not execute to cable to cather time. Log	cludes or /2 Mous CAT6 cal xceed mo with supposition gin Experien gin Exper	he full he bles (eac ore than port up t ce on sh ience, Re	S/2 Keyb th of 5 m I-2watts to 10mtr, ared ter esponsiv	neters s. The /32ft. minal	_	c
	Monitor		connectiv degrees (r higher Li ity with n horizontal	natt blac /vertical)	k finish, , wall m ification	brightnes ounting p	ort VDI,	with Win	dows Ce	gie 170 ertificatio	degrees	1 100	Please	Tick
	Serial no.		ī		-	Pls	. fill the s	erial no.	s of all th	e 12 Mo	nitors				
	1			m	L	Y	6	S	S	0	1	4	3	પ	5
			0	Ч	A	A	0	8	5	1	0	4	3	u	_
1	2		0	2	3	χ C	x 2-	5	S	0	4	L	<u>J</u>	4	6
			m	M		X	K	S	S	0	1	4	3	4	6
	3		0	2	4	5	D	4	2	0	4				
			m	M	L	×	K	S	2	0	l	4	3	4	6
	4		0	2	3	D	B	4	2	0	4				
	4		M	M	L	Y	6	2	S	0	l	4	3	4	3
	5	2 ,22	0	4	D	6	2	8	5	t	٥				
4	, , , , , , , , , , , , , , , , , , ,	12	M	M	1	Y	6	S	2	0	1	4	3	q	5
- P	6		0	4	C	0	6	8	5	-1	0		97.5		
			M	M	L	F	6	S	2	0	l	4	3	y	5
	7		0	4	B	D	7	8	5	l	0			1	
			M	M	L	Y	6	S	S	0	1	4	3	4	5
	8		0	4	B	B	B	8	5	1	0				
			M	m	L	Y	6	5	2	0	1	4	3	4	5
	9		0	1	C	8	B	8	5	L	0	-			
	10		M	m	-	X	K	S	S	0	1	4	3	4	. 2
	10		0	1	7	8	C	4	2	0	4				
	11		M	m	L	X	K	5	S	0	1	4	3	4	6
			0	-1	D	B	3	4	2	0	4	0			-
	42		M	m	٤	7	6	3	2	0	1	4	3	4	3
	12		0	- (C	٠٠	F	8	5	1	0				and Tief
5	Web Cam Brand (Piz. tick) Wipro	1	Min	5MP cam	era, Sup	port for I		reductio	n	0 pixels)	, Built-in	mic wit	th noise	2	lease Tick
6	Headphones	40					Head Vay 3.5-m	phone w						,	lease Tick

		-	Tc :-		2	1		2	1 2)	1°2		0	ase Ti	
8	Integrated Computer Projector K-YAN	1	Specification: Projection System: DLP Technology:Brightness: 2500-ANSI Lumens (Short Throw) Resolution: SVGA(800x600); Contrast Ratio: 2500:1 Computer System: X86 architecture, 3.2GHz or higher with 4 dedicated Cores, Minimum 4MB 1.3 Cache, Compatible chipset with HD graphics, 4GB DDR3 RAM expandable to 16GB, 500 GB Serial SATA II 7200 RPM HDD, Optical Drive DVD RW, Wireless Keyboard & optical Scroll Mouse. OS: DOS; Input: PS/2 Mouse & Keyboard, RF -in for TV, USB ports, Microphone in; Output: Internal 30 watts Audio Output, LAN: 1x Gbps LAN, Integrated analogue cable TV tuner.													
9-1, j. 1., 1.	Serial no.	I	1	3	_	G	C :	Z C) @	1	2	2	8	9	T	
9	Interactive White Board Smart	1	Active A approxi Aspect maniter isoprop operating support consum USB cable for Electron Data Po PC, Soft DVD. Soft without product availability palm to specific and facility. A facility. A facility. A facility. A facility.	mately 32 Ratio: 4:3 R	mum acti 2767 x 327. Board Su e, compat (IPA), Opi and Linux uch and Liess than 0 sess tha	ive area : 767 rface: Du ible with erating Sy x, Writing use of nor .5 W (100 nux* com unlight ar connect a comple e availabl for an onl nat can au Vindows* immeder. W eaboration ts. Minim Pens, US	rable Hard dry-erase stem: Wir To mechania mA at 5 N aputers. Te ad other e- ad other e- a	d-coated st markers an indows XP S th finger an ical and bat V). Must ob- echnology: xter nal infl peed USB 1 n of the wh- or download nunity. Soft lly scan for operating s p shots, recy additional and manag on the same on the same on maximum ioftware CE	eel surface of easily in the period of the p	te, optimicleaned vious Vistauch with objects. I chnology. 2.0). Sto ling softwamust be a tit be avail ates and should hactures, ree to colla ver other simultan r can con	zing reso zed for p vith white a* SP2 or out any s Power Op he comp No inter rage: Sav vare appl able to a clable for alert use ve intera eveal opt borate ex- content. eously al currently	lution is projection, eboard cle window; pecial too ptions: Pouter through the project of the pr	eaner or s 7 ols, wer ugh the com s in a CD or software a a		ase Ti	
	Serial no.		2	B	4	8	0	_	2	0	6	2	2	5	7	
	· · · · · · · · · · · · · · · · · · ·	100		Un to 19				oor Drint		lask		1		Plea	se Tic	
10	Multi Function Printer Brand (Pls. tick) Ricoh	1	(best): Proces: 10/100 Autom	Up to 60 sor speed Base-T El atic Scan	0 x 600 d d: Minimi thernet r ner type:	lpi (1200 um 400 ľ network j Flatbed	MHz, Con port, RJ-1 ADF, Sc	ctive), Dis nectivity, 11 Telepho an file for resolution	play: at l standard one port, mat: JPE	east 2-lir : Hi-Spec Duplex G, TIF (co	ed USB 2 printing: ompress	ed	l by IDC.	~	_	
10	Brand (Pls. tick)	1	(best): Proces: 10/100 Autom	Up to 60 sor speed Base-T El atic Scan	0 x 600 d d: Minimi thernet r ner type:	lpi (1200 um 400 ľ network j Flatbed	dpi effe MHz, Con oort, RJ-1 , ADF, Sc	ctive), Dis nectivity, L1 Telepho an file for	play: at l standard one port, mat: JPE	east 2-lir : Hi-Spec Duplex G, TIF (co	ed USB 2 printing: ompress	ed	by IDC.	~		
10	Brand (Pls. tick) Ricoh	1	(best): Proces: 10/100 Autom. and un ISO 9000 sine wav Sealed. I With DG	Up to 60 sor speec Base-T Etatic Scanic compress:	0 x 600 dd: Minimuthernet riner type: sed), PDF	Ipi (1200 um 400 N etwork p. Flatbed, F. GIF, BN EVER FLOOR	dpi effer MHz, Con port, RJ-1 ADF, Sc. IP, Scan	ctive), Dis nectivity, 11 Telepho an file for resolution	play: at I standard one port, mat: JPEc , optical: power bac out Power e Conversertz, opera	east 2-lir : Hi-Sper Duplex G, TIF (cc Up to 1	printing: printing: printing: printing: printing: printing: put Wav 0.90, Bat ine UPS ar perature	ed Certified e Form - F ttery type nd Cabling : 0 to 50	Pure :	~	see Tic	
	Brand (Pis. tick) Ricoh Serial no. On Line UPS		(best): Proces: 10/100 Autom. and un ISO 9000 sine wav Sealed. I With DG	Up to 60 sor speec Base-T Etatic Scanic compress:	0 x 600 dd: Minimuthernet riner type: sed), PDF	Ipi (1200 um 400 N etwork p. Flatbed, F. GIF, BN EVER FLOOR	dpi effer MHz, Con port, RJ-1 ADF, Sc. IP, Scan	ctive), Dis nectivity, 11 Telepho an file for resolution D minutes p ull load, Inp ased Doubl 0+/* 6% he	play: at I standard one port, mat: JPEc , optical: power bac out Power e Conversertz, opera	east 2-lir : Hi-Sper Duplex G, TIF (cc Up to 1	printing: printing: printing: printing: printing: printing: put Wav 0.90, Bat ine UPS ar perature	ed Certified e Form - F ttery type nd Cabling : 0 to 50	Pure :	~		
	Brand (Pls. tick) Ricoh Serial no. On Line UPS Delta		ISO 9001 sine wav Sealed. I With DG degrees	Up to 60 sor speecibase-T Elatic Scanic compress: L Certified e, Efficien Maintenan Set comp celcius, no	0 x 600 d i: Minimut thernet r ner type: sed), PDF L. Online L ccy 90 % o nce Free, patibilities bise level:	JPS of 2K' or better of Micro Coi , frequency as per th	dpi effer MHz, Con Dort, RJ-1 ADF, Sci IP, Scan	ctive), Dis nectivity, 11 Telepho an file for resolution D minutes p ull load, Inp ased Doubl 0+/* 6% he	play: at I standard ne port, mat: JPEr, optical:	east 2-lir : Hi-Spec Duplex G, TIF (cc Up to 1 Ckup, Out Factor > sion Onlir atting tem pure sin	port Wav 0.90, Bata apperature e wave o	ed Certified ee Form - F ttery type nd Cabling : 0 to 50 output	Pure :	Pleas		
	Brand (Pls. tick) Ricoh Serial no. On Line UPS Delta Serial no.		ISO 9001 sine wav Sealed. I With DG degrees	Up to 60 sor speecibase-T Etatic Scanic compress: L Certified e.e., Efficient Maintenan Set compression conditions of the compression of the comp	0 x 600 d i: Minimut thernet r ner type: sed), PDF L. Online L ccy 90 % o nce Free, patibilities bise level:	JPS of 2K' or better of Micro Coi , frequency as per th	dpi effer MHz, Con Dort, RJ-1 ADF, Sci IP, Scan	ctive), Dis nectivity, L1 Telepho an file for resolution 8 D minutes pull load, Inpassed Doubl 00+/* 6% henert norm	play: at I standard ne port, mat: JPEr, optical:	east 2-lir : Hi-Spec Duplex G, TIF (cc Up to 1 Ckup, Out Factor > sion Onlir atting tem pure sin	port Wav 0.90, Bata apperature e wave o	ed Certified ee Form - F ttery type nd Cabling : 0 to 50 output	Pure :	Plea:	To see Tic	
11	Brand (Pis. tick) Ricoh Serial no. On Line UPS Delta Serial no. Networking		ISO 9001 sine way Sealed. If With DG degrees	Unmanage cntion pi	0 x 600 d i: Minimuthernet r iner type: sed), PDF I. Online L icy 90 % o ince Free, i patibilities poise level: Sable GIG rinters, Pi	UPS of 2K's requested by the second of the s	dpi effer MHz, Con Dort, RJ-1 ADF, Sci IP, Scan	ctive), Dis nectivity, L1 Telepho an file for resolution 8 D minutes pull load, Inpased Doubl 0+/* 6% hement norm	play: at I standard ine port, mat: JPEr, optical: power bar bar bar bar bar bar bar bar bar ba	east 2-lir : Hi-Sper Duplex G, TIF (cc Up to 1 Ckup, Out Factor > sion Onlir ating tem pure sin	put Wav 0.90, Bat a perature e wave o	ed Certified e Form - Fittery type and Cabling : 0 to 50 output	Pure : g.	Plea:	q	

	U DISE CODE		+ 1		2			2	1	0	1	2		0	- Tiels			
14	Servo Stabilizer Protect		5KVA (1 Rhase Servo Motor Operated Line Voltage Corrector), input Range:: SOV-270V (Single Phase, Mounting: On Wheels Output range: 220V/230V/240V single phase (adjustable), earthing terminals, overload cutoff, output protection through MCB, Frequen range: 304-4, 3% herts. Operating temperature: 0 to 50 degrees celsius.												e Tick			
	Serial no.		1	2	0	2	1	Ч	0	1			. /					
	Silent Generator Set Champ	-	ISO 900 Cabling	1 Certifi	ed, Minim	num 3 K\	/A Petro	I/Diesel b	ased sile	nt genera	tor set	with Saf	e	Pleas	se Tick			
15	Serial no.	1	5-	1	3	1	1	0	3	6	l	0	2	~				
16	Initial meter reading of the Silent Generator Set					(9							Please Tick				
17	Earthing (as per IS specifications)		Copper plate earthing stations making earthing with copper earth plate												se Tick			
18	Lighting (ISI mark)				with Ele									~	se Tick			
19	Ceiling / Wall mounted fans (ISI mark)	2	48" blade with regulator, 3 Blade Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj/ Havells															
20	Exhaust fans (ISI mark)	2	300mm sweep, 45 Watts, Speed 1330 RPM Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj / Havells												ase Tick			
21		15	5 A- 240 V switches															
	Switches and sockets (ISI mark)	15	2 in 1 5A and 15A Sockets															
	(ISI Mark)	2	15 A - 240 V socket with shutter															
			Indicative Brands: - Anchor / Havells / crabtree /Wipro /Phillips / Legrand Switches and sockets is to be provided for all electronics/IT equipments including printer and Projection System to be placed at lab technician table.															
22	Computer Table Tajpuria	13	Dimensions Width 1200mm x Depth 609mm x Height 750mm 18mm pre laminated particle board conforming IS: 12823. Pretreated 8t powder coated steel frame. Good quality PVC edge bending to be provided on pre laminated board. No Sharp corners, smooth edges are essential. Legs frame made of 1.5 inch square pipe, 16 gauges. Table rests on good quality glide screws. Full length footrest is to be provided. One 65mm diameter hole for drawing cables is to be provided, this hole has to be covered with steel cover Good quality telescopic slider along with full width keyboard with 30cm projected depth panel, keyboard free space is 10 cm. Table must have a modesty panel of 200mm height to be provided. End caps to be provided. BIFMA Certified												ase Tick			
23	Chair Uma Plastic/Moderna	41	Armle	ess Mould	ded Chairs	s, Cream	coloui, st	tandard Co	mpliant			jn		Ple	ease Tic			
24	Electrical meter Initial reading	- 1					9.	•			175							
. 25	Painting	r = le r	OMS	M and sh	Wall and all be app as appro	lied with	2 coats	ited, shall of primer MSM.	be prepa and then	red to the with 2 co	e satisfac oats of di	ction of (istemper	OKCL / paint of		ease Tic			
26	Lab Cleanliness Kit	1 set	one F	oot mat				Dust clot	34.52			oments a	ind		ease Tic			
27	Curtains	Full lab	To ma	aintain pr	oper dark	ness in t	he Lab /	Classroom	during f	Projection	1				ease Tio			
28	Wall Clock	1	ISI Ma	ark, Wall	Clock	721 U			7 70 1						Please Tick			
29	Notice Board	1	5 feet	t x 3 feet,	P/F 15 th	ık Pinup l	board wi	th fabric w	rapped a	all around				1	ease Ti			
30	White Board	1	4 ftx3	ft minin	num 18m	m thickne	ess white	board						PI	Please Tic			

*** Please note that all the three signatures are mandatory on all the sheets.

****All fields are to be filled up mandatorily.

ature of implementation partner's

Sarahe From Triping.

Signature of OKCI Representative with Seal

HEADMASTER

Signature of School Head Master) Mistress with Seal