

IP Cam 30

User manual 💥

Video resolution High: 1280 x 720 / Normal: 640 x 360 **Produkt Strukture Delivery** Main features Frame rate 30fps Viewing angel 80°(horizontal) Camera • WiFi wireless transmission 5M Night vision distance Photosensitive · Wall hanging bracket Support 720P HD cloud video recording operation Audio input Built-in microphone Setting button Indicator light · Wall dowel · Can read images saved in cloud storage anytime Wireless network 802.11 b/g/n Camera lens - Screws · Easy to install and use, and can be easily set by QR code Wireless safety WEP/WPA/WAP2/WPA-PSK/WPA2-PSK 90° swinging Operation system Android / iOS Power adapter • Built-in IR-CUT wide-angle lens, infrared lamp images are with high definition and delicate Motion detection Support Power supply Micro USB 5V Power supply 0758 Support motion detection Consumption current 270 mA (IR LED off) / 490 mA (IR LED on) 360° swinging -· Message service, master trends at first time **Operation Temperature** $10^{\circ} \sim +50^{\circ}$ Storage Temperature $-20^{\circ} \sim +60^{\circ}$ Operation humidity 15% ~ 85% BH Wall hanging bracket Dimensions 93.5 x 88.7 x 41 mm (Folded state) Weight 159 g

Installation

Place the camera on a plane surface



Place the camera lens directly onto the horizontal plane.



Drill on the wall, knock in the nail, and then fix the wall hanging bracket onto the proper monitoring position with screws.



Drill on the wall, knock in the nail, turn the screws into the nail, and then slide the wall hanging bracket onto the screws.



Specifications

Image sensor Minimum illumination 1/4" CMOS

OLUX (IR LED ON)

After fixing the wall hanging bracket, stick the DV into the wall hanging bracket. Notes: align the slots before pressing down. Camera lens plug in. Insert one end of the power line into the supply hub at the back of the camera lens, and the other end into power outlet, and the indicator light lights up. Notes: power line plug and camera lens jack are marked as the same plane



Operation

iOS devices

- 1. Open iPhone client end, and click icon of App Store.
- 2. Search keyword "Walle" in APP Store.
- 3. Click "install" and the software will be installed to the
- smart client.



Android devices

- 1. Open Android smart client, and enter GOOGLE PLAY store
- 2. Search software "Walle" and download.
- Click "install"and the software will be installed to the smart client.

Fix and installation: users can choose to fix directly or install with side fastener to the wall.



Register an account. Open APP software, and register an account first. Below image will show if it is successful.





offware, int first. ill show cessful.



Hi the

you st

Ema

bo

😋 😢 🚫 🚾 🤣 📰 😻 🔯 🌳 🖑 🖬 🖭 17:07

2 🖬 🥥 🖾 🖧 📩 🖓 🕅 🔛 17:18	4 C (Q 1	🗿 🔤 🗿 🖏 📩 🖓 👘 🔛 17/07	
	E	Welle	
e! We need a few things to help get arted:	Yester	Contrast a carriers	
al contraction of the second se		whit now by talocing below	
sword		Antipanina	
firm password			
Şiqn up			
Log in \geqslant an one up for the splify closeli messiletter.			
ing up, you agree to our privacy policy and I service.			