

## We help create great leisure experiences!

- ✓ Expertise in pump and heating solutions for leisure
- ✓ Investing in innovation
- ✓ Providing reliable products to improve your van experience
- ✓ Highest levels of support and service



### Heating and Water System Range 2013

Proud to manufacture in the UK

Water Pumps & Supply

Space Heating

Taps & Showers

Plumbing

Water Heating

NEW Intelligent Control

## Whale still leading innovation

Whale offers a professional and personal service. The company's expertise has been built on over 40 years of manufacturing high quality products for the recreational vehicle market.



### Quality

Every product, fully tested, every time



### Innovation

Award winning designs



### Service

Tried and tested, trusted for decades



“At Whale, we consistently strive to provide our customers with innovative, market leading products with professional proactive support services.

In achieving this, our employees will consistently act with integrity and honesty, and radiate a passion for our company, our culture and for customers.”

**Patrick Hurst, Managing Director**

## Index

### About Us

Meet the Whale Team	7
Whale Support	8
Whale Go Caravanning	9

### NEW Intelligent Control

i Van® – Intelligent Control Panel	12
Watermaster® IC – Pump Controller	14

<b>Space Heater Range</b>	<b>18</b>
<b>Water Heater Range</b>	<b>30</b>

### Water Pumps and Supply

Aquasmart Pressurised Water Delivery System	38
NEW Watermaster Onboard Freshwater Pump Range	40
Watermaster Freshwater Connection Range	42
Underfloor 40L Fresh Water Tank	45
Submersible Freshwater Pump Range	46
In Line Booster Freshwater Pump Range	48
Aquasource Mains Water Connection	50
Portable Pump Kit	52
Superfill Pump Kit	54

### Manual Pumps

V Freshwater Pump	56
Babyfoot Freshwater Pump	57

### Plumbing

Plumbing Systems	58
------------------	----

### Taps and Showers

Metal Tap Range	64
Elite Tap and Shower Range	66
Elegance Tap and Shower Range	68
Swim'n'Rinse – Exterior Shower	74

### Water System Accessories

Pressure Switch	77
Aquasmart Water Filter	79
Aqua Source Clear Water Filter	78
Surge Damper	80
One Way Valves	81
One Way Solenoid Valve	82

### Whale Support

Pre-season Preparation	84
Getting Ready for Winter	85
Adjusting your Pressure Switch	86
Onboard Pump Guide	87
Service Kits and Accessories	91
Affiliations and Accreditations	98
Customer Support Services	100



# Fit Whale throughout your van

Whale manufactures high quality reliable water and heating systems for caravan and motorhomes. Our products are lightweight, durable and proven to provide reliable heating and water supply to allow you to have great leisure experiences. All this is backed up by a dedicated Whale Support team on hand to provide spares and technical assistance when you need it.



Easy Install



Efficiency



Light Weight



Reliability



Serviceability


## Typical Whale Water and Heating Installation

### WHALE QUICK CONNECT PLUMBING

Reliable plumbing solutions specifically designed for mobile applications. Pages 58-61

### WHALE TAPS AND SHOWERS

Whale modern style taps and showers are lightweight and the range includes models for use with either micro-switch or pressure switch systems. Pages 63-75



### WHALE SPACE HEATING

A full range of blown air space heaters designed to maximize living space inside the van. Pages 16-25

### WHALE PUMPS AND WATER SUPPLY

Our wide range of pumps are designed to deliver smooth constant supply. Pages 37-57

### WHALE WATER HEATING

Our range of water heaters include high capacity and fast heat up models operating on gas and or electric. Pages 28-35

See our latest Intelligent Control Range – pages 11 -15





## Quality

Every product, fully tested, every time

At Whale, we pride ourselves on applying sophisticated manufacturing technology coupled with the latest design techniques. Whale employees are committed to providing excellent customer service.



## Innovation

Award winning designs

Whale's proven pioneering technology has led the way for decades. Innovations in pumps, plumbing systems, heating technology and advanced electronics have resulted in ground-breaking products such as Whale Underfloor Space Heating, and a new Intelligent Control range.



## Service

Tried and tested, trusted for decades

Our strong reputation for reliability has been built on decades of experience in UK manufacturing. We support our products with advice and service kits many years after the original fit.

## Meet the Whale Team



Sarah Baird  
Commercial Manager



Steed Barbour  
Customer Support Engineer



Alex Duggan  
Customer Support Engineer



Richard Bovill  
Engineering Manager



Aiden Devlin  
Customer Service Representative



Stanley McFarland  
Engineering Director



Chris Ragg  
Project Engineer



David Smyth  
Design Engineer



Mark Walmsley  
Product Manager



John Matchett  
Quality Engineer

## Whale Out and About







# Whale Support

At Whale, we always do our best to back up all products with the highest level of customer service

Need water and heating system advice?  
For advice on your Whale heating system call our support line

Call us today

**0845 217 2922**

Find your nearest retailer or accredited service engineer

[www.whalepumps.com/rv/where-to-buy.aspx](http://www.whalepumps.com/rv/where-to-buy.aspx)

Choose a region for a list of retailers and accredited service engineers.



## Whale - Support UK

tel: +44 (0)28 9127 0531  
fax: +44 (0)28 9146 6421

**Whale Heater Support**  
**0845 217 2922**

info@whalepumps.com  
whalepumps.com

**Call us directly for product  
and installation advice**

UK

## Experience and understanding Whale go caravanning!

**We go caravanning and it helps us to understand what you need when you are on site. At Whale, we really live and breathe the leisure lifestyle.**



### Whale go rallying

We attend caravan rallies around the UK so that you can get advice whatever the weather!

### Our Whale vans

Our company caravans are a great way for our design team to test installations and prototypes, as well as an opportunity for all employees to enjoy caravanning holidays.

### A Lifetime of caravanning

Our team include avid caravanners and motorhomers who have enjoyed a lifetime of caravan experience, as well those who have recently bought vehicles. This experience means we understand what you need on site.



## What is Whale IC?

### Whale Intelligent control

#### A new innovation in system control

The latest in a long line of innovation from Whale®, Whale's IC products offer advanced technology systems for caravans and motorhomes. Intelligent Control is built into these products to offer you our most advanced trouble-free water and heating supply ever!

#### **i Van intuitive touch screen control panel**

The easy way to control your living environment

#### **Wireless Control of Whale® Water heater, Space Heater and water pump (optional)**

Find out more: page 12



#### **Our New Watermaster IC Pump Controller**

- Ensures that you never need to adjust your pressure switch again, enjoy a smooth constant water supply
- Never let your pump run dry
- Protect and prolong your submersible pump life

Find out more: page 14




# NEW i Van® Control Panel

**The easy way to control your living environment**  
**Simple, intuitive touchscreen display**  
**Easy to set programmable timer**



- Simple** – Intuitive icons
- Wireless** – Proven home automation technology
- Intelligent** – Easy to use
- Control** – Easy to set timers and boost functions
- Hub** – One control panel for water heating, room heating and water supply

- The easy way to control your living environment
- Simple, intuitive touchscreen display
- Easy to set programmable timer



Pump control module is only available on IV1002B.  
 Please note: i Van® is available to vehicle manufacturers only.

Modern and stylish intelligent control panel for Whale® Water heaters, Space Heaters and Water Pumps

## How does Whale i Van® work?

The intuitive touchscreen control panel communicates wirelessly with Whale® Water and Space Heaters, creating your ideal living environment with ease. It simply guides you through setting your water heating and air temperature controls, and also allows you to set automatic timers (up to 3 per day) for each unit individually.



Product Code	Description
IV1001B	i Van® with water and space heater control
IV1002B	i Van® with water heater, space heater and pump control

Available to manufacturers only

## Easy to set programmable heaters timers\*

- Up to 3 programmable settings per day, per unit
- Control temperature and power separately

Room Timer Settings			Water Timer Settings	
1000W	8:00 - 9:00	18°C	750W	6:30 - 9:00
500W	11:00 - 14:00	18°C	1500W	12:00 - 14:00
1000W+Gas	16:00 - 22:00	21°C	600W+Gas	16:00 - 19:00

\*Example timer settings shown are based on a site with amp usage limited to 10 Amps (approx. 2300W), and allows for other powered equipment to run simultaneously e.g. kettle/toaster etc.

Visit [www.whalepumps.com](http://www.whalepumps.com) for more information on i Van® features, instructions and video guides

**Simple / Wireless / Intelligent / Touchscreen / Control / Hub**

Please note: i Van® is available to vehicle manufacturers only

# NEW Watermaster® IC Pump Controller


## Intelligently controls the submersible pump for trouble-free operation and peace of mind



- **Never adjust your pressure switch again**
  - Enjoy a smooth, constant water flow
- **Never let your pump run dry**
  - Protect and prolong your submersible pump's life



Watermaster IC Pump Controller unit – fits easily to back of socket



Easily retrofitted to a Whale Watermaster pressure switch socket (ES1001 or ES5001)

### How does Watermaster® IC Pump Controller work?

In a pressure based water system a surge in battery voltage can cause the internal pressure switch in the socket to fluctuate. This leads to pulsations in water flow. Similarly, if the battery voltage drops, the pump may be unable to produce enough pressure to activate the pressure switch and the pump may run on continuously. Also, if the external water container runs out, the pump will continue to run on. This drains the battery and may reduce the life of the pump. Until now, the only solution has been to manually adjust the pressure switch.

**Watermaster® IC Pump Controller** eliminates these problems and the need for pressure switch adjustment. Innovative electronic control circuitry monitors the level of battery voltage and compensates for any surges/reductions in battery voltage that can occur. It also cleverly senses when the water container runs dry and switches the pump off.




Kit Includes:

Watermaster IC Unit  
Watermaster High



Flow Submersible Pump



### Intelligently controls the submersible pump Easily retrofitted to a Whale® Watermaster pressure switch socket (only)

- Stops pump pulsating at high voltages
- Stops pump running continuously at low voltages
- Detects when water container has run out and turns pump off

### Protect and prolong your submersible pump

- No more pressure switch adjustments
- Surge damper no longer required
- Protects and prolongs the submersible pump
- Helps lengthen the battery life
- Built-in fault diagnostics system
- Service free, one-step calibration process
- Easily retro-fitted\*

\*Note - Whale® Watermaster IC is compatible with a Whale® Watermaster pressure switch socket and a Whale® Watermaster High-Flow Pump Only

Intelligent Control **15**



### For use with

Whale Watermaster sockets with built-in pressure switches as pictured above (ES1001 / ES5001)



### Not compatible with

Inline pressure switch systems

### i Product Information

#### Watermaster® IC Pump Controller (with Intelligent Control)

Part No:	EP1632
Voltage:	Voltage range 9.5V d.c. to 14.5V d.c. (normal operation) Voltage range 8.5V d.c. to 9.5V d.c.(limited operation)
Nominal Current:	Operating 3.7 Amps, Standby 0.007 Amps
Recommended fuse size:	5 amp Automotive
Weight:	0.65kg
Materials:	Pump body: ABS, Seals: Nitrile®, Strainer: Polypropylene Impeller: PBT, Cable: PVC, Grease Seal/ Nitrile®. Wire: PVC insulated copper, Hose: PVC, Plug: PBT Watermaster IC: Polycarbonate
Accessories:	WF1230 12 mm in-line water filter (available separately)
Service Kits:	Watermaster IC Pump Controller is not a serviceable part Replacement high-flow submersible pump EP1612

#### Performance

Data @ 13.6V	
Discharge head:	Flow rate per minute / current draw:
0m (0ft)	15.8 ltrs / 3.8 amps
1m (3ft)	14.8 ltrs / 3.7 amps
3m (9ft)	12.8 ltrs / 3.5 amps
Compatible For use with Whale High-Flow pumps: Watermaster (EP1612) ONLY	
Operating temperature range:	30°C to 40°C
Storage temperature range	-30°C to 60°C





## Space / Room Heating

Our room heating product range include models that run on gas or electric or both energy sources.

Our innovative underfloor models help vehicle designers to free up space inside the van.

Simple intuitive controls

For advice on your space heater or for details of your local Whale Authorised Dealer

**Whale Support 0845 2172922**



*Please note: All Whale Space and Water Heater products must be installed and serviced by a qualified gas engineer in accordance with the appropriate installation instructions. Underfloor models available to vehicle manufacturers only.*


# NEW High Output Space Heater

## NEW 4kW High Output Underfloor Space Heater

Higher heat output, maximum performance


### New boost setting balances gas and electric inputs to effectively and efficiently adjust the heat output

- Maintains a comfortable living environment
- Uses both gas and electric for higher powered heating
- New twin ducting system for more installation options and higher heat output
- Mounted underfloor, more space inside
- Lightweight design
- No chimney or flue covers required
- Intuitive and simple controls



Please note: All Whale Space and Water Heater products must be installed and serviced by a qualified gas engineer in accordance with the appropriate installation instructions. Underfloor models available to vehicle manufacturers only.

## Installation



Typical Installation

## Control Panel




- Easy to mount
- Simple to use with position stops to prevent accidental adjustment
- Six Variable Heat Settings:
  - Low/Quiet Night Time Setting
  - Medium Heat Setting
  - High Heat Setting
  - Boost Setting
  - Circulation fan setting
  - Gas Only Setting

- Easy to mount
- Flexible ducts for easy installation
- Flue pipes mounted underfloor for safe and discreet space saving
- Available in 0.75m (FK2075), 1.25m (FK2125) and 2m (FK2020) lengths.

Please note: For space heating accessories see page 28

## Dimensions



### Model Specifications

Model	SH4312B ( underfloor gas & electric)	
Gas	Gas Type	Butane & Propane
	Heat Input (Gross)	2.9kW
	Gas Connection	8mm Compression fitting
	Current Consumption (12V)	1.8 Amps (<22W) (0.01 Amps on stand by)
Electricity	Supply	12V d.c. + 230V a.c. 50 Hz
	Heat Input (Gross)	2.0kW
	Max. Current Consumption (230V)	9 Amps (2kW settings)
	Max Current Consumption (12V)	2.2 Amps (2kW settings)
Gas & Electric	Combined	12V d.c + 230V a.c. 50 Hz

Certified to: ECE\_R 122

## Flue Mounting Options



## Gas and Electric Space Heaters Underfloor Models

External location, more internal living space



### Features and Benefits

- **External location - most compact installation option**
  - More internal living space
- **Lightweight yet robust**
- **Built to withstand harsh external conditions**
- **Weatherproof body**
  - galvanised and sealed
- **Flue system redesigned for shorter depth**
  - more clearance underneath the vehicle
- **No flue vent through the floor removes the risk of water ingress**
- **Quiet night time setting available on electric model**




SH2211B Underfloor Gas Only Model

**3 Year Warranty**




SH2212B Underfloor Gas and Electric Model




### Product Information



SH2211B Underfloor Gas Only Model



SH2212B Underfloor Gas and Electric Only Model



Please see page 24 for specification details

Please note: for space heater accessories see page 26

Please note: All Whale Space and Water Heater products must be installed and serviced by a qualified gas engineer in accordance with the appropriate installation instructions. Underfloor models available to vehicle manufacturers only.

## Gas and Electric Space Heaters - Installed inside the vehicle

- Choose from gas only, or gas and electric models
- Simple and intuitive to use
- More compact installation
- Better insulation
- Improved service access
- Lightweight unit (from only 5.4kg)
- No internal flue or chimney required
- No wiring, simply plug in


3 Year Warranty




Space Heater  
SH2201  
Internal Gas Model

Microprocess  
controlled includes  
fault diagnosis

7.4 KG




Space Heater  
SH2202  
Internal Gas and Electric Model




Typical  
Installation

### **i** Product Information



SH2201 Gas Model  
Installed inside vehicle

SH2202 Gas and Electric Model  
Installed inside vehicle



Please note: All Whale Space and Water Heater products must be installed and serviced by a qualified gas engineer in accordance with the appropriate installation instructions. Underfloor models available to vehicle manufacturers only.

Please see page 24 for specification details  
Please note: for space heater accessories see page 26



# Space Heater Range

## Intuitive and simple controls

- Electric settings 500W/1000W/2000W
- Gas setting
- Circulation fan setting

## Certified to the following directives

- Low Voltage Directive 2006/95/EC
- Gas Appliance Directive 90/396/EEC
- EMC Directive 2004/108/EC
- Vehicle in Motion approved (for motorhomes!)

## Model Specifications

Model	<b>MODEL SH2201 (Internal Gas Only) see page 22-23</b> <b>MODEL SH2202 (Internal Gas and Electric) see page 22-23</b> <b>MODEL SH2211B (Underfloor Gas Only) see page 20-21</b> <b>MODEL SH2212B (Underfloor Gas and Electric) see page 20-21</b>	
Gas	Gas Type	Butane and Propane (29/37 or 30mbar regulators)
	Heat Input (Gross)	2.0 kW
	Gas Connection	8mm Compression fitting
	Current Consumption, (12V)	1.6 Amps (<20W) (0.01 Amps on stand by)
Electricity	Supply	12V d.c. + 230V a.c. 50 Hz
	Heat Input (gross)	2.0 Kw
	Max. Current Consumption, (230V)	9 Amps (2kW settings)
	Max. Current Consumption, (12V)	2.2 Amps (2kW settings)

Please note: All Whale Space and Water Heater products must be installed and serviced by a qualified gas engineer in accordance with the appropriate installation instructions. Underfloor models available to vehicle manufacturers only.

Contact Whale Support for details of your local Whale Authorised Dealer:

**Whale Support 0845 217 2922**



## For advice on your Whale Space and Water heaters



UK

### Whale - Support UK

tel: +44 (0)28 9127 0531  
fax: +44 (0)28 9146 6421

**Whale Heater Support**  
**0845 217 2922**

info@whalepumps.com  
whalepumps.com

**Call us directly for product and installation advice**

## Flue Mounting Flexibility

- Flexible ducts for easy installation
- Flue pipes mounted under floor for safe and discreet, space saving.
- Available in various lengths, 0.75m (FK2075), 1.25m (FK2125), 2m (FK2020)



## Minimal Wiring

- 3 Pin Plug
- Simply plug in
    - no wiring required



## Choice of Vent Colours

- To suit your interior decor (Beige, Black, and Cream)
- Range includes fixed and directional options



Directional Fitting (DX6511)



Fixed Fitting (DX6516)



Directional Fitting (DX6531)



Fixed Fitting (DX6536)



Directional Fitting (DX6521)



Fixed Fitting (DX6526)

## Simple to Use Control Panel

- Simple to use with position stops to prevent accidental adjustment
- Three Heat Settings
  - Quiet Night Time Setting (on electric 500W)
  - Heat Boost Setting (on electric 2000W)
  - Frost Protection Setting
- Easy to mount
- One 3.5m cable with modern connectors



## Range of Ducting Fittings

- For standard 65mm air ducting for cold air inlet and hot air outlet



End Cap Fitting (DX6501)



Straight Fitting (DX6502)



T Fitting (DX6503)



Y Fitting (DX6504)

## Spares

Contact Whale Support for list of available spares

**0845 217 2922**



# Water Heating

Our range of Water Heaters includes high capacity and rapid heat up models

Compact designs more living space

For advice on your Water heater or for details of your local Whale Authorised Dealer

**Whale Support 0845 2172922**



*Please note: All Whale Space and Water Heater products must be installed and serviced by a qualified gas engineer in accordance with the appropriate installation instructions.*


# Water Heater - High Capacity

## More hot water for longer Gas and Electric Storage Water Heater 13L High Capacity

- **Compact design**
  - More internal living space
- **Easy installation**
- **Choice of settings**
  - Fast heat up or low current draw
- **New flue design**
  - Easily installed, no cover required
- **Pressure relief valve with drain function**
  - Drain water system faster
- **Highly durable burner design**
- **Robust polypropylene insulation**
  - Retains heat for longer
  - Shorter re-heat times
- **Simple to use ON/OFF control panel**
- **13 litre capacity**
- **Weighs only 10kg (dry weight)**



## **i** Product Information



Please note: for water heating accessories see page 35

### Model Specifications

Model	WH1302	
Water	Capacity	13 litres
	Pressure relief valve setting	2.6 bar
	Maximum water inlet pressure	1.9 bar
Gas	Gas Type	Butane and Propane CAT I3+ (29/37) CAT I3B/P (30)
	Heat Input (net)	1.25kW
	Gas Consumption	93 g/hr
	Gas Connection	8mm compression fitting
Electricity	Supply	12V d.c. + 230V a.c. 50 Hz
	Electric lowest Eco Setting	600W
	Electric highest setting	1500W
	Max. Current Consumption (12V)	0.36 Amps (0.01 Amp on standby)
	Max. Current Consumption (230V)	2.6 / 5.2 Amp
Approximate heat up times (15 to 70 degrees C)	Gas Operation	43 mins
	Electrical Operation	32 mins
	Gas & Electrical Operation	22 mins
Certified to the following directives	Low Voltage Directive 2006/95/EC	
	Gas Appliance Directive 90/396/EEC	
	EMC Directive 2004/108/EC	
	Directive 74/483/EEC including 2006/96/EE	
	Vehicle Type Approval	

Suitable for: Caravans, Motorhomes and Mobile Applications


Please note: All Whale Space and Water Heater products must be installed and serviced by a qualified gas engineer in accordance with the appropriate installation instructions.




# Water Heater Rapid Heat

## Compact design - fast heat up times Gas and Electric Storage Water Heater 8L Rapid Heat

- **Compact designs**
  - More internal living space
- **Easy installation**
- **Choice of settings**
  - Fast heat up or low current draw
- **New flue design**
  - Easily installed, no cover required
- **Pressure relief valve with drain function**
  - Drain water system faster
- **Highly durable burner design**
- **Robust polypropylene insulation**
  - Retains heat for longer
  - Shorter re-heat times
- **Simple to use ON/OFF control panel**
- **8 litre capacity**
- **Weighs only 8kg (dry weight)**



### **i** Product Information



Please note: for water heating accessories see page 35


#### Model Specifications

Model	WH0802	
Water	Capacity	8 litres
	Pressure relief valve setting	2.6 bar
	Maximum water inlet pressure	1.9 bar
Gas	Gas Type	Butane and Propane CAT I3+ (29/37) CAT I3B/P (30)
	Heat Input (net)	1.25kW
Electricity	Gas Consumption	93 g/hr
	Gas Connection	8mm OD copper tube
	Supply	12V d.c. + 230V a.c. 50 Hz
	Electric lowest Eco Setting	750W
	Electric highest setting	1500W
Approximate heat up times (15 to 70 degrees C)	Max. Current Consumption (12V)	0.36 Amps (0.01 Amp on standby)
	Max. Current Consumption (230V)	6.5 Amps (1.5kW settings)
	Gas Operation	26 mins
Certified to the following directives	Electrical Operation	20 mins
	Gas & Electrical Operation	12 mins
	Low Voltage Directive 2006/95/EC	Gas Appliance Directive 90/396/EEC
	EMC Directive 2004/108/EC	Directive 74/483/EEC including 2006/96/EE
	Vehicle Type Approval	

Suitable for: Caravans, Motorhomes and Mobile Applications

Please note: All Whale Space and Water Heater products must be installed and serviced by a qualified gas engineer in accordance with the appropriate installation instructions.

# Water Heater Range



## One Control Panel

### Includes Easy to Mount and Use Control Panel

- One model 5 settings
- Simple to use Control Panel
- One 3.5m cable with simple connectors



### One model - 5 running options

- Gas only setting
- Electric low setting (600W/2.6A)
- Electric high setting (1200W/5.2A)
- Gas and electric low setting
- Gas and electric high setting

Please note: All Whale Space and Water Heater products must be installed and serviced by a qualified gas engineer in accordance with the appropriate installation instructions.

Contact Whale Support for details of your local Whale Authorised Dealer:


**Whale Support 0845 217 2922**

# Water Heater Accessories

Water Heating **35**

## Easily Assembled Flue

- New aesthetically designed flue
  - In line with type approval
- Innovative design
  - No cover required



## Minimal Wiring

### 3 Pin Plug

- Simply plug in
  - no wiring required



## Spares

Contact Whale Support for list of available spares

**0845 217 2922**

## Ideal Retro-fit

Replace your existing water heater

By using our universal adaptor plate (AK1203)

## Quick Connect Plumbing

### Whale 12mm Quick Connect Pre-Assembled Plumbing

- Quick connection to hot and cold water pipework
- Adaptors for other pipework systems included
- For details on our full plumbing range, contact Whale Support



## Maintenance

- Diagnostics system for easy fault finding
- Easily accessible components

# Water Pumps and Supply

Whale's wide range of Water Supply products include manual and electric pumps, plumbing and accessories all manufactured in the UK to the highest quality standards.

Our renowned Watermaster® range now includes water pumps for fitting outside van or mounting on-board the vehicle.





## Onboard Fresh Water Pump System

Superior showering through improved, consistent flow rate and temperature

- Better all-round flow rates in your caravan
- Self-priming pump, pressure switch and carbon filter all on one unit
- Compatible with Whale Watermaster®, Truma Crystal II® and Truma Compact® sockets
- Upgrades existing microswitch / pressure switch systems
- Runs dry without damage
- Easily replaceable carbon filter (removes nasty tastes and impurities) WF3000 - see page 79 for details




## i Product Information

### Model Specifications

Model	AquaSmart®
Product Code	AQ0814
Open Flow Rate per Min	5.5 ltrs
Voltage	12 V d.c.
Cut Out Pressure	2 bar (30 psi)
Recommended Fuse Size	5 amp automotive
Weight	2.5 kg (5.5 lbs)
Inlet/Outlet on Pump Connections	12 mm Quick Connect
Hose Connections	Fittings included for 3/8" and 1/2" flexible pipework
Materials in Contact with Liquid	Glass-filled Polypropylene, Monprene®, Nitrile®, Stainless Steel, PBT, PVC, Carbon, ABS
Service Kits	Microswitch (AK1317) Plug & filter combo (UH0814) Replacement pump head (AK1318) see page 91
Maximum Head	20 metres (66 ft)
Maximum Lift	3 metres (10 ft)

## Typical Installation



## Tips

1. When the system is first used or if air is sucked into the system when emptying or refilling your water container:
    - Open one hot tap (e.g.kitchen sink)
    - Place carbon filter which is fitted to hose into the water container
    - Insert plug into wall socket and close lid to lock plug in place
    - Switch on 12V d.c. supply to pump
    - When water is flowing smoothly close hot tap and open cold tap to expel remaining air
  2. Use hose retaining clip in plug to hold hose and carbon filter off the ground when not in use
  3. If you do not change your carbon filter as recommended this will invalidate the pump warranty
  4. It is recommended that you change your AquaSmart® water filter every 3000 litres or after approx 30 days use, as debris will build up in the filter and effect the pump's performance
  5. Allow filter to sink to bottom of water container before use
- For guide on caring for your on-board pump see page 87



# NEW Watermaster On Board Water Pump

Delivers smooth consistent flow and runs dry without damage

20% lighter than a Whale Smartflo!\*  
Plus, 8L of water per minute

2 Year Warranty

Vertically mounted to fit into tight spaces

Smooth constant flow from specifically designed diaphragms


Quick Connect 12mm ports

Fully sealed protective motor cover


Rubber feet to absorb vibration



Only 1.48kg!



Plan View



Side View

## Tips

When the system is first used or if air is sucked into the system when emptying or refilling your water container:

- 1 Open one hot tap (e.g.) kitchen sink
- 2 Place hose into the external water container / onboard tank
- 3 Insert plug into wall socket and close lid to lock plug in place
- 4 Switch on 12V d.c. supply to pump
- 5 When water is flowing smoothly close hot tap and open cold tap to expel remaining air

Please note: Following these instructions will maximize the performance of your pump.

Please note: Pump's performance will depend on the plumbing system and restrictions on outlets in your caravan/motorhome.  
\*Based on tests carried out in the Whale® Laboratory, information is correct Sept 2012.

## Product Information

### Model Specifications

Model	Watermaster On Board P2V 8 Litre Capacity
Product Code	FP0814
Open Flow Rate per Min	8 ltrs
Voltage	12V d.c.
Cut Out Pressure	2 bar (30psi)
Recommended Fuse Size	5 amp automotive
Weight	1.48 kg (3.21 lbs)
Inlet/Outlet Size	Whale Quick Connect 12 mm Female
Hose Connections	For 1/2" flexible hose use WU1282 (supplied with pump) For 3/8" flexible hose use WU1280 (not supplied with pump)
Semi-rigid Pipework System Connections	For Whale Quick Connect 12mm NO ADAPTOR REQUIRED 12mm semi-rigid pipe WX7112 (not supplied with pump)
Materials in Contact with Liquid	Glass-filled Polypropylene, Monprene® Nitrile®, Stainless Steel
Service Kits	Microswitch Kit AK1317, Full head service kit AK1318 Strainer replacement AK1320, see page 91
Maximum Wire Size	2.5 mm <sup>2</sup> (13AWG)
Maximum Head	20 m (66 ft)
Maximum Lift	3 m (10 ft)


### Important

- ONLY 8 ltr pressurised pumps are suitable for caravan or motorhome installation
- The inlet strainer included with this product is ONLY suitable for caravan and motorhome installations that ONLY PUMP FROM AN ON BOARD WATER TANK. It is not suitable for mains water connections.


### Watermaster On Board Pump - Typical uses:

- Providing water from tank to taps
- Filling the on-board tank from the outside

#### Typical Installation Standard System



#### Typical Installation Manual System for use with on-board water tanks



For guide on caring for your Watermaster pump see page 87

## The Name Says It All!

- Simplifies the connection between an outside water container into the caravan
- Top performance pump
- Kink-resistant, wipe clean hose for easy storage
- Suitable for microswitch or pressurised systems
- Anti airlock design



## i Product Information

### Product Codes

EP1322

### Watermaster® Range Descriptions

Watermaster® with 12 V d.c. Premium pump and plug compatible with Truma Crystal II® & Compact® socket (light blue hose)

EP1622

Watermaster® with 12 V d.c. High Flow pump and plug compatible with Truma Crystal II® & Compact® socket (light blue hose)

EP1312

Watermaster® with 12 V d.c. Premium pump and plug for Whale® Socket (dark blue hose)

EP1612

Watermaster® with 12 V d.c. High Flow pump and plug for Whale® Socket (dark blue hose)

EP1322 and EP1622 Models Feature Whale Easyplug - Simply squeeze and pull to disconnect



## Tips

EP1322 and EP1312 Watermaster® with Premium Pump recommended for multi outlet applications

EP1622 and EP1612 Watermaster® with High Flow Pump with higher flow rate for showering

## i Product Information

### Model Specifications

	Watermaster
Weight	0.5 kg (1.06 lbs)
Fuse	5 amp Automotive
Materials	Pump Body: ABS, Seals: Nitrile®, Strainer: Polpropylene, Impeller: Stainless Steel / PBT, Cable: PVC, Grease Seal: Nitrile®, Wire: PVC insulated copper, Hose: PVC, Plug: PBT

### Performance Data Flow Rate Per Minute / Current Draw

Model Product Code Discharge Head	Premium EP1312 & EP1322	High Flow EP1612 & EP1622
0m (0 ft)	13.2 litres 3.6 amps	15.8 litres 3.8 amps
1m (3 ft)	11.75 litres 3.3 amps	14.8 litres 3.7 amps
3m (9 ft)	9.25 litres 2.9 amps	12.8 litres 3.5 amps

Please note: Pump performance may vary depending on the plumbing system and restrictions on outlets in your caravan



See page 14 for New Watermaster IC Pump Controller for use with EP1612 pump and ES1001 / ES5001 Sockets



Watermaster® Socket



Hose holder keeps hose clean when refilling Aquaroll

## You may also like


Aquasource Clear Whale's Inline Water Filters see page 78

Whale Tap Range see pages 63-75

## Tips

- To lubricate "O" ring and make connection of plug to socket easier, use a water-based lubricant such as silicone grease. Please note: Do not use vaseline to lubricate "O" ring
- The plug on EP1312/EP1612 incorporates a clip to hold hose and pump from the ground while not in use
- The plug on EP1322/EP1622 incorporates an easy release mechanism to disengage plug from retaining wings - simply push in sides for easy release

Replacement Sockets are available to easily retro-fit



**Product Codes Watermaster Range Descriptions**

<b>ES1000</b>	Whale® socket compatible with microswitch taps and AquaSmart® system for Submersible pump systems (ivory)
<b>ES1001</b>	Whale® socket with built in pressure switch (ivory) Watermaster® Socket Microswitch Service Kit AS5005 (see page 65) Watermaster® Service Kit AK8834 (see page 91)
<b>ES5000</b>	Whale® socket with Microswitch (white)
<b>ES5001</b>	Whale® socket with built in pressure switch (White)
<b>ES5002B</b>	Whale® socket for motorhome

Easy fit replacement lid kits allow you to replace lost / broken covers without replacing the entire socket



**NEW**  
See page 14 for New Watermaster IC Pump Controller for use with EP1612 pump and ES1001 / ES5001 Sockets


Maximises capacity while saving space with underfloor fitting

- Tri wall construction
  - Helps delay freezing
- Electronic control module.
  - Monitors water level.
- Easy fill with float switch cut off
  - No water wasted when filling from outside Aquaroll
- Automatic float switch change over system
  - Switches to outside Aquaroll automatically
- Whale easy drain – hands off operation
  - Simply drained by lifting & rotating handle inside the vehicle



**Model Specifications**

Model	40L water tank	
Product Code	WT4100B	
Construction	Tri-wall	Polyethylene / Foam Polyethylene / Polyethylene
Capacity	38.5 litres	
Dry Weight	5.3kg	
Tank Chassis Support Bracket	3mm galvanized steel	
Control Module	Float Switch Body	Polypropylene
	Easy Drain Handle	ABS
	Easy Drain Stem	Acetal
	Level Sensor Housing	Stainless steel
High Flow Submersible Pump	Optional Extra	(If internal pump not already fitted.)
Voltage	10V d.c. to 14.2V d.c.	
Nominal current Draw:	3.5 amps	
Max Operating Pressure:	1.2 bar	
Fuse:	5 amps automotive	
Pump body:	ABS	



Please note: This product is available to vehicle manufacturers only, not available as a retail product

# Submersible Freshwater Pump Range

## Higher Flow Rates and Greater Life

Compact, quiet, lightweight design suitable for use with pressure switch and microswitch systems. Ideal for use pumping from external water containers.

### Standard Pump 10 ltrs/min - GP1002

- Simple, compact and an economical solution
- Ideal for basic, one outlet applications

### Premium Pump 13 ltrs/min - GP1352

- Reliable, general purpose and suitable for multiple outlets
- Long life, very quiet with low power consumption
- An inexpensive way to update a manual to an electric system

### HighFlow Pump 16 ltrs/min - GP1652

- Market leading submersible pump for flow performance suitable for showering

#### i Product Information

1 Year Warranty



#### i Product Information

#### Model Specifications

Model	Standard	Premium	High Flow
Voltage	12V d.c.	12V d.c.	24V d.c.
Pump	Sub	Sub	Sub
Submersible Pump Old Model	GP8015	GP8815	GP8825
Submersible Pump New Model	<b>GP1002</b>	<b>GP1352</b>	<b>GP1354</b>
Fuse Size	5 amp automotive		3 amp automotive
Weight	0.15kg ( 0.3 lbs)		
Connection to Flexible Hose	10 mm bore hose	Suits 10 mm or 13 mm Bore Hose	
Connection to 12 mm Quick Connect Plumbing	WU1211 (Stem Adaptor 11mm - 12 mm) see page 59		
Materials in Contact with Liquid	Pump Body: ABS, Seals: Nitrile®, Strainer: Polypropylene, Impeller: Stainless Steel		

Please note: New model codes are direct replacements for old model codes


Please note: Pump performance may vary depending on the plumbing system and restrictions on outlets in your caravan/motorhome.

#### Performance Data

#### Flow Rate Per Minute / Current Draw

Model	Standard 12V d.c.	12V d.c.	Premium	24V d.c.	High Flow 12V d.c.
Discharge Head	GP1002	GP1352		GP1354	GP1652
0 m (0ft)	10.3 ltrs 2.4 amps	13.2 ltrs 3.6 amps		13.2 ltrs 1.8 amps	15.8 ltrs 3.8 amps
1 m (3ft)	8.75 ltrs 2.2 amps	11.75 ltrs 3.3 amps		11.75 ltrs 1.6 amps	14.8 ltrs 3.7 amps
3 m (9ft)	5.75 ltrs 2.0 amps	9.75 ltrs 2.9 amps		9.75 ltrs 1.45 amps	12.8 ltrs 3.5 amps

Please note: Pump performance may vary depending on the plumbing system and restrictions on outlets in your caravan/motorhome.



#### For best performance:

- Maximum continuous operation should not exceed 15 minutes
- Do not run pump dry as it will cause pump damage
- Do not use to pump water that is over 60°C
- We recommend the pump stands vertically in the tank
- Before switching on, place the pump in water and shake for a few seconds to release trapped air. This will ensure successful priming and should be repeated after refilling the water tank
- Add an in-line pump into a system to boost water flow (see page 48)

#### Tips



## Boosts Flow in Manual or Electric Pump

- Simple, compact and low-cost pump
- Low power consumption and very quiet
- Ideal for two or three outlets
- Fits unsupported into pipework neatly
- Operates with a microswitched tap, pressure switch or with a separate switch
- Designed for use inline above a submersible electric pump (see pages 46) and a manual foot pump (see page 56-57)



### **i** Product Information


#### Model Specifications

Model	In-Line Premium GP1392	In-Line Premium GP1394	In-Line High Flow GP1692
Voltage	12 V d.c.	24 V d.c.	12 V d.c.
Recommended Fuse Size	5 amp automotive	3 amp automotive	5 amp automotive
Weight	0.15 kg (0.3 lbs)		
Connections to Flexible Hose	Suitable for 10 mm (3/8") or 13 mm (1/2") Bore Hose		
Connection to 12 mm Quick Connect Plumbing	WU1211 (Stem Adaptor 11mm - 12 mm) see page 59		
Materials in Contact with Liquid	Pump Body: ABS, Seal: Nitrile®, Impeller: Stainless Steel		

#### Performance Data

Discharge Head	Flow Rate Per Minute Current Draw		
	0 m (0 ft)	13.2 ltrs 3.6 amps	13.2 ltrs 1.8 amps
1 m (3 ft)	11.75 ltrs 3.3 amps	11.75 ltrs 1.6 amps	14.75 ltrs 3.7 amps
3 m (9 ft)	9.75 ltrs 2.9 amps	9.75 ltrs 1.45 amps	12.75 ltrs 3.5 amps


Please note: Pump performance may vary depending on the plumbing system and restrictions on outlets in your caravan/motorhome.



**Tips** For best performance install the pump in the suction pipe between the foot pump and the water tank, not between the foot pump and tap.

## The Easy Way to Connect to Mains Water

- No need to carry heavy water containers
- Allows a reliable continuous supply of water
- Delivers water without using battery power
- Suitable for use with caravans and motorhomes with either microswitch or pressure switch systems
- Regulates mains water pressure to nominal 1.5 bar (max. 1.8 bar)
- Ideal for use in UK and European Parks with mains water hook-up facilities
- Lay flat hose for easy storage



**FREE** Plug adaptor included



Typical Installation

### Model Specifications

Product Code	EM 9401
Weight	0.9 kg (1.91 lbs)
Hose Connections	3/4" bsp threaded
Hose Length	7.5m
Max. Mains Water Supply Pressure	8 bar (116 psi)
Accessories	7.5 m hose extension (EM9403) see page 93

### Tips

- Ensure your mains tap is turned off when not in use or when van is unattended
- Ensure Aquasource Mains Hook Up is kept in a clean dry storage area away from direct sunlight when not in use
- Can be used as a hose pipe by fitting the plug adaptor to the plug which will allow water to flow

### Important

Please note: To use the Aquasource Mains Water Hook Up with an onboard pump, the inlet strainer (if included with the pump) must be removed.

## The Versatile Portable Pumping Solution!

The Versatile Self-Venting Portable Pump Kit now includes battery clips and a cigar lighter plug to make electrical connection even easier


- Great performance low voltage pump
- Easy to maintain with a wipe clean hose and nozzle
- Suitable for cold and warm water, diesel, light oils and water-based fluids including most water-based pesticides

### The kit now includes

- Low voltage high flow submersible pump
- Nozzle with adjustable on / off, fine spray or a jet of water
- 3.75m (12.5 ft) food quality clear hose
- 3.75m (12.5 ft) cable with battery clips and cigar lighter connector

### Can be used in a variety of applications

- Wash down for car, caravan, motorhome or boat
- Suitable for pumping diesel
- Showering, spraying and garden watering
- Storm water clearance
- Filling on board water tank



## Typical Applications



Pumping Diesel



Wash down



Spraying



Filling on Board Tank

### Model Specifications

Model	Self-Venting Portable Submersible Pump Kit
Product Code	GP1642
Voltage	12V d.c.
Fuse Size	5 amp Automotive
Power Connection	Crocodile Clips and Cigar Light Plug
Weight	0.70 kg
Materials	Stainless Steel, Nitrile®, PVC, Polypropylene, ABS

### Performance Data

Discharge Head	Flow Rate and Current Draw
0m (0ft)	15.8 ltrs/min (3.8 amps)
3m (9ft)	12.8 ltrs/min (3.5 amps)

### Tips

Before switching on, place the pump in water and shake for a few seconds to release trapped air. This will ensure successful priming.

### Warning

Please note the Whale Portable Pump Kit is not suitable for petrol, low flash point liquids or aggressive chemicals. This pump must not be used for pumping petrol or any highly inflammable or corrosive liquids.

# Superfil Pump Kit

## The Easy Way to Fill Caravan / Motorhome In-board Water / Toilet Tanks from an External Water Supply

- Easy to use
- Compact for storage
- Reliable 13 ltrs/min flow rate submersible pump

### Kit includes

- 12 V d.c. premium submersible pump
- 1.5m black hose and 1.38m cable
- Two pin plug and 12 V d.c. socket for installation
- Full step by step installation instructions



1 Year Warranty

### i Product Information



### Model Specifications

Model	Superfil
<b>Product Code</b>	<b>GP1332</b>
Voltage	12 V d.c.
Pump	Submersible
Fuse size	5 Amp Automotive
Weight	0.15 kg (0.3 lbs)
Materials in Contact with Liquid	Pump Body: ABS, Seals: Nitrile® Impeller: Stainless Steel, Hose: PVC and Polypropylene
Service Kit	Socket / Gasket (AS8092) See page 91



# V Pump


## Vertical Self-Priming Hand Pump

- Ideal where space is limited
- Suitable for pumping freshwater
- Angled spout and adjustable height provide various options for installation
- Capacity is 8 ltrs per minute
- Narrow mounting base allows installation between two sinks
- Delivers a smooth flow on each stroke up and down
- Ideal as a back up pump for electric freshwater systems



### **i** Product Information

Code: GP0650



5 Year Warranty

### Model Specifications

Model	V Pump
Product Code	GP0650
Hose Connections	Suitable for Quick Connect 15 mm plumbing and 13 mm (1/2") Flexible Hose
Weight	0.26 kg (0.6 lbs)
Materials	Pump Body: Acetal, Pump Barrel: Anodized Aluminium Alloy Seals: Neoprene, Nitrile®, Fasteners: Stainless Steel
Maximum Suction Lift	3 m (10 ft)
Maximum Discharge Head	4 m (13 ft)
Maximum Output per Minute	8 ltrs
Service Kit	AK0618 - Service Kit for V Pump, Mk 5, Mk 6, Mk 7 Models see page 91

# Babyfoot® Pump

## Self-Priming Compact Foot Operated Freshwater Pump


- Smooth and easy operation
- Easy to install compact design
- Ideal for installation where space is limited
- Angled design ensures more comfortable operation
- Ideal as a priming pump for use with Whale In-Line electric booster pumps (see page 48)
- Suitable for pumping freshwater and saltwater

Code: GP4618




5 Year Warranty


### **i** Product Information



Front View



Side View



Plan View

### Model Specifications

Model	Babyfoot®
Product Code	GP4618
Hose Connections	Suitable for 13 mm (1/2") Flexible Hose
Weight	0.3 kg (0.7 lbs)
Materials	Pump Body: Nylon, Ports: Acetal, Seals: Neoprene Fasteners: Stainless Steel
Service Kit	AK4615 - Service Kit for Babyfoot® Pump See page 91
Maximum Suction Lift	1.5 m (5 ft)
Maximum Discharge Head	3 m (10 ft)
Maximum Output per Minute	8 ltrs

# Quick Connect Plumbing System

**Whale Quick Connect fittings ensure a high integrity, reliable, plumbing system solution, specifically designed for use in mobile applications.**

## Save Time and Money by Using Whale Quick Connect

Fittings and pipework design ensures easy installation and re-usability of components.

The simple two step installation procedure does not require special tools to make a watertight connection.



## Features and Benefits

- Unique 'Double Gripper' design provides secure lifelong pipework retention even at high pressures
- The innovative 'cage collet' eliminates leaks where fittings are installed close to tight bends
- Collet has internal support ring ensuring o ring seal is held in position and does not distort or leak under pressure
- High integrity single piece moulding ensures the strength of the fittings
- Outer sleeve incorporates collet cover, thus preventing accidental pipework release
- Collet clips are not necessary and therefore reduce installation time
- Pipework includes measured cut marks, designed to be a visual guide to ensure that fittings are pushed fully home

## i Product Information


	<b>Equal Tee</b> WU1202		<b>Shut Off Valve</b> WU1270
	<b>Equal Elbow</b> WU1203		<b>3 Way Valve</b> WU1271
	<b>Equal Straight</b> WU1204		<b>Stem Tee</b> WU1205
	<b>End Plug</b> WU1208		<b>Non-return valve</b> FV1300B
	<b>Adaptor 11 - 12mm</b> WU1211		<b>Stem Shut off valve</b> WU1272
	<b>Tap Tail Adaptor</b> $\frac{3}{8}$ " BSP Male WU1213		<b>Stem Adaptor <math>\frac{3}{8}</math>" Hose (For Elite Taps)</b> WU1280
	<b>Adaptor <math>\frac{1}{2}</math>" BSP Male</b> WU1214		<b>Stem Adaptor <math>\frac{1}{2}</math>" Hose 12mm (For Elite Taps)</b> WU1282
	<b>Tank Fitting</b> WU1212		<b>Adaptor 15-12mm</b> WU1512
	<b>Stem Reducer 15-12mm</b> WU1215		<b>Pipework 12mm Blue</b> 30m WX7112 <b>(For cold water)</b>
	<b>Stem Elbow</b> WU1222		<b>Pipework 12mm Red</b> 30m WX7114 <b>(For hot water)</b>
	<b>Adaptor <math>\frac{1}{2}</math>" BSP Female</b> WU1232		<b>Pipework 15mm Blue</b> 30m WX7152 <b>(For cold water)</b>
	<b>Stem Adaptor <math>\frac{1}{2}</math>" BSP-12mm Male</b> WU1264		<b>Pipework 15mm Red</b> 30m WX7154 <b>(For hot water)</b>
	<b>Mounting Clip</b> WU1265		<b>WX7950</b> Pipework Cutters - must be used to cut Whale Semi-Rigid Pipework

Please note: This illustration is intended as a guide only and represents a typical caravan water and heating system installation. For advice on your specific installation contact Whale support.



## Installation Guide

- Step 1** Cut pipework to length by making a straight clean cut using Whale cutters WX7950 (see fig.1)
- Step 2** Simply push the pipework length into the fitting to the second internal stop (see fig. 2)
- Step 3** To release pipework: Push back the grey collet into the fitting, then hold the collet in and pull out the pipework length (see fig. 3 and 4)



Please note: Do not lubricate the end of the tubing with silicone

## Whale Quick Connect Semi-Rigid Pipework

Whale Quick Connect colour coded semi-rigid pipework is available in 12 mm, Medium Density Polyethylene (MDPE). 15mm is also available in high performance (Whalex) material. The pipework's flexibility enables tight bends to be formed, hence reducing both the number of fittings and time required at installation.

Whale Quick Connect semi-rigid pipework offers the integrity of metal, but the usability of plastic, and is fully tested and recommended for use with the complete range of Whale fittings.

## Minimum Bend Radii Recommendations

All grades of Whale Quick Connect semi-rigid pipework are flexible and can be bent into a tight radius to facilitate easy installations. This reduces the number of fittings required and the cost of the total water system.

## Temperature Settings

**WARNING:** To prevent scalding, (regardless of the water heating method or the control devices used), the temperature for the hot water supplied to the taps and showers should be controlled in the range of 43 °C to 60 °C

(110 °F to 140 °F) with a fail safe set at 82 °C (180 °F).

**CAUTION:** Ideally, the temperature should be set at 46 °C (115 °F) for health and safety reasons, higher settings will increase the risk of scald injury. Those at greatest risk of scald injury include children, the elderly, disabled, and diabetics.

## Minimum Storage Temperature

The minimum dry storage temperature is -40 °C (-40 °F)

Please note: It is vital that the system is fully winterized to prevent frost damage.



# Taps and Showers


- High quality lightweight taps and showers.
- Modern stylish designs.
- Range includes metal or plastic models for micro-switched or pressure switch water systems.






## Single Lever Kitchen Chrome Tap

- Easy to operate single lever action allows precise flow and temperature control
- Simple to install with a single round hole mounting
- Supplied with 1/2" taptails
- Securing Kit includes: Rubber C washer, metal C clamp, threaded bar with nut and sealing O ring`
- For use in pressurised systems only
- Quality chromed brass with ceramic valves



## Single Lever Vanity Chrome Tap


- Easy to operate single lever action allows precise flow and temperature control
- Simple to install with a single round hole mounting
- Supplied with 1/2" taptails
- Securing Kit includes: Rubber C washer, metal C clamp, threaded bar with nut and sealing O ring`
- For use in pressurised systems only
- Quality chromed brass with ceramic valves



Please note: These taps are intended for use in freshwater systems in recreational vessels / vehicles only and are designed for pressure systems only

## Single Lever Swan Neck Kitchen Chrome Tap

- Easy to operate single lever action allows precise flow and temperature control
- Simple to install with a single round hole mounting
- Supplied with 1/2" taptails
- Securing Kit includes: Rubber C washer, metal C clamp, threaded bar with nut and sealing O ring`
- For use in pressurised systems only
- Quality chromed brass with ceramic valves



### Tips

For guide to drain the filter for winterization see page 85



### Ideal for

For all TT Metal tap models  
Use in pressurised systems only

Please note: These taps are intended for use in freshwater systems in recreational vessels / vehicles only.

## Attractive, lightweight modern domestic style with superb flow

- Easy to operate single lever action allows precise flow and temperature control
- Simple to install with a single round hole mounting
- Lightweight and easily plumbed
- 12 mm Quick Connect plumbing connections built-in
- Ideal for installation where space is limited
- Adaptor plates available
- Retrofits to Whale Elegance taps by using chrome mounting plate, (MT0112)

Easy touch swivel lever



Stylish shine chrome finish

Swivel spout

1 Year Warranty




Light Weight

### **i** Product Information


#### Model Specifications

Model	Long Spout	Short Spout
Finish	Chrome	Chrome
Product Code (With Microswitch)	MT0111	MT0113
Product Code (Without Microswitch)	MT1111	MT1113
Diameter of Mounting Hole	48 mm (1 7/8")	
Materials in Contact with Liquid	Tap Body: Noryl, Spout: ABS	Tap Body: Noryl Spout: Brass
Connection to Quick Connect 15 mm Plumbing	WU1215 or WU1512 - Adaptor 15 mm to 12 mm	
Connection to 10 mm (3/8") Flexible Hose	WU1280 - Stem Adaptor 3/8" Hose	
Connection to 13 mm (1/2") Flexible Hose	WU1282 - Stem Adaptor 1/2" Hose	
Service Kit	Replacement Microswitch RT9000 See page 92	

Elite Long Spout Model



Elite Short Spout Model



#### Tips

For guide on winterization see page 85



#### Ideal for

Use in pressure switch and microswitch systems (with easily replaceable microswitch)

Please note: These taps are intended for use in freshwater systems in recreational vessels / vehicles only.

## Single Lever Showers

- Easy to operate single lever action allows precise flow and temperature control
- Simple to install with a single round hole mounting
- Lightweight and easily plumbed
- 12 mm Quick Connect plumbing connections built-in
- For use in pressure switch and microswitch systems (with replaceable microswitch)
- Ideal for installation where space is limited
- Retrofits to Whale Elegance taps by using mounting plate. (See page 70)




Code: MT0140B / MT0144B

1 Year Warranty

### Model Specifications

Model	Shower
Colour	Chrome and Diamond White
Product Code (With Microswitch)	MT0140B
Product Code (Without Microswitch)	MT0144B
Connect to Quick Connect 15 mm Plumbing	WU1215 or WU1512 - Adaptor 15 mm-12 mm
Connect to 10 mm (3/8") Flexible Hose	WU1280 - Stem Adaptor 3/8" Hose
Connect to 13 mm (1/2") Flexible Hose	WU1282 - Stem Adaptor 1/2" Hose
Hose Length	1.25 m (4 1/8 ft)
Service Kit	See page 92



Please note: These taps are intended for use in freshwater systems in recreational vessels / vehicles only.

# Elegance Tap Range

## Ideal for use with Pressure Switch or Microswitch Systems


- Easy installation
- Ideal where installation space is limited
- Connects directly to Whale Quick Connect 12 mm plumbing
- Full range of mixer and cold only taps
- For systems operating at up to 2.4 bar (35 psi)
- Mixer tap standard outlet comes with combined tap and shower outlet (see page 72)



## i Product Information

### Model Specifications

Model	RT1010	RT1210	RT2010	RT2210	RT2007
Description	Single Tap Cold Only		Mixer Tap Standard Outlet		Mixer Tap Long Outlet
Colour	White				
Hose Connections	12 mm	½" Threaded	12 mm	½" Threaded	12 mm
Materials in Contact With Fluid	Body: ABS, Spout and Valves: Acetal, Seals: Neoprene				
Base Plate (mm)	113 x 55 (4 7/16" x 2 1/8")	113 x 55 (4 7/16" x 2 1/8")	164 x 55 (6 7/16" x 2 1/8")	171 x 62 (6 3/4" x 3 5/8")	164 x 55 (6 7/16" x 2 1/8")
Depth Beneath Surface	92 mm (3 5/8")	60 mm (2 3/8")	92 mm (3 5/8")	60 mm (2 3/8")	92 mm (3 5/8")
Connection to Quick Connect 15 mm	WU1512	WX1532	WU1512	WX1532	WU1512
Connection to 10 mm (3/8") Flexible Hose	WU1280 WU1204	Not Applicable	WU1280 WU1204	Not Applicable	WU1280 WU1204
Connection to 13 mm (1/2") Flexible Hose	WU1282 WU1204	WX1532 WX1584	WU1282 WU1204	WX1532 WX1584	WU1282 WU1204
Service Kits	RT9000 Micoswitch Service Kit see page 92				



**Tips** For guide on winterization see page 64




### Ideal for

Use with Pressure Switch or Microswitch Systems



## Combined Model with Tap and Shower Functions

- Ideal where shower installation space is at a premium
- Retractable hose makes for neat storage when shower is not in use
- Water flow can be temporarily shut off at shower head to maintain mix setting
- One unit can be used as either a worktop mounted tap or a 'pull up style' shower
- 1.7 m (5' 7") long hose
- Connects directly to Whale Quick Connect 12 mm plumbing
- For systems operating at up to 2.4 bar (35 psi)




**2** products in **1**

Light Weight

Code: RT2500  
Combination Mixer Shower Unit  
1 Year Warranty

### Model Specifications

Model	RT2500	RT1470	RT2498
Description	Mixer Combination Tap / Shower with Wall Bracket	Cold Only Combination Tap / Shower	Mixer Combination Tap / Shower
Colour	White		
Hose Connections	12 mm	½" Threaded	½" Threaded
Base Plate (mm)	164 x 55 (6 7/16" x 2 1/8")	164 x 55 (6 7/16" x 2 1/8")	171 x 62 (6 3/4" x 3 5/8")
Depth Beneath Surface	108 mm (4 1/4")	80 mm (3 1/8")	80 mm (3 1/8")
Connection to Quick Connect 15 mm	WX1512	WX1532	WX1532
Connection to 10 mm (3/8") Flexible Hose	WU1280 WU1204	Not Applicable	Not Applicable
Connection to 13 mm (1/2") Flexible Hose	WU1282 WU1204	WX1532 WX1584	WX1532 WX1584
Service Kits	See page 91-92		




Please note: These taps are intended for use in freshwater systems in recreational vessels / vehicles only.

# Swim 'n' Rinse External Shower

## Mixer Shower Designed For External Use


- For easy washdown outside the motor home
- Handset design allows water to be set to the desired temperature and closed minimising water wasted
- Hinged cover provides a neat finish to the unit (lockable cover version also available)
- Connects directly to Whale Quick Connect 15 mm plumbing see page 58
- Mounting hole 125 mm (4 15/16") X 250 mm (9 7/8")



## **i** Product Information

### Model Specifications

Model	Cold Only (no cover)	Cold Only (cover included)	Hot and Cold Mixer (no cover)	Hot and Cold Mixer (lockable cover included)
<b>Product Code</b>	<b>RT1648</b>	<b>RT1649</b>	<b>RT2648</b>	<b>RT2662</b>
Colour	White			
Base Plate	167 mm (6 1/2") X 292 mm (11 1/2")			
Depth Beneath Surface	88 mm (3 1/2")			
Hose Connections	1/2" Male Threaded (BSP / NPT)			
Connection to Quick Connect 15 mm Plumbing	WX1532 - Adaptor Female 1/2" - 15 mm			
Hose Length	2.1 m (7 ft)			
Service Kits	AS5123 Combo handset white - AS5122 Tap / Shower Upgrade (see page 91)			



**Tips** For guide on winterization see page 64



### Ideal for

Use with Pressure Switch or Microswitch Systems

# Water system Accessories

Complete your water system with high quality Whale accessories.

Fit Whale throughout your van's water system for a reliable constant smooth water supply.

## In-Line Pressure Switch

Accessories **77**

**Allows Regulation of the Pressure in your Water System**

- Adjustable cut in / cut out pressure setting
- Suitable for installation into 12mm Whale Quick Connect or 1/2" flexible hose systems
- Controls the pump turning it on and off by sensing changes in water system pressure
- Recommended for use with Whale submersible and in-line booster pumps (see pages 48-49)




1 Year Warranty

Code: WU7207

### **i** Product Information

#### Model Specifications

Model	Pressure Switch
Product Code	<b>WU7207</b>
Weight	0.063 kg (0.14 lbs)
Hose Connections	Suitable for Whale Quick Connect 12 mm and 10 mm (3/8") Flexible Hose
Current Rating	10 amp: 12 V d.c. systems 5 amp: 24 V d.c. systems
Maximum Pressure	2 bar (30 psi)
Materials	Body: Acetal, Seals and Valves: Nitrile®, EPDM Spring: Phosphor Bronze, Fasteners: Stainless Steel
Service Kits	AK7208 - See page 93



- Tips** For guide on adjusting see page 86
- Direction of arrow indicates the direction the water should flow
  - Pressure Switch must be set when running on battery power (12V d.c.)



# AquaSource Clear Water Filter

## For That Refreshing Taste

- Removes unpleasant tastes and smells from water from in board tanks
- Simple installation (free clips included)
- Silverised carbon filter
- Maintenance-free design
- Can be mounted vertically or horizontally
- Suitable for use with Whale Quick Connect and flexible pipework
- Lasts one full season or 4500 litres
- Installed in the freshwater plumbing pipework - usually under the sink see page 60
- Slimline design fits easily into pipework under sink

1 Year Warranty



Code: WF1230 / WF1530

### i Product Information

#### Model Specifications


Product Code	Pipe System Used	Fitting Required
WF1230	Quick Connect 12 mm	Connects Directly Using Whale Quick Connect 12 mm Fittings
WF1530	Quick Connect 15 mm	Connects Directly Using Whale Quick Connect 15 mm Fittings
WF1230	10 mm (3/8") Flexible Hose	Stainless Steel Hose Clips
WF1530	13 mm (1/2") Flexible Hose	Stainless Steel Hose Clips

Maximum Pressure 4 bar (60 psi)

### Tips

For guide to drain the filter for winterization see page 85

Please note: This is NOT a bacterial filter



# AquaSmart® Water Filter

## Removes unpleasant tastes and smells from water

- Simply lift out of water container and twist off / on to replace
- 3000 litres of filtered water
- Silverized carbon filter
- For details of the complete AquaSmart® System please see page 38


Code: WF3000



### i Product Information

1 Year Warranty

## Typical Installation



### Tips

- It is recommended that you change your AquaSmart® water filter every 3000 litres or after approx 30 days of use as smells and debris will build up in the filter and effect the pump's performance
- Allow filter to sink to bottom of water container before use



Easy change filter

Please note: This is NOT a bacterial filter



# Surge Damper

## Smooths Water Flow

- Helps reduce noise and pulsations in the water system
- Protects the pressure switch in pressurised systems
- Suitable for installation into soft hose system
- Supplied complete with mounting clips
- Designed to be mounted in a vertical position
- Connects directly in-line to Whale Quick Connect Plumbing
- For typical installation see page 60

1 Year Warranty




Code: WS7205



### Product Information

#### Model Specifications

Product Code	Pipe System Used	Fitting Required
WS7205	Quick Connect 12 mm 10 mm (3/8") Flexible Hose	Connects Directly Using Whale Quick Connect 12 mm Fittings Stainless Steel Hose Clips
Capacity	150 ml (1/4 pint)	
Maximum Pressure	4 bar (60 psi)	



Front View

### Tips

Install as close to the outlet of the pump as possible or as close to the outlet side of the pressure switch (WU7207). See page 60.

# One Way Valves

## Help Maintain Prime in Manual or Electric Systems

- Available in Plastic and Chromed Brass
- Ideal for use with electric submersible pumps (see page 46)


1 Year Warranty



### Product Information

#### Model Specifications

Product Code	FV1227	FV1235
Hose Connections	Suitable for 13 mm (1/2") Flexible Hose	
Materials	Body: ABS / Chromed Brass, Spring: Phosphor Bronze, Seal: Nitrile®	
Weight	0.04 kg (0.9 lbs)	0.22 kg (0.5 lbs)



### Tips

- Ensure the valve is installed with the arrow pointing in the direction of the water flow
- The one way valve is for maintaining prime over short periods of time. The low restriction design will have a small drip return.

# Electric Solenoid Valve


## Solenoid Valve used for Controlling Potable Water

- Ideal for redirecting water flow for on-board tank filling
- Can be connected to existing 12 mm plumbing
- Fitted with 12 mm Whale Quick Connect fittings for direct connection
- Valves remains closed until 12 V d.c. is applied



Code: WU1273

### **i** Product Information



### **Tips**

When installing the solenoid with a float switch for automatic tank filling cut off,

we recommend that a relay is used to ensure that the solenoid current draw does not damage the float switch.

**WARNING:** During operation the solenoid coil can become hot. Do not leave activated for extended periods of time (more than 15 mins) since the solenoid coil will become hot and unnecessary battery drain may occur.

# Whale help you go caravanning and motorhoming

- Hints and tips guides to help you get ready for the season, prepare for winter
- Extra tips to get the best from your Whale products.

We are here to assist you, contact Whale Support today

**Whale Support**

**0845 2172922**



# Pre-Season Water System Preparation

Follow this guide to prepare your leisure vehicle for the new season

## Why should I follow this Guide?

Over the winter months bacteria can grow in your water system. Particles of minerals and dirt gather in joins and any undrained areas. To check the system hasn't suffered any frost damage over the winter and floods your van.

## After following this guide, change your water filter

If you have a Whale AquaSmart system, change your Whale WF3000 Water Filter.  
If you have an in line filter in your plumbing system, Whale recommend you your plumbing system,  
Whale recommend you use **WF1230 Aquasource Water Filter**.

Close all drain valves in your van's water system.

Re-attach your shower head.

Ensure all taps and showers are positioned over sinks and drains.

Check condition of leisure battery, if it is below 12V please connect to mains electricity supply.

**C'VAN** Rinse out fresh and waste water tanks with water, add a non-caustic cleaning and purifying agent  
**M'HOME** Add a non-caustic cleaning and purifying agent to the fresh water tank.

Completely fill your fresh water tank with tap water.

Leave the hot tap that is furthest away from the water heater fully open, close all remaining taps and showers.

Turn on isolation switch for water pump, normally found on the control panel or in a menu within the control panel's software.

You should hear the pump running or the pressure coming from the open hot tap.

Water will pop and splash as it comes from the hot tap, it will take some time for a flow of water to arrive as the water heater needs to fill up first.

Once an even flow is achieved, work back towards the water heater, opening the next furthest away hot tap until all have been opened and there is a smooth water flow.

The next stage is to close all hot water taps and open the cold water taps in the same order as the hot taps, beginning at the furthest away cold tap.

When an even flow is achieved through all the taps in your van close all the taps.  
The pump should turn off (after a few seconds if it is a pressurised system).

Remain in your van after the pump has stopped and inspect all the taps and shower heads for leaks.  
You may need to dry them down first to spot any leaks). If there is access to the underside of the taps check for water leaks.

### Have you found a water leak?

**NO**      **YES**

While checking the taps and showers you may hear the pump turn on and off a few times.  
If you hear this, turn on and off all the taps for 10 seconds individually to remove any trapped air from the system.

If there is a water leak coming from the connections on the underside of the tap try to push them home or tighten them with a spanner depending on the connections.  
If the leak originates from a crack or an unknown source check the rest of the taps and showers before turning off the water pump. Then drain the water system as the water pressure will continue to escape through the leak and will cause water damage to your van.  
Contact your local dealer to rectify the leak(s).

If the pump continues to run intermittently for short bursts this can indicate a leak as pressure is being lost.  
Follow all the water pipes and check if there is any water leaking from joints or if a pipe is burst.

Should you find a leak at a joint, tighten the joint or push the pipe fully into the Quickfit fitting to dry up the water and wait to see if the problem persists

If you find a burst pipe or damaged tap/shower we recommend that you contact your nearest Caravan/Motorhome dealer.

After the cleaning agent has remained in the system for the required time, purge the system by running 2 or 3 full tanks of water through the system using all taps and showers in the mixed position.

Change your filter.

Finally your system is ready for use.

If you have successfully carried out this guide please check your water heater is functioning correctly, to do this please follow the manufacturers instructions.  
Enjoy the new season.

**Note: These pre-season tips are intended as a general guide only. For servicing and product advice for your specific vehicle, contact Whale Support:**  
Tel: +44 (0)28 9127 0531 Fax: +44 (0)28 9146 6421  
Email: info@whalepumps.com

# Getting Ready for the Winter

Follow this guide to prepare your leisure vehicle for winter

## Do you own a Caravan or Motorhome?

Ensuring that all water is removed from the caravan/ motorhome's pipework, taps and appliances will reduce the risk of frost damage occurring. Frost damage can occur when water left in the system freezes and expands, causing pipework and appliances to split, crack or burst.

Ideally position caravan/motorhome so the drain valves are at the lowest point i.e. tilt the caravan/motorhome or park on a slope.

Turn the pump off.

Open all taps/mixers in the mid position, including the external shower (if fitted).

Remove shower handset (including the external shower, if fitted) and shake water out.

Open water heater drain valve and leave open.

Open on board tank drain valve (if present) and leave open.

Where grey waste tanks are fitted, remove all sink plugs and open the drain tap.

Open any other drain points (if present).

External water components - shake water out of pump/AquaSource/Aquasmart filter assembly and store inside the van.

Internal pump - turn on and allow to run to expel additional water for 2 minutes.

If internal pump is accessible disconnect outlet pipe and turn on pump to purge water into an adequate basin. Only reconnect pump when water system is to be used.

**Before following this guide**, ideally carry out this procedure prior to moving the caravan /motorhome to its winter storage location. (The movement of the vehicle will encourage residual water to drain from the system).

### USER TIP

If mains electric hook up is available and a Whale Space Heater is fitted select 500w electric (-) and set temperature to frost protection.

### USER TIP

Fully drain /empty holding tank and flush tank of toilet in accordance with the manufacturer's instructions.

### USER TIP

Ensure the gas is turned off at the bottle.

### USER TIP

Do not close the fridge door tightly, leave ajar to prevent mildew forming.

### USER TIP

To maintain the battery periodically charge throughout the winter.

\*Please note: Where 'wet' heating systems are fitted, please refer to the manufacturer's instructions for winterising. These winterising tips are intended as a general guide only.

For servicing and product advice for your specific vehicle, please contact Whale Customer Support:

Tel: +44 (0)28 9127 0531 Fax: +44 (0)28 9146 6421  
Email: info@whalepumps.com www.whalepumps.com

Please note: this winterising information is intended as a general guide only.  
For servicing and product advice for your specific vehicle contact Whale Support  
tel: +44 (0)28 9127 0531 fax: +44 (0)28 9146 6421 email: info@whalepumps.com

# Adjusting your Pressure Switch

Your pressure switch is factory set and should not normally require adjustment. However, adjustment may be required if the power supply voltage has varied from the previous setting, either due to battery drainage or higher voltage being supplied when the battery charger is operating. In the event that your pump doesn't switch off when you close the taps, or it pulses on and off rapidly when the taps are fully open, follow these guidelines to re-adjust the pressure switch setting.

## Which Pressure Switch do you have?

**In-Line Pressure Switch**  
Internally located within the water system pipework



Pressure Switch

**Integral Pressure Switch**  
Located on the back of the water inlet socket

Locking Nut



Pressure Switch

## Pressure Switch Setting

Ensure the system, including the heater is full of water and all taps are closed. Refer to your user manual.

Tighten the adjusting screw clockwise until the pump comes on.  
(For integral socket based pressure switches, first loosen the pressure switch locknut in an anti-clockwise direction.)

Open any tap until you have a smooth flow of water, then close the tap.  
You should hear the pump running and the pump running light if fitted will be on.

Return to the pressure switch and turn the pressure switch adjustment screw slowly anti-clockwise until the pump has stopped.  
Turn the screw a further half turn (180 degrees) anti-clockwise.

Check for correct operation by opening and closing all taps individually. The pump should turn on when the cold tap is opened and switch off immediately when the cold tap is closed. NB. There will normally be some pulsations at low flows.

The hot side may take about 10 seconds to react (both on and off) due to cushioning effect in the water heater.

For integral socket based pressure switches, carefully tighten the locknut until it is tight keeping the adjustment screw in position.

### THREE GOLDEN RULES:

1. NEVER allow the pump to run dry
2. NEVER allow the pump to run continuously for more than 15 minutes
3. The pump assembly MUST be unplugged BEFORE putting the pump back into the refilled water container.

If setting of the pressure switch is still not correct you may experience:

Pump running continuously, even with tap closed. If undiscovered, could result in pump failure and flat battery. Most likely causes are that present voltage is significantly lower when last adjusted, or water container is empty. **CURE: Re-adjust switch or refill container**

Pump does not run at all. If not due to blown fuse or faulty connections, then most likely cause is excessive continuous running (see above) **CURE: Replace pump and re-adjust switch**

Pump runs intermittently ON, OFF, ON, OFF etc. Seen as pulsing flow from tap, or as inability to set constant water temperature, water goes hot, cold, hot, cold instead of constant warm. Most likely cause is that present voltage is significantly higher than when last adjusted. **CURE: Re-adjust pressure switch, if problem persists add a Whale Surge Damper (WS7205).**

Pump runs very noisily but does not pump water. Likely to occur after water container has been refilled. Pump is air-locked and is fighting to get air out and water in.

**CURE: Unplug from the socket, allowing pump to flood, and reconnect by plugging in again. The correct sequence when refilling the container is to unplug, put pump into container, then reconnect.**

Pump continues to run for up to 30 seconds after tap is turned off. This is not a problem. This is a characteristic of pressure switch systems caused by the dampening effect of the hot water heater or surge damper on the cold side.

If after following these procedures the system continues to pulse when all taps are closed there may be a leak in the system. Please contact Whale Support for further guidance.

Please note: this Pressure Switch information is intended as a general guide only. For servicing and product advice for your specific vehicle contact Whale Support tel: +44 (0)28 9127 0531 fax: +44 (0)28 9146 6421 email: info@whalepumps.com

**Never adjust your pressure switch again! NEW Watermaster IC Pump Controller page 14**

# Onboard Pump Guide

## WINTERISING


If water is allowed to freeze in the system, it can expand causing pipework and appliances to split, crack or burst. To best avoid this damage, completely drain the water system using the guideline below. Ideally carry out this procedure prior to moving the caravan / motorhome to its winter location. The movement of the vehicle will encourage residual water to drain from the system.

Ideally position the caravan/motorhome so the drain valves are at the lowest point i.e. tilt the caravan/motorhome or park on a slope.

Turn the pump off, open all taps/mixers in the mid position, including the external shower (if fitted)

Remove shower handset (including the external shower, if fitted) and shake water out.

Position manual valve handles as shown below:



Open the water heater and on board tank drain valve (if present) and leave open.

Where grey waste tanks are fitted, remove all sink plugs and open any other drain points (if present), and leave open.

External water components – shake water out of pump/AquaSource/Aquasmart filter assembly and store inside the van.

Internal pump – turn on and allow to run to expel additional water for 2 minutes.

**User Tip** If internal pump is accessible, disconnect outlet pipe and turn on pump to purge water into an adequate basin. Only reconnect the pump with water system is to be used.



# Onboard Pump Guide

## VIBRATIONS

Higher powered onboard pumps naturally tend to be more noisy than smaller, external pumps. However, some steps can be taken to minimise this, as follows:

Regularly replace the submersible carbon filter (WF3000) at least twice a season, as excessive restrictions in the system can cause the pump to work harder.

Air in the system can cause additional noise. Refill the water tank regularly to avoid pumping air through the system, and ensure the o-rings and joints on the suction side of the system are in good condition

Ensure pipework does not vibrate against the floor or walls by moving it clear. Grey pipe insulation can sometimes be used to achieve this.

Earlier pumps were fitted with black (hard) rubber feet, grey (softer) feet which absorb the vibrations more effectively, are available as a replacement free of charge. Please contact Whale Support for details (contact details overleaf).

## PRIMING YOUR SYSTEM

To maximise the performance of your pump, follow these guidelines of how to re-prime your pump every time the water supply is reconnected:

Open one hot tap (e.g kitchen sink).

Place AquaSmart carbon filter (WF3000) into the water container.

Insert plug into wall socket and close lid to lock plug in place.

Switch on 12v d.c. supply to pump

When water is flowing smoothly close hot tap and open cold tap to expel remaining air.

Repeat for all other hot and cold taps.

User Tip It is important that the o-rings on the suction side of the pump are kept in good condition and well lubricated. This will make the connection of the plug to socket easier, and will help keep the water system in good working order. To lubricate the o-rings, use a water-based lubricant such as silicone grease. DO NOT use Vaseline or cooking oil, as this will corrode the rubber.

Please note: these tips are intended as a general guide only. For servicing and product advice for your specific vehicle contact Whale Support  
 tel: +44 (0)28 9127 0531 fax: +44 (0)28 9146 6421  
 email: info@whalepumps.com

**NEW Watermaster on board  
 - Whale's latest water pump page 40**

Fault	Cause	Solution
Pump does not run	No power to pump	Check power supply Attach leads/clean connections
Fuse has blown	Replace fuse-Do not exceed recommended fuse size of 5	Amp automotive
	Blockage in pipework	Check pipework for kinks
Pump runs but no water appears	No water getting to pump	Check that water tank is not empty Check strainer is not blocked Check all connections from tank to inlet of pump are secure - any air leaks will prevent prim
Water leaking at outlet side of pump	Check pipework /fittings for leaks and repair	Pump runs but will not switch off
	Water leaking at outlet side of pump	Check pipework /fittings for leaks and repair Check system drain plugs are closed
	No water	Check water supply level
Pump cycles on and off periodically when all taps are closed. (Normal with a partially opened tap)	Water leaking at outlet side of pump	Check pipework/fittings for leaks and repair Check system drain plugs are closed
	Leak Back	Possibly caused by dirt particles in the valves. This may be cleared by flushing through with clean water. Alternatively, the pump head can be disassembled and the valves carefully cleaned. Pump cycles on and off excessively when tap/s are open
	Excessive back pressure	Check pipework for kinks and filters etc are clear Check shower rose/taps for blockage and repair
Noisy Operation	Pump drawing air	See cause 'No water getting to pump' (see above)
	Noise created by vibration	See overleaf
Low flow	Bore of pipework connection too small	8.5 mm minimum bore recommended Check for kinks in pipework Check pipework is not blocked
Power supply to the pump	*Check power supply to pump uses correct gauge wire (2.5mm <sup>2</sup> /AWG 13) to give full voltage at pump Check battery is not discharged	
Pipework /connections crushed	Replace damaged connections due to overtightened jubilee	clips
Pump too far from water tank	Pump should be situated beside water tank	
	Water leaking at outlet side of pump	Check pipework/fittings for leaks and repair Check system drain plugs are closed
	Pump strainer clogged	Remove clear lid, rinse and replace to main strainer body (retain strainer mesh to lid)

## On Board Pump Guide Servicing

Onboard Pressure pumps are robust products that experience few failures. Most problems that occur can be cured by following the trouble shooting instructions below which may help you diagnose the fault and provide a solution:

### Tips

#### Using and Changing Your Water Filter (WF3000)

It is recommended that you replace your water filter twice a season, after 30 days of continuous use or 3000 litres of water.

Simply twist off to change the filter. When fitting your filter to your water inlet socket the carbon container should always be placed into the water before pushing connection into the socket. This minimizes the risk of trapped air when fitting.

After fitting a new filter, elements of carbon may appear in your water; run a generous amount of water through the system until the water runs clear.



### Tips

#### User Tip Service Kits

There are three serviceable components for the Smartflo:

1. AK1318 - Full Head Assembly Replacement
2. AK1317 - Microswitch Replacement
3. AK1320 - Inlet Strainer Replacement



## Service Kits and Accessories

### Space Heater Accessories

#### Flue Pipe Range:

- FK2075** 0.75m Flue Pipe
- FK2125** 1.25m Flue Pipe
- FK2020** 2m Flue Pipe

#### Ducting Fittings Range:

- DX6501** End Cap Fitting
- DX6502** Straight Fitting
- DX6503** Tee Fitting
- DX6504** Y Fitting

#### Vent Range:

- DX6511** Directional Fitting (Beige)
- DX6521** Directional Fitting (Black)
- DX6531** Directional Fitting (Cream)
- DX6516** Fixed Fitting (Beige)
- DX6536** Fixed Fitting (Cream)
- DX6526** Fixed Fitting (Black)

### Water Heater Accessories

- AK1203** Universal Adapter Plate
- AK1202** Control Unit Extension Cable

### Electric Pump Service Kits

**AK1318 On Board Pump Replacement Pump Head (for Smartflo or Watermaster On Board)**

**AK8834 Watermaster Exterior Pump Service Kit**

- Contains**
- 4 O Rings
  - 1 O Ring
  - 1 Diaphragm
  - 2 Non Return Valves

**AK1317 On Board Pump Microswitch Kit (for Smartflo or Watermaster On Board)**

- Contains**
- 1 Microswitch

**AK1320 On Board Pump Strainer Service Kit (for Smartflo or Watermaster On Board)**

- Contains**
- 12mm Smartflo Quick Connection Filter Assembly

**AS5005 Watermaster Exterior Pump Socket Microswitch Service Kit**

- Contains**
- 1 Microswitch
  - 1 Microswitch Contact Strip

**AS8090 Superfil - Plug & Gasket Service Kit**

- Contains**
- 1 Plug
  - 1 Cover & Gasket

**AS8092 Superfil - Socket & Gasket Service Kit**

- Contains**
- 1 Socket
  - 1 Cover & Gasket

**UH0814 Aquasmart plug and Filter Combo**

### Manual Pump Service Kits

**AK0618 V Pump Service Kit**

- Contains**
- 1 Handle Buffer
  - 1 Cup packing
  - 1 Buffer
  - 1 Valve
  - 1 Valve Stem
  - 1 Gland U Packing
  - 3 O rings

**AK4615 Babyfoot Pump Service Kit**

- Contains**
- Diaphragm
  - Valves
  - O Rings
  - Springs
  - Fasteners

### Elegance Taps & Showers

**AK5030 Tap/Shower Service Kit**

- Contains**
- 8 O-Ring
  - 2 Valve Washer
  - 4 Screw Cover - White
  - 4 Screw Cover - Large White
  - 4 Screw Cover - Beige
  - 4 Screw No.6 csk
  - 4 Screw No.6 pan

**AS5122 Tap / Shower Upgrade Kit - White**

**Contains** 2 Knobs + Spindles  
1 Ring - Blue  
1 Ring - Red

**AS5123 Combo Handset - White**

**Contains** 1 Handset  
1 O-Ring

**AS5020 Elegance Short Outlet - White**

**Contains** 1 O-Ring  
1 Gland Screw  
1 Combo Shower Head

**AS5125 Elegance Long Spout - White**

**Contains** 1 O-Ring  
1 Gland Screw  
1 Handset

**RT9000 Microswitch Service Kit****AS5145 Shower Hose Kit - white**

**Contains** 2 O-Rings  
1 1.5 m Hose Assembly

**AS5147 Shower Hose 2.1m - White**

**Contains** 2 O-Rings  
2 2.1 m Hose Assembly

**AS5149 Shower Hose Connection Service Kit - White**

**Contains** 4 O-Ring  
2 Outer Collar  
2 Hose Ferrule

**AS5623 Combo Handset - Beige**

**Contains** 1 O-Ring  
1 Handset

**AS5625 Elegance Long Spout - Beige**

**Contains** 1 O-Ring  
1 Gland Screw  
1 Handset

**AS5089 Elbow Single Tap Service Kit**

**Contains** 1 Elbow Piece Assembly

**AS5626 Tap / Shower Upgrade Kit - Beige**

**Contains** 2 Knobs and spindles  
1 Ring - Blue  
1 Ring - Red

**AS5146 Shower Hose (1/2" BSP) - White**

**Contains** 1 1/2"-3/8" Bsp Shower Hose 2.1m -1.7m

**AS5148 Hose for Swim'n'rinse**

**Contains** 1 1/2"-3/8" Bsp Shower Hose 2.1m

**AS5050 Shower Elbow Service Kit**

**Contains** 1 Ring  
1 Shower Elbow  
1 O-Ring

**AS5645 Shower Hose Kit - Beige**

**Contains** 4 O-Rings  
1 Shower Socket  
1 Bush  
1 Hose 1.5m  
2 Outer Collar  
2 Hose Ferrule

**AS5649 Shower Hose Connector - Beige**

**Contains** 4 O-Rings  
2 Outer Collars  
2 Hose Ferrule

**Elite Taps & Showers Spares Kits****AK6310 Replacement Spout - Chrome**

**Contains** 1 Nozzle  
2 O-Rings  
1 Spout

**AK6350 Replacement Spout - White**

**Contains** 2 O-Rings  
1 Nozzle (Gold)  
1 Spout

**RT9000 Replacement Microswitches X 2****Accessories****AK7208 In-Line Pressure Switch Service Kit**

**Contains** 1 O ring (valve)  
1 Valve Stem  
1 Microswitch  
1 Valve Spring  
1 O ring (tailpiece)  
1 Diaphragm  
1 Valve

**AK7209 Inline Pressure Switch Service Kit (for grooved stem version - suitable for 12mm Quick Connector)**

**Contains** 1 O ring (valve)  
1 Valve Stem  
1 Microswitch  
1 Valve Spring  
1 O ring (tailpiece)  
1 Diaphragm  
1 Valve

**EM9402 Aquasource Mains Connection**

**Contains** Adaptor to connect to service towers

**EM9403 Aquasource Mains Extension**

**Contains** 7.5m lay flat mains hose  
3 Hose fitting connectors

**EM9406 Aquasource Mains Connector**

**Contains** 1 Push fit female mains connector  
1 Tap connector

**EM9407 Aquasource Plug Adaptor**

**Contains** Adaptor compatible with Truma Crystal II®  
and Compact® Sockets

**AS8836 Dual Connector Plug Assembly Kit**

**Contains** 1 Retaining Screw  
2 O-Rings  
1 Plastic Plug  
4 Screw Grubs  
4 Contact Pins

**AS8839 Cap and Gasket Dual Connector****Abbreviations**

<b>ABS</b>	Acrylonitrile – Butadiene – Styrene
<b>BSP</b>	British Standard Pipe Thread
<b>Ft</b>	Feet
<b>Kg</b>	Kilograms
<b>lbs</b>	Pounds
<b>ltrs/min</b>	Litres per Minute
<b>ltrs</b>	Litres
<b>mm</b>	Millimetres
<b>m</b>	Metres
<b>PBT</b>	Polybutylene Terephthalate
<b>PVC</b>	Polyvinyl Chloride
<b>V d.c.</b>	Voltage (Direct Current)
<b>“</b>	Inches

**AK7208 In-Line Pressure Switch Service Kit**

**Contains** 1 O ring (valve)  
1 Valve Stem  
1 Microswitch  
1 Valve Spring  
1 O ring (tailpiece)  
1 Diaphragm  
1 Valve

**AK7209 Inline Pressure Switch Service Kit (for grooved stem version - suitable for 12mm Quick Connector)**

**Contains** 1 O ring (valve)  
1 Valve Stem  
1 Microswitch  
1 Valve Spring  
1 O ring (tailpiece)  
1 Diaphragm  
1 Valve

**EM9402 Aquasource Mains Connection**

**Contains** Adaptor to connect to service towers

**EM9403 Aquasource Mains Extension**

**Contains** 7.5m lay flat mains hose  
3 Hose fitting connectors

**EM9406 Aquasource Mains Connector**

**Contains** 1 Push fit female mains connector  
1 Tap connector

**EM9407 Aquasource Plug Adaptor**

**Contains** Adaptor compatible with Truma Crystal II®  
and Compact® Sockets

**AS8836 Dual Connector Plug Assembly Kit**

**Contains** 1 Retaining Screw  
2 O-Rings  
1 Plastic Plug  
4 Screw Grubs  
4 Contact Pins

**AS8839 Cap and Gasket Dual Connector****Abbreviations**

<b>ABS</b>	Acrylonitrile – Butadiene – Styrene
<b>BSP</b>	British Standard Pipe Thread
<b>Ft</b>	Feet
<b>Kg</b>	Kilograms
<b>lbs</b>	Pounds
<b>ltrs/min</b>	Litres per Minute
<b>ltrs</b>	Litres
<b>mm</b>	Millimetres
<b>m</b>	Metres
<b>PBT</b>	Polybutylene Terephthalate
<b>PVC</b>	Polyvinyl Chloride
<b>V d.c.</b>	Voltage (Direct Current)
<b>“</b>	Inches

**MUNSTER SIMMS ENGINEERING LIMITED AND WHALE WATER SYSTEMS INC (a subsidiary of Munster Simms Engineering Limited) (“Company”)****STATEMENT OF LIMITED WARRANTY**

The products manufactured and supplied by the Company (“**Products**”), are warranted to be free from material defects in design, workmanship and material under normal use (“**Defects**”) for (unless otherwise extended in advance in writing by the Company) a period of 12 months from date of purchase, save that this warranty shall not apply where the Defect is attributable to defective materials supplied by third parties. In such event, the only remedy of the buyer of the Products (“**Buyer**”) will be against that third party.

This warranty applies only to Products that are properly installed and used in accordance with all oral and written maintenance and operation instructions provided by the Company. The Company shall not be liable for a breach of any of the warranties in this Statement of Limited Warranty if the Buyer makes any further use of the Products after giving the Company notice of any Defect or the Buyer alters or repairs such Products without the written consent of the Company. Products that have been disassembled or modified (without prior written approval of the Company) are not covered by this warranty.

All Products are covered by a 1 year limited warranty (detailed below) from (unless otherwise extended in advance in writing by the Company) date of purchase (“**Standard Warranty**”). In addition to the Standard Warranty, some individual Products are covered by a further warranty, as detailed in Table 1 below (“**Additional Warranty**”).

In the event that any of the warranties offered by the Company are breached, the Company shall (at its discretion) repair, replace or issue a spares kit for the defective Product subject to prior examination at Company premises. If the Company complies with this paragraph, it shall have no further liability for a breach of the warranties in respect of such Products. Adjustment or replacement of defective parts made under this warranty will not extend the warranty period applicable either under the Standard Warranty and/or the Additional Warranty.

The Company shall not bear any costs of removal, installation, transportation, or other charges that may arise in connection with a warranty claim by the Buyer. Such costs shall be the Buyer’s sole responsibility.

No claim in respect of defective Products will be valid unless the alleged defective Products are returned at the Buyer’s expense to the Company for inspection, together with proof of purchase. Non-stock/ special order items are non-returnable by the Buyer in any circumstances, and this warranty does not apply to prototype models.

**EXCLUSIONS:**

The Company shall not be liable for any indirect loss or for any special, incidental, punitive or consequential damages suffered by the Buyer and/or any third party, whether this loss arises from breach of a duty in contract or tort or breach of a statutory duty or in any other way, including, without limitation, loss arising from the negligence, default, breach of duty, non-delivery, delay in delivery or defects or errors in the work undertaken by the Company pursuant to the terms of this Statement of Limited Warranty or in connection with any other claim arising in connection with manufacture and/or supply of the Products.

In particular, the Company shall not be liable (without limitation) for:

- Loss of profits, increased production costs or other economic injury or loss;
- Loss of contracts or opportunity; and/or
- (insofar as is permitted by applicable law) damage to property of the Buyer or any third party.



The Company shall under no circumstances be liable for any breach of its obligations hereunder and/or under any contract governing sale and purchase of the Products (“Contract”) resulting from causes beyond its control including but not limited to fires, strikes, lockouts, insurrection or riots, terrorism or civil disorder, embargoes, wrecks or delays in transportation, requirements or regulations of any governmental authority, tempest, earthquake or other natural disaster, flood, bursting or overflowing of water tanks, failure or shortage of power, fuel or other utilities, or loss of data and/or communications due to causes such as those referred to in this paragraph.

This statement sets out the Company's entire liability in respect of the Products and the Company's liability under this statement shall be in lieu of all other warranties, conditions, terms and liabilities, express or implied, statutory or otherwise howsoever except any implied by law which cannot be excluded.

All warranties, conditions and other terms implied by statute or common law (save for the conditions implied by section 12 of the Sale of Goods Act 1979) are, to the fullest extent permitted by law, excluded from the Contract.

Subject to the remaining provisions of this Statement of Limited Warranty, the Company's total liability in contract, tort (including negligence or breach of statutory duty), misrepresentation, restitution or otherwise, arising in connection with the performance or contemplated performance of the Contract and supply of the Products shall be limited to the Contract price.

Nothing in this Statement of Limited Warranty shall operate so as to exclude or restrict the Company's liability for death or personal injury caused by its negligence. The Company shall NOT be liable for any condition, warranty or representation made by a distributor or other person acting on behalf of the Company unless expressly confirmed by the Company in writing.

This Statement of Limited Warranty shall be governed and construed in accordance with Northern Irish law and all disputes arising in connection hereto shall be submitted to the exclusive jurisdiction of the Northern Irish Courts.

**Table 1:**

Product type	2 years	3 years	5 years	10 years
Smartflo & Watermaster On Board Pump	✓			
Chromed metal taps (TT)	✓			
Smartbail Bilge Pump		✓		
Orca Bilge Pump		✓		
Supersub Bilge Pump		✓		
Space Heater / Water Heater		✓		
Manual Bilge Pump			✓	
Manual Freshwater Pump			✓	
Manual Toilet Pump			✓	
Quick Connect Plumbing fittings				✓
WhaleX tubing				✓

The period of such Additional Warranty shall commence automatically the date the Standard Warranty expires.

Note that these periods may be further enhanced through special offers, or revisions. Please see your product documentation for details.

## DISCLAIMER

All Products are rated and appropriate for use with water unless otherwise specified by the Company. Compatibility and suitability for other liquids should be verified in writing by the Company prior to such use. All specification information on Products included in Product literature is based on tests using clean cold water unless otherwise specified. Any performance / specification figures shown have been calculated using standard testing procedures. Where maximum output is stated, such maximum output refers to pumps acting at zero lift and zero head. Actual performance may vary depending on the application, installation and environmental factors. Neither the accuracy nor completeness of the information contained in any Product brochure is guaranteed by the Company and may be subject to change at its sole discretion. The Company may, at its sole discretion, change the technical performance, dimensions or appearance of any of its Products without prior notification to purchasers. The Company shall not be liable to a purchaser for any indirect or consequential loss or damage (whether for loss of profit, loss of business, depletion of goodwill or otherwise), costs, expenses or other claims for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use of a Product. Where dimensions are stated, such dimensions are for guidance only. Inch measurements are conversions from millimetre dimensions and are shown to the nearest 1/16". US gallons volumes are conversions from litres and are also shown for guidance purposes only to the nearest 1/16. Please contact the Company directly if precise measurements are required.

Please note: All products shown in this brochure are designed for use in caravan / recreational vehicles and are not suitable for installation in domestic applications. Unless otherwise stated in your manufacturers' user information.

Whale's policy is one of continuous improvement and we reserve the right to change specifications without prior notice. Illustrations are for guidance purposes only.

© Whale® 2013. All rights reserved.

Whale® is a registered trademark of Munster Simms Engineering Ltd, trading as Whale®

Please note that by contacting Whale Support, you will be indicating your consent to receiving product updates, recall information, help guides, and appropriate marketing messages from us via post, email or telephone unless you indicated an objection to receiving such messages.

©2013 Copyright Munster Simms Engineering (also trading as Whale) all rights reserved.

Copyright Whale 2013

All rights reserved.

Whale's policy is one of continuous improvement and we reserve the right to change specifications without prior notice. Illustrations are for guidance purposes only.

Santoprene® is a registered trade name of Advanced Elastomer Systems, LP, an Exxonmobil Chemical Affiliate  
 Delrin®, Teflon® and Neoprene are registered trade names of Dupont Neumeurs and Co.  
 Monprene® is a registered trade name of Technore Apex  
 Truma® Crystal II® Compact® are registered trade names of Truma GmbH & Co.

# Affiliations and Accreditations

## Recreational Vehicle Builder Technical Partnership

Our technical support team of highly skilled engineers work in partnership with recreational vehicle builders around the world. This collaboration delivers bespoke systems that are ideal for each builder, saving both time and money.

## Quality Assurance

All Whale electrical products have the appropriate CE Mark, hence conforming to the relevant European Union Standards. It is not advisable to install electrical products which do not carry the CE Mark.

Our company aims to consistently provide the highest quality products and customer service, delivered through efficient engineering and production processes. Our success has been recognised through gaining ISO 9001:2008, Quality Management System and ISO14001:2004, Environment Management System and BS OHSAS 18001: 2007 Health and Safety Management System.

## Whale Trade Names

Whale®, Babyfoot®, AquaSmart®, Smartflo®, i Van®, Whale IC®, IC Logo Device® Watermaster® are trade names of Munster Simms Engineering Limited, Bangor, Northern Ireland. (Also trading as Whale)



## Patent and Design Registration Applications

### SPACE HEATER / WATER HEATER RANGE pages 16 to 35

International PCT Patent Application WO 2011/029826.

### WHALE WATER HEATER RANGE pages 30 to 35

### DUAL ELECTRICAL ELEMENT WITH SINGLE THERMOSTAT

Patents pending in Europe (10705275.5), Australia (AU 2010213125) and New Zealand (NZ 595169).

### WATERMASTER EXTERIOR RANGE page 40 to 41

Patents pending in Europe (11184422.1) and the United Kingdom (1117353.1).

### AQUASMART page 38 to 39

This product is protected by the following granted patent: United Kingdom Patent No. GB 2 409 703.

### AQUASOURCE page 50 to 51

This product is protected by the following granted patent: United Kingdom Patent No. GB 2 289 747.

### WATERMASTER IC PUMP CONTROLLER page 14 to 15

Patents pending for water supply for a mobile home in UK Patent No. GB2409703B.

### WATERMASTER ON BOARD page 40

Patents pending: 1214335.0

### WATERMASTER IC page 14

This product is protected by the following pending Patent Application Patent UK Application No. 1017025.6



## Customer Support Services

Whale employees are committed to providing excellent customer service, product installation and maintenance advice.



## Whale Customers Say...

“I find it very refreshing that Whale water systems obviously cares for its customers over the smallest detail.”

**Geoffrey Beaven**

“It is refreshing to find a manufacturer, that not only supplies first rate products but also gives excellent back-up service...”

**Brian Jarvis (Caravan Owner)**

“This has got to be the finest after sales service I have experienced. What a superb company to deal with.”

**Rodney Grainger, Caravan Owner**

Whale  
Munster Simms Engineering Ltd.  
Old Belfast Road, Bangor, BT19 1LT, N.Ireland  
tel: +44 (0)28 9127 0531 fax: +44 (0)28 9146 6421  
info@whalepumps.com whalepumps.com





### Whale - Support UK

tel: +44 (0)28 9127 0531  
fax: +44 (0)28 9146 6421

#### Whale Heater Support

**0845 217 2922**

info@whalepumps.com  
whalepumps.com

**Call us directly for product and installation advice**