

BOTANY DELUXE START UP INSTRUCTIONS

1. Remove the cabinet panels from underneath the spas touch pad.
2. Remove both filters from the spa (see page 16 in your user manual).
Place a hose in the filter box to fill the spa with water (see page 14 in your user manual).
(Remove the fittings from your hose to prevent them falling into the spas plumbing).

As the spa is filling with water check all barrel unions inside the cabinet for any leaks as it is possible for these fitting to have worked their way loose in transport. The barrel unions are the fitting which connect the pumps to the plumbing.

Also set your main diverter on the spa to the centre so that both sides of the spas plumbing will fill up with water. The main diverter is the largest handle on the top side of your spa.

Fill the spa until the water level covers the top of the highest jet.
(The two shoulder jets in your spa are not to be under the water level)

Note: Do not leave your spa exposed to the sun with-out water in it and the hardcover on, this will cause the spa to delaminate and is not covered under warranty (this can happen within a 30 minute period if it is a hot enough day). It is extremely important that you fill your spa with water and fit the hardcover as soon as the spa is put outside even if your electrician is not coming straight away.

3. Have a qualified electrician connect the spa to power. The power supply your electrician needs to connect is 15Amp Single Phase with the appropriate sized RCD in your houses metre box. The wiring diagram can be found on page 10 of your user manual. The panels to remove from the spa to find the electrical connection point will be the panels directly underneath the digital touch pad on the spa.

Your electrician can drill a hole anywhere through the fibreglass base to pull the electrical cable through. Just make sure that the area behind where they drill is clear of any spa parts inside the cabinet.

Once the spa has power connected to it and it is filled with water turn the power on. Never turn the spa on if you do not have it filled with water. The spa will go through a self-check mode where you will see a series of numbers appearing on the screen, allow the spa to go through this procedure and do not press any buttons on the control pad. After 6 minutes the spa will turn itself on and run for approx. 10 minutes, please let it go through this procedure until it turns itself off.

4. Your spa has an inbuilt Aroma Therapy stick, it is the smallest plastic fitting on the topside of the spa. You will need to unscrew the stick from the spa and remove the plastic transport cover by unscrewing the blue cap and sliding the opaque cover off to expose the scented stick inside, screw the blue cap back onto the aroma stick leaving the opaque cover off. Reinstall the stick back into the spa, turning the handle to the right works the aroma scent when you have the air blower turned on. Turning the handle to the left will turn off the aroma scent off.
5. Go to page 17 in your user manual and follow the instructions to set your desired temperature and make sure the spa is in standard mode.
6. Go to your chemical instructions and balance the spas water.