

15" (14.0" VIS) XSD™ monitor



- 15-inch (14.0" VIS) color monitor with excellent front of screen performance for use with MACs and PCs
- Autoscan covers horizontal frequencies up to 54 kHz offering a maximum resolution of 1024 x 768 with flicker free display of 800 x 600 at up to 87 Hz
- Flat square CRT with 0.28 mm dot pitch (0.24 hdp)
- XSD-Xtra Space Design saves desk space: World's shortest 15-inch conventional monitor with maximum depth of only 379 mm/14.9"



Optional
USB HUB
PCUH411

Let's make things better.



PHILIPS

15" (14.0" VIS) XSD™ monitor



Technical Specifications

CRT

- Size (inch/cm) 15"/ 36 cm
- Deflection angle (degrees) 90°
- Dot pitch/ Grille pitch 0.28 mm
- Horizontal pitch 0.24 mm
- Tube type Shadow mask, Flat Square, Glare, Light Transmission 57%
- Phosphor P22
- Recom. display area(mm) 270 x 202 mm
- Recom. display area(inch) 10.6" x 8.0"
- Max. display area(mm) 284 x 213 mm
- Max. display area(inch) 11.2" x 8.4"

Scanning

- Horizontal scanning 30 - 54 kHz
- Vertical scanning 50 - 120 Hz

Video

- Video dot rate 65 MHz
- Input impedance
 - Video 75 Ohm
 - Sync 2.2k Ohm
- Input signal levels 0.7 Vpp
- Sync input signal Separate sync
- Sync polarities Positive and negative

White color temperature

Chromaticity CIE coordinates:

- at 9300 K: x=0.283, y=0.297

Resolution and preset modes

- Max. resolution 1024 x 768
 - Recom. resolution 800 x 600
 - 10 user definable modes
 - 6 factory preset modes:
- | | H.freq (kHz)/V.freq (Hz) |
|------------|--------------------------|
| 640 x 400 | 31.5K/70 |
| 640 x 480 | 31.5K/60 |
| 640 x 480 | 37.5K/75 |
| 800 x 600 | 46.9K/75 |
| 800 x 600 | 53.7K/85 |
| 1024 x 768 | 48.4K/60 |

Plug and play compatibility

- Display Data Channel DDC 2B (VESA)
- Microsoft® Windows® 95/98/Me & 2000/NT/XP compatible

Power management

Complies with EPA Energy Star and NUTEK specifications

- Operation 65 W (typical)
- Suspend/Stand By mode < 8 W
- Off mode/Deep Sleep < 8 W

Low-emission characteristics

- Complies with MPR-II specifications

Monitor controls and functions

- Front
 - Power on/off
 - Contrast
 - Brightness
- On Screen Display
 - Language (English, Spanish, French, German, Italian, Chinese), zoom, horizontal, vertical, pincushion, balanced, trapezoid, parallelogram, color, reset, degauss, moire, serial number, resolution, frequency

Connections and Cables

- Connections
 - Video 15-pin D-sub
- Cables D-Sub Video cable(fixed), power cord

Physical specifications

- Dim. incl. base (WxHxD)(mm) 358 x 380 x 379
- Dim. incl. base (WxHxD)(inch) 14.1" x 14.9" x 14.9"
- Dim. excl. base (WxHxD)(mm) 358 x 335 x 379
- Dim. excl. base (WxHxD)(inch) 14.1" x 13.2" x 14.9"
- Weight (kg) 11.7 kg
- Power supply 90 - 264 VAC, 50/60Hz
- Temperature (operational) 0°C to 40°C/ 32°F to 104°F
- Temperature (storage) -25°C to 65°C/ -13°F to 149°F
- Relative humidity 5% to 95%
- MTBF > 50,000 H

Other

- USB Hub option type: PCUH411

As an Energy Star partner, Philips has determined that this product meets the Energy Star guidelines for energy efficiency.
Microsoft and Windows are registered trademarks of Microsoft Corporation
All trademark acknowledged. Copyright 2001 Koninklijke Philips Electronics N.V.

All data subject to change without notice

Release date: May 2002

www.philips.com

Let's make things better.



PHILIPS