

Overview

Models

HP A-MSR20-10 Router	JD431A
HP A-MSR20-11 Router	JF239A
HP A-MSR20-12 Router	JF241A
HP A-MSR20-12-W Router	JF807A
HP A-MSR20-12-T Router	JF806A
HP A-MSR20-13 Router	JF240A
HP A-MSR20-13-W Router	JF808A
HP A-MSR20-15-A Router	JF237A
HP A-MSR20-15-A-W Router	JF809A
HP A-MSR20-15-I Router	JF236A
HP A-MSR20-15-I-W Router	JF238A
HP A-MSR20-15 Router	JF817A

Key features

- WAN, LAN, wireless, voice, firewall all-in-one box
- Compact design for both desktop and rack mount
- Both fixed-port and modular design
- Embedded encryption, firewall, security feature
- Unified and ease management

Product overview

The HP A-MSR20-1x Series is a set of full-featured, economical routers designed for converged WAN, wired, and wireless LAN traffic at enterprise branch locations and small to medium-sized businesses. They deliver high performance while reducing complexity, simplifying management, and increasing control. These routers enable an agile and flexible network infrastructure that can quickly adapt to changing business requirements, while delivering integrated, concurrent services on a single, easy-to-manage platform.

Features and benefits

Quality of Service (QoS)

- **Traffic policing:** supports Committed Access Rate (CAR) and line rate
- **Congestion management:** supports FIFO, PQ, CQ, WFQ, CBQ, and RTPQ
- **Congestion avoidance:** weighted Random Early Detection (WRED)/RED
- **Other QoS technologies:** support traffic shaping, FR QoS, MPLS QoS, and MP QoS/LFI

Management

- **Industry-standard CLI with a hierarchical structure:** reduces training time and expenses, and increases productivity in multivendor installations
- **Management security:** multiple privilege levels, with password protection, restrict access to critical configuration commands; ACLs provide telnet and SNMP access; local and remote syslog capability allow logging of all access
- **SNMPv1, v2, and v3:** provide complete support of SNMP; SNMPv3 supports increased security using encryption; provide full support of industry-standard MIBs plus private MIB extensions
- **Remote monitoring (RMON):** uses standard SNMP to monitor essential network functions; supports events, alarm, history, and



Overview

statistics group plus a private alarm extension group

- **FTP, TFTP, and SFTP support:** File Transfer Protocol allows bi-directional transfers over a TCP/IP network and is used for configuration updates; Trivial FTP is a simpler method using UDP
- **Debug and sampler utility:** supports ping and traceroute for both IPv4 and IPv6
- **Network Time Protocol (NTP):** synchronizes timekeeping among distributed time servers and clients; keeps consistent timekeeping among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time
- **Info center:** provides a central information center for system and network information; aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity; outputs the network information to multiple channels based on user-defined rules
- **Management interface control:** provides management access through modem port and terminal interface; provides access through terminal interface, telnet, or SSH
- **Network Quality Analyzer (NQA):** analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays; allows network manager to determine overall network performance and diagnose and locate network congestion points or failures

Connectivity

- **Packet storm protection:** protects against broadcast, multicast, or unicast storms with user-defined thresholds
- **Loopback:** supports internal loopback testing for maintenance purposes and an increase in availability; loopback detection protects against incorrect cabling or network configurations and can be enabled on a per-port or per-VLAN basis for added flexibility
- **3G access support:** allows use of SIC 3G module for high reliability; supports popular USB 3G modem
- **Flexible port selection:** provides combination of fiber and copper interface modules, 100/1000Base-X auto-speed selection, and 10/100/1000Base-T auto-speed detection plus auto duplex and MDI/MDI-X
- **Multiple WAN interfaces:** provide a traditional link with Serial, E1/T1, ADSL, and ISDN/AM backup; provide high-density Ethernet access with WAN Fast Ethernet/Gigabit Ethernet and LAN 4- and 9-port Fast Ethernet; provide mobility access with 11g/n Wi-Fi and 3G
- **High-density port connectivity:** 1 interface module slot and up to 10 Fast Ethernet ports

Performance

- **Powerful encryption capacity:** includes embedded hardware encryption accelerator to improve encryption performance
- **Flexible chassis selection:** offers a choice 12 routers; meets different requirements on enterprise branches
- **Excellent forwarding performance:** provides forwarding performance up to 160 Kpps; meets today's and future demand for an enterprise organization's bandwidth-intensive applications

Resiliency and high availability

- **Virtual Router Redundancy Protocol (VRRP):** allows a group of routers to dynamically back each other up to create highly available routed environments
- **Backup Centre:** functions as a part of the management and backup function to provide backup for interfaces on your device; delivers reliability by switching traffic over to a backup interface when the primary one fails

Layer 2 switching

- **Spanning Tree:** fully supports standard IEEE 802.1D Spanning Tree Protocol, IEEE 802.1w Rapid Spanning Tree Protocol for faster convergence, and IEEE 802.1s Multiple Spanning Tree Protocol
- **IGMP and MLD snooping:** effectively control and manage the flooding of multicast packets in a Layer 2 network
- **Port mirroring:** duplicates port traffic (ingress and egress) to a local or remote monitoring port
- **VLANs:** support IEEE 802.1Q-based VLANs

Layer 3 services



Overview

- **Address Resolution Protocol (ARP):** determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network
- **User Datagram Protocol (UDP) helper:** redirects UDP broadcasts to specific IP subnets to prevent server spoofing
- **Dynamic Host Configuration Protocol (DHCP):** simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets

Layer 3 routing

- **Static IPv4 routing:** provides simple, manually configured IPv4 routing
- **Routing Information Protocol (RIP):** uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection
- **OSPF:** Interior Gateway Protocol (IGP) using link-state protocol for faster convergence; supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- **Border Gateway Protocol 4 (BGP-4):** Exterior Gateway Protocol (EGP) with path vector protocol uses TCP for enhanced reliability for the route discovery process, reduces bandwidth consumption by advertising only incremental updates, and supports extensive policies for increased flexibility, as well as scales to very large networks
- **Intermediate system to intermediate system (IS-IS):** Interior Gateway Protocol (IGP) using path-vector protocol, which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)
- **Static IPv6 routing:** provides simple, manually configured IPv6 routing
- **Dual stack:** maintains separate stacks for IPv4 and IPv6 to ease transition from an IPv4-only network to an IPv6-only network design
- **Routing Information Protocol next generation (RIPng):** extends RIPv2 to support IPv6 addressing
- **OSPFv3:** extends OSPFv2 to support IPv6 addressing
- **BGP+:** extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- **IS-IS for IPv6:** extends IS-IS to support IPv6 addressing
- **IPv6 tunneling:** is an important element for the transition from IPv4 to IPv6; allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6to4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels
- **Multiprotocol Label Switching (MPLS):** uses BGP to advertise routes across Label Switching Paths (LSPs), but uses simple labels to forward packets from any Layer 2 or Layer 3 protocol, thus reducing complexity and increasing performance; supports graceful restart for reduced failure impact; supports LSP tunneling and multilevel stacks
- **Multiprotocol Label Switching (MPLS) Layer 3 VPN:** allows Layer 3 VPNs across a provider network; uses MP-BGP to establish private routes for increased security; supports RFC 2547bis multiple autonomous system VPNs for added flexibility
- **Multiprotocol Label Switching (MPLS) Layer 2 VPN:** establishes simple Layer 2 point-to-point VPNs across a provider network using only MPLS LDPs; requires no routing and therefore decreases complexity, increases performance, and allows VPNs of non-routable protocols; uses no routing information for increased security; supports Circuit Cross Connect (CCC), Static Virtual Circuits (SVCs), Martini draft, and Kompella-draft technologies
- **Policy routing:** allows custom filters for increased performance and security; supports ACLs, IP prefix, AS paths, community lists, and aggregate policies

Security

- **Access control list (ACL):** supports powerful ACLs for both IPv4 and IPv6; ACLs are used for filtering traffic to prevent illegal users from accessing the network, or for controlling network traffic to save resources; rules can either deny or permit traffic to be forwarded; rules can be based on a Layer 2 header or a Layer 3 protocol header; rules can be set to operate on specific dates or times
- **TACACS+:** is an authentication tool using TCP with encryption of the full authentication request that provides added security
- **MAC authentication:** provides simple authentication based on a user's MAC address; supports local or RADIUS-based authentication



Overview

- **Network login:** standard IEEE 802.1x allows authentication of multiple users per port
- **RADIUS:** eases security access administration by using a password authentication server
- **Network address translation (NAT):** supports one-to-one NAT, many-to-many NAT, and NAT control, enabling NAT to support multiple connections; supports blacklist in NAT/NAPT, a limit on the number of connections, session log, and multi-instance
- **Secure Shell (SSHv2):** uses external servers to securely login into a remote device or securely login into MSR from a remote location; with authentication and encryption, it protects against IP spoofing and plain text password interception; increases the security of SFTP transfers
- **Unicast Reverse Path Forwarding (URPF):** allows normal packets to be forwarded correctly, but discards the attaching packet due to lack of reverse path route or incorrect inbound interface; prevents source spoofing and distributed attacks

Convergence

- **Internet Group Management Protocol (IGMP):** is used by IP hosts to establish and maintain multicast groups; supports v1, v2, and v3; utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks
- **Protocol Independent Multicast (PIM):** is used for IPv4 and IPv6 multicast applications; supports PIM dense mode (PIM-DM), sparse mode (PIM-SM), and source-specific mode (PIM-SSM)
- **Multicast Source Discovery Protocol (MSDP):** is used for inter-domain multicast applications, allowing multiple PIM-SM domains to interoperate
- **Multicast Border Gateway Protocol (MBGP):** allows multicast traffic to be forwarded across BGP networks, separate from unicast traffic

Integration

- **Embedded NetStream:** local and global server load balancing module improves traffic distribution using powerful scheduling algorithms, including Layer 4 to 7 services; monitors the health status of servers and firewalls
- **Embedded VPN firewall:** provides enhanced stateful packet inspection and filtering; provides advanced VPN services with Triple DES (3DES) and Advanced Encryption Standard (AES) encryption at high performance and low latency, Web content filtering, and application prioritization and enhancement

Additional information

- **OPEX savings:** a common operating system simplifies and streamlines deployment, management, and training, thereby cutting costs, as well as reducing the chance for human error associated with having to manage multiple operating systems across different platforms and network layers
- **High reliability:** provides a state-of-the-art unified code base
- **Faster time to market:** engineering efficiencies allow new and custom features to be brought rapidly to the market with better initial and ongoing stability
- **Green initiative support:** provides support for RoHS and WEEE regulations

Product architecture

- **Ideal multiservice platform:** provides data, voice SIP and H.323, LAN switching, wireless, 3G, firewall, and IPSec/SSL VPN all in one box
- **USB interface:** uses USB memory disk to download and upload configuration files; supports external USB 3G modem for 3G WAN uplink
- **Flexible modular design:** multiple types of modules meet different requirements; for example, Smart Interface Cards (SICs) are small and cost-effective modules, Multi-functional Interface Modules (MIMs) are more high-density and affordable modules, Flexible Interface Cards (FICs) provide high reliability and are hot-swappable, and double-width modules provide high density

Warranty and support

- **1-year warranty:** with advance replacement and 30-calendar-day delivery (available in most countries)



Overview

- **Electronic and telephone support:** limited electronic and telephone support is available from HP; refer to: www.hp.com/networking/warranty for details on the support provided and the period during which support is available
- **Software releases:** refer to: www.hp.com/networking/warranty for details on the software releases provided and the period during which software releases are available for your product(s)



Technical Specifications

HP A-MSR20-10 Router (JD431A)

Ports	1 S1C slot 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full 4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
Physical characteristics	Dimensions 9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm) (1U height) Weight 6.61 lb. (3.0 kg)
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	Throughput up to 160 Kpps (64-byte packets) Routing table size 10000 entries
Environment	Operating temperature 32°F to 104°F (0°C to 40°C) Operating relative humidity 5% to 90%, noncondensing Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C) Nonoperating/Storage relative humidity 5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr) Voltage 100-120/200-240 VAC Maximum power rating 25 W Frequency 50/60 Hz Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; CAN/CSA 22.2 No. 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J
Emissions	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B
Telecom	FCC part 68
Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
Notes	Weight is with no optional modules installed.
Services	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E)



Technical Specifications

- 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

(applies to all products in series)

BGP

- RFC 1163 Border Gateway Protocol (BGP)
- RFC 1267 Border Gateway Protocol 3 (BGP-3)
- RFC 1657 Definitions of Managed Objects for BGPv4
- RFC 1771 BGPv4
- RFC 1772 Application of the BGP
- RFC 1773 Experience with the BGP-4 Protocol
- RFC 1774 BGP-4 Protocol Analysis
- RFC 1965 BGP4 confederations
- RFC 1997 BGP Communities Attribute
- RFC 1998 PPP Gandalf FZA Compression Protocol
- RFC 2385 BGP Session Protection via TCP MD5
- RFC 2439 BGP Route Flap Damping

Device management

- RFC 1305 NTPv3
- RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
- RFC 2271 FrameWork
- RFC 2452 MIB for TCP6
- RFC 2454 MIB for UDP6

General protocols

- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- RFC 768 UDP
- RFC 783 TFTP Protocol (revision 2)
- RFC 791 IP
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET

RFC 3036 LDP Specification

- RFC 3046 DHCP Relay Agent Information Option
- RFC 3063 MPLS Loop Prevention Mechanism
- RFC 3065 Support AS confederation
- RFC 3137 OSPF Stub Router Advertisement
- RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
- RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
- RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
- RFC 3214 LSP Modification Using CR-LDP
- RFC 3215 LDP State Machine
- RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
- RFC 3277 IS-IS Transient Blackhole Avoidance
- RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3392 Support BGP capabilities advertisement
- RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
- RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
- RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
- RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
- RFC 3784 ISIS TE support
- RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
- RFC 3811 Definitions of Textual Conventions (TCs)



Technical Specifications

RFC 855 Telnet Option Specification	for Multiprotocol Label Switching (MPLS)
RFC 856 TELNET	Management
RFC 858 Telnet Suppress Go Ahead Option	RFC 3812 Multiprotocol Label Switching (MPLS)
RFC 894 IP over Ethernet	Traffic Engineering (TE) Management Information
RFC 925 Multi-LAN Address Resolution	Base (MIB)
RFC 950 Internet Standard Subnetting Procedure	RFC 3847 Restart signaling for IS-IS
RFC 959 File Transfer Protocol (FTP)	
RFC 1006 ISO transport services on top of the TCP: Version 3	IP multicast
RFC 1027 Proxy ARP	RFC 1112 IGMP
RFC 1034 Domain Concepts and Facilities	RFC 2236 IGMPv2
RFC 1035 Domain Implementation and Specification	RFC 2283 Multiprotocol Extensions for BGP-4
RFC 1042 IP Datagrams	RFC 2362 PIM Sparse Mode
RFC 1058 RIPv1	RFC 2365 Administratively Scoped IP Multicast
RFC 1071 Computing the Internet Checksum	RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 1091 Telnet Terminal-Type Option	RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 1122 Host Requirements	RFC 3376 IGMPv3
RFC 1141 Incremental updating of the Internet checksum	
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	IPv6
RFC 1144 Compressing TCP/IP headers for low-speed serial links	RFC 1981 IPv6 Path MTU Discovery
RFC 1195 OSI ISIS for IP and Dual Environments	RFC 2080 RIPng for IPv6
RFC 1256 ICMP Router Discovery Protocol (IRDP)	RFC 2292 Advanced Sockets API for IPv6
RFC 1293 Inverse Address Resolution Protocol	RFC 2373 IPv6 Addressing Architecture
RFC 1315 Management Information Base for Frame Relay DTEs	RFC 2460 IPv6 Specification
RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)	RFC 2463 ICMPv6
RFC 1333 PPP Link Quality Monitoring	RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 1334 PPP Authentication Protocols (PAP)	RFC 2472 IP Version 6 over PPP
RFC 1349 Type of Service	RFC 2473 Generic Packet Tunneling in IPv6
RFC 1350 TFTP Protocol (revision 2)	RFC 2475 IPv6 DiffServ Architecture
RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)	RFC 2529 Transmission of IPv6 Packets over IPv4
RFC 1381 SNMP MIB Extension for X.25 LAPB	RFC 2545 Use of MP-BGP-4 for IPv6
RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol	RFC 2553 Basic Socket Interface Extensions for IPv6
RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol	RFC 2740 OSPFv3 for IPv6
RFC 1490 Multiprotocol Interconnect over Frame Relay	RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 1519 CIDR	RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
RFC 1534 DHCP/BOOTP Interoperation	RFC 3513 IPv6 Addressing Architecture
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol	RFC 3596 DNS Extension for IPv6
RFC 1552 The PPP Internetworking Packet Exchange	



Technical Specifications

- Control Protocol (IPXCP)
 - RFC 1577 Classical IP and ARP over ATM
 - RFC 1613 Cisco Systems X.25 over TCP (XOT)
 - RFC 1624 Incremental Internet Checksum
 - RFC 1631 NAT
 - RFC 1638 PPP Bridging Control Protocol (BCP)
 - RFC 1661 The Point-to-Point Protocol (PPP)
 - RFC 1662 PPP in HDLC-like Framing
 - RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
 - RFC 1701 Generic Routing Encapsulation
 - RFC 1702 Generic Routing Encapsulation over IPv4 networks
 - RFC 1721 RIP-2 Analysis
 - RFC 1722 RIP-2 Applicability
 - RFC 1723 RIP v2
 - RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
 - RFC 1812 IPv4 Routing
 - RFC 1829 The ESP DES-CBC Transform
 - RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
 - RFC 1944 Benchmarking Methodology for Network Interconnect Devices
 - RFC 1973 PPP in Frame Relay
 - RFC 1974 PPP Stac LZS Compression Protocol
 - RFC 1990 The PPP Multilink Protocol (MP)
 - RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
 - RFC 2091 Trigger RIP
 - RFC 2131 DHCP
 - RFC 2132 DHCP Options and BOOTP Vendor Extensions
 - RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
 - RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
 - RFC 2280 Routing Policy Specification Language (RPSL)
 - RFC 2284 EAP over LAN
 - RFC 2338 VRRP
 - RFC 2364 PPP Over AAL5
 - RFC 2374 An Aggregatable Global Unicast Address Format
 - RFC 2451 The ESP CBC-Mode Cipher Algorithms
 - RFC 2453 RIPv2
 - RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
 - RFC 2511 Internet X.509 Certificate Request
 - RFC 2011 SNMPv2 MIB for IP
 - RFC 2012 SNMPv2 MIB for TCP
 - RFC 2013 SNMPv2 MIB for UDP
 - RFC 2233 Interfaces MIB
 - RFC 2454 IPV6-UDP-MIB
 - RFC 2465 IPv6 MIB
 - RFC 2466 ICMPv6 MIB
 - RFC 2618 RADIUS Client MIB
 - RFC 2620 RADIUS Accounting MIB
 - RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
 - RFC 2737 Entity MIB (Version 2)
 - RFC 2863 The Interfaces Group MIB
 - RFC 2933 IGMP MIB
 - RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
 - RFC 1155 Structure of Management Information
 - RFC 1157 SNMPv1
 - RFC 1905 SNMPv2 Protocol Operations
 - RFC 2272 SNMPv3 Management Protocol
 - RFC 2273 SNMPv3 Applications
 - RFC 2274 USM for SNMPv3
 - RFC 2275 VACM for SNMPv3
 - RFC 2575 SNMPv3 View-based Access Control Model (VACM)
 - RFC 3164 BSD syslog Protocol
- OSPF**
- RFC 1245 OSPF protocol analysis
 - RFC 1246 Experience with OSPF
 - RFC 1587 OSPF NSSA
 - RFC 1765 OSPF Database Overflow
 - RFC 1850 OSPFv2 Management Information Base (MIB), traps
 - RFC 2328 OSPFv2
 - RFC 2370 OSPF Opaque LSA Option
 - RFC 3101 OSPF NSSA
- QoS/CoS**
- IEEE 802.1P (CoS)
 - RFC 2474 DS Field in the IPv4 and IPv6 Headers
 - RFC 2475 DiffServ Architecture
 - RFC 2597 DiffServ Assured Forwarding (AF)
 - RFC 2598 DiffServ Expedited Forwarding (EF)
 - RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
- Security**
- IEEE 802.1X Port Based Network Access Control
 - RFC 1321 The MD5 Message-Digest Algorithm
 - RFC 2082 RIP-2 MD5 Authentication



Technical Specifications

Message Format	RFC 2104 Keyed-Hashing for Message Authentication
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)	RFC 2138 RADIUS Authentication
RFC 2644 Directed Broadcast Control	RFC 2209 RSVP-Message Processing
RFC 2661 L2TP	RFC 2246 Transport Layer Security (TLS)
RFC 2663 NAT Terminology and Considerations	RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5	RFC 2865 RADIUS Authentication
RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)	RFC 2866 RADIUS Accounting
RFC 2702 Requirements for Traffic Engineering Over MPLS	RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
RFC 2747 RSVP Cryptographic Authentication	VPN
RFC 2763 Dynamic Name-to-System ID mapping support	RFC 2403 - HMAC-MD5-96
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)	RFC 2404 - HMAC-SHA1-96
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)	RFC 2405 - DES-CBC Cipher algorithm
RFC 2784 Generic Routing Encapsulation (GRE)	RFC 2547 BGP/MPLS VPNs
RFC 2787 Definitions of Managed Objects for VRRP	RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 2961 RSVP Refresh Overhead Reduction Extensions	RFC 2842 Capabilities Advertisement with BGP-4
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS	RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2973 IS-IS Mesh Groups	RFC 2918 Route Refresh Capability for BGP-4
RFC 2993 Architectural Implications of NAT	RFC 3107 Carrying Label Information in BGP-4
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)	IPsec
RFC 3027 Protocol Complications with the IP Network Address Translator	RFC 1828 IP Authentication using Keyed MD5
RFC 3031 Multiprotocol Label Switching Architecture	RFC 2401 IP Security Architecture
RFC 3032 MPLS Label Stack Encoding	RFC 2402 IP Authentication Header
	RFC 2406 IP Encapsulating Security Payload
	RFC 2407 - Domain of interpretation
	RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
	RFC 2411 IP Security Document Roadmap
	RFC 2412 - OAKLEY
	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-11 Router (JF239A)

Ports	1 SIC slot
	1 Serial port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
Physical characteristics	Dimensions 9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm) (1U height)
	Weight 6.61 lb. (3 kg)
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.



Technical Specifications

Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	5% to 95%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-120/200-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J	
Emissions	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	
Notes	Weight is with no optional modules installed.	
Services	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E) 5 Yr 6 hr Call-to-Repair Onsite (UW081E)	



Technical Specifications

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols

(applies to all products in series)

BGP

RFC 1163 Border Gateway Protocol (BGP)
RFC 1267 Border Gateway Protocol 3 (BGP-3)
RFC 1657 Definitions of Managed Objects for BGPv4
RFC 1771 BGPv4
RFC 1772 Application of the BGP
RFC 1773 Experience with the BGP-4 Protocol
RFC 1774 BGP-4 Protocol Analysis
RFC 1965 BGP4 confederations
RFC 1997 BGP Communities Attribute
RFC 1998 PPP Gandalf FZA Compression Protocol
RFC 2385 BGP Session Protection via TCP MD5
RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
RFC 2271 FrameWork
RFC 2452 MIB for TCP6
RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 855 Telnet Option Specification
RFC 856 TELNET
RFC 858 Telnet Suppress Go Ahead Option
RFC 894 IP over Ethernet
RFC 925 Multi-LAN Address Resolution
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1006 ISO transport services on top of the TCP: IP multicast Version 3
RFC 1027 Proxy ARP
RFC 1034 Domain Concepts and Facilities
RFC 1035 Domain Implementation and

RFC 3036 LDP Specification
RFC 3046 DHCP Relay Agent Information Option
RFC 3063 MPLS Loop Prevention Mechanism
RFC 3065 Support AS confederation
RFC 3137 OSPF Stub Router Advertisement
RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
RFC 3214 LSP Modification Using CR-LDP
RFC 3215 LDP State Machine
RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3392 Support BGP capabilities advertisement
RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
RFC 3784 ISIS TE support
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
RFC 3847 Restart signaling for IS-IS

IP multicast

RFC 1112 IGMP
RFC 2236 IGMPv2
RFC 2283 Multiprotocol Extensions for BGP-4
RFC 2362 PIM Sparse Mode



Technical Specifications

Specification	RFC 2365 Administratively Scoped IP Multicast
RFC 1042 IP Datagrams	RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 1058 RIPv1	RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 1071 Computing the Internet Checksum	RFC 3376 IGMPv3
RFC 1091 Telnet Terminal-Type Option	
RFC 1122 Host Requirements	
RFC 1141 Incremental updating of the Internet checksum	IPv6
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	RFC 1981 IPv6 Path MTU Discovery
RFC 1144 Compressing TCP/IP headers for low-speed serial links	RFC 2080 RIPng for IPv6
RFC 1195 OSI ISIS for IP and Dual Environments	RFC 2292 Advanced Sockets API for IPv6
RFC 1256 ICMP Router Discovery Protocol (IRDP)	RFC 2373 IPv6 Addressing Architecture
RFC 1293 Inverse Address Resolution Protocol	RFC 2460 IPv6 Specification
RFC 1315 Management Information Base for Frame Relay DTEs	RFC 2463 ICMPv6
RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)	RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 1333 PPP Link Quality Monitoring	RFC 2472 IP Version 6 over PPP
RFC 1334 PPP Authentication Protocols (PAP)	RFC 2473 Generic Packet Tunneling in IPv6
RFC 1349 Type of Service	RFC 2475 IPv6 DiffServ Architecture
RFC 1350 TFTP Protocol (revision 2)	RFC 2529 Transmission of IPv6 Packets over IPv4
RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)	RFC 2545 Use of MP-BGP-4 for IPv6
RFC 1381 SNMP MIB Extension for X.25 LAPB	RFC 2553 Basic Socket Interface Extensions for IPv6
RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol	RFC 2740 OSPFv3 for IPv6
RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol	RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 1490 Multiprotocol Interconnect over Frame Relay	RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
RFC 1519 CIDR	RFC 3513 IPv6 Addressing Architecture
RFC 1534 DHCP/BOOTP Interoperation	RFC 3596 DNS Extension for IPv6
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol	MIBs
RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)	RFC 1213 MIB II
RFC 1577 Classical IP and ARP over ATM	RFC 1229 Interface MIB Extensions
RFC 1613 Cisco Systems X.25 over TCP (XOT)	RFC 1286 Bridge MIB
RFC 1624 Incremental Internet Checksum	RFC 1493 Bridge MIB
RFC 1631 NAT	RFC 1573 SNMP MIB II
RFC 1638 PPP Bridging Control Protocol (BCP)	RFC 1724 RIPv2 MIB
RFC 1661 The Point-to-Point Protocol (PPP)	RFC 1757 Remote Network Monitoring MIB
RFC 1662 PPP in HDLC-like Framing	RFC 1850 OSPFv2 MIB
RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2	RFC 2011 SNMPv2 MIB for IP
RFC 1701 Generic Routing Encapsulation	RFC 2012 SNMPv2 MIB for TCP
RFC 1702 Generic Routing Encapsulation over	RFC 2013 SNMPv2 MIB for UDP
	RFC 2233 Interfaces MIB
	RFC 2454 IPV6-UDP-MIB
	RFC 2465 IPv6 MIB
	RFC 2466 ICMPv6 MIB
	RFC 2618 RADIUS Client MIB
	RFC 2620 RADIUS Accounting MIB
	RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
	RFC 2737 Entity MIB (Version 2)
	RFC 2863 The Interfaces Group MIB



Technical Specifications

IPv4 networks	RFC 2933 IGMP MIB
RFC 1721 RIP-2 Analysis	RFC 3813 MPLS LSR MIB
RFC 1722 RIP-2 Applicability	
RFC 1723 RIP v2	
RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1	Network management
RFC 1812 IPv4 Routing	IEEE 802.1D (STP)
RFC 1829 The ESP DES-CBC Transform	RFC 1155 Structure of Management Information
RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses	RFC 1157 SNMPv1
RFC 1944 Benchmarking Methodology for Network Interconnect Devices	RFC 1905 SNMPv2 Protocol Operations
RFC 1973 PPP in Frame Relay	RFC 2272 SNMPv3 Management Protocol
RFC 1974 PPP Stac LZS Compression Protocol	RFC 2273 SNMPv3 Applications
RFC 1990 The PPP Multilink Protocol (MP)	RFC 2274 USM for SNMPv3
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)	RFC 2275 VACM for SNMPv3
RFC 2091 Trigger RIP	RFC 2575 SNMPv3 View-based Access Control Model (VACM)
RFC 2131 DHCP	RFC 3164 BSD syslog Protocol
RFC 2132 DHCP Options and BOOTP Vendor Extensions	
RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements	OSPF
RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification	RFC 1245 OSPF protocol analysis
RFC 2280 Routing Policy Specification Language (RPSL)	RFC 1246 Experience with OSPF
RFC 2284 EAP over LAN	RFC 1587 OSPF NSSA
RFC 2338 VRRP	RFC 1765 OSPF Database Overflow
RFC 2364 PPP Over AAL5	RFC 1850 OSPFv2 Management Information Base (MIB), traps
RFC 2374 An Aggregatable Global Unicast Address Format	RFC 2328 OSPFv2
RFC 2451 The ESP CBC-Mode Cipher Algorithms	RFC 2370 OSPF Opaque LSA Option
RFC 2453 RIPv2	RFC 3101 OSPF NSSA
RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols	
RFC 2511 Internet X.509 Certificate Request Message Format	QoS/CoS
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)	IEEE 802.1P (CoS)
RFC 2644 Directed Broadcast Control	RFC 2474 DS Field in the IPv4 and IPv6 Headers
RFC 2661 L2TP	RFC 2475 DiffServ Architecture
RFC 2663 NAT Terminology and Considerations	RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5	RFC 2598 DiffServ Expedited Forwarding (EF)
RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)	RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
RFC 2702 Requirements for Traffic Engineering Over MPLS	
	Security
	IEEE 802.1X Port Based Network Access Control
	RFC 1321 The MD5 Message-Digest Algorithm
	RFC 2082 RIP-2 MD5 Authentication
	RFC 2104 Keyed-Hashing for Message Authentication
	RFC 2138 RADIUS Authentication
	RFC 2209 RSVP-Message Processing
	RFC 2246 Transport Layer Security (TLS)
	RFC 2716 PPP EAP TLS Authentication Protocol
	RFC 2865 RADIUS Authentication
	RFC 2866 RADIUS Accounting
	RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
	VPN



Technical Specifications

RFC 2747 RSVP Cryptographic Authentication	RFC 2403 - HMAC-MD5-96
RFC 2763 Dynamic Name-to-System ID mapping support	RFC 2404 - HMAC-SHA1-96
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)	RFC 2405 - DES-CBC Cipher algorithm
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)	RFC 2547 BGP/MPLS VPNs
RFC 2784 Generic Routing Encapsulation (GRE)	RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 2787 Definitions of Managed Objects for VRRP	RFC 2842 Capabilities Advertisement with BGP-4
RFC 2961 RSVP Refresh Overhead Reduction Extensions	RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS	RFC 2918 Route Refresh Capability for BGP-4
RFC 2973 IS-IS Mesh Groups	RFC 3107 Carrying Label Information in BGP-4
RFC 2993 Architectural Implications of NAT	
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)	IPsec
RFC 3027 Protocol Complications with the IP Network Address Translator	RFC 1828 IP Authentication using Keyed MD5
RFC 3031 Multiprotocol Label Switching Architecture	RFC 2401 IP Security Architecture
RFC 3032 MPLS Label Stack Encoding	RFC 2402 IP Authentication Header
	RFC 2406 IP Encapsulating Security Payload
	RFC 2407 - Domain of interpretation
	RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
	RFC 2411 IP Security Document Roadmap
	RFC 2412 - OAKLEY
	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-12 Router (JF241A)

Ports	1 SIC slot
	1 E1 port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
Physical characteristics	Dimensions 9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm) (1U height)
	Weight 6.61 lb. (3.0 kg)
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	Throughput up to 160 Kpps (64-byte packets)
	Routing table size 10000 entries
Environment	Operating temperature 32°F to 104°F (0°C to 40°C)
	Operating relative humidity 5% to 90%, noncondensing
	Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity 5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr)
	Voltage 100-120/200-240 VAC



Technical Specifications

Maximum power rating	25 W
Frequency	50/60 Hz
Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Safety UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J

Emissions EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B

Telecom FCC part 68

Management IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB

Notes Height does not include antennas on wireless models; weight is with no optional modules installed.

Services
 3-year, parts only, global next-day advance exchange (UW075E)
 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)
 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)
 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)
 3-year, 24x7 SW phone support, software updates (UW012E)
 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
 4-year, 24x7 SW phone support, software updates (UW013E)
 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
 5-year, 24x7 SW phone support, software updates (UW014E)
 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
 5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols
 (applies to all products in series)

BGP	RFC 3036 LDP Specification
RFC 1163 Border Gateway Protocol (BGP)	RFC 3046 DHCP Relay Agent Information Option
RFC 1267 Border Gateway Protocol 3 (BGP-3)	RFC 3063 MPLS Loop Prevention Mechanism
RFC 1657 Definitions of Managed Objects for BGPv4	RFC 3065 Support AS confederation
RFC 1771 BGPv4	RFC 3137 OSPF Stub Router Advertisement
RFC 1772 Application of the BGP	RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
RFC 1773 Experience with the BGP-4 Protocol	RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
RFC 1774 BGP-4 Protocol Analysis	RFC 3212 Constraint-Based LSP setup using LDP
RFC 1965 BGP4 confederations	



Technical Specifications

RFC 1997 BGP Communities Attribute	(CR-LDP)
RFC 1998 PPP Gandalf FZA Compression Protocol	RFC 3214 LSP Modification Using CR-LDP
RFC 2385 BGP Session Protection via TCP MD5	RFC 3215 LDP State Machine
RFC 2439 BGP Route Flap Damping	RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
Device management	RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 1305 NTPv3	RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0	RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 2271 FrameWork	RFC 3392 Support BGP capabilities advertisement
RFC 2452 MIB for TCP6	RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 2454 MIB for UDP6	RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
General protocols	RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
IEEE 802.1D MAC Bridges	RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
IEEE 802.1p Priority	RFC 3784 ISIS TE support
IEEE 802.1Q VLANs	RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
IEEE 802.1s Multiple Spanning Trees	RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
IEEE 802.1w Rapid Reconfiguration of Spanning Tree	RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
RFC 768 UDP	RFC 3847 Restart signaling for IS-IS
RFC 783 TFTP Protocol (revision 2)	IP multicast
RFC 791 IP	RFC 1112 IGMP
RFC 792 ICMP	RFC 2236 IGMPv2
RFC 793 TCP	RFC 2283 Multiprotocol Extensions for BGP-4
RFC 826 ARP	RFC 2362 PIM Sparse Mode
RFC 854 TELNET	RFC 2365 Administratively Scoped IP Multicast
RFC 855 Telnet Option Specification	RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 856 TELNET	RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 858 Telnet Suppress Go Ahead Option	RFC 3376 IGMPv3
RFC 894 IP over Ethernet	IPv6
RFC 925 Multi-LAN Address Resolution	RFC 1981 IPv6 Path MTU Discovery
RFC 950 Internet Standard Subnetting Procedure	RFC 2080 RIPng for IPv6
RFC 959 File Transfer Protocol (FTP)	RFC 2292 Advanced Sockets API for IPv6
RFC 1006 ISO transport services on top of the TCP: Version 3	RFC 2373 IPv6 Addressing Architecture
RFC 1027 Proxy ARP	RFC 2460 IPv6 Specification
RFC 1034 Domain Concepts and Facilities	RFC 2463 ICMPv6
RFC 1035 Domain Implementation and Specification	
RFC 1042 IP Datagrams	
RFC 1058 RIPv1	
RFC 1071 Computing the Internet Checksum	
RFC 1091 Telnet Terminal-Type Option	
RFC 1122 Host Requirements	
RFC 1141 Incremental updating of the Internet checksum	
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	
RFC 1144 Compressing TCP/IP headers for low-speed serial links	
RFC 1195 OSI ISIS for IP and Dual Environments	
RFC 1256 ICMP Router Discovery Protocol (IRDP)	
RFC 1293 Inverse Address Resolution Protocol	



Technical Specifications

- RFC 1315 Management Information Base for Frame Relay DTEs
- RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
- RFC 1333 PPP Link Quality Monitoring
- RFC 1334 PPP Authentication Protocols (PAP)
- RFC 1349 Type of Service
- RFC 1350 TFTP Protocol (revision 2)
- RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
- RFC 1381 SNMP MIB Extension for X.25 LAPB
- RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol
- RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol
- RFC 1490 Multiprotocol Interconnect over Frame Relay
- RFC 1519 CIDR
- RFC 1534 DHCP/BOOTP Interoperation
- RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
- RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)
- RFC 1577 Classical IP and ARP over ATM
- RFC 1613 Cisco Systems X.25 over TCP (XOT)
- RFC 1624 Incremental Internet Checksum
- RFC 1631 NAT
- RFC 1638 PPP Bridging Control Protocol (BCP)
- RFC 1661 The Point-to-Point Protocol (PPP)
- RFC 1662 PPP in HDLC-like Framing
- RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
- RFC 1701 Generic Routing Encapsulation
- RFC 1702 Generic Routing Encapsulation over IPv4 networks
- RFC 1721 RIP-2 Analysis
- RFC 1722 RIP-2 Applicability
- RFC 1723 RIP v2
- RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
- RFC 1812 IPv4 Routing
- RFC 1829 The ESP DES-CBC Transform
- RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
- RFC 1944 Benchmarking Methodology for Network Interconnect Devices
- RFC 2464 Transmission of IPv6 over Ethernet Networks
- RFC 2472 IP Version 6 over PPP
- RFC 2473 Generic Packet Tunneling in IPv6
- RFC 2475 IPv6 DiffServ Architecture
- RFC 2529 Transmission of IPv6 Packets over IPv4
- RFC 2545 Use of MP-BGP-4 for IPv6
- RFC 2553 Basic Socket Interface Extensions for IPv6
- RFC 2740 OSPFv3 for IPv6
- RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
- RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
- RFC 3513 IPv6 Addressing Architecture
- RFC 3596 DNS Extension for IPv6
- MIBs**
- RFC 1213 MIB II
- RFC 1229 Interface MIB Extensions
- RFC 1286 Bridge MIB
- RFC 1493 Bridge MIB
- RFC 1573 SNMP MIB II
- RFC 1724 RIPv2 MIB
- RFC 1757 Remote Network Monitoring MIB
- RFC 1850 OSPFv2 MIB
- RFC 2011 SNMPv2 MIB for IP
- RFC 2012 SNMPv2 MIB for TCP
- RFC 2013 SNMPv2 MIB for UDP
- RFC 2233 Interfaces MIB
- RFC 2454 IPV6-UDP-MIB
- RFC 2465 IPv6 MIB
- RFC 2466 ICMPv6 MIB
- RFC 2618 RADIUS Client MIB
- RFC 2620 RADIUS Accounting MIB
- RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
- RFC 2737 Entity MIB (Version 2)
- RFC 2863 The Interfaces Group MIB
- RFC 2933 IGMP MIB
- RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
- RFC 1155 Structure of Management Information
- RFC 1157 SNMPv1
- RFC 1905 SNMPv2 Protocol Operations
- RFC 2272 SNMPv3 Management Protocol
- RFC 2273 SNMPv3 Applications
- RFC 2274 USM for SNMPv3
- RFC 2275 VACM for SNMPv3
- RFC 2575 SNMPv3 View-based Access Control Model (VACM)



Technical Specifications

RFC 1973 PPP in Frame Relay
RFC 1974 PPP Stac LZS Compression Protocol
RFC 1990 The PPP Multilink Protocol (MP)
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
RFC 2091 Trigger RIP
RFC 2131 DHCP
RFC 2132 DHCP Options and BOOTP Vendor Extensions
RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
RFC 2280 Routing Policy Specification Language (RPSL)
RFC 2284 EAP over LAN
RFC 2338 VRRP
RFC 2364 PPP Over AAL5
RFC 2374 An Aggregatable Global Unicast Address Format
RFC 2451 The ESP CBC-Mode Cipher Algorithms
RFC 2453 RIPv2
RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
RFC 2511 Internet X.509 Certificate Request Message Format
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
RFC 2644 Directed Broadcast Control
RFC 2661 L2TP
RFC 2663 NAT Terminology and Considerations
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5
RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)
RFC 2702 Requirements for Traffic Engineering Over MPLS
RFC 2747 RSVP Cryptographic Authentication
RFC 2763 Dynamic Name-to-System ID mapping support
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)
RFC 2784 Generic Routing Encapsulation (GRE)
RFC 2787 Definitions of Managed Objects for VRRP
RFC 2961 RSVP Refresh Overhead Reduction Extensions
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS

RFC 3164 BSD syslog Protocol

OSPF

RFC 1245 OSPF protocol analysis
RFC 1246 Experience with OSPF
RFC 1587 OSPF NSSA
RFC 1765 OSPF Database Overflow
RFC 1850 OSPFv2 Management Information Base (MIB), traps
RFC 2328 OSPFv2
RFC 2370 OSPF Opaque LSA Option
RFC 3101 OSPF NSSA

QoS/CoS

IEEE 802.1P (CoS)
RFC 2474 DS Field in the IPv4 and IPv6 Headers
RFC 2475 DiffServ Architecture
RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)
RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP

Security

IEEE 802.1X Port Based Network Access Control
RFC 1321 The MD5 Message-Digest Algorithm
RFC 2082 RIP-2 MD5 Authentication
RFC 2104 Keyed-Hashing for Message Authentication
RFC 2138 RADIUS Authentication
RFC 2209 RSVP-Message Processing
RFC 2246 Transport Layer Security (TLS)
RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication

VPN

RFC 2403 - HMAC-MD5-96
RFC 2404 - HMAC-SHA1-96
RFC 2405 - DES-CBC Cipher algorithm
RFC 2547 BGP/MPLS VPNs
RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 2842 Capabilities Advertisement with BGP-4
RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2918 Route Refresh Capability for BGP-4
RFC 3107 Carrying Label Information in BGP-4

IPsec

RFC 1828 IP Authentication using Keyed MD5
RFC 2401 IP Security Architecture



Technical Specifications

RFC 2973 IS-IS Mesh Groups	RFC 2402 IP Authentication Header
RFC 2993 Architectural Implications of NAT	RFC 2406 IP Encapsulating Security Payload
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)	RFC 2407 - Domain of interpretation
RFC 3027 Protocol Complications with the IP Network Address Translator	RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
RFC 3031 Multiprotocol Label Switching Architecture	RFC 2411 IP Security Document Roadmap
RFC 3032 MPLS Label Stack Encoding	RFC 2412 – OAKLEY
	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-12-W Router (JF807A)

Ports	1 SIC slot	
	1 E1 port	
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full	
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full	
AP characteristics	Radios	Single (b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification*	b/g Wi-Fi Certified
	* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.	
Physical characteristics	Dimensions	9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm) (1U height)
	Weight	6.61 lb. (3.0 kg)
Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	
Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	5% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-120/200-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz



Technical Specifications

Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.

Safety UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J

Emissions EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B

Telecom FCC part 68

Management IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB

Notes Height does not include antennas on wireless models; weight is with no optional modules installed.

Services
 3-year, parts only, global next-day advance exchange (UW075E)
 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)
 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)
 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)
 3-year, 24x7 SW phone support, software updates (UW012E)
 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
 4-year, 24x7 SW phone support, software updates (UW013E)
 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
 5-year, 24x7 SW phone support, software updates (UW014E)
 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
 5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols
 (applies to all products in series)

BGP	RFC 3036 LDP Specification
RFC 1163 Border Gateway Protocol (BGP)	RFC 3046 DHCP Relay Agent Information Option
RFC 1267 Border Gateway Protocol 3 (BGP-3)	RFC 3063 MPLS Loop Prevention Mechanism
RFC 1657 Definitions of Managed Objects for BGPv4	RFC 3065 Support AS confederation
RFC 1771 BGPv4	RFC 3137 OSPF Stub Router Advertisement
RFC 1772 Application of the BGP	RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
RFC 1773 Experience with the BGP-4 Protocol	RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
RFC 1774 BGP-4 Protocol Analysis	RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
RFC 1965 BGP4 confederations	RFC 3214 LSP Modification Using CR-LDP
RFC 1997 BGP Communities Attribute	RFC 3215 LDP State Machine
RFC 1998 PPP Gandalf FZA Compression Protocol	
RFC 2385 BGP Session Protection via TCP MD5	



Technical Specifications

RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
RFC 2271 FrameWork
RFC 2452 MIB for TCP6
RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 855 Telnet Option Specification
RFC 856 TELNET
RFC 858 Telnet Suppress Go Ahead Option
RFC 894 IP over Ethernet
RFC 925 Multi-LAN Address Resolution
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1006 ISO transport services on top of the TCP: Version 3
RFC 1027 Proxy ARP
RFC 1034 Domain Concepts and Facilities
RFC 1035 Domain Implementation and Specification
RFC 1042 IP Datagrams
RFC 1058 RIPv1
RFC 1071 Computing the Internet Checksum
RFC 1091 Telnet Terminal-Type Option
RFC 1122 Host Requirements
RFC 1141 Incremental updating of the Internet checksum
RFC 1142 OSI IS-IS Intra-domain Routing Protocol
RFC 1144 Compressing TCP/IP headers for low-speed serial links
RFC 1195 OSI ISIS for IP and Dual Environments
RFC 1256 ICMP Router Discovery Protocol (IRDP)
RFC 1293 Inverse Address Resolution Protocol
RFC 1315 Management Information Base for Frame Relay DTEs

RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3392 Support BGP capabilities advertisement
RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
RFC 3784 ISIS TE support
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
RFC 3847 Restart signaling for IS-IS

IP multicast

RFC 1112 IGMP
RFC 2236 IGMPv2
RFC 2283 Multiprotocol Extensions for BGP-4
RFC 2362 PIM Sparse Mode
RFC 2365 Administratively Scoped IP Multicast
RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 3376 IGMPv3

IPv6

RFC 1981 IPv6 Path MTU Discovery
RFC 2080 RIPng for IPv6
RFC 2292 Advanced Sockets API for IPv6
RFC 2373 IPv6 Addressing Architecture
RFC 2460 IPv6 Specification
RFC 2463 ICMPv6
RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 2472 IP Version 6 over PPP



Technical Specifications

- RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
- RFC 1333 PPP Link Quality Monitoring
- RFC 1334 PPP Authentication Protocols (PAP)
- RFC 1349 Type of Service
- RFC 1350 TFTP Protocol (revision 2)
- RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
- RFC 1381 SNMP MIB Extension for X.25 LAPB
- RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol
- RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol
- RFC 1490 Multiprotocol Interconnect over Frame Relay
- RFC 1519 CIDR
- RFC 1534 DHCP/BOOTP Interoperation
- RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
- RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)
- RFC 1577 Classical IP and ARP over ATM
- RFC 1613 Cisco Systems X.25 over TCP (XOT)
- RFC 1624 Incremental Internet Checksum
- RFC 1631 NAT
- RFC 1638 PPP Bridging Control Protocol (BCP)
- RFC 1661 The Point-to-Point Protocol (PPP)
- RFC 1662 PPP in HDLC-like Framing
- RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
- RFC 1701 Generic Routing Encapsulation
- RFC 1702 Generic Routing Encapsulation over IPv4 networks
- RFC 1721 RIP-2 Analysis
- RFC 1722 RIP-2 Applicability
- RFC 1723 RIP v2
- RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
- RFC 1812 IPv4 Routing
- RFC 1829 The ESP DES-CBC Transform
- RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
- RFC 1944 Benchmarking Methodology for Network Interconnect Devices
- RFC 1973 PPP in Frame Relay
- RFC 1974 PPP Stac LZS Compression Protocol
- RFC 1990 The PPP Multilink Protocol (MP)
- RFC 2473 Generic Packet Tunneling in IPv6
- RFC 2475 IPv6 DiffServ Architecture
- RFC 2529 Transmission of IPv6 Packets over IPv4
- RFC 2545 Use of MP-BGP-4 for IPv6
- RFC 2553 Basic Socket Interface Extensions for IPv6
- RFC 2740 OSPFv3 for IPv6
- RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
- RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
- RFC 3513 IPv6 Addressing Architecture
- RFC 3596 DNS Extension for IPv6
- MIBs**
- RFC 1213 MIB II
- RFC 1229 Interface MIB Extensions
- RFC 1286 Bridge MIB
- RFC 1493 Bridge MIB
- RFC 1573 SNMP MIB II
- RFC 1724 RIPv2 MIB
- RFC 1757 Remote Network Monitoring MIB
- RFC 1850 OSPFv2 MIB
- RFC 2011 SNMPv2 MIB for IP
- RFC 2012 SNMPv2 MIB for TCP
- RFC 2013 SNMPv2 MIB for UDP
- RFC 2233 Interfaces MIB
- RFC 2454 IPV6-UDP-MIB
- RFC 2465 IPv6 MIB
- RFC 2466 ICMPv6 MIB
- RFC 2618 RADIUS Client MIB
- RFC 2620 RADIUS Accounting MIB
- RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
- RFC 2737 Entity MIB (Version 2)
- RFC 2863 The Interfaces Group MIB
- RFC 2933 IGMP MIB
- RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
- RFC 1155 Structure of Management Information
- RFC 1157 SNMPv1
- RFC 1905 SNMPv2 Protocol Operations
- RFC 2272 SNMPv3 Management Protocol
- RFC 2273 SNMPv3 Applications
- RFC 2274 USM for SNMPv3
- RFC 2275 VACM for SNMPv3
- RFC 2575 SNMPv3 View-based Access Control Model (VACM)
- RFC 3164 BSD syslog Protocol
- OSPF**



Technical Specifications

- RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
 - RFC 2091 Trigger RIP
 - RFC 2131 DHCP
 - RFC 2132 DHCP Options and BOOTP Vendor Extensions
 - RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
 - RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
 - RFC 2280 Routing Policy Specification Language (RPSL)
 - RFC 2284 EAP over LAN
 - RFC 2338 VRRP
 - RFC 2364 PPP Over AAL5
 - RFC 2374 An Aggregatable Global Unicast Address Format
 - RFC 2451 The ESP CBC-Mode Cipher Algorithms
 - RFC 2453 IPv2
 - RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
 - RFC 2511 Internet X.509 Certificate Request Message Format
 - RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
 - RFC 2644 Directed Broadcast Control
 - RFC 2661 L2TP
 - RFC 2663 NAT Terminology and Considerations
 - RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5
 - RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)
 - RFC 2702 Requirements for Traffic Engineering Over MPLS
 - RFC 2747 RSVP Cryptographic Authentication
 - RFC 2763 Dynamic Name-to-System ID mapping support
 - RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)
 - RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)
 - RFC 2784 Generic Routing Encapsulation (GRE)
 - RFC 2787 Definitions of Managed Objects for VRRP
 - RFC 2961 RSVP Refresh Overhead Reduction Extensions
 - RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS
 - RFC 2973 IS-IS Mesh Groups
 - RFC 2993 Architectural Implications of NAT
 - RFC 3022 Traditional IP Network Address
 - RFC 1245 OSPF protocol analysis
 - RFC 1246 Experience with OSPF
 - RFC 1587 OSPF NSSA
 - RFC 1765 OSPF Database Overflow
 - RFC 1850 OSPFv2 Management Information Base (MIB), traps
 - RFC 2328 OSPFv2
 - RFC 2370 OSPF Opaque LSA Option
 - RFC 3101 OSPF NSSA
- QoS/CoS**
- IEEE 802.1P (CoS)
 - RFC 2474 DS Field in the IPv4 and IPv6 Headers
 - RFC 2475 DiffServ Architecture
 - RFC 2597 DiffServ Assured Forwarding (AF)
 - RFC 2598 DiffServ Expedited Forwarding (EF)
 - RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
- Security**
- IEEE 802.1X Port Based Network Access Control
 - RFC 1321 The MD5 Message-Digest Algorithm
 - RFC 2082 RIP-2 MD5 Authentication
 - RFC 2104 Keyed-Hashing for Message Authentication
 - RFC 2138 RADIUS Authentication
 - RFC 2209 RSVP-Message Processing
 - RFC 2246 Transport Layer Security (TLS)
 - RFC 2716 PPP EAP TLS Authentication Protocol
 - RFC 2865 RADIUS Authentication
 - RFC 2866 RADIUS Accounting
 - RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
- VPN**
- RFC 2403 - HMAC-MD5-96
 - RFC 2404 - HMAC-SHA1-96
 - RFC 2405 - DES-CBC Cipher algorithm
 - RFC 2547 BGP/MPLS VPNs
 - RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
 - RFC 2842 Capabilities Advertisement with BGP-4
 - RFC 2858 Multiprotocol Extensions for BGP-4
 - RFC 2918 Route Refresh Capability for BGP-4
 - RFC 3107 Carrying Label Information in BGP-4
- IPsec**
- RFC 1828 IP Authentication using Keyed MD5
 - RFC 2401 IP Security Architecture
 - RFC 2402 IP Authentication Header
 - RFC 2406 IP Encapsulating Security Payload
 - RFC 2407 - Domain of interpretation



Technical Specifications

Translator (Traditional NAT)	RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
RFC 3027 Protocol Complications with the IP Network Address Translator	RFC 2411 IP Security Document Roadmap
RFC 3031 Multiprotocol Label Switching Architecture	RFC 2412 – OAKLEY
RFC 3032 MPLS Label Stack Encoding	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-12-T Router (JF806A)

Ports	1 SIC slot	
	1 T1 port	
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full	
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full	
Physical characteristics	Dimensions	9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm) (1U height)
	Weight	6.61 lb. (3 kg)
Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	
Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	5% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-120/200-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J	
Emissions	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68	



Technical Specifications

Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
Notes	Height does not include antennas on wireless models; weight is with no optional modules installed.
Services	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E) 5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols (applies to all products in series)

BGP	RFC 1163 Border Gateway Protocol (BGP)	RFC 3036 LDP Specification
	RFC 1267 Border Gateway Protocol 3 (BGP-3)	RFC 3046 DHCP Relay Agent Information Option
	RFC 1657 Definitions of Managed Objects for BGPv4	RFC 3063 MPLS Loop Prevention Mechanism
	RFC 1771 BGPv4	RFC 3065 Support AS confederation
	RFC 1772 Application of the BGP	RFC 3137 OSPF Stub Router Advertisement
	RFC 1773 Experience with the BGP-4 Protocol	RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
	RFC 1774 BGP-4 Protocol Analysis	RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
	RFC 1965 BGP4 confederations	RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
	RFC 1997 BGP Communities Attribute	RFC 3214 LSP Modification Using CR-LDP
	RFC 1998 PPP Gandalf FZA Compression Protocol	RFC 3215 LDP State Machine
	RFC 2385 BGP Session Protection via TCP MD5	RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
	RFC 2439 BGP Route Flap Damping	RFC 3277 IS-IS Transient Blackhole Avoidance
Device management	RFC 1305 NTPv3	RFC 3279 Algorithms and Identifiers for the Internet
	RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0	X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
	RFC 2271 FrameWork	RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
	RFC 2452 MIB for TCP6	RFC 3392 Support BGP capabilities advertisement
	RFC 2454 MIB for UDP6	RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
General protocols	IEEE 802.1D MAC Bridges	RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic
	IEEE 802.1p Priority	
	IEEE 802.1Q VLANs	
	IEEE 802.1s Multiple Spanning Trees	



Technical Specifications

- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
 - RFC 768 UDP
 - RFC 783 TFTP Protocol (revision 2)
 - RFC 791 IP
 - RFC 792 ICMP
 - RFC 793 TCP
 - RFC 826 ARP
 - RFC 854 TELNET
 - RFC 855 Telnet Option Specification
 - RFC 856 TELNET
 - RFC 858 Telnet Suppress Go Ahead Option
 - RFC 894 IP over Ethernet
 - RFC 925 Multi-LAN Address Resolution
 - RFC 950 Internet Standard Subnetting Procedure
 - RFC 959 File Transfer Protocol (FTP)
 - RFC 1006 ISO transport services on top of the TCP: Version 3
 - RFC 1027 Proxy ARP
 - RFC 1034 Domain Concepts and Facilities
 - RFC 1035 Domain Implementation and Specification
 - RFC 1042 IP Datagrams
 - RFC 1058 RIPv1
 - RFC 1071 Computing the Internet Checksum
 - RFC 1091 Telnet Terminal-Type Option
 - RFC 1122 Host Requirements
 - RFC 1141 Incremental updating of the Internet checksum
 - RFC 1142 OSI IS-IS Intra-domain Routing Protocol
 - RFC 1144 Compressing TCP/IP headers for low-speed serial links
 - RFC 1195 OSI ISIS for IP and Dual Environments
 - RFC 1256 ICMP Router Discovery Protocol (IRDP)
 - RFC 1293 Inverse Address Resolution Protocol
 - RFC 1315 Management Information Base for Frame Relay DTEs
 - RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
 - RFC 1333 PPP Link Quality Monitoring
 - RFC 1334 PPP Authentication Protocols (PAP)
 - RFC 1349 Type of Service
 - RFC 1350 TFTP Protocol (revision 2)
 - RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
 - RFC 1381 SNMP MIB Extension for X.25 LAPB
 - RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol
 - RFC 1472 The Definitions of Managed Objects for Engineering
 - RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
 - RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
 - RFC 3784 ISIS TE support
 - RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
 - RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
 - RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
 - RFC 3847 Restart signaling for IS-IS
- IP multicast**
- RFC 1112 IGMP
 - RFC 2236 IGMPv2
 - RFC 2283 Multiprotocol Extensions for BGP-4
 - RFC 2362 PIM Sparse Mode
 - RFC 2365 Administratively Scoped IP Multicast
 - RFC 2710 Multicast Listener Discovery (MLD) for IPv6
 - RFC 2934 Protocol Independent Multicast MIB for IPv4
 - RFC 3376 IGMPv3
- IPv6**
- RFC 1981 IPv6 Path MTU Discovery
 - RFC 2080 RIPng for IPv6
 - RFC 2292 Advanced Sockets API for IPv6
 - RFC 2373 IPv6 Addressing Architecture
 - RFC 2460 IPv6 Specification
 - RFC 2463 ICMPv6
 - RFC 2464 Transmission of IPv6 over Ethernet Networks
 - RFC 2472 IP Version 6 over PPP
 - RFC 2473 Generic Packet Tunneling in IPv6
 - RFC 2475 IPv6 DiffServ Architecture
 - RFC 2529 Transmission of IPv6 Packets over IPv4
 - RFC 2545 Use of MP-BGP-4 for IPv6
 - RFC 2553 Basic Socket Interface Extensions for IPv6
 - RFC 2740 OSPFv3 for IPv6
 - RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
 - RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
 - RFC 3513 IPv6 Addressing Architecture
 - RFC 3596 DNS Extension for IPv6



Technical Specifications

the Security Protocols of the Point-to-Point Protocol	MIBs
RFC 1490 Multiprotocol Interconnect over Frame Relay	RFC 1213 MIB II
RFC 1519 CIDR	RFC 1229 Interface MIB Extensions
RFC 1534 DHCP/BOOTP Interoperation	RFC 1286 Bridge MIB
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol	RFC 1493 Bridge MIB
RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)	RFC 1573 SNMP MIB II
RFC 1577 Classical IP and ARP over ATM	RFC 1724 RIPv2 MIB
RFC 1613 Cisco Systems X.25 over TCP (XOT)	RFC 1757 Remote Network Monitoring MIB
RFC 1624 Incremental Internet Checksum	RFC 1850 OSPFv2 MIB
RFC 1631 NAT	RFC 2011 SNMPv2 MIB for IP
RFC 1638 PPP Bridging Control Protocol (BCP)	RFC 2012 SNMPv2 MIB for TCP
RFC 1661 The Point-to-Point Protocol (PPP)	RFC 2013 SNMPv2 MIB for UDP
RFC 1662 PPP in HDLC-like Framing	RFC 2233 Interfaces MIB
RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2	RFC 2454 IPV6-UDP-MIB
RFC 1701 Generic Routing Encapsulation	RFC 2465 IPv6 MIB
RFC 1702 Generic Routing Encapsulation over IPv4 networks	RFC 2466 ICMPv6 MIB
RFC 1721 RIP-2 Analysis	RFC 2618 RADIUS Client MIB
RFC 1722 RIP-2 Applicability	RFC 2620 RADIUS Accounting MIB
RFC 1723 RIP v2	RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1	RFC 2737 Entity MIB (Version 2)
RFC 1812 IPv4 Routing	RFC 2863 The Interfaces Group MIB
RFC 1829 The ESP DES-CBC Transform	RFC 2933 IGMP MIB
RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses	RFC 3813 MPLS LSR MIB
RFC 1944 Benchmarking Methodology for Network Interconnect Devices	
RFC 1973 PPP in Frame Relay	Network management
RFC 1974 PPP Stac LZS Compression Protocol	IEEE 802.1D (STP)
RFC 1990 The PPP Multilink Protocol (MP)	RFC 1155 Structure of Management Information
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)	RFC 1157 SNMPv1
RFC 2091 Trigger RIP	RFC 1905 SNMPv2 Protocol Operations
RFC 2131 DHCP	RFC 2272 SNMPv3 Management Protocol
RFC 2132 DHCP Options and BOOTP Vendor Extensions	RFC 2273 SNMPv3 Applications
RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements	RFC 2274 USM for SNMPv3
RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification	RFC 2275 VACM for SNMPv3
RFC 2280 Routing Policy Specification Language (RPSL)	RFC 2575 SNMPv3 View-based Access Control Model (VACM)
RFC 2284 EAP over LAN	RFC 3164 BSD syslog Protocol
	OSPF
	RFC 1245 OSPF protocol analysis
	RFC 1246 Experience with OSPF
	RFC 1587 OSPF NSSA
	RFC 1765 OSPF Database Overflow
	RFC 1850 OSPFv2 Management Information Base (MIB), traps
	RFC 2328 OSPFv2
	RFC 2370 OSPF Opaque LSA Option
	RFC 3101 OSPF NSSA
	QoS/CoS
	IEEE 802.1P (CoS)
	RFC 2474 DS Field in the IPv4 and IPv6 Headers
	RFC 2475 DiffServ Architecture



Technical Specifications

RFC 2338 VRRP
RFC 2364 PPP Over AAL5
RFC 2374 An Aggregatable Global Unicast Address Format
RFC 2451 The ESP CBC-Mode Cipher Algorithms
RFC 2453 RIPv2
RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
RFC 2511 Internet X.509 Certificate Request Message Format
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
RFC 2644 Directed Broadcast Control
RFC 2661 L2TP
RFC 2663 NAT Terminology and Considerations
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5
RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)
RFC 2702 Requirements for Traffic Engineering Over MPLS
RFC 2747 RSVP Cryptographic Authentication
RFC 2763 Dynamic Name-to-System ID mapping support
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)
RFC 2784 Generic Routing Encapsulation (GRE)
RFC 2787 Definitions of Managed Objects for VRRP
RFC 2961 RSVP Refresh Overhead Reduction Extensions
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS
RFC 2973 IS-IS Mesh Groups
RFC 2993 Architectural Implications of NAT
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)
RFC 3027 Protocol Complications with the IP Network Address Translator
RFC 3031 Multiprotocol Label Switching Architecture
RFC 3032 MPLS Label Stack Encoding

RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)
RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP

Security

IEEE 802.1X Port Based Network Access Control
RFC 1321 The MD5 Message-Digest Algorithm
RFC 2082 RIP-2 MD5 Authentication
RFC 2104 Keyed-Hashing for Message Authentication
RFC 2138 RADIUS Authentication
RFC 2209 RSVP-Message Processing
RFC 2246 Transport Layer Security (TLS)
RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication

VPN

RFC 2403 - HMAC-MD5-96
RFC 2404 - HMAC-SHA1-96
RFC 2405 - DES-CBC Cipher algorithm
RFC 2547 BGP/MPLS VPNs
RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 2842 Capabilities Advertisement with BGP-4
RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2918 Route Refresh Capability for BGP-4
RFC 3107 Carrying Label Information in BGP-4

IPsec

RFC 1828 IP Authentication using Keyed MD5
RFC 2401 IP Security Architecture
RFC 2402 IP Authentication Header
RFC 2406 IP Encapsulating Security Payload
RFC 2407 - Domain of interpretation
RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
RFC 2411 IP Security Document Roadmap
RFC 2412 - OAKLEY
RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-13 Router (JF240A)

Ports

- 1 SIC slot
- 1 RJ-11 4-wire G.shdsl port
- 1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full



Technical Specifications

	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
Physical characteristics	<p>Dimensions 9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm) (1U height)</p> <p>Weight 6.61 lb. (3.0 kg)</p>
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	<p>Throughput up to 160 Kpps (64-byte packets)</p> <p>Routing table size 10000 entries</p>
Environment	<p>Operating temperature 32°F to 104°F (0°C to 40°C)</p> <p>Operating relative humidity 5%% to 90%%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 5% to 90%, noncondensing</p>
Electrical characteristics	<p>Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr)</p> <p>Voltage 100-120/200-240 VAC</p> <p>Maximum power rating 25 W</p> <p>Frequency 50/60 Hz</p> <p>Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p>
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J
Emissions	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B
Telecom	FCC part 68
Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
Notes	Height does not include antennas on wireless models; weight is with no optional modules installed.
Services	<p>3-year, parts only, global next-day advance exchange (UW075E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)</p> <p>3-year, 24x7 SW phone support, software updates (UW012E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)</p> <p>4-year, 24x7 SW phone support, software updates (UW013E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)</p>



Technical Specifications

- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols (applies to all products in series)

BGP

- RFC 1163 Border Gateway Protocol (BGP)
- RFC 1267 Border Gateway Protocol 3 (BGP-3)
- RFC 1657 Definitions of Managed Objects for BGPv4
- RFC 1771 BGPv4
- RFC 1772 Application of the BGP
- RFC 1773 Experience with the BGP-4 Protocol
- RFC 1774 BGP-4 Protocol Analysis
- RFC 1965 BGP4 confederations
- RFC 1997 BGP Communities Attribute
- RFC 1998 PPP Gandalf FZA Compression Protocol
- RFC 2385 BGP Session Protection via TCP MD5
- RFC 2439 BGP Route Flap Damping

Device management

- RFC 1305 NTPv3
- RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
- RFC 2271 FrameWork
- RFC 2452 MIB for TCP6
- RFC 2454 MIB for UDP6

General protocols

- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- RFC 768 UDP
- RFC 783 TFTP Protocol (revision 2)
- RFC 791 IP
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET
- RFC 855 Telnet Option Specification
- RFC 856 TELNET
- RFC 858 Telnet Suppress Go Ahead Option
- RFC 894 IP over Ethernet
- RFC 925 Multi-LAN Address Resolution

RFC 3036 LDP Specification

- RFC 3046 DHCP Relay Agent Information Option
- RFC 3063 MPLS Loop Prevention Mechanism
- RFC 3065 Support AS confederation
- RFC 3137 OSPF Stub Router Advertisement
- RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
- RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
- RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
- RFC 3214 LSP Modification Using CR-LDP
- RFC 3215 LDP State Machine
- RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
- RFC 3277 IS-IS Transient Blackhole Avoidance
- RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3392 Support BGP capabilities advertisement
- RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
- RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
- RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
- RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
- RFC 3784 ISIS TE support
- RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
- RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
- RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)



Technical Specifications

RFC 950 Internet Standard Subnetting Procedure	RFC 3847 Restart signaling for IS-IS
RFC 959 File Transfer Protocol (FTP)	
RFC 1006 ISO transport services on top of the TCP: Version 3	IP multicast
RFC 1027 Proxy ARP	RFC 1112 IGMP
RFC 1034 Domain Concepts and Facilities	RFC 2236 IGMPv2
RFC 1035 Domain Implementation and Specification	RFC 2283 Multiprotocol Extensions for BGP-4
RFC 1042 IP Datagrams	RFC 2362 PIM Sparse Mode
RFC 1058 RIPv1	RFC 2365 Administratively Scoped IP Multicast
RFC 1071 Computing the Internet Checksum	RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 1091 Telnet Terminal-Type Option	RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 1122 Host Requirements	RFC 3376 IGMPv3
RFC 1141 Incremental updating of the Internet checksum	
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	IPv6
RFC 1144 Compressing TCP/IP headers for low-speed serial links	RFC 1981 IPv6 Path MTU Discovery
RFC 1195 OSI ISIS for IP and Dual Environments	RFC 2080 RIPng for IPv6
RFC 1256 ICMP Router Discovery Protocol (IRDP)	RFC 2292 Advanced Sockets API for IPv6
RFC 1293 Inverse Address Resolution Protocol	RFC 2373 IPv6 Addressing Architecture
RFC 1315 Management Information Base for Frame Relay DTEs	RFC 2460 IPv6 Specification
RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)	RFC 2463 ICMPv6
RFC 1333 PPP Link Quality Monitoring	RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 1334 PPP Authentication Protocols (PAP)	RFC 2472 IP Version 6 over PPP
RFC 1349 Type of Service	RFC 2473 Generic Packet Tunneling in IPv6
RFC 1350 TFTP Protocol (revision 2)	RFC 2475 IPv6 DiffServ Architecture
RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)	RFC 2529 Transmission of IPv6 Packets over IPv4
RFC 1381 SNMP MIB Extension for X.25 LAPB	RFC 2545 Use of MP-BGP-4 for IPv6
RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol	RFC 2553 Basic Socket Interface Extensions for IPv6
RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol	RFC 2740 OSPFv3 for IPv6
RFC 1490 Multiprotocol Interconnect over Frame Relay	RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 1519 CIDR	RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
RFC 1534 DHCP/BOOTP Interoperation	RFC 3513 IPv6 Addressing Architecture
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol	RFC 3596 DNS Extension for IPv6
RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)	
RFC 1577 Classical IP and ARP over ATM	MIBs
RFC 1613 Cisco Systems X.25 over TCP (XOT)	RFC 1213 MIB II
RFC 1624 Incremental Internet Checksum	RFC 1229 Interface MIB Extensions
RFC 1631 NAT	RFC 1286 Bridge MIB
	RFC 1493 Bridge MIB
	RFC 1573 SNMP MIB II
	RFC 1724 RIPv2 MIB
	RFC 1757 Remote Network Monitoring MIB
	RFC 1850 OSPFv2 MIB
	RFC 2011 SNMPv2 MIB for IP
	RFC 2012 SNMPv2 MIB for TCP
	RFC 2013 SNMPv2 MIB for UDP
	RFC 2233 Interfaces MIB
	RFC 2454 IPV6-UDP-MIB



Technical Specifications

- RFC 1638 PPP Bridging Control Protocol (BCP)
 - RFC 1661 The Point-to-Point Protocol (PPP)
 - RFC 1662 PPP in HDLC-like Framing
 - RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
 - RFC 1701 Generic Routing Encapsulation
 - RFC 1702 Generic Routing Encapsulation over IPv4 networks
 - RFC 1721 RIP-2 Analysis
 - RFC 1722 RIP-2 Applicability
 - RFC 1723 RIP v2
 - RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
 - RFC 1812 IPv4 Routing
 - RFC 1829 The ESP DES-CBC Transform
 - RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
 - RFC 1944 Benchmarking Methodology for Network Interconnect Devices
 - RFC 1973 PPP in Frame Relay
 - RFC 1974 PPP Stac LZS Compression Protocol
 - RFC 1990 The PPP Multilink Protocol (MP)
 - RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
 - RFC 2091 Trigger RIP
 - RFC 2131 DHCP
 - RFC 2132 DHCP Options and BOOTP Vendor Extensions
 - RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
 - RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
 - RFC 2280 Routing Policy Specification Language (RPSL)
 - RFC 2284 EAP over LAN
 - RFC 2338 VRRP
 - RFC 2364 PPP Over AAL5
 - RFC 2374 An Aggregatable Global Unicast Address Format
 - RFC 2451 The ESP CBC-Mode Cipher Algorithms
 - RFC 2453 RIPv2
 - RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
 - RFC 2511 Internet X.509 Certificate Request Message Format
 - RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
 - RFC 2644 Directed Broadcast Control
 - RFC 2661 L2TP
 - RFC 2465 IPv6 MIB
 - RFC 2466 ICMPv6 MIB
 - RFC 2618 RADIUS Client MIB
 - RFC 2620 RADIUS Accounting MIB
 - RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
 - RFC 2737 Entity MIB (Version 2)
 - RFC 2863 The Interfaces Group MIB
 - RFC 2933 IGMP MIB
 - RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
 - RFC 1155 Structure of Management Information
 - RFC 1157 SNMPv1
 - RFC 1905 SNMPv2 Protocol Operations
 - RFC 2272 SNMPv3 Management Protocol
 - RFC 2273 SNMPv3 Applications
 - RFC 2274 USM for SNMPv3
 - RFC 2275 VACM for SNMPv3
 - RFC 2575 SNMPv3 View-based Access Control Model (VACM)
 - RFC 3164 BSD syslog Protocol
- OSPF**
- RFC 1245 OSPF protocol analysis
 - RFC 1246 Experience with OSPF
 - RFC 1587 OSPF NSSA
 - RFC 1765 OSPF Database Overflow
 - RFC 1850 OSPFv2 Management Information Base (MIB), traps
 - RFC 2328 OSPFv2
 - RFC 2370 OSPF Opaque LSA Option
 - RFC 3101 OSPF NSSA
- QoS/CoS**
- IEEE 802.1P (CoS)
 - RFC 2474 DS Field in the IPv4 and IPv6 Headers
 - RFC 2475 DiffServ Architecture
 - RFC 2597 DiffServ Assured Forwarding (AF)
 - RFC 2598 DiffServ Expedited Forwarding (EF)
 - RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
- Security**
- IEEE 802.1X Port Based Network Access Control
 - RFC 1321 The MD5 Message-Digest Algorithm
 - RFC 2082 RIP-2 MD5 Authentication
 - RFC 2104 Keyed-Hashing for Message Authentication
 - RFC 2138 RADIUS Authentication
 - RFC 2209 RSVP-Message Processing
 - RFC 2246 Transport Layer Security (TLS)



Technical Specifications

RFC 2663 NAT Terminology and Considerations	RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5	RFC 2865 RADIUS Authentication
RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)	RFC 2866 RADIUS Accounting
RFC 2702 Requirements for Traffic Engineering Over MPLS	RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
RFC 2747 RSVP Cryptographic Authentication	VPN
RFC 2763 Dynamic Name-to-System ID mapping support	RFC 2403 - HMAC-MD5-96
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)	RFC 2404 - HMAC-SHA1-96
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)	RFC 2405 - DES-CBC Cipher algorithm
RFC 2784 Generic Routing Encapsulation (GRE)	RFC 2547 BGP/MPLS VPNs
RFC 2787 Definitions of Managed Objects for VRRP	RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 2961 RSVP Refresh Overhead Reduction Extensions	RFC 2842 Capabilities Advertisement with BGP-4
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS	RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2973 IS-IS Mesh Groups	RFC 2918 Route Refresh Capability for BGP-4
RFC 2993 Architectural Implications of NAT	RFC 3107 Carrying Label Information in BGP-4
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)	IPsec
RFC 3027 Protocol Complications with the IP Network Address Translator	RFC 1828 IP Authentication using Keyed MD5
RFC 3031 Multiprotocol Label Switching Architecture	RFC 2401 IP Security Architecture
RFC 3032 MPLS Label Stack Encoding	RFC 2402 IP Authentication Header
	RFC 2406 IP Encapsulating Security Payload
	RFC 2407 - Domain of interpretation
	RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
	RFC 2411 IP Security Document Roadmap
	RFC 2412 - OAKLEY
	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-13-W Router (JF808A)

Ports	1 SIC slot
	1 RJ-11 4-wire G.shdsl port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full

AP characteristics	Radios	Single (b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification*	b/g Wi-Fi Certified

* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.

Physical characteristics	Dimensions	9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm) (1U height)
	Weight	6.61 lb. (3.0 kg)



Technical Specifications

Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	
Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	5% to 95%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 95%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-120/200-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J	
Emissions	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	
Notes	Height does not include antennas on wireless models; weight is with no optional modules installed.	
Services	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E)	



Technical Specifications

5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols (applies to all products in series)

BGP

RFC 1163 Border Gateway Protocol (BGP)
RFC 1267 Border Gateway Protocol 3 (BGP-3)
RFC 1657 Definitions of Managed Objects for BGPv4
RFC 1771 BGPv4
RFC 1772 Application of the BGP
RFC 1773 Experience with the BGP-4 Protocol
RFC 1774 BGP-4 Protocol Analysis
RFC 1965 BGP4 confederations
RFC 1997 BGP Communities Attribute
RFC 1998 PPP Gandalf FZA Compression Protocol
RFC 2385 BGP Session Protection via TCP MD5
RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
RFC 2271 FrameWork
RFC 2452 MIB for TCP6
RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges
IEEE 802.1p Priority
IEEE 802.1Q VLANs
IEEE 802.1s Multiple Spanning Trees
IEEE 802.1w Rapid Reconfiguration of Spanning Tree
RFC 768 UDP
RFC 783 TFTP Protocol (revision 2)
RFC 791 IP
RFC 792 ICMP
RFC 793 TCP
RFC 826 ARP
RFC 854 TELNET
RFC 855 Telnet Option Specification
RFC 856 TELNET
RFC 858 Telnet Suppress Go Ahead Option
RFC 894 IP over Ethernet
RFC 925 Multi-LAN Address Resolution
RFC 950 Internet Standard Subnetting Procedure
RFC 959 File Transfer Protocol (FTP)
RFC 1006 ISO transport services on top of the TCP: **IP multicast**
Version 3
RFC 1027 Proxy ARP

RFC 3036 LDP Specification
RFC 3046 DHCP Relay Agent Information Option
RFC 3063 MPLS Loop Prevention Mechanism
RFC 3065 Support AS confederation
RFC 3137 OSPF Stub Router Advertisement
RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
RFC 3214 LSP Modification Using CR-LDP
RFC 3215 LDP State Machine
RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 3392 Support BGP capabilities advertisement
RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
RFC 3784 ISIS TE support
RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
RFC 3847 Restart signaling for IS-IS
RFC 1112 IGMP
RFC 2236 IGMPv2



Technical Specifications

- RFC 1034 Domain Concepts and Facilities
 - RFC 1035 Domain Implementation and Specification
 - RFC 1042 IP Datagrams
 - RFC 1058 RIPv1
 - RFC 1071 Computing the Internet Checksum
 - RFC 1091 Telnet Terminal-Type Option
 - RFC 1122 Host Requirements
 - RFC 1141 Incremental updating of the Internet checksum
 - RFC 1142 OSI IS-IS Intra-domain Routing Protocol
 - RFC 1144 Compressing TCP/IP headers for low-speed serial links
 - RFC 1195 OSI ISIS for IP and Dual Environments
 - RFC 1256 ICMP Router Discovery Protocol (IRDP)
 - RFC 1293 Inverse Address Resolution Protocol
 - RFC 1315 Management Information Base for Frame Relay DTEs
 - RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
 - RFC 1333 PPP Link Quality Monitoring
 - RFC 1334 PPP Authentication Protocols (PAP)
 - RFC 1349 Type of Service
 - RFC 1350 TFTP Protocol (revision 2)
 - RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
 - RFC 1381 SNMP MIB Extension for X.25 LAPB
 - RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol
 - RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol
 - RFC 1490 Multiprotocol Interconnect over Frame Relay
 - RFC 1519 CIDR
 - RFC 1534 DHCP/BOOTP Interoperation
 - RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
 - RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)
 - RFC 1577 Classical IP and ARP over ATM
 - RFC 1613 Cisco Systems X.25 over TCP (XOT)
 - RFC 1624 Incremental Internet Checksum
 - RFC 1631 NAT
 - RFC 1638 PPP Bridging Control Protocol (BCP)
 - RFC 1661 The Point-to-Point Protocol (PPP)
 - RFC 1662 PPP in HDLC-like Framing
 - RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
 - RFC 2283 Multiprotocol Extensions for BGP-4
 - RFC 2362 PIM Sparse Mode
 - RFC 2365 Administratively Scoped IP Multicast
 - RFC 2710 Multicast Listener Discovery (MLD) for IPv6
 - RFC 2934 Protocol Independent Multicast MIB for IPv4
 - RFC 3376 IGMPv3
- IPv6**
- RFC 1981 IPv6 Path MTU Discovery
 - RFC 2080 RIPng for IPv6
 - RFC 2292 Advanced Sockets API for IPv6
 - RFC 2373 IPv6 Addressing Architecture
 - RFC 2460 IPv6 Specification
 - RFC 2463 ICMPv6
 - RFC 2464 Transmission of IPv6 over Ethernet Networks
 - RFC 2472 IP Version 6 over PPP
 - RFC 2473 Generic Packet Tunneling in IPv6
 - RFC 2475 IPv6 DiffServ Architecture
 - RFC 2529 Transmission of IPv6 Packets over IPv4
 - RFC 2545 Use of MP-BGP-4 for IPv6
 - RFC 2553 Basic Socket Interface Extensions for IPv6
 - RFC 2740 OSPFv3 for IPv6
 - RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
 - RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
 - RFC 3513 IPv6 Addressing Architecture
 - RFC 3596 DNS Extension for IPv6
- MIBs**
- RFC 1213 MIB II
 - RFC 1229 Interface MIB Extensions
 - RFC 1286 Bridge MIB
 - RFC 1493 Bridge MIB
 - RFC 1573 SNMP MIB II
 - RFC 1724 RIPv2 MIB
 - RFC 1757 Remote Network Monitoring MIB
 - RFC 1850 OSPFv2 MIB
 - RFC 2011 SNMPv2 MIB for IP
 - RFC 2012 SNMPv2 MIB for TCP
 - RFC 2013 SNMPv2 MIB for UDP
 - RFC 2233 Interfaces MIB
 - RFC 2454 IPV6-UDP-MIB
 - RFC 2465 IPv6 MIB
 - RFC 2466 ICMPv6 MIB
 - RFC 2618 RADIUS Client MIB
 - RFC 2620 RADIUS Accounting MIB
 - RFC 2674 802.1p and IEEE 802.1Q Bridge MIB



Technical Specifications

- RFC 1701 Generic Routing Encapsulation
 - RFC 1702 Generic Routing Encapsulation over IPv4 networks
 - RFC 1721 RIP-2 Analysis
 - RFC 1722 RIP-2 Applicability
 - RFC 1723 RIP v2
 - RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
 - RFC 1812 IPv4 Routing
 - RFC 1829 The ESP DES-CBC Transform
 - RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
 - RFC 1944 Benchmarking Methodology for Network Interconnect Devices
 - RFC 1973 PPP in Frame Relay
 - RFC 1974 PPP Stac LZS Compression Protocol
 - RFC 1990 The PPP Multilink Protocol (MP)
 - RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
 - RFC 2091 Trigger RIP
 - RFC 2131 DHCP
 - RFC 2132 DHCP Options and BOOTP Vendor Extensions
 - RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
 - RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
 - RFC 2280 Routing Policy Specification Language (RPSL)
 - RFC 2284 EAP over LAN
 - RFC 2338 VRRP
 - RFC 2364 PPP Over AAL5
 - RFC 2374 An Aggregatable Global Unicast Address Format
 - RFC 2451 The ESP CBC-Mode Cipher Algorithms
 - RFC 2453 RIPv2
 - RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
 - RFC 2511 Internet X.509 Certificate Request Message Format
 - RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
 - RFC 2644 Directed Broadcast Control
 - RFC 2661 L2TP
 - RFC 2663 NAT Terminology and Considerations
 - RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5
 - RFC 2694 DNS extensions to Network Address Translators (DNS ALG)
 - RFC 2737 Entity MIB (Version 2)
 - RFC 2863 The Interfaces Group MIB
 - RFC 2933 IGMP MIB
 - RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
 - RFC 1155 Structure of Management Information
 - RFC 1157 SNMPv1
 - RFC 1905 SNMPv2 Protocol Operations
 - RFC 2272 SNMPv3 Management Protocol
 - RFC 2273 SNMPv3 Applications
 - RFC 2274 USM for SNMPv3
 - RFC 2275 VACM for SNMPv3
 - RFC 2575 SNMPv3 View-based Access Control Model (VACM)
 - RFC 3164 BSD syslog Protocol
- OSPF**
- RFC 1245 OSPF protocol analysis
 - RFC 1246 Experience with OSPF
 - RFC 1587 OSPF NSSA
 - RFC 1765 OSPF Database Overflow
 - RFC 1850 OSPFv2 Management Information Base (MIB), traps
 - RFC 2328 OSPFv2
 - RFC 2370 OSPF Opaque LSA Option
 - RFC 3101 OSPF NSSA
- QoS/CoS**
- IEEE 802.1P (CoS)
 - RFC 2474 DS Field in the IPv4 and IPv6 Headers
 - RFC 2475 DiffServ Architecture
 - RFC 2597 DiffServ Assured Forwarding (AF)
 - RFC 2598 DiffServ Expedited Forwarding (EF)
 - RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
- Security**
- IEEE 802.1X Port Based Network Access Control
 - RFC 1321 The MD5 Message-Digest Algorithm
 - RFC 2082 RIP-2 MD5 Authentication
 - RFC 2104 Keyed-Hashing for Message Authentication
 - RFC 2138 RADIUS Authentication
 - RFC 2209 RSVP-Message Processing
 - RFC 2246 Transport Layer Security (TLS)
 - RFC 2716 PPP EAP TLS Authentication Protocol
 - RFC 2865 RADIUS Authentication
 - RFC 2866 RADIUS Accounting
 - RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication



Technical Specifications

RFC 2702 Requirements for Traffic Engineering Over MPLS	VPN
RFC 2747 RSVP Cryptographic Authentication	RFC 2403 - HMAC-MD5-96
RFC 2763 Dynamic Name-to-System ID mapping support	RFC 2404 - HMAC-SHA1-96
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)	RFC 2405 - DES-CBC Cipher algorithm
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)	RFC 2547 BGP/MPLS VPNs
RFC 2784 Generic Routing Encapsulation (GRE)	RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 2787 Definitions of Managed Objects for VRRP	RFC 2842 Capabilities Advertisement with BGP-4
RFC 2961 RSVP Refresh Overhead Reduction Extensions	RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS	RFC 2918 Route Refresh Capability for BGP-4
RFC 2973 IS-IS Mesh Groups	RFC 3107 Carrying Label Information in BGP-4
RFC 2993 Architectural Implications of NAT	IPsec
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)	RFC 1828 IP Authentication using Keyed MD5
RFC 3027 Protocol Complications with the IP Network Address Translator	RFC 2401 IP Security Architecture
RFC 3031 Multiprotocol Label Switching Architecture	RFC 2402 IP Authentication Header
RFC 3032 MPLS Label Stack Encoding	RFC 2406 IP Encapsulating Security Payload
	RFC 2407 - Domain of interpretation
	RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
	RFC 2411 IP Security Document Roadmap
	RFC 2412 - OAKLEY
	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-15-A Router (JF237A)

Ports	1 SIC slot
	1 RJ-45 ADSL2+ port
	1 Analog Modem port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
Physical characteristics	Dimensions 9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm) (1U height)
	Weight 6.61 lb. (3.0 kg)
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	Throughput up to 160 Kpps (64-byte packets)
	Routing table size 10000 entries
Environment	Operating temperature 32°F to 104°F (0°C to 40°C)
	Operating relative humidity 5% to 90%, noncondensing
	Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity 5% to 90%, noncondensing



Technical Specifications

Electrical characteristics	Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr) Voltage 100-120/200-240 VAC Maximum power rating 25 W Frequency 50/60 Hz Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J
Emissions	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B
Telecom	FCC part 68
Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
Notes	Height does not include antennas on wireless models; weight is with no optional modules installed.
Services	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E) 5 Yr 6 hr Call-to-Repair Onsite (UW081E)
	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.
Standards and protocols (applies to all products in series)	BGP RFC 1163 Border Gateway Protocol (BGP) RFC 1267 Border Gateway Protocol 3 (BGP-3) RFC 1657 Definitions of Managed Objects for BGPv4 RFC 1771 BGPv4 RFC 1772 Application of the BGP RFC 1773 Experience with the BGP-4 Protocol RFC 1774 BGP-4 Protocol Analysis RFC 3036 LDP Specification RFC 3046 DHCP Relay Agent Information Option RFC 3063 MPLS Loop Prevention Mechanism RFC 3065 Support AS confederation RFC 3137 OSPF Stub Router Advertisement RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels



Technical Specifications

RFC 1965 BGP4 confederations	RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
RFC 1997 BGP Communities Attribute	RFC 3214 LSP Modification Using CR-LDP
RFC 1998 PPP Gandalf FZA Compression Protocol	RFC 3215 LDP State Machine
RFC 2385 BGP Session Protection via TCP MD5	RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
RFC 2439 BGP Route Flap Damping	RFC 3277 IS-IS Transient Blackhole Avoidance
Device management	RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 1305 NTPv3	RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0	RFC 3392 Support BGP capabilities advertisement
RFC 2271 FrameWork	RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 2452 MIB for TCP6	RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
RFC 2454 MIB for UDP6	RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
General protocols	RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
IEEE 802.1D MAC Bridges	RFC 3784 ISIS TE support
IEEE 802.1p Priority	RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
IEEE 802.1Q VLANs	RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
IEEE 802.1s Multiple Spanning Trees	RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
IEEE 802.1w Rapid Reconfiguration of Spanning Tree	RFC 3847 Restart signaling for IS-IS
RFC 768 UDP	IP multicast
RFC 783 TFTP Protocol (revision 2)	RFC 1112 IGMP
RFC 791 IP	RFC 2236 IGMPv2
RFC 792 ICMP	RFC 2283 Multiprotocol Extensions for BGP-4
RFC 793 TCP	RFC 2362 PIM Sparse Mode
RFC 826 ARP	RFC 2365 Administratively Scoped IP Multicast
RFC 854 TELNET	RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 855 Telnet Option Specification	RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 856 TELNET	RFC 3376 IGMPv3
RFC 858 Telnet Suppress Go Ahead Option	IPv6
RFC 894 IP over Ethernet	RFC 1981 IPv6 Path MTU Discovery
RFC 925 Multi-LAN Address Resolution	RFC 2080 RIPng for IPv6
RFC 950 Internet Standard Subnetting Procedure	RFC 2292 Advanced Sockets API for IPv6
RFC 959 File Transfer Protocol (FTP)	RFC 2373 IPv6 Addressing Architecture
RFC 1006 ISO transport services on top of the TCP: Version 3	RFC 2460 IPv6 Specification
RFC 1027 Proxy ARP	
RFC 1034 Domain Concepts and Facilities	
RFC 1035 Domain Implementation and Specification	
RFC 1042 IP Datagrams	
RFC 1058 RIPv1	
RFC 1071 Computing the Internet Checksum	
RFC 1091 Telnet Terminal-Type Option	
RFC 1122 Host Requirements	
RFC 1141 Incremental updating of the Internet checksum	
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	
RFC 1144 Compressing TCP/IP headers for low-speed serial links	
RFC 1195 OSI ISIS for IP and Dual Environments	
RFC 1256 ICMP Router Discovery Protocol (IRDP)	



Technical Specifications

- RFC 1293 Inverse Address Resolution Protocol
 - RFC 1315 Management Information Base for Frame Relay DTEs
 - RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
 - RFC 1333 PPP Link Quality Monitoring
 - RFC 1334 PPP Authentication Protocols (PAP)
 - RFC 1349 Type of Service
 - RFC 1350 TFTP Protocol (revision 2)
 - RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
 - RFC 1381 SNMP MIB Extension for X.25 LAPB
 - RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol
 - RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol
 - RFC 1490 Multiprotocol Interconnect over Frame Relay
 - RFC 1519 CIDR
 - RFC 1534 DHCP/BOOTP Interoperation
 - RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
 - RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)
 - RFC 1577 Classical IP and ARP over ATM
 - RFC 1613 Cisco Systems X.25 over TCP (XOT)
 - RFC 1624 Incremental Internet Checksum
 - RFC 1631 NAT
 - RFC 1638 PPP Bridging Control Protocol (BCP)
 - RFC 1661 The Point-to-Point Protocol (PPP)
 - RFC 1662 PPP in HDLC-like Framing
 - RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
 - RFC 1701 Generic Routing Encapsulation
 - RFC 1702 Generic Routing Encapsulation over IPv4 networks
 - RFC 1721 RIP-2 Analysis
 - RFC 1722 RIP-2 Applicability
 - RFC 1723 RIP v2
 - RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
 - RFC 1812 IPv4 Routing
 - RFC 1829 The ESP DES-CBC Transform
 - RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
 - RFC 1944 Benchmarking Methodology for Network
 - RFC 2463 ICMPv6
 - RFC 2464 Transmission of IPv6 over Ethernet Networks
 - RFC 2472 IP Version 6 over PPP
 - RFC 2473 Generic Packet Tunneling in IPv6
 - RFC 2475 IPv6 DiffServ Architecture
 - RFC 2529 Transmission of IPv6 Packets over IPv4
 - RFC 2545 Use of MP-BGP-4 for IPv6
 - RFC 2553 Basic Socket Interface Extensions for IPv6
 - RFC 2740 OSPFv3 for IPv6
 - RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
 - RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
 - RFC 3513 IPv6 Addressing Architecture
 - RFC 3596 DNS Extension for IPv6
- MIBs**
- RFC 1213 MIB II
 - RFC 1229 Interface MIB Extensions
 - RFC 1286 Bridge MIB
 - RFC 1493 Bridge MIB
 - RFC 1573 SNMP MIB II
 - RFC 1724 RIPv2 MIB
 - RFC 1757 Remote Network Monitoring MIB
 - RFC 1850 OSPFv2 MIB
 - RFC 2011 SNMPv2 MIB for IP
 - RFC 2012 SNMPv2 MIB for TCP
 - RFC 2013 SNMPv2 MIB for UDP
 - RFC 2233 Interfaces MIB
 - RFC 2454 IPV6-UDP-MIB
 - RFC 2465 IPv6 MIB
 - RFC 2466 ICMPv6 MIB
 - RFC 2618 RADIUS Client MIB
 - RFC 2620 RADIUS Accounting MIB
 - RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
 - RFC 2737 Entity MIB (Version 2)
 - RFC 2863 The Interfaces Group MIB
 - RFC 2933 IGMP MIB
 - RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
 - RFC 1155 Structure of Management Information
 - RFC 1157 SNMPv1
 - RFC 1905 SNMPv2 Protocol Operations
 - RFC 2272 SNMPv3 Management Protocol
 - RFC 2273 SNMPv3 Applications
 - RFC 2274 USM for SNMPv3
 - RFC 2275 VACM for SNMPv3
 - RFC 2575 SNMPv3 View-based Access Control



Technical Specifications

Interconnect Devices
RFC 1973 PPP in Frame Relay
RFC 1974 PPP Stac LZS Compression Protocol
RFC 1990 The PPP Multilink Protocol (MP)
RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
RFC 2091 Trigger RIP
RFC 2131 DHCP
RFC 2132 DHCP Options and BOOTP Vendor Extensions
RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
RFC 2280 Routing Policy Specification Language (RPSL)
RFC 2284 EAP over LAN
RFC 2338 VRRP
RFC 2364 PPP Over AAL5
RFC 2374 An Aggregatable Global Unicast Address Format
RFC 2451 The ESP CBC-Mode Cipher Algorithms
RFC 2453 RIPv2
RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
RFC 2511 Internet X.509 Certificate Request Message Format
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
RFC 2644 Directed Broadcast Control
RFC 2661 L2TP
RFC 2663 NAT Terminology and Considerations
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5
RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)
RFC 2702 Requirements for Traffic Engineering Over MPLS
RFC 2747 RSVP Cryptographic Authentication
RFC 2763 Dynamic Name-to-System ID mapping support
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)
RFC 2784 Generic Routing Encapsulation (GRE)
RFC 2787 Definitions of Managed Objects for VRRP
RFC 2961 RSVP Refresh Overhead Reduction Extensions
RFC 2966 Domain-wide Prefix Distribution with

Model (VACM)
RFC 3164 BSD syslog Protocol

OSPF

RFC 1245 OSPF protocol analysis
RFC 1246 Experience with OSPF
RFC 1587 OSPF NSSA
RFC 1765 OSPF Database Overflow
RFC 1850 OSPFv2 Management Information Base (MIB), traps
RFC 2328 OSPFv2
RFC 2370 OSPF Opaque LSA Option
RFC 3101 OSPF NSSA

QoS/CoS

IEEE 802.1P (CoS)
RFC 2474 DS Field in the IPv4 and IPv6 Headers
RFC 2475 DiffServ Architecture
RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)
RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP

Security

IEEE 802.1X Port Based Network Access Control
RFC 1321 The MD5 Message-Digest Algorithm
RFC 2082 RIP-2 MD5 Authentication
RFC 2104 Keyed-Hashing for Message Authentication
RFC 2138 RADIUS Authentication
RFC 2209 RSVP-Message Processing
RFC 2246 Transport Layer Security (TLS)
RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication

VPN

RFC 2403 - HMAC-MD5-96
RFC 2404 - HMAC-SHA1-96
RFC 2405 - DES-CBC Cipher algorithm
RFC 2547 BGP/MPLS VPNs
RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 2842 Capabilities Advertisement with BGP-4
RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2918 Route Refresh Capability for BGP-4
RFC 3107 Carrying Label Information in BGP-4

IPsec

RFC 1828 IP Authentication using Keyed MD5



Technical Specifications

Two-Level IS-IS	RFC 2401 IP Security Architecture
RFC 2973 IS-IS Mesh Groups	RFC 2402 IP Authentication Header
RFC 2993 Architectural Implications of NAT	RFC 2406 IP Encapsulating Security Payload
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)	RFC 2407 - Domain of interpretation
RFC 3027 Protocol Complications with the IP Network Address Translator	RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
RFC 3031 Multiprotocol Label Switching Architecture	RFC 2411 IP Security Document Roadmap
RFC 3032 MPLS Label Stack Encoding	RFC 2412 – OAKLEY
	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-15-A-W Router (JF809A)

Ports	1 SIC slot	
	1 RJ-45 ADSL2+ port	
	1 Analog Modem port	
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full	
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full	
AP characteristics	Radios	Single (b/g)
	Radio operation modes	Client access
	AP operation modes	Autonomous
	Wi-Fi Alliance Certification*	b/g Wi-Fi Certified
* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing preformed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.		
Physical characteristics	Dimensions	9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm) (1U height)
	Weight	6.61 lb. (3.0 kg)
Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	
Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries
Environment	Operating temperature	32°F to 104°F (0°C to 40°C)
	Operating relative humidity	5% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-120/200-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz



Technical Specifications

	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J	
Emissions	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	
Notes	Height does not include antennas on wireless models; weight is with no optional modules installed.	
Services	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E) 5 Yr 6 hr Call-to-Repair Onsite (UW081E)	
	Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.	
Standards and protocols (applies to all products in series)	BGP RFC 1163 Border Gateway Protocol (BGP) RFC 1267 Border Gateway Protocol 3 (BGP-3) RFC 1657 Definitions of Managed Objects for BGPv4 RFC 1771 BGPv4 RFC 1772 Application of the BGP RFC 1773 Experience with the BGP-4 Protocol RFC 1774 BGP-4 Protocol Analysis RFC 1965 BGP4 confederations RFC 1997 BGP Communities Attribute RFC 1998 PPP Gandalf FZA Compression Protocol RFC 2385 BGP Session Protection via TCP MD5	RFC 3036 LDP Specification RFC 3046 DHCP Relay Agent Information Option RFC 3063 MPLS Loop Prevention Mechanism RFC 3065 Support AS confederation RFC 3137 OSPF Stub Router Advertisement RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP) RFC 3214 LSP Modification Using CR-LDP RFC 3215 LDP State Machine



Technical Specifications

RFC 2439 BGP Route Flap Damping

Device management

RFC 1305 NTPv3

RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0

RFC 2271 FrameWork

RFC 2452 MIB for TCP6

RFC 2454 MIB for UDP6

General protocols

IEEE 802.1D MAC Bridges

IEEE 802.1p Priority

IEEE 802.1Q VLANs

IEEE 802.1s Multiple Spanning Trees

IEEE 802.1w Rapid Reconfiguration of Spanning Tree

RFC 768 UDP

RFC 783 TFTP Protocol (revision 2)

RFC 791 IP

RFC 792 ICMP

RFC 793 TCP

RFC 826 ARP

RFC 854 TELNET

RFC 855 Telnet Option Specification

RFC 856 TELNET

RFC 858 Telnet Suppress Go Ahead Option

RFC 894 IP over Ethernet

RFC 925 Multi-LAN Address Resolution

RFC 950 Internet Standard Subnetting Procedure

RFC 959 File Transfer Protocol (FTP)

RFC 1006 ISO transport services on top of the TCP: **IP multicast**

Version 3

RFC 1027 Proxy ARP

RFC 1034 Domain Concepts and Facilities

RFC 1035 Domain Implementation and Specification

RFC 1042 IP Datagrams

RFC 1058 RIPv1

RFC 1071 Computing the Internet Checksum

RFC 1091 Telnet Terminal-Type Option

RFC 1122 Host Requirements

RFC 1141 Incremental updating of the Internet checksum

RFC 1142 OSI IS-IS Intra-domain Routing Protocol

RFC 1144 Compressing TCP/IP headers for low-speed serial links

RFC 1195 OSI ISIS for IP and Dual Environments

RFC 1256 ICMP Router Discovery Protocol (IRDP)

RFC 1293 Inverse Address Resolution Protocol

RFC 1315 Management Information Base for Frame

Relay DTEs

RFC 3268 Advanced Encryption Standard (AES)

Ciphersuites for Transport Layer Security (TLS)

RFC 3277 IS-IS Transient Blackhole Avoidance

RFC 3279 Algorithms and Identifiers for the Internet

X.509 Public Key Infrastructure Certificate and

Certificate Revocation List (CRL) Profile

RFC 3280 Internet X.509 Public Key Infrastructure

Certificate and Certificate Revocation List (CRL)

Profile

RFC 3392 Support BGP capabilities advertisement

RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)

RFC 3564 Requirements for Support of

Differentiated Services-aware MPLS Traffic

Engineering

RFC 3602 The AES-CBC Cipher Algorithm and Its

Use with IPsec

RFC 3706 A Traffic-Based Method of Detecting

Dead Internet Key Exchange (IKE) Peers

RFC 3784 ISIS TE support

RFC 3786 Extending the Number of IS-IS LSP

Fragments Beyond the 256 Limit

RFC 3811 Definitions of Textual Conventions (TCs)

for Multiprotocol Label Switching (MPLS)

Management

RFC 3812 Multiprotocol Label Switching (MPLS)

Traffic Engineering (TE) Management Information

Base (MIB)

RFC 3847 Restart signaling for IS-IS

IP multicast

RFC 1112 IGMP

RFC 2236 IGMPv2

RFC 2283 Multiprotocol Extensions for BGP-4

RFC 2362 PIM Sparse Mode

RFC 2365 Administratively Scoped IP Multicast

RFC 2710 Multicast Listener Discovery (MLD) for IPv6

RFC 2934 Protocol Independent Multicast MIB for IPv4

IPv4

RFC 3376 IGMPv3

IPv6

RFC 1981 IPv6 Path MTU Discovery

RFC 2080 RIPng for IPv6

RFC 2292 Advanced Sockets API for IPv6

RFC 2373 IPv6 Addressing Architecture

RFC 2460 IPv6 Specification

RFC 2463 ICMPv6

RFC 2464 Transmission of IPv6 over Ethernet Networks

RFC 2472 IP Version 6 over PPP



Technical Specifications

- RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
 - RFC 1333 PPP Link Quality Monitoring
 - RFC 1334 PPP Authentication Protocols (PAP)
 - RFC 1349 Type of Service
 - RFC 1350 TFTP Protocol (revision 2)
 - RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
 - RFC 1381 SNMP MIB Extension for X.25 LAPB
 - RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol
 - RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol
 - RFC 1490 Multiprotocol Interconnect over Frame Relay
 - RFC 1519 CIDR
 - RFC 1534 DHCP/BOOTP Interoperation
 - RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
 - RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)
 - RFC 1577 Classical IP and ARP over ATM
 - RFC 1613 Cisco Systems X.25 over TCP (XOT)
 - RFC 1624 Incremental Internet Checksum
 - RFC 1631 NAT
 - RFC 1638 PPP Bridging Control Protocol (BCP)
 - RFC 1661 The Point-to-Point Protocol (PPP)
 - RFC 1662 PPP in HDLC-like Framing
 - RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
 - RFC 1701 Generic Routing Encapsulation
 - RFC 1702 Generic Routing Encapsulation over IPv4 networks
 - RFC 1721 RIP-2 Analysis
 - RFC 1722 RIP-2 Applicability
 - RFC 1723 RIP v2
 - RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
 - RFC 1812 IPv4 Routing
 - RFC 1829 The ESP DES-CBC Transform
 - RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
 - RFC 1944 Benchmarking Methodology for Network Interconnect Devices
 - RFC 1973 PPP in Frame Relay
 - RFC 1974 PPP Stac LZS Compression Protocol
 - RFC 1990 The PPP Multilink Protocol (MP)
 - RFC 2473 Generic Packet Tunneling in IPv6
 - RFC 2475 IPv6 DiffServ Architecture
 - RFC 2529 Transmission of IPv6 Packets over IPv4
 - RFC 2545 Use of MP-BGP-4 for IPv6
 - RFC 2553 Basic Socket Interface Extensions for IPv6
 - RFC 2740 OSPFv3 for IPv6
 - RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
 - RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
 - RFC 3513 IPv6 Addressing Architecture
 - RFC 3596 DNS Extension for IPv6
- MIBs**
- RFC 1213 MIB II
 - RFC 1229 Interface MIB Extensions
 - RFC 1286 Bridge MIB
 - RFC 1493 Bridge MIB
 - RFC 1573 SNMP MIB II
 - RFC 1724 RIPv2 MIB
 - RFC 1757 Remote Network Monitoring MIB
 - RFC 1850 OSPFv2 MIB
 - RFC 2011 SNMPv2 MIB for IP
 - RFC 2012 SNMPv2 MIB for TCP
 - RFC 2013 SNMPv2 MIB for UDP
 - RFC 2233 Interfaces MIB
 - RFC 2454 IPV6-UDP-MIB
 - RFC 2465 IPv6 MIB
 - RFC 2466 ICMPv6 MIB
 - RFC 2618 RADIUS Client MIB
 - RFC 2620 RADIUS Accounting MIB
 - RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
 - RFC 2737 Entity MIB (Version 2)
 - RFC 2863 The Interfaces Group MIB
 - RFC 2933 IGMP MIB
 - RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
 - RFC 1155 Structure of Management Information
 - RFC 1157 SNMPv1
 - RFC 1905 SNMPv2 Protocol Operations
 - RFC 2272 SNMPv3 Management Protocol
 - RFC 2273 SNMPv3 Applications
 - RFC 2274 USM for SNMPv3
 - RFC 2275 VACM for SNMPv3
 - RFC 2575 SNMPv3 View-based Access Control Model (VACM)
 - RFC 3164 BSD syslog Protocol
- OSPF**



Technical Specifications

- RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
 - RFC 2091 Trigger RIP
 - RFC 2131 DHCP
 - RFC 2132 DHCP Options and BOOTP Vendor Extensions
 - RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
 - RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
 - RFC 2280 Routing Policy Specification Language (RPSL)
 - RFC 2284 EAP over LAN
 - RFC 2338 VRRP
 - RFC 2364 PPP Over AAL5
 - RFC 2374 An Aggregatable Global Unicast Address Format
 - RFC 2451 The ESP CBC-Mode Cipher Algorithms
 - RFC 2453 IPv2
 - RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
 - RFC 2511 Internet X.509 Certificate Request Message Format
 - RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
 - RFC 2644 Directed Broadcast Control
 - RFC 2661 L2TP
 - RFC 2663 NAT Terminology and Considerations
 - RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5
 - RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)
 - RFC 2702 Requirements for Traffic Engineering Over MPLS
 - RFC 2747 RSVP Cryptographic Authentication
 - RFC 2763 Dynamic Name-to-System ID mapping support
 - RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)
 - RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)
 - RFC 2784 Generic Routing Encapsulation (GRE)
 - RFC 2787 Definitions of Managed Objects for VRRP
 - RFC 2961 RSVP Refresh Overhead Reduction Extensions
 - RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS
 - RFC 2973 IS-IS Mesh Groups
 - RFC 2993 Architectural Implications of NAT
 - RFC 3022 Traditional IP Network Address
 - RFC 1245 OSPF protocol analysis
 - RFC 1246 Experience with OSPF
 - RFC 1587 OSPF NSSA
 - RFC 1765 OSPF Database Overflow
 - RFC 1850 OSPFv2 Management Information Base (MIB), traps
 - RFC 2328 OSPFv2
 - RFC 2370 OSPF Opaque LSA Option
 - RFC 3101 OSPF NSSA
- QoS/CoS**
- IEEE 802.1P (CoS)
 - RFC 2474 DS Field in the IPv4 and IPv6 Headers
 - RFC 2475 DiffServ Architecture
 - RFC 2597 DiffServ Assured Forwarding (AF)
 - RFC 2598 DiffServ Expedited Forwarding (EF)
 - RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
- Security**
- IEEE 802.1X Port Based Network Access Control
 - RFC 1321 The MD5 Message-Digest Algorithm
 - RFC 2082 RIP-2 MD5 Authentication
 - RFC 2104 Keyed-Hashing for Message Authentication
 - RFC 2138 RADIUS Authentication
 - RFC 2209 RSVP-Message Processing
 - RFC 2246 Transport Layer Security (TLS)
 - RFC 2716 PPP EAP TLS Authentication Protocol
 - RFC 2865 RADIUS Authentication
 - RFC 2866 RADIUS Accounting
 - RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
- VPN**
- RFC 2403 - HMAC-MD5-96
 - RFC 2404 - HMAC-SHA1-96
 - RFC 2405 - DES-CBC Cipher algorithm
 - RFC 2547 BGP/MPLS VPNs
 - RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
 - RFC 2842 Capabilities Advertisement with BGP-4
 - RFC 2858 Multiprotocol Extensions for BGP-4
 - RFC 2918 Route Refresh Capability for BGP-4
 - RFC 3107 Carrying Label Information in BGP-4
- IPsec**
- RFC 1828 IP Authentication using Keyed MD5
 - RFC 2401 IP Security Architecture
 - RFC 2402 IP Authentication Header
 - RFC 2406 IP Encapsulating Security Payload
 - RFC 2407 - Domain of interpretation



Technical Specifications

Translator (Traditional NAT)	RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
RFC 3027 Protocol Complications with the IP Network Address Translator	RFC 2411 IP Security Document Roadmap
RFC 3031 Multiprotocol Label Switching Architecture	RFC 2412 – OAKLEY
RFC 3032 MPLS Label Stack Encoding	RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-15-I Router (JF236A)

Ports	1 SIC slot
	1 RJ-45 ADSL2+ port
	1 ISDN port
	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
Physical characteristics	Dimensions 9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm)
	Weight 6.61 lb. (3.0 kg)
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	Throughput up to 160 Kpps (64-byte packets)
	Routing table size 10000 entries
Environment	Operating temperature 32°F to 104°F (0°C to 40°C)
	Operating relative humidity 5% to 90%, noncondensing
	Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity 5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr)
	Voltage 100-120/200-240 VAC
	Maximum power rating 25 W
	Frequency 50/60 Hz
	Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J
Emissions	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B
Telecom	FCC part 68



Technical Specifications

Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB
Notes	Height does not include antennas on wireless models; weight is with no optional modules installed.
Services	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E) 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E) 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E) 5-year, 24x7 SW phone support, software updates (UW014E) 3 Yr 6 hr Call-to-Repair Onsite (UW079E) 4 Yr 6 hr Call-to-Repair Onsite (UW080E) 5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols (applies to all products in series)

BGP	RFC 1163 Border Gateway Protocol (BGP)	RFC 3036 LDP Specification
	RFC 1267 Border Gateway Protocol 3 (BGP-3)	RFC 3046 DHCP Relay Agent Information Option
	RFC 1657 Definitions of Managed Objects for BGPv4	RFC 3063 MPLS Loop Prevention Mechanism
	RFC 1771 BGPv4	RFC 3065 Support AS confederation
	RFC 1772 Application of the BGP	RFC 3137 OSPF Stub Router Advertisement
	RFC 1773 Experience with the BGP-4 Protocol	RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
	RFC 1774 BGP-4 Protocol Analysis	RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
	RFC 1965 BGP4 confederations	RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
	RFC 1997 BGP Communities Attribute	RFC 3214 LSP Modification Using CR-LDP
	RFC 1998 PPP Gandalf FZA Compression Protocol	RFC 3215 LDP State Machine
	RFC 2385 BGP Session Protection via TCP MD5	RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
	RFC 2439 BGP Route Flap Damping	RFC 3277 IS-IS Transient Blackhole Avoidance
Device management	RFC 1305 NTPv3	RFC 3279 Algorithms and Identifiers for the Internet
	RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0	X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
	RFC 2271 FrameWork	RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
	RFC 2452 MIB for TCP6	RFC 3392 Support BGP capabilities advertisement
	RFC 2454 MIB for UDP6	RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
General protocols	IEEE 802.1D MAC Bridges	RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic
	IEEE 802.1p Priority	
	IEEE 802.1Q VLANs	
	IEEE 802.1s Multiple Spanning Trees	



Technical Specifications

- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
 - RFC 768 UDP
 - RFC 783 TFTP Protocol (revision 2)
 - RFC 791 IP
 - RFC 792 ICMP
 - RFC 793 TCP
 - RFC 826 ARP
 - RFC 854 TELNET
 - RFC 855 Telnet Option Specification
 - RFC 856 TELNET
 - RFC 858 Telnet Suppress Go Ahead Option
 - RFC 894 IP over Ethernet
 - RFC 925 Multi-LAN Address Resolution
 - RFC 950 Internet Standard Subnetting Procedure
 - RFC 959 File Transfer Protocol (FTP)
 - RFC 1006 ISO transport services on top of the TCP: Version 3
 - RFC 1027 Proxy ARP
 - RFC 1034 Domain Concepts and Facilities
 - RFC 1035 Domain Implementation and Specification
 - RFC 1042 IP Datagrams
 - RFC 1058 RIPv1
 - RFC 1071 Computing the Internet Checksum
 - RFC 1091 Telnet Terminal-Type Option
 - RFC 1122 Host Requirements
 - RFC 1141 Incremental updating of the Internet checksum
 - RFC 1142 OSI IS-IS Intra-domain Routing Protocol
 - RFC 1144 Compressing TCP/IP headers for low-speed serial links
 - RFC 1195 OSI ISIS for IP and Dual Environments
 - RFC 1256 ICMP Router Discovery Protocol (IRDP)
 - RFC 1293 Inverse Address Resolution Protocol
 - RFC 1315 Management Information Base for Frame Relay DTEs
 - RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
 - RFC 1333 PPP Link Quality Monitoring
 - RFC 1334 PPP Authentication Protocols (PAP)
 - RFC 1349 Type of Service
 - RFC 1350 TFTP Protocol (revision 2)
 - RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
 - RFC 1381 SNMP MIB Extension for X.25 LAPB
 - RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol
 - RFC 1472 The Definitions of Managed Objects for Engineering
 - RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
 - RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
 - RFC 3784 ISIS TE support
 - RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
 - RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
 - RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
 - RFC 3847 Restart signaling for IS-IS
- IP multicast**
- RFC 1112 IGMP
 - RFC 2236 IGMPv2
 - RFC 2283 Multiprotocol Extensions for BGP-4
 - RFC 2362 PIM Sparse Mode
 - RFC 2365 Administratively Scoped IP Multicast
 - RFC 2710 Multicast Listener Discovery (MLD) for IPv6
 - RFC 2934 Protocol Independent Multicast MIB for IPv4
 - RFC 3376 IGMPv3
- IPv6**
- RFC 1981 IPv6 Path MTU Discovery
 - RFC 2080 RIPng for IPv6
 - RFC 2292 Advanced Sockets API for IPv6
 - RFC 2373 IPv6 Addressing Architecture
 - RFC 2460 IPv6 Specification
 - RFC 2463 ICMPv6
 - RFC 2464 Transmission of IPv6 over Ethernet Networks
 - RFC 2472 IP Version 6 over PPP
 - RFC 2473 Generic Packet Tunneling in IPv6
 - RFC 2475 IPv6 DiffServ Architecture
 - RFC 2529 Transmission of IPv6 Packets over IPv4
 - RFC 2545 Use of MP-BGP-4 for IPv6
 - RFC 2553 Basic Socket Interface Extensions for IPv6
 - RFC 2740 OSPFv3 for IPv6
 - RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
 - RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
 - RFC 3513 IPv6 Addressing Architecture
 - RFC 3596 DNS Extension for IPv6



Technical Specifications

- the Security Protocols of the Point-to-Point Protocol
- RFC 1490 Multiprotocol Interconnect over Frame Relay
- RFC 1519 CIDR
- RFC 1534 DHCP/BOOTP Interoperation
- RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
- RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)
- RFC 1577 Classical IP and ARP over ATM
- RFC 1613 Cisco Systems X.25 over TCP (XOT)
- RFC 1624 Incremental Internet Checksum
- RFC 1631 NAT
- RFC 1638 PPP Bridging Control Protocol (BCP)
- RFC 1661 The Point-to-Point Protocol (PPP)
- RFC 1662 PPP in HDLC-like Framing
- RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
- RFC 1701 Generic Routing Encapsulation
- RFC 1702 Generic Routing Encapsulation over IPv4 networks
- RFC 1721 RIP-2 Analysis
- RFC 1722 RIP-2 Applicability
- RFC 1723 RIP v2
- RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
- RFC 1812 IPv4 Routing
- RFC 1829 The ESP DES-CBC Transform
- RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
- RFC 1944 Benchmarking Methodology for Network Interconnect Devices
- RFC 1973 PPP in Frame Relay
- RFC 1974 PPP Stac LZS Compression Protocol
- RFC 1990 The PPP Multilink Protocol (MP)
- RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
- RFC 2091 Trigger RIP
- RFC 2131 DHCP
- RFC 2132 DHCP Options and BOOTP Vendor Extensions
- RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
- RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
- RFC 2280 Routing Policy Specification Language (RPSL)
- RFC 2284 EAP over LAN
- MIBs**
- RFC 1213 MIB II
- RFC 1229 Interface MIB Extensions
- RFC 1286 Bridge MIB
- RFC 1493 Bridge MIB
- RFC 1573 SNMP MIB II
- RFC 1724 RIPv2 MIB
- RFC 1757 Remote Network Monitoring MIB
- RFC 1850 OSPFv2 MIB
- RFC 2011 SNMPv2 MIB for IP
- RFC 2012 SNMPv2 MIB for TCP
- RFC 2013 SNMPv2 MIB for UDP
- RFC 2233 Interfaces MIB
- RFC 2454 IPV6-UDP-MIB
- RFC 2465 IPv6 MIB
- RFC 2466 ICMPv6 MIB
- RFC 2618 RADIUS Client MIB
- RFC 2620 RADIUS Accounting MIB
- RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
- RFC 2737 Entity MIB (Version 2)
- RFC 2863 The Interfaces Group MIB
- RFC 2933 IGMP MIB
- RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
- RFC 1155 Structure of Management Information
- RFC 1157 SNMPv1
- RFC 1905 SNMPv2 Protocol Operations
- RFC 2272 SNMPv3 Management Protocol
- RFC 2273 SNMPv3 Applications
- RFC 2274 USM for SNMPv3
- RFC 2275 VACM for SNMPv3
- RFC 2575 SNMPv3 View-based Access Control Model (VACM)
- RFC 3164 BSD syslog Protocol
- OSPF**
- RFC 1245 OSPF protocol analysis
- RFC 1246 Experience with OSPF
- RFC 1587 OSPF NSSA
- RFC 1765 OSPF Database Overflow
- RFC 1850 OSPFv2 Management Information Base (MIB), traps
- RFC 2328 OSPFv2
- RFC 2370 OSPF Opaque LSA Option
- RFC 3101 OSPF NSSA
- QoS/CoS**
- IEEE 802.1P (CoS)
- RFC 2474 DS Field in the IPv4 and IPv6 Headers
- RFC 2475 DiffServ Architecture



Technical Specifications

RFC 2338 VRRP
RFC 2364 PPP Over AAL5
RFC 2374 An Aggregatable Global Unicast Address Format
RFC 2451 The ESP CBC-Mode Cipher Algorithms
RFC 2453 RIPv2
RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
RFC 2511 Internet X.509 Certificate Request Message Format
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
RFC 2644 Directed Broadcast Control
RFC 2661 L2TP
RFC 2663 NAT Terminology and Considerations
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5
RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)
RFC 2702 Requirements for Traffic Engineering Over MPLS
RFC 2747 RSVP Cryptographic Authentication
RFC 2763 Dynamic Name-to-System ID mapping support
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)
RFC 2784 Generic Routing Encapsulation (GRE)
RFC 2787 Definitions of Managed Objects for VRRP
RFC 2961 RSVP Refresh Overhead Reduction Extensions
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS
RFC 2973 IS-IS Mesh Groups
RFC 2993 Architectural Implications of NAT
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)
RFC 3027 Protocol Complications with the IP Network Address Translator
RFC 3031 Multiprotocol Label Switching Architecture
RFC 3032 MPLS Label Stack Encoding

RFC 2597 DiffServ Assured Forwarding (AF)
RFC 2598 DiffServ Expedited Forwarding (EF)
RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP

Security

IEEE 802.1X Port Based Network Access Control
RFC 1321 The MD5 Message-Digest Algorithm
RFC 2082 RIP-2 MD5 Authentication
RFC 2104 Keyed-Hashing for Message Authentication
RFC 2138 RADIUS Authentication
RFC 2209 RSVP-Message Processing
RFC 2246 Transport Layer Security (TLS)
RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication

VPN

RFC 2403 - HMAC-MD5-96
RFC 2404 - HMAC-SHA1-96
RFC 2405 - DES-CBC Cipher algorithm
RFC 2547 BGP/MPLS VPNs
RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 2842 Capabilities Advertisement with BGP-4
RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2918 Route Refresh Capability for BGP-4
RFC 3107 Carrying Label Information in BGP-4

IPsec

RFC 1828 IP Authentication using Keyed MD5
RFC 2401 IP Security Architecture
RFC 2402 IP Authentication Header
RFC 2406 IP Encapsulating Security Payload
RFC 2407 - Domain of interpretation
RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
RFC 2411 IP Security Document Roadmap
RFC 2412 - OAKLEY
RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-15-I-W Router (JF238A)

Ports
1 SIC slot
1 RJ-45 ADSL2+ port
1 ISDN port



Technical Specifications

	1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
	4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
AP characteristics	<p>Radios Single (b/g)</p> <p>Radio operation modes Client access</p> <p>AP operation modes Autonomous</p> <p>Wi-Fi Alliance Certification* b/g Wi-Fi Certified</p> <p>* HP access points and access devices are Wi-Fi Certified, providing our customers with the assurance that these products have met and passed the rigorous interoperability testing performed by the Wi-Fi Alliance Organization. See the Specifications section of this series for more information.</p>
Physical characteristics	<p>Dimensions 9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm) (1U height)</p> <p>Weight 6.61 lb. (3 kg)</p>
Memory and processor	Processor RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.
Performance	<p>Throughput up to 160 Kpps (64-byte packets)</p> <p>Routing table size 10000 entries</p>
Environment	<p>Operating temperature 32°F to 104°F (0°C to 40°C)</p> <p>Operating relative humidity 5% to 90%, noncondensing</p> <p>Nonoperating/Storage temperature -40°F to 158°F (-40°C to 70°C)</p> <p>Nonoperating/Storage relative humidity 5% to 90%, noncondensing</p>
Electrical characteristics	<p>Maximum heat dissipation 85 BTU/hr (89.68 kJ/hr)</p> <p>Voltage 100-120/200-240 VAC</p> <p>Maximum power rating 25 W</p> <p>Frequency 50/60 Hz</p> <p>Notes Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.</p>
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; EN 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J
Emissions	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B
Telecom	FCC part 68
Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB



Technical Specifications

Notes Height does not include antennas on wireless models; weight is with no optional modules installed.

Services

- 3-year, parts only, global next-day advance exchange (UW075E)
- 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E)
- 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E)
- 3-year, 24x7 SW phone support, software updates (UW012E)
- 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E)
- 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E)
- 4-year, 24x7 SW phone support, software updates (UW013E)
- 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols
(applies to all products in series)

BGP

- RFC 1163 Border Gateway Protocol (BGP)
- RFC 1267 Border Gateway Protocol 3 (BGP-3)
- RFC 1657 Definitions of Managed Objects for BGPv4
- RFC 1771 BGPv4
- RFC 1772 Application of the BGP
- RFC 1773 Experience with the BGP-4 Protocol
- RFC 1774 BGP-4 Protocol Analysis
- RFC 1965 BGP4 confederations
- RFC 1997 BGP Communities Attribute
- RFC 1998 PPP Gandalf FZA Compression Protocol
- RFC 2385 BGP Session Protection via TCP MD5
- RFC 2439 BGP Route Flap Damping

Device management

- RFC 1305 NTPv3
- RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
- RFC 2271 FrameWork
- RFC 2452 MIB for TCP6
- RFC 2454 MIB for UDP6

General protocols

- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- RFC 768 UDP

RFC 3036 LDP Specification

- RFC 3046 DHCP Relay Agent Information Option
- RFC 3063 MPLS Loop Prevention Mechanism
- RFC 3065 Support AS confederation
- RFC 3137 OSPF Stub Router Advertisement
- RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
- RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
- RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
- RFC 3214 LSP Modification Using CR-LDP
- RFC 3215 LDP State Machine
- RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
- RFC 3277 IS-IS Transient Blackhole Avoidance
- RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3392 Support BGP capabilities advertisement
- RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
- RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
- RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec



Technical Specifications

- RFC 783 TFTP Protocol (revision 2)
 - RFC 791 IP
 - RFC 792 ICMP
 - RFC 793 TCP
 - RFC 826 ARP
 - RFC 854 TELNET
 - RFC 855 Telnet Option Specification
 - RFC 856 TELNET
 - RFC 858 Telnet Suppress Go Ahead Option
 - RFC 894 IP over Ethernet
 - RFC 925 Multi-LAN Address Resolution
 - RFC 950 Internet Standard Subnetting Procedure
 - RFC 959 File Transfer Protocol (FTP)
 - RFC 1006 ISO transport services on top of the TCP: Version 3
 - RFC 1027 Proxy ARP
 - RFC 1034 Domain Concepts and Facilities
 - RFC 1035 Domain Implementation and Specification
 - RFC 1042 IP Datagrams
 - RFC 1058 RIPv1
 - RFC 1071 Computing the Internet Checksum
 - RFC 1091 Telnet Terminal-Type Option
 - RFC 1122 Host Requirements
 - RFC 1141 Incremental updating of the Internet checksum
 - RFC 1142 OSI IS-IS Intra-domain Routing Protocol
 - RFC 1144 Compressing TCP/IP headers for low-speed serial links
 - RFC 1195 OSI ISIS for IP and Dual Environments
 - RFC 1256 ICMP Router Discovery Protocol (IRDP)
 - RFC 1293 Inverse Address Resolution Protocol
 - RFC 1315 Management Information Base for Frame Relay DTEs
 - RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)
 - RFC 1333 PPP Link Quality Monitoring
 - RFC 1334 PPP Authentication Protocols (PAP)
 - RFC 1349 Type of Service
 - RFC 1350 TFTP Protocol (revision 2)
 - RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)
 - RFC 1381 SNMP MIB Extension for X.25 LAPB
 - RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol
 - RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol
 - RFC 1490 Multiprotocol Interconnect over Frame Relay
 - RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
 - RFC 3784 ISIS TE support
 - RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
 - RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
 - RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
 - RFC 3847 Restart signaling for IS-IS
- IP multicast**
- RFC 1112 IGMP
 - RFC 2236 IGMPv2
 - RFC 2283 Multiprotocol Extensions for BGP-4
 - RFC 2362 PIM Sparse Mode
 - RFC 2365 Administratively Scoped IP Multicast
 - RFC 2710 Multicast Listener Discovery (MLD) for IPv6
 - RFC 2934 Protocol Independent Multicast MIB for IPv4
 - RFC 3376 IGMPv3
- IPv6**
- RFC 1981 IPv6 Path MTU Discovery
 - RFC 2080 RIPng for IPv6
 - RFC 2292 Advanced Sockets API for IPv6
 - RFC 2373 IPv6 Addressing Architecture
 - RFC 2460 IPv6 Specification
 - RFC 2463 ICMPv6
 - RFC 2464 Transmission of IPv6 over Ethernet Networks
 - RFC 2472 IP Version 6 over PPP
 - RFC 2473 Generic Packet Tunneling in IPv6
 - RFC 2475 IPv6 DiffServ Architecture
 - RFC 2529 Transmission of IPv6 Packets over IPv4
 - RFC 2545 Use of MP-BGP-4 for IPv6
 - RFC 2553 Basic Socket Interface Extensions for IPv6
 - RFC 2740 OSPFv3 for IPv6
 - RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
 - RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
 - RFC 3513 IPv6 Addressing Architecture
 - RFC 3596 DNS Extension for IPv6
- MIBs**
- RFC 1213 MIB II
 - RFC 1229 Interface MIB Extensions



Technical Specifications

- RFC 1519 CIDR
 - RFC 1534 DHCP/BOOTP Interoperation
 - RFC 1542 Clarifications and Extensions for the Bootstrap Protocol
 - RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)
 - RFC 1577 Classical IP and ARP over ATM
 - RFC 1613 Cisco Systems X.25 over TCP (XOT)
 - RFC 1624 Incremental Internet Checksum
 - RFC 1631 NAT
 - RFC 1638 PPP Bridging Control Protocol (BCP)
 - RFC 1661 The Point-to-Point Protocol (PPP)
 - RFC 1662 PPP in HDLC-like Framing
 - RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
 - RFC 1701 Generic Routing Encapsulation
 - RFC 1702 Generic Routing Encapsulation over IPv4 networks
 - RFC 1721 RIP-2 Analysis
 - RFC 1722 RIP-2 Applicability
 - RFC 1723 RIP v2
 - RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
 - RFC 1812 IPv4 Routing
 - RFC 1829 The ESP DES-CBC Transform
 - RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
 - RFC 1944 Benchmarking Methodology for Network Interconnect Devices
 - RFC 1973 PPP in Frame Relay
 - RFC 1974 PPP Stac LZS Compression Protocol
 - RFC 1990 The PPP Multilink Protocol (MP)
 - RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
 - RFC 2091 Trigger RIP
 - RFC 2131 DHCP
 - RFC 2132 DHCP Options and BOOTP Vendor Extensions
 - RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
 - RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
 - RFC 2280 Routing Policy Specification Language (RPSL)
 - RFC 2284 EAP over LAN
 - RFC 2338 VRRP
 - RFC 2364 PPP Over AAL5
 - RFC 2374 An Aggregatable Global Unicast
 - RFC 1286 Bridge MIB
 - RFC 1493 Bridge MIB
 - RFC 1573 SNMP MIB II
 - RFC 1724 RIPv2 MIB
 - RFC 1757 Remote Network Monitoring MIB
 - RFC 1850 OSPFv2 MIB
 - RFC 2011 SNMPv2 MIB for IP
 - RFC 2012 SNMPv2 MIB for TCP
 - RFC 2013 SNMPv2 MIB for UDP
 - RFC 2233 Interfaces MIB
 - RFC 2454 IPV6-UDP-MIB
 - RFC 2465 IPv6 MIB
 - RFC 2466 ICMPv6 MIB
 - RFC 2618 RADIUS Client MIB
 - RFC 2620 RADIUS Accounting MIB
 - RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
 - RFC 2737 Entity MIB (Version 2)
 - RFC 2863 The Interfaces Group MIB
 - RFC 2933 IGMP MIB
 - RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
 - RFC 1155 Structure of Management Information
 - RFC 1157 SNMPv1
 - RFC 1905 SNMPv2 Protocol Operations
 - RFC 2272 SNMPv3 Management Protocol
 - RFC 2273 SNMPv3 Applications
 - RFC 2274 USM for SNMPv3
 - RFC 2275 VACM for SNMPv3
 - RFC 2575 SNMPv3 View-based Access Control Model (VACM)
 - RFC 3164 BSD syslog Protocol
- OSPF**
- RFC 1245 OSPF protocol analysis
 - RFC 1246 Experience with OSPF
 - RFC 1587 OSPF NSSA
 - RFC 1765 OSPF Database Overflow
 - RFC 1850 OSPFv2 Management Information Base (MIB), traps
 - RFC 2328 OSPFv2
 - RFC 2370 OSPF Opaque LSA Option
 - RFC 3101 OSPF NSSA
- QoS/CoS**
- IEEE 802.1P (CoS)
 - RFC 2474 DS Field in the IPv4 and IPv6 Headers
 - RFC 2475 DiffServ Architecture
 - RFC 2597 DiffServ Assured Forwarding (AF)
 - RFC 2598 DiffServ Expedited Forwarding (EF)
 - RFC 3168 The Addition of Explicit Congestion



Technical Specifications

Address Format
RFC 2451 The ESP CBC-Mode Cipher Algorithms
RFC 2453 IPv2
RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
RFC 2511 Internet X.509 Certificate Request Message Format
RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
RFC 2644 Directed Broadcast Control
RFC 2661 L2TP
RFC 2663 NAT Terminology and Considerations
RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5
RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)
RFC 2702 Requirements for Traffic Engineering Over MPLS
RFC 2747 RSVP Cryptographic Authentication
RFC 2763 Dynamic Name-to-System ID mapping support
RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)
RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)
RFC 2784 Generic Routing Encapsulation (GRE)
RFC 2787 Definitions of Managed Objects for VRRP
RFC 2961 RSVP Refresh Overhead Reduction Extensions
RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS
RFC 2973 IS-IS Mesh Groups
RFC 2993 Architectural Implications of NAT
RFC 3022 Traditional IP Network Address Translator (Traditional NAT)
RFC 3027 Protocol Complications with the IP Network Address Translator
RFC 3031 Multiprotocol Label Switching Architecture
RFC 3032 MPLS Label Stack Encoding

Notification (ECN) to IP

Security

IEEE 802.1X Port Based Network Access Control
RFC 1321 The MD5 Message-Digest Algorithm
RFC 2082 RIP-2 MD5 Authentication
RFC 2104 Keyed-Hashing for Message Authentication
RFC 2138 RADIUS Authentication
RFC 2209 RSVP-Message Processing
RFC 2246 Transport Layer Security (TLS)
RFC 2716 PPP EAP TLS Authentication Protocol
RFC 2865 RADIUS Authentication
RFC 2866 RADIUS Accounting
RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication

VPN

RFC 2403 - HMAC-MD5-96
RFC 2404 - HMAC-SHA1-96
RFC 2405 - DES-CBC Cipher algorithm
RFC 2547 BGP/MPLS VPNs
RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
RFC 2842 Capabilities Advertisement with BGP-4
RFC 2858 Multiprotocol Extensions for BGP-4
RFC 2918 Route Refresh Capability for BGP-4
RFC 3107 Carrying Label Information in BGP-4

IPsec

RFC 1828 IP Authentication using Keyed MD5
RFC 2401 IP Security Architecture
RFC 2402 IP Authentication Header
RFC 2406 IP Encapsulating Security Payload
RFC 2407 - Domain of interpretation
RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
RFC 2411 IP Security Document Roadmap
RFC 2412 - OAKLEY
RFC 2865 - Remote Authentication Dial In User Service (RADIUS)

HP A-MSR20-15 Router (JF817A)

Ports

1 SIC slot
1 RJ-45 ADSL2+ port
1 RJ-45 autosensing 10/100 WAN port (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full
4 RJ-45 autosensing 10/100 LAN ports (IEEE 802.3 Type 10BASE-T, IEEE 802.3u Type 100BASE-TX); Duplex: half or full



Technical Specifications

Physical characteristics	Dimensions	9.45(d) x 11.81(w) x 1.74(h) in. (24 x 30 x 4.42 cm)
	Weight	6.61 lb. (3.0 kg)
Memory and processor	Processor	RISC @ 333 MHz, 256 MB DDR SDRAM, 32 MB flash
Mounting	Desktop or can be mounted in a standard 19-in. rack when used with the optional rack-mount kit.	
Performance	Throughput	up to 160 Kpps (64-byte packets)
	Routing table size	10000 entries
	Operating temperature	32°F to 104°F (0°C to 40°C)
Environment	Operating relative humidity	5% to 90%, noncondensing
	Nonoperating/Storage temperature	-40°F to 158°F (-40°C to 70°C)
	Nonoperating/Storage relative humidity	5% to 90%, noncondensing
Electrical characteristics	Maximum heat dissipation	85 BTU/hr (89.68 kJ/hr)
	Voltage	100-120/200-240 VAC
	Maximum power rating	25 W
	Frequency	50/60 Hz
	Notes	Maximum power rating and maximum heat dissipation are the worst-case theoretical maximum numbers provided for planning the infrastructure with fully loaded PoE (if equipped), 100% traffic, all ports plugged in, and all modules populated.
Safety	UL 60950-1; AS/NZS 60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; IEC 60950-1; CAN/CSA-C22.2 No. 60950-1-03; EN 60950-1/A11; FDA 21 CFR Subchapter J	
Emissions	EN 55022 Class B; ICES-003 Class B; ANSI C63.4 2003; ETSI EN 300 386 V1.3.3; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-3-2:2006; EN 61000-3-3:1995 +A1:2001+A2:2005; EMC Directive 2004/108/EC; EN 55024:1998+ A1:2001 + A2:2003; EN 61000-4-11:2004; EN 61000-4-8:2001; AS/NZS CISPR22 Class B; FCC (CFR 47, Part 15) Class B	
Telecom	FCC part 68	
Management	IMC - Intelligent Management Center; command-line interface; Web browser; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); SNMP Manager; Telnet; RMON1; FTP; IEEE 802.3 Ethernet MIB	
Notes	1. Height does not include antennas on wireless models; weight is with no optional modules installed. 2. JF817A is just for Brazil market, if other region have similar requirement, please choose from JF236A/JF809A/JF237A/JF238A.	
Services	3-year, parts only, global next-day advance exchange (UW075E) 3-year, 4-hour onsite, 13x5 coverage for hardware (UW076E) 3-year, 4-hour onsite, 24x7 coverage for hardware (UW006E) 3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (UW009E) 3-year, 24x7 SW phone support, software updates (UW012E) 4-year, 4-hour onsite, 13x5 coverage for hardware (UW077E) 4-year, 4-hour onsite, 24x7 coverage for hardware (UW007E) 4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW010E) 4-year, 24x7 SW phone support, software updates (UW013E) 5-year, 4-hour onsite, 13x5 coverage for hardware (UW078E)	



Technical Specifications

- 5-year, 4-hour onsite, 24x7 coverage for hardware (UW008E)
- 5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UW011E)
- 5-year, 24x7 SW phone support, software updates (UW014E)
- 3 Yr 6 hr Call-to-Repair Onsite (UW079E)
- 4 Yr 6 hr Call-to-Repair Onsite (UW080E)
- 5 Yr 6 hr Call-to-Repair Onsite (UW081E)

Refer to the HP website at: www.hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.

Standards and protocols (applies to all products in series)

BGP

- RFC 1163 Border Gateway Protocol (BGP)
- RFC 1267 Border Gateway Protocol 3 (BGP-3)
- RFC 1657 Definitions of Managed Objects for BGPv4
- RFC 1771 BGPv4
- RFC 1772 Application of the BGP
- RFC 1773 Experience with the BGP-4 Protocol
- RFC 1774 BGP-4 Protocol Analysis
- RFC 1965 BGP4 confederations
- RFC 1997 BGP Communities Attribute
- RFC 1998 PPP Gandalf FZA Compression Protocol
- RFC 2385 BGP Session Protection via TCP MD5
- RFC 2439 BGP Route Flap Damping

Device management

- RFC 1305 NTPv3
- RFC 1945 Hypertext Transfer Protocol -- HTTP/1.0
- RFC 2271 FrameWork
- RFC 2452 MIB for TCP6
- RFC 2454 MIB for UDP6

General protocols

- IEEE 802.1D MAC Bridges
- IEEE 802.1p Priority
- IEEE 802.1Q VLANs
- IEEE 802.1s Multiple Spanning Trees
- IEEE 802.1w Rapid Reconfiguration of Spanning Tree
- RFC 768 UDP
- RFC 783 TFTP Protocol (revision 2)
- RFC 791 IP
- RFC 792 ICMP
- RFC 793 TCP
- RFC 826 ARP
- RFC 854 TELNET
- RFC 855 Telnet Option Specification
- RFC 856 TELNET
- RFC 858 Telnet Suppress Go Ahead Option
- RFC 894 IP over Ethernet
- RFC 925 Multi-LAN Address Resolution

RFC 3036 LDP Specification

- RFC 3046 DHCP Relay Agent Information Option
- RFC 3063 MPLS Loop Prevention Mechanism
- RFC 3065 Support AS confederation
- RFC 3137 OSPF Stub Router Advertisement
- RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels
- RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels
- RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP)
- RFC 3214 LSP Modification Using CR-LDP
- RFC 3215 LDP State Machine
- RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)
- RFC 3277 IS-IS Transient Blackhole Avoidance
- RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
- RFC 3392 Support BGP capabilities advertisement
- RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
- RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
- RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
- RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
- RFC 3784 ISIS TE support
- RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
- RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
- RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)



Technical Specifications

RFC 950 Internet Standard Subnetting Procedure	RFC 3847 Restart signaling for IS-IS
RFC 959 File Transfer Protocol (FTP)	
RFC 1006 ISO transport services on top of the TCP: Version 3	IP multicast
RFC 1027 Proxy ARP	RFC 1112 IGMP
RFC 1034 Domain Concepts and Facilities	RFC 2236 IGMPv2
RFC 1035 Domain Implementation and Specification	RFC 2283 Multiprotocol Extensions for BGP-4
RFC 1042 IP Datagrams	RFC 2362 PIM Sparse Mode
RFC 1058 RIPv1	RFC 2365 Administratively Scoped IP Multicast
RFC 1071 Computing the Internet Checksum	RFC 2710 Multicast Listener Discovery (MLD) for IPv6
RFC 1091 Telnet Terminal-Type Option	RFC 2934 Protocol Independent Multicast MIB for IPv4
RFC 1122 Host Requirements	RFC 3376 IGMPv3
RFC 1141 Incremental updating of the Internet checksum	
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	IPv6
RFC 1144 Compressing TCP/IP headers for low-speed serial links	RFC 1981 IPv6 Path MTU Discovery
RFC 1195 OSI ISIS for IP and Dual Environments	RFC 2080 RIPng for IPv6
RFC 1256 ICMP Router Discovery Protocol (IRDP)	RFC 2292 Advanced Sockets API for IPv6
RFC 1293 Inverse Address Resolution Protocol	RFC 2373 IPv6 Addressing Architecture
RFC 1315 Management Information Base for Frame Relay DTEs	RFC 2460 IPv6 Specification
RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)	RFC 2463 ICMPv6
RFC 1333 PPP Link Quality Monitoring	RFC 2464 Transmission of IPv6 over Ethernet Networks
RFC 1334 PPP Authentication Protocols (PAP)	RFC 2472 IP Version 6 over PPP
RFC 1349 Type of Service	RFC 2473 Generic Packet Tunneling in IPv6
RFC 1350 TFTP Protocol (revision 2)	RFC 2475 IPv6 DiffServ Architecture
RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)	RFC 2529 Transmission of IPv6 Packets over IPv4
RFC 1381 SNMP MIB Extension for X.25 LAPB	RFC 2545 Use of MP-BGP-4 for IPv6
RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol	RFC 2553 Basic Socket Interface Extensions for IPv6
RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol	RFC 2740 OSPFv3 for IPv6
RFC 1490 Multiprotocol Interconnect over Frame Relay	RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers
RFC 1519 CIDR	RFC 3056 Connection of IPv6 Domains via IPv4 Clouds
RFC 1534 DHCP/BOOTP Interoperation	RFC 3513 IPv6 Addressing Architecture
RFC 1542 Clarifications and Extensions for the Bootstrap Protocol	RFC 3596 DNS Extension for IPv6
RFC 1552 The PPP Internetworking Packet Exchange Control Protocol (IPXCP)	
RFC 1577 Classical IP and ARP over ATM	MIBs
RFC 1613 Cisco Systems X.25 over TCP (XOT)	RFC 1213 MIB II
RFC 1624 Incremental Internet Checksum	RFC 1229 Interface MIB Extensions
RFC 1631 NAT	RFC 1286 Bridge MIB
	RFC 1493 Bridge MIB
	RFC 1573 SNMP MIB II
	RFC 1724 RIPv2 MIB
	RFC 1757 Remote Network Monitoring MIB
	RFC 1850 OSPFv2 MIB
	RFC 2011 SNMPv2 MIB for IP
	RFC 2012 SNMPv2 MIB for TCP
	RFC 2013 SNMPv2 MIB for UDP
	RFC 2233 Interfaces MIB
	RFC 2454 IPV6-UDP-MIB



Technical Specifications

- RFC 1638 PPP Bridging Control Protocol (BCP)
 - RFC 1661 The Point-to-Point Protocol (PPP)
 - RFC 1662 PPP in HDLC-like Framing
 - RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIv2
 - RFC 1701 Generic Routing Encapsulation
 - RFC 1702 Generic Routing Encapsulation over IPv4 networks
 - RFC 1721 RIP-2 Analysis
 - RFC 1722 RIP-2 Applicability
 - RFC 1723 RIP v2
 - RFC 1795 Data Link Switching: Switch-to-Switch Protocol AIW DLSw RIG: DLSw Closed Pages, DLSw Standard Version 1
 - RFC 1812 IPv4 Routing
 - RFC 1829 The ESP DES-CBC Transform
 - RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses
 - RFC 1944 Benchmarking Methodology for Network Interconnect Devices
 - RFC 1973 PPP in Frame Relay
 - RFC 1974 PPP Stac LZS Compression Protocol
 - RFC 1990 The PPP Multilink Protocol (MP)
 - RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP)
 - RFC 2091 Trigger RIP
 - RFC 2131 DHCP
 - RFC 2132 DHCP Options and BOOTP Vendor Extensions
 - RFC 2166 APPN Implementer's Workshop Closed Pages Document DLSw v2.0 Enhancements
 - RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification
 - RFC 2280 Routing Policy Specification Language (RPSL)
 - RFC 2284 EAP over LAN
 - RFC 2338 VRRP
 - RFC 2364 PPP Over AAL5
 - RFC 2374 An Aggregatable Global Unicast Address Format
 - RFC 2451 The ESP CBC-Mode Cipher Algorithms
 - RFC 2453 RIPv2
 - RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols
 - RFC 2511 Internet X.509 Certificate Request Message Format
 - RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)
 - RFC 2644 Directed Broadcast Control
 - RFC 2661 L2TP
 - RFC 2465 IPv6 MIB
 - RFC 2466 ICMPv6 MIB
 - RFC 2618 RADIUS Client MIB
 - RFC 2620 RADIUS Accounting MIB
 - RFC 2674 802.1p and IEEE 802.1Q Bridge MIB
 - RFC 2737 Entity MIB (Version 2)
 - RFC 2863 The Interfaces Group MIB
 - RFC 2933 IGMP MIB
 - RFC 3813 MPLS LSR MIB
- Network management**
- IEEE 802.1D (STP)
 - RFC 1155 Structure of Management Information
 - RFC 1157 SNMPv1
 - RFC 1905 SNMPv2 Protocol Operations
 - RFC 2272 SNMPv3 Management Protocol
 - RFC 2273 SNMPv3 Applications
 - RFC 2274 USM for SNMPv3
 - RFC 2275 VACM for SNMPv3
 - RFC 2575 SNMPv3 View-based Access Control Model (VACM)
 - RFC 3164 BSD syslog Protocol
- OSPF**
- RFC 1245 OSPF protocol analysis
 - RFC 1246 Experience with OSPF
 - RFC 1587 OSPF NSSA
 - RFC 1765 OSPF Database Overflow
 - RFC 1850 OSPFv2 Management Information Base (MIB), traps
 - RFC 2328 OSPFv2
 - RFC 2370 OSPF Opaque LSA Option
 - RFC 3101 OSPF NSSA
- QoS/CoS**
- IEEE 802.1P (CoS)
 - RFC 2474 DS Field in the IPv4 and IPv6 Headers
 - RFC 2475 DiffServ Architecture
 - RFC 2597 DiffServ Assured Forwarding (AF)
 - RFC 2598 DiffServ Expedited Forwarding (EF)
 - RFC 3168 The Addition of Explicit Congestion Notification (ECN) to IP
- Security**
- IEEE 802.1X Port Based Network Access Control
 - RFC 1321 The MD5 Message-Digest Algorithm
 - RFC 2082 RIP-2 MD5 Authentication
 - RFC 2104 Keyed-Hashing for Message Authentication
 - RFC 2138 RADIUS Authentication
 - RFC 2209 RSVP-Message Processing
 - RFC 2246 Transport Layer Security (TLS)



Technical Specifications

- RFC 2663 NAT Terminology and Considerations
 - RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5
 - RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)
 - RFC 2702 Requirements for Traffic Engineering Over MPLS
 - RFC 2747 RSVP Cryptographic Authentication
 - RFC 2763 Dynamic Name-to-System ID mapping support
 - RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT)
 - RFC 2766 Network Address Translation - Protocol Translation (NAT-PT)
 - RFC 2784 Generic Routing Encapsulation (GRE)
 - RFC 2787 Definitions of Managed Objects for VRRP
 - RFC 2961 RSVP Refresh Overhead Reduction Extensions
 - RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS
 - RFC 2973 IS-IS Mesh Groups
 - RFC 2993 Architectural Implications of NAT
 - RFC 3022 Traditional IP Network Address Translator (Traditional NAT)
 - RFC 3027 Protocol Complications with the IP Network Address Translator
 - RFC 3031 Multiprotocol Label Switching Architecture
 - RFC 3032 MPLS Label Stack Encoding
 - RFC 2716 PPP EAP TLS Authentication Protocol
 - RFC 2865 RADIUS Authentication
 - RFC 2866 RADIUS Accounting
 - RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication
- VPN**
- RFC 2403 - HMAC-MD5-96
 - RFC 2404 - HMAC-SHA1-96
 - RFC 2405 - DES-CBC Cipher algorithm
 - RFC 2547 BGP/MPLS VPNs
 - RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP
 - RFC 2842 Capabilities Advertisement with BGP-4
 - RFC 2858 Multiprotocol Extensions for BGP-4
 - RFC 2918 Route Refresh Capability for BGP-4
 - RFC 3107 Carrying Label Information in BGP-4
- IPsec**
- RFC 1828 IP Authentication using Keyed MD5
 - RFC 2401 IP Security Architecture
 - RFC 2402 IP Authentication Header
 - RFC 2406 IP Encapsulating Security Payload
 - RFC 2407 - Domain of interpretation
 - RFC 2410 - The NULL Encryption Algorithm and its use with IPsec
 - RFC 2411 IP Security Document Roadmap
 - RFC 2412 - OAKLEY
 - RFC 2865 - Remote Authentication Dial In User Service (RADIUS)



Accessories

HP A-MSR20-1x Series accessories

Transceivers

HP X110 100M SFP LC FX Transceiver	JD102B
HP X110 100M SFP LC LX Transceiver	JD120B
HP X110 100M SFP LC LH40 Transceiver	JD090A
HP X110 100M SFP LC LH80 Transceiver	JD091A
HP X120 1G SFP LC SX Transceiver	JD118B
HP X120 1G SFP LC LX Transceiver	JD119B
HP X124 1G SFP LC LH40 1310nm Transceiver	JD061A
HP X120 1G SFP LC LH40 1550nm Transceiver	JD062A
HP X125 1G SFP LC LH70 Transceiver	JD063B

Cables

HP X200 V.24 DTE 3m Serial Port Cable	JD519A
HP X200 V.24 DCE 3m Serial Port Cable	JD521A
HP X200 V.35 DTE 3m Serial Port Cable	JD523A
HP X200 V.35 DCE 3m Serial Port Cable	JD525A
HP X200 X.21 DTE 3m Serial Port Cable	JD527A
HP X200 X.21 DCE 3m Serial Port Cable	JD529A
HP X260 RS449 3m DTE Serial Port Cable	JF825A
HP X260 RS449 3m DCE Serial Port Cable	JF826A
HP X260 RS530 3m DTE Serial Port Cable	JF827A
HP X260 RS530 3m DCE Serial Port Cable	JF828A
HP X260 Auxiliary Router Cable	JD508A
HP X260 E1 RJ45 3m Router Cable	JD509A
HP X260 E1 BNC 75 ohm 40m Router Cable	JD516A
HP X260 E1 BNC 75 ohm 3m Router Cable	JD175A
HP X260 E1 BNC 20m Router Cable	JD514A
HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable	JD511A
HP X260 2E1 BNC 3m Router Cable	JD643A
HP X260 T1 Voice Router Cable	JD535A
HP X260 T1 Router Cable	JD518A
HP X260 SIC-8AS RJ45 0.28m Router Cable	JD642A
HP X260 E1 RJ45 20m Router Cable	JD517A
HP X260 T1VI DB15M RJ45 3m Router Cable	JF843A

Router Modules

HP A-MSR 9-port 10/100Base-T Switch DSIC Module	JD574B
HP A-MSR 4-port 10/100Base-T Switch SIC Module	JD573B
HP A-MSR 1-port GbE Combo SIC Module	JD572A
HP A-MSR 1-port 10/100Base-T SIC Module	JD545B
HP A-MSR 1-port 100Base-X SIC Module	JF280A
HP A-MSR 2-port FXO SIC Module	JD558A



Accessories

HP A-MSR 1-port FXO SIC Module	JD559A
P A-MSR 2-port FXS SIC Module	JD560A
HP A-MSR 1-port FXS SIC Module	JD561A
HP A-MSR 2-port FXS/1-port FXO SIC Module	JD632A
HP A-MSR 2-port ISDN-S/T Voice SIC Module	JF821A
HP 1-port Analog Modem SIC A-MSR Module	JD536A
HP A-MSR 1-port ADSL over POTS SIC Module	JD537A
HP A-MSR 1-port T1/Fractional T1 SIC Module	JD538A
HP A-MSR 1-port Enhanced Sync/Async Serial SIC Module	JD557A
HP A-MSR 1-port ISDN-U SIC Module	JD570A
HP A-MSR 1-port ISDN-S/T SIC Module	JD571A
HP A-MSR 1-port E1/Fractional E1 SIC Module	JD634B
HP A-MSR 8-port Async Serial SIC Module	JF281A
HP A-MSR 802.11b/g/n Wireless Access Point SIC Module	JF819A
HP 3G Wireless GSM/WCDMA WAN SIC Module	JF820A
HP A-MSR 2-port E1/Fractional E1 SIC Module	JF842A
HP A-MSR20-12 Router (JF241A)	
HP A-MSR 1-port E1 Voice SIC Module	JD575A
HP A-MSR 1-port T1 Voice SIC Module	JD576A
HP A-MSR 32-Channel Voice Processing Module	JD598A
HP A-MSR 24-Channel Voice Processing Module	JD599A
HP A-MSR 16-Channel Voice Processing Module	JD600A
HP A-MSR 8-Channel Voice Processing Module	JD601A
HP A-MSR Voice Co-processing Module	JD610A
HP A-MSR20-12-W Router (JF807A)	
HP A-MSR 1-port E1 Voice SIC Module	JD575A
HP A-MSR 1-port T1 Voice SIC Module	JD576A
HP A-MSR 32-Channel Voice Processing Module	JD598A
HP A-MSR 24-Channel Voice Processing Module	JD599A
HP A-MSR 16-Channel Voice Processing Module	JD600A
HP A-MSR 8-Channel Voice Processing Module	JD601A
HP A-MSR Voice Co-processing Module	JD610A
HP A-MSR20-12-T Router (JF806A)	
HP A-MSR 1-port E1 Voice SIC Module	JD575A
HP A-MSR 1-port T1 Voice SIC Module	JD576A
HP A-MSR 32-Channel Voice Processing Module	JD598A
HP A-MSR 24-Channel Voice Processing Module	JD599A
HP A-MSR 16-Channel Voice Processing Module	JD600A
HP A-MSR 8-Channel Voice Processing Module	JD601A
HP A-MSR Voice Co-processing Module	JD610A
HP A-MSR20-15-A Router (JF237A)	



Accessories

HP A-MSR 1-port E1 Voice SIC Module	JD575A
HP A-MSR 1-port T1 Voice SIC Module	JD576A
HP A-MSR 32-Channel Voice Processing Module	JD598A
HP A-MSR 24-Channel Voice Processing Module	JD599A
HP A-MSR 16-Channel Voice Processing Module	JD600A
HP A-MSR 8-Channel Voice Processing Module	JD601A
HP A-MSR Voice Co-processing Module	JD610A
HP A-MSR20-15-A-W Router (JF809A)	
HP A-MSR 1-port E1 Voice SIC Module	JD575A
HP A-MSR 1-port T1 Voice SIC Module	JD576A
HP A-MSR 32-Channel Voice Processing Module	JD598A
HP A-MSR 24-Channel Voice Processing Module	JD599A
HP A-MSR 16-Channel Voice Processing Module	JD600A
HP A-MSR 8-Channel Voice Processing Module	JD601A
HP A-MSR Voice Co-processing Module	JD610A
HP A-MSR20-15-I Router (JF236A)	
HP A-MSR 1-port E1 Voice SIC Module	JD575A
HP A-MSR 1-port T1 Voice SIC Module	JD576A
HP A-MSR 32-Channel Voice Processing Module	JD598A
HP A-MSR 24-Channel Voice Processing Module	JD599A
HP A-MSR 16-Channel Voice Processing Module	JD600A
HP A-MSR 8-Channel Voice Processing Module	JD601A
HP A-MSR Voice Co-processing Module	JD610A
HP A-MSR20-15-I-W Router (JF238A)	
HP A-MSR 1-port E1 Voice SIC Module	JD575A
HP A-MSR 1-port T1 Voice SIC Module	JD576A
HP A-MSR 32-Channel Voice Processing Module	JD598A
HP A-MSR 24-Channel Voice Processing Module	JD599A
HP A-MSR 16-Channel Voice Processing Module	JD600A
HP A-MSR 8-Channel Voice Processing Module	JD601A
HP A-MSR Voice Co-processing Module	JD610A
HP A-MSR20-15 Router (JF817A)	
HP A-MSR 1-port E1 Voice SIC Module	JD575A
HP A-MSR 1-port T1 Voice SIC Module	JD576A
HP A-MSR 32-Channel Voice Processing Module	JD598A
HP A-MSR 24-Channel Voice Processing Module	JD599A
HP A-MSR 16-Channel Voice Processing Module	JD600A
HP A-MSR 8-Channel Voice Processing Module	JD601A
HP A-MSR Voice Co-processing Module	JD610A



Accessories

To learn more, visit: www.hp.com/networking

© Copyright 2010-2011 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

