

Multimedia Projector EB-95 / EB-96W / EB-905 / EB-915W / EB-925

SPECIFICATIONS		EB-95	EB-96W	EB-905	EB-915W	EB-925
Projection System		RGB Liquid-Crystal Shutter Projection System				
Specification of LCD	Size	0.55 inch with MLA (D8)	0.59 inch with MLA (D8)	0.63 inch with MLA (D7)	0.59 inch with MLA (D8)	0.63 inch with MLA (D7)
Main Parts	Driving Method	Polysilicon TFT Active Matrix				
	Pixel Number	786432 dots (1024 x 768) x 3	1024000 dots (1280 x 800) x 3	786432 dots (1024 x 768) x 3	1024000 dots (1280 x 800) x 3	786432 dots (1024 x 768) x 3
	Native Resolution	XGA	WXGA	XGA	WXGA	XGA
Projection Lens		Manual Focus & 1.2 x Optical Zoom F=1.58 - 1.72 / F=16.9 - 20.28 mm		Manual Focus & 1.6 x Optical Zoom F=1.51 - 1.99 / F=18.1 - 29.2 mm		
Lamp	Type	E-TORL 200W UHE			E-TORL 230W UHE	
	Life	5000 hours (High Brightness mode) / 6000 hours (ECO mode)			4000 hours (High Brightness mode) / 6000 hours (ECO mode)	
Screen Size		33 to 300 inch		30 to 300 inch		30 to 300 inch
Offset		8:1		10:1	8.6:1	8.6:1
Light Output* (Compliance with ISO21118)		2600 lm / 2080 lm		2700 lm / 2160 lm	3000 lm / 2400 lm	3200 lm / 2240 lm
Color Light Output*		2600 lm		2700 lm	3000 lm	3200 lm
Contrast*		2000:1				
Color Reproduction		Full-Color (16.77 million colors)				
Sound Output		16W Monaural				
Effective Scanning	Pixel Clock	13.5 MHz to 162 MHz, up to UXGA 60Hz				
Frequency Range (Analog)	Horizontal	15 KHz to 92 KHz				
	Vertical	50 Hz to 85 Hz				
Auto Keystone Correction		Vertical: -30 to +30 degrees				
Analog RGB I/O	Display Performance	Native	1024 x 768 dots	1280 x 800 dots	1024 x 768 dots	1280 x 800 dots
	Input Terminal	Video	D-sub 15-pin x 2			
		Audio	Stereo mini-jack x 2			
	Output Terminal	Video	D-sub 15-pin x 1			
Audio		Stereo mini-jack x 1				
Video I/O	Input Signal	Video Standard	NTSC / NTSC4.43 / PAL / M-PAL / N-PAL / PAL60 / SECAM			
	Input Terminal	Video	Composite Video: RCA (Yellow) x 1, S-Video: Mini DIN x 1 Component Video: D-sub 15-pin (Blue molding) x 2, RGB-Video: D-sub 15-pin x 2			
		Audio	RCA x 1 (White / Red)			
HDMI	Input Signal	Video Standard	480i / 576i / 480p / 576p / 720p / 1080i / 1080p			
		Video Signal	TMDS (TMDS is signal for HDMI.)			
		Audio Signal	Linear PCM			
Input Terminal	HDMI x 1					
Mic Input	Input Terminal	Audio Stereo mini-jack x 1				
Control I/O	USB I/O	USB Type B x1 (for USB Display, mouse, K/B, control)				
	Serial I/O	RS232C (D-sub 9-pin x 1)				
Memory I/O	USB I/O	Type A x 1 (for USB Memory & ELPDC06)				
Network for	Wired LAN	RJ45 x1 100Mbps				
Projection	Wireless	Terminal	USB Type A x 1			
		Support Speeds for each mode	IEEE 802.11b: 11 Mbps** IEEE 802.11g: 54 Mbps** IEEE 802.11n: 130 Mbps**			
Operating Temperature		5°C to 35°C < 41°F to 95°F > (20% - 80% humidity, unfrozen)				
Operating Altitude		0 m to 2286 m < 0 ft to 7500 ft > (over 1,500m / 4,921 ft; with High altitude mode)				
Start-up Period		About 7 seconds (warm-up period: 30 seconds)				
Direct Power On		Yes				
Cool-down Period		Instant off				
Power Supply Voltage		100 - 240V AC +/- 10%, 50 / 60 Hz				
Power Consumption	Lamp On / Standby	100 - 120V	312W / 0.31W	313W / 0.29W	355W / 0.29W	
		220 - 240V	299W / 0.4W	300W / 0.39W	337W / 0.39W	
Dimensions (D x W x H)		263 x 345 x 93 mm				
Weight		Approx. 3.2kg		Approx. 3.4kg		
Fan Noise Brightness Control - High / Low		33 dB / 28 dB		37 dB / 29 dB		


* Light Output / Color Light Output / Contrast --- Color mode: Dynamic, Zoom: Wide # Windows & Mac
**Maximum speed and range is achievable when used with same enhanced mode technology. Actual data rates, features and performance may vary depending on your computer system, and environment.

SUPPLIED ACCESSORIES	
Power Cable	1.8 m
Remote Control	Yes
Computer Cable	1.8 m
Password Protect Sticker	
User's Manual	
Epson Projector Software (CD-Rom)	

WARRANTY SERVICE	
2 Years Onsite Warranty Service to be provided for local purchase only.	
EPSON COVERPLUS Extended Warranty	
# The warranty service can be extended by purchasing Epson Coverplus Extended Warranty. For more information, please contact Epson customer support.	

OPTIONAL ACCESSORIES	
ELPLP60	Spare Lamp (EB-95 / 96W / 905)
ELPLP61	Spare Lamp (EB-915W / 925)
ELPAF29	Air Filter Set
ELPAP07	Wireless LAN Unit
ELPAP08	Quick Wireless Connection USB Key

Bold, Bright, Beautiful... 3LCD Technology
3LCD technology achieves bright, natural images and smooth, sharp video playback. No color break-up makes images gentle on the eyes.



Optical unit with high light-use efficiency

CONNECTOR PANEL			
1	HDMI	9	Audio-L Input Port
2	S-Video	10	Audio-R Input Port
3	Computer 1 Input Port	11	Audio 1 Input Port
4	Computer 2 Input Port	12	Audio 2 Input Port
5	USB (Type B)	13	MIC Input Port
6	USB (Type A)	14	Monitor Out Port
7	LAN Port	15	Audio Out Port
8	Video	16	RS-232C Port

Multimedia Projector EB-95 EB-96W EB-905 EB-915W EB-925

EPSON
EXCEED YOUR VISION



Make the classroom a fun place to be with more effective lessons

EPSON
EXCEED YOUR VISION

Epson Hong Kong Limited
Unit 715-723, 7/F Trade Square,
681 Cheung Sha Wan Road,
Cheung Sha Wan, Kowloon, Hong Kong

Hong Kong Region:
Epson Authorized Customer Service Centre (Repair Service)
Room 1006, 10/F, Block B, Sea View Estate, 4-6 Watson Road,
North Point, Hong Kong

Kowloon Region:
Epson Authorized Customer Service Centre (Collection Point)
Room 1006-8, 10/F, Park-In Commercial Centre, 56 Dundas Street,
Mong Kok, Kowloon


Enquiry hotline : (852) 2827 8711
Technical hotline : (852) 2827 8911

URL: www.epson.com.hk

FEB11-119-PROJECTOR


1 Easy and flexible usability

Horizontal Keystone




These projectors provide vertical (automatic/manual) and horizontal (manual) keystone correction. Thanks to these functions, it is not necessary to put the projector in the center of the desk. You can place the projector anywhere you want.

Bigger Control Panel




The larger control panel & clear lettering allow for easier projector operation. This new Epson control panel was designed for educational products.

Template Function



When projecting to a whiteboard, blackboard, etc, this function projects lines to make writing on the board easier. Various types of line patterns can be selected.

1.6x Zoom Lens (EB-905/915W/925)




The wider range of set up provides a high likelihood of corresponding with the position of the previously used projector.

2 Enhanced audio

16W Built-in Speaker

The powerful 16W built-in speaker replaces the need for an external speaker. The high quality output can be heard clearly even in a large room.



Microphone Input

The inclusion of a microphone input terminal makes it possible to use a microphone in conjunction with the 16W speaker.

3 Advanced operation with wider connectivity

Wide-ranging Connectivity

Its wide-ranging compatibility with devices like HDMI, LAN cables, microphones, and, of course, PCs, makes it well suited to any classroom setting. Easy integration and advanced connectivity features allow you to evolve your classroom as you incorporate additional technology.




Direct Connection with ELPDC06



These projectors can be connected directly to ELPDC06 (Epson Document Camera) via USB cable. ELPDC06 helps facilitate effective presentations and lessons.


3 Advanced operation with wider connectivity

USB Display 3 in 1



Projection set-up is no longer a troublesome process. Images can be projected by simply connecting the PC and projector via USB cable. Sound data can also be sent. A built-in speaker allows you to enjoy powerful sound without having to prepare a separate speaker.


Wireless Connection



Free from complicated and dangerous cables! A wireless LAN connection is possible via an access point. You can also make a direct connection between the projector and a PC.

Wireless / Wired Projection with Audio

In the case of wireless connections, sound can also be transmitted wirelessly to the projector so that it isn't necessary to connect an audio cable.




Multi Screen Display



You can share more information with large audiences using the Multi Screen Display function.

Monitoring & Control Function



With Epson Network monitoring and control software (Easy MP monitor), a single PC allows you to see which projectors are available and if they are running efficiently, even across the largest of networks. This series can be configured remotely, and you can receive instant email alerts for pre-defined critical indicators such as non-functioning devices or overheating lamps. You can also access a projector's serial number remotely via LAN/serial connection.


4 Low TCO

6000H - Long Lamp Life & EasyLamp Replacement



Longer lamp life enables customers to extend maintenance cycles to up to 6000H.

High Efficiency Filter



The new electrostatic filter enables customers to extend maintenance cycles to up to 5000H, leading to dramatic savings in time and maintenance costs. The surface area of the filter is more than double that of current models.