



Immerse yourself in HD projection



HD Ready



View HD from Blu-ray, games consoles, TV boxes and computers



Brilliant high brightness images – 2500 ANSI Lumens



Crystal clarity - 2500:1 Contrast ratio



HDMI input for pure digital images



VGA input for convenient computer connectivity



Environmentally friendly - less than 1W standby mode












HD experience in your home


The DW318 produces an exceptionally bright 2500 Lumens image enabling quality viewing even in high ambient light conditions. Use it like a TV and leave the lights on! Immerse yourself in life size HD characters for an extreme gaming experience or project all the atmosphere of a live sporting event into your home.





WXGA\HD READY RESOLUTION

The widescreen DW318 is the perfect companion for Blu-ray and DVD players, TV boxes, games consoles or widescreen computers and laptops.



TRUE HDMI

Project crystal clear images using the latest HDMI v1.3 input. Hassle-free projection from a widescreen computer/HD source with a single HDMI cable – no need for separate audio cables.

CLEAR, FOCUSED IMAGES

Technology from Texas Instruments produces a stunning 2500:1 contrast ratio for pin sharp graphics and crystal clear text. Crisper whites, ultra-rich blacks makes images come alive and text easier to read - ideal for business and education presentations.





1000:1 contrast ratio

2500:1 contrast ratio

‡Simulated Image

CONTROL

The extensive RS232 command set makes it simple and easy to control the DW318 with any control system.



AMX Compatibility – Dynamic Discovery Protocol is incorporated into the DW318. This feature allows for easy installation with AMX control systems.

AMAZING COLOURS

The DW318 incorporates BrilliantColor™ technology to produce stunningly bright images with perfectly balanced life-like colours.

Preset display modes allow you to achieve a perfect image on a variety of surfaces including screens and interactive whiteboards.

COLOUR GUARANTEE

We are so confident that the DW318 image colour quality will remain as good as the day you bought it that Optoma will guarantee it for five years.





Enjoy big bright images

VIRTUALLY MAINTENANCE FREE = LOWER TOTAL COST OF OWNERSHIP (TCO)

DW318 provides lower cost of ownership, longer life and improved reliability. The filter-free projector design does not require regular filter cleaning or filter replacement, saving you time and money.



ENVIRONMENTALLY FRIENDLY

The DW318 incorporates energy saving features to conserve power and extend the lamp life:



To achieve the maximum 4000hrs** lamp life time the projector should be operating in STD mode and the shut down timer should be enabled to automatically switch off the projector if it is accidentally left on when no longer required. Enabling the <1W Standby mode will ensure the minimum energy consumption when the projector is not being used.



It takes less than 10 seconds for the projector to power up and shutdown, saving both time and energy.



DW318 SPECIFICATIONS

Native Resolution	WXGA 1280 x 800				
Compressed Resolution	up to UXGA (1600 x 1200)				
Brightness	2500/2100 Lumens (BRIGHT/STD mode)				
Contrast	2500:1				
Noise Level	28dB				
Lamp Life**	4000/3000 (STD/BRIGHT mode)				
Projection Lens	F/2.5 ~ 2.67, f=21.86 ~ 24.0mm, 1.1x Manual Zoom				
Throw Ratio	1.55 - 1.7:1 (Projection Distance:Image Width)				
Projection Distance	1.2 - 12m				
Image Size	0.83 - 9.13m (32.77" - 359.44") Diagonal 16:10				
Display Technology	Single 0.65" WXGA DMD chip DLP® Technology				
Diopidy Teermology	by Texas Instruments				
Weight / Dimensions (W x D x H)	2.3 kg / 286 x 192 x 84mm				
Remote Control	Full function remote with direct source selecting				
INPUTS	HDMI (HDCP) - audio supported (DVI-D via adaptor) 15 Pin D-Sub VGA (SCART & Component via adaptor)				
	S-Video 4 Pin Mini Din				
	Composite RCA				
	3.5mm Audio Mini Jack				
CONTROL	RS232 3 Pin Mini DIN				
OUTPUTS	15 Pin D-Sub VGA (monitor loop-through)				
33.1.3.3	3.5mm Audio Mini Jack				
Audio	1 x 2W Speaker				
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible				
Keystone Correction	± 40° Vertical				
On Screen Display	18 Languages: English, German, French, Italian, Spanish,				
on corcon proping	Portuguese, Polish, Dutch, Russian, Swedish, Greek,				
	Norwegian, Danish, Hungarian, Czech, Turkish, Farsi & Arabic				
Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p				
Uniformity	85%				
Displayable Colours	16.7 Million				
Horizontal Scan Rate	15.3 – 91.1kHz				
Vertical Scan Rate	24 – 120Hz				
Power Supply	100 - 240V, 50 - 60Hz				
Power Consumption	233W BRIGHT mode < 1W Standby mode				
,	207W STD mode < 1W Standby mode				
Operating Conditions	Operating: 5 - 35°C, 85% Humidity (Max),				
-parameter	3000m Altitude (Max)				
Security	One Kensington Lock Port, Password Protection				
Standard Accessories	Lens Cover, AC Power Cord, VGA Cable, Carry Bag, Full				
C	Function Remote, Batteries x 2, Quick Start Guide, CD				
	User Manual, Warranty, WEEE Card				
RoHS	Compliant				
Lamp Warranty	6 months or 1000 hours - whichever comes sooner				
Warranty	Warranty may vary by country. Please see				
	www.optomaeurope.com or ask your local				
	supplier for details				
Colour Guarantee*	5 Years				
3D Support	120Hz frame sequential 3D for resolutions up to 720p.				
	60Hz field sequential 3D for resolutions up to 480i				
3D Viewing	Requires Optoma DLP® Link™ active shutter glasses				
- 3	- sold separately				
3D Compatibility	The 3D features of the DW318 can only be used with				
- +	compatible 3D content and do not support 3D TV				
	broadcast systems, including the 3D SKY service in the				
	UK, or 3D Blu-ray. Support for these applications may				
	be added in future using additional hardware				
	20 added in fatare doing additional flataware				

EASY TO USE REMOTE CONTROL

DW318 Remote Control

- 1 Vertical Keystone Correction
- 2 Volume Control
- 3 Brightness Adjustment
- 4 AV Mute
- 5 Direct Input Source Selection

DW318 Connections

- 6 VGA 1 SCART & Component
- 7 VGA Out
- 8 HDMI (audio supported)
- 9 S-Video
- 10 Composite Video
- 11 RS232 3 Pin
- 12 Audio In
- 13 Audio Out
- 14 Security Bar
- **15** Kensington™ Lock



Exceptional Connectivity/ Multiple Terminals



Easy to use remote with buttons to change the input sources



Projection Distance (m)	Max. Horizontal Image Size (m)	Min. Horizontal Image Size (m)	Max. Vertical Image Size (m)	Min. Vertical Image Size (m)	Max Diagonal Image Size (m)	Max Diagonal Image Size (inch)	Max. Image Offset (m)
1.20	0.77	0.71	0.48	0.44	0.91	35.94	0.06
2.00	1.29	1.18	0.81	0.74	1.52	59.91	0.10
2.50	1.61	1.47	1.01	0.92	1.90	74.88	0.13
3.00	1.94	1.76	1.21	1.10	2.28	89.86	0.15
4.00	2.58	2.35	1.61	1.47	3.04	119.81	0.20
5.00	3.23	2.94	2.02	1.84	3.80	149.76	0.25
6.00	3.87	3.53	2.42	2.21	4.56	179.72	0.30
7.00	4.52	4.12	2.82	2.57	5.33	209.67	0.35
8.00	5.16	4.71	3.23	2.94	6.09	239.62	0.40
9.00	5.81	5.29	3.63	3.31	6.85	269.58	0.45
10.00	6.45	5.88	4.03	3.68	7.61	299.53	0.50
11.00	7.10	6.47	4.44	4.04	8.37	329.48	0.55
12.00	7.74	7.06	4.84	4.41	9.13	359.44	0.60

For guide purposes onl

DW318 is capable of 4:3 and 16:9 aspect ratio projection. When projecting a 4:3/16:9 image the image sizes, screen height and offset information will differ from the above.

Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ

www.optoma.co.uk

