

you can
Canon
 DIGITAL
 IXUS
 750



The Digital IXUS 750 is part of Canon's Digital IXUS range of stylish and compact digital still cameras. It replaces the Digital IXUS 700.

Canon's Digital IXUS range consists of the following products:

Digital IXUS 750, Digital IXUS 55, Digital IXUS 50, Digital IXUS 40, Digital IXUS *i* zoom

Embargo Date: 22 August 2005 – 12PM CET
Sales Start Date: 01 September 2005
Target Market: Personal/Home

Key Features in Importance Order:

- Exclusive silver all-metal perpetual curve design – **NEW!**
- 7.1 Megapixel CCD
- 3x optical zoom
- DIGIC II & iSAPS
- 2.5" LCD with wide viewing angle & improved UI – **NEW!**
- Night Display & Quick-bright
- 15 shooting modes (9 Special Scene Modes) – **NEW!**
- Long 30 fps VGA movies
- PictBridge & Print/Share button
- USB 2.0 Hi-Speed connectivity
- Software & CIG

Product Name	Mercury Code	EAN Code	Recommended Retail Price
DIGITAL IXUS 750 (Silver)	0798B005	8714574957975	778.-

What's in the box:

Digital IXUS 750 Camera, Wrist Strap WS-600, SD Memory Card SDC-32M, Battery Pack NB-3L, NB-3L Terminal Cap, Battery Charger CB-2LUE, AC Cable, AV Cable AVC-DC300, Interface Cable IFC-400PCU, User Manual Kit

Country of origin: Japan

New Accessories	Mercury Code	EAN Code
Waterproof Case WP-DC80	0778B001AA	4960999294322

Technical Specifications

IMAGE SENSOR Type Effective Pixels Colour Filter Type	1/1.8" CCD Approx. 7.1M Primary Colour
IMAGE PROCESSOR Type	DIGIC II with iSAPS technology
LENS Focal Length Zoom Maximum f/number Construction	7.7 – 23.1mm (35mm film equivalent: 37 – 111mm) Optical 3x, digital approx. 4.0x ¹ , combined approx. 12x f/2.8 - f/4.9 7 elements in 5 groups (2 aspherical elements)
FOCUSING Type AF System/Points AF Lock AF Assist Beam Closest Focusing Distance	TTL 9-point AiAF, 1-point AF (Fixed centre) On/Off Selectable YES 5cm
EXPOSURE CONTROL Metering Modes AE Lock Exposure Compensation ISO Speed Equivalent	Evaluative, Centre-weighted average, Spot (centre) On/Off Selectable +/- 2 EV in 1/3 stop increments AUTO, 50, 100, 200, 400
SHUTTER Speed	15 – 1/2,000 sec (Slow Shutter speeds of 1 sec and more, available in Long Shutter Mode only. Shutter speeds of 1.3 sec and more operate with noise reduction).
WHITE BALANCE Type Settings	TTL Auto, Daylight, Cloudy, Tungsten, Fluorescent, Fluorescent H, Custom
VIEWFINDER Viewfinder	Real-image zoom, optical viewfinder
LCD MONITOR Monitor Coverage Brightness	2.5" P-Si TFT. approx. 115,000 pixels 100% Adjustable to one of fifteen levels
FLASH Modes Slow Sync Speed Red-eye Reduction Flash Exposure Lock Built-in Flash Range External Flash	Auto, Manual Flash On/Off YES YES YES 50cm – 5.0m (W)/3.0m (T) (at ISO AUTO equivalent) Canon's High Power Flash HF-DC1
SHOOTING Modes Photo Effects Drive Modes Continuous Shooting	Auto, Manual, Digital Macro, Special Scene Mode (Portrait, Foliage, Snow, Beach, Fireworks, Underwater, Indoor, Kids & Pets, Night Snapshot), My Colors (9 settings), Stitch Assist, Movie Vivid, Neutral, Low Sharpening, Sepia, Black & White, My Colors (9 settings) Single, Continuous, Self-Timer Approx. 2.0 fps ² (until memory card becomes full) ³
RECORDING PIXELS/ COMPRESSION Image Size Compression Movies Movie Length	(L)3072 x 2304, (M1)2592 x 1944, (M2)2048 x 1536, (M3)1600 x 1200, (S) 640 x 480, Postcard Date Imprint Superfine, Fine, Normal (L)640 x 480, 30/15 fps (M)320 x 240, 60/30/15 fps (S)160 x 120, 15 fps Up to 1GB (640 x 480, 320 x 240, 30/15 fps) ³ Up to 3 min (160 x 120) ³ Up to 1 min (320 x 240, 60 fps) ³

FILE TYPES Still Image Type Movies Sound Files	JPEG compression (Exif 2.2 [Exif Print] compliant)/Design rule for Camera File system, Digital Print Order Format [DPOF] Version 1.1 compliant AVI [Motion JPEG compression + WAVE (monaural)] WAVE (monaural)
DIRECT PRINT Canon Printers PictBridge	Canon SELPHY Compact Photo Printers and PIXMA Printers supporting PictBridge (ID Photo Print, Movie Print supported on SELPHY CP printers only) YES
OTHER FEATURES My Camera Sound Memo Intelligent Orientation Sensor Histogram Playback Zoom Self Timer Menu Languages	Start-up image and camera sounds customisation Up to 60 sec per image YES YES Approx. 2x – 10x Approx. 2 or 10 sec or Custom English, German, French, Dutch, Danish, Finnish, Italian, Norwegian, Swedish, Spanish, Simplified Chinese, Chinese (traditional), Japanese, Russian, Portuguese, Korean, Greek, Polish, Czech, Hungarian, Turkish, Thai
INTERFACE Computer Other	USB 2.0 Hi-Speed (Mini-B, PTP) A/V output (PAL/NTSC)
MEMORY CARD Type	Secure Digital (SD) Card, MultiMediaCard (MMC), 32MB SD card supplied
SUPPORTED OPERATING SYSTEM PC Macintosh	Windows 98SE/Me/2000 SP4/XP/XP SP1-2 OS X v10.2 – 10.3
SOFTWARE Browsing & Printing Other Drivers Image Manipulation	ZoomBrowser EX (PhotoRecord)/ImageBrowser PhotoStitch TWAIN (Windows 98/2000), WIA (Windows Me) ArcSoft PhotoStudio
POWER SOURCE Batteries Battery Life A/C Power Supply	Rechargeable Li-ion Battery NB-3L (battery and charger supplied) Approx. 150 shots ⁴ Approx. 180 min playback Optional, AC Adapter Kit ACK 900
ACCESSORIES Case Waterproof/Weatherproof Case Flash Remote Controller/Switch Power Supply & Battery Chargers Other	Soft Case SC-DC20, Soft Leather Case DCC-70, Digital IXUS Metal (Neck) Strap Waterproof Case (40m) WP-DC80, Waterproof Case Weights WW-DC1 High Power Flash HF-DC1 - - AC Adapter Kit ACK900 -
PHYSICAL SPECIFICATIONS Operating Environment Dimensions (WxHxD) Weight (body only)	0 – 40°C, 10 – 90% humidity 89.5 x 57.0 x 27.4mm (excluding protrusions) Approx. 170g

¹ Digital zoom available for still image and standard movie modes only.

² Large/Fine with LCD monitor off.

³ Depending on memory card speed/capacity.

⁴ Based on the CIPA Standard and using the batteries and memory card format supplied with the camera, except where indicated.

All data is based on Canon standard testing methods except where indicated. Specifications are subject to change without notice. ™ and ®: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries