



WARNINGS

VISION X Raptor LED Fog Light Kit requires attention before you use it. Please read the accompanying information carefully first.

- 1) Don't stare directly into the light or shine directly into the eyes of another person as this may cause temporary loss of vision.
- 2) Never disassemble the products, as all parts must be factory serviced to insure proper operation and will void warranty if opened.
- 3) Don't interchange the parts inside this light with other products.
- 4) The LED light is to be mounted on the vehicle only in a vertical, bottom-mounting, or in a suspended position.
- 5) Be careful when you touch the body, maybe "HOT"
- 6) Use the supplied wire adapters for electrical installation.
- 7) "Do Not Use Air Tools"
- 8) Ensure this system does not adversely affect the performance of low beam, high beam, engine cooling or the driver's view.

FORD RAPTOR LED FOG LIGHT KIT

Installation Instructions & User's Manual






www.VISIONXUSA.com

VISION X FORD RAPTOR KIT



Installation Instructions & User's Manual



1	Optimus Square & Bracket	2	Integration Harness	3	Mounting Hardware
					
LED Light & Bracket		Part (M1)	Qty: 2	Part (M1)	Qty: 8

APPLICATION GUIDE

- 1) At this time this kit has been tested to fit the 10-13 Ford Raptor

MAINTENANCE

- 1) All VISON X models have been designed for maintenance free use. In the case a LED lamp or other part replacement please contact your authorized service center.

MOUNTING INSTALLATION

- 1) Behind the lower air dam near the openings, locate painted frame support, (usually painted same as body color).
- 2) Line up flat edge of the VX brackets (use below image for what sides to the rear edge of the frame support (see image)
- 3) Mark the 4 holes, then pre-drill using a 1/8" drill bit.
- 4) These are self tapping screws but we suggest "Not" using air tools at all as they will strip the threads. You can use a cordless on lowest torque setting to install these self tapping bolts with the VX brackets/Lights
- 5) Mount both side (below image of each side) the same way, always test fit your work first as you only get one shot at this.
- 6) After the brackets are installed properly, and wiring is complete, start the vehicle, turn on the lights. At this time you can adjust these to your preference. After the adjustments are complete tighten the mounting bolts on the plates as well as the side bolts on the lights. They will be difficult to get to but tighten all of them



Passenger

Driver