



Add: Room 801, Huashenghui General Building, Jinhai Road, Xixiang St., Bao'an District, Shenzhen, Guangdong, China (Mainland)


Tel: +86-(0)755-66603665 Fax: +86-(0)755--25872283 Mobile: 8613128889471

Website:www.cameralarms.com Alibaba web: http://alarm-camera.en.alibaba.com Global sources : http://www.globalsources.com/camera-alarm.co

E-mail: phoebe@cameralarms.com MSN:phoebe.security@hotmail.com skype:phoebe.security



Quotation

GSM&PSTN dual network alarm system

Picture	Model Number:GS-G110E (900/1800,850/1900mhz)
<p style="text-align: center;"><i>Promotion</i></p> 	<p>1,7 wired and 100 wireless defense zones; GSM and PSTN dual network</p> <p>2,LCD screen with time clock display;</p> <p>3,Voice prompt for all operations, English/Spanish/French for choice</p> <p>4,3 groups of timely arm and disarm;</p> <p>5,Can store 6 phone numbers: when it is alarming, system will make alarm call to these numbers automatically;</p> <p>6,Can store 3 SMS numbers: when alarming, system will send alarming SMS automatically;</p> <p>7,10-second automatic message recording;</p> <p>8,Built-in artificial intelligent digital voice announcer;</p> <p>9. comfortable keypad with cover preventing the kids to press.</p>
<p>Standard packing list</p> <p>One main unit</p> <p>One wireless door/window sensor</p> <p>One wireless PIR sensor</p> <p>Two remote controllers</p> <p>One wired siren</p> <p>One AC adapter</p>	<p>10,Users can make calls by using keypad on alarm panel, work like a telephone;</p> <p>11,One-key-control function: Away Arm, Home Arm, Remote Arm;</p> <p>12,SOS, fire, gas, door, hall, window, balcony, and boundary places alarm;</p> <p>13,Real-time, delay, 24 hours, bypass defense zones programming function;</p> <p>14,Wireless coding: easy to add additional wireless accessories;</p> <p>15,Remote control Arm, Disarm, Monitor, and Intercom by phone;</p> <p>16,Built-in AAA NI-HI rechargeable battery: make alarm sounds when power off;</p> <p>17,Comply with CCC safety standard and GB12663-2001 national standard.</p>
	<p>Price (USD) Sample: FOB Shenzhen \$58</p>
	<p>10 to 50sets :\$55</p>
	<p>51 to 200sets:\$50</p>

Quotation


GSM&PSTN dual network alarm system

Piceture	Model Number:GS-G180E (900/1800,850/1900Mhz)
	<ol style="list-style-type: none"> 1.Touch keypad; Large LCD display; Internal antenna 2.GSM+PSTN dual network. 3. 30 wireless zones + 8 wired zones 4.Supports 15s' monitoring via phone call 5.Alarm SMS include alarm zone and sensors name 6.Support wireless “ding-dong” doorbell function 7.Alarm priority, Reset, activate and disable alarm call and alarm SMS
<p>Standard Package: One alarm host</p> <p>One wireless door/window magnetic contact</p> <p>One PIR motion sensor</p> <p>Two remote controllers</p> <p>One AC adapter</p> <p>One English user manual</p> <p>Nice package:</p>	<ol style="list-style-type: none"> 8. Work with Ademco Contact ID protocol and supports uploading to monitoring center (alarm/arm information, status information, AC power off and recover, host and sensor low voltage notice) 9. Arm\ Disarm the system in 5 ways: remote SMS message, remote phone call, Main Host (Keypad), Wireless Keypad (optional), Keychain Remotes. (PSTN alarm don't support SMS) 10.Message of host and sensor in low battery or energy will be sent to preset phone No. 11. Multi-languages version for choice: English/French/German/Spanish/Italian/Russian/Danish/Dutch/Turkish/ Swedish and all languages available if you can help in translation
	<p>Advantages: 1.touch keypad 2. internal antenna and nice look. 3.Many language version available</p> <p>4.large LCD 5. ABS fire-proof material 6. GSM+PSTN dual-network</p>
	Price(USD)Sample:FOB ShenZhen\$90
	10 to 50sets:\$85
	51 to 200sets:\$79

Quotation


GSM&PSTN dual network alarm system

GSM alarm system

Picture	Model Number:GS-G81 (900/1800,850/1900mhz)
 The image shows the main alarm unit, a keypad, a PIR motion sensor, an indoor siren, a door magnetic sensor, and two remote controllers. The main unit is a white rectangular device with a blue LCD screen and a keypad. The keypad is a small white device with a numeric keypad and function buttons. The PIR motion sensor is a white rectangular device with a lens. The indoor siren is a white cylindrical device. The door magnetic sensor is a small white device. The remote controllers are two small black devices with buttons.	<ol style="list-style-type: none">1. Keypad , blue backlights; blue LCD displays Date, Day of the week, Time and current Armed Status;2. Concise icons menu . Suitable for every market all over the world.3. 2 /4 Band GSM net-work. Supports phone call alarm and SMS alarm at the same time, SMS includes zone number and alarm event type. Automatically switch to GSM dialing when telephone line is cut.4. 15 wireless zones (Each zone supports up to 4 sensors) and 1 dedicated zones for remotes (Supports up to 10 remotes or wireless keypads per zone). Supports 2 wired zones (optional).5. 6 phone numbers can be preset and will dial in sequence. Every mobile phone number can be set for phone call alarm or SMS alarm.6. Intelligent logic analysis technology, corresponding zone number can be displayed on LCD screen.7. Arm\ Disarm the system by 5 ways: SMS, Main Host (Keypad), Wireless Keypad (optional), Keychain Remotes, and phone calls. (PSTN alarm don't support SMS)8. Work in AC\DC power, 110V TO 240 v outside power and DC12V backup battery. Host low-voltage alerts.9. Door\window status self-check and "Ding Dong" doorbell can be completed as optional functions.10. Support CID uploading to CMS (Center monitoring Station) .can user our GSM SMS CID connector to complete this function.11. Built-in Lithium backup battery, perfect system self-check, alerts of landline phone cable cut, no SIM card, alarm host low power, no external power supply and even low battery power of sensors.
1* main unit 1* PIR motion sensor 1* indoor siren 1* door magnetic sensor 2* remote controllers	<p>Price (USD) Sample: EXW Shenzhen \$52</p> <p>10 to 50sets : \$50</p> <p>51 to 200 sets : \$49</p>


Quotation

GSM&PSTN dual network alarm system

Picture	Model Number:GS-G60E GSM alarm system
	<p>Main functions:</p> <ol style="list-style-type: none"> 1.An advanced and reliable communication technology, dialing alarm 2.8 wired, 99 wireless defense zones 3.Remote control intelligent code, up to 5 wireless remote controls 4.LCD display, built-in calendar clock, operates easily 5.Full voice prompts, installation setting and daily operation are more easily 6.Arm and disarm, and siren on/off are could be controlled by SMS instruction 7.SMS prompt of low power 8.SMS prompt of AC power broken and recover 9.Built-in intercom speaker, can achieve duplex intercom function 14.Up to 2 SMS numbers to notify you of abnormal conditions 15.10 seconds artificially recording message 10.Built-in wireless transmitter module, wireless siren and smart home system can be linked 11.Preset 2 groups timing arm and disarm time 12.Calls out up to 6 phone numbers to notify you of abnormal conditions 13.Call out up to 2 phone numbers to notify the receiving alarm center 14.Up to 2 SMS numbers to notify you of abnormal conditions 15.10 seconds artificially recording message 16.Built-in digital voice, voice broadcast alarm situation automatically 18.Multiple defense zones including instant, delay, 24 hours, bypass 17.All arm and disarm function could be realized by one key GS-G60E 19.Wireless coding: adding new accessories convenient, safe and efficient
Standard packing list	
One main unit	
One wireless door/window magnetic contact	
One wireless PIR sensor	
Two remote controllers	
One White siren	
One AC adapter	
One English user manual	
Technical Parameters	
1.Working power: AC=100~230V,	
2.Static current:<50mA (when not charging)	
3.Alarm current:<500mA	
4.Built-in Li-Ion backup battery: 3.7V	
1200mAH(rechargeable), Standby: around 16 hours,Full charging time: 12 hours	
	<p>Price: Sample(USD): FOB Shenzhen \$68</p> <p>10 to 50sets :\$63</p> <p>51 to 200sets:\$59</p>



Quotation

GSM&PSTN dual network alarm system

Picture	Model Number:GS-G82 (900/1800,850/1900mhz)
	<ol style="list-style-type: none"> 1. Touch Screen, white color , internal antenna 2. LCD Screen displays Date, Day of the week, Time, and current Armed Status 3. 29 wireless zones (Each zone supports up to 4 sensors) and 2 dedicated zones for remotes (Supports up to 4 remotes or wireless keypads per zone) 4. Intelligent logic analysis technology, corresponding zone and sensor name can be displayed. 5. Can dial up to 5 phone numbers in sequence 6. Support seperated wireless doorbell, and will sound chord “Ding-Dong” from alarm hot panel when you press doorbell button. 7. Arm\ Disarm the system by: SMS, Main Host(Keypad), Wireless Keypad, Keychain Remotes, or even remotely by phones. (PSTN alarm don't support SMS) 8. Available in both AC\DC with Low-voltage Indicators 9. Learning sensors to alarm host, very easy operation. 10. Store up to 100 alarm records(alarm history) and 100 arm\disarm records(arm/disarm operation history) 11. Support CID uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function 12. Non-volatile chip, information stored automatically when off power 13. Check door>window status automatically (This is when the system is disarmed only, if a door is opened, it will sound fast “bi bi bi”) 14. AC FAILURE NOTIFICATION to CID Center monitoring station (Optional function) 15. Support wireless “ding-dong” doorbell function
Standard packing list	
One alarm host	
One intelligent wireless door/window magnetic contact	
One intelligent wireless PIR motion sensor	
One indoor siren	Price (USD) Sample: FOB Shenzhen \$98
Two remote controllers	10 to 50sets : \$95
One English user manual	51 to 200 sets : \$92


Quotation

GSM&PSTN dual network alarm system

Picture	Model Number:GS-G80AE (900/1800,850/1900mhz)
	<ol style="list-style-type: none"> 1. Touch Screen 2. LCD Screen displays Date, Day of the week, Time, and current Armed Status 3. Supported Languages: Simple Chinese\ Traditional Chinese\ English\ German\ French\ Russian\Danish and more. 4. 29 wireless zones (Each zone supports up to 4 sensors) and 2 dedicated zones for remotes (Supports up to 4 remotes or wireless keypads per zone) 5. 8 more wired zones(Optional), add US \$2.5 cost 6. Intelligent logic analysis technology, corresponding zone and sensor name can be displayed. 7. Support seperated wireless doorbell, and will sound chord "Ding-Dong" from alarm hot panel when you press doorbell button. 8. Can dial up to 5 phone numbers in sequence 9. Record up to a 10 second greeting for the auto-dialer, Then play the greeting back. 10. Arm\ Disarm the system by: SMS, Main Host(Keypad), Wireless Keypad, Keychain Remotes, or even remotely by phones. (PSTN alarm don't support SMS) 11. Available in both AC\DC with Low-voltage Indicators 12. Learning sensors to alarm host, very easy operation. 13. Store up to 100 alarm records(alarm history) and 100 arm\disarm records(arm/disarm operation history) 14. Support CID uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function 15. Non-volatile chip, information stored automatically when off power 16. Check door>window status automatically (This is when the system is disarmed only, if a door is opened, it will sound fast "bi bi bi") 17. AC FAILURE NOTIFICATION to CID Center monitoring station (Optional function) 18. Support wireless "ding-dong" doorbell function (Optional)
Standard packing list	
One main unit	
One wireless door/window magnetic con	
One wireless PIR sensor	
Two remote controllers	
One strobe siren	
One AC adapter	
One English user manual	
White version	
	<p>GSM frequency:</p> <p>GS-G80AE GSM900/1800MHZ</p> <p>GS-G80AEA GSM850/1900MHZ</p> <p>Price (USD) Sample: FOB Shenzhen \$93</p> <p>10 to 50sets : \$90</p> <p>51 to 200 sets : \$88</p> <p>Note:GS-G80AE has 868mhz version</p>


Quotation

GSM&PSTN dual network alarm system

Picture	Model Number:GS-G80CE (900/1800,850/1900mhz)	
	1.Touch keypad, blue backlights; blue LCD displays Date, Day of the week, Time and current Armed Status;	
	2. Concise icons guided LCD display. Suitable for every market all over the world.	
	3. 2 /4 Band GSM net-work. Supports phone call alarm and SMS alarm at the same time, SMS includes zone number and alarm event type. Automatically switch to GSM dialing when telephone line is cut.	
	4. 15 wireless zones (Each zone supports up to 4 sensors) and 1 dedicated zones for remotes (Supports up to 10 remotes or wireless keypads per zone). Supports 2 wired zones (optional).	
	5.Can preset up to 6 phone numbers and dial in sequence. Every mobile phone number can be set for phone call alarm or SMS alarm.	
	6. Intelligent logic analysis technology, corresponding zone number can be displayed on LCD screen.	
	7.Record up to a 10 second greeting for phone call alarms which can be heard when answering the alarm call.	
	8.Arm\ Disarm the system by 5 ways: SMS, Main Host (Keypad), Wireless Keypad (optional), Keychain Remotes, and phone calls. (PSTN alarm don't support SMS)	
	9.Available in AC\DC, Low-voltage alerts.	
	10. "One-Key" arm, studies sensors to alarm host, very easy operation.	
	11. Non-volatile chip, information stored automatically when off power.	
	12.Door/window status self-check and "Ding Dong" doorbell can be completed as optional functions.	
Standard packing list	13.8 zone electrical appliance control and 8 groups of scene control can be completed as optional functions.	
One main unit	14.Support CID uploading to CMS (Center monitoring Station) .can user our GSM SMS CID connector to complete this function.	
One wireless door/window magnetic sensor	15.Disconnection alarm, auto priority to occupy the telephone and monitoring function to hear what is happening.	
One wireless PIR sensor Two remote controllers	16. Built-in Lithium backup battery, perfect system self-check, alerts of landline phone cable cut, no SIM card, alarm host low power,no external power supply and even low battery power of sensors.	
One wireless strobe siren		
One AC adapter	Packaging Method	Packaging Dimension and Weight
Specification of main unit:	1 set of GS-G80CE into one gift box	Gift Box: G.W.:1.2kgs
1 Working power: AC=100~230V,	5 gift boxes into one carton.	Size:290(L)*270(W)* 85(H) mm
2.Alarm current:<500mA		Carton: G.W.:6.7kgs
3.Built-in Li-Ion backup battery: 3.7V		Size: 445(L)*305 x 290 (H)mm
4.1200mAH(rechargeable), Standby:	Price (USD) Sample: FOB Shenzhen \$85	
16 hours,Full charging time:12 hours	10 to 50sets : \$82	
	51 to 200 sets : \$78	

Quotation



GSM&PSTN dual network alarm system

Picture	Model Number:GS-G70E (900/1800,850/1900mhz)
	1. Color LCD screen, keypad with blue light
	2. Support ADEMCO Contact ID protocol uploading to CMS(Center monitoring Station)
	3. Maximum 30 wireless zones,support 8 more wired zones, add US \$2.5 cost .
	4. LCD display with calender, available in English/Chinese/Germany/Russian/French and Japanese etc. Non-volatile chip, information stored automatically when power off.
	5. One-key arm operation,With learning code programme method,it's easy to operate
	6.Preset 5 Telephone & 5 SMS number to inform alarm
	7. Switch to Backup rechargeable battery when the power is failure or cut by intruder.
Standard packing list	8. 5 methods Arm/Disarm: Remote Controller, Host Keypad, Remote Keypad(options),Telephone/Mobile phone and GSM SMS
One main unit	9. Internal & external antenna for your options
One wireless door/window magnetic contact	10. It will use GSM and has capability for land line where GSM is not possible
One wireless PIR sensor	11. External power failure and external power return informed via SMS
Two remote controllers	12. 2²⁰ wireless address encode reduce the rate of same code greatly.
One Wireless strobe siren	13. Learning code wireless accessories.
One AC adapter	14. SMS control & program
One English user manual	15. SMS modifies wireless zones name.
	20. Entry delay alarm.
Specification of main unit:	22. Internal MIC or external high sensitivity MIC (optional)
Output power: DC12V	25. Working with monitoring center, such as police station
Input power: AC110V to 220V,50Hz or 60 Hz	GSM frequency:
Working hours of standby Battery(DC8.4V):	GS-G70E GSM900/1800MHZ
More than 15 hours	GS-G70EA GSM850/1900MHZ
Wireless frequency for above accessories:	Price (USD) Sample: FOB Shenzhen \$92
315MHZ/433MHZ	10 to 50sets : \$88
	51 to 200 sets : \$86
	Note:GS-G70E has 868mhz version

Quotation


GSM&PSTN dual network alarm system

PSTN Alarm

Picture	Model Number:GS-T01
 	<ol style="list-style-type: none">1.99 wireless defence zones2.Each zone supports 3 modes freely. Switch off mode, Intelligent mode and Emergency mode Emergency mode: It use for put smoke detector, gas detector and other 24h working sensors. Intelligent mode: Usually switch on it when user at home. The zone for put PIR motion sensor, door sensor which user will be detecting when he in the house. The sensor in intelligent zone be triggered, it will not alarming.3.Anti-wireless signal interfere function.4.Can program 6 alarm phone numbers for receiving alarm phone call5.Preset sound alarming and silence alarming.6.Arm/disarm by remote control and phone call.7.Alarm phone call to be 1st function.8.Some zone can be disarmed by remote control solely.9*.Anti-phone line cut alarm function.
packing list:	
One main unit	10. Switch to Backup rechargeable battery automatically when power is failure or cut by intruder.
One wireless door/window sensor	11.Support doorbell functions: Detector will be Door Bell when disarmed
One wireless PIR sensor	12.With learning code programme method,it's easy to operate
Two remote controllers	
One strobe siren	
One AC adapter	Price (USD) Sample: FOB Shenzhen \$28
	10 to 50sets :\$25
	51 to 200 sets : \$21
One English user manual	


Quotation

GSM&PSTN dual network alarm system

Picture	Model Number:GS-T08E
	1,100 wireless and 8 wire defense zones.
	2,Blue backlighting graphic display.
	3,6 groups of voice alarm phones (mobile phone), and 2 groups of phones in alarm receipt center.
	4,Built-in perpetual calendar and clock; auto record alarm history by time sequence.
	5,Message recording playback: human recording, synchronous playback for recording effect in audition.
	6,More defense modes: remote defense, keypad defense, and non-local remote defense by telephone; stay-in defense, timing defense, and individual defense
	7,Programming of defense zone type: all zones could be programmed via keypad for immediate, delayed, 24-hour and bypass alarm modes.
	8,Alarm Position Programming: Intelligent automatic speech recognition: SOS alarm, fire alarm, gas leak, magnetic contact alarm, hall alarm, window alarm, balcony alarm, and perimeter alarm
	9,Timing arm and disarm: console features automatic timing arm and disarm.
	10,Two arm models:
Technical parameters:	1)home alarm model:console music and voice alarm, external siren mute
a)Input Voltage: DC12V 500mA	2) home away arm model:console voice alarm, loud external siren alarm.
b)Standby Current: 50mA	11,Password Recovery: Whether the console is in defense or withdrawal, the lost password can be recovered.
c)Alarm Current: 450mA max	12,Intelligent learning code: intelligent learning code, newly added with detector which is prompt and efficient, and convenient and simple.
e)Output current: DC12V 150mA	13,Event Log Query: console automatically records 45 pieces of all information concerning defense, withdrawal and alarm events.
f)Wireless Frequency: 315MHz	14,Line priority alarm: the console will cut the busy call and switch to priority alarm in case of the alarm during ongoing call, no matter incoming or outgoing call.
g)Coding Method: 2262 IC / 4.7MΩ	15,Phone disconnection detection: automatic detection and alarm warning in line disconnection, for anti-sabotage of telephone lines.
h)Alarm noise: 110dB	16,Remote control: through remote phone (cell phone) dial-up, many operations could be realized, like defense, withdrawal and on-site monitoring by the console in the remote control form.
i)Back-up Battery: AAA 7.2V	17Console is equipped with battery box, with optional AAA NI-HM rechargeable battery.Console meets 3C safety standards and national standard GB12663-20
j)Environment Temperature: -20℃ ~ +55℃	18,Compatible with internationally accepted protocol of alarm receipt center: Ademco Contact ID alarm communication protocol.
	Price (USD) Sample: FOB Shenzhen \$38
	10 to 50sets :\$36
	51 to 200 sets : \$34


Quotation

GSM&PSTN dual network alarm system

Picture	Model Number:GS-T01A
	1. LED display, 15 wireless zones, can work with up to 60 wireless sensors (each zone supports up to 4 sensors)
	2.You can connect wired & wireless PIR sensor, door/window contact, smoke detector, gas leakage detector, glass break sensor, emergency button etc. Each wireless zone can match numberless wireless sensors.
	3. With 13 working LEDs and control keyboard on the mainframe.
	4.You can record your voice in the mainframe in advance and will call you or the police and play the voice while alarming.
	5.Can Auto-dial 6 phone No. while alarming.
	6.You can call the mainframe at any time and listen what happened in the alarm area, and you can arm/disarm and program the system by control keyboard on the mainframe & phone
	7..Support ADEMCO Contact ID protocol uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function
	8.With voice reminder & password protection while the system is working.
	9. Remote monitor and check the alarm zones by phone.
	10. Arm mode: immediate arm, delayed arm and partial arm.
	11. Can set the ring times of alarm mainframe. When there is coming call, the mainframe can get through it automatically after checking the preset ring times.
One package includes:	12. Can choose to set/cancel the alarm function of cutting telephone line.
One main unit	13. Switch to Backup rechargeable battery automatically when power is failure or cut by intruder.
One wireless door/window magnetic contact	11. When the system alarms, it can report and follow up the latest alarm zones.
One wireless PIR sensor	14. Can send alarm signals to monitoring center through telephone network, such as the police station.
Two remote controllers	
One strobe siren	Price (USD) Sample: FOB Shenzhen \$45
One AC adapter	10 to 50sets :\$42
One English user manual	51 to 200 sets : \$39
	Note:GS-T01A has 868mhz version

Quotation


GSM&PSTN dual network alarm system

Picture	Model Number:GS-T01B
	Remark:
	The difference between GS-T01A and GS-T01B: GS-T01B has following extra features:
	1) LCD display
	2) With year/week /time/armed status
	3) Available to display in the following languages: English, Chinese, German, Russian, French, Japanese etc.
	4) 30 wireless zones, can work with up to 120 wireless sensors (each zone supports up to 4 sensors)
	5)Support ADEMCO Contact ID protocol uploading to CMS(Center monitoring Station) , can user our GSM CID connector to have this function
	All the functions and specification are same except for above
Price (USD) Sample: FOB Shenzhen \$60	
10 to 50sets :\$58	
51 to 200 sets : \$55	
Note:GS-T01B has 868mhz version	

Quotation

GSM&PSTN dual network alarm system





GPRS MMS Alarm System

Picture	Model Number:GS-M22E (900/1800,850/1900mhz)
	<i>*With camera & PIR itself</i>
	<i>*Can send MMS to your mobile phone.</i>
	<i>*Can Send picture to your E-mail.</i>
	<i>*Can match wireless detectors/sensors with alarm host by learning code.</i>
	<i>*Build-in 2G SD card to store pictures(In standard package,there is no SD card)</i>
	1. Built-in 300,000 pixels night vision digital camera,suitable fo night use.
	2. Support 2G SD card , convenient for long-term storage of image evidence.
	3. Support PIR motion detecting with photo-taking.
4. Support SMS, MMS,phone,E-mail to alarm.	
5. Image size is adjustable: QCIF(160×128)、CIF(320×240)、VGA(640×480)	
6. Can pre-set arm / disarm time,convenient for user or alarm center to control.	
7. The time of reporting can be set regularly .	
Technical parameter	8. 16 wireless zones,each can be prgrammed independently,eg : arm,disarm and 24-hour arm.
Static Current : 40 mA	9. Can set 5 user phone numbers ,can listen-in when alarming.
Power Supply : 9-12 V	10.Can set 2 email address: send scene image alarm info to E-mial.
Support PHASE2/2 & protocol	11.Support GSM / CDMA mobile phone to receive SMS alarm and send SMS commands to control the system.
Receive Coding : ASK	12.Can send scene color images to mibile phone immediately after alarming .
Receive Frequency : 315/433 MHZ	14.User can remotely listen-in by calling the host.Can hear the voice at the scene .
Remote Control Distance :30m	13.Can capture scene color photos and send to user by sending SMS command.
Detectors : 16	14.Built-in Li battery, AC-DC shift, automatically recharge
	15.Password operation ensure the security of system.
	16.Support Real-Time Clock adjustment, SD card image stored with time, convenient for inquire.
	17.Wireless system, no need to set wire and easy to install. Special suitable for garage, storeroom, and other places where there is no wired network.
	Price (USD) Sample: FOB Shenzhen \$90
	10 to 50sets :\$87
	51 to 200 sets : \$82

Quotation


GSM&PSTN dual network alarm system

3G Video ALARM SYSTEM

Picture	Model Number:GS-98A	850/900/1900/2100MHZ	
 	1. Camera can send alarm messages by SMS, video call, voice call		
	2.Max 15 wireless alarm sensors can be added.		
	3.Support to record the alarming image to the camera		
	4.Wireless remote control: it can arm ,disarm or send emergency alarm		
	5.Up to 11 telephone numbers can be pre-stored in the system		
	6.Including the intensity detection and infrared lighting functions		
	7. Motion detection function within 6m		
	8.using high sensitivity MIC, can make calls within 7m.		
	Standard Paking:	9.you can call the video phone to check the video of monitoring	
	one alarm host	10.3G standard:WCDMA,Built-in 2GB TF card	
one wireless door sensor	Price (USD) Sample: FOB Shenzhen \$119		
	5 to 50sets :\$117		
	51 to 100sets:\$115		
	101 sets to 200 sets:112		
Picture	Model Number:GS-98B	850/900/1900/2100MHZ	
 	1. Camera can send alarm messages by SMS, video call, voice call		
	2.Max 15 wireless alarm sensors can be added.		
	3.Support to record the alarming image to the camera		
	4.Wireless remote control: it can arm ,disarm or send emergency alarm		
	5.Up to 11 telephone numbers can be pre-stored in the system		
	6.Including the intensity detection and infrared lighting functions		
	7. Built-in PIR detection function within 6m		
	8.using high sensitivity MIC, can make calls within 7m.		
	Standard Paking:	9.you can call the video phone to check the video of monitoring	
	one alarm host	10.3G standard:WCDMA,The outer TF card	
one wireless door sensor	Price (USD) Sample: FOB Shenzhen \$112		
two remote controller	5 to 50sets :\$108		
	51 to 100sets:\$105		
	101 sets to 200 sets:103		

Quotation

GSM&PSTN dual network alarm system

Picture	Model Number:GS-6828	850/900/1900/2100MHZ
	1. Camera can send alarm messages by SMS, video call, voice call	
	2.Max 15 wireless alarm sensors can be added.	
	3.Support to record the alarming image to the camera	
	4.Wireless remote control: it can arm ,disarm or send emergency alarm	
	5.Up to 11 telephone numbers can be pre-stored in the system	
	6.Including the intensity detection and infrared lighting functions	
	7. Built-in PIR detection function within 6m	
	8.Built-in MIC and speaker,enables two-way intercom and on-site shouting function	
	9.you can call the video phone to check the video of monitoring	
Standard Paking:	10.3G standard:WCDMA	
one alarm host	11.The outer TF card	
one wireless door sensor	12.3G frequency:850/900/1900/2100MHZ	
two remote controller		
	Price (USD) Sample: FOB Shenzhen \$129	
	5 to 50sets :\$125	
	51 to 100sets:\$122	
	101 sets to 200 sets:119	