



# **DELL 3330dn LASER PRINTER**

# Dell B

# AN AFFORDABLE A4 MONO LASER PRINTER THAT'S IDEAL FOR BUSINESSES OF ANY SIZE

The Dell" 3330dn laser printer brings a new level of high-performance monochrome printing within reach of any company, from small businesses to large enterprises. It offers exceptional resolution, intuitive operation and very low print costs, enabling everyone in the workgroup to benefit from affordable, quality printing.

In addition to high-speed performance and razor-sharp resolution, an intuitive 4-line LCD panel with number pad makes operation quick and easy, with a host of advanced technologies enhancing productivity for your entire organisation including key benefits such as faster 'first page out' time, instant warm-up and duplex (print both sides) as standard. Moreover, the Dell 333Odn comes network ready, meaning faster deployment, hassle-free operation and ease of maintenance at a very affordable price.

## DELL 3330dn LASER PRINTER

### **PRODUCT BENEFITS**

### **EVEN FASTER PRINTING**

The Dell 3330dn delivers high-performance printing of up to 38 ppm with a duty cycle of up to 80 000 pages per month. This means less time waiting for print-outs and more time for productive work. And with a true print resolution of up to 1200 x 1200 dots per inch (dpi), the Dell 3330dn prints both text and business graphics with crystal clarity.

### **NETWORKING OUT OF THE BOX**

Embedded networking capabilities on the Dell 3330dn enable everyone in a workgroup to print professional-quality documents quickly and conveniently. The Dell 3330dn is expandable with an optional 550 sheet paper drawer and additional memory for demanding highcapacity printing, so your printer can grow along with your business.

### PRODUCTIVITY-BOOSTING EASE OF USE

The Dell 3330dn is equipped with a 4-line LCD panel that is easy to see and easy to use. It comes with a complete suite of management

software including the Dell Toner Management System, which alerts you to low toner levels. Re-ordering toner **ORDER** is simple. Just visit www.dell.com/supplies or order **SUPPLIES** by telephone from Dell or through selected resellers. **ONLINE** All this convenience adds up to less time fussing with your printer - and more time for getting work done.

### **LOWER PRINTING COSTS**

With an attractive price and low cost per page of printing, the 3330dn makes high-performance mono laser printing affordable not just for large companies, but also for small and medium-sized businesses. What's more, a rugged design, great reliability and Dell's comprehensive support services will help you protect your investment while you bring down costs.

### PRINT WITH THE ENVIRONMENT IN MIND

The Dell 3330dn paper drawer supports both the use of recycled paper and the re-use of freshly printed paper. "N-Up" multiplesheet printing reduces paper consumption by allowing you to print multiple pages on a single sheet of paper. On average, Energy Star qualified imaging equipment is 25% more efficient than conventional models according to US Environmental Protection Agency (source: www.energystar.gov).

Like all Dell printers, the 3330dn has been designed to reduce the use of non-recyclable materials and to eliminate hazardous materials. Dell printer users within most western European countries can return toner cartridges to Dell **DELL IS** for recycling at no cost, and we'll even help you dispose GREEN! of your old printers and other computer equipment in an environmentally responsible manner.



Dell 3330dn Laser printer with optional 550 sheet paper drawer



Dell 3330dn Laser printer operator panel



Dell 3330dn Laser printer Opened 50 sheet standard multipurpose tray



Toner and drum

### GET THE MOST OUT OF YOUR DELL PRINTER WITH GENUINE DELL OPTIONS AND SUPPLIES

Toner cartridges Dell 3330dn black toner cartridge High capacity: approximately 14 000 pages Standard: approximately 7000 pages

Toner yield based on testing in accordance with ISO/IEC 19752. Yields vary with usage and environmental conditions

Additional Consumables Dell 3330dn Imaging Drum Kit (included as standard with every new printer): replacement required after approximately 30 000 pages

Dell 3 m USB cable Connectivity

Dell 3 m Ethernet cable

Parallel cable

Service and support Installation service available

Next Business Day, onsite service options, extendable to 5 years

ProSupport service options, extendable to 5 years

Additional paper drawer An additional 550 sheet paper drawer is available for this printer, enabling less frequent paper refills or easy access to different types

of media (for example, plain paper in the standard drawer, preprinted notepaper in the second drawer) where supported by application



# DELL 3330dn LASER PRINTER

### **Product description**

### Low running-cost, high-speed networked monochrome laser printer with a compact footprint

**Printer specifications** 

Print speed Up to 38 A4 pages per minute (ppm)<sup>1</sup> From 'Ready' state - As fast as 6.5 seconds From 'Power Saver' mode - As fast as 7.0 seconds First page out time

Print resolution 600 x 600 dpi (printer default), maximum 1200 x 1200 dpi

User interface Data streams

4 line backlit LCD (text and graphics), 1 two-tone LED and a 20 button keypad PCL\* 5e, PCL 6, HTML, Personal Printer Data Stream (PPDS), HBP v3 (GDI), XPS (GDI) and PostScript\* Level 3 Emulation

466 MHz

Processor Memory (RAM) 64 MB standard, 576 MB maximum using optional 512 MB memory module One DIMM slot available for optional 128 MB, 256 MB or 512MB memory module Memory expansion

Maximum Duty cycle Up to 80 000 pages per month

Paper handling

Standard input sources 250 sheet covered drawer (75 gsm stock<sup>3</sup>) and 50 sheet multipurpose tray

One optional 550 sheet drawer can be fitted Additional input capacity

Maximum input capacity 850 sheets (250 sheet drawer + 50 sheet multipurpose tray + 1 x optional 550 sheet drawer)

Duplex unit Automatic duplex unit (print both sides) included as standard

Standard output destination 150 sheets bin face-down

Supported media types sizes and paper weights

Media types supported

Plain, Recycled, Light, Bond, Colored, Greeting Card Stock (No Duplex support), Envelopes (smooth), Paper Labels, Transparencies, Letterhead, Preprinted Paper

250 sheet standard tray (Tray 1) Media and Size: A4, A5, A6, JIS B5, US letter, US Legal, Executive, Folio, Statement, Universal, B5/C5/DL Envelope, 7 3/4

Envelope (Monarch) & 9 Envelope. Types: Paper, Paper labels, Transparencies Weight: 60 - 90 gsm

Media and Size: A4, A5, A6, JIS B5, US letter, US Legal, Executive, Folio, Statement, Universal, B5/C5/DL Envelope, 7 3/4

Envelope (Monarch) & 9 Envelope. Types: Paper, Paper labels, Transparencies Weight: 60 - 90 gsm Optional 550 sheet drawer (Tray 2)

Multipurpose Tray

Media and Size: A4, A5, A6, US B5, US letter, US Legal, Executive, Folio, Statement, Universal, 7 3/4 Envelope, 9 Envelope, 10 Envelope, B5 Envelope, C5 Envelope, DL Envelope, Other Envelope. Types: Paper, Paper labels, Transparencies, Card stock, Envelopes Weight: 60 - 160 gsm.

Media and Size: A4, Folio, US Letter, US Letter, Legal Types: Paper Weight: 60 - 160 gsm.

Duplexer Page layout options

Portrait or Landscape orientation, multiple copies, duplex printing, multipage printing (N-up), watermarks, collate Within 4 mm of all edges of the media

Printable area

Connectivity Standard interfaces Print languages and fonts

Hi-Speed USB 2.0 port, Parallel IEEE-1284, 10/100 baseT RJ45 Ethernet port. Note - cables are not included 3 of 9 scalable PCL 5e fonts in Narrow, Regular and Wide, 2 PCL bitmap fonts 39 scalable PPDS fonts, 5 PPDS bitmap fonts, 84 scalable PCL fonts, OCR-A, OCR-B scalable PCL 5e fonts, 91 scalable PostScript fonts

Operating Systems (OS) support

Microsoft\* Windows Server\* 2008, Windows Server 2003, Windows Server 2000, Windows\* XP 32 bit/64 bit, 2000, Microsoft Vista\* 32 bit/64 bit, Windows 7 (expected when released), Linux - Ubuntu 8.10, 9.04, Debian GNU/Linux 5.0 RH Linux 3.0, 4.0, 5.0 WS SuSE Linux 8.0, 9.0, 10.0. SuSE Linux Enterprise Server 11, SuSE Linux Enterprise Desktop 11, OpenSuSE 11.1, Novell Net Ware 5.1, 6.x. Macintosh version (OS 9.2 and OS X 10.2 -10.6), Unix( PS PPD for Sun Solaris 8,9, 10.0) HP UX. Citrix Metaframe Presentation Server 3.0 & 4.0 (compatible) and 4.5 (certified), SAP.

Network protocols

TCP/IP IPv4, IPX/SPX, AppleTalk\*, LexLink (DLC), TCP/IP IPv6, TCP, UDP, LPR/LPD Direct IP (Port 9100), Enhanced IP (Port 9400), FTP, TFTP, IPP 1.1 (Internet Printing Protocol), ThinPrint .print integration , HTTP, HTTPs (SSL\*/TLS), SNMPv3, WINS, IGMP, BOOTP, RARP, APIPA (AutoIP), DHCP, ICMP, DNS, SNMPv2c, Bonjour, DDNS mDNS, ARP, NTP, Telnet, Finger.

### Consumables

Toner management

Ship-with toner cartridge capacity<sup>2</sup> Refill toner cartridge capacity

Imaging Drum Additional toner Toner reycling Additional Consumables In conjunction with the printer and software, features include toner level reporting, low toner elects, auto-generated alert

e-mails, toner conservation, Web access via Dell Printer Web Tool, and the Dell Toner Management System™
The printer ships with a standard capacity toner cartridge (approx 7 000 pages based on ISO 19752 testing standard).
Standard capacity (approx 7 000 pages based on ISO 19752 testing standard) or High capacity cartridges (approx 14 000 pages based on ISO 19752 testing standard) are available for this printer

Customer-replaceable Imaging Drum - yield approximately 30 000 printed sides Available through Dell online, by telephone or through selected resellers Toner cartridges are recyclable using Dell's recycling program, details of which are included with each product

No additional consumables are required

Language and regulatory certifications

Printer firmware including LCD operator panel, and printer driver software User documentation

**EMC** certifications

Design for environment

English, French, Italian, German, Spanish, Dutch

Softcopy user manual on CD in English, French, Italian, German, Spanish, Danish, Dutch, Norwegian, Swedish, Finnish, Iberian Portuguese, Polish, Czech, Greek, Arabic, Hebrew, Russian, Turkish

Basic set-up and safety instructions available in English, French, Italian, German, Spanish, Dutch, Arabic, Finnish, Hungarian, Romanian, Czech, Danish, Norwegian, Polish, Iberian Portuguese, Russian, Swedish, Turkish, Greek

IEC/EN60950-1:2001 (International); IEC60825-1 (Laser); CE Mark (EU); NEMKO (Nordic); GS Mark (Germany); GOST and Hygienic (Russia); SASO (Saudi Arabia); SABS (South Africa); UL 60950-1, First Edition (2003) EN 60950-1:2001 I EC 60950-1, Safety certifications

First Edition (2001); FDA; other safety approvals required by individual countries
Class B EN 55022:2006 / CISPR 22:2005 EN 55024:1998 + A1:2001 + A2:2003 EN 61000-3-2:2006 and IEC 61000-3-2:2005 EN 61000-3-3:1995 + A1:2001 + A2:2005; ICES-003, CE (EU countries); GOST (Russia); SABS (South Africa)

Meet Environmental design requirements including material restrictions and energy consumption requirements i.e. EU WEEE, RoHS<sup>4</sup> compliant, Energy Star 1.1 compliant, Blue Angel Compliant.

Other certifications and compliances SAP, Novell Yes, Citrix ready, Cerner, Citrix Metaframe XP Presentation Server, Citrix Metaframe Presentation Server 3.0 & 4.0

(compatible) and 4.5 (certified). TAA compliant f220V, Section 508 Compliant.



# DELL 3330dn LASER PRINTER

Printer management

Dell Toner Management System" intelligent toner monitoring proactively notifies you before you run out of toner. Dell Printer Web Tool. Printer Alert Utility. TCP/IP Setup Utility CA's Unicenter\*, HP OpenView", and virtually any printer or device network management system that supports Embedded

Compatible printer management software

Web Server (EWS)

Warranty and Service options

Standard Service
1 year limited hardware warranty<sup>5</sup>

24 x 7 online Technical Support

12 months Next Business Day on Site repair

Printer options and accessories

Refill toner cartridges

Additional memory

Dell 3330dn black toner cartridge - standard capacity (approximately 7 000 pages²)

Additional input paper capacity

Dell 3330dn black toner cartridge - high capacity (approximately 14 000 pages²)
One additional optional 550 sheet drawer can be fitted (maximum capacity 850 sheets) enabling less frequent paper refills
Additional 550 sheet paper drawer dimensions WxDxH - 426 mm x 370 mm x 130 mm, weight 3.4 kg

An optional 128/256 or 512 MB DDR2 memory module is available. Additional memory may speed the

processing of large/complex print files, or networked print files

Physical specifications

Dimensions (mm) - HxWxD

Printer: 260 x 422 x 369 mm

Shipping carton: 355 mm H x 430 mm W x 520 mm D
Printer: 14.1 kg; Packaged shipping weight 16.7 kg
Operating: air temperature 16°C to 32°C, Relative Humidity 8 - 80%, maximum altitude 2 500m Operating environment

Storage (unpackaged): air temperature 0°C to 40°C, Relative Humidity 8 - 80%

Acoustics

Voltage

Weiaht

Average Sound Pressure Level

Printing Simplex: 53 dBA6 Printing Duplex: 52 dBA6 Inaudible6

Printing: 6.7 BA<sup>6</sup>

Standby Mode Sound Power Level Standby Mode Inaudible<sup>6</sup>

220 - 240 V at 50/60 ± 3 Hz. Power cord included with shipped printer.

Power consumption Printing 500 W or less (simplex), 310 W or less (duplex): Standby mode (ready mode) 12 W: Power Saver 11 W: Off 0 W. Energy

Star® 1.1 compliant 2.72 kWh per week

Typical electricity consumption8

User-definable - 1-240 minutes (default 60 min) Power Save options

### NOTES

Print speed quoted refers to A4 Simplex (single-sided) page using default print mode (600 dpi). Actual print speed may vary depending upon system configuration, software application and document complexity.

Tested in accordance with ISO/IEC 19752 testing methodology. Yields vary with usage and environmental conditions.

250 sheets is the maximum input capacity when using 75 gsm paper stock. If heavier stock paper is used the capacity will be reduced slightly

Meets the requirements of the EU Directive on the Restriction of the use of certain Hazardous Substances (RoHS) dated 27 January 2003. Service may be provided by third party. Technician will be dispatched if necessary following phone-based troubleshooting. Subject to parts availability, geographical restrictions and terms of service contract. Service timing dependent upon time of day call placed to Dell. Defective unit must be returned. Replacements may be refurbished.

Tested in accordance with ISO 7779 and reported in accordance with ISO 9296, Acoustics - Declared noise emission values of computer and business equipment.

This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit.

The Typical Energy Consumption value is derived from printer energy consumption specifications combined with typical business printing usage for this model. The midpoint of the Typical Monthly Print Volume is assumed to be printed at 30 minute intervals across a 10 hour business day (0800-1800), 5 days per week The printer enters standby mode when the print job is complete, and enters sleep mode after the default period.

The printer is assumed to remain in sleep mode at all other times including two weekend days. Energy consumption will be further reduced if the printer is powered down when not in use for long periods. Actual energy consumption will vary according to print volume and usage patterns.

