

AirKing®

Ventilation Products

SPECIFICATIONS

52" Ceiling Fan

52" BUILDER'S CHOICE CEILING FANS

120 Volts, 0.5 amps, 60 hz.

► **FAN BODY**

Powder coated .0035" thick steel body housing.

► **MOTOR**

Permanently lubricated, powerful 3-speed reversible motor. 120 volt, 60 hz, 0.5 amp, 60 watt.

► **UNIT MOUNTING**

Dual mounting. Close to ceiling mounting or Downrod. All mounting hardware including a 4" downrod is included in box.

► **FINISHES**

- 9800 - Polished Brass body
- 9805 - White/Polished Brass body
- 9810 - White body
- 9815 - Antique Brass body



► **PADDLES**

- 9800 - 5 reversible Cherry/Oak paddles
- 9805 - 5 reversible White/Bleached Oak paddles
- 9810 - 5 reversible White/Bleached Oak paddles
- 9815 - 5 reversible Cherry/Dark Oak paddles

► **SINGLE PACK SHIPPING INFO**

- Box Dim 21"x 9^{13/16}"x 10^{1/8}"
- UPC: 9800 0-4601337088-4
- 9805 0-4601337188-1
- 9810 0-4601337288-8
- 9815 0-4601337388-5
- Shipping Weight - 14.1 lbs.

PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY			DATE
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



U.S.: 820 Lincoln Avenue
 West Chester, Pennsylvania 19380-4466
 Tel: (610) 692-7400 • 1-877-304-3785
 Fax: (610) 696-4648

Canada: 110 Glidden Road
 Brampton, Ontario L6T 2J3
 Tel: (905) 456-2033
 Fax: (905) 456-1015