



Data Sheet

HD110C

Heavy-Duty Digital Multimeter

Key features:

- Measures 1500 VDC
- CAT IV 1000 V
- IP67 Rated
- Magne-Grip™ holster with magnetic hanging strap

- Highest voltage capability, measuring to 1500 V dc and 1000 V ac
- CAT IV 1000 V rated
- Special sealing for environment and water resistance. IP67 rated
- Constructed with drop-resistant housing and PCB mounting
- Magne-Grip™ holster, frees both hands for work
- Includes high voltage test leads with threaded alligator clips

The HD110C is designed for professional use in harsh environments. The meter is unusually rugged and reliable in everyday heavy use applications. The meter is made using waterproof construction to prevent dirt, grime and moisture from entering the case and causing inaccurate readings or damaging shorts.

Built of tough, fire-retardant thermoplastic resistant to grease and chemical spills, with all sensitive components shock-mounted for a drop resistant to at least eight feet.

HD110C has an extended voltage measurement capability of 1500 V dc and 1000 V ac, unmatched by any other line of digital multimeters. The extended voltage ranges can withstand transients up to 12 kV.



HD110C

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.





HD110C Technical Specifications

Data Sheet

General Specifications

Display	3-1/2 digit LCD, 1999 counts, with annunciators and menu features
Polarity Indication	Automatic
Input overload indication	1
Low Battery Indication	; < 50 hours battery life remain, accuracy is no longer guaranteed
Display Update Rate	2.5/sec, nominal
Oper. Temp.	0 °C to +50 °C, (< 75 % R.H.)
Storage Temp	-20 °C to 60 °C, 0 to 80 % RH, battery removed
Temperature coefficient	0.1 x (spec. accuracy)/°C (0 ° to 18 °C and 28° to 50 °C) all functions and ranges except for mVDC 0.3 x (spec. accuracy)/°C (0 ° to 18 °C and 28° to 50 °C) for mVDC
Altitude	Up to 2000 m — indoor use
Fuse	F 2 A/1500 V fuse (8 mm x 65 mm), I.R. 30 kA – Amprobe® p/n FP700
Power	Standard 9 V battery, NEDA 1604, JIS 006P, IEC 6F22
Auto Power-Down	Meter powers down after approx. 30 min. of inactivity.
Battery Life	250 hours typical with carbon-zinc, 500 hours typical with alkaline
Dimensions, with holster (H x W x D)	200 x 102 x 59 mm (7.9 in x 4.0 in x 2.3 in)
Weight (incl. battery)	642 g (20 oz)
Accessories	Heavy Duty CAT IV 1000 V Test leads with threaded alligator clips (TL1500), battery (in instrument), hex wrench in holster, Magne-Grip flex strap and User Manual
Case material	Flame retardant, high-impact thermoplastic
Safety	Meets EN 61010-1 CAT IV 1000 V (1500 V DC max) Class II, EN 60529:IP67
EMC	Meets EN 61326-1

Electrical Specifications *(Accuracies at 23 °C ± 5 °C, <75 % RH non-condensing, guaranteed for one year.)*

Function	Range	Accuracy
DC Volts		
Ranges	200 mV, 2 V, 20 V, 200 V, 1500 V	
Resolution	0.1 mV	
Accuracy	All ranges	±(0.1 % rdg+2 dgts)
Input Impedance	10 MΩ	
OL Protection	1500 V dc/1000 V ac rms	
Transient Protection	12 kV impulse (1.2 μS/50 μS) based on EN 61010-1:2001 impulse requirement for at CAT IV 1000 V product. This product should not be used in installations where transients exceed 12 kV.	
AC Volts (45 Hz to 2 kHz)		
Ranges	200 mV, 2 V, 20 V, 200 V, 1000 V	
Resolution	0.1 mV	
Accuracy	200 mV to 200 V (45-500 Hz)	±(0.8 % rdg+4 dgts)
	200 mV to 200 V (500 Hz-2 kHz)	±(1.5 % rdg+5 dgts)
	1000 V (50-60 Hz)	±(0.8 % rdg+4 dgts)
	1000 V (60-500 Hz)	±(1.5 % rdg+5 dgts)
Input Impedance	10 MΩ	
OL Protection	1500 V dc/1000 V ac rms	
Transient Protection	12 kV impulse (1.2 μS/50 μS) based on EN 61010-1:2001 impulse requirement for at CAT IV 1000 V product. This product should not be used in installations where transients exceed 12 kV.	
DC Current		
Ranges	200 μA, 2 mA, 20 mA, 200 mA, 2 A	
Resolution	0.1 μA	
Accuracy	200 μA to 20 mA	±(0.5 % rdg+2 dgts)
	200 mA to 2 A	±(1.0 % rdg+2 dgts)



HD110C Technical Specifications (continued)

Data Sheet

Function	Range	Accuracy
DC Current (cont.)		
Voltage Burden	250 mV max. (1 mV/1 μ A on 200 μ A Range) (100 mV/1 mA on 2 mA Range) (10 mV/1 mA on 20 mA Range) (1.5 mV/1 mA on 200 mA Range) (500 mV/1 A on 2 A Range)	
OL Protection	A Input (F 2 A/1500 V, size 8 x 65 mm IR fast blow ceramic) (FP 700)	
AC Current (45 Hz to 1 kHz)		
Ranges	200 μ A, 2 mA, 20 mA, 200 mA, 2 A	
Resolution	0.1 μ A	
Accuracy	200 μ A to 20 mA 200 mA to 2 A	$\pm(0.8 \% \text{ rdg}+4 \text{ dgts})$ $\pm(1.2 \% \text{ rdg}+4 \text{ dgts})$
Voltage Burden	250 mV max. (1 V on 2 A range)	
OL Protection	same as DC Current	
Resistance		
Ranges	200 Ω , 2 k Ω , 20 k Ω , 200 k Ω , 2 M Ω , 20 M Ω	
Resolution	0.1 Ω	
Accuracy	200 Ω 2 k Ω to 200 k Ω 2 M Ω 20 M Ω	$\pm(0.5 \% \text{ rdg}+4 \text{ dgts})$ $\pm(0.3 \% \text{ rdg}+2 \text{ dgts})$ $\pm(1.0 \% \text{ rdg}+4 \text{ dgts})$ $\pm(2.0 \% \text{ rdg}+4 \text{ dgts})$
OL Protection	1500 V dc/1000 V ac rms	
Open Circuit Voltage	200 Ω range all other ranges	3.0 V dc typical 0.3 V dc typical.
Diode/Continuity Test		
Test Current	1m A dc typical	
Test/Open Circuit Voltage	3.0 V dc Typical	
Diode Accuracy	$\pm(1.5 \% \text{ rdg}+2 \text{ dgts})$	
Continuity Audible Threshold	<50 $\Omega \pm 25 \Omega$	
Response Time	<100 msec	
OL Protection	1500 V dc/1000 V ac rms	



Included Accessories

Heavy Duty CAT IV 1000 V Test leads with threaded alligator clips (TL1500), battery (in instrument), hex wrench in holster, Magne-Grip flex strap and User Manual

Optional Accessories

- | | |
|-----------|---|
| TL1500 | Cat IV 1000 V Test Leads with Alligator Clips |
| CT235A | 1000 A ac/dc Clamp |
| CT237A | 200 A ac/dc Current Clamp |
| CT238A | 20 A ac/dc Current Clamp |
| VC221B | Padded Vinyl Case. Fits meter & holster. |
| DC205C | Deluxe Hard-Shell Carry Case |
| DC207C | Large Deluxe Hard-Shell Carry Case with extra space for accessories |
| HV231-10A | High Voltage Probe |
| FP700 | Replacement Fuse, 2 A/1500 V, pack of two |

Amprobe® Test Tools

website: www.Amprobe.com
email: info@amprobe.com
6920 Seaway Blvd.
Everett, WA 98203
tel: 877-AMPROBE

Amprobe® Test Tools Europe

P.O. Box 1186
5602 BD Eindhoven
The Netherlands



Data Sheet

HD160C

Heavy-Duty Digital Multimeter

Rugged autoranging meter with true-rms

Key features:

- Measures 1500 VDC
- CAT IV 1000 V
- IP67 Rated
- Temperature, Frequency & Capacitance
- Magne-Grip™ holster with magnetic hanging strap

No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

- Highest voltage capability, measuring to 1500 Vdc and 1000 Vac
- CAT IV 1000 V rated
- Special sealing for environment and water resistance. IP67 rated
- Constructed with drop-resistant housing and PCB mounting
- Measures capacitance, temperature and frequency
- Superior 10,000 count resolution with bar graph
- Magne-Grip™ holster, frees both hands for work
- Includes high voltage test leads with threaded alligator clips
- Temperature measurement built-in
- Frequency and capacitance
- Digi-Glo™ bright backlight

The HD160C is designed for professional use in harsh environments. The meter is unusually rugged and reliable in everyday heavy use applications. The meter is made using waterproof construction to prevent dirt, grime and moisture from entering the case and causing inaccurate readings or damaging shorts.

Built of tough, fire-retardant thermoplastic resistant to grease and chemical spills, with all sensitive components shock-mounted for a drop resistance to at least eight feet.

Model HD160C has an extended voltage measurement capability of 1500 V dc and 1000 V ac, unmatched by any other line of digital multimeters. The extended voltage ranges can withstand transients up to 12 kV.



HD160C



HD160C Technical Specifications

Data Sheet

General Specifications

Display	4 digit LCD, 9999 counts, with annunciators, menu features and 41 segment bargraph.
Polarity Indication	Automatic
Input overload indication	OL, -OL.
Low Battery Indication	 ; less than 50 hours battery life remain, accuracy is no longer guaranteed
Display Update Rate	2/sec, nominal; 20/sec for bargraph.
Oper. Temp.	0 °C to +50 °C @ 0 to 75 % R.H.
Storage Temp.	-20 °C to 60 °C @ 0 to 80 % RH, battery removed
Altitude	2000 meters - indoor use
Temperature coefficient	0.1 x (spec. accuracy)/°C (0 °C to 18 °C and 28 °C to 50 °C)
Fuse	F 2 A/1500 V fuse (8 mm x 65 mm), I.R. 30 kA – Amprobe® p/n FP700
Power	Standard 9-volt battery, NEDA 1604, JIS 006P, IEC 6F22
Auto Power-Down	Meter powers down after approximately 30 minutes of inactivity. Not in Min/Max function.
Battery Life (typical)	150 hours, alkaline. Backlight usage consumes extra power and will decrease battery life significantly. Backlight auto-off after approx. 60 seconds.
Dimensions, without holster (H x W x D)	200 x 102 x 59 mm (7.9 in x 4.0 in x 2.3 in)
Weight (incl. battery)	642 g (22 oz)
Accessories	Heavy Duty CAT IV 1000 V Test leads with threaded alligator clips (TL1500), battery (installed), hex wrench (inside holster), Holster with Magne-Grip strap, Type K thermocouple probe (TP255), Temperature Adaptor (TA-1A) and User Manual.
Case material	Reinforced, high-impact, fire retardant thermoplastic
Safety	Meets EN 61010-1 CAT IV 1000 V (1500 V DC max) Class II, EN 60529:IP67
EMC	Meets EN 61326-1

Electrical Specifications *(Accuracy at 23 °C ± 5 °C, <75 % RH, guaranteed for one year.)*

Function	Range	Accuracy
DC Volts		
Ranges	1000 mV, 10 V, 100 V, 1500 V	
Resolution	0.1 mV in 1000 mV range	
Accuracy	±(0.1 % rdg + 5 dgt)	
Input Impedance	10 MΩ	
CMRR	>120 dB up to 1500 V dc	
NMRR	>60 dB at 50 or 60 Hz	
OL Protection	1500 V dc or 1000 V ac rms.	
Transient protection	12 kV impulse (1.2 μS/50 μS) based on EN 61010-1:2001 impulse requirement for at CAT IV 1000 V/1500V dc product. This product should not be used in installations where transients exceed 12 kV.	
AC Volts True rms		
Ranges	1000 mV, 10 V, 100 V, 1000 V	
Resolution	0.1 mV in 1000 mV range	
Accuracy	1000 mV (45 Hz to 400 Hz)	± (1.2 % rdg + 10 dgt)
	10 V, 100 V (45 Hz to 500 Hz)	± (1.2 % rdg + 10 dgt)
	10 V, 100 V (500 Hz to 2 kHz)	± (2.0 % rdg + 10 dgt)
	1000 V (45 Hz to 1 kHz)	± (2.0 % rdg + 10 dgt)
Input Impedance	10 MΩ	
Conversion type	True rms, ac coupled 5 % to 100 % of range	
Crest factor	≤ 3	
OL Protection	1500 V dc or 1000 V ac rms	
Transient protection	12 kV impulse (1.2 μS/50 μS) based on EN 61010-1:2001 impulse requirement for at CAT IV 1000 V product. This product should not be used in installations where transients exceed 12 kV	



HD160C Technical Specifications (continued)

Data Sheet

Function	Range	Accuracy
DC Current		
Ranges	100 μA, 1000 μA, 10mA, 100mA, 400mA, 2A (Auto/Manual ranging)	
Resolution	0.01μA in 100 μA range	
Accuracy	100 μA range	± (0.5% rdg + 10 dgts)
	1000 μA to 400 mA ranges	± (0.5% rdg + 5 dgts)
	2 A range	± (1.5% rdg + 10 dgts)
Input protection	2 A/1500 V fast blow ceramic fuse 8×65 mm on A input , FP700	
Burden voltage	μA range of 1 mV/1 μA, mA range of 10 mV/1 mA, 2A range of 500 mV/1A, 500 mV max. (2 V max. on 1000 μA, 100 mA, 400 mA, 2 A ranges)	
OL Protection	A Input (F 2 A/1500 V, size 8 x 65 mm IR fast blow ceramic)	
AC Current True rms		
Ranges	100 μA, 1000 μA, 10 mA, 100 mA, 400 mA, 2 A	
Resolution	0.01 μA in 100 μA range	
Accuracy (45 Hz to 1kHz)	100 μA to 100 mA	± (1.5 % + 10 dgts)
	400 mA	± (2.0 % + 10 dgts)
	2 A	± (2.5 % + 20 dgts)
Voltage burden	see DC Current	
Conversion type	True rms ac coupled 10 to 100% of range	
Crest factor	≤ 3	
OL protection	see DC Current	
Resistance		
Ranges	1000 Ω, 10 kΩ, 100 kΩ, 1000 kΩ, 10 MΩ, 40 MΩ	
Resolution	0.1 Ω in 1000 Ω range	
Accuracy	1000 Ω to 1000 kΩ ranges	± (0.5 % rdg + 8 dgts)
	10 MΩ range	± (1.0 % rdg + 10 dgts)
	40 MΩ range	± (2.0 % rdg + 10 dgts)
Overload protection, all ranges	1500 V dc or 1000 V ac rms	
Continuity Test		
Audible indication	Less than 40 Ω	
Response time	100 ms	
Overload protection	1500 V dc or 1000 V ac rms	
Capacitance		
Ranges	40 ηF, 400 ηF, 4 μF, 40 μF, 400 μF (3999 counts) (Auto/Manual ranging)	
Resolution	0.01 ηF	
Accuracy	40 ηF, 400 μF ranges	±(3.0% rdg +10 dgts)
	400 ηF to 40 μF ranges	±(3.0% rdg +5 dgts)
Test voltage	< 1 V	
Test Frequency	1.3 Hz on 40 ηF to 40 μF ranges; 0.7 Hz on 400 μF range	
Overload protection	1500 V dc or 1000 V ac rms	
Temperature		
Ranges	-20 °C ~ 1300 °C (-4° F ~ 2372 °F)	3999 counts
Resolution	1 °C, 1 °F	
Accuracy	-20 °C ~ 10 °C	±(2.0% rdg + 4 °C)
	10 °C ~ 200 °C	±(1.0% rdg + 3 °C)
	200 °C ~ 1300 °C	±(2.0% rdg + 2 °C)
	-4 °F ~ 50 °F	±(2.0% rdg + 8 °F)
	50° F ~ 400 °F	±(1.0% rdg + 6 °F)
	400 °F ~2372 °F	±(2.0% rdg + 4 °F)
Overload protection	1500 V dc or 1000 V ac rms	

(continued on next page)

HD160C Technical Specifications (continued)

Data Sheet

Function	Range	Accuracy
Frequency		
Ranges	100Hz, 1000Hz, 10kHz, 100kHz, 1000kHz, 10MHz	
Resolution	0.01 Hz on 100 Hz range	
Accuracy	±(0.1% rdg + 5 dgts)	
Sensitivity	3 Hz to 1 MHz 1MHz to 10MHz	>2.5 V ac rms >2.5 V ac rms, <5 V ac rms
Minimum input range	100 Hz range 1000 Hz range	>3 Hz; >30 Hz
Minimum pulse width	> 25 ns	
Duty cycle limits	> 30 % and < 70 %	
Overload protection	1500 V dc or 1000 V ac rms	



Included Accessories

Heavy Duty CAT IV 1000 V Test leads with threaded alligator clips (TL1500), battery (installed), hex wrench (inside holster), Holster with Magne-Grip strap, Type K thermocouple probe (TP255), Temperature Adaptor (TA-1A) and User Manual.

Optional Accessories

- TL1500** Cat IV 1000 V Test Leads with Alligator Clips
- CT235A** 1000 A ac/dc Clamp
- CT237A** 200 A ac/dc Current Clamp
- CT238A** 20 A ac/dc Current Clamp
- VC221B** Padded Vinyl Case. Fits meter & holster.
- DC205C** Deluxe Hard-Shell Carry Case
- DC207C** Large Deluxe Hard-Shell Carry Case with extra space for accessories
- HV231-10A** High Voltage Probe
- FP700** Replacement Fuse, 2 A/1500 V, pack of two
- TA-1A** K-type thermocouple, temperature adapter

Amprobe® Test Tools

website: www.Amprobe.com
email: info@amprobe.com
6920 Seaway Blvd.
Everett, WA 98203
tel: 877-AMPROBE

Amprobe® Test Tools Europe

P.O. Box 1186
5602 BD Eindhoven
The Netherlands