Overview

The HP XP7 Storage is bulletproof storage for mission-critical converged infrastructure where constant access to data is required-even in the event of a disaster. Designed for organizations that simply cannot afford any downtime, the XP7 combines an ultra-highperformance on-line scalable fully redundant hardware platform with unique data replication capabilities integrated with clustering solutions for complete business continuity and data protection. The XP7 can adapt to changing business conditions in real time, while increasing data center capacity and lifespan and provide solutions that decrease risk and costs.

The HP XP7 Software Family decreases the complexities of critical data management. Through Smart Tiering and thin provisioning, organizations can improve storage resource utilization. Advanced virtualization simplifies the management of diverse systems. Smart Tiers improves storage performance and controls costs. Massive consolidation becomes a reality by managing open systems, mainframe, and HP Non-Stop applications all on a single XP7 with ultra-high performance, low latency and reduced data center costs.

HP XP7 Storage is Unstoppable, Unbreakable, Unbeatable and Unconditional.



HP XP7 Storage



Overview

Scalability of the HP XP7				
	MIN	INCREMENT	MAX	
Racks	1	1	6	
Data Drives SFF	0	4	2304	
Data Drives LFF 0	0	4	1152	
Data Drives SSD	0	4	384*	
Data Media Modules FMD	0	4	192*	
Spare Media	0	1	128	
SBX (SFF Media Chassis)	0	1	12	
UBX (LFF Media Chassis)	0	1	12	
FBX (FMD Media Chassis)	0	1	4*	
Capacity	0 GB in a diskless configuration	Single parity group of 4 HDD, SSD or FMD	4.5 PB raw 3.9 PB useable	
SAS Disk Adapter (DKA) Pairs	0	1	4	
Channel Adapter (CHA) Pairs	1	1	12	
16 Gbps FC Host Ports	8	8	96	
8 GBps FC Host Ports	16	16	192	
FICON Host Ports	16	16	176	
FCoE Host Ports	8	8	88	
Cache	32 GB (2 x16 GB)	32 GB (2 x 16 GB)	2 TB	
LDEVs	0	1	65,280	

* It is physically possible to place more in the XP7, and that will be allowed on an exception basis in the configuration ordering tools.



Standard Features



The XP7 hardware consists of one or two DKC racks that will hold up to 2 media form factor chassis in each DKC rack. There are three separate media chassis for 3 media form factors Each media chassis may contain a maximum of

- 192 Small Form Factor media (SFF HDDs and/or SFF SSDs) each. or
- 96 Large Form Factor Hard disk drives (LFF HDDs) each, or
- 48 XP Flash Modules (FMD) each.

Media chassis may be ordered as upgrades and placed in racks as a field upgrade. Each DKC rack can attach to one or two optional DKU racks. The DKU Racks may contain one or two media chassis each.

A DKC Rack contains one or two Controller Chassis (DKCs)

A single DKC rack may contain one or two media chassis.
 A Dual DKC rack is 2 DKCs in a single rack2 DKCs are connected to create one high



Standard Features

performance system. Such a rack will include two FMD chassis

• A Twin DKC configuration consist of 2 single DKC racks where the DKCs are joined into one high performance DKC system (pictured above)

A maximum capacity XP7 configuration includes:

• 2 DKC racks with one DKC each, connected into a high performance DKC system and 2 media chassis per rack, and 4 DKU racks, each with 2 media chassis

A maximum performance XP7 FMD configuration includes:

- 2 DKC racks with one DKC each, connected into a high performance DKC system and 2 FMD chassis, OR
- 1 DKC rack with two DKC, connected into a high performance DKC system and 2 FMD chassis

Disk Controller Chassis -
DKCThe Disk Controller Chassis (DKC) includes one Cache Path Control Adapter (CPEX), one Multi-Processor
Blade Pair (MPB), one Service Processor (SVP), Cooling Fans and AC-DC Power Supplies.

One Backup Memory Kit (BKM) is required per CPEX. Batteries and cache flash memories are installed in the Cache Backup Module Kit (BKM) to prevent data loss by the occurrence of power outage or the like.

The options which can be added to a Disk Controller Chassis (DKC) consist of Channel Adapters (CHA), Disk Adapters (DKA), and Multi-Processor Blade Pairs (MPB). A network HUB or Option SVP is required in case additional option MPBs are located in the CHA/MBP location.

The storage system continues to operate when a single point of failure occurs. The addition, the replacement of the components and the upgrading of the microcode can be processed while the storage system is in operation.

The SVP implements a setting and a modification of the storage system configuration information, and observes the operational status. Connecting this SVP to HP C-Track enables the remote monitoring of the storage system. An Option SVP may be added to provide storage management and monitoring continuity in case of the main SVP fails and need to be replaced.



Standard Features

Drive Chassis / Media Chassis - DKU	Drive Chassis (DKU)			
	Three types of media chassis are available:			
	 SFF HDD/SSD Chassis for 2.5-inch media - Referred to as a SBX. LFF Drive Chassis for 3.5-inch drives - Referred to as an UBX. FMD Chassis for Flash Module Devices (FMD) - Referred to as a FBX. SBX: The SFF Drive Chassis is a chassis to install the SFF media, and consists of SSW boards and the AC-DC Power Supplies equipped with built-in cooling fans.			
	UBX : The LFF Drive Chassis is AC-DC Power Supplies equipp	a chassis to install the LFF disk drives, and consists of SSW boards and the ed with built-in cooling fans.		
	FBX : The FMD Chassis is a cha DC Power Supplies equipped v	issis to install Flash Module Devices, and consists of SSW boards and the AC- with built-in cooling fans.		
Channel Adapter Pairs - CHA	Channel Adapters (CHA) pairs (either directly connected to t External Storage devices and minimum of 1 CHA pair is requ depends on the number of DK • Max 4 CHA pair with 2 C • Max 5 CHA pair with 1 C • Max 6 CHA pair with 0 C	provide connections to host or servers that use the XP7 for data storage the servers or through SAN switches). CHA pairs also provide connections to to remote replication devices. CHAs are configured in pairs for redundancy. A uired. The maximum number of CHA pairs that can be installed in one DKC (As installed: DKA pairs installed DKA pair installed		
	The maximum number of allowed CHA pairs may be reduced depending on the number of additional MPBs.			
	CHA pairs and transceivers av	ailable for use in the XP7 include:		
	Fibre Channel	HP XP7 16-port 8Gbps Fibre Host Adapter		
	Fibre Channel	HP XP7 8-port 16Gbps Fibre Host Adapter		
	FICON SW	HP XP7 16p 8Gbps MF Shortwave Fibre CHA		
	FICON LW	HP XP7 16p 8Gbps MF Longwave Fibre CHA		
	LW	HP XP7 8Gbps Longwave SFP Transceiver		
	LW	HP XP7 16Gbps Longwave SFP Transceiver		
	SW	HP XP7 8Gbps Shortwave SFP Transceiver		
	The Fibre Channel CHA pair uses SFP (small form factor pluggable) Transceivers on each port of the CHA. Each port is configurable as short wave or long wave by installing the appropriate transceiver.			
Disk Adapter Sets - DKA	The Disk Adapter (DKA) performs all data movement between the drives and Cache Memory. The DKA also provides data protection using RAID 1, RAID 5, and RAID 6.			
	The XP7 may have zero DKA pairs (for an all External Storage configuration), and from one to up to four DKA pairs for internal storage media connection.			



Standard Features	
Encryption Ready Disk Adapter Sets - E-DKA	The XP7 encryption option requires the Encryption Ready Disk Adapters as well as an encryption software license. Data encryption occurs at the DKA device resulting in encrypted data at rest (DARE) on the drive/media.
	Please see the software section for information on the HP XP7 DKA Encryption Software LTU
Cache Memory	Cache Memory is used to temporarily store data from the host until it is written to drive storage, or to stage data requested by the host from a drive. The XP7 contains global mirrored cache. All write data is duplicated in both cache clusters. Cache control data (Shared Memory) and Cache data is also backed up to SSD for each Cache Memory Adapter in case of power outage (back up battery installed by default) or DKC power off.
	This insures that even if one cache board fails that the data is still in the other one until it is safely written to a drive. Read data is not mirrored as a copy of that data remains on the drives, allowing more of the total cache capacity available for data.
	XP7 Cache Memory can be configured into partitions allocated to particular host/port combinations to ensure that those hosts/ports enjoy optimized performance of cache-oriented I/O. These cache partitions are assigned to specified Array Groups. Up to 32 partitions of at least 4GB can be created in a XP7. Assigning cache in this way provides another method for tuning performance for data access for performance critical applications.
Media: HDD / SSD Drives and Flash Modules	The XP7 supports a variety of 2.5" small form-factor hard disk drives and solid state drives (SSDs), 3.5" large form-factor hard disk drives and XP Flash Modules. The number and type of media installed in a XP7 is flexible. Media must be added in minimum groups of four. Additional capacity can be installed over time as capacity needs grow. All XP7 media use the industry standard dual ported 6 Gbps SAS interface. Each media is connected to both blades of the redundant DKA pair by separate connections. Spare media are automatically used in the event of a media failure.
	SSDs have a limited number of writes that can occur before reaching the SSD's write endurance limit. The write endurance limit of enterprise MLC SSDs is generally high enough so wear out will not occur during the expected service life of an XP7 under the great majority of configurations, IO patterns, and workloads. The XP7 tracks all writes to e-MLC SSDs and can report the percent of the total write limit that has been used. This allows any SSD approaching the write limit to be proactively replaced before they are automatically spared out.
Flash Modules	The XP7 supports Flash Modules, which provide solid-state non-volatile high-performance data capacity. Flash Module capacity can be configured for use in the array in the same way as any other HDD or SSD. The number of Flash Modules that can be installed in a XP7 is flexible. Flash Modules must be added in groups of four or more. Additional capacity can be installed over time as capacity needs grow. Spare Flash Modules are automatically used in the event of a Flash Module failure.
	Up to two 48 slot Flash Module Chassis may be configured to each DKC. Flash Module Chassis use the industry standard dual ported 6 Gbps SAS interface. Each Flash Module Chassis is connected to both blades of the redundant DKA pair by separate connections.



Standard Features	
Service Processor	The Service Processor (SVP) manages the XP7 configuration, gathers statistical information, and is used for some maintenance activities.
	The XP7 Storage does not require a functioning SVP in order to make capacity available for reading and writing. However, as external management functions have become dependent on the availability of the SVP in the XP7, some customers may desire to have fast recovery from an SVP failure by having a standby SVP. If the primary SVP fails, the hot standby SVP is switched into operation automatically within approximately six minutes.
	The XP7 Continuous Track remote support functions require connection to HP Insight Remote Support via the internet.
Continuous Track Remote Support	The HP Continuous Track (C-Track) remote support solution uses internet connectivity to transmit heartbeats, system information messages (SIMs), and configuration information to the HP Storage Technology Centers (STCs) for remote data collection and remote monitoring purposes.
	C-Track also enables the STCs to remotely diagnose certain issues that may exist on the XP7. With HP's secure remote device access, HP support personnel have the enhanced ability, in many cases, to quickly fix a support issue entirely through remotely performed actions.
Server connectivity	The XP7 connects to a variety of servers and operating systems. For details on which servers and operating systems are currently supported, please contact your resellers and your HP technical support to review the supported server and operating system information.
Switch support details	The XP7 connects to the leading Fibre Channel and FCoE switches in the industry today. For detailed information on supported switch configurations, please contact your sales representative.
Application Solutions	The HP XP7 Storage is a member of the HP XP7 Storage family. The XP7 is ideal for customers running Oracle, Microsoft, SAP, and VMware environments that simply cannot afford any downtime or tolerate any data loss.
	The XP7 provides these mission critical application environments with a complete hardware/ software storage solution to decrease risks, lower costs, and accelerate business growth and agility. Data replication and tightly integrated clustering solutions, along with disaster recovery support, enable a multi-site disaster tolerant design to achieve business continuity in the most mission-critical environment.
	The XP7 is the premier enterprise-class storage solution for database environments that demand a mission critical solution to meet business and storage demands of Oracle, Microsoft, SAP, and VMware environments with technology that helps drive business success and mitigates risk with constant data availability.
	HP has developed an in-depth understanding of Oracle, Microsoft, SAP, and VMware technologies by extensive lab-testing best practices with the HP XP7 Storage, HP servers, and management software; high availability and disaster recovery solutions; and backup and recovery on the Oracle, Microsoft, and SAP application platforms. As a result, our customers can expect a wide range of operational and business benefits where they can:



HP XP7 Storage Family

QuickSpecs

Standard Features

- Maintain Hardware Redundancy. Every active component within an XP7 array is redundant, hotswappable, and can be upgraded online.
- Achieve Data Loss Protection to monitor the array around the clock for unseen issues, and investigate and resolve problems proactively and immediately.
- Increase utilization efficiency and reduce storage costs with XP7 Smart Tiers and XP7 Thin Provisioning.
- Increase return on investment with reduced cooling and power requirements along with increased reliability and storage density with HP Smart Tiers.
- Maximize performance and consistent low response times with XP7 ultra high performance configurations and XP7 Flash Modules
- Easily integrate to existing Oracle, Microsoft, SAP, and VMware environments with choice of FC, iSCSI, or SAS attached controllers.

To learn more about specific HP Storage Solutions that are built with Oracle, Microsoft, SAP, and VMware environments in mind, visit the solution sites supporting each of these applications. HP Storage for Oracle hyperlink to: http://www.hp.com/storage/oracle HP Storage for Microsoft hyperlink to: http://www.hp.com/storage/microsoft HP Storage for SAP hyperlink to: http://www.hp.com/storage/sap HP Storage for VMware hyperlink to: www.hp.com/go/vmware/storage



Technical Specifications

Each XP7 can be a custom with the requirements to o	configuration. For more information, please contact your reseller or authorized HP representative configure the product correctly.	to work
Rack	HP XP7 Storage Rack	H6F54A
	Each XP7 rack is suitable for DKC and DKU racks. The rack SKU includes a key kit.	
DKCs - Disk Controller	HP XP7 Primary DKC	H6F56A
Chassis	Includes: Disk Controller Chassis with 1 Multi-Processor Blade Pair (MPB), 1 CPEX, 1 SVP, Bezel and Rail Kit	
	HP XP7 Secondary DKC	H6F57A
	Includes: Disk Controller Chassis with 1 Multi-Processor Blade Pair (MPB), 1 CPEX, 1 internal HUB, Bezel and Rail Kit	
Media Chassis	HP XP7 2.5 inch Drive Chassis	H6F60A
SBX	192 slot SFF Drive Chassis with Bezels and Rail Kit	
UBX	HP XP7 3.5 inch Drive Chassis	H6F61A
	96 slot LFF Drive Chassis with Bezels and Rail Kit	
FBX	HP XP7 Flash Module Chassis	H6F62A
	48 slot Flash Module Chassis with Bezels and Rail Kit	
PDU -	HP XP7 Single Phase 60Hz PDU	H6F70A
Power Distribution Unit	Power Distribution Units with 4 power cords	
	HP XP7 Three Phase 60Hz PDU	H6F71A
	Power Distribution Units with 2 power cords	
	HP XP7 Single Phase 50Hz PDU	H6F72A
	Power Distribution Units with 4 power cords	
	HP XP7 Three Phase 50Hz PDU	H6F73A
	Power Distribution Units with 2 power cords	
Power Cords	HP XP7 60Hz DKC Power Cords	H6F80A
	PDU Controller Chassis interconnect power cord sets.	
	HP XP7 60Hz DKU Power Cords	H6F81A
	PDU Drive Chassis interconnect power cord sets.	
	HP XP7 60Hz Flash Module Power Cords	H6F82A
	Flash Module Chassis interconnect power cord sets.	
	HP XP7 50Hz DKC Power Cords	H6F83A
	PDU Controller Chassis interconnect power cord sets.	
	HP XP7 50Hz DKU Power Cords	H6F84A
	PDU Drive Chassis interconnect power cord sets.	



HP XP7 Storage Family

Technical Specificatio	ns	
	HP XP7 50Hz Flash Module Power Cords	H6F85A
	Flash Module Chassis interconnect power cord sets.	
	HP XP7 China DKC Power Cords	H6F86A
	PDU Controller Chassis interconnect power cord sets.	
	HP XP7 China DKU Power Cords	H6F87A
	PDU Drive Chassis interconnect power cord sets.	
	HP XP7 China Flash Module Power Cords	
	Flash Module Chassis interconnect power cord sets.	
SVP	HP XP7 Service Processor	H6F95A
	For redundant array management functions. Required if primary DKC has 3 or more MPB Pairs installed.	
Hub	HP XP7 Internal Hub	H6F97A
	Required if secondary DKC has 3 or more MPB Pairs installed.	
SSP	HP XP7 Storage	H6F99A
	The XP7 is a Structured Solution Product (SSP). This product number (H6F99A is a zero- price ordering mechanism that is used as an "umbrella" product to indicate to the ordering system that this is a new XP7 order	
DKC connecting kits	HP XP7 5M DKC Interconnect Kit	H6G00A
5, 30 and 100 meter kits to	Default to this kit when secondary controller is ordered	
connect primary and secondary controllers	HP XP7 30M DKC Interconnect Kit	H6G01A
secondary controllers.	Can be used instead of H6G00A.	
	HP XP7 100M DKC Interconnect Kit	H6G02A
	Can be used instead of H6G00A.	
DKC connecting cable kits	HP XP7 5M DKC Interconnect Cable	H6G03A
5, 30 and 100 meter kit to	Default to this kit when secondary controller is ordered	
the primary and secondary	HP XP7 30M DKC Interconnect Cable	H6G04A
controllers. If no additional	Can be used instead of H6G03A.	
CPEX are installed, these	HP XP7 100M DKC Interconnect Cable	H6G05A
are not needed.	Can be used instead of H6G03A.	
DKA	HP XP7 Disk Adapter	H6G06A
	Disk Adapter controls data transfer between the drives and cache memory.	
eDKA	HP XP7 Encryption Ready Disk Adapter	H6G07A
	Encryption is supported with this DKA and optional encryption software LTU.	



Technical Specifications

MPB -	HP XP7 Processor Blade	H6G08A
Multi-Processor Blade Pairs	Includes 1 Pair of XP7 Multi-Processor Blades, which include DIMMs, CPU and chip set and controls the CHA, DKA, PCI-Express interface, local memory and communication between the SVPs by Ethernet.	
Device Interface Cables	HP XP7 1M Cu Intra-chassis Dev Int Cable	H6G10A
	1 meter backend SAS Copper cables - will default for the intra-chassis connections	
	HP XP7 2M Cu Intra-rack Dev Int Cable	H6G11A
	2 meter backend SAS Copper cables - will default for the intra-rack connections (both DKA to Chassis, and Chassis to Chassis)	
	HP XP7 4M Cu Inter-rack Dev Int Cable	H6G12A
	4 meter backend SAS Copper cables - will default for the inter-rack connections (Chassis to Chassis)	
CPEX - Cache Path	HP XP7 Cache Path Controller Adapter	H6G20A
Controller Adapter	Consists of 2 boards to install the cache memory. Each board has 8 CM-DIMM slots. The CPEX connects between MPB, CHA, DKA and BKM by using PCI-Express path and distributes data and sends hot-line signals to the MPB.	
Cache Memory Module	HP XP7 16GB Cache Memory Pair	H6G21A
Pairs	Consists of two 16GB DIMMs	
	HP XP7 32GB Cache Memory Pair	H6G22A
	Consists of two 32GB DIMMs	
BKM - Cache Backup	HP XP7 Small Backup Memory Kit	H6G23A
Module Kits	For use with H6G25A	
	HP XP7 Large Backup Memory Kit	H6G24A
	For use with H6G26A	
Cache Backup Memory	HP XP7 128GB Backup Memory Pair	H6G25A
Pairs	Required for 256GB or less cache memory data backup.	
	HP XP7 256GB Backup Memory Pair	H6G26A
	Required for 512GB or less cache memory data backup.	
CHA - Channel Host	HP XP7 16-port 8Gbps Fibre Host Adapter	H6G30A
Adapters	1 Pair of 8 port 8Gbps Fibre Channel Host Adapters	
	HP XP7 8-port 16Gbps Fibre Host Adapter	H6G31A
	1 Pair of 4 port 16Gbps Fibre Channel Host Adapters	
	HP XP7 16p 8Gbps MF Shortwave Fibre CHA	H6G32A
	1 Pair of 8 port 8Gbps FICON Shortwave Fibre Host Adapters	



. • • ••

. . .

Model	HP XP7 Storage	
	HP XP7 3.2TB Flash Module Device	H6G71A
FMD	HP XP7 1.6TB Flash Module Device	H6G70A
	HP XP7 800GB SAS SFF (2.5-inch) Dual Port MLC Solid State Drive	H6G61A
SSD	HP XP7 400GB SAS SFF (2.5-inch) Dual Port MLC Solid State Drive	H6G60A
LFF HDD	HP XP7 4TB 6G SAS 7.2k rpm LFF (3.5 inch) Dual Port Hard Drive	H6G51A
	HP XP7 1.2TB 6G SAS 10K rpm SFF (2.5-inch) Dual Port Hard Drive	H6G43A
	HP XP7 900GB 6G SAS 10K rpm SFF (2.5-inch) Dual Port Hard Drive	H6G42A
	HP XP7 600GB 6G SAS 10K rpm SFF (2.5-inch) Dual Port Hard Drive	H6G41A
SFF HDD	HP XP7 300GB 6G SAS 15K rpm SFF (2.5-inch) Dual Port Hard Drive	H6G40A
	1 8Gbps Shortwave Transceiver for one port.	
	HP XP7 8Gbps Shortwave SFP Transceiver	H6G36A
	1 8Gbps Longwave Transceiver for one port.	
	HP XP7 16Gbps Longwave SFP Transceiver	H6G35A
	1 8Gbps Longwave Transceiver for one port.	
Transceivers	HP XP7 8Gbps Longwave SFP Transceiver	H6G34A
	1 Pair of 8 port 8Gbps FICON Longwave Fibre Host Adapters	
	HP XP7 16p 8Gbps MF Longwave Fibre CHA	H6G33A
rechnical Specif	ications	

HP XP7 Storage

Number of Disk Drives

0 -2304 slots in 1 to 6 racks (single DKC racks hold 2 media chassis and DKU racks hold 2 media chassis each)

Disk Drives

Drive Specifications	4TB 7.2K	600 GB 10K	900 GB 10K	1.2 TB 10K	300 GB 15K
Raw capacity (User area)	3916.14GB*	576.43 GB*	864.64 GB*	1152.79GB*	288.20 GB*
Rotation speed	7,200 rpm	10,000 rpm	10,000 rpm	10,000 rpm	15,000 rpm
Mean latency time	4.16 ms	2.99 ms	2.99 ms	3 ms	2.01 ms
Mean seek time (Read/Write)	7.8/8.5 ms	3.8/4.4 ms	3.7/4.1 ms	4.6/5.0 ms	2.9/3.3 ms
Internal data transfer rate	Up to 276 MB/sec	Up to 253.6 MB/sec	Up to 238.8 MB/sec	Up to 279 MB/sec	Up to 242 MB/sec
Interface type	Dual ported 6 Gbps SAS				



Technical Specifications

SSD / Flash Modules	Drive Specifications	400 GB (eMLC) SSD	800 GB (eMLC) SSD	1.6TB Flash Module	3.2 TB Flash Module
	Raw capacity (User area)	393.85 GB*	787.69 GB*	1759.2GB*	3518.4 GB*
	Interface type	Dual ported SAS	Dual ported SAS		
	* Based on industry standa on 1K = 1000, not 1024. Th	rd, the drive capacit is means that 1 GB =	y, and therefore the = 1,000,000,000 byte	raw data capacity o es, not (1024)3	f the XP7, is based
System Capacity	0 GB - 4.5 PB raw 0 GB - 3.9 PB usable				
RAID Levels	RAID 1 (2D + 2D) RAID 1 (4D + 4D) RAID 5 (3D + 1P) RAID 5 (7D + 1P) RAID 5 (14D + 2P) RAID 5 (28 D + 4P) RAID 6 (6D + 2P) RAID 6 (14D + 2P) Recomm	ended			
Maximum number of Logical Devices (LDEVs)	65,280				
Cache Memory	32 GB - 2 TB				
Operating Systems	HP-UX, HP NonStop, VMWa	ire, AIX, Linux, Windo	ows, Solaris, Mainfra	me, Open VMS	
Host Interface	Fibre Channel, FCoE, FICON				
Host Ports	8 to 96 16 Gbps FC ports 16 to 192 8 Gbps FC ports 16 to 176 FICON ports 8 to 88 FCoE ports				
Regulatory Approvals	This product meets all appl	licable safety and re	gulatory specificatio	ins	
Physical Dimensions -	Width x Depth x Height	24.1 x 43.8 x 79.0	in (61.0 x 111.2 x 20	0.6 cm)	
DKC Rack	Max Weight	1775 lbs. (807 kg)	for 1 DKC rack with 3	384 SFF drives	
	Max Weight	1852 lbs. (842 kg)	for 2 DKC single rack	with 96 FMD	
Physical Dimensions -	Width x Depth x Height	24.1 x 43.8 x 79.0	in (61.0 x 111.2 x 20	0.6 cm)	
DKU Rack	Max Weight	1393 lbs. (633 kg)	for 1 DKU rack with 3	384 SFF drives	
	Max Weight	1459 lbs. (663 kg)	for 1 DKU rack with [•]	192 LFF drives	
Shipping Dimensions DKC	Width x Depth x Height	37.4 x 50.8 x 86.9	in (95.0 X 129.0 X 22	0.5 cm)	
& DKU Racks	Max Weight of Packaging per Rack	166 lbs. (75 kilos)			



Technical Specifications

Environmental Specifications

Condition				
ltem	O perating ¹	Non-operation ²	Shipping & Storage ³	
Temperature (°C)	16 to 32	-10 to 43 -10 to 35 ¹⁰	-25 to 60	
Relative Humidity (%) ⁴	20 to 80	8 to 90	5 to 95	
Max. Wet Bulb (°C)	26	27	29	
Temperature Deviation (°C/hour)	10	10	20	
Vibration ⁵	5 to 10Hz: 0.25 mm 10 to 300Hz: 0.49m/s ²	5 to 10Hz: 2.5mm 10 to 70Hz: 4.9m/s ² 70 to 99Hz: 0.05mm 99 to 300Hz: 9.8m/s ²	6 Sine Vibration: 4.9m/s ² , 5min. At the resonant frequency with the highest displacement found between 3 to 100Hz 6 Random Vibration: 0.147m ² /s ³ , 30min, 5 to 100Hz	
Shock	-	78.4m/s², 15ms	8 Horizontal: Incline Impact 1.22m/s 9 Vertical: Rotational Edge 0.15m	
Altitude	-60 to	。 3,000m	-	

¹ The requirements for operating condition should be satisfied before the storage system is powered on. Maximum temperature of 32°C should be strictly satisfied at air inlet portion.

The recommended operational room temperature is 21°C to 24°C.

² Non-operating condition includes both packing and unpacking conditions unless otherwise specified.

³ For shipping and storage, the product should be packed with factory packing.

⁴ No condensation in and around the drives/media should be observed under any conditions.

⁵ The vibration specifications apply to all three axes.

⁶ See ASTM D999-01 The Methods for Vibration Testing of Shipping Containers.

⁷ See ASTM D4728-01 Test Method for Random Vibration Testing of Shipping Containers.

⁸ See ASTM D5277-92 Test Method for Performing Programmed Horizontal Impacts Using an Inclined Impact Tester.

⁹ See ASTM D6055-96 Test Methods for Mechanical Handling of Unitized Loads and Large Shipping Cases and

Crates.

¹⁰ When FMDs are installed.

Accessories	An extensive list of accessories is available for this product; for more information, please contact your HP sales representative

Safety

This product meets all applicable safety and regulatory specifications



Service and Support, HP Care Pack, and Warranty Information

Warranty	Warranty level of hardware reactive support is 3 years, 24×7, with 4-hour onsite response
	For more information about HP's Global Limited Warranty and Technical Support, visit: http://h18004.www1.hp.com/storage/warranty.html
Service and Support	Services to accelerate time to results HP Storage Services bring you a rich portfolio of consulting and support services designed to add value to our core storage products and solutions. We have the know-how and experience to put storage technology to work for you. We work closely with you as your strategic partner, leveraging our full services portfolio to make sure that everything works to optimize your enterprise.
	Choose from services aligned to our storage product offerings and lifecycle. From mission-critical onsite services to innovative web-based remote support, you choose the precise level of attention and support your business demands.
	What HP Storage Technology Services can do for you HP Storage Technology Services can help you design, deploy, test, integrate, support, and manage IT and infrastructure solutions. HP storage lifecycle support services offer a full spectrum of customer care-from technology support to complex migrations to complete managed services.
	Choose the right level of support, deployment and integration services HP support recommendations are designed to help you enhance technology operations and lower risk- and make it easier for you to seek the right balance between affordability and service-level commitments. Depending on your individual support needs, choose from three levels of care that cover the entire lifecycle to better address your needs-Optimized Care, Standard Care, and Basic Care. If none of our support recommendations meet your needs, we can tailor a service solution for your unique support requirements. Only HP brings together deep expertise, proactive and business critical support and a strong partner network-plus, a full set of infrastructure services designed to power a Converged Infrastructure.
Discover, plan, and design	Choose from a rich portfolio of services to make the most of HP XP7 Storage, so you can efficiently and affordably consolidate, manage, and extract value from unstructured data. Start here to understand your data protection options. Next, develop a methodical plan and design the optimal Storage that addresses your unique technology requirements.
	HP Storage Efficiency Analysis - HP Storage Efficiency Analysis (SEA) combine tool-based fact gathering and HP's expertise for a quick path to identify immediate issues and their resolution, and helps customer realize the benefits of HP Storage Technology. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-6727ENW.pdf
	HP Storage Impact Analysis - This service provides assessment service to analyze your current storage and evaluate the impact of change to the infrastructure. It is ideal for customers looking to achieving top utilization of your storage technology and assessing the likely impact of data growth and future projects that require storage.

http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA4-1174ENW.pdf

HP Storage Modernization service - Storage Modernization helps customers seamlessly position themselves to effectively integrate the latest technological advancements in storage. It helps clients modernize, reduce costs, and improve quality of service through the execution of process and technology



Service and Support, HP Care Pack, and Warranty Information

changes to achieve demand management. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-4620ENW.pdf

Deploy and integrate Implement HP XP7 Storage correctly-right from the start-so you can count on reduced risk and accelerated deployment, while implementing a best-practice configuration from day one.

HP XP Storage Installation and Startup Service - Installs, configures, and tests your HP XP7 hardware and software onsite. We deliver deployment of your XP7 storage properly integrated into your environment.

http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-4064ENW.pdf

HP Storage Data Migration Service - End-to-end data migration service providing seamless discovery, assessment, planning, and design, completely customizable to your organization's storage area network (SAN) or network attached storage (NAS) environment and using innovative software to help you migrate to HP storage quickly and efficiently. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-0774ENW.pdf

HP Enhanced Implementation Service for SANs - HP delivers complete design and implementation services for Fibre Channel, FCoE, FCIP, SAS, and iSCSI SAN connectivity components. http://h20195.www2.hp.com/V2/GetPDF.aspx/5981-8527EN.pdf

HP Data Replication Solution Service - Configuration of real-time data mirroring or snapshot capabilities of HP Business Copy and Continuous Access to safeguard your critical business information. http://h20195.www2.hp.com/V2/GetPDF.aspx/5982-4153EN.pdf http://h20195.www2.hp.com/V2/GetPDF.aspx/5982-4154EN.pdf

HP Storage Virtual Volume Design and Implementation Service - Activities your organization needs to design and implement a new LUN, virtual volume, or virtual disk (Vdisk) configuration. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-3764ENW.pdf

HP Proactive Select - A flexible way to purchase services to fit your environment with an extensive menu of HP Proactive Select event and technical services, such as onsite firmware upgrades, health checks, assessments, and education. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA2-3842ENW.pdf

Operate and supportHP Performance Analysis Service - Data collection, detailed input/output (I/O) analysis, and
enhancement recommendations to improve HP Storage disk array performance, stability, and availability
by identifying potential problems and understanding the possible solutions that will help avoid them.
http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA4-1669ENW.pdf

Optimized Care- delivers best performance and stability through deployment and proactive management practices

Choose the right support to maximize uptime, free up your resources, and achieve improved value-as you get the most out of the existing IT assets while accelerating time-to-revenue.

HP Critical Service - Provides proactive activities and 24x7 monitoring of your environment making it the right choice when uninterrupted uptime is essential. We implement improvement projects to mitigate risks and reduce incidents to maximize uptime. If outages do occur, they will be addressed immediately through access to our dedicated critical support escalation resources, with a six-hour call-to-repair commitment from our mission-critical call center. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA0-1613ENW.pdf



Service and Support, HP Care Pack, and Warranty Information

Standard Care -maintains high level of uptime, along with expert help to cut the cost and complexity of implementation and support	HP 6-hour Call-to-Repair Proactive Care Service with Personalized support option - Provides an integrated set of reactive and proactive services designed to help you improve the stability and performance of your converged infrastructure, including six-hour call-to-repair hardware support. The Personalized Support option provides onsite technical advice, HP best practice sharing and support reviews from an assigned account support manager. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-8855ENW.pdf
Basic Care -Minimum recommended support	HP 4-hour 24x7 Proactive Care Service with Personalized support option - Provides an integrated set of reactive and proactive services designed to help you improve the stability and performance of your converged infrastructure, including 4-hour onsite hardware support. The Personalized Support option provides onsite technical advice, HP best practice sharing and support reviews from an assigned account support manager. http://h20195.www2.hp.com/V2/GetPDF.aspx/4AA3-8855ENW.pdf
	designed to expand your skills and keep you up to speed with the latest storage and virtualization technology from HP Storage. http://education.hp.com/curr-storsan.htm
For more information	www.hp.com/services/storage To learn more on HP Storage Services, please contact your HP sales representative or HP Authorized Channel Partner
	HP Care Pack Services are sold by HP and HP Authorized Service Partners:

 Services for customers purchasing from HP or an enterprise reseller are quoted using HP order configuration tools.



Capacity-licensed XP7 Software

HP XP7 Software Products

The HP XP7 family offers a complete portfolio of software applications designed to help you confidently manage your XP7 Storage.

The software offerings can be grouped into several major categories as follows:

- Device and Configuration Management
- Performance Management
- High Availability and Replication
- Business Continuity Solutions
- Mainframe-connect Tools

For additional information regarding HP XP7 Software products, refer to the following:

- Trial licenses are available for most XP7 software products. Please contact your HP Sales Representative for details.
- For more information on XP7 Software, please refer to the HP XP7 Licensing compendium.

HP XP7 Array Manager Suite

Overview

HP XP7 Array Manager Suite consists of Array Manager software, Resource Partition software, External Storage Software and Thin Provisioning Software

Array Manager software provides web-based volume management, resource allocation, access control, and data security for your XP7 Storage. Configure and manage data volumes for most effective use of your XP7. Partition array resources to isolate applications, reserve cache memory for your most frequently accessed data, and control host port usage so that your most critical applications have the port bandwidth they need. Configure, manage, and secure all host access to the XP7 so that you have efficient access to your data. Create read-only volumes for archiving and data retention, and securely delete your data when necessary.

Thin Provisioning Software allows you to supply storage capacity to your applications from a pool of virtualized storage. By enabling you to allocate your anticipated future storage capacity needs from virtual storage, HP XP7 Thin Provisioning Software reduces the amount of physical drive capacity initially required. As utilization of physical drive space increases over time, you can purchase more drive capacity as it is needed, and install it without affecting your applications. By removing the guessing from capacity planning, HP XP7 Thin Provisioning reduces the cost of volume management.

Resource Partition allows role based access control of XP7 resources. It allows storage administrators to partition XP7 resources, at Physical and logical level and to assign these resources to sub-administrators while retaining overall control. Administrators can partition a XP7 Storage at a physical level (ports, hosts, LDEVs and Parity Groups) and dedicate part of their arrays for specific requirements. They can also partition at a logical level (Host Groups and LDEVs) and keep Ports, Parity Groups and External Storage as a shared infrastructure.

HP XP7 Resource Partition software is ideal for a multi-tenant environment set up where dedicated subadministrators need to manage the IT infrastructure needs of their respective business units. At the same time, it allows the datacenter administrator retain complete control of XP7 Storage resources. Datacenter administrators can decide to partition XP7 Storage resources either at a logical level to improve storage utilization efficiency or at a physical level to improve quality of service and avoid data and access breaches across multiple tenants.



HP XP7 External Storage allows you to host XP7 Storage LUNs on select external storage subsystems. XP7 External Storage allows you to tier storage capabilities and provision a XP7 solution to optimize return on IT investment - letting you focus high-performance/high availability native XP7 Storage capacity against your most mission-critical data while hosting less critical data on cost optimized external storage subsystems. Data stored on external devices connected behind a XP7 appear to a server to be stored inside the XP7.

XP7 External Storage provides significant consolidation scalability - up to 255 Petabytes (PB) of external storage can be configured behind a single XP7 Storage. Coupled with the significant cost advantages that external storage systems can provide, you can confidently scale your XP7 solution to simplify configuration complexity and reduce ongoing management cost. XP7 External Storage is compatible with a wide range of XP7 software tools, including XP7 Business Copy for local replication, XP7 Continuous Access for remote replication, and XP7 Auto LUN for performance optimization.

NOTE: HP XP7 Array Manager Suite is a required product for all XP7 Storage implementations, except Mainframe-only environments.

HP XP7 Array Manager Suite Base LTU	TK914AA
HP XP7 Array Manager Suite 1TB 0-100TB LTU	TK914AB
HP XP7 Array Manager Suite 1TB 101-250TB LTU	TK914AC
HP XP7 Array Manager Suite 1TB 251-500TB LTU	TK914AD
HP XP7 Array Manager Suite 1TB Over 500TB LTU	TK914AE

Product Highlights

Models

HP XP7 Array Manager provides several important capabilities. The following table lists the functions included in XP7 Array Manager.

Function Name	Supported Systems	Description
LUN Manager	Open Systems	Add paths, delete paths, set host mode, set/reset command device, configure ports, create LUNs and assign them to ports, configure port security, prevent IOSCAN by unauthorized servers from finding secure LUNs, and check every I/O for proper security.
Open Volume Manager	Open Systems	Create expanded volumes that are larger than standard volumes (also called LU Size Expansion or LUSE), and create custom size volumes that are smaller than standard volumes (also called Custom Volume Size or CVS).
Virtual LVI (VLVI)	Mainframe	Create custom size mainframe volumes that are smaller than standard volumes. Also called Custom Volume Size or CVS.
Data Retention Utility	Open Systems	LUN access control, enabling archiving and data retention. Protect key files from being updated, copied, accessed, or queried. Also known as LUN Security XP Extension.
Cache Residency Manager	Open Systems	Improve performance by reserving areas of Cache Memory for frequently accessed data. Also known as Cache LUN.
Cache Residency Manager for Mainframe	Mainframe	Improve performance by reserving areas of Cache Memory for frequently accessed data.
Volume Retention Manager for Mainframe	Mainframe	Volume access control, enabling archiving and data retention. Assign access permissions (read/write, read-only, and protect) to mainframe volumes.



Capacity-licensed XP7 Software

Performance Control	Open Systems	Allocate disk array port I/Os and transfer rate so that your most important applications have the performance they need. Also known as Server Priority Manager.
Performance Monitor	Both	Monitor usage, workload, and performance of drives, volumes, processors, and host interfaces in the XP7 Storage. View the information in graphical formats
Volume Shredder	Both	Securely delete data with repetitive overwrites to minimize the likelihood that it could be recovered. Overwrite up to eight times with random or user selected patterns. Also known as Data Shredder.
RAID Manager	Both	Host based command line interface that controls XP7 Continuous Access, XP7 Business Copy, and Data Retention Utility (LUN Security XP Extension).
Cache Partition	Both	Improve performance by reserving areas of cache to store frequently accessed data. Divide Cache into up to 32 partitions and configure dedicated Cache for critical applications to improve their performance.
XP7Info (Previously known as XPInfo)	Open Systems	Understand the mapping between device files on the server and their associated storage ports and LDEVs in the XP7 by using the XP7Info command line utility.

In summary, HP XP7 Array Manager Suite provides the following capabilities:

- Add or delete I/O paths
- Configure Host ports
- Create expanded LUNs
- Create custom size volumes (Mainframe and Open Systems)
- Establish volume host access permissions (Mainframe and Open Systems)
- Partition parity groups, cache, and host ports
- Control port bandwidth available to hosts
- Create read-only volumes for archiving and data retention (Mainframe and Open Systems)
- Reserve cache memory for frequently accessed data (Mainframe and Open Systems)
- Securely delete data (Mainframe and Open Systems) •
- Automate array configuration and management tasks using the bundled in XP7 Command View AE • CLI
- Interface with SRM software platforms using the bundled in XP7 Command View AE SMI-S provider •

Support Licensing

- See Service & Support section ٠ ٠
 - See Capacity-Licensed XP7 Software section
- For the XP7 Storage, license-to-use is based on the total internal and external usable capacity of . the array(NOTE: The licensed capacity must cover all internal and external usable capacity, XP7



HP XP7 Array Manager Conversion Suite

0	V	e	r	٧Ĭ	e	W	

HP XP7 Array Manager Conversion Suite is used to provide a upgrade path to customers for moving from mainframe only environment to a mixed environment comprising of both open and mainframe system.

For pure open system environment, HP XP7 Array Manager Suite is a mandatory title. Similarly, for pure mainframe environment, HP XP7 Mainframe Basic Suite is a mandatory title. XP7 Conversion Suite is required for customers moving from mainframe only to both mainframe and open system environment.

Models

HP XP7 Array Manager Conversion Suite is licensed by internal and external usable capacity	
HP XP7 Array Manager Conversion Suite Base LTU	TK934AA
HP XP7 Array Manager Conversion Suite 1TB 0-100TB LTU	TK934AB
HP XP7 Array Manager Conversion Suite 1TB 101-250TB LTU	TK934AC
HP XP7 Array Manager Conversion Suite 1TB 251-500TB LTU	TK934AD
HP XP7 Array Manager Conversion Suite 1TB Over 500TB LTU	TK934AE

Product Highlights

Function Name	Supported Systems	Description
LUN Manager	Open Systems	Add paths, delete paths, set host mode, set/reset command device, configure ports, create LUNs and assign them to ports, configure port security, prevent IOSCAN by unauthorized servers from finding secure LUNs, and check every I/O for proper security.
Data Retention Utility	Open Systems	LUN access control, enabling archiving and data retention. Protect key files from being updated, copied, accessed, or queried. Also known as LUN Security XP Extension.
Cache Residency Manager	Open Systems	Improve performance by reserving areas of Cache Memory for frequently accessed data. Also known as Cache LUN.
Performance Control	Open Systems	Allocate disk array port I/Os and transfer rate so that your most important applications have the performance they need. Also known as Server Priority Manager.
XP7Info (Previously known as XPInfo)	Open Systems	Understand the mapping between device files on the server and their associated storage ports and LDEVs in the XP7 by using the XP7Info command line utility.

Support

See Service & Support section

Licensing

- See Capacity-Licensed XP7 Software section
- " For the XP7 Storage, license-to-use is based on the total internal and external usable capacity of the array (NOTE: The licensed capacity must cover all internal and external usable capacity, XP7)

HP XP7 Command View Advanced Edition Suite

Overview

HP XP7 Command View Advanced Edition suite consists of HP XP7 Command View Advanced Edition Software and HP XP7 Replication Manager.

HP XP7 Command View Advanced Edition Software provides centralized, web-based management for XP7 Storage. It reduces total cost of ownership by enabling collaboration among team members and by increasing the efficiency of storage administrators. It can be used together with the Remote Web Console software shipped free with every HP XP7 Storage. In an environment with many HP XP7 Storage systems, with complex replication, or with a need to migrate data among tiers of storage, HP XP7 Command View AE



provides the device management capability you need. It allows you to manage multiple HP XP7 Storage systems from a central location. It provides the ability to install optional plug-in applications for enhanced functionality like visualizing complicated replication environments or non-disruptively migrating data between tiers of storage. HP XP7 Command View AE includes a Command Line Interface (CLI) to automate disk array configuration and management and includes an SMI-S provider to interface with SRM software.

XP7 Command View AE also includes the Provisioning Manager functionalities. Provisioning Manager was a separate product in the previous generation (XP) software portfolio. With XP7, Provisioning Manager product has been integrated with XP7 CVAE.

The CVAE CLI/SMI-S capabilities are conveniently included with the XP7 Storage Controller. There is also a native CLI/SMI-S included with the SVP for XP7 Storage. Refer to the Remote Web Console section for more details on the differences of the 2 CLI/SMI-S capabilities.

HP XP7 Replication Manager Software enables you to create, manage, and maintain HP XP7 Storage replication pairs. It provides centralized management of replication applications, decreases storage administration complexity, increases productivity, and improves service levels by providing a single enterprise view of the replication environment. It allows you to view replication status graphically in real time, improving your efficiency.

In addition to replication status, HP XP7 Replication Manager Software also provides early warning of impending problems. It eliminates tedious data entry that can cause outages and simplifies difficult replication tasks. In addition, it reduces costs and training expenses associated with replication management.

NOTE: HP XP7 Replication Manager only requires the CLI/SMI-S portion of XP7 Command View AE.

- Single visual point of management for all replication tasks
- Create, manage, and monitor Open Systems replication pairs, and monitor Mainframe replication pairs
- Makes managing replication easier for the Storage Administrator
- Manages and monitors local as well as remote replication pairs
- Reports pair status
- Displays the pair configurations relative to servers and subsystems
- Remote management of replication pairs

	Set up and control multi-site DR environments	
Models	HP XP7 Command View Advanced Edition Suite Base LTU	TK981AA
	HP XP7 Command View Advanced Edition Suite 1TB 0-100TB LTU	TK981AB
	HP XP7 Command View Advanced Edition Suite 1TB 101-250TB LTU	TK981AC
	HP XP7 Command View Advanced Edition Suite 1TB 251-500TB LTU	TK981AD
	HP XP7 Command View Advanced Edition Suite 1TB Over 500TB LTU	TK981AE
Product Highlights	 Includes Provisioning Manager functionalities. Wizard-based dialog modules for ease of use. Provides for seamless integration into higher-level infrastructure managements Storage Essentials. 	ent utilities such as

- Centralized, multi-array health and status management for XP7, XP24000, XP20000, XP12000, and XP10000 arrays
- Flexible Administrative Security configuration
- Supports Graphical User Interface (GUI), and Command Line Interface (CLI)
- Integration with enterprise framework applications such as OpenView, Tivoli, and BMC



Capacity-licensed XP7 Software

	 Easy access from GUI to Remote Web Console by selecting physical view
Support	See Service & Support section
Prerequisites	 XP7 Command View Advanced Edition Management Station (provided separately by customer). Please contact your HP Sales Representative for the latest details. Windows Server 2008/32-bit and x64; Windows Server 2008 R2/x64; Windows 7/32-bit and x64; Windows Server 2003 (SP1)/32-bit; Windows Server 2003 (SP2)/32-bit and x64; Windows XP Professional (SP2, SP3); Windows Vista/32-bit; Windows Vista (SP1)/32-bit; SuSE Linux 10/32-bit and x64; VMware, Hyper-V 1 GHz CPU minimum, 2 GHz CPU or faster is recommended 1 GB RAM minimum, 2 GB or greater is recommended A GB free drive space minimum, 5 GB or greater is recommended At least one Ethernet LAN card connected to network
Licensing	 For XP7 Storage: License-to-use is based on the total usable (internal+external) capacity of the XP7 being managed. As more LDEVs are configured in the array, additional licensing for XP7 Command View AE must also be purchased to cover the newly configured LDEVs. The HP XP7 Command View AE CLI SMI-S License is included with the XP7 Storage. It entitles you to use the SMI-S provider and the core command line interface (CLI) of HP XP7 Command View Advanced Edition Suite. The core CLI has all the capabilities of the full CLI except the logical group commands. For more information about CLI features, see the HP XP7 Command View Advanced Edition Suite Device Manager CLI user guide. To install the HP XP7 Command View AE CLI SMI-S License, first obtain a license key using the registration number from the HP XP7 Command View AE CLI SMI-S License Entitlement Certificate. Next, install HP XP7 Command View AE using the Server Installation DVD from the media kit. Then install the CLI SMI-S license key (previously obtained) using the License button in the HP XP7 Command View AE web client login window. For installation instructions, see the HP XP7 Command View Advanced Edition Suite server installation and configuration guide for Device Manager. To use all the features of HP XP7 Command View Advanced Edition Suite, purchase and install the HP XP7 Command View AE license.

Applications integrated with HP XP7 Command View AE

HP XP7 Tiered Storage Manager Software XP7 Command View AE Plug-in

Overview

HP XP7 Tiered Storage Manager is a plug-in application for XP7 Command View AE that transparently migrates XP7 data (including internal and externally connected) among storage tiers, seamlessly and without down time. It lets you take advantage of various storage tiers to better manage system cost and performance. XP7 Tiered Storage Manager includes the data migration functionality of XP7 Auto LUN.

When integrated with HP XP7 Performance Advisor, Tiered Storage Manager reports Array Group Busy Rates, allowing you to consider performance implications before migrating data.

NOTE: If you require automatic performance-based migration, purchase HP XP7 Auto LUN. HP XP7 Auto LUN includes data migration functionality and performance monitoring functionality. Only the data migration functionality of XP7 Auto LUN is included with HP XP7 Tiered Storage Manager.



Capacity-licensed XP7 Software

Models	HP XP7 Tiered Storage Manager Software Base LTU	TK985AA
	HP XP7 Tiered Storage Manager Software 1TB 0-100TB LTU	TK985AB
	HP XP7 Tiered Storage Manager Software 1TB 101-250TB LTU	TK985AC
	HP XP7 Tiered Storage Manager Software 1TB 251-500TB LTU	TK985AD
	HP XP7 Tiered Storage Manager Software 1TB Over 500TB LTU	TK985AE
Product Highlights	 Transparent migration - no need to disrupt or quiesce applications Non-disruptive to users Migrates data for both Internal or External Storage (MSA/EVA/XP7) Provide persistent volume classifications (Migration Groups) Provide easily customizable available storage pools (Storage Tiers) No limit to the number of Storage Tiers - Volumes can reside within multiple tiers Easy search operations for building Migration Groups and Storage Tiers Easy realignment to accommodate changes Migrations are batched together but are manually released Reports Array Group Busy Rates, when integrated with HP XP7 Performance Advisor. XP7 Performance Advisor v5.3 and XP7 Command View AE v7.3 provide the best combination and performance. 	of features
Support	See Services/Support section	
Prerequisites	 Software O HP XP7 Command View Advanced Edition Suite 	
Licensing	• For the XP7 Storage: The License-To-Use is based on the sum of the total internal usable the XP7 Storage plus the configured usable capacity of all External Storage LUNs attache XP7 Storage.	capacity of d to the

HP XP7 Remote Web Console

Overview	Remote Web Console is shipped free of charge with the array firmware on the SVP. It is accessible by customers and provides basic single XP7 Storage management. It can be easily accessed by the XP7 Command View AE GUI. If Remote Web Console is used as the only array device manager, it is accessed via a remote IP URL to the SVP. (See user manual for more details). Also note that the SVP shipped with XP7 Storage includes a native CLI/SMI-S provider.
	NOTE: There are 2 separate CLI/SMI-S providers shipped with XP7 Storage now - SVP CLI/SMI-S provider and CVAE CLI/SMI-S provider. The SVP CLI/SMI-S provider is included with the SVP. The CVAE CLI/SMI-S provider is shipped as a part of XP7 Storage Controller and is included on a separate CVAE media kit.
	CVAE SMI-S is what is referred to as a "proxy" SMI-S provider since it resides on a separate server that is not an integral part of the array. When the Array itself implements the SMI-S such as it is with is on the XP7 SVP, it is referred to as an "embedded" provider. The industry trend is toward embedded providers. In general they should provide better overall response times and do not suffer as much from synchronization issues as proxy providers. For example the CVAE SMI-S data, comes out of the CVAE database which as we know can have synchronization lags with the array.
Models	No product or license is required to be ordered, it comes free with the XP7 firmware on the SVP.
Licensing	No license key required, product is pre-enabled and comes free with every XP7 Storage.



HP XP7 Cache Partition

Overview	Improve performance by reserving areas of cache to store frequently accessed data. Divide Cache into up to 32 logical partitions and configure dedicated Cache for critical applications to improve their performance.
Models	Included with HP XP7 Array Manager - see section for more details
Product Highlights	Isolate applications by subdividing the XP P9000 Storage cache into smaller independent partitions
Support	See Service & Support section
Licensing	License-to-use for unlimited storage capacity on one XP7 Storage

HP XP7 DKA Encryption Software

Overview	XP7 DKA Encryption software enables the encryption capability for all the data that stored on the ir drives of the XP7 Storage. The Enhanced DKA encrypts the data on drives so that data cannot be re- drive that is removed from the XP7. Only data on the drives is encrypted (data in cache is not encrypt	iternal ad off a oted).
Models	HP XP7 DKA Encryption Software LTU	TK901A
Support	See Service & Support section	
Licensing	License-to-use for unlimited storage capacity on one XP7 Storage	

XP7 External Storage

Overview	HP XP7 External Storage allows you to host XP7 Storage LUNs on select external storage subsystems. XP7 External Storage allows you to tier storage capabilities and provision a XP7 solution to optimize return on IT investment - letting you focus high-performance/high availability native XP7 Storage capacity against your most mission-critical data while hosting less critical data on cost optimized external storage subsystems. Data stored on external devices connected behind a XP7 appear to a server to be stored inside the XP7.
	XP7 External Storage provides significant consolidation scalability - up to 255 Petabytes (PB) of external storage can be configured behind a single XP7 Storage. Coupled with the significant cost advantages that external storage systems can provide, you can confidently scale your XP7 solution to simplify configuration complexity and reduce ongoing management cost. XP7 External Storage is compatible with a wide range of XP7 software tools, including XP7 Business Copy for local replication, XP7 Continuous Access for remote replication, and XP7 Auto LUN for performance optimization.
	Note that the XP7 External Storage does not have a separate license. It is included in XP7 Array Manager Suite
Licensing	Included in XP7 Array Manager Suite.



HP XP7 Resource Partition Software

Externa HP XP7 adminis time, it adminis utilizati	Resource Partition software is ideal for a multi-tenant environment set up where dedicated sub- strators need to manage the IT infrastructure needs of their respective business units. At the same allows the datacenter administrator retain complete control of XP7 Storage resources. Datacenter strators can decide to partition XP7 Storage resources either at a logical level to improve storage ion efficiency or at a physical level to improve quality of service and avoid data and access breaches
across i	multiple tenants.
models include	u in HP XP7 Array Manager Suite
Product Highlights • A r • L F • N E c c • C t	Assign role based access controls to sub-administrators to modularize IT infrastructure nanagement, even with a central IT infrastructure resource pool. Jseful for cloud service providers and for organizations with consolidated IT infrastructure, providing a platform to multiple tenants to host storage and charging as per usage. Maximize XP7 Storage resource utilization with shared resources such as Ports, Parity Groups and External Storage, and dedicated resources such as host groups and LDEVs, with logical partitioning of XP7 Storage. Create resource groups based on the needs of your customers or business units, helping to ensure that quality of service and data secrecy requirements are met with hardware based partitioning.
Licensing • I	ncluded in XP7 Array Manager Suite.

HP XP7 RAID Manager

Overview	HP XP7 RAID Manager provides OS-specific, host based software initiated from a server via a command line interface that allows full user control of HP XP7 Continuous Access and HP XP7 Business Copy from the host server. XP7 RAID Manager also provides functionality for synchronized operation with cache and OS, etc. If launching from a host using scripts, a consulting engagement may be recommended. XP7 RAID Manager also provides host agent/command support for HP Data Retention Utility (LUN Security XP Extension) based solutions (see Data Retention Utility for more information).
Models	Included with XP7 Array Manager
Product Highlights	Host-resident integration of XP7 Software
Support	See Service & Support section
Licensing	NA: product provided at no charge



HP XP7 Cache LUN (also known as Cache Residency)

Overview	HP XP7 Cache LUN lets you reserve areas of memory cache on your HP XP7 Storage to store frequently accessed information. It improves file access times and enables faster data transfers. Assigning information to on-board cache speeds up access to your data because cache-resident data is available at host data transfer speeds for both read and write operations. XP7 Cache LUN redirects I/O requests from the XP7 drives to data locked in the array's cache. It is transparent, it is simple to implement, and the performance gains it delivers are immediate.		
Models	Included with HP XP7 Array Manager - see section for more information		
Product Highlights	 XP7 Storage Firmware based Lock data in cache memory Flexible user configuration Scalable 		
Support	See Service & Support section		
Licensing	See Capacity-Licensed XP7 Software section		

HP XP7 Performance Control

performances they need to meet business objectives. You can also ensure that business processes (like backups and data warehouse loads) get the array bandwidth they need to comple targeted time windows. XP7 Performance Control enables sophisticated service provider solutio on performance level quality-of-service. Because it ensures that array resources are best used, i improves ROI of your XP disk array solution.	te within ns based t
ModelsHP XP7 StorageIncluded with HP XP7 Array Manager - see section for more information.	
 Product Highlights Set Upper Limit function to cap performance on non-priority hosts Set Threshold Value function to relax policies when priority host performance consumption Set WWN and Port level settings Determine IOPS or MB/s settings for random or sequential I/O-oriented processing worklow Define Host Bus Adapter names to allow intuitive naming of hosts Define Host Bus Adapter group names to allow intuitive naming of hosts 	n is low ads
Support • See Service & Support section	
• License-to-use for unlimited storage capacity on one XP Disk Array	



HP XP7 Data Shredder (also known as Volume Shredder)

Overview	HP XP7 Data Shredder is a software product designed for the enterprise storage market and is supported on the XP7. It helps IT staff by securely deleting data on the XP7 Storage via successive overwrites to minimize the likelihood that the deleted data could be restored. This may help to promote peace of mind and improved data security for high security environments that use the XP7. It will be most useful for sensitive financial data or high security data in a variety of industries.	
Models	Included with HP XP7 Array Manager Suite - see section for more information.	
Product Highlights	 Overwrites data volumes up to 8 times User selectable overwrite patterns Ease of use Verification that overwrites have been completed Percentage of completion display Abort feature to stop the process 	
Support	See Service & Support section	
Licensing	License-to-use for unlimited storage capacity on one XP7 Storage	

HP XP7 Smart Tiers Software

Overview	HP XP7 Smart Tiers improves storage performance and controls costs by transparent appropriate tiers of storage within the HP XP7 Storage. Smart Tiers manages data in pools. It monitors performance at the page level and can migrate data online to a diff automatically or manually, based on policies. Smart Tiers supports up to three tiers p supports external storage, which allows users to setup inexpensive external storage tiers for infrequently accessed data. RAID 1, RAID 5 and RAID 6 are supported	ly migrating data to thin provisioning erent tier, er pool. Smart Tiers as one of the storage
Models	HP XP7 Smart Tiers Software Base LTU	TK916AA
	HP XP7 Smart Tiers Software 1TB 0-100TB LTU	TK916AB
	HP XP7 Smart Tiers Software 1TB 101-250TB LTU	TK916AC
	HP XP7 Smart Tiers Software 1TB 251-500TB LTU	TK916AD
	HP XP7 Smart Tiers Software 1TB Over 500TB LTU	TK916AE
Product Highlights	 HP XP7 Smart Tiers Software 11B Over 5001B LTU TK916A Improve Performance Frequently accessed data is always in the fastest tier. Highly utilized Thin Provisioning pages are relocated to the fastest drives in the pool. Tier relocation is performed periodically, either automatically or manually based on performance monitoring algorithm. Optimize resource utilization Expensive fast tiers of storage are always holding the most frequently accessed data only Pages are allocated to upper tiers as long as the performance potential of each tier (group o pool volumes) is not exceeded. Enhanced tiering policy for migrating pages between tiers for better resource utilization Drive coexistence in a Tier. Supports multiple tiers for external storage Reduce management cost Set data migration policies for continued enhanced performance, saving on management time to keep the XP7 at its optimal performance. Option setting enables detailed setting of Tier Management, Cycle Time, and Monitoring Period. 	
Support	 See Service & Support section 	



Capacity-licensed XP7 Software

Prerequisites

- XP7 Smart Tiers works with Thin Provisioning pages, XP7 Thin Provisioning is already bundled with Array Manager Suite.
- Licensing

• License to use is based on the total capacity of the thin provisioning pool managed by Smart Tiers

HP XP7 Auto LUN Software

Overview	HP XP7 Auto LUN Software provides web-based automatic or manual monitoring and load balancing for all your XP7 Storage. Now you can make the most of your arrays by moving high-priority tasks to underutilized volumes, replicating volumes for backup and recovery, and viewing the health of your arrays. You set performance goals, you set the limits, and XP7 Auto LUN does the rest. It proposes a migration plan and even estimates how much your storage performance will improve when it is done. XP7 Auto LUN lets you evaluate array usage and determine whether resources are overloaded or out of balance. Use its easy-to-follow menus to define when data is collected and arrays are monitored. It makes spotting trends simple, using up to 90 days of stored historical data to create up-to-the-minute reports. You can even export data to third-party analysis tools like Microsoft Excel. If resources are overloaded, XP7 Auto LUN will create a plan to move volumes, then stands by for your approval to make changes.	
Models	HP XP7 Auto LUN Software Base LTU HP XP7 Auto LUN Software 1TB 0-100TB LTU HP XP7 Auto LUN Software 1TB 101-250TB LTU HP XP7 Auto LUN Software 1TB 251-500TB LTU HP XP7 Auto LUN Software 1TB Over 500TB LTU	TK915AA TK915AB TK915AC TK915AD TK915AE
Product Highlights	 Identifies data volumes stressed by high I/O workloads Moves high priority data to underutilized array volumes Creates a volume migration plan Migrates data across different drives or RAID levels Virtually assures successful volume migration with "Never Give Up" mode option 	
Support	See Service & Support section	
Licensing	• See Capacity-Licensed XP7 Software section, Licensed by total usable capacity (interview)	ernal + external).

HP XP7 Performance Advisor Software

Overview	HP XP7 Performance Advisor Software is a web-based application for collecting, monitoring displaying the performance of your XP7 Storage. With XP7 Performance Advisor, you choose duration of performance data collection-so you can pinpoint activities that significantly affer and tune the array accordingly. You can easily monitor storage performance and display us for your storage system at any level, from a complete system overview down to individual. You can also filter hosts, arrays, and array components, so you are only seeing the hosts ar want to see. You can also generate, schedule and view detailed performance reports that widentify any performance bottlenecks in your XP7 Storage. Performance Advisor integrates with HP XP7 Tiered Storage Manager, providing Array Grou data. This allows Tiered Storage Manager to monitor access patterns so that you can conside performance implications before migrating data.	g, and se the time and ect your XP7 age statistics components. nd arrays you ill allow you to p performance der
Models	HP XP7 Performance Advisor Software Base LTU	TK990AA
	HP XP7 Performance Advisor Software 1TB 0-100TB LTU	TK990AB
	HP XP7 Performance Advisor Software 1TB 101-250TB LTU	TK990AC
	HP XP7 Performance Advisor Software 1TB 251-500TB LTU	TK990AD



Capacity-licensed XP7 Software

	HP XP7 Performance Advisor Software 1TB Over 500TB LTU	TK990AE
	NOTE: The HP XP7 Performance Advisor Base License includes the media kit.	
Product Highlights	 Real time data gathering and analysis System view of all array resources Dashboard for quick review of XP7 performance status Macro view of applications to quickly isolate and troubleshoot performance problems Graphical presentation of array component metrics in form of charts Enhanced troubleshooting Metrics for other products running on XP array like Thin Provisioning , Smart Tiers, CA Detailed performance report generation and scheduling Flexible event notification and large 320 GB historical repository Multi-OS support Multiple management stations support Coexistence of Windows-based host agent and Windows-based management station on server (not recommended for large configurations) XP7 Storage External Storage performance monitoring Integrates with HP XP7 Tiered Storage Manager (Requires Performance Advisor and HP X Command View AE. Performance Advisor and Command View AE provide the best combin features and performance.) 	the same P7 ation of
Support	See Service & Support section	
Prerequisites	 Management Station for standalone deployment (provided separately by customer) Management Server on its own management station Supports single core, dual-core, and quad-core processors 3-GHz CPU, 4-GHz CPU (recommended for large configurations > 2GB database) 2 GB RAM (minimum), 4 GB RAM (recommended for large configurations > 2GB database) 10 GB free drive space (minimum), 320GB free drive space (for maximum history d NTFS DVD drive VGA monitor with 256 colors or better At least one LAN Card Host Agent: refer to the HP XP7 Performance Advisor Installation Guide Minimum Array Firmware - refer to the release notes associated with the particular verse Performance Advisor 	abase) etail) ion of
Licensing	 For XP7 Storage, License-to-use is based on total installed usable(internal + external) ca Capacity-Licensed XP7 Software section for more details. 	pacity. See

Mainframe Environment

HP XP7 Mainframe Basic Suite

Overview

HP XP7 Mainframe Basic Suite consist of mainframe related software features, thin provisioning software, resource partition software and external storage software

Basic mainframe software features provides web-based volume management, resource allocation, access control, and data security for your XP7 Storage. Configure and manage data volumes for most effective use of your XP7. Partition array resources to isolate applications, reserve cache memory for your most frequently accessed data, and control host port usage so that your most critical applications have the port bandwidth they need. Configure, manage, and secure all host access to the XP7 so that you have efficient



access to your data. Create read-only volumes for archiving and data retention, and securely delete your data when necessary.

Thin Provisioning Software allows you to supply storage capacity to your applications from a pool of virtualized storage. By enabling you to allocate your anticipated future storage capacity needs from virtual storage, HP XP7 Thin Provisioning Software reduces the amount of physical drive capacity initially required. As utilization of physical drive space increases over time, you can purchase more drive capacity as it is needed, and install it without affecting your applications. By removing the guessing from capacity planning, HP XP7 Thin Provisioning reduces the cost of volume management.

Resource Partition allows role based access control of XP7 resources. It allows storage administrators to partition XP7 resources, at Physical and logical level and to assign these resources to sub-administrators while retaining overall control. Administrators can partition a XP7 Storage at a physical level (ports, hosts, LDEVs and Parity Groups) and dedicate part of their arrays for specific requirements. They can also partition at a logical level (Host Groups and LDEVs) and keep Ports, Parity Groups and External Storage as a shared infrastructure.

HP XP7 Resource Partition software is ideal for a multi-tenant environment set up where dedicated subadministrators need to manage the IT infrastructure needs of their respective business units. At the same time, it allows the datacenter administrator retain complete control of XP7 Storage resources. Datacenter administrators can decide to partition XP7 Storage resources either at a logical level to improve storage utilization efficiency or at a physical level to improve quality of service and avoid data and access breaches across multiple tenants

HP XP7 External Storage allows you to host XP7 Storage LUNs on select external storage subsystems. XP7 External Storage allows you to tier storage capabilities and provision a XP7 solution to optimize return on IT investment - letting you focus high-performance/high availability native XP7 Storage capacity against your most mission-critical data while hosting less critical data on cost optimized external storage subsystems. Data stored on external devices connected behind a XP7 appear to a server to be stored inside the XP7.

XP7 External Storage provides significant consolidation scalability - up to 255 Petabytes (PB) of external storage can be configured behind a single XP7 Storage. Coupled with the significant cost advantages that external storage systems can provide, you can confidently scale your XP7 solution to simplify configuration complexity and reduce ongoing management cost. XP7 External Storage is compatible with a wide range of XP7 software tools, including XP7 Business Copy for local replication, XP7 Continuous Access for remote replication, and XP7 Auto LUN for performance optimization.

NOTE: HP XP7 Mainframe Basic Suite is a required product for all XP7 Storage Maiframe implementations

HP XP7 Mainframe Basic Suite Base LTU	TK924AA
HP XP7 Mainframe Basic Suite 1TB 0-100TB LTU	TK924AB
HP XP7 Mainframe Basic Suite 1TB 101-250TB LTU	TK924AC
HP XP7 Mainframe Basic Suite 1TB 251-500TB LTU	TK924AD
HP XP7 Mainframe Basic Suite 1TB Over 500TB LTU	TK924AE



Models

Capacity-licensed XP7 Software

Product	Highlights
---------	------------

Function Name	Supported Systems	Description
Volume Manager	Mainframe	Create volumes of specific sizes desired as well as provision volumes using regular or thin provisioning. Volume Manager allows you to change the volume configuration in the array to address changing requirements.
Cache Residency Manager for Mainframe	Mainframe	Improve performance by reserving areas of Cache Memory for frequently accessed data.
Volume Retention Manager for Mainframe	Mainframe	Volume access control, enabling archiving and data retention. Assign access permissions (read/write, read-only, and protect) to mainframe volumes.
Performance Monitor	Both	Monitor usage, workload, and performance of drives, volumes, processors, and host interfaces in the XP7 Storage. View the information in graphical formats
Cache Partition	Both	Improve performance by reserving areas of cache to store frequently accessed data. Divide Cache into up to 32 partitions and configure dedicated Cache for critical applications to improve their performance.
Volume Shredder	Both	Securely delete data with repetitive overwrites to minimize the likelihood that it could be recovered. Overwrite up to eight times with random or user selected patterns. Also known as Data Shredder.
Volume Security for Mainframe	Mainframe	Volume security for mainframe attached XP Disk Arrays that protects volumes from access by unauthorized hosts.

Support

Licensing

See Service & Support section

Mainframe Basic Suite is licensed by total usable capacity(internal + external)

HP XP7 Mainframe Performance Suite

Overview

HP XP7 Mainframe Performance Suite consist of Compatible PAV, Compatible Hyper PAV and High Performance FICON software.

Compatible PAV Enables high performance concurrent access of mainframe volumes by permitting a mainframe host system to issue multiple I/O requests in parallel to individual logical devices within the XP7 Storage. Compatible PAV also enables the use of the multiple allegiance feature in z/OS when using multiple physical mainframes to access the same volumes in a single array. Compatible PAV provides static or dynamic PAV functionality

Compatible Hyper PAV greatly reduces the number of PAV aliases needed per logical subsystem while maintaining response times. PAV aliases are only bound to PAV bases for the duration of a single I/O operation, thus reducing the number of aliases needed.

High Performance FICON for system z or zHPF is an enhancement of the FICON channel architecture; which also means compatibility with certain standards such as Fibre Channel Physical and Signaling standard (FC-FS), Fibre Channel Switch Fabric and Switch Control Requirements (FC-SW), and Fibre Channel Single-Byte-4 (FC-SB-4) standards. Enhancements have been made to the z/Architecture[®] and the FICON interface architecture to deliver improvements for online transaction processing (OLTP) workloads. zHPF is implemented exclusively in System z10. When High Performance FICON is exploited by the FICON



	channel, the z/OS operating system, and the control unit; the FICON channel ov is achieved by simplification of the protocol, and by reducing the number of inf resulting in more efficient use of the fibre link	erhead will be reduced. This ormation units processed,
Models	HP XP7 Mainframe Performance Suite Base LTU	TK944AA
	HP XP7 Mainframe Performance Suite 1TB 0-100TB LTU	TK944AB
	HP XP7 Mainframe Performance Suite 1TB 101-250TB LTU	TK944AC
	HP XP7 Mainframe Performance Suite 1TB 251-500TB LTU	TK944AD
	HP XP7 Mainframe Performance Suite 1TB Over 500TB LTU	TK944AE
Support	See Service & Support section	
Licensing	Mainframe Performance Suite is licensed by used capacity	

HP XP7 Mainframe Tiering Suite

Overview	HP XP7 Mainframe Tiering Suite consists of Smart Tiers software and Smart Ma	anager for MF software
	HP XP7 Smart Tiers software improves storage performance and controls cost migrating data to appropriate tiers of storage within the HP XP7 Storage. Sma provisioning pools. It monitors performance at the page level and can migrate different tier, automatically or manually, based on policies. Smart Tiers suppo Smart Tiers supports external storage, which allows users to setup inexpensiv the storage tiers for infrequently accessed data. RAID 1, RAID 5 and RAID 6 are	ts by transparently rt Tiers manages data in thin the data online to a rts up to three tiers per pool. re external storage as one of supported.
	HP XP7 Smart Manager for Mainframe software provides centralized managen in a mainframe environment. It works together with Smart Tiers to help mainfr easily manage the location of volumes by tier. It allows mainframe storage ad transparently manage the location of volumes in a Smart Tiers pool such that s satisfied. With Smart Manager for Mainframe your storage resources can be fu efficiently utilized.	nent of Smart Tiers volumes rame users conveniently and ministrators to SLA requirements can be ırther optimized and
Models	HP XP7 Mainframe Tiering Suite Base LTU	TK926AA
	HP XP7 Mainframe Tiering Suite 1TB 0-100TB LTU	TK926AB
	HP XP7 Mainframe Tiering Suite 1TB 101-250TB LTU	TK926AC
	HP XP7 Mainframe Tiering Suite 1TB 251-500TB LTU	TK926AD
	HP XP7 Mainframe Tiering Suite 1TB Over 500TB LTU	TK926AE
Support	See Service & Support section	
Prerequisite	Thin Provisioning is a requirement for Mainframe Tiering bundle	
Licensing	 Mainframe Tiering Suite is licensed by used capacity 	



HP XP7 Business Copy Software

Overview	HP XP7 Business Copy makes nearly instantaneous copies of data from XP7 Storage for development testing or backup, without ever interrupting your online production. XP7 Business Copy creates and maintains RAID-protected copy volumes without interrupting access to the source volumes. Becaus makes asynchronous copy volume updates, copies stay up to date with minimal I/O response time degradations for your primary applications. These copy volumes can at any time be "split" from the corresponding source volume and accessed by other applications. Therefore, while copy volumes a being utilized, primary applications can continue to access and update their source volumes as neer without taking a performance hit. By creating multiple online copies of critical business data without disrupting your business, XP7 Business Copy lets you get the most from your data. Fast Snap is a feature of Business Copy that also replicates data volumes. However, it is slightly diff in that it makes space-efficient secondary copies that might only be a fraction of the size of the print copy. Only data that is about to be overwritten in the primary volume is written to the secondary vor This is called Copy-after-Write. As a result, if the volume capacity required for Snapshot XP7 can be smaller, then the cost of replication can be lowered. Fast Snap is recommended for application environments where the I/O to the secondary volume is not write-centric or intensive (reads or write These secondary copies are also known as "virtual volumes", or V-VOL. All V-VOLs reside in a snaps pool, or POOL-VOL, which is sized based on the number of V-VOLs and the IO ratio of the primary vol associated with these V-VOLs.	ent, I Se it Se it Pre ded, It ferent mary Solume. Ses).
Models	HP XP7 Business Copy Software Base LTU T	K913AA
	HP XP7 Business Copy Software 1TB 0-100TB LTU T	K913AB
	HP XP7 Business Copy Software 1TB 101-250TB LTU T	K913AC
	HP XP7 Business Copy Software 1TB 251-500TB LTU T	K913AD
	HP XP7 Business Copy Software 1TB Over 500TB LTU T	K913AE
Product Highlights	 Real time local data mirroring Enables a wide range of data protection and recovery solutions Instant access to copied volumes New Fast Snap Copy-After-Write (CAW) Snapshots significantly improve P-VOL response tim compared to legacy COW (Copy On Write) Snapshots Support for up to 1024 Snapshots per P-VOL with Fast Snap Host Agent integration using XP7 RAID Manager Includes licenses for Business Copy for Mainframe, providing local replication for mainframe types 	es volume
Support	See Service & Support section	
Prerequisite	 Software XP7 RAID Manager (required for host agent integration). RAID Manager is included in X Array Manager. Business Continuity Manager is required for z/OS host management of Business Copy Mainframe XP7 Thin Provisioning required for Fast Snap. XP7 Thin Provisioning is included in XP7 Manager Suite 	:P7 for Array
Licensing	 See Capacity-Licensed XP7 Software section. Licensing is based on the sum of all P-VOLs, S- (full copies) and POOL-VOL (Snapshot copies) 	VOLs



HP XP7 Continuous Access Suite

Overview	 The HP XP7 Continuous Access family of high availability data and disaster recovery too data mirroring between XP7 Storage. They provide continuous availability for all your im protect you from catastrophic failures. XP7 Continuous Access products deliver host-incosed remote recovery for a wide range of open systems environments. XP7 Continuous high-performance remote mirroring in high-workload environments. Using shared mirror connect interfaces, you will better utilize your array resources. In addition, with seamles a full spectrum of remote mirroring-based solutions, XP7 Continuous Access can be depranging from data migration to high-availability server clustering. HP XP7 Continuous Access Suite includes HP XP7 Continuous Access Synchronous and H Access JournalXP7 Continuous Access Synchronous, the base product, provides replicati synchronous link between XP7 Storage. XP7 Continuous Access can be used to copy da Storage and between XP7 Disk Arrays of different generations. For up to date information Continuous Access compatibility between XP7/XP Disk Array generations, please contact representative. 	ls enable real-time portant data and lependent, array- s Access provides bring and host- is integration into loyed for activities P XP7 Continuous on using a tion using an ta between XP7 n on XP7 t your HP
Models	XP7 Storage Continuous Access Synchronous LTUs	
	HP XP7 Continuous Access Suite Base LTU	TK911AA
	HP XP7 Continuous Access Suite 1TB 0-100TB LTU	TK911AB
	HP XP7 Continuous Access Suite 1TB 101-250TB LTU	TK911AC
	HP XP7 Continuous Access Suite 1TB 251-500TB LTU	TK911AD
	HP XP7 Continuous Access Suite 1TB Over 500TB LTU	TK911AE
Product Highlights	 Remote data mirroring between XP7/XP Disk Arrays Enables a wide range of remote mirroring solutions XP7 Continuous Access Synchronous: Synchronous copy mode XP7 Continuous Access Journal: Asynchronous copy mode Fast failover/failback for seamless, reliable mirroring recovery Provides data consistency for Open/Mainframe VOLs in a Multi-DKC 3 Data center configuration Supports 3DC Continuous Access Journal x Continuous Access Journal configurati Host Agent integration using XP7 RAID Manager XP7 Continuous Access Sync includes licenses for Continuous Access Synchronou providing synchronous remote replication for mainframe volume types XP7 Continuous Access Journal includes licenses for Continuous Access Synchron Continuous Access Journal for Mainframe, and Cont Access Journal 3DC & 4x4 for providing asynchronous journal-based remote replication for mainframe volume BCM is required for z/OS host management of CA Journal for MF, 3DC and Journal 	multi-target on s for Mainframe, ous for Mainframe, Mainframe, types 4*4 for Mainframe
Support	See Service & Support section	
Prerequisite	 Thin Provisioning is a requirement for Continuous Access Journal(Open and MF) for volumes 	or Journal
Licensing	See Capacity-Licensed XP7 Software section	



HP XP7 Dynamic Link Manager Advanced

Overview	HP XP7 DLM Advanced for VMware, HP XP7 DLM Advanced for IBM AIX, HP XP7 DLM Adva Solaris, HP XP7 DLM Advanced for Windows, and HP XP7 DLM Advanced for Linux are ser software tools that provide I/O path failover and load balancing for your XP7s. They offe to improve performance, while the software's automatic error detection features provide infrastructure to avert data stoppages or catastrophic halts. It automatically routes I/Os path, and administrators see and manage all I/O activity via an easy-to-use graphical intrusers users see only reliable system performance.	nced for Sun ver-based er load balancing e a fault-tolerant to an alternate erface - while
Models	Hitachi HDLM Media Kit	HIT5208A
	HP XP7 Dynamic Link Manager Advanced for Windows LTU	TK918A
	HP XP7 Dynamic Link Manager Advanced for Linux LTU	TK919A
	HP XP7 Dynamic Link Manager Advanced for AIX 1 Server LTU	TK921A
	HP XP7 Dynamic Link Manager Advanced for AIX Unlimited Server LTU	TK922A
	HP XP7 Dynamic Link Manager Advanced for Solaris 1 Server LTU	TK923A
	HP XP7 Dynamic Link Manager Advanced for Solaris Unlimited Server LTU	TK925A
	HP XP7 Dynamic Link Manager Advanced for VMware 1 Server LTU	TK927A
	HP XP7 Dynamic Link Manager Advanced for VMware Unlimited Server LTU	TK928A
Product Highlights	 Supports wide range of operating systems - Supports path failover and load balar IBM AIX, Microsoft Windows, SUN Solaris, and Linux operating systems Offers fault-tolerant path management - manual or automatic failover and failbac path health checks, multiple active paths allowing bandwidth control at the HBA p LUN addition and deletion without a server reboot, easy installation and operation discovery function 	ncing for VMware, ck, automated ort level , dynamic n through auto-
Support	See Service & Support section	
Licensing	 HDLM Media Kit includes installers for all operating systems. However, installation services for each operating system must be purchased separately. For 1 Server LTU: License-to-use on a single server/XP7 Storage pair. Example: if you have two XP7 Storage and ten servers, all using Hitachi HDLM for IBM AIX, you would need 20 of the 1 Server LTUs. For Unlimited Server LTU: License-to-use with unlimited servers connected to a single XP7 Storage. Example: if you have two XP7 Storage and ten servers, all using Hitachi HDLM for IBM AIX, you would need two of the Unlimited Server LTUs. If a server has multiple partitions, a copy of HDLM is required for every partition that will be using HDLM. For example, if you have a server with 2 partitions and both partitions require HDLM, then you would need two of the 1 Server LTUs or one Unlimited Server LTU. 	



HP XP7 Global Link Manager

Overview	HP XP7 Global Link Manager uses multipath management software path control fu integrated path management for large sized system configurations. While multipat software manages paths for a host, XP7 Global Link Manager batch manages paths	nctionality to provide th management s for multiple hosts.
	When you use a large sized system configuration containing many hosts, the workl from each host grows in proportion to the size of the system. Global Link Manager the workload by providing unified management of the path information for the mu	load for managing paths enables you to reduce ltiple hosts.
Models	HP XP7 Global Link Manager 1 Server LTU	TK907A
	HP XP7 Global Link Manager Unlimited Server LTU	TK917A
Support	See Service & Support section	
Licensing	 For 1 Server LTU: The number of HDLM instances/servers that HGLM has und For Unlimited Server LTU: 1 HGLM unlimited license allows users to register a number of HDLM instances/servers on 1 platform connected to 1 DKC 	ler management and manage unlimited

HP Serviceguard Metrocluster with XP7 and XP Continuous Access and HP Serviceguard for Linux x86 Enterprise edition

Quarviaw	
Overview	

HP Serviceguard Metrocluster with XP7 and XP Continuous Access seamlessly integrates XP7 Storage remote replication capabilities with HP Serviceguard for HP-UX and Linux. It provides automatic and bidirectional failover/failback of business critical data and applications between data centers. HP Metrocluster with XP7 and XP Continuous Access supports XP7 Storage in a two Data Center configuration.

For HP Serviceguard for Linux, Enterprise edition brings in disaster recovery capability and is for customers who want to protect their applications against site outages up to any distance where latency between the sites is lower than 100ms. This edition provides automatic, bi-directional failover and failback across data centers up to several hundred miles apart. Enterprise edition supports storage array-based replication technologies with HP P9000/EVA Continuous Access, P6000/XP Continuous Access, HP 3PAR Remote Copy and EMC SRDF for Symmetrix arrays.

When combined with the HP Continental clusters product, HP Serviceguard Metrocluster with XP7 and XP Continuous Access or HP Serviceguard for Linux x86 Enterprise edition can also be used to replicate data and to perform application recovery across three data centers using the following storage devices: XP7, XP P9500, XP24000, XP20000, XP12000, and XP10000.

NOTE: HP Metrocluster is a component of HP Serviceguard for Linux x86 Enterprise edition since February 2014.

	For more information, please refer to: http://www.hp.com/go/dt or http://www.h	p.com/go/sglx
Models	HP Metrocluster with XP7 and XP Continuous Access	B8109CA
	HP Serviceguard for Linux x86 1y 24x7 Enterprise PSL Flexible LTU	BB097AC
	HP Serviceguard for Linux x86 1y 24x7 Enterprise PSL E-LTU	BB097ACE
	HP Serviceguard for Linux x86 Enterprise DVD Media	BB097AA
	HP Serviceguard for Linux Enterprise Trade-in	BB097ACN
Product Highlights	• Extends protection provided by a Serviceguard cluster to cover disasters th center.	at affect the whole data

• Functions as an automatic failover/failback disaster recovery solution for HP Serviceguard for HP-



	 UX and Linux. When combined with the HP Continentalclusters product, provides the ability to replicate data across three data centers (with XP7, P9500, XP24000, XP20000, XP12000 and XP10000 Disk Arrays) resulting in minimal Recovery Point Objective (RP0) / Recovery Time Objective (RT0). This configuration provides protection against widespread disasters that may affect an entire region.
Support	 Please contact your HP representative for details
Prerequisites	Software
	 HP-UX 11i v1 or higher. The 3 Data Center capability is available only on HP-UX 11i v2 or higher. RHEL 5 or 6, SUSE 11 (SP2 or higher) HP Serviceguard
	 XP7 Continuous Access (XP7 Continuous Access Sync, or XP7 Continuous Access Journal) XP7 RAID Manage
Licensing	One license needed for every clustered environment

HP Serviceguard Continentalclusters

···· ·································		
Overview	HP Serviceguard Continentalclusters software provides the highest levels of disaster t eliminating the cluster itself as a single point of failure. It uses data replication techno application recovery across multiple widely separated HP-UX or Linux Serviceguard clu	olerance by logies to provide usters.
	Continentalclusters provides the ability to monitor a Serviceguard cluster and recover applications to a remote Serviceguard cluster, should the monitored cluster become u is a disaster at the cluster site. Continentalclusters allows for a semi-automatic push to recovery. When a cluster failure or a site disaster is detected, Continentalclusters gene An operator, upon receipt of a notification, can start the recovery of applications at a r using a single Continentalclusters command that automates the recovery procedure. O supports mutual recovery across two clusters. In a mutual recovery pair, each cluster recover the mission-critical applications running in the other cluster.	mission-critical navailable or if there outton type of erates a notification. ecovery cluster Continentalclusters is configured to
	Applications can be configured in Continentalclusters for disaster tolerance using HP X XP7 Continuous Access data replication technology.	(P7 Storage and HP
	For more information, please refer to: http://www.hp.com/go/dt or http://www.hp.co	m/go/sglx.
Models	HP Continentalclusters LTU	T2346BA
	HP Serviceguard for Linux Continentalclusters x86 1y 24x7 PSL Flx LTU	BB100AC
	HP Serviceguard for Linux Continentalclusters x86 1y 24x7 PSL E-LTU	BB100ACE
	NOTE: Either of the above LTUs is required.	
	HP Serviceguard for Linux Continentalclusters x86 PSL LTU Trade-in	BB100ACN
	HP Serviceguard Continentalclusters for Linux Media Kit	BB086AA
Product Highlights	 Continental clusters supports recovery of single instance applications like Oracl and CVM/CFS 5.0.1 and 5.1 SP1 	e over LVM, VxVM
	 Continental clusters supports recovery of multi-instance applications like Oracle CVM/CFS 5.0.1 and 5.1 SP1. 	e RAC over SLVM and
	HP Serviceguard for Linux Continentalclusters does not support Oracle RAC ove	r SLVM or CVM/CFS
Support	 Please contact your HP representative for details 	



Capacity-licensed XP7 Software

Ρ

Prerequisites	Software
	 HP-UX 11i v1 or higher, RHEL 5 or 6, SUSE 11 (SP2 onwards) (For more information, please refer to: http://docs.hp.com) HP Serviceguard (11.20) HP Metrocluster with XP7 Continuous Access
Licensing	 One license of Serviceguard Continentalclusters covers two pairs of clusters (Primary and Recovery). Use Option 888 (designed for use with HP Metrocluster with XP7 Continuous Access). Each license of Serviceguard Continentalclusters requires one license of HP Metrocluster with XP7 Continuous Access. When purchasing HP Serviceguard for Linux, appropriate number of Licenses to Use (LTU) must be ordered and a copy of the Software must be ordered separately. The Software copy can be ordered by e-Delivery or by Physical Media (DVD).

• One License to Use (LTU) must be ordered for each active socket running HP Serviceguard for Linux software. This new Per Socket License (PSL) is offered, replacing System-wide licenses and Per Core Licenses (PCL).

HP XP Cluster Extension Software

Overview	HP XP Cluster Extension Software offers protection against system downtime to critical applications for enterprise customers using the HP XP Storage family. It allows for hands-free failover/failback of server- storage system. It detects failures and automatically manages recovery without human intervention, offering comprehensive disaster tolerance against application downtime from fault, failure, or site disaster. HP XP Cluster Extension Software resurrects your critical applications at a remote site within seconds/minutes after a failover event over both metropolitan and global distances. XP Cluster Extension works seamlessly with your open-system clustering software, HP XP Continuous Access Software and your XP Storage system to provide a highly available IT system.	
	For more information, please refer to: http://www.hp.com/go/clx	
Models	HP XP Cluster Extension Software Windows LTU	TB534A
	HP XP Cluster Extension Windows Array LTU	BC886B
Product Highlights	 Automatic failover/failback recovery solution for native clusters on Red Hat and SUSE Linux Microsoft Cluster Service (MSCS) for Windows Seamless integration of remote mirroring with server clusters Fully scripted turnkey solution for disaster recovery on Linux and Widows 	.9
Support	See Service & Support section	
Prerequisites	Software	
	 XP7 Continuous Access Synchronous (required for synchronous copy mode-integrated solu XP7 Continuous Access Journal (required for asynchronous copy mode-integrated solution) XP7 RAID Manager (required for host agent integration) 	tion)
Licensing	 License-to-use either on a per server node basis or an array basis. Node based: One License required for each server running XP Cluster Extension Software. Array based: One License required for every array connected to the server running XP Cluster Extension Software. 	?r



HP XP7 Virtualization Adapter

Overview	HP XP7 Virtualization Adapter (XP7 Virtualization Adapter) provides an interface between VMware Site Recovery Manager (SRM) and HP XP7 Storage. The interface enables SRM to provide automatic access to remote data copies when virtual machines become unavailable locally.	
	XP7 Virtualization Adapter supports XP7,XP P9500, XP24000/XP20000, XP12000/XP10000 Disk Arrays.	
	For additional information, please visit hp.com at the following URL: http://www.hp.com/go/storage/vmware	
Product Highlights	HP XP7 Virtualization Adapter performs the following functions for SRM:	
	 Discovers disk arrays Discovers replicated LUNs Fails over storage for testing (test a recovery plan) Fails over storage for recovery (execute a recovery plan) 	
Prerequisites	 Servers with VMware Site Recovery Manager XP7 Continuous Access Synch and/or XP7 Continuous Access Journal installed on both the local and remote XP7 Storage RAID Manager 1.24.13 or later (to support XP7 Storage) 	
	Optional: XP7 Business Copy installed on both the local and the remote XP7 Storage	
Licensing	 The XP7 Virtualization Adapter is provided as a free download. Visit: http://www.hp.com/go/storage/vmware 	
HP DBUtil		
Overview	HP DButil is a command-line utility to facilitate application-consistent replication of a Microsoft SQL Server database. HP DButil commands place the database in a transactionally consistent state and suspend write operations while HP replication software is used to copy the database. Other HP DButil commands then resume the database and normal write operations. HP DButil now supports Microsoft SQL Server 2008 and Microsoft Windows Server 2008 operating system. HP DButil can be downloaded at no charge from the following site: http://h20000.www2.hp.com/bizsupport/TechSupport/SoftwareDescription.jsp?lang=	

en&cc=us&swItem=co-62583-1&jumpid=reg_R1002_USEN



HP XP7 Smart Manager for Mainframe

Overview	HP XP7 Smart Manager for Mainframe provides centralized management of Smart Tiers volumes in a mainframe environment. It works together with Smart Tiers to help mainframe users conveniently and easily manage the location of volumes by tier. It allows mainframe storage administrators to transparently manage the location of volumes in a Smart Tiers pool such that SLA requirements can be satisfied. With Smart Manager for Mainframe your storage resources can be further optimized and efficiently utilized.	
Models	HP XP7 Smart Manager for Mainframe Base LTU	TK906AA
	HP XP7 Smart Manager for Mainframe 1TB 0-100TB LTU	TK906AB
	HP XP7 Smart Manager for Mainframe 1TB 101-250TB LTU	TK906AC
	HP XP7 Smart Manager for Mainframe 1TB 251-500TB LTU	TK906AD
	HP XP7 Smart Manager for Mainframe 1TB Over 500TB LTU	TK906AE
Product Highlights	 Smart Tiers management of z/OS for mainframe volumes. Recognizes z/OS DASD based on VOLSER, Storage Group and z/OS device numbers. Transparent migration - no need to disrupt or quiesce applications 	
Support	See Service & Support section	
Prerequisites	 Software HP XP7 Thin Provisioning HP XP7 Smart Tiers Operating System IBM z/OS (required) 	
Licensing	 Smart Manager for MF is licensed by used capacity for XP7 Storage. See licensing sect details 	ion for more

HP XP7 for Data Exchange

Overview	HP XP7 Data Exchange Software allows seamless data exchange between mainframe and open systems hosts. It provides management of data format and code conversions, and allows information sharing across computing platforms.	
Models	HP XP7 Data Exchange Software LTU	TK920AE
Product Highlights	 Mainframe and open systems data managed and stored on single XP7 Storage Automatic data format and code conversions Supports HP UX, Windows, Linux, Sun Solaris, and AIX Operating Systems 	
Support	See Service & Support section	
Licensing	 License-to-use on a per server basis (per server connected to one XP7 Storage). One Lie required for each server running XP7 for Data Exchange Software. 	cense



HP XP7 for Compatible Extended Remote Copy (XRC)

Overview	Provides asynchronous remote copies using IBM's System Data Mover on the ma XRC works with the SDM functions for z/OS Global Mirror to provide compatible r IBM GDPS/XRC implementations.	inframe host. Compatible replication. Required for
Models	HP XP7 Extended Remote Copy Software Base LTU	TK938AA
	HP XP7 Extended Remote Copy Software 1TB 0-100TB LTU	TK938AB
	HP XP7 Extended Remote Copy Software 1TB 101-250TB LTU	TK938AC
	HP XP7 Extended Remote Copy Software 1TB 251-500TB LTU	TK938AD
	HP XP7 Extended Remote Copy Software 1TB Over 500TB LTU	TK938AE
Support	See Service & Support section	
Licensing	 Licensing on one XP7 Storage based on total capacity of XRC P-VOLs. Also, add the total capacity of the XRC S-VOLs on the array if reverse copy will be used for recovery operations. See Capacity-Licensed XP7 Software section 	

HP XP7 FlashCopy Mirroring

Overview HP XP7 for FlashCopy Mirroring Software provides snapshot capability for local copy of main volumes. It enhances data availability for mainframe data and improves productivity by provi FlashCopy compatible point-in-time copies within an HP XP7 Storage. As soon as a copy is cre becomes available for use. The copy can be either virtual or physical. If a virtual copy is specif remains a pointer-based copy that only saves the changes from the original. However, if a ph specified, a full copy will be completed in the background while both the source and the copy available for access.		ainframe oviding IBM created, it ecified, it physical copy is py remain
	For additional availability, FlashCopy can be combined with Business Copy for Mainframe, Access Synchronous for Mainframe, Continuous Access Journal for Mainframe, and HP XP7 Extended Remote Copy.	Continuous ' for Compatible
	FlashCopy Space Efficient - Storage space required by copies can be saved with FlashCop Efficient. FlashCopy SE uses space based on actual data being copied, not based on the P-V reducing the physical size required for T-VOLs. Only volumes can be FlashCopy'ed with Spa FlashCopy.	y Space /OL size, thus ace Efficient
Models	HP XP7 FlashCopy Mirroring Software Base LTU	TK940AA
	HP XP7 FlashCopy Mirroring Software 1TB 0-100TB LTU	TK940AB
	HP XP7 FlashCopy Mirroring Software 1TB 101-250TB LTU	TK940AC
	HP XP7 FlashCopy Mirroring Software 1TB 251-500TB LTU	TK940AD
	HP XP7 FlashCopy Mirroring Software 1TB Over 500TB LTU	TK940AE
	HP XP7 FlashCopy Space Efficient Software Base LTU	TK941AA
	HP XP7 FlashCopy Space Efficient Software 1TB 0-100TB LTU	TK941AB
	HP XP7 FlashCopy Space Efficient Software 1TB 101-250TB LTU	TK941AC
	HP XP7 FlashCopy Space Efficient Software 1TB 251-500TB LTU	TK941AD
	HP XP7 FlashCopy Space Efficient Software 1TB Over 500TB LTU	TK941AE
Support	See Service & Support section	
Prerequisite	Thin Provisioning is a requirement for Space efficient Flash Copy	

Capacity-licensed XP7 Software

Licensing

 See Capacity-Licensed XP7 Software section. Thin Provisioning for Mainframe is a pre-requisite for FlashCopy Space Efficient.

the Business Copy for Mainframe, Continuous Access Synchronous for Mainframe, and Continuous Access Journal for Mainframe P-VOLs for all of the arrays and purchase the licenses based on the overall total (unlike other XP7 software licenses which are licensed per array). See Capacity-

HP XP7 Business Continuity Manager

Overview	HP XP7 for Business Continuity Manager provides centralized and automated mana of Business Copy for Mainframe, Continuous Access Synchronous for Mainframe, , Journal for Mainframe.	agement and monitoring and Continuous Access
	XP7 Business Continuity Manager includes Business Continuity Manager Extended allowing you to maintain data consistency within and across multiple XP7 Storage Synchronous for Mainframe operations.	CT Group functionality, for Continuous Access
Models	HP XP7 Business Continuity Manager Server LTU	TB553A
	HP XP7 Business Continuity Manager Software Base LTU	TK954AA
	HP XP7 Business Continuity Manager Software 1TB 0-100TB LTU	TK954AB
	HP XP7 Business Continuity Manager Software 1TB 101-250TB LTU	TK954AC
	HP XP7 Business Continuity Manager Software 1TB 251-500TB LTU	TK954AD
	HP XP7 Business Continuity Manager Software 1TB Over 500TB LTU	TK954AE
Support	See Service & Support section	
Prerequisite	 Operating System O IBM z/OS (required) 	
	NOTE: Business Continuity Manager is only supported in z/OS environments. Other environments, like IBM z/VM, IBM z/VSE, and non-IBM operating systems are not set of the set o	r mainframe upported.
Licensing	 One TK953A Server LTU for each server connected to a XP7 or XP Disk Array controlled by Business Continuity Manager. For XP7 Storage: TK954AA/AB/AC/AD/AE licensed on one XP7 or XP P9500 Disk Array, based on total capacity of the P-VOLs associated with Business Copy for Mainframe, Continuous Access Synchronous for Mainframe, and Continuous Access Journal for Mainframe. S-VOLs are not included in the total. For multiple arrays managed under the same Business Continuity Manager, sum all of 	

Licensed XP7 Software section.

HP XP7 Business Continuity Manager Continuous Access Journal 4x4 Ext CTG

Overview	HP XP7 Business Continuity Manager Continuous Access Journal 4x4 Ext CTG Software allow maintain data consistency within and across multiple (up to four) XP7 Storage for Continuou Journal for Mainframe operations.	is the user to Is Access
Models	HP XP7 Business Continuity Mgr Continuous Access Journal 4x4 Ext Consistency Group Base LTU	TK956AA
	HP XP7 Business Continuity Mgr Continuous Access Journal 4x4 Ext Consistency Group 1TB 0-100TB LTU	TK956AB
	HP XP7 Business Continuity Mgr Continuous Access Journal 4x4 Ext Consistency Group 1TB 101-250TB LTU	TK956AC
	HP XP7 Business Continuity Mgr Continuous Access Journal 4x4 Ext Consistency Group 1TB 251-500TB LTU	TK956AD
	HP XP7 Business Continuity Mgr Continuous Access Journ 4x4 Ext Consistency Group 1TB Over 500TB LTU	TK956AE
Support	See Service & Support section	
Prerequisite	 Software HP XP7 for Business Continuity Manager (required) Continuous Access Journal for Mainframe (required - included with XP7 HP Con Suite 	tinuous Access
Licensing	 For XP7 Storage: TK956AA/AB/AC/AD/AE licensed on one XP7, based on total capacit associated with Continuous Access Journal for Mainframe. For multiple arrays manag same Business Continuity Manager, sum all of the Continuous Access Journal for Main for all of the arrays and purchase the licenses based on the overall total (unlike other licenses that are licensed per array). See Capacity-Licensed XP7 Software section. 	y of the P-VOLs ed under the nframe P-VOLs XP7 software

HP XP7 High Performance FICON(R) Connectivity Software

Overview	High Performance FICON for system z or zHPF is an enhancement of the FICON channel architecture; which also means compatibility with certain standards such as Fibre Channel Physical and Signaling standard (FC-FS), Fibre Channel Switch Fabric and Switch Control Requirements (FC-SW), and Fibre Channel Single-Byte-4 (FC-SB-4) standards. Enhancements have been made to the z/Architecture® and the FICON interface architecture to deliver improvements for online transaction processing (OLTP) workloads. zHPF is implemented exclusively in System z10. When High Performance FICON is exploited by the FICON channel, the z/OS operating system, and the control unit; the FICON channel overhead will be reduced. This is achieved by simplification of the protocol, and by reducing the number of information units processed, resulting in more efficient use of the fibre link.
Models	Included in XP7 Mainframe Performance Suite
Support	See Service & Support section
Licensing	Included in XP7 Mainframe Performance Suite bundle licensed by used capacity.



Capacity-licensed XP7 Software

Many XP7 software titles are licensed based on some measure of the storage capacity of the system. This structure allows customer costs for software to scale with the cost for their hardware solution. In all cases, a 1TB increment is the smallest increment available. Therefore, for all capacity requirement calculations, capacity figures should be rounded up to the next highest TB. The capacity-licensed XP7 Software products are licensed using a "band" structure.

Band-based Capacity-licensed XP7 Software Product Structure

Band-based capacity-licensed XP7 Software licenses are ordered in 1TB increments only, with different 1TB license types corresponding to each of the capacity "band" product numbers of the software product structure:

Description	Product Number
Base License	ТК9ххАА
1TB increment, 0TB to 100TB	TK9xxAB
1TB increment, 101TB to 250TB	TK9xxAC
1TB increment, 251TB to 500TB	TK9xxAD
1TB increment, Over 500TB	ТК9ххАЕ

Customers purchase the Base License and then purchase all capacity licenses under a fixed schedule depending on the license capacity required. All capacity figures should be rounded up to the nearest TB. Purchase of capacity-based software falls into two categories:

- New Software purchase: Software licenses are being purchased along with a new XP7 Storage or for a new software purchase for an existing XP7 Storage implementation.
- License Capacity upgrade purchase: A customer is adding usable storage capacity to their system or expanding the use of certain software titles, requiring that they expand the license capacity by purchasing additional LTU products.

NOTE: Because of the band pricing structure, if your configuration is near the top of a band, compare the price of the entry point of the next higher band to see if it might provide a lower price. For example, consider 100TB of XP7 Array Manager. 100TB is at the top of the first band. If you move up to the next band and buy 101TB instead, you will find that the price for 101TB is actually lower than the price for 100TB.

For new software purchase:	Purchase the Base License and then purchase all capacity licenses from the capacity band that matches the total capacity required. Example: Customer purchases an 18TB raw capacity XP7 Storage. Consider that total usable capacity, based on the capacity of all configured LDEVs, is 12TB. Customer wants HP XP7 Auto LUN. In this case, customer will need to purchase 12TB of Auto LUN LTUs. To provide for 12TB license capacity for the software, the customer would order the following:			
		1	HP XP7 Auto LUN Software Base LTU	ТК915АА
	12	HP XP7 Auto LUN Software 1TB 0-100TB LTU	TK915AB	



For license capacity upgrades:	The customer purchases additional license product from the band that matches the sum of the current installed capacity plus the desired upgrade capacity.		
	Example: Custom XP7 Auto LUN. Th total usable stora TB (100.5 TB - 97 capacity of the au capacity for a tot the 101 to 250 Th	her has a 96.5TB usable capacity system with existing 97TB ins hey then install more drives and configure 4 TB additional usab age capacity of the array up to 100.5 TB). In this case, the custo TB) additional license capacity of XP7 Auto LUN in order to "co ray. Rounding 3.5 TB up to the nearest TB, they customer need al of 101 TB. Because the total capacity is 101 TB, the upgrade B band	italled license capacity of le capacity (bringing the omer requires at least 3.5 over" the new total usable ds to purchase 4 TB license e capacity is purchased from
	Quantity	Description	Product Number
	4	HP XP7 Auto LUN Software 1TB 101-250TB LTU	TK915AC

Usable Capacity-licensed Software Titles

For usable capacity-licensed titles, customers license the use of the software by purchasing License products that "cover" them for the amount of total usable storage capacity present on their array (i.e. for the total capacity of all the LDEVs configured in the array). In other words, usable capacity is based upon the total usable capacity of all created LDEVs

Total Usable Capacity = Allocated LDEVs + Unallocated LDEVs + Reserved Capacity. Note that Usable Capacity for software licenses is to be calculated in binary (TiB). A factor of 1024 is to be used for converting from raw to usable capacity. Example: Customer has a XP7 Storage with 100TB physical raw capacity. The entire raw capacity has been configured as RAID 1. Thus, the total effective capacity available to customer is 50TB. Customer configures a number of LDEVs whose total capacity equals 40TB. This 40TB will be considered as the "usable" capacity of the array. All software titles licensed on usable capacity will need to have 40TB

licenses if they need to be used on this array.

Note that if a customer crosses the boundary by creating too many LDEV's, they can restore management to the array by deleting LDEVs until they are back below the licensed threshold again. It is not necessary to de-install array groups to correct exceeding the licensed capacity.

The following XP7 Family Software Titles are licensed based on the (internal + external) usable storage capacity of the array:

- HP XP7 Command View AE
- HP XP7 Tiered Storage Manager
- HP XP7 Array Manager
- HP XP7 Auto LUN
- HP XP7 Performance Advisor
- HP XP7 Mainframe Basic Suite

For these titles, customers license the use of the software by purchasing License products that "cover" them for the amount of usable storage capacity present on their array (i.e. for the total capacity of all the configured LDEVs in the array excluding spare drives).



Used Capacity-licensed Software Titles

The following XP7 Family Software Titles are licensed based on the amount of storage actually employed by the Software:

- HP XP7 Smart Tiers (licensed on the capacity of the thin provisioning pool that is managed by Smart Tiers)
- HP XP7 Continuous Access Suite (includes Continuous Access Journal and Continuous Access Synchronous)
 - Used capacity = Open Systems P-Vols and S-Vols plus Mainframe P-Vols and S-Vols.
 Oplu P. Vols and S. Vols are counted when determining license guartity. Capacity used
 - Only P-Vols and S-Vols are counted when determining license quantity. Capacity used for journal volumes is not counted.
- HP XP7 Business Copy (includes Fast Snap and Business Copy for Mainframe)
 - Used capacity = Business Copy P-Vols and S-Vols, plus Business Copy for Mainframe P-Vols and S-Vols, plus Snapshot P-Vols and Pool-Vols.
- Business Copy for Mainframe
- HP XP7 Mainframe Performance Suite (includes Compatible Parallel Access Volumes (PAV) licensed on total used mainframe LDEV capacity. This is the sum of total capacity of mainframe base LDEVs (data volumes) that will be defined with ALIASES via the Remote Web Console at the time PAV is installed, and base volumes that are accessed by Hyper PAV (if HyperPAV is installed).
- HP XP7 Mainframe Tiering Suite (includes Smart Tiers and Smart Manager for Mainframe)
- HP XP7 for FlashCopy Mirroring
- HP XP7 for FlashCopy Space Efficient
- HP XP7 for Compatible Extended Remote Copy (XRC) (total capacity of XRC P-VOLs. Also, add the total capacity of XRC S-VOLs if reverse copy will be used for recovery operations.)
- HP XP7 for Business Continuity Manager (total capacity of the P-VOLs associated with Business Copy for Mainframe, Continuous Access Synchronous for Mainframe, and Continuous Access Journal for Mainframe for all XP7 Disk Arrays managed under the same Business Continuity Manager)
- Hitachi Business Continuity Manager Extended CT Group (total capacity of the P-VOLs associated with Continuous Access Synchronous for Mainframe for all of the arrays managed under the same Business Continuity Manager)
- HP XP7 for Business Continuity Manager Continuous Access Journal 4x4 Ext CG (total capacity of the P-VOLs associated with Continuous Access Journal for Mainframe for all of the arrays managed under the same Business Continuity Manager. For these titles, customers license the use of the software by purchasing License products that "cover" them for the amount of storage capacity actually used by the software title in question.

For HP XP7 Continuous Access Suite, and	Used capacity is defined as the total capacity of all logical volumes that are Remote Mirroring P-Vols (source volumes on a primary XP7 Storage) or S-Vols (copy volumes on a secondary XP7 Storage). This amount represents the true usable capacity of these volumes corresponding with the configured LDEV sizes (i.e. the amount excludes RAID mirroring overhead).
Continuous Access Synchronous for Mainframe, and Continuous Access	Example : Based upon their total storage need, a customer requires a primary XP7 Storage with 5TB raw capacity. The customer also requires XP7 Continuous Access for the purpose of deploying a disaster recovery solution. For their solution, they determine that they will mirror 70 LUNs of equal LDEV size to a secondary XP7 Storage in their remote data center. Each LUN LDEV is roughly 14.5 GB in size. Each source LUN is a P-Vol and each copy LUN is an S-Vol. On both the primary and secondary, the customer must purchase license capacity to cover all LUNs being managed as XP7 Continuous Access P-Vols plus S-Vols. In this case, the total used capacity would be calculated as follows:
Journal for Mainframe:	 On the Primary array: Used Capacity = P-Vol (source) LUNs = 70 x 14.5-GB = 1,015 GB. Dividing by 1024 to convert to TB gives 0.99 TB. Rounded up to the next highest TB: 1 TB total used capacity On the Secondary array: Used Capacity = S-Vol (copy) LUNs = 70 x 14.5-GB = 1,015 GB. Dividing by 1024 to convert to TB gives 0.99 TB. Rounded up to the next highest TB: 1 TB total used capacity

Therefore, for the primary and secondary XP7s, the customer must purchase at least 1 TB worth of license capacity on each array.



Capacity-licensed XP7 Software

For HP XP7 Business Copy and	Used capacity is defined as the total capacity of all logical volumes that are either Local Copy P-Vols (BC source) or traditional S-Vols (BC copy) or POOL-Vols (where Snapshot data is stored). This amount represents the true usable capacity of these volumes corresponding with the configured LDEV sizes (i.e. it excludes RAID mirroring overhead).
Business Copy for Mainframe	Example : Based upon their total storage need, a customer requires a 5 TB raw capacity XP7 Storage. The customer also requires XP7 Business Copy for the purpose of online backup and application testing and all of the copy LUNs will be traditional, full-size volumes. For their solution, they determine that they will mirror 70 LUNs of equal LDEV size, with one copy each for the first 30 LUNs and two copies each for the other 40 LUNs. Each LUN LDEV is roughly 14.5 GB in size. Each source LUN is a P-Vol and each copy LUN is an S-Vol. The customer must purchase license capacity to cover all LUNs being managed as a XP7 Business Copy P-Vol or S-Vol. In this case, the total used capacity would be calculated as follows:
	 Used Capacity = P-Vol (source) LUNs + S-Vols (copy) LUNs = 70 x 14.5-GB + 1 x 30 x 14.5-GB + 2 x 40 x 14.5-GB = 1,015 GB + 1,595 GB = 2,610 GB. Dividing by 1024 to convert to TB gives 2.55 TB. Rounded to the next highest TB: 3 TB used capacity.
	For HP XP7 Business Copy using Fast Snap replication Used capacity is defined as the total capacity of all logical volumes that are P-Vols (Fast Snap source) plus Pool Volume (where all Copy-after-Write data is stored). This amount represents the true usable capacity of these volumes corresponding with the configured LDEV sizes (i.e., it excludes RAID mirroring overhead).
	The Pool Volume size is estimated by understanding:
	 the size of data that will be changed for each P-Vol per generation of Snapshot V-Vol (X) the number of generations of Snapshots that will be created/retained (Y) the number of P-Vols that will have Snapshots taken (Z)
	The Pool volume size = XxYxZ (rounded up to the next TB)
	Example : Based on a customer's total storage need, they have 300 P-Vols, each sized at 100GB (30,000GB, dividing by 1024 to convert to TB gives 29.3 TB, rounded to the next highest TB: 30TB total). The customer wants to keep 7 generations of Snapshot V-Vols. Finally, it has been estimated that 4.7GB of data will be updated between each generation. The customer must purchase license capacity to cover all LUNs being managed as a Snapshot XP7 P-Vol or V-Vol. In this case, the total used capacity would be calculated as follows:
	 Used Capacity = P-Vol (source) LUNs + Pool volume size = 30TB + (4.7GBx7x300 = 9,870GB, dividing by 1024 to convert to TB gives 9.64 TB, rounded to the next highest TB: 10TB) for a total licensing requirement of 40TB
	Fast Snap requires a V-Vol management area in Shared Memory. The Shared Memory requirement for the V-Vol management area is the sum of the P-Vol information capacity requirement + the Pool Volume information capacity requirement. See the Fast Snap Users Guide for complete details regarding configuring Shared Memory for Fast Snap.

Shared Memory requirement for XP7 Storage - refer to the configuration guide to understand the Shared Memory requirements for XP7 Storage.



Capacity-licensed XP7 Software

For Mainframe Software bundling with Open Systems Software: The following mainframe local and remote mirroring software titles are bundled with their open systems equivalents when ordered for the XP7 Storage:

- Continuous Access Synchronous for Mainframe (included with HP XP7 Continuous Access Synchronous)
- Continuous Access Journal for Mainframe (included with HP XP7 Continuous Access Journal)
- Business Copy for Mainframe (included with HP XP7 Business Copy)

For these products, customer must purchase license capacity to cover the total open systems and mainframe used capacity.

Example: A customer has a XP7 Storage with mainframe and open systems connect. They want to use HP XP7 Continuous Access to synchronously mirror 2 TB of open systems volumes and Continuous Access Synchronous for Mainframe to mirror 1 TB of mainframe volumes to another XP7 Storage. For each array, this customer requires at least 3 TB of license capacity of HP XP7 Continuous Access (which includes Continuous Access Synchronous for Mainframe).

© Copyright 2014 Hewlett-Packard Development Company, L.P.

The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

For drives, 1 GB = 1 billion bytes. Actual formatted capacity is less

