

Department of School & Mass Education, Govt. Of Odisha



Implementation of e Vidyalaya Project in 4000 Govt. & Govt. aided Schools of Odisha

This is to certify that the following items/Human Resources have been duly delivered and installed/deployed in our school and all equipment/items are in proper condition for implementation of ICT lab with following details.

IMI	T	II TOIIOV						is applicable												
	+	Please tick whichever is applicable																		
	IL&FS Education & Technology Services Ltd. Telecommunication Cosultants India Ltd																			
	2	1	a	TA	T	10														
		Date				*	d	3	2	D	10	8	+	10	9	$\perp \mathcal{O}$	5			
School Name	G	0	V	T		5	5	D		#	Î	6	+1	7	1		T			
	5	C	H	0	0	L		R	A	1	G	#	A	P						
Village	R	A		6	H	A	R							1			1			
Block	2	A	1	6	#	A	2				4	-		1						
District	N	A	B	A	R	A	N	61	P	V	0									
Address	M	A	I	N	24.	R	0	A	D		R	A	T	(71	H	A	R			
											Pin:				1	-	1			
Name of Head Master/ Mistress(HM)	5	A	N	0		K	I	S	H	0	R	E		N	A	Y	A			
HM Contact No.				<u> </u>	7							\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \								
riivi Contact No.	1		1	4	+	1	+	0	1	3	4	0	0			- 6				
Name of School Coordinator		A	6	A	N		M	0	H	A	N		N	A	6					
School Coordinator's Contact no.	9	1	7	7	Q	7	4	1	3	6	3									
Implementation partner's School Code	.0	D	2	6	-	N	A	3	A	D	2	2	8	1	2					
Room Dimension (in feet)	Length:		18	, ,		Breadth:									Please Tick					
Sr. no.	Ma	Item ake & Mod	el	Qty.		· ·		Specification & Serial No.												
Desktop Acer Make						X86 Architecture 3.2 Ghz or higher Processor with 4 dedicated cores, RAM 4GB or higher expandable to 16GB, 500 GB HDD, 19-inch or Higher LED Monitor, Built-in audio, 300 Watt , Desktop Speaker, DVD Writer,10/100/1000BaseT Ethernet, 104 Key Keyboard and Optical Mouse With at least 2 Free Full Height PCI slots,											, ,			
	Serial no.			A final	V	X	V	8	5	S		0	1	9						
Desktop(Stand by) Acer Make						able to 1	6GB, 500	or highe GB HDD, riter,10/1	19-inch c	or Higher	LED Mor	itor, Bu	ilt-in au	dio. 300	Watt	Please	Tick			
2				1	. 2		Moi	use With	at least 2	Free Ful	Height I	PCI slots	,	,	- steal					
4,	5	Serial no.			V	X	V	8	5	S	1	0		8						
					E	3	3	9	0	4	3)								

	U DISE CODE				2		2	8	0	8	100	0	9	Please	Tick
3	Two Shared Computing Devices per Desktop. Multibox device which allows 6 users to share a single host PC through a share computing PC-Sharing kit (which includes one full height PCI Card, Virtualization software, access devices with speaker output, PS/2 Shared Computing Mouse and PS/2 Keyboard output. SVGA Monitor output and RJ45 Connection Port. with 5 CAT6 cables (each of 5 meters length)), Power consumption of each access device should not										th 5 ld not AT 6 on the	e			
	Monitor		19-inch o connectiv degrees (GOLD / T	ity with	matt blac	ck finish, al), wall n	brightne nounting	ss 250 cd	/m2, viev	wing ang	le 170 d	egrees/	160	Pleas	e Tick
	Serial no.				lb.	Pls	. fill the	serial no	s of all th	ne 12 Mc	nitors				
	1		M	M	7	X	K	5	5	0	1 2	4	4		
	2		M	17	L	X	K	5	5	0	1	4	4		
	3		3 M	M	L	X	4	5	8 5	0	1	4	4		
			3	0	D	B	5	D	C	4	2	0	4		2
	4		M	M	L	X	K	5	5	0	1	4	4		
			3	0	0	B	5	4	E	4	2	0	4		
	5		M	m	2	X	K	S	5	9	1	4	4	3	
		12	100	V	13	~	<u>د</u>	1	4	D	1	4	1		
•	6		M	M		n	-	0	>	1	3	7	1		_
			3	0	0	13	10)	0	4	1	1	7		-
	7		3	m 0	0	B	9	F	2	4	2	0	4		
			M	M	L	×	K	5	5	0	1	4	4		
	8		3	D	Ò	B	5	C	E	4	2	D	4		
	_		m	m	L	X	K	5	5	0	1	4	4		
	9		3	0	D	B	5	E	7	4	2	0	4		
	1090	70	M	m	1	X	K	5	5	0	1	4	4		
	10		2	0	1	n	(T	9	4	2	0	4		
			M	m	2	X	·K	ζ	5	1	7)	A	4		
	11		>	n	0	B	-	D	A	4	2	0	A		
	12		m	m	L	X	K	5	3	0	1	4	4		
	* 12		2	0	0	A	4	D	F	4	2	D	4		
5	Web Cam Brand (Pis. tick) Wipro	1	Min 5	MP came	era, Supp	ort for H		calling (1		pixels),	Built-in	mic witl	n noise	Ple	ase Tick
6	Headphones	40					Headp	hone wi	h Mic					L	ase Tick
7	Headphone Sharer	10	1			5-W	ay 3.5-m	m Headp	hone Spl	tter				Ple	ase Tick

				U DISE CODE			2	1	9	9	1	0	1	7	6	2	A
8 Integrated Computer Projector K-YAN				1	Specification: Projection System: DLP Technology; Brightness: 2500-ANSI Lumens (Short Throw) Resolution: SVGA (800x600); Contrast Ratio: 2500:1 Computer System: X86 architecture, 3.2GHz or higher with 4 dedicated Cores, Minimum 4MB L3 Cache, Compatible chipset with HD graphics, 4GB DDR3 RAM expandable to 16 GB, 500 GB Serial SATA II 7200 RPM HDD, Optical Drive DVD RW, Wireless Keyboard & optical Scroll Mouse. OS: DOS; Input: PS/2 Mouse & Keyboard, RF –in for TV, USB ports, Microphone in; Output: Internal 30 watts Audio Output, LAN: 1x Gbps LAN, Integrated analogue cable TV tuner.											e Tick	
			200	Serial no.		1 2	3 2	GI		20	D	1	22	-	8/1	1-0	. 0
		9		Interactive White Board Smart	1	Active Area: approximate Aspect Ratio maintenance isopropyl alc operating sys supports mul consumption USB cable for Wir Electromagne Data Ports: 1 DYD. Software: DVD. Software DVD. Software into upda availability. A palm touch, i specific part c and facilitate application fe into each oth facility.Access	Minimum 77" Minimu	ive area 1.767 rface: Dur rface:	able Hard-dry-erase m stem: Wind Tools: Both mechanica mA at 5 V). puters. Tecd other ext of the tools will be too the tools of the too	coated stenarkers and ows XP SI if singer and land battle. Must obtain the coate of the whole of the same additional of the same maximum	eel surface d easily c P3, Winde d pen tou ery free c tain powe Fouch tec lences 1 or USB 2 to USB 3 to Service lences software and delive content 500 user	e, optimi leaned w leave Vista look vista lo	ing resoluted for prith white SP2 or out any spower Opne computer age: Saviare applied to accomple to	ution is rojection eboard cl Window pecial too tions: Po tier throu ference f ing of file cation on custo the custo the custo the incitive feat ion, focus ternal coMust su ind write o	eaner or s 7 yels, wer light the rom s in a CD or software is a ures like to ontent pply an directly		sse Ticl
				Serial no.		Mode: Up to	o 18 ppm, Prin	nt techno	logy: Laser	r, Print qu	uality bla	ck	160			Pleas	e Tick
		10	ř,	Multi Function Printer Brand (Pls. tick) Ricoh	1	(best): Up to Processor sp 10/100Base- Automatic So	o 600 x 600 dp beed: Minimu -T Ethernet no canner type: bressed), PDF,	m 400 Mi etwork po Flatbed, /	Hz, Connec ort, RJ-11 ADF. Scan	ctivity, sta Telephon file form	andard: I le port, D at: JPEG.	Hi-Speed Juplex programmer of the contract of	USB 2.0	4	by IDC.		
		10		Brand (Pis. tick)	1	(best): Up to Processor sp 10/100Base- Automatic So	o 600 x 600 dp beed: Minimu -T Ethernet ne canner type:	m 400 Mi etwork po Flatbed, /	Hz, Connec ort, RJ-11 ADF. Scan	ctivity, sta Telephon file form	andard: I le port, D at: JPEG.	Hi-Speed Juplex programmer of the contract of	USB 2.0	4	by IDC.		ŝ
		10		Brand (Pis. tick) Ricoh	1	(best): Up to Processor sp 10/100Base- Automatic So	o 600 x 600 dp opeed: Minimu canner type: oressed), PDF, rtified. Online ove, Efficiency : Sealed. Mai ling. With DG :: 0 to 50 degr	H 400 Mi etwork po Flatbed, , GIF, BMF UPS of 2 90 % or intenance Set com	Hz, Connector, RJ-11 ADF, Scan P, Scan reserved KVA with better on reserved reserved.	Telephon file form olution, columns of the form olution, columns of the form olution, columns of the form of the f	es powe load, Injoller Basicy range	r backup out Powed Double 50+/- 6	d USB 2.1 rinting: npressei 00 dpi, C 0, Output er Factor le Conve % hertz, nt norms	t Wave Fr > 0.90, persion On operation	form -	Pleas	e Tick
				Brand (Pis. tick) Ricoh Serial no. On Line UPS	1	ISO 9001 Cer Pure sine wa Battery type UPS and Cabl temperature: sine wave ou	o 600 x 600 dp opeed: Minimu canner type: oressed), PDF, rtified. Online ove, Efficiency : Sealed. Mai oling. With DG :: 0 to 50 degr orthyte	WIPS of 2	KVA with better on re Free, Mic patibilities us, noise le	30 minut rated full cro Control, frequency els as pe	es power load, Ingoller Basicy range er the go	r backupper pur Power out	J USB 2.1 rinting: npresser 10 dpi, C O, Outpur er Factor le Conve % hertz, nt norms	t Wave Fr > 0.90, ersion Or operation. output	form - nline ng : pure	Pleas	e Tick
		11		Brand (Pis. tick) Ricoh Serial no. On Line UPS Delta	1	ISO 9001 Cer Pure sine war Battery type UPS and Cabl temperature:	o 600 x 600 dp opeed: Minimu canner type: oressed), PDF, rtified. Online ove, Efficiency : Sealed. Mai lling. With DG :: 0 to 50 degr rtput	UPS of 2 90 % or intenance Set compees celcie	KVA with better on re Free, Mic patibilities us, noise le	30 minut rated full cro Control, frequency els as pe	es power load, Ingoller Basicy range er the go	r backupper pur Power out	J USB 2.1 rinting: npresser 10 dpi, C O, Outpur er Factor le Conve % hertz, nt norms	t Wave Fr > 0.90, ersion Or operation. output	form - nline ng : pure	Please	١
_				Brand (Pis. tick) Ricoh Serial no. On Line UPS Delta Serial no.	1	ISO 9001 Cer Pure sine wa Battery type UPS and Cabl temperature sine wave ou	o 600 x 600 dp opeed: Minimu canner type: oressed), PDF, rtified. Online ove, Efficiency : Sealed. Mai lling. With DG :: 0 to 50 degr rtput	UPS of 2 90 % or intenance Set compees celcie	KVA with better on re Free, Mic patibilities us, noise le	30 minut rated full cro Control, frequency els as pe	es power load, Ingoller Basicy range er the go	r backupper pur Power out	J USB 2.1 rinting: npresser 10 dpi, C O, Outpur er Factor le Conve % hertz, nt norms	t Wave Fr > 0.90, ersion Or operation. output	form - nline ng : pure	~ W	١
_		11		Brand (Pis. tick) Ricoh Serial no. On Line UPS Delta Serial no. Networking	1	ISO 9001 Cer Pure sine wa Battery type UPS and Cabl temperature: sine wave ou ### 16 Port Unma Mutil fucntio	o 600 x 600 dp opeed: Minimu canner type: oressed), PDF, rtified. Online ove, Efficiency : Sealed. Mai lling. With DG :: 0 to 50 degr rtput	e UPS of 2 90 % or intenance set commerces celcit	KVA with better on 12 Free, Micpatibilities us, noise le	30 minut rated full cro Controls, frequent vel: as pe	es power load, Injoller Basney range er the go	r backup r back	JUSB 2.1 rinting: rin	t Wave Fr > 0.90, ersion Or operation, output	orm - nline ng : pure	~ W	Je Tick

1	U DISE CODE		2112908109	05									
14	Servo Stabilizer Protect	1	5KVA (1 Phase Servo Motor Operated Line Voltage Corrector), Input Range: : 50V-270V (Single Phase), Mounting: On Wheels. Output range: 220V/230V/240V single phase (adjustable), earthing terminals, overload cutoff, output protection through MCB, Frequency range: 50+/- 3% hertz. Operating temperature: 0 to 50 degrees celsius.										
	Serial no.		0802140108										
	Silent Generator Set Champ		ISO 9001 Certified, Minimum 3 KVA Petrol/Diesel based silent generator set with Safe Cabling and Installation										
15	Serial no.	1	51311036126										
16	Initial meter reading of the Silent Generator Set		0000.4.22 (Four hour)	Please Tick									
17	Earthing (as per IS specifications)		Copper plate earthing stations making earthing with copper earth plate	Please Tick									
18	Lighting (ISI mark)	4	40W Tube Light with Electronic Choke (ISI mark)	Please Tick									
19	Ceiling / Wall mounted fans (ISI mark)	2	48" blade with regulator, 3 Blade Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj/ Havells	Please Tick									
20	Exhaust fans (ISI mark)	2	300mm sweep, 45 Watts, Speed 1330 RPM Indicative Brands: Philips / Wipro/ Usha/Crompton Greaves /Khaitan /Bajaj / Havells										
		15	5 A- 240 V switches										
21	Switches and sockets (ISI Mark)	15	2 in 1 5A and 15A Sockets										
		2	15 A – 240 V socket with shutter										
			Indicative Brands: - Anchor / Havells / crabtree /Wipro /Phillips / Legrand Switches and sockets is to be provided for all electronics/IT equipments including printer and Projection System to be placed at lab technician table.										
22	Computer Table Tajpuria	13	Dimensions Width 1200mm x Depth 609mm x Height 750mm 18mm pre laminated particle board conforming IS: 12823. Pretreated & powder coated steel frame. Good quality PVC edge bending to be provided on pre laminated board. No Sharp corners, smooth edges are essential. Legs frame made of 1.5 inch square pipe, 16 gauges. Table rests on good quality glide screws. Full length footrest is to be provided. One 65mm diameter hole for drawing cables is to be provided , this hole has to be covered with steel cover Good quality telescopic slider along with full width keyboard with 30cm projected depth panel, keyboard free space is 10 cm. Table must have a modesty panel of 200mm height to be provided. End caps to be provided. BIFMA Certified	Please Tick									
23	Chair Uma Plastic/Moderna	41	Armless Moulded Chairs, Cream colour, IStandard Compliant	Please Tick									
24	Electrical meter Initial reading		00003										
25	Painting	-	The surface of Wall and Ceiling to be painted, shall be prepared to the satisfaction of OKCL / OMSM and shall be applied with 2 coats of primer and then with 2 coats of distemper paint of standard make as approved by OKCL / OMSM.	Please Tick									
26	Lab Cleanliness Kit	1 set	Dusting cloth, hand held vacuum cleaner, Dust cloth covers for all the IT equipments and one Foot mat										
27	Curtains	Full lab	To maintain proper darkness in the Lab / Classroom during Projection	Please Tick									
28	Wall Clock	1	ISI Mark, Wall Clock	Please Tick									
29	Notice Board	1	5feet x 3feet, P/F 15 thk Pinup board with fabric wrapped all around	Please Tick									
30	White Board	1	4 ftx3 ft minimum 18mm thickness white board	Please Tick									

^{***} Please note that all the three signatures are mandetory on all the sheets.

Signature of Implementation partner's
Representative with Seal
BHUBANESWAR

175

Signature of OKCL Representative with Seal

Signature of Schools Gad Master/Wistress with Seal

^{****}All fields are to be filled up mandatorily.